

▼ NumPy Exercises

Now that we've learned about NumPy let's test your knowledge. We'll start off with a few simple tasks, and then you'll be asked some more complicated questions.

▼ Import NumPy as np

```
import numpy as np
```

▼ Create an array of 10 zeros

```
zeros = np.zeros(10)
zeros
array([0., 0., 0., 0., 0., 0., 0., 0., 0., 0.])
```

▼ Create an array of 10 ones

```
ones = np.ones(10)
ones
array([1., 1., 1., 1., 1., 1., 1., 1., 1., 1.])
```

▼ Create an array of 10 fives

```
fives = np.full(10, 5.)
fives
array([5., 5., 5., 5., 5., 5., 5., 5., 5., 5.])
```

▼ Create an array of the integers from 10 to 50

```
integers = np.arange(10, 51)
integers
array([10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26,
       27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43,
       44, 45, 46, 47, 48, 49, 50])
```

▼ Create an array of all the even integers from 10 to 50

```
even = numbers[numbers % 2 == 0]
even
array([10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42,
       44, 46, 48, 50])
```

[+ Code](#)[+ Text](#)

▼ Create a 3x3 matrix with values ranging from 0 to 8

```
matrix = np.arange(9).reshape(3, 3)
matrix
array([[0, 1, 2],
       [3, 4, 5],
       [6, 7, 8]])
```

▼ Create a 3x3 identity matrix

```
identity_matrix = np.eye(3)
identity_matrix
```

```
array([[1., 0., 0.],
       [0., 1., 0.],
       [0., 0., 1.]])
```

▼ Use NumPy to generate a random number between 0 and 1

```
random_number = np.random.rand()
random_number

0.8808764210495326
```

▼ Use NumPy to generate an array of 25 random numbers sampled from a standard normal distribution

```
standard_normal_numbers = np.random.randn(25)
standard_normal_numbers

array([-1.61036061, -1.00928905,  0.42890368,  0.98888809,  1.09988754,
       -0.50540337, -0.13706241, -2.82282399,  1.16372985,  0.05640484,
       -0.11708381,  0.56802605, -0.87081437,  0.34447755,  2.04055766,
       -0.48160917,  0.78172343,  0.77268729, -0.59990174, -0.47156014,
        1.34534554,  2.20173031, -1.08019287, -0.21194419, -1.75445829])
```

▼ Create the following matrix:

```
matrix = np.arange(0.01, 1.01, 0.01).reshape(10, 10)
matrix

array([[0.01, 0.02, 0.03, 0.04, 0.05, 0.06, 0.07, 0.08, 0.09, 0.1 ],
       [0.11, 0.12, 0.13, 0.14, 0.15, 0.16, 0.17, 0.18, 0.19, 0.2 ],
       [0.21, 0.22, 0.23, 0.24, 0.25, 0.26, 0.27, 0.28, 0.29, 0.3 ],
       [0.31, 0.32, 0.33, 0.34, 0.35, 0.36, 0.37, 0.38, 0.39, 0.4 ],
       [0.41, 0.42, 0.43, 0.44, 0.45, 0.46, 0.47, 0.48, 0.49, 0.5 ],
       [0.51, 0.52, 0.53, 0.54, 0.55, 0.56, 0.57, 0.58, 0.59, 0.6 ],
       [0.61, 0.62, 0.63, 0.64, 0.65, 0.66, 0.67, 0.68, 0.69, 0.7 ],
       [0.71, 0.72, 0.73, 0.74, 0.75, 0.76, 0.77, 0.78, 0.79, 0.8 ],
       [0.81, 0.82, 0.83, 0.84, 0.85, 0.86, 0.87, 0.88, 0.89, 0.9 ],
       [0.91, 0.92, 0.93, 0.94, 0.95, 0.96, 0.97, 0.98, 0.99, 1.  ]])
```

▼ Create an array of 20 linearly spaced points between 0 and 1:

```
linearly_spaced_numbers = np.linspace(0, 1, 20)
linearly_spaced_numbers

array([0.          , 0.05263158, 0.10526316, 0.15789474, 0.21052632,
       0.26315789, 0.31578947, 0.36842105, 0.42105263, 0.47368421,
       0.52631579, 0.57894737, 0.63157895, 0.68421053, 0.73684211,
       0.78947368, 0.84210526, 0.89473684, 0.94736842, 1.          ])
```

▼ Numpy Indexing and Selection

Now you will be given a few matrices, and be asked to replicate the resulting matrix outputs:

```
mat = np.arange(1,26).reshape(5,5)
mat

array([[ 1,  2,  3,  4,  5],
       [ 6,  7,  8,  9, 10],
       [11, 12, 13, 14, 15],
       [16, 17, 18, 19, 20],
       [21, 22, 23, 24, 25]])
```

```
# WRITE CODE HERE THAT REPRODUCES THE OUTPUT OF THE CELL BELOW
# BE CAREFUL NOT TO RUN THE CELL BELOW, OTHERWISE YOU WON'T
# BE ABLE TO SEE THE OUTPUT ANY MORE
```

```
output = mat[2:,1:]
output
```

```
array([[12, 13, 14, 15],
       [17, 18, 19, 20],
       [22, 23, 24, 25]])
```

```
# WRITE CODE HERE THAT REPRODUCES THE OUTPUT OF THE CELL BELOW
# BE CAREFUL NOT TO RUN THE CELL BELOW, OTHERWISE YOU WON'T
# BE ABLE TO SEE THE OUTPUT ANY MORE
```

```
element_at_row_3_column_4 = mat[3, 4]
element_at_row_3_column_4
```

```
20
```

```
# WRITE CODE HERE THAT REPRODUCES THE OUTPUT OF THE CELL BELOW
# BE CAREFUL NOT TO RUN THE CELL BELOW, OTHERWISE YOU WON'T
# BE ABLE TO SEE THE OUTPUT ANY MORE
```

```
new_mat = mat[:3, [1]]
new_mat
```

```
array([[ 2],
       [ 7],
       [12]])
```

```
# WRITE CODE HERE THAT REPRODUCES THE OUTPUT OF THE CELL BELOW
# BE CAREFUL NOT TO RUN THE CELL BELOW, OTHERWISE YOU WON'T
# BE ABLE TO SEE THE OUTPUT ANY MORE
```

```
new_mat = mat[-1,:]
new_mat
```

```
array([21, 22, 23, 24, 25])
```

```
# WRITE CODE HERE THAT REPRODUCES THE OUTPUT OF THE CELL BELOW
# BE CAREFUL NOT TO RUN THE CELL BELOW, OTHERWISE YOU WON'T
# BE ABLE TO SEE THE OUTPUT ANY MORE
```

```
last_two_rows_and_last_column = mat[-2:,:]
last_two_rows_and_last_column
```

```
array([[16, 17, 18, 19, 20],
       [21, 22, 23, 24, 25]])
```

▼ Now do the following

▼ Get the sum of all the values in mat

```
sum_of_all_values = np.sum(mat)
sum_of_all_values
```

```
325
```

▼ Get the standard deviation of the values in mat

```
standard_deviation = np.std(mat)
standard_deviation
```

```
7.211102550927978
```

▼ Get the sum of all the columns in mat

```
sum_of_all_columns = np.sum(mat, axis=0)
sum_of_all_columns

array([55, 60, 65, 70, 75])
```

Double-click (or enter) to edit

