

▼ ASSIGNMENT 5

Harsh Kumar

21BDS0391

harsh.kumar2021@vitstudent.ac.in

Assignment 5:

```
Take all the columns in mall_customers.csv
gender age annual income spending score
perform label encoding on gender
train your data
```

▼ 1. import necessary libraries.

```
import numpy as np
import pandas as pd
import seaborn as sns
import matplotlib.pyplot as plt
```

▼ 2. import dataset.

```
df = pd.read_csv("Mall_Customers.csv")
df.head()
```

	CustomerID	Genre	Age	Annual Income (k\$)	Spending Score (1-100)	
0	1	Male	19	15	39	
1	2	Male	21	15	81	
2	3	Female	20	16	6	
3	4	Female	23	16	77	
4	5	Female	31	17	40	

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 200 entries, 0 to 199
Data columns (total 5 columns):
#   Column                Non-Null Count  Dtype
---  -
0   CustomerID            200 non-null   int64
1   Genre                 200 non-null   object
2   Age                   200 non-null   int64
3   Annual Income (k$)    200 non-null   int64
4   Spending Score (1-100) 200 non-null   int64
dtypes: int64(4), object(1)
memory usage: 7.9+ KB
```

▼ 4. Label Encoding

```
from sklearn.preprocessing import LabelEncoder
le = LabelEncoder()
```

```
df["Genre"] = le.fit_transform(df["Genre"])
```

▼ 3. Select the feature to cluster.

```
# Selecting annual income and spending as features for clustering.
```

```
X = df.iloc[:, 1:].values
X

[ 0, 28, 76, 40],
[ 0, 32, 76, 87],
[ 1, 25, 77, 12],
[ 1, 28, 77, 97],
[ 1, 48, 77, 36],
[ 0, 32, 77, 74],
[ 0, 34, 78, 22],
[ 1, 34, 78, 90],
[ 1, 43, 78, 17],
[ 1, 39, 78, 88],
[ 0, 44, 78, 20],
[ 0, 38, 78, 76],
[ 0, 47, 78, 16],
[ 0, 27, 78, 89],
[ 1, 37, 78, 1],
[ 0, 30, 78, 78],
[ 1, 34, 78, 1],
[ 0, 30, 78, 73],
[ 0, 56, 79, 35],
[ 0, 29, 79, 83],
[ 1, 19, 81, 5],
[ 0, 31, 81, 93],
[ 1, 50, 85, 26],
[ 0, 36, 85, 75],
[ 1, 42, 86, 20],
[ 0, 33, 86, 95],
[ 0, 36, 87, 27],
[ 1, 32, 87, 63],
[ 1, 40, 87, 13],
[ 1, 28, 87, 75],
[ 1, 36, 87, 10],
[ 1, 36, 87, 92],
[ 0, 52, 88, 13],
[ 0, 30, 88, 86],
[ 1, 58, 88, 15],
[ 1, 27, 88, 69],
[ 1, 59, 93, 14],
[ 1, 35, 93, 90],
[ 0, 37, 97, 32],
[ 0, 32, 97, 86],
[ 1, 46, 98, 15],
[ 0, 29, 98, 88],
[ 0, 41, 99, 39],
[ 1, 30, 99, 97],
[ 0, 54, 101, 24],
[ 1, 28, 101, 68],
[ 0, 41, 103, 17],
[ 0, 36, 103, 85],
[ 0, 34, 103, 23],
[ 0, 32, 103, 69],
[ 1, 33, 113, 8],
[ 0, 38, 113, 91],
[ 0, 47, 120, 16],
[ 0, 35, 120, 79],
[ 0, 45, 126, 28],
[ 1, 32, 126, 74],
[ 1, 32, 137, 18],
[ 1, 30, 137, 83]]
```

```
type(X)
```

```
numpy.ndarray
```

▼ 5. Find the optimal number of clusters -- elbow method.

```
from sklearn.cluster import KMeans
```

```
# Trying different values of k and calculating WCSS for each value of k
```

```
wcss = []
```

```
for k in range(1,16):
```

```
    kmeans = KMeans(n_clusters = k, init="k-means++", random_state=0)
```

```
    kmeans.fit(X)
```

```
    wcss.append(kmeans.inertia_) #savind wcss value in a list
```

```
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. You should set `n_init` to the new value to avoid this warning.
warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. You should set `n_init` to the new value to avoid this warning.
warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. You should set `n_init` to the new value to avoid this warning.
warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. You should set `n_init` to the new value to avoid this warning.
warnings.warn(
```

```

/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. You should set it to the value you want to use now.
warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. You should set it to the value you want to use now.
warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. You should set it to the value you want to use now.
warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. You should set it to the value you want to use now.
warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. You should set it to the value you want to use now.
warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. You should set it to the value you want to use now.
warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. You should set it to the value you want to use now.
warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. You should set it to the value you want to use now.
warnings.warn(
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. You should set it to the value you want to use now.
warnings.warn(

```

WCSS

```

[308862.06000000006,
212889.44245524303,
143391.59236035676,
104414.67534220168,
75399.61541401484,
58348.641363315044,
51132.703212576904,
44392.11566567935,
41000.8742213207,
37649.69225429742,
34665.087277598795,
31659.187454375693,
29388.61288883975,
28170.631036266237,
26470.47953378321]


```

PLOTTING ELBOW METHOD GRAPH

```

plt.figure(figsize = (8,6))
plt.plot(range(1,16), wcss, "o--", color="red")
plt.title("Elbow method for finding optimal K")
plt.xlabel("Number of clusters K")
plt.ylabel("WCSS")
plt.grid()
plt.show()

```



Taking K=6 instead of because WCSS value is low

- 6. Train the model on dataset using optimal cluster value $k=6$.

```
kmeans = KMeans(n_clusters = 6, init="k-means++", random_state=0) # "k-means++" means initializing the random clusters
# return a label for data based on their cluster.
Y_kmeans = kmeans.fit_predict(X)
```

```
/usr/local/lib/python3.10/dist-packages/sklearn/cluster/_kmeans.py:870: FutureWarning: The default value of `n_init` will change from 10 to 1 in the future. This will affect the results of KMeans and MiniBatchKMeans.
  warnings.warn(
```

Y_kmeans

[illegible]

+ Code

+ Text

```
# Age that belongs to cluster 0
X[Y_kmeans == 0,1]
```

```
array([31, 27, 29, 31, 33, 31, 27, 19, 18, 19, 32, 26, 40, 23, 38, 21, 22,
       34, 18, 40, 32, 24, 27, 20, 23, 26, 21, 19, 38, 19, 18, 19, 27, 38,
       40, 23, 25, 28])
```

```
# Age that belongs to cluster 1
X[Y_kmeans == 1,1]
```

```
array([65, 48, 50, 49, 59, 50, 47, 51, 69, 53, 70, 67, 54, 63, 43, 68, 70,
       47, 60, 60, 59, 45, 49, 57, 67, 46, 48, 55, 50, 68, 48, 47, 48, 49,
       67, 49, 66, 54, 68, 66, 65, 63, 49, 51, 50])
```

```
# Age that belongs to cluster 2
X[Y_kmeans == 2,1]
```

```
array([43, 59, 47, 20, 44, 19, 57, 25, 48, 34, 43, 44, 47, 37, 34, 56, 19,
       50, 42, 36, 40, 36, 52, 58, 59, 37, 46, 41, 54, 41, 34, 33, 47, 45,
       32])
```

```
# Data points that belong to cluster 0
X[Y_kmeans == 0]
```

```
array([[ 0, 31, 39, 61],
       [ 0, 27, 40, 47],
       [ 0, 29, 40, 42],
       [ 0, 31, 40, 42],
       [ 1, 33, 42, 60],
       [ 0, 31, 43, 54],
       [ 0, 27, 46, 51],
       [ 1, 19, 46, 55],
       [ 1, 18, 48, 59],
       [ 1, 19, 48, 59],
       [ 0, 32, 48, 47],
       [ 1, 26, 54, 54],
       [ 1, 40, 54, 48],
       [ 0, 23, 54, 52],
       [ 1, 38, 54, 55],
       [ 0, 21, 54, 57],
       [ 0, 22, 57, 55],
       [ 0, 34, 58, 60],
       [ 1, 18, 59, 41],
       [ 0, 40, 60, 40],
       [ 0, 32, 60, 42],
       [ 1, 24, 60, 52],
       [ 0, 27, 60, 50],
       [ 1, 20, 61, 49],
       [ 0, 23, 62, 41],
       [ 1, 26, 62, 55],
       [ 0, 21, 62, 42],
       [ 0, 19, 63, 54],
       [ 0, 38, 64, 42],
       [ 1, 19, 64, 46],
       [ 0, 18, 65, 48],
       [ 0, 19, 65, 50],
       [ 1, 27, 67, 56],
       [ 0, 38, 67, 40],
```

```
[ 0, 40, 69, 58],  
[ 0, 23, 70, 29],  
[ 0, 25, 72, 34],  
[ 0, 28, 76, 40]])
```