

Apex Basics and Database

AccountHandler.apxc

```
public class AccountHandler {  
    public static Account insertNewAccount(String AccountName){  
        try {  
            Account newacct = new Account(Name=AccountName);  
            insert newacct;  
            return newacct;  
        } catch (DmlException e) {  
            System.debug('A DML exception has occurred: ' +  
                e.getMessage());  
            return null;  
        }  
    }  
}
```

ContactAndLeadSearch.apxc

```
public class ContactAndLeadSearch {  
  
    //a public static method that accepts an incoming string as a parameter  
    public static List<List<sObject>> searchContactsAndLeads (String incoming) {  
        //write a SOSQL query to search by lead or contact name fields for the incoming string.  
        List<List<sObject>> searchList = [FIND :incoming IN NAME FIELDS  
            RETURNING Contact(FirstName,LastName),Lead(FirstName,LastName)];  
        //return the list of the same kind  
        return searchList;  
    }  
}
```

ContactSearch.apxc

```
public class ContactSearch{
    public static list<Contact> searchForContacts(string name1, string name2){
        List <Contact> con = new List<contact>();
        con = [SELECT ID,FirstName from Contact where LastName =:name1 and
MailingPostalCode=:name2];
        return con;
    }
}
```

StringArrayTest.apxc

```
public class StringArrayTest {
    public static List<String> generateStringArray(Integer N){
        List<String> TestList = new List<String>();
        for(Integer i=0;i<N;i++){
            TestList.add('Test ' + i);
            system.debug(TestList[i]);
        }
        return TestList;
    }
}
```

Apex Integration Services

AccountManager.apxc

```
@RestResource(urlMapping='/Accounts/*/contacts')
global with sharing class AccountManager{
    @HttpGet
    global static Account getAccount(){
        RestRequest req = RestContext.request;
        String accId = req.requestURI.substringBetween('Accounts/', '/contacts');
        Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
                        FROM Account WHERE Id = :accId];

        return acc;
    }
}
```

AccountManagerTest.apxc

@IsTest

```
private class AccountManagerTest{
    @isTest static void testAccountManager(){
        Id recordId = getTestAccountId();
        // Set up a test request
        RestRequest request = new RestRequest();
        request.requestUri =
            'https://ap5.salesforce.com/services/apexrest/Accounts/'+ recordId +'/contacts';
        request.httpMethod = 'GET';
        RestContext.request = request;

        // Call the method to test
        Account acc = AccountManager.getAccount();

        // Verify results
        System.assert(acc != null);
    }

    private static Id getTestAccountId(){
        Account acc = new Account(Name = 'TestAcc2');
        Insert acc;

        Contact con = new Contact(LastName = 'TestCont2', AccountId = acc.Id);
        Insert con;

        return acc.Id;
    }
}
```

AnimalLocator.apxc

```
public class AnimalLocator{ public static String getAnimalNameById(Integer id) {    Http
http = new Http();    HttpRequest request = new HttpRequest();
request.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/'+id);
request.setMethod('GET');    HttpResponse response = http.send(request);    String strResp
= "";    system.debug('*****response '+response.getStatusCode());
system.debug('*****response '+response.getBody());    // If the request is successful, parse
the JSON response.    if (response.getStatusCode() == 200)    {    // Deserializes the
JSON string into collections of primitive data types.    Map<String, Object> results =
(Map<String, Object>) JSON.deserializeUntyped(response.getBody());    // Cast the values
in the 'animals' key as a list    Map<string,object> animals = (map<string,object>)
results.get('animal');    System.debug('Received the following animals:' + animals );
strResp = string.valueOf(animals.get('name'));    System.debug('strResp >>>>>' + strResp
);    }    return strResp ; }}
```

AnimalLocatorMock.apxc

@isTest

```
global class AnimalLocatorMock implements HttpCalloutMock {
    // Implement this interface method
    global HTTPResponse respond(HTTPRequest request) {
        // Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody('{"animal":{"id":1,"name":"chicken","eats":"chicken food","says":"cluck
cluck"}}');
        response.getStatusCode(200);
        return response;
    }
}
```

AnimalLocatorTest.apxc

```
@isTest public class AnimalLocatorTest { @isTest public static void AnimalLocatorMock() {
Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());    string result =
AnimalLocator.getAnimalNameById(1);    system.debug(result);    String expectedResult =
'chicken';    System.assertEquals(result, expectedResult );  }}
```

AsyncParksService.apxc

```
public class AsyncParksService {
    public class byCountryResponseFuture extends System.WebServiceCalloutFuture {
        public String[] getValue() {
            parksService.byCountryResponse response =
(parksService.byCountryResponse)System.WebServiceCallout.endInvoke(this);
            return response.return_x;
        }
    }
    public class AsyncParksImplPort {
        public String endpoint_x = 'https://th-apex-soap-service.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public String clientCertName_x;
        public Integer timeout_x;
        private String[] ns_map_type_info = new String[]{'http://parks.services/', 'parksService'};
        public AsyncParksService.byCountryResponseFuture
beginByCountry(System.Continuation continuation,String arg0) {
            parksService.byCountry request_x = new parksService.byCountry();
            request_x.arg0 = arg0;
            return (AsyncParksService.byCountryResponseFuture)
```

```

System.WebServiceCallout.beginInvoke(
    this,
    request_x,
    AsyncParksService.byCountryResponseFuture.class,
    continuation,
    new String[]{endpoint_x,
        "",
        'http://parks.services/',
        'byCountry',
        'http://parks.services/',
        'byCountryResponse',
        'parksService.byCountryResponse'}
    );
}
}
}

```

ParkLocator.apxc

```

public class ParkLocator {
    public static String[] country(String country){
        ParkService.ParksImplPort parks = new ParkService.ParksImplPort();
        String[] parksname = parks.byCountry(country);
        return parksname;
    }
}

```

ParkLocatorTest.apxc

```

@isTestprivate class ParkLocatorTest{
    @isTest static void testParkLocator() {
        Test.setMock(WebServiceMock.class, new ParkServiceMock());
        String[] arrayOfParks = ParkLocator.country('India');
        System.assertEquals('Park1', arrayOfParks[0]);
    }
}

```

ParkService.apxc

```
public class ParkService { public class byCountryResponse { public String[] return_x;
private String[] return_x_type_info = new String[]{'return','http://parks.services/',null,'0','-
1','false'}; private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'}; private String[] field_order_type_info = new
String[]{'return_x'}; } public class byCountry { public String arg0; private String[]
arg0_type_info = new String[]{'arg0','http://parks.services/',null,'0','1','false'}; private
String[] apex_schema_type_info = new String[]{'http://parks.services/','false','false'}; private
String[] field_order_type_info = new String[]{'arg0'}; } public class ParksImplPort {
public String endpoint_x = 'https://th-apex-soap-service.herokuapp.com/service/parks';
public Map<String,String> inputHttpHeaders_x; public Map<String,String>
outputHttpHeaders_x; public String clientCertName_x; public String clientCert_x;
public String clientCertPasswd_x; public Integer timeout_x; private String[]
ns_map_type_info = new String[]{'http://parks.services/', 'ParkService'}; public String[]
byCountry(String arg0) { ParkService.byCountry request_x = new
ParkService.byCountry(); request_x.arg0 = arg0; ParkService.byCountryResponse
response_x; Map<String, ParkService.byCountryResponse> response_map_x = new
Map<String, ParkService.byCountryResponse>(); response_map_x.put('response_x',
response_x); WebServiceCallout.invoke( this, request_x,
response_map_x, new String[]{endpoint_x, "", 'http://parks.services/',
'byCountry', 'http://parks.services/', 'byCountryResponse',
'ParkService.byCountryResponse'} ); response_x =
response_map_x.get('response_x'); return response_x.return_x; } }}
```


ParkServiceMock.apxc

```
@isTestglobal class ParkServiceMock implements WebServiceMock { global void doInvoke(
Object stub,      Object request,      Map<String, Object> response,      String endpoint,
String soapAction,      String requestName,      String responseNS,      String
responseName,      String responseType) {      // start - specify the response you want to send
ParkService.byCountryResponse response_x =      new ParkService.byCountryResponse();
List<String> myStrings = new List<String> {'Park1','Park2','Park3'};      response_x.return_x =
myStrings;      // end      response.put('response_x', response_x);  }}
```

Apex Testing

RandomContactFactory.apxc

```
public class RandomContactFactory {

    public static List<Contact> generateRandomContacts(Integer num, String lastName){
        List<Contact> contactList = new List<Contact>();
        for(Integer i = 1; i <= num; i++){
            Contact ct = new Contact(FirstName = 'Test '+i, LastName = lastname);
            contactList.add(ct);
        }
        return contactList;
    }
}
```

RestrictContactByName.apxt

```
trigger RestrictContactByName on Contact (before insert, before update) {

    //check contacts prior to insert or update for invalid data
    For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') {           //invalidname is invalid
            c.AddError('The Last Name "'+c.LastName+'" is not allowed for DML');
        }
    }
}
```

```
}
```

TestRestrictContactByName.apxc

```
@isTest
public class TestRestrictContactByName {
    @isTest static void testContact(){
        Contact ct = new Contact();
        ct.LastName = 'INVALIDNAME';
        Database.SaveResult res = Database.insert(ct, false);
        System.assertEquals("The Last Name \"INVALIDNAME\" is not allowed for DML",
res.getErrors()[0].getMessage());
    }
}
```

TestVerifyDate.apxc

```
@isTest
public class TestVerifyDate {
    @isTest static void Test_CheckDates_case1(){
        Date d = VerifyDate.CheckDates(Date.parse('01/01/2020'), Date.parse('01/03/2020'));
        System.assertEquals(Date.parse('01/03/2020'), d);
    }
    @isTest static void Test_CheckDates_case2(){
        Date d = VerifyDate.CheckDates(Date.parse('01/01/2020'), Date.parse('03/03/2020'));
        System.assertEquals(Date.parse('01/31/2020'), d);
    }
}
```

VerifyDate.apxc

```
public class VerifyDate {

    //method to handle potential checks against two dates
    public static Date CheckDates(Date date1, Date date2) {
        //if date2 is within the next 30 days of date1, use date2. Otherwise use the end of the
month
        if(DateWithin30Days(date1,date2)) {
            return date2;
        } else {
            return SetEndOfMonthDate(date1);
        }
    }

    //method to check if date2 is within the next 30 days of date1
    private static Boolean DateWithin30Days(Date date1, Date date2) {
        //check for date2 being in the past
        if( date2 < date1) { return false; }

        //check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1
        if( date2 >= date30Days ) { return false; }
        else { return true; }
    }
}
```

```
//method to return the end of the month of a given date
private static Date SetEndOfMonthDate(Date date1) {
    Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
    Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
    return lastDay;
}

}
```

Apex Triggers

-

AccountAddressTrigger.apxt

-

```
trigger AccountAddressTrigger on Account (before insert, before update) {  
    for(Account account:Trigger.New){  
        if(account.Match_Billing_Address__c == True){  
            account.ShippingPostalCode = account.BillingPostalCode;  
        }  
    }  
}
```

ClosedOpportunityTrigger.apxt

```
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {  
    List<Task> tasklist = new List<Task>();  
  
    for(Opportunity op: Trigger.New){  
        if(op.StageName == 'Closed Won'){  
            tasklist.add(new Task(Subject = 'Follow Up Test Task', WhatId = op.Id));  
        }  
    }  
    if(tasklist.size() > 0){  
        insert tasklist;  
    }  
}
```

Asynchronous Apex

AccountProcessor.apxc

```
public class AccountProcessor {

    @future
    public static void countContacts(List<Id> accountsIds){
        List<Account> accList = [Select Id, Number_Of_Contacts__c, (Select Id from Contacts)
from Account where Id in :accountsIds];

        for(Account acc: accList){
            acc.Number_Of_Contacts__c = acc.Contacts.size();
        }

        update accList;
    }
}
```

AccountProcessorTest.apxc

@isTest

```
public class AccountProcessorTest {
```

```
    public static testmethod void testAccountProcessor(){
```

```
        Account a = new Account();
```

```
        a.Name = 'Test Account';
```

```
        insert a;
```

```
        Contact con = new Contact();
```

```
        con.FirstName = 'Yash';
```

```
        con.LastName = 'Kalola';
```

```
        con.AccountId = a.Id;
```

```
        insert con;
```

```
        List<Id> accListId = new List<Id>();
```

```
        accListId.add(a.Id);
```

```
        Test.startTest();
```

```
        AccountProcessor.countContacts(accListId);
```

```
        Test.stopTest();
```

```
        Account acc = [Select Number_Of_Contacts__c from Account where Id =: a.Id];
```

```
        System.assertEquals(Integer.valueOf(acc.Number_Of_Contacts__c), 1);
```

```
    }
```

```
}
```


AddPrimaryContact.apxc

```
public class AddPrimaryContact implements Queueable {
    public contact c;
    public String state;

    public AddPrimaryContact(Contact c, String state) {
        this.c = c;
        this.state = state;
    }

    public void execute(QueueableContext qc) {
        system.debug('this.c = '+this.c+' this.state = '+this.state);
        List<Account> acc_lst = new List<account>([select id, name, BillingState from account
where account.BillingState = :this.state limit 200]);
        List<contact> c_lst = new List<contact>();
        for(account a: acc_lst) {
            contact c = new contact();
            c = this.c.clone(false, false, false, false);
            c.AccountId = a.Id;
            c_lst.add(c);
        }
        insert c_lst;
    }
}
```

AddPrimaryContactTest.apxc

@IsTest

public class AddPrimaryContactTest {

 @IsTest

 public static void testing() {

 List<account> acc_lst = new List<account>();

 for (Integer i=0; i<50;i++) {

 account a = new account(name=string.valueOf(i),billingstate='NY');

 system.debug('account a = '+a);

 acc_lst.add(a);

 }

 for (Integer i=0; i<50;i++) {

 account a = new account(name=string.valueOf(50+i),billingstate='CA');

 system.debug('account a = '+a);

 acc_lst.add(a);

 }

 insert acc_lst;

 Test.startTest();

 contact c = new contact(lastname='alex');

 AddPrimaryContact apc = new AddPrimaryContact(c,'CA');

 system.debug('apc = '+apc);

 System.enqueueJob(apc);

 Test.stopTest();

 List<contact> c_lst = new List<contact>([select id from contact]);

 Integer size = c_lst.size();

 system.assertEquals(50, size);

 }

}

DailyLeadProcessor.apxc

```
global class DailyLeadProcessor implements Schedulable {

    global void execute(SchedulableContext ctx) {

        //Retrieving the 200 first leads where lead source is in blank.
        List<Lead> leads = [SELECT ID, LeadSource FROM Lead where LeadSource = " LIMIT
200];

        //Setting the LeadSource field the 'Dreamforce' value.
        for (Lead lead : leads) {
            lead.LeadSource = 'Dreamforce';
        }

        //Updating all elements in the list.
        update leads;
    }
}
```

DailyLeadProcessorTest.apxc

```
@isTest
private class DailyLeadProcessorTest {

    @isTest
    public static void testDailyLeadProcessor(){

        //Creating new 200 Leads and inserting them.
        List<Lead> leads = new List<Lead>();
        for (Integer x = 0; x < 200; x++) {
            leads.add(new Lead(lastname='lead number ' + x, company='company number ' + x));
        }
        insert leads;

        //Starting test. Putting in the schedule and running the DailyLeadProcessor execute method.
        Test.startTest();
        String jobId = System.schedule('DailyLeadProcessor', '0 0 12 * * ?', new
DailyLeadProcessor());
        Test.stopTest();

        //Once the job has finished, retrieve all modified leads.
        List<Lead> listResult = [SELECT ID, LeadSource FROM Lead where LeadSource =
'Dreamforce' LIMIT 200];

        //Checking if the modified leads are the same size number that we created in the start of this
method.
        System.assertEquals(200, listResult.size());

    }
}
```

LeadProcessor.apxc

```
global class LeadProcessor implements Database.Batchable<sObject> {
    global Integer count = 0;

    global Database.QueryLocator start(Database.BatchableContext bc){
        return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
    }

    global void execute(Database.BatchableContext bc, List<Lead> L_list){
        List<lead> L_list_new = new List<lead>();

        for(lead L:L_list){
            L.leadsource = 'Dreamforce';
            L_list_new.add(L);
            count += 1;
        }

        update L_list_new;
    }
    global void finish(Database.BatchableContext bc){
        System.debug('count = '+count);
    }
}
```

LeadProcessorTest.apxc

```
@isTest
public class LeadProcessorTest {
    @isTest
    public static void testit(){
        List<lead> L_list = new List<lead>();

        for(Integer i=0; i<200; i++){
            Lead L = new lead();
            L.LastName = 'name' + i;
            L.Company = 'Company';
            L.Status = 'Random Status';
            L_list.add(L);
        }
        insert L_list;

        Test.startTest();
        LeadProcessor lp = new LeadProcessor();
        Id batchId = Database.executeBatch(lp);
        Test.stopTest();
    }
}
```

Superbadge Apex Specialist

Challenge 1 : Automate Record Creation

MaintenanceRequest.apxt

```
trigger MaintenanceRequest on Case (before update, after update) { // ToDo: Call
MaintenanceRequestHelper.updateWorkOrdersif(Trigger.isAfter)MaintenanceRequestHelper.upd
ateWorkOrders(Trigger.New);}
```

MaintenanceRequestHelper.apxc

```
public with sharing class MaintenanceRequestHelper {public static void
updateWorkOrders(List<Case> caseList) {List<case> newCases = new
List<Case>();Map<String,Integer> result=getDueDate(caseList);for(Case c :
caseList){ if(c.status=='closed')if(c.type=='Repair' || c.type=='Routine Maintenance'){ Case
newCase = new Case();newCase.Status='New';newCase.Origin='web';newCase.Type='Routine
Maintenance';newCase.Subject='Routine Maintenance of
Vehicle';newCase.Vehicle__c=c.Vehicle__c;newCase.Equipment__c=c.Equipment__c;newCase.
Date_Reported__c=Date.today();if(result.get(c.Id)!=null)newCase.Date_Due__c=Date.today()+r
esult.get(c.Id);elsenewCase.Date_Due__c=Date.today();newCases.add(newCase);}}insert
newCases;}//public static  Map<String,Integer> getDueDate(List<case>
CaseIDs){Map<String,Integer> result = new Map<String,Integer>();Map<Id, case> caseKeys =
new Map<Id, case> (CaseIDs);List<AggregateResult> wpc=[select Maintenance_Request__r.ID
cID,min(Equipment__r.Maintenance_Cycle__c)cyclefrom Work_Part__c where
Maintenance_Request__r.ID in :caseKeys.keySet() group by      Maintenance_Request__r.ID
];for(AggregateResult res :wpc){ Integer
addDays=0;if(res.get('cycle')!=null)addDays+=Integer.valueOf(res.get('cycle'));result.put((String
)res.get('cID'),addDays);}return result;}}
```

Challenge - 2 : Synchronize Salesforce data with an external system

Anonymous Window Code:

```
WarehouseCalloutService.runWarehouseEquipmentSync();
```

WarehouseCalloutService.apxc

```
public with sharing class WarehouseCalloutService {private static final String
WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';@future(callout=true)public static void
runWarehouseEquipmentSync() {//ToDo: complete this method to make the callout (using
@future) to the// REST endpoint and update equipment on hand.HttpResponse response =
getResponse();if(response.getStatusCode() == 200){List<Product2> results =
getProductList(response); //get list of products from Http callout responseif(results.size()
>0)upsert results Warehouse_SKU__c; //Upsert the products in your org based on the external ID
SKU}}//Get the product list from the external linkpublic static List<Product2>
getProductList(HttpResponse response){List<Object> externalProducts = (List<Object>)
JSON.deserializeUntyped(response.getBody()); //desrialize the json responseList<Product2>
newProducts = new List<Product2>();for(Object p : externalProducts){Map<String, Object>
productMap = (Map<String, Object>) p;Product2 pr = new Product2();//Map the fields in the
response to the appropriate fields in the Equipment objectpr.Replacement_Part__c =
```



```
(Boolean)productMap.get('replacement');pr.Cost__c =
(Integer)productMap.get('cost');pr.Current_Inventory__c =
(Integer)productMap.get('quantity');pr.Lifespan_Months__c =
(Integer)productMap.get('lifespan') ;pr.Maintenance_Cycle__c =
(Integer)productMap.get('maintenanceperiod');pr.Warehouse_SKU__c =
(String)productMap.get('sku');pr.ProductCode = (String)productMap.get('_id');pr.Name =
(String)productMap.get('name');newProducts.add(pr);}return newProducts;}// Send Http GET
request and receive Http responsepublic static HttpResponse getResponse() {Http http = new
Http();HttpRequest request = new
HttpRequest();request.setEndpoint(WAREHOUSE_URL);request.setMethod('GET');HttpRespon
se response = http.send(request);return response;}}
```

Challenge - 3 : Schedule Synchronization

Anonymous Window Code

```
WarehouseSyncSchedule scheduleInventoryCheck();
```

WarehouseSyncSchedule.apxc

```
global class WarehouseSyncSchedule implements Schedulable{// implement scheduled code  
hereglobal void execute (SchedulableContext  
sc){WarehouseCalloutService.runWarehouseEquipmentSync();//optional this can be done by  
debug modeString sch = '00 00 01 * * ?';//on 1  
pmSystem.schedule('WarehouseSyncScheduleTest', sch, new WarehouseSyncSchedule());}}
```

Challenge - 4 : Test automation logic

InstallationTests.apxc

```
@IsTestprivate class InstallationTests {private static final String STRING_TEST =
'TEST';private static final String NEW_STATUS = 'New';private static final String WORKING =
'Working';private static final String CLOSED = 'Closed';private static final String REPAIR =
'Repair';private static final String REQUEST_ORIGIN = 'Web';private static final String
REQUEST_TYPE = 'Routine Maintenance';private static final String REQUEST_SUBJECT =
'AMC Spirit';public static String CRON_EXP = '0 0 1 * * ?';static testmethod void
testMaintenanceRequestNegative() {Vehicle__c vehicle = createVehicle();insert vehicle;Id
vehicleId = vehicle.Id;Product2 equipment = createEquipment();insert equipment;Id
equipmentId = equipment.Id;Case r = createMaintenanceRequest(vehicleId, equipmentId);insert
r;Work_Part__c w = createWorkPart(equipmentId, r.Id);insert w;Test.startTest();r.Status =
WORKING;update r;Test.stopTest();List<case> allRequest = [SELECT IdFROM
Case];Work_Part__c workPart = [SELECT IdFROM Work_Part__cWHERE
Maintenance_Request__c =: r.Id];System.assert(workPart !=
null);System.assert(allRequest.size() == 1);}static testmethod void testWarehouseSync()
{Test.setMock(HttpCalloutMock.class, new
WarehouseCalloutServiceMock());Test.startTest();String jobId =
System.schedule('WarehouseSyncSchedule',CRON_EXP,new
WarehouseSyncSchedule());CronTrigger ct = [SELECT Id, CronExpression, TimesTriggered,
NextFireTimeFROM CronTriggerWHERE id = :jobId];System.assertEquals(CRON_EXP,
ct.CronExpression);System.assertEquals(0, ct.TimesTriggered);Test.stopTest();}private static
Vehicle__c createVehicle() {Vehicle__c v = new Vehicle__c(Name = STRING_TEST);return
v;}private static Product2 createEquipment() {Product2 p = new Product2(Name =
STRING_TEST,Lifespan_Months__c = 10,Maintenance_Cycle__c = 10,Replacement_Part__c =
true);return p;}private static Case createMaintenanceRequest(Id vehicleId, Id equipmentId)
{Case c = new Case(Type = REPAIR,Status = NEW_STATUS,Origin =
REQUEST_ORIGIN,Subject = REQUEST_SUBJECT,Equipment__c = equipmentId,Vehicle__c
= vehicleId);return c;}private static Work_Part__c createWorkPart(Id equipmentId, Id requestId)
{Work_Part__c wp = new Work_Part__c(Equipment__c =
equipmentId,Maintenance_Request__c = requestId);return wp;}}
```

MaintenanceRequest.apxt

trigger MaintenanceRequest on Case (before update, after update) {if(Trigger.isUpdate && Trigger.isAfter)MaintenanceRequestHelper.updateWorkOrders(Trigger.New);}

-

MaintenanceRequestHelper.apxc

```
public with sharing class MaintenanceRequestHelper {public static void
updateWorkOrders(List<case> caseList) {List<case> newCases = new
List<case>();Map<String,Integer> result=getDueDate(caseList);for(Case c :
caseList){if(c.status=='closed')if(c.type=='Repair' || c.type=='Routine Maintenance'){Case
newCase = new Case();newCase.Status='New';newCase.Origin='web';newCase.Type='Routine
Maintenance';newCase.Subject='Routine Maintenance of
Vehicle';newCase.Vehicle__c=c.Vehicle__c;newCase.Equipment__c=c.Equipment__c;newCase.
Date_Reported__c=Date.today();if(result.get(c.Id)!=null)newCase.Date_Due__c=Date.today()+r
esult.get(c.Id);elsenewCase.Date_Due__c=Date.today();newCases.add(newCase);}}insert
newCases;}//public static Map<String,Integer> getDueDate(List<case>
CaseIDs){Map<String,Integer> result = new Map<String,Integer>();Map<Id, case> caseKeys =
new Map<Id, case> (CaseIDs);List<aggregateresult> wpc=[select Maintenance_Request__r.ID
cID,min(Equipment__r.Maintenance_Cycle__c)cyclefrom Work_Part__c where
Maintenance_Request__r.ID in :caseKeys.keySet() group by Maintenance_Request__r.ID
];for(AggregateResult res :wpc){Integer
addDays=0;if(res.get('cycle')!=null)addDays+=Integer.valueOf(res.get('cycle'));result.put((String
)res.get('cID'),addDays);}return result;}}
```

MaintenanceRequestTest.apxc

```
@isTestpublic class MaintenanceRequestTest {static List<case> caseList1 = new
List<case>();static List<product2> prodList = new List<product2>();static List<work_part__c>
wpList = new List<work_part__c>();@testSetupstatic void getData(){caseList1= CreateData(
300,3,3,'Repair');}public static List<case> CreateData( Integer numOfcase, Integer numofProd,
Integer numofVehicle,String type){List<case> caseList = new List<case>();//Create
VehicleVehicle__c vc = new Vehicle__c();vc.name='Test Vehicle';upsert vc;//Create
Equipmentfor(Integer i=0;i<numofProd;i++){Product2 prod = new Product2();prod.Name='Test
Product'+i;if(i!=0)prod.Maintenance_Cycle__c=i;prod.Replacement_Part__c=true;prodList.add(
prod);}upsert prodlist;//Create Casefor(Integer i=0;i< numOfcase;i++){Case newCase = new
Case();newCase.Status='New';newCase.Origin='web';if( math.mod(i, 2)
==0)newCase.Type='Routine
Maintenance';elsenewCase.Type='Repair';newCase.Subject='Routine Maintenance of Vehicle'
+i;newCase.Vehicle__c=vc.Id;if(i<numofProd)newCase.Equipment__c=prodList.get(i).ID;elsen
ewCase.Equipment__c=prodList.get(0).ID;caseList.add(newCase);}upsert caseList;for(Integer
i=0;i<numofProd;i++){Work_Part__c wp = new Work_Part__c();wp.Equipment__c
=prodlist.get(i).Id ;wp.Maintenance_Request__c=caseList.get(i).id;wplist.add(wp) ;}upsert
wplist;return caseList;}public static testmethod void
testMaintenanceHelper(){Test.startTest();getData();for(Case cas: caseList1)cas.Status
='Closed';update caseList1;Test.stopTest();}}
```

Challenge - 5 : Test Callout Logic

WarehouseCalloutServiceMock.apxc

```
@isTestpublic class WarehouseCalloutServiceMock implements HTTPCalloutMock {//
implement http mock calloutpublic HTTPResponse respond (HttpRequest
request){HTTPResponse response = new HTTPResponse();response.setHeader('Content-
type','application/json');response.setBody(["{"_id":"55d66226726b611100aaf741","replacement":
false,"quantity":5,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"},{"_id":"55d6622672
6b611100aaf742","replacement":true,"quantity":183,"name":"Cooling
Fan","maintenanceperiod":0,"lifespan":0,"cost":300,"sku":"100004"},{"_id":"55d66226726b611
100aaf743","replacement":true,"quantity":143,"name":"Fuse
20A","maintenanceperiod":0,"lifespan":0,"cost":22,"sku":"100005"}]);response.setStatusCode(2
00);return response;}}
```

WarehouseCalloutServiceTest.apxc

```
@IsTestprivate class WarehouseCalloutServiceTest {// implement your mock callout test
here@isTeststatic void testWareHouseCallout(){Test.setMock(HTTPCalloutMock.class, new
WarehouseCalloutServiceMock());WarehouseCalloutService.runWarehouseEquipmentSync();}}
```

Challenge - 6 : Test Scheduling Logic

WarehouseSyncScheduleTest.apxc

```
@isTest
private class WarehouseSyncScheduleTest {
    public static String CRON_EXP = '0 0 0 15 3 ? 2022';
    static testmethod void testjob(){
        MaintenanceRequestTest.CreateData( 5,2,2,'Repair');
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String joBID= System.schedule('TestScheduleJob', CRON_EXP, new WarehouseSyncSchedule());
        // List<Case> caselist = [Select count(id) from case where case]
        Test.stopTest();
    }
}
```