

APEX SPECIALIST SUPER BADGE CODES

APEX TRIGGERS

AccountAddressTrigger.axpt:

```
trigger AccountAddressTrigger on Account (before insert,before update) {  
  for(Account account:Trigger.New){  
    if(account.Match_Billing_Address__c == True){  
      account.ShippingPostalCode = account.BillingPostalCode;  
    }  
  }  
}
```

ClosedOpportunityTrigger.axpt:

```
trigger ClosedOpportunityTrigger on Opportunity (after insert,after update) {  
  List<Task> tasklist = new List<Task>();  
  for(Opportunity opp: Trigger.New){  
    if(opp.StageName == 'Closed Won'){  
      tasklist.add(new Task(Subject = 'Follow Up Test Task',WhatId = opp.Id));  
    }  
  }  
  if(tasklist.size() > 0){  
    insert tasklist;  
  }  
}
```

APEX TESTING

VerifyData.apxc:

```
public class VerifyDate {  
  public static Date CheckDates(Date date1, Date date2) {  
    if(DateWithin30Days(date1,date2)) {  
      return date2;  
    } else {  
      return SetEndOfMonthDate(date1);  
    }  
  }  
  
  @TestVisible private static Boolean DateWithin30Days(Date date1, Date date2) {  
    //check for date2 being in the past  
    if( date2 < date1) { return false; }  
    //check that date2 is within (>=) 30 days of date1  
    Date date30Days = date1.addDays(30); //create a date 30 days away from date1
```

```

if( date2 >= date30Days ) { return false; }
else { return true; }
}
//method to return the end of the month of a given date
@TestVisible private static Date SetEndOfMonthDate(Date date1) {
Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
return lastDay;
}
}
TestVerifyData.apxc:
@Test
private class TestVerifyDate {
@Test static void Test_CheckDates_case1(){
Date D = VerifyDate.CheckDates(date.parse('01/01/2022'),date.parse('01/05/2022'));
System.assertEquals(date.parse('01/05/2022'), D);
}
@Test static void Test_CheckDates_case2(){
Date D = VerifyDate.CheckDates(date.parse('01/01/2022'), date.parse('05/05/2022'));
System.assertEquals(date.parse('01/31/2022'), D);
}
@Test static void Test_Within30Days_case1(){
Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2022'),
date.parse('12/30/2021'));
System.assertEquals(false, flag);
}
@Test static void Test_Within30Days_case2(){
Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2022'),
date.parse('02/02/2021'));
System.assertEquals(false, flag);
}
@Test static void Test_Within30Days_case3(){
Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2022'),
date.parse('01/15/2022'));
System.assertEquals(true, flag);
}
@Test static void Test_SetEndOfMonthDate(){

```

```
Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2022'));  
}  
}
```

RestrictContactByName.apxt:

```
trigger RestrictContactByName on Contact (before insert, before update) {  
    //check contacts prior to insert or update for invalid data  
    For (Contact c : Trigger.New) {  
        if(c.LastName == 'INVALIDNAME') { //invalidname is invalid  
            c.AddError('The Last Name "'+c.LastName+'" is not allowed for DML');  
        }  
    }  
}
```

TestRestrictContactByName.apxc:

```
@isTest  
private class TestRestrictContactByName {  
    @isTest static void Test_insertupdateContact(){  
        Contact cnt = new Contact();  
        cnt.LastName = 'INVALIDNAME';  
        Test.startTest();  
        Database.SaveResult result = Database.insert(cnt,false);  
        Test.stopTest();  
        System.assert(!result.isSuccess());  
        System.assert(result.getErrors().size() > 0);  
        System.assertEquals('The Last Name "INVALIDNAME" is not allowed for DML',  
            result.getErrors()[0].getMessage());  
    }  
}
```

RandomContactFactory.apxc:

```
public class RandomContactFactory {  
    public static List<Contact> generateRandomContacts(Integer num_cnts, string  
        lastname) {  
        List<Contact> contacts = new List<Contact>();  
        for(Integer i = 0; i < num_cnts; i++) {  
            Contact cnt = new Contact(FirstName = 'Test' +i,LastName = lastname);  
            contacts.add(cnt);  
        }  
        return contacts;  
    }  
}
```

```
}  
}
```

ASYNCHRONOUS APEX

AccountProcessor.apxc:

```
public class AccountProcessor {  
    @future  
    public static void countContacts(List<Id> accountIds){  
        List<Account> accountsToUpdate = new List<Account>();  
        List<Account> accounts = [Select Id, Name, (Select Id from Contacts)from Account  
        Where Id in  
        :accountIds];  
        For(Account acc: accounts) {  
            List<Contact> contactList = acc.contacts;  
            acc.Number_Of_Contacts__c = contactList.size();  
            accountsToUpdate.add(acc);  
        }  
        update accountsToUpdate;  
    }  
}
```

AccountProcessorTest.apxc:

```
@isTest  
public class AccountProcessorTest {  
    @isTest  
    private static void testCountContacts() {  
        Account newAccount = new Account(Name = 'Test Account');  
        insert newAccount;  
        Contact newContact1 = new Contact(FirstName = 'John',LastName = 'Doe',AccountId =  
        newAccount.Id);  
        insert newContact1;  
        Contact newContact2 = new Contact(FirstName = 'John',LastName = 'Doe',AccountId =  
        newAccount.Id);  
        insert newContact2;  
        List<Id> accountIds = new List<Id>();  
        accountIds.add(newAccount.Id);  
        Test.startTest();  
        AccountProcessor.countContacts(accountIds);  
        Test.stopTest();  
    }  
}
```

```
}  
}
```

LeadProcessor.apxc:

```
global class LeadProcessor implements Database.Batchable<sObject>{  
    global Integer count = 0;  
    global Database.QueryLocator start(Database.BatchableContext bc) {  
        return Database.getQueryLocator('SELECT ID,LeadSource FROM Lead');  
    }  
    global void execute(Database.BatchableContext bc, List<Lead> L_list){  
        List<lead> L_list_new = new List<lead>();  
        for(lead L: L_list){  
            L.leadSource = 'Dreamforce';  
            L_list_new.add(L);  
            count += 1;  
        }  
        update L_list_new;  
    }  
    global void finish(Database.BatchableContext bc){  
        system.debug('count = ' + count);  
    }  
}
```

LeadProcessorTest.apxc:

```
@isTest  
public class LeadProcessorTest {  
    @isTest  
    public static void testit() {  
        List<lead> L_list = new List<lead>();  
        for(Integer i = 0; i < 200; i++) {  
            Lead L = new Lead();  
            L.LastName = 'name' + i;  
            L.Company = 'Company';  
            L.Status = 'Random Status';  
            L_list.add(L);  
        }  
        insert L_list;  
        Test.startTest();  
        LeadProcessor lp = new LeadProcessor();
```

```

    Id batchId = Database.executeBatch(lp);
    Test.stopTest();
}
}

AddPrimaryContact.apxc:
public class AddPrimaryContact implements Queueable{
    private Contact con;
    private String state;
    public AddPrimaryContact(Contact con, String state) {
        this.con = con;
        this.state = state;
    }
    public void execute(QueueableContext context) {
        List<Account> accounts = [Select Id,Name,(Select FirstName,LastName, Id from
        contacts)
        from Account where BillingState = :state Limit 200];
        List<Contact> primaryContacts = new List<Contact>();
        for(Account acc : accounts) {
            Contact c = con.clone();
            c.AccountId = acc.Id;
            primaryContacts.add(c);
        }
        if(primaryContacts.size() > 0) {
            insert primaryContacts;
        }
    }
}

AddPrimaryContactTest.apxc:
@isTest
public class AddPrimaryContactTest {
    static testmethod void testQueueable() {
        List<Account> testAccounts = new List<Account>();
        for(Integer i = 0; i < 50; i++) {
            testAccounts.add(new Account (Name = 'Account' + i,BillingState = 'CA'));
        }
        for(Integer j = 0; j < 50; j++) {
            testAccounts.add(new Account(Name = 'Account'+ j, BillingState = 'NY'));
        }
    }
}

```

```

}
insert testAccounts;
Contact testContact = new Contact(FirstName = 'John', LastName = 'Doe');
insert testContact;
AddPrimaryContact addit = new AddPrimaryContact(testContact,'CA');
Test.startTest();
system.enqueueJob(addit);
Test.stopTest();
System.assertEquals(50, [Select count() from Contact where accountId in (Select Id
from
Account where BillingState = 'CA')]);
}
}
DailyLeadProcessor.apxc:
global class DailyLeadProcessor implements Schedulable{
global void execute(SchedulableContext ctx) {
List<Lead> leadstoupdate = new List<Lead>();
List<Lead> leads = [Select id From Lead Where LeadSource = NULL Limit 200];
for(Lead l: leads) {
l.LeadSource = 'Dreamforce';
leadstoupdate.add(l);
}
update leadstoupdate;
}
}
DailyLeadProcessorTest.apxc:
@isTest
private class DailyLeadProcessorTest {
public static String CRON_EXP = '0 0 0 15 3 ? 2024';
static testmethod void testScheduledJob() {
List<Lead> leads = new List<Lead>();
for(Integer i = 0; i < 200; i++) {
Lead l = new Lead(
FirstName = 'First' + i,
LastName = 'LastName',
Company = 'The Inc'
);

```

```

leads.add(l);
}
insert leads;
Test.startTest();
String jobId = System.schedule('ScheduledApexTest',CRON_EXP,new
DailyLeadProcessor());
Test.stopTest();
List<Lead> checkleads = new List<Lead>();
checkleads = [Select Id From Lead Where LeadSource = 'Dreamforce' and Company =
'The Inc'];
System.assertEquals(200,checkleads.size(),'Leads were not created');
}
}

```

APEX INTEGRATION SERVICES

AnimalLocator.apxc:

```

public class AnimalLocator{
public static String getAnimalNameById(Integer x){
Http http = new Http();
HttpRequest req = new HttpRequest();
req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + x);
req.setMethod('GET');
Map<String, Object> animal= new Map<String, Object>();
HttpResponse res = http.send(req);
if (res.getStatusCode() == 200) {
Map<String, Object> results = (Map<String,
Object>)JSON.deserializeUntyped(res.getBody());
animal = (Map<String, Object>) results.get('animal');
}
return (String)animal.get('name');
}
}

```

AnimalLocatorTest.apxc:

```

@Test
private class AnimalLocatorTest{
@Test static void AnimalLocatorMock1() {
Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
string result = AnimalLocator.getAnimalNameById(3);
}
}

```



```

String expectedResult = 'chicken';
System.assertEquals(result,expectedResult );
}
}
AnimalLocatorMock.apxc:
@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
// Implement this interface method
global HTTPResponse respond(HTTPRequest request) {
// Create a fake response
HttpResponse response = new HttpResponse();
response.setHeader('Content-Type', 'application/json');
response.setBody('{"animals": ["majestic badger", "fluffy bunny", "scary bear", "chicken",
"mighty
moose"]}');
response.setStatusCode(200);
return response;
}
}
ParkLocator.apxc:
public class ParkLocator {
public static string[] country(string theCountry) {
ParkService.ParksImplPort parkSvc = new ParkService.ParksImplPort(); // remove
space
return parkSvc.byCountry(theCountry);
}
}
ParkLocatorTest.apxc:
@isTest
private class ParkLocatorTest {
@isTest static void testCallout() {
Test.setMock(WebServiceMock.class, new ParkServiceMock ());
String country = 'United States';
List<String> result = ParkLocator.country(country);
List<String> parks = new List<String>{'Yellowstone', 'Mackinac National Park',
'Yosemite'};
System.assertEquals(parks, result);
}
}

```

```

}
}
ParkServiceMock.apxc:
@isTest
global class ParkServiceMock implements WebServiceMock {
global void doInvoke(
Object stub,
Object request,
Map<String, Object> response,
String endpoint,
String soapAction,
String requestName,
String responseNS,
String responseName,
String responseType) {
// start - specify the response you want to send
ParkService.byCountryResponse response_x = new ParkService.byCountryResponse();
response_x.return_x = new List<String>{'Yellowstone', 'Mackinac National Park',
'Yosemite'};
// end
response.put('response_x', response_x);
}
}
AccountManager.apxc:
@RestResource(urlMapping='/Accounts/*/contacts')
global class AccountManager {
@HttpGet
global static Account getAccount() {
RestRequest req = RestContext.request;
String accId = req.requestURI.substringBetween('Accounts/', '/contacts');
Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
FROM Account WHERE Id = :accId];
return acc;
}
}
AccountManagerTest.apxc:
@isTest

```

```

private class AccountManagerTest {
private static testMethod void getAccountTest1() {
Id recordId = createTestRecord();
// Set up a test request
RestRequest request = new RestRequest();
request.requestUri = 'https://na1.salesforce.com/services/apexrest/Accounts/'+
recordId
+'/contacts' ;
request.httpMethod = 'GET';
RestContext.request = request;
// Call the method to test
Account thisAccount = AccountManager.getAccount();
// Verify results
System.assert(thisAccount != null);
System.assertEquals('Test record', thisAccount.Name);
}
// Helper method
static Id createTestRecord() {
// Create test record
Account TestAcc = new Account(
Name='Test record');
insert TestAcc;
Contact TestCon= new Contact(
LastName='Test',
AccountId = TestAcc.id);
return TestAcc.Id;
}
}

```

APEX SPECIALIST SUPER BADGE

Challenge-1

MaintenanceRequestHelper.apxc:

```

public with sharing class MaintenanceRequestHelper {
public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
Set<Id> validIds = new Set<Id>();
For (Case c : updWorkOrders){
if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){

```

```

if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
validIds.add(c.Id);
}
}
}
if (!validIds.isEmpty()){
List<Case> newCases = new List<Case>();
Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c,
Equipment__r.Maintenance_Cycle__c,(SELECT Id,Equipment__c,Quantity__c FROM
Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM
Equipment_Maintenance_Item__c
WHERE
Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];
for (AggregateResult ar : results){
maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));
}
for(Case cc : closedCasesM.values()){
Case nc = new Case (
ParentId = cc.Id,
Status = 'New',
Subject = 'Routine Maintenance',
Type = 'Routine Maintenance',
Vehicle__c = cc.Vehicle__c,
Equipment__c =cc.Equipment__c,
Origin = 'Web',
Date_Reported__c = Date.Today()
);
If (maintenanceCycles.containsKey(cc.Id)){
nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
}
newCases.add(nc);
}
}

```

```

insert newCases;
List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
Equipment_Maintenance_Item__c wpClone = wp.clone();
wpClone.Maintenance_Request__c = nc.Id;
ClonedWPs.add(wpClone);
}
}
insert ClonedWPs;
}
}
}
MaintenanceRequest.apxt:
trigger MaintenanceRequest on Case (before update, after update) {
if(Trigger.isUpdate && Trigger.isAfter){
MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
}
}
MaintenanceRequestHelperTest.apxc:
@istest
public with sharing class MaintenanceRequestHelperTest {
private static final string STATUS_NEW = 'New';
private static final string WORKING = 'Working';
private static final string CLOSED = 'Closed';
private static final string REPAIR = 'Repair';
private static final string REQUEST_ORIGIN = 'Web';
private static final string REQUEST_TYPE = 'Routine Maintenance';
private static final string REQUEST_SUBJECT = 'Testing subject';
PRIVATE STATIC Vehicle__c createVehicle(){
Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');
return Vehicle;
}
PRIVATE STATIC Product2 createEq(){
product2 equipment = new product2(name = 'SuperEquipment',

```

```

lifespan_months__C = 10,
maintenance_cycle__C = 10,
replacement_part__c = true);
return equipment;
}

PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
case cs = new case(Type=REPAIR,
Status=STATUS_NEW,
Origin=REQUEST_ORIGIN,
Subject=REQUEST_SUBJECT,
Equipment__c=equipmentId,
Vehicle__c=vehicleId);
return cs;
}

PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c =
equipmentId,
Maintenance_Request__c = requestId);
return wp;
}

@istest
private static void testMaintenanceRequestPositive(){
Vehicle__c vehicle = createVehicle();
insert vehicle;
id vehicleId = vehicle.Id;
Product2 equipment = createEq();
insert equipment;
id equipmentId = equipment.Id;
case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
insert somethingToUpdate;
Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
insert workP;
test.startTest();
somethingToUpdate.status = CLOSED;

```

```

update somethingToUpdate;
test.stopTest();
Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c, Vehicle__c,
Date_Due__c
from case
where status =:STATUS_NEW];
Equipment_Maintenance_Item__c workPart = [select id
from Equipment_Maintenance_Item__c
where Maintenance_Request__c =:newReq.Id];
system.assert(workPart != null);
system.assert(newReq.Subject != null);
system.assertEquals(newReq.Type, REQUEST_TYPE);
SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);
SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);
SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
}
@istest
private static void testMaintenanceRequestNegative(){
Vehicle__C vehicle = createVehicle();
insert vehicle;
id vehicleId = vehicle.Id;
product2 equipment = createEq();
insert equipment;
id equipmentId = equipment.Id;
case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
insert emptyReq;
Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId, emptyReq.Id);
insert workP;
test.startTest();
emptyReq.Status = WORKING;
update emptyReq;
test.stopTest();
list<case> allRequest = [select id
from case];
Equipment_Maintenance_Item__c workPart = [select id
from Equipment_Maintenance_Item__c
where Maintenance_Request__c = :emptyReq.Id];

```

```

system.assert(workPart != null);
system.assert(allRequest.size() == 1);
}
@istest
private static void testMaintenanceRequestBulk(){
list<Vehicle__C> vehicleList = new list<Vehicle__C>();
list<Product2> equipmentList = new list<Product2>();
list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
list<case> requestList = new list<case>();
list<id> oldRequestIds = new list<id>();
for(integer i = 0; i < 300; i++){
vehicleList.add(createVehicle());
equipmentList.add(createEq());
}
insert vehicleList;
insert equipmentList;
for(integer i = 0; i < 300; i++){
requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
}
insert requestList;
for(integer i = 0; i < 300; i++){
workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
}
insert workPartList;
test.startTest();
for(case req : requestList){
req.Status = CLOSED;
oldRequestIds.add(req.Id);
}
update requestList;
test.stopTest();
list<case> allRequests = [select id
from case
where status =: STATUS_NEW];
list<Equipment_Maintenance_Item__c> workParts = [select id

```



```

from Equipment_Maintenance_Item__c
where Maintenance_Request__c in: oldRequestIds];
system.assert(allRequests.size() == 300);
}
}

```

Challenge-2

WarehouseCalloutService.apxc:

```

public with sharing class WarehouseCalloutService implements Queueable {
private static final String WAREHOUSE_URL = 'https://thsuperbadge
apex.herokuapp.com/equipment';
//class that makes a REST callout to an external warehouse system to get a list of
equipment
that
needs to be updated.
//The callout's JSON response returns the equipment records that you upsert in
Salesforce.
@future(callout=true)
public static void runWarehouseEquipmentSync(){
Http http = new Http();
HttpRequest request = new HttpRequest();
request.setEndpoint(WAREHOUSE_URL);
request.setMethod('GET');
HttpResponse response = http.send(request);
List<Product2> warehouseEq = new List<Product2>();
if (response.getStatusCode() == 200){
List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
System.debug(response.getBody());
//class maps the following fields: replacement part (always true), cost, current inventory,
lifespan, maintenance cycle, and warehouse SKU
//warehouse SKU will be external ID for identifying which equipment records to update
within
Salesforce
for (Object eq : jsonResponse){
Map<String,Object> mapJson = (Map<String,Object>)eq;
Product2 myEq = new Product2();
myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');

```

```

myEq.Name = (String) mapJson.get('name');
myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
myEq.Cost__c = (Integer) mapJson.get('cost');
myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
myEq.ProductCode = (String) mapJson.get('_id');
warehouseEq.add(myEq);
}
if (warehouseEq.size() > 0){
upsert warehouseEq;
System.debug('Your equipment was synced with the warehouse one');
}
}
}
public static void execute (QueueableContext context){
runWarehouseEquipmentSync();
}
}
WarehouseCalloutServiceMock.apxc:
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
// implement http mock callout
global static HttpResponse respond(HttpRequest request) {
HttpResponse response = new HttpResponse();
response.setHeader('Content-Type', 'application/json');
response.setBody(['{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5
,"name":
"Gene
rator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"},"{"_id":"55d66226
726b611
100a
af742","replacement":true,"quantity":183,"name":"Cooling
Fan","maintenanceperiod":0,"lifespan":0,"cost":300,"sku":"100004"},"{"_id":"55d66226726b6
11100a
af743

```

```

    ,"replacement":true,"quantity":143,"name":"Fuse
    20A","maintenanceperiod":0,"lifespan":0,"cost":22,"sku":"100005"]]);
    response.setStatusCode(200);
    return response;
}
}

```

WarehouseCalloutServiceTest.apxc:

```

@IsTest
private class WarehouseCalloutServiceTest {
// implement your mock callout test here
@isTest
static void testWarehouseCallout() {
test.startTest();
test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
WarehouseCalloutService.execute(null);
test.stopTest();
List<Product2> product2List = new List<Product2>();
product2List = [SELECT ProductCode FROM Product2];
System.assertEquals(3, product2List.size());
System.assertEquals('55d66226726b611100aaf741', product2List.get(0).ProductCode);
System.assertEquals('55d66226726b611100aaf742', product2List.get(1).ProductCode);
System.assertEquals('55d66226726b611100aaf743', product2List.get(2).ProductCode);
}
}

```

Challenge-3

WarehouseSyncSchedule.apxc:

```

global with sharing class WarehouseSyncSchedule implements Schedulable{
global void execute(SchedulableContext ctx){
System.enqueueJob(new WarehouseCalloutService());
}
}

```

WarehouseSyncScheduleTest.apxc:

```

@isTest
public class WarehouseSyncScheduleTest {
@isTest static void WarehouseScheduleTest(){
String scheduleTime = '00 00 01 * * ?';
Test.startTest();
}
}

```

```

Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
String jobId=System.schedule('Warehouse Time To Schedule to Test', scheduleTime,
new
WarehouseSyncSchedule());
Test.stopTest();
//Contains schedule information for a scheduled job. CronTrigger is similar to a cron job
on
UNIX
systems.
// This object is available in API version 17.0 and later.
CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
System.assertEquals(jobID, a.Id,'Schedule ');
}
}

```

Challenge-4

MaintenanceRequestHelperTest.apxc:

```

@istest
public with sharing class MaintenanceRequestHelperTest {
private static final string STATUS_NEW = 'New';
private static final string WORKING = 'Working';
private static final string CLOSED = 'Closed';
private static final string REPAIR = 'Repair';
private static final string REQUEST_ORIGIN = 'Web';
private static final string REQUEST_TYPE = 'Routine Maintenance';
private static final string REQUEST_SUBJECT = 'Testing subject';
PRIVATE STATIC Vehicle__c createVehicle(){
Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');
return Vehicle;
}
PRIVATE STATIC Product2 createEq(){
product2 equipment = new product2(name = 'SuperEquipment',
lifespan_months__C = 10,
maintenance_cycle__C = 10,
replacement_part__c = true);
return equipment;
}
PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){

```

```

case cs = new case(Type=REPAIR,
Status=STATUS_NEW,
Origin=REQUEST_ORIGIN,
Subject=REQUEST_SUBJECT,
Equipment__c=equipmentId,
Vehicle__c=vehicleId);
return cs;
}
PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c =
equipmentId, Maintenance_Request__c = requestId);
return wp;
}
@istest
private static void testMaintenanceRequestPositive(){
Vehicle__c vehicle = createVehicle();
insert vehicle;
id vehicleId = vehicle.Id;
Product2 equipment = createEq();
insert equipment;
id equipmentId = equipment.Id;
case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
insert somethingToUpdate;
Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
insert workP;
test.startTest();
somethingToUpdate.status = CLOSED;
update somethingToUpdate;
test.stopTest();
Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c, Vehicle__c,
Date_Due__c
from case
where status =:STATUS_NEW];
Equipment_Maintenance_Item__c workPart = [select id

```

```

from Equipment_Maintenance_Item__c
where Maintenance_Request__c =:newReq.Id];
system.assert(workPart != null);
system.assert(newReq.Subject != null);
system.assertEquals(newReq.Type, REQUEST_TYPE);
SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);
SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);
SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
}

@istest
private static void testMaintenanceRequestNegative(){
Vehicle__C vehicle = createVehicle();
insert vehicle;
id vehicleId = vehicle.Id;
product2 equipment = createEq();
insert equipment;
id equipmentId = equipment.Id;
case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
insert emptyReq;
Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId, emptyReq.Id);
insert workP;
test.startTest();
emptyReq.Status = WORKING;
update emptyReq;
test.stopTest();
list<case> allRequest = [select id
from case];
Equipment_Maintenance_Item__c workPart = [select id
from Equipment_Maintenance_Item__c
where Maintenance_Request__c = :emptyReq.Id];
system.assert(workPart != null);
system.assert(allRequest.size() == 1);
}

@istest
private static void testMaintenanceRequestBulk(){
list<Vehicle__C> vehicleList = new list<Vehicle__C>();
list<Product2> equipmentList = new list<Product2>();

```

```

list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
list<case> requestList = new list<case>();
list<id> oldRequestIds = new list<id>();
for(integer i = 0; i < 300; i++){
vehicleList.add(createVehicle());
equipmentList.add(createEq());
}
insert vehicleList;
insert equipmentList;
for(integer i = 0; i < 300; i++){
requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
}
insert requestList;
for(integer i = 0; i < 300; i++){
workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
}
insert workPartList;
test.startTest();
for(case req : requestList){
req.Status = CLOSED;
oldRequestIds.add(req.Id);
}
update requestList;
test.stopTest();
list<case> allRequests = [select id
from case
where status =: STATUS_NEW];
list<Equipment_Maintenance_Item__c> workParts = [select id
from Equipment_Maintenance_Item__c
where Maintenance_Request__c in: oldRequestIds];
system.assert(allRequests.size() == 300);
}
}
MaintenanceRequestHelper.apxc:
public with sharing class MaintenanceRequestHelper {

```

```

public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
        if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
            if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                validIds.add(c.Id);
            }
        }
    }
    if (!validIds.isEmpty()){
        List<Case> newCases = new List<Case>();
        Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c,
Equipment__r.Maintenance_Cycle__c,(SELECT Id,Equipment__c,Quantity__c FROM
Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
        Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
        AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM
Equipment_Maintenance_Item__c
WHERE
Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];
        for (AggregateResult ar : results){
            maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));
        }
        for(Case cc : closedCasesM.values()){
            Case nc = new Case (
                ParentId = cc.Id,
                Status = 'New',
                Subject = 'Routine Maintenance',
                Type = 'Routine Maintenance',
                Vehicle__c = cc.Vehicle__c,
                Equipment__c =cc.Equipment__c,
                Origin = 'Web',
                Date_Reported__c = Date.Today()
            );

```



```

If (maintenanceCycles.containsKey(cc.Id)){
nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
}
newCases.add(nc);
}
insert newCases;
List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
Equipment_Maintenance_Item__c wpClone = wp.clone();
wpClone.Maintenance_Request__c = nc.Id;
ClonedWPs.add(wpClone);
}
}
insert ClonedWPs;
}
}
}

```

Challenge-5

WarehouseCalloutService.apxc:

```

public with sharing class WarehouseCalloutService implements Queueable {
private static final String WAREHOUSE_URL = 'https://thsuperbadge
apex.herokuapp.com/equipment';
//class that makes a REST callout to an external warehouse system to get a list of
equipment
that
needs to be updated.
//The callout's JSON response returns the equipment records that you upsert in
Salesforce.
@future(callout=true)
public static void runWarehouseEquipmentSync(){
Http http = new Http();
HttpRequest request = new HttpRequest();
request.setEndpoint(WAREHOUSE_URL);
request.setMethod('GET');

```

```

HttpResponse response = http.send(request);
List<Product2> warehouseEq = new List<Product2>();
if (response.getStatusCode() == 200){
List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
System.debug(response.getBody());
//class maps the following fields: replacement part (always true), cost, current inventory,
lifespan, maintenance cycle, and warehouse SKU
//warehouse SKU will be external ID for identifying which equipment records to update
within
Salesforce
for (Object eq : jsonResponse){
Map<String,Object> mapJson = (Map<String,Object>)eq;
Product2 myEq = new Product2();
myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
myEq.Name = (String) mapJson.get('name');
myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
myEq.Cost__c = (Integer) mapJson.get('cost');
myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
myEq.ProductCode = (String) mapJson.get('_id');
warehouseEq.add(myEq);
}
if (warehouseEq.size() > 0){
upsert warehouseEq;
System.debug('Your equipment was synced with the warehouse one');
}
}
}

public static void execute (QueueableContext context){
runWarehouseEquipmentSync();
}
}

WarehouseCalloutServiceMock.apxc:
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {

```

```
// implement http mock callout
global static HttpResponse respond(HttpRequest request) {
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
    response.setBody('[{ "_id": "55d66226726b611100aaf741", "replacement": false, "quantity": 5, "name": "Generator 1000 kW", "maintenanceperiod": 365, "lifespan": 120, "cost": 5000, "sku": "100003"}, { "_id": "55d66226726b611100aaf742", "replacement": true, "quantity": 183, "name": "Cooling Fan", "maintenanceperiod": 0, "lifespan": 0, "cost": 300, "sku": "100004"}, { "_id": "55d66226726b611100aaf743", "replacement": true, "quantity": 143, "name": "Fuse 20A", "maintenanceperiod": 0, "lifespan": 0, "cost": 22, "sku": "100005"} ]');
    response.setStatusCode(200);
    return response;
}
}
```

WarehouseCalloutServiceTest.apxc:

```
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request) {
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody('[{ "_id": "55d66226726b611100aaf741", "replacement": false, "quantity": 5, "name": "Generator 1000 kW", "maintenanceperiod": 365, "lifespan": 120, "cost": 5000, "sku": "100003"}, { "_id": "55d66226726b611100aaf742", "replacement": true, "quantity": 183, "name": "Cooling Fan", "maintenanceperiod": 0, "lifespan": 0, "cost": 300, "sku": "100004"}, { "_id": "55d66226726b611100aaf743", "replacement": true, "quantity": 143, "name": "Fuse 20A", "maintenanceperiod": 0, "lifespan": 0, "cost": 22, "sku": "100005"} ]');
        response.setStatusCode(200);
        return response;
    }
}
```

11100a

af743

```
","replacement":true,"quantity":143,"name":"Fuse
20A","maintenanceperiod":0,"lifespan":0,"cost":22,"sku":"100005"]]);
response.setStatusCode(200);
return response;
}
}
```

Challenge-6

WarehouseSyncSchedule.apxc:

```
global with sharing class WarehouseSyncSchedule implements Schedulable{
global void execute(SchedulableContext ctx){
System.enqueueJob(new WarehouseCalloutService());
}
}
```

WarehouseSyncScheduleTest.apxc:

```
@isTest
public class WarehouseSyncScheduleTest {
@isTest static void WarehousescheduleTest(){
String scheduleTime = '00 00 01 * * ?';
Test.startTest();
Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
String jobId=System.schedule('Warehouse Time To Schedule to Test', scheduleTime,
new
WarehouseSyncSchedule());
Test.stopTest();
//Contains schedule information for a scheduled job. CronTrigger is similar to a cron job
on
UNIX
systems.
// This object is available in API version 17.0 and later.
CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
System.assertEquals(jobID, a.Id,'Schedule ');
}
}
```