

APEX TRIGGERS

GET STARTED WITH APEX TRIGGERS

1. AccountAddressTrigger.apxt

```
trigger AccountAddressTrigger on Account (before insert, before update) {

    for(Account a: Trigger.New){

        if(a.Match_Billing_Address__c == true && a.BillingPostalCode!= null){

            a.ShippingPostalCode=a.BillingPostalCode;

        }

    }

}
```

BULK APEX TRIGGERS

1. ClosedOpportunityTrigger.apxt

```
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {

    List<Task> taskList = new List<Task>();

    for(Opportunity opp : Trigger.new) {

        if(Trigger.isInsert) {
            if(Opp.StageName == 'Closed Won') {
                taskList.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));
            }
        }

        if(Trigger.isUpdate) {
            if(Opp.StageName == 'Closed Won'
            && Opp.StageName != Trigger.oldMap.get(opp.Id).StageName) {
                taskList.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));
            }
        }
    }

}
```

```

    }

    if(taskList.size()>0) {
        insert taskList;
    }
}

```

APEX TESTING

GET STARTED WITH APEX UNIT TEST

1. VerifyDate.apxc

```

public class VerifyDate {

    //method to handle potential checks against two dates
    public static Date CheckDates(Date date1, Date date2) {
        //if date2 is within the next 30 days of date1, use date2. Otherwise use the end of
the month
        if(DateWithin30Days(date1,date2)) {
            return date2;
        } else {
            return SetEndOfMonthDate(date1);
        }
    }

    //method to check if date2 is within the next 30 days of date1
    private static Boolean DateWithin30Days(Date date1, Date date2) {
        //check for date2 being in the past
        if( date2 < date1) { return false; }

        //check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1
        if( date2 >= date30Days ) { return false; }
        else { return true; }
    }

    //method to return the end of the month of a given date
    private static Date SetEndOfMonthDate(Date date1) {
        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
        Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
        return lastDay;
    }
}

```

```
}
```

```
}
```

2. TestVerifyDate.apxc

```
@isTest
```

```
public class TestVerifyDate
```

```
{
```

```
    static testMethod void testMethod1()
```

```
    {
```

```
        Date d = VerifyDate.CheckDates(System.today(),System.today()+1);
```

```
        Date d1 = VerifyDate.CheckDates(System.today(),System.today()+60);
```

```
    }
```

```
}
```

TEST APEX TRIGGERS

1. RestrictContactByName.apxt

```
trigger RestrictContactByName on Contact (before insert, before update) {
```

```
    //check contacts prior to insert or update for invalid data
```

```
    For (Contact c : Trigger.New) {
```

```
        if(c.LastName == 'INVALIDNAME') { //invalidname is invalid
```

```
            c.AddError('The Last Name "'+c.LastName+'" is not allowed for DML');
```

```
        }
```

```
    }
```

2. TestRestrictContactByName.apxt

```

@isTest
private class TestRestrictContactByName {

    static testMethod void metodoTest()
    {

        List<Contact> listContact= new List<Contact>();
        Contact c1 = new Contact(FirstName='Francesco', LastName='Riggio' ,
email='Test@test.com');
        Contact c2 = new Contact(FirstName='Francesco1', LastName =
'INVALIDNAME',email='Test@test.com');
        listContact.add(c1);
        listContact.add(c2);

        Test.startTest();
        try
        {
            insert listContact;
        }
        catch(Exception ee)
        {
        }

        Test.stopTest();

    }

}
}

```

CREATE TEST DATA FOR APEX TESTS

1. RandomContactFactory.apxc

```

public class RandomContactFactory {
    public static List<Contact> generateRandomContacts(Integer numContactsToGenerate, String
FName) {
        List<Contact> contactList = new List<Contact>();

        for(Integer i=0;i<numContactsToGenerate;i++) {
            Contact c = new Contact(FirstName=FName + ' ' + i, LastName = 'Contact '+i);
            contactList.add(c);
            System.debug(c);
        }
    }
}

```

```

    }
    //insert contactList;
    System.debug(contactList.size());
    return contactList;
}
}

```

ASYNCHRONOUS APEX

USE FUTURE METHODS

1. AccountProcessor.apxc

```

public class AccountProcessor {

    @future

    public static void countContacts(List<Id> accountIds){

        List<Account> accountsToUpdate = new List<Account>();

        List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from Account Where Id in :accountIds];

        For(Account acc:accounts){

            List<Contact> contactList = acc.Contacts;

            acc.Number_Of_Contacts__c = contactList.size();

            accountsToUpdate.add(acc);

        }
    }
}

```

```
        update accountsToUpdate;

    }

}
```

2. AccountProcessorTest.apxc

@IsTest

```
private class AccountProcessorTest {
```

```
    @IsTest
```

```
    private static void testCountContacts(){
```

```
        Account newAccount = new Account(Name='Test Account');
```

```
        insert newAccount;
```

```
        Contact c = new Contact();
```

```
        c.FirstName = 'Bob';
```

```
        c.LastName = 'Willie';
```

```
        c.AccountId = newAccount.Id;
```

```
        Contact c2 = new Contact();
```

```
        c2.FirstName = 'Tom';
```

```
        c2.LastName = 'Cruise';
```

```
        c2.AccountId = newAccount.Id;
```

```

        List<Id> accountIds = new List<Id>();

        accountIds.add(newAccount.Id);

        Test.startTest();

        AccountProcessor.countContacts(accountIds);

        Test.stopTest();

    }

}

```

USE BATCH APEX

1. LeadProcessor.apxc

```

global class LeadProcessor implements Database.Batchable<sObject>, Database.Stateful {

    //Retrieving all Leads records (First step in Batch)
    global Database.QueryLocator start(Database.BatchableContext bc) {
        return Database.getQueryLocator([SELECT ID, LeadSource FROM Lead]);
    }

    global void execute(Database.BatchableContext bc, List<Lead> scope) {
        for (Lead lead : scope) {
            lead.LeadSource = 'Dreamforce';
            recordsProcessed = recordsProcessed + 1;
            System.debug(lead.LeadSource);
        }
        update scope;
    }
}

```

```

    global void finish(Database.BatchableContext bc){
        System.debug(recordsProcessed + ' records processed. Shazam!');
    }
}

```

2. LeadProcessorTest.apxc

```

@isTest
private class LeadProcessorTest {

    @TestSetup
    static void setup(){
        List<Lead> leads = new List<Lead>();

        for (Integer i = 0; i < 200; i++) {
            leads.add(new Lead(LastName='Lead ' + i, Company='Company Number ' + i,
                Status='Open - Not Contacted'));
        }

        insert leads;
    }

    static testMethod void test() {

        Test.startTest();
        LeadProcessor lp = new LeadProcessor();
        Id batchId = Database.executeBatch(lp);
        Test.stopTest();

        System.assertEquals(200, [select count() from lead where LeadSource = 'Dreamforce']);
    }
}

```

CONTROL PROCESSES WITH QUEUEABLE APEX

1. AddPrimaryContact.apxc

```

public class AddPrimaryContact implements Queueable
{
    private Contact c;
}

```



```

private String state;
public AddPrimaryContact(Contact c, String state)
{
    this.c = c;
    this.state = state;
}
public void execute(QueueableContext context)
{
    List<Account> ListAccount = [SELECT ID, Name ,(Select id,FirstName,LastName from
contacts ) FROM ACCOUNT WHERE BillingState = :state LIMIT 200];
    List<Contact> lstContact = new List<Contact>();
    for (Account acc:ListAccount)
    {
        Contact cont = c.clone(false,false,false,false);
        cont.AccountId = acc.id;
        lstContact.add( cont );
    }

    if(lstContact.size() >0 )
    {
        insert lstContact;
    }

}
}

```

2. AddPrimaryContactTest.apxc

```

@isTest
public class AddPrimaryContactTest
{
    @isTest static void TestList()
    {
        List<Account> Teste = new List <Account>();
        for(Integer i=0;i<50;i++)
        {
            Teste.add(new Account(BillingState = 'CA', name = 'Test'+i));
        }
        for(Integer j=0;j<50;j++)
        {
            Teste.add(new Account(BillingState = 'NY', name = 'Test'+j));
        }
    }
}

```

```

insert Teste;

Contact co = new Contact();
co.FirstName='demo';
co.LastName ='demo';
insert co;
String state = 'CA';

AddPrimaryContact apc = new AddPrimaryContact(co, state);
Test.startTest();
    System.enqueueJob(apc);
Test.stopTest();
}
}

```

SCHEDULE JOBS USING APEX SCHEDULER

1. DailyLeadProcessor.apxc

```

public class DailyLeadProcessor implements Schedulable {
    Public void execute(SchedulableContext SC){
        List<Lead> LeadObj=[SELECT Id from Lead where LeadSource=null limit 200];
        for(Lead l:LeadObj){
            l.LeadSource='Dreamforce';
            update l;
        }
    }
}

```

2. DailyLeadProcessorTest.apxc

```

@isTest
private class DailyLeadProcessorTest {
    static testMethod void testDailyLeadProcessor() {
        String CRON_EXP = '0 0 1 * * ?';
        List<Lead> IList = new List<Lead>();
        for (Integer i = 0; i < 200; i++) {
            IList.add(new Lead(LastName='Dreamforce'+i, Company='Test1 Inc.',
Status='Open - Not Contacted'));
        }
        insert IList;

        Test.startTest();
    }
}

```

```

        String jobId = System.schedule('DailyLeadProcessor', CRON_EXP, new
DailyLeadProcessor());
    }
}

```

APEX INTEGRATION SERVICES

APEX REST CALLOUTS

1. AnimalLocator.apxc

```

public class AnimalLocator{
    public static String getAnimalNameById(Integer x){
        Http http = new Http();
        HttpRequest req = new HttpRequest();
        req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + x);
        req.setMethod('GET');
        Map<String, Object> animal= new Map<String, Object>();
        HttpResponse res = http.send(req);
        if (res.getStatusCode() == 200) {
            Map<String, Object> results = (Map<String, Object>)JSON.deserializeUntyped(res.getBody());
            animal = (Map<String, Object>) results.get('animal');
        }
        return (String)animal.get('name');
    }
}

```

2. AnimalLocatorMock.apxc

```

@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
    // Implement this interface method
    global HTTPResponse respond(HTTPRequest request) {
        // Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody('{ "animals": ["majestic badger", "fluffy bunny", "scary bear", "chicken",
"mighty moose"]}');
        response.getStatusCode(200);
        return response;
    }
}

```

3. AnimalLocatorTest.apxc

```
@isTest
private class AnimalLocatorTest{
    @isTest static void AnimalLocatorMock1() {
        Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
        string result = AnimalLocator.getAnimalNameById(3);
        String expectedResult = 'chicken';
        System.assertEquals(result,expectedResult );
    }
}
```

APEX SOAP CALLOUTS

1. ParkService.apxc

```
public class ParkService {
    public class byCountryResponse {
        public String[] return_x;
        private String[] return_x_type_info = new String[]{ 'return','http://parks.services/',null,'0','-1','false'};
        private String[] apex_schema_type_info = new String[]{ 'http://parks.services/', 'false', 'false'};
        private String[] field_order_type_info = new String[]{ 'return_x'};
    }
    public class byCountry {
        public String arg0;
        private String[] arg0_type_info = new String[]{ 'arg0','http://parks.services/',null,'0','1','false'};
        private String[] apex_schema_type_info = new String[]{ 'http://parks.services/', 'false', 'false'};
        private String[] field_order_type_info = new String[]{ 'arg0'};
    }
    public class ParksImplPort {
        public String endpoint_x = 'https://th-apex-soap-service.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public Map<String,String> outputHttpHeaders_x;
        public String clientCertName_x;
        public String clientCert_x;
        public String clientCertPasswd_x;
        public Integer timeout_x;
        private String[] ns_map_type_info = new String[]{ 'http://parks.services/', 'ParkService'};
        public String[] byCountry(String arg0) {
            ParkService.byCountry request_x = new ParkService.byCountry();
            request_x.arg0 = arg0;
            ParkService.byCountryResponse response_x;
```

```

        Map<String, ParkService.byCountryResponse> response_map_x = new Map<String,
ParkService.byCountryResponse>();
        response_map_x.put('response_x', response_x);
        WebServiceCallout.invoke(
            this,
            request_x,
            response_map_x,
            new String[]{endpoint_x,
                "",
                'http://parks.services/',
                'byCountry',
                'http://parks.services/',
                'byCountryResponse',
                'ParkService.byCountryResponse'}
        );
        response_x = response_map_x.get('response_x');
        return response_x.return_x;
    }
}
}

```

2. ParkServiceMock.apxc

@isTest

```

global class ParkServiceMock implements WebServiceMock {
    global void doInvoke(
        Object stub,
        Object request,
        Map<String, Object> response,
        String endpoint,
        String soapAction,
        String requestName,
        String responseNS,
        String responseName,
        String responseType) {
        // start - specify the response you want to send
        ParkService.byCountryResponse response_x = new ParkService.byCountryResponse();
        response_x.return_x = new List<String>{'Yellowstone', 'Mackinac National Park', 'Yosemite'};
        // end
        response.put('response_x', response_x);
    }
}

```

3. ParkLocator.apxc

```
public class ParkLocator {  
  
    public static string[] country(string theCountry) {  
  
        ParkService.ParksImplPort parkSvc = new ParkService.ParksImplPort(); // remove space  
  
        return parkSvc.byCountry(theCountry);  
  
    }  
  
}
```

4. ParkLocatorTest.apxc

```
@isTest  
  
private class ParkLocatorTest {  
  
    @isTest static void testCallout() {  
  
        Test.setMock(WebServiceMock.class, new ParkServiceMock ());  
  
        String country = 'United States';  
  
        List<String> result = ParkLocator.country(country);  
  
        List<String> parks = new List<String>{'Yellowstone', 'Mackinac National Park', 'Yosemite'};  
  
        System.assertEquals(parks, result);  
  
    }  
  
}
```

APEX WEB SERVICES

1. AccountManager.apxc

```
@RestResource(urlMapping='/Accounts/*/contacts')  
  
global class AccountManager {
```

```
@HttpGet
```

```
global static Account getAccount() {
```

```
    RestRequest req = RestContext.request;
```

```
    String accId = req.requestURI.substringBetween('Accounts/', '/contacts');
```

```
    Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
```

```
        FROM Account WHERE Id = :accId];
```

```
    return acc;
```

```
}
```

```
}
```

2. AccountManagerTest.apxc

```
@isTest
```

```
private class AccountManagerTest {
```

```
    private static testMethod void getAccountTest1() {
```

```
        Id recordId = createTestRecord();
```

```
        // Set up a test request
```

```
        RestRequest request = new RestRequest();
```

```
        request.requestUri = 'https://na1.salesforce.com/services/apexrest/Accounts/'+ recordId  
+ '/contacts' ;
```

```
        request.httpMethod = 'GET';
```

```
        RestContext.request = request;
```

```
        // Call the method to test
```

```
        Account thisAccount = AccountManager.getAccount();
```

```
        // Verify results
```

```
        System.assert(thisAccount != null);
```

```
        System.assertEquals('Test record', thisAccount.Name);
```

```
}
```

```
// Helper method
```

```
    static Id createTestRecord() {
```

```
        // Create test record
```

```

Account TestAcc = new Account(
    Name='Test record');
insert TestAcc;
Contact TestCon= new Contact(
    LastName='Test',
    AccountId = TestAcc.id);
return TestAcc.Id;
    }
}

```

APEX SPECIALIST SUPERBADGE

AUTOMATE RECORD CREATION

1. MaintenanceRequest.apxt

```

trigger MaintenanceRequest on Case (before update, after update) {

    if(Trigger.isUpdate && Trigger.isAfter){

        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);

    }

}

```

2. MaintenanceRequestHelper.apxc

```

public with sharing class MaintenanceRequestHelper {
    public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){

```



```

        if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
            if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                validIds.add(c.Id);
            }
        }
    }

    if (!validIds.isEmpty()){
        List<Case> newCases = new List<Case>();
        Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT Id,Equipment__c,Quantity__c
FROM Equipment_Maintenance_Items__r)
                                FROM Case WHERE Id IN :validIds]);
        Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
        AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM Equipment_Maintenance_Item__c WHERE
Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];

        for (AggregateResult ar : results){
            maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));
        }

        for(Case cc : closedCasesM.values()){
            Case nc = new Case (
                ParentId = cc.Id,
                Status = 'New',
                Subject = 'Routine Maintenance',
                Type = 'Routine Maintenance',
                Vehicle__c = cc.Vehicle__c,
                Equipment__c =cc.Equipment__c,
                Origin = 'Web',
                Date_Reported__c = Date.Today()

            );

            If (maintenanceCycles.containsKey(cc.Id)){
                nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
            }

            newCases.add(nc);
        }
    }

```

```

        insert newCases;

        List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
        for (Case nc : newCases){
            for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
                Equipment_Maintenance_Item__c wpClone = wp.clone();
                wpClone.Maintenance_Request__c = nc.Id;
                ClonedWPs.add(wpClone);

            }
        }
        insert ClonedWPs;
    }
}
}

```

SYNCHRONIZATION SALESFORCE DATA WITH AN EXTERNAL SYSTEM

1. WarehouseCalloutService.apxc

```

public with sharing class WarehouseCalloutService {

    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

    // @future(callout=true)
    public static void runWarehouseEquipmentSync(){

        Http http = new Http();
        HttpRequest request = new HttpRequest();

        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);

        List<Product2> warehouseEq = new List<Product2>();
    }
}

```

```

if (response.getStatusCode() == 200){
    List<Object> jsonResponse = (List<Object>)JSON.deserializeUntyped(response.getBody());
    System.debug(response.getBody());

    for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost__c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
    }

    if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
    }
}
}
}

```

SCHEDULE SYNCHRONIZATION USING APEX CODE

1. WarehouseSyncSchedule.apxc

```

global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

```

TEST AUTOMATIC LOGIC

1. MaintenanceRequestHelperTest.apxc

@istest

```

public with sharing class MaintenanceRequestHelperTest {

    private static final string STATUS_NEW = 'New';
    private static final string WORKING = 'Working';
    private static final string CLOSED = 'Closed';
    private static final string REPAIR = 'Repair';
    private static final string REQUEST_ORIGIN = 'Web';
    private static final string REQUEST_TYPE = 'Routine Maintenance';
    private static final string REQUEST_SUBJECT = 'Testing subject';

    PRIVATE STATIC Vehicle__c createVehicle(){
        Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');
        return Vehicle;
    }

    PRIVATE STATIC Product2 createEq(){
        product2 equipment = new product2(name = 'SuperEquipment',
                                           lifespan_months__C = 10,
                                           maintenance_cycle__C = 10,
                                           replacement_part__c = true);

        return equipment;
    }

    PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
        case cs = new case(Type=REPAIR,
                           Status=STATUS_NEW,
                           Origin=REQUEST_ORIGIN,
                           Subject=REQUEST_SUBJECT,
                           Equipment__c=equipmentId,
                           Vehicle__c=vehicleId);

        return cs;
    }

    PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
        Equipment_Maintenance_Item__c wp = new Equipment_Maintenance_Item__c(Equipment__c
= equipmentId,

                                           Maintenance_Request__c = requestId);

        return wp;
    }
}

```

@istest

```

private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;

    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;

    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;

    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();

    Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c, Vehicle__c,
Date_Due__c
                    from case
                    where status =:STATUS_NEW];

    Equipment_Maintenance_Item__c workPart = [select id
                                                from Equipment_Maintenance_Item__c
                                                where Maintenance_Request__c =:newReq.Id];

    system.assert(workPart != null);
    system.assert(newReq.Subject != null);
    system.assertEquals(newReq.Type, REQUEST_TYPE);
    SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);
    SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);
    SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
}

@istest
private static void testMaintenanceRequestNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

```

```

product2 equipment = createEq();
insert equipment;
id equipmentId = equipment.Id;

case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
insert emptyReq;

Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId, emptyReq.Id);
insert workP;

test.startTest();
emptyReq.Status = WORKING;
update emptyReq;
test.stopTest();

list<case> allRequest = [select id
                        from case];

Equipment_Maintenance_Item__c workPart = [select id
                                           from Equipment_Maintenance_Item__c
                                           where Maintenance_Request__c = :emptyReq.Id];

system.assert(workPart != null);
system.assert(allRequest.size() == 1);
}

@istest
private static void testMaintenanceRequestBulk(){
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();

    for(integer i = 0; i < 300; i++){
        vehicleList.add(createVehicle());
        equipmentList.add(createEq());
    }
    insert vehicleList;
    insert equipmentList;

```

```

for(integer i = 0; i < 300; i++){
    requestList.add(createMaintenanceRequest(vehicleList.get(i).id, equipmentList.get(i).id));
}
insert requestList;

for(integer i = 0; i < 300; i++){
    workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
}
insert workPartList;

test.startTest();
for(case req : requestList){
    req.Status = CLOSED;
    oldRequestIds.add(req.Id);
}
update requestList;
test.stopTest();

list<case> allRequests = [select id
                        from case
                        where status =: STATUS_NEW];

list<Equipment_Maintenance_Item__c> workParts = [select id
                                                from Equipment_Maintenance_Item__c
                                                where Maintenance_Request__c in: oldRequestIds];

system.assert(allRequests.size() == 300);
}
}

```

2. MaintenanceRequestHelper.apxc

```

public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }
    }
}

```

```

    }
    }
}

if (!validIds.isEmpty()){
    List<Case> newCases = new List<Case>();
    Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT Id,Equipment__c,Quantity__c
FROM Equipment_Maintenance_Items__r)
                                FROM Case WHERE Id IN :validIds]);
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
    AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM Equipment_Maintenance_Item__c WHERE
Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];

    for (AggregateResult ar : results){
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));
    }

    for(Case cc : closedCasesM.values()){
        Case nc = new Case (
            ParentId = cc.Id,
            Status = 'New',
            Subject = 'Routine Maintenance',
            Type = 'Routine Maintenance',
            Vehicle__c = cc.Vehicle__c,
            Equipment__c =cc.Equipment__c,
            Origin = 'Web',
            Date_Reported__c = Date.Today()

        );

        If (maintenanceCycles.containsKey(cc.Id)){
            nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
        }

        newCases.add(nc);
    }

    insert newCases;

```



```

        List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
        for (Case nc : newCases){
            for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
                Equipment_Maintenance_Item__c wpClone = wp.clone();
                wpClone.Maintenance_Request__c = nc.Id;
                ClonedWPs.add(wpClone);

            }
        }
        insert ClonedWPs;
    }
}
}

```

3. MaintenanceRequest.apxt

```

trigger MaintenanceRequest on Case (before update, after update) {

    if(Trigger.isUpdate && Trigger.isAfter){

        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);

    }

}

```

TEST CALLOUT LOGIC

1. WarehouseCalloutService.apxc

```

public with sharing class WarehouseCalloutService {

    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

    // @future(callout=true)
    public static void runWarehouseEquipmentSync(){

        Http http = new Http();
        HttpRequest request = new HttpRequest();
    }
}

```

```

request.setEndpoint(WAREHOUSE_URL);
request.setMethod('GET');
HttpResponse response = http.send(request);

List<Product2> warehouseEq = new List<Product2>();

if (response.getStatusCode() == 200){
    List<Object> jsonResponse = (List<Object>)JSON.deserializeUntyped(response.getBody());
    System.debug(response.getBody());

    for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost__c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
    }

    if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
    }

}
}
}

```

2. WarehouseCalloutServiceTest.apxc

@isTest

```

private class WarehouseCalloutServiceTest {
    @isTest
    static void testWareHouseCallout(){
        Test.startTest();
        // implement mock callout test here
    }
}

```

```

        Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.runWarehouseEquipmentSync();
        Test.stopTest();
        System.assertEquals(1, [SELECT count() FROM Product2]);
    }
}

```

3. WarehouseCalloutServiceMock.apxc

```

@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request){

        System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
        System.assertEquals('GET', request.getMethod());

        // Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');

response.setBody('{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5,"name":"G
enerator 1000 kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}');
        response.setStatusCode(200);
        return response;
    }
}

```

TEST SCHEDULING LOGIC

1. WarehouseSyncSchedule.apxc

```

global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

```

2. WarehouseSyncScheduleTest.apxc

```

@isTest
public class WarehouseSyncScheduleTest {

    @isTest static void WarehousescheduleTest(){
        String scheduleTime = '00 00 01 * * ?';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String jobId=System.schedule('Warehouse Time To Schedule to Test', scheduleTime, new
WarehouseSyncSchedule());
        Test.stopTest();
        //Contains schedule information for a scheduled job. CronTrigger is similar to a cron job on
UNIX systems.
        // This object is available in API version 17.0 and later.
        CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
        System.assertEquals(jobID, a.Id,'Schedule ');

    }
}

```