

Apex Integration Services

AccountManager.apxc;

@RestResource(urlMapping='/Accounts/*/contacts')

global class AccountManager {

 @HttpGet

 global static Account getAccount() {

 RestRequest req = RestContext.request;

 String accId = req.requestURI.substringBetween('Accounts/', '/contacts');

 Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)

 FROM Account WHERE Id = :accId];

 return acc;

 }

}

AccountManagerTest.apxc.

@isTest

private class AccountManagerTest {

 private static testMethod void getAccountTest1() {

 Id recordId = createTestRecord();

 // Set up a test request

 RestRequest request = new RestRequest();

 request.requestUri =

'https://na1.salesforce.com/services/apexrest/Accounts/'+recordId+'/contacts';

 request.httpMethod = 'GET';

 RestContext.request = request;

 // Call the method to test

 Account thisAccount = AccountManager.getAccount();

 // Verify results

 System.assert(thisAccount != null);

 System.assertEquals('Test record', thisAccount.Name);

 }

```

// Helper method
static Id createTestRecord() {
    // Create test record
    Account TestAcc = new Account(
        Name='Test record');
    insert TestAcc;
    Contact TestCon= new Contact(
        LastName='Test',
        AccountId = TestAcc.id);
    return TestAcc.Id
;
}
}

```

AnimalLocator.apxc.

```

public class AnimalLocator {
    public class cls_animal {
        public Integer id;

        public String name;

        public String eats;

        public String says;
    }
    public class JSONOutput{
        public cls_animal animal;

        //public JSONOutput parse(String json){
        //return (JSONOutput) System.JSON.deserialize(json, JSONOutput.class);
        //}
    }

    public static String getAnimalNameById (Integer id) {
        Http http = new Http();
        HttpRequest request = new HttpRequest();
        request.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + id);
    }
}

```

```

        //request.setHeader('id', String.valueOf(id)); -- cannot be used in this challenge :)
        request.setMethod('GET');
        HttpResponse response = http.send(request);
        system.debug('response: ' + response.getBody());
        //Map<String,Object> map_results = (Map<String,Object>)
JSON.deserializeUntyped(response.getBody());
        jsonOutput results = (jsonOutput) JSON.deserialize(response.getBody(),
jsonOutput.class);
        //Object results = (Object) map_results.get('animal');
        system.debug('results= ' + results.animal.name);
        return(results.animal.name);
    }

}

```

AnimalLocatorMock.apxc

@IsTest

global class AnimalLocatorMock implements HttpCalloutMock {

```

    global HTTPResponse respond(HTTPRequest request) {
        Httpresponse response = new Httpresponse();
        response.setStatusCode(200);
        //-- directly output the JSON, instead of creating a logic
        //response.setHeader('key, value)
        //Integer id = Integer.valueOf(request.getHeader('id'));
        //Integer id = 1;
        //List<String> lst_body = new List<String> {'majestic badger', 'fluffy bunny'};
        //system.debug('animal return value: ' + lst_body[id]);
        response.setBody('{"animal":{"id":1,"name":"chicken","eats":"chicken
food","says":"cluck cluck"}}');
        return response;
    }

}

```

AnimalLocatorTest.apxc.

```

@IsTest
public class AnimalLocatorTest {
    @isTest
    public static void testAnimalLocator() {
        Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
        //HttpResponse response = AnimalLocator.getAnimalNameById(1);
        String s = AnimalLocator.getAnimalNameById(1);
        system.debug('string returned: ' + s);
    }
}

```

ParkLocatorTest.apxc.

```

@isTest
private class ParkLocatorTest {
    @isTest static void testCallout() {
        Test.setMock(WebServiceMock.class, new ParkServiceMock ());
        String country = 'United States';
        List<String> result = ParkLocator.country(country);
        List<String> parks = new List<String>{'Yellowstone', 'Mackinac National Park',
'Yosemite'};
        System.assertEquals(parks, result);
    }
}

```

ParkService.apxc.

//Generated by wsdl2apex

```

public class ParkService {
    public class byCountryResponse {
        public String[] return_x;
        private String[] return_x_type_info = new
String[]{'return','http://parks.services/',null,'0','-1','false'};
        private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
        private String[] field_order_type_info = new String[]{'return_x'};
    }
}

```

```

    }
    public class byCountry {
        public String arg0;
        private String[] arg0_type_info = new
String[]{'arg0','http://parks.services/',null,'0','1','false'};
        private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
        private String[] field_order_type_info = new String[]{'arg0'};
    }
    public class ParksImplPort {
        public String endpoint_x = 'https://th-apex-soap-
service.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public Map<String,String> outputHttpHeaders_x;
        public String clientCertName_x;
        public String clientCert_x;
        public String clientCertPasswd_x;
        public Integer timeout_x;
        private String[] ns_map_type_info = new String[]{'http://parks.services/',
'ParkService'};
        public String[] byCountry(String arg0) {
            ParkService.byCountry request_x = new ParkService.byCountry();
            request_x.arg0 = arg0;
            ParkService.byCountryResponse response_x;
            Map<String, ParkService.byCountryResponse> response_map_x = new
Map<String, ParkService.byCountryResponse>();
            response_map_x.put('response_x', response_x);
            WebServiceCallout.invoke(
                this,
                request_x,
                response_map_x,
                new String[]{endpoint_x,
                ",
                'http://parks.services/',
                'byCountry',
                'http://parks.services/',
                'byCountryResponse',

```

```

        'ParkService.byCountryResponse'}
    );
    response_x = response_map_x.get('response_x');
    return response_x.return_x;
}
}
}

```

ParkServiceMock.apxc.

```

@isTest
global class ParkServiceMock implements WebServiceMock {
    global void doInvoke(
        Object stub,
        Object request,
        Map<String, Object> response,
        String endpoint,
        String soapAction,
        String requestName,
        String responseNS,
        String responseName,
        String responseType) {
        // start - specify the response you want to send
        ParkService.byCountryResponse response_x = new
ParkService.byCountryResponse();
        response_x.return_x = new List<String>{'Yellowstone', 'Mackinac National Park',
'Yosemite'};
        // end
        response.put('response_x', response_x);
    }
}

```

Apex Testing

RandomContactFactory.apxc.

```

public class RandomContactFactory {

    public static List<Contact> generateRandomContacts(Integer numcnt, string

```

```

lastname){
    List<Contact> contacts = new List<Contact>();
    for(Integer i=0;i<numcnt;i++){
        Contact cnt = new Contact(FirstName = 'Test '+i, LastName = lastname);
        contacts.add(cnt);
    }
    return contacts;
}
}

```

RestrictContactByName.apxt

```

trigger RestrictContactByName on Contact (before insert, before update) {

    //check contacts prior to insert or update for invalid data
    For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') {      //invalidname is invalid
            c.AddError('The Last Name "' + c.LastName + '" is not allowed for
DML');
        }

    }

}
}

```

TestRestrictContactByName.apxc.

```

@isTest
public class TestRestrictContactByName {

    @isTest static void Test_insertupdateContact(){
        Contact cnt = new Contact();
        cnt.LastName = 'INVALIDNAME';

        Test.startTest();
        Database.SaveResult result = Database.insert(cnt, false);
        Test.stopTest();
    }
}

```

```

        System.assert(!result.isSuccess());
        System.assert(result.getErrors().size() > 0);
        System.assertEquals('The Last Name "INVALIDNAME" is not allowed for DML',
result.getErrors()[0].getMessage());
    }
}

```

TestVerifyDate.apxc.

```

@isTest
private class TestVerifyDate {

    @isTest static void Test_CheckDates_casel(){
        Date D = VerifyDate.CheckDates(date.parse('01/01/2020'),
date.parse('01/05/2020'));
        System.assertEquals(date.parse('01/05/2020'), D);
    }

    @isTest static void Test_CheckDates_case2(){
        Date D = VerifyDate.CheckDates(date.parse('01/01/2020'),
date.parse('05/05/2020'));
        System.assertEquals(date.parse('01/31/2020'), D);
    }

    @isTest static void Test_DateWithin30Days_case1(){
        Boolean flag =
VerifyDate.DateWithin30Days(date.parse('01/01/2020'),date.parse('12/30/2019'));
        system.assertEquals(false, flag);
    }

    @isTest static void Test_DateWithin30Days_case2(){
        Boolean flag =
VerifyDate.DateWithin30Days(date.parse('01/01/2020'),date.parse('02/02/2020'));
        system.assertEquals(false, flag);
    }

    @isTest static void Test_DateWithin30Days_case3(){

```



```

        Boolean flag =
VerifyDate.DateWithin30Days(date.parse('01/01/2020'),date.parse('01/15/2020'));
        system.assertEquals(true, flag);
    }

```

```

    @isTest static void Test_SetEndOfMonthDate(){
        Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2020'));
    }

}

```

VerifyDate.apxc.

```

public class VerifyDate {

    //method to handle potential checks against two dates
    public static Date CheckDates(Date date1, Date date2) {
        //if date2 is within the next 30 days of date1, use date2. Otherwise use
the end of the month
        if(DateWithin30Days(date1,date2)) {
            return date2;
        } else {
            return SetEndOfMonthDate(date1);
        }
    }

    //method to check if date2 is within the next 30 days of date1
    @TestVisible private static Boolean DateWithin30Days(Date date1, Date date2) {
        //check for date2 being in the past
        if( date2 < date1) { return false; }

        //check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1
        if( date2 >= date30Days ) { return false; }
        else { return true; }
    }

    //method to return the end of the month of a given date

```

```

    @TestVisible private static Date SetEndOfMonthDate(Date date1) {
        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
        Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
        return lastDay;
    }
}

```

Apex Triggers

AccountAddressTrigger.apxt

```

trigger AccountAddressTrigger on Account (before insert, before update) {

    for(Account account:Trigger.New){
        if(account.Match_Billing_Address__c == True){
            account.ShippingPostalCode = account.BillingPostalCode;
        }
    }
}

```

ClosedOpportunityTrigger.apxt

```

trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {
    List<Task> tasklist = new List<Task>();

    for(Opportunity opp: Trigger.New){
        if(opp.StageName == 'Closed Won'){
            tasklist.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));
        }
    }

    if(tasklist.size()>0){
        insert tasklist;
    }
}

```

Asynchronous Apex

AccountProcessor.apxc.

```
public class AccountProcessor {
    @future
    public static void countContacts(List<Id> accountIds){

        List<Account> accountsToUpdate = new List<Account>();

        List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from
Account Where Id in :accountIds];

        For(Account acc:accounts){
            List<Contact> contactList = acc.Contacts;
            acc.Number_Of_Contacts__c = contactList.size();
            accountsToUpdate.add(acc);

        }
        update accountsToUpdate;

    }
}
```

AccountProcessorTest.apxc.

```
@IsTest
private class AccountProcessorTest {
    @IsTest
    private static void testCountContacts(){
        Account newAccount = new Account(Name= 'Test Account');
        insert newAccount;

        Contact newContact1 = new
Contact(FirstName='John',LastName='Doe',AccountId = newAccount.Id);
        insert newContact1;

        Contact newContact2 = new
Contact(FirstName='Jane',LastName='Doe',AccountId = newAccount.Id);
```

```

        insert newContact2;

        List<Id> accountIds = new List<Id>();
        accountIds.add(newAccount.Id);

        Test.startTest();
        AccountProcessor.countContacts(accountIds);
        Test.stopTest();

    }
}

```

AddPrimaryContact.apxc

```

public class AddPrimaryContact implements Queueable{

    private Contact con;
    private String state;

    public AddPrimaryContact(Contact con, String state){
        this.con = con;
        this.state = state;
    }

    public void execute(QueueableContext context){
        List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id
from contacts)
                                from Account where BillingState = :state Limit 200];
        List<Contact> primaryContacts = new List<Contact>();

        for(Account acc:accounts){
            Contact c = con.clone();
            c.AccountId = acc.Id;
            primaryContacts.add(c);
        }

        if(primaryContacts.size() > 0){

```

```

        insert primaryContacts;
    }
}
}

```

AddPrimaryContactTest.apxc.

@isTest

public class AddPrimaryContactTest {

static testmethod void testQueueable(){

List<Account> testAccounts = new List<Account>();

for(Integer i=0;i<50;i++){

testAccounts.add(new Account(Name='Account '+i,BillingState='CA'));

}

for(Integer j=0;j<50;j++){

testAccounts.add(new Account(Name='Account '+j,BillingState='NY'));

}

insert testAccounts;

Contact testContact = new Contact(FirstName = 'John', LastName = 'Doe');

insert testContact;

AddPrimaryContact addit = new addPrimaryContact(testContact, 'CA');

Test.startTest();

system.enqueueJob(addit);

Test.stopTest();

**System.assertEquals(50,[Select count() from Contact where accountId in
(Select Id from Account where BillingState='CA')]);**

}

}

DailyLeadProcessor.apxc.

global class DailyLeadProcessor implements Schedulable{

```

global void execute(SchedulableContext ctx){
    List<Lead> leads = [SELECT Id, LeadSource FROM Lead WHERE
LeadSource = ''];

    if(leads.size() > 0){
        List<Lead> newLeads = new List<Lead>();

        for(Lead lead : leads){
            lead.LeadSource = 'DreamForce';
            newLeads.add(lead);
        }

        update newLeads;
    }
}

```

DailyLeadProcessorTest.apxc.

```

@isTest
private class DailyLeadProcessorTest{
    //Seconds Minutes Hours Day_of_month Month Day_of_week optional_year
    public static String CRON_EXP = '0 0 0 2 6 ? 2022';

    static testmethod void testScheduledJob(){
        List<Lead> leads = new List<Lead>();

        for(Integer i = 0; i < 200; i++){
            Lead lead = new Lead(LastName = 'Test ' + i, LeadSource = '', Company =
'Test Company ' + i, Status = 'Open - Not Contacted');
            leads.add(lead);
        }

        insert leads;

        Test.startTest();
        // Schedule the test job
        String jobId = System.schedule('Update LeadSource to DreamForce',

```

```
CRON_EXP, new DailyLeadProcessor());
```

```
    // Stopping the test will run the job synchronously
    Test.stopTest();
}
}
```

LeadProcessor.apxc.

```
global class LeadProcessor implements Database.Batchable<sObject> {
    global Integer count = 0;

    global Database.QueryLocator start(Database.BatchableContext bc){
        return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
    }

    global void execute (Database.BatchableContext bc, List<Lead> L_list){
        List<lead> L_list_new = new List<lead>();

        for(lead L:L_list){
            L.leadsource = 'Dreamforce';
            L_list_new.add(L);
            count += 1;
        }
        update L_list_new;
    }

    global void finish(Database.BatchableContext bc){
        system.debug('count = ' + count);
    }
}
```

LeadProcessorTest.apxc.

```
@isTest
private class LeadProcessorTest
```

```

{
    private static testMethod void LeadProcess()
    {
        List<Lead> lstLead = new List<Lead>();
        for(Integer i=0 ;i <200;i++)
        {
            lstLead.add(new Lead(LastName ='LastName'+i, Company ='demo'+i,
City='New York', Country='US', LeadSource='Phone inquiry'));
        }

        insert lstLead;

        Test.startTest();

        LeadProcessor obj = new LeadProcessor();
        DataBase.executeBatch(obj);

        Test.stopTest();
    }
}

```

APEX SPECIALIST SUPERBADGE

MaintenanceRequest.apxt.

```

trigger MaintenanceRequest on Case (before update, after update) {

    if(Trigger.isUpdate && Trigger.isAfter){

        MaintenanceRequestHelper.updateWorkOrders(Trigger.New,
Trigger.OldMap);

    }

}

```


MaintenanceRequestHelper.apxc.

```
public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders,
    Map<Id,Case> nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }

        if (!validIds.isEmpty()){
            List<Case> newCases = new List<Case>();
            Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id,
            Vehicle__c, Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
            Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
            FROM Case WHERE Id IN :validIds]);
            Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
            AggregateResult[] results = [SELECT Maintenance_Request__c,
            MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM
            Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds
            GROUP BY Maintenance_Request__c];

            for (AggregateResult ar : results){
                maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
                ar.get('cycle'));
            }

            for(Case cc : closedCasesM.values()){
                Case nc = new Case (
                    ParentId = cc.Id,
```

```

        Status = 'New',
        Subject = 'Routine Maintenance',
        Type = 'Routine Maintenance',
        Vehicle__c = cc.Vehicle__c,
        Equipment__c = cc.Equipment__c,
        Origin = 'Web',
        Date_Reported__c = Date.Today()

    );

    If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
    }

    newCases.add(nc);
}

insert newCases;

List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
        Equipment_Maintenance_Item__c wpClone = wp.clone();
        wpClone.Maintenance_Request__c = nc.Id;
        ClonedWPs.add(wpClone);

    }
}
insert ClonedWPs;
}
}
}

```

WarehouseCalloutService.apxc

```
public with sharing class WarehouseCalloutService {

    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

    //@future(callout=true)
    public static void runWarehouseEquipmentSync(){

        Http http = new Http();
        HttpRequest request = new HttpRequest();

        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);

        List<Product2> warehouseEq = new List<Product2>();

        if (response.getStatusCode() == 200){
            List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
            System.debug(response.getBody());

            for (Object eq : jsonResponse){
                Map<String,Object> mapJson = (Map<String,Object>)eq;
                Product2 myEq = new Product2();
                myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
                myEq.Name = (String) mapJson.get('name');
                myEq.Maintenance_Cycle__c = (Integer)
mapJson.get('maintenanceperiod');
                myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
                myEq.Cost__c = (Decimal) mapJson.get('lifespan');
                myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
                myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
                warehouseEq.add(myEq);
            }
        }
    }
}
```

```

        if (warehouseEq.size() > 0){
            upsert warehouseEq;
            System.debug('Your equipment was synced with the warehouse one');
            System.debug(warehouseEq);
        }
    }
}

```

WarehouseSyncSchedule.apxc

```

global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

```

MaintenanceRequest.apxc.

```

trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New,
        Trigger.OldMap);
    }
}

```

MaintenanceRequestHelper.apxc

```

public with sharing class MaintenanceRequestHelper {
    public static void updateworkOrders(List<Case> updWorkOrders,
    Map<Id,Case> nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){

```

```

        if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
            if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                validIds.add(c.Id);
            }
        }
    }

    if (!validIds.isEmpty()){
        List<Case> newCases = new List<Case>();
        Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id,
Vehicle__c, Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
        Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
        AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds
GROUP BY Maintenance_Request__c];

        for (AggregateResult ar : results){
            maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
        }

        for(Case cc : closedCasesM.values()){
            Case nc = new Case (
                ParentId = cc.Id,
                Status = 'New',
                Subject = 'Routine Maintenance',
                Type = 'Routine Maintenance',
                Vehicle__c = cc.Vehicle__c,
                Equipment__c =cc.Equipment__c,
                Origin = 'Web',
                Date_Reported__c = Date.Today()
            )
        }
    }
}

```

```

    );

    If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
    }

    newCases.add(nc);
}

insert newCases;

List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
        Equipment_Maintenance_Item__c wpClone = wp.clone();
        wpClone.Maintenance_Request__c = nc.Id;
        ClonedWPs.add(wpClone);

    }
}
insert ClonedWPs;
}
}
}
}

```

MaintenanceRequestHelperTest.apxc

```

@istest
public with sharing class MaintenanceRequestHelperTest {

    private static final string STATUS_NEW = 'New';
    private static final string WORKING = 'Working';
    private static final string CLOSED = 'Closed';
    private static final string REPAIR = 'Repair';

```

```
private static final string REQUEST_ORIGIN = 'Web';  
private static final string REQUEST_TYPE = 'Routine Maintenance';  
private static final string REQUEST_SUBJECT = 'Testing subject';
```

```
PRIVATE STATIC Vehicle__c createVehicle(){  
    Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');  
    return Vehicle;  
}
```

```
PRIVATE STATIC Product2 createEq(){  
    product2 equipment = new product2(name = 'SuperEquipment',  
                                       lifespan_months__C = 10,  
                                       maintenance_cycle__C = 10,  
                                       replacement_part__c = true);  
    return equipment;  
}
```

```
PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id  
equipmentId){  
    case cs = new case(Type=REPAIR,  
                       Status=STATUS_NEW,  
                       Origin=REQUEST_ORIGIN,  
                       Subject=REQUEST_SUBJECT,  
                       Equipment__c=equipmentId,  
                       Vehicle__c=vehicleId);  
    return cs;  
}
```

```
PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id  
equipmentId,id requestId){  
    Equipment_Maintenance_Item__c wp = new  
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,  
                               Maintenance_Request__c =  
requestId);  
    return wp;  
}
```

```

@istest
private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;

    case somethingToUpdate =
createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;

    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;

    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();

    Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c,
Vehicle__c, Date_Due__c
                    from case
                    where status =:STATUS_NEW];

    Equipment_Maintenance_Item__c workPart = [select id
                                                from Equipment_Maintenance_Item__c
                                                where Maintenance_Request__c =:newReq.Id];

    system.assert(workPart != null);
    system.assert(newReq.Subject != null);
    system.assertEquals(newReq.Type, REQUEST_TYPE);
    SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);

```



```
SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);
SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
}
```

@istest

```
private static void testMaintenanceRequestNegative(){
```

```
    Vehicle__C vehicle = createVehicle();
```

```
    insert vehicle;
```

```
    id vehicleId = vehicle.Id;
```

```
    product2 equipment = createEq();
```

```
    insert equipment;
```

```
    id equipmentId = equipment.Id;
```

```
    case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
```

```
    insert emptyReq;
```

```
    Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,
emptyReq.Id);
```

```
    insert workP;
```

```
    test.startTest();
```

```
    emptyReq.Status = WORKING;
```

```
    update emptyReq;
```

```
    test.stopTest();
```

```
    list<case> allRequest = [select id
                           from case];
```

```
    Equipment_Maintenance_Item__c workPart = [select id
                                               from Equipment_Maintenance_Item__c
                                               where Maintenance_Request__c = :emptyReq.Id];
```

```
    system.assert(workPart != null);
```

```
    system.assert(allRequest.size() == 1);
```

```
}
```

```

@istest
private static void testMaintenanceRequestBulk(){
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();

    for(integer i = 0; i < 300; i++){
        vehicleList.add(createVehicle());
        equipmentList.add(createEq());
    }
    insert vehicleList;
    insert equipmentList;

    for(integer i = 0; i < 300; i++){
        requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    }
    insert requestList;

    for(integer i = 0; i < 300; i++){
        workPartList.add(createWorkPart(equipmentList.get(i).id,
requestList.get(i).id));
    }
    insert workPartList;

    test.startTest();
    for(case req : requestList){
        req.Status = CLOSED;
        oldRequestIds.add(req.Id);
    }
    update requestList;
    test.stopTest();

    list<case> allRequests = [select id

```

```

        from case
        where status =: STATUS_NEW];

    list<Equipment_Maintenance_Item__c> workParts = [select id
                                                    from Equipment_Maintenance_Item__c
                                                    where Maintenance_Request__c in:
oldRequestIds];

    system.assert(allRequests.size() == 300);
}
}

```

WarehouseCalloutService.apxc.

```

public with sharing class WarehouseCalloutService {

    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

    //@future(callout=true)
    public static void runWarehouseEquipmentSync(){

        Http http = new Http();
        HttpRequest request = new HttpRequest();

        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);

        List<Product2> warehouseEq = new List<Product2>();

        if (response.getStatusCode() == 200){
            List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
            System.debug(response.getBody());

            for (Object eq : jsonResponse){

```

```

    Map<String,Object> mapJson = (Map<String,Object>)eq;
    Product2 myEq = new Product2();
    myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
    myEq.Name = (String) mapJson.get('name');
    myEq.Maintenance_Cycle__c = (Integer)
mapJson.get('maintenanceperiod');
    myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
    myEq.Cost__c = (Decimal) mapJson.get('lifespan');
    myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
    myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
    warehouseEq.add(myEq);
}

if (warehouseEq.size() > 0){
    upsert warehouseEq;
    System.debug('Your equipment was synced with the warehouse one');
    System.debug(warehouseEq);
}

}
}
}

```

WarehouseCalloutServiceMock.apxc

```

@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request){

        System.assertEquals('https://th-superbadge-
apex.herokuapp.com/equipment', request.getEndpoint());
        System.assertEquals('GET', request.getMethod());

        // Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
    }
}

```

```

response.setBody(['{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5,"name":"Generator 1000 kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}']);
response.setStatusCode(200);
return response;
}
}

```

WarehouseCalloutServiceTest.apxc.

@isTest

```

private class WarehouseCalloutServiceTest {
    @isTest
    static void testWareHouseCallout(){
        Test.startTest();
        // implement mock callout test here
        Test.setMock(HTTPCalloutMock.class, new
WarehouseCalloutServiceMock());
        WarehouseCalloutService.runWarehouseEquipmentSync();
        Test.stopTest();
        System.assertEquals(1, [SELECT count() FROM Product2]);
    }
}

```

WarehouseSyncSchedule.apxc

```

global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

```

WarehouseSyncScheduleTest.apxc

@isTest

public class WarehouseSyncScheduleTest {

@isTest static void WarehousescheduleTest(){

String scheduleTime = '00 00 01 * * ?';

Test.startTest();

Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());

String jobId=System.schedule('Warehouse Time To Schedule to Test',
scheduleTime, new WarehouseSyncSchedule());

Test.stopTest();

//Contains schedule information for a scheduled job. CronTrigger is similar to
a cron job on UNIX systems.

// This object is available in API version 17.0 and later.

CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];

System.assertEquals(jobID, a.Id,'Schedule ');

}

}