# **Apex Triggers**

# AccountAddressTrigger

```
trigger AccountAddressTrigger on Account (before insert, before update) {
   for(Account account:Trigger.new){
      if(account.Match_Billing_Address__c == True){
        account.ShippingPostalCode = account.BillingPostalCode;
    }
   }
}
```

# ClosedOpportunityTrigger

```
trigger ClosedOpportunityTrigger on Opportunity (after insert,after update) {
   List<Task> tasklist = new List<Task>();

for(Opportunity opp: Trigger.New){
   if(opp.StageName == 'Closed Won'){
     tasklist.add(New Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));
   }
}

if(tasklist.size()>0){
   insert tasklist;
}
```

# **Apex Testing**

# VerifyDate

```
public class VerifyDate {
```

```
//method to handle potential checks against two dates
      public static Date CheckDates(Date date1, Date date2) {
             //if date2 is within the next 30 days of date1, use date2. Otherwise use
the end of the month
             if(DateWithin30Days(date1,date2)) {
                    return date2;
             } else {
                    return SetEndOfMonthDate(date1);
             }
      }
      //method to check if date2 is within the next 30 days of date1
      @TestVisible private static Boolean DateWithin30Days(Date date1, Date date2) {
             //check for date2 being in the past
      if( date2 < date1) { return false; }</pre>
      //check that date2 is within (>=) 30 days of date1
      Date date30Days = date1.addDays(30); //create a date 30 days away from date1
             if( date2 >= date30Days ) { return false; }
             else { return true; }
      }
      //method to return the end of the month of a given date
      @TestVisible private static Date SetEndOfMonthDate(Date date1) {
             Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
             Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
             return lastDay;
      }
}
```

```
@isTest
private class TestVerifyDate {
  @isTest static void Test_CheckDates case1(){
    Date D =
VerifyDate.CheckDates(date.parse('01/01/2020'),date.parse('01/05/2020'));
    System.assertEquals(date.parse('01/05/2020'),D);
  }
  @isTest static void Test CheckDates case2(){
    Date D =
VerifyDate.CheckDates(date.parse('01/01/2020'),date.parse('05/05/2020'));
    System.assertEquals(date.parse('01/31/2020'),D);
  }
  @isTest static void Test DateWithin30Days case1(){
    Boolean flag =
VerifyDate.DateWithin30Days(date.parse('01/01/2020'),date.parse('12/30/2019'));
    System.assertEquals(false, flag);
  }
  @isTest static void Test_DateWithin30Days_case2(){
    Boolean flag =
VerifyDate.DateWithin30Days(date.parse('01/01/2020'),date.parse('02/02/2019'));
    System.assertEquals(false, flag);
  }
  @isTest static void Test DateWithin30Days case3(){
    Boolean flag =
VerifyDate.DateWithin30Days(date.parse('01/01/2020'),date.parse('01/15/2020'));
    System.assertEquals(true, flag);
  }
  @isTest static void Test SetEndOfMonthDate(){
    Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2020'));
  }
}
```

```
trigger RestrictContactByName on Contact (before insert, before update) {
      //check contacts prior to insert or update for invalid data
      For (Contact c : Trigger.New) {
             if(c.LastName == 'INVALIDNAME') {      //invalidname is invalid
                    c.AddError('The Last Name "'+c.LastName+" is not allowed for
DML');
             }
      }
}
TestRestrictContactByName
@isTest
public class TestRestrictContactByName {
  @isTest static void Test_insertupdateContact(){
    Contact cnt = new Contact();
    cnt.LastName = 'INVALIDNAME';
    Test.startTest();
    Database.SaveResult result = Database.insert(cnt, false);
    Test.stopTest();
    System.assert(!result.isSuccess());
    System.assert(result.getErrors().size() > 0);
    System.assertEquals('The Last Name "INVALIDNAME" is not allowed for
DML',result.getErrors()[0].getMessage());
}
```

# RandomContactFactory

```
public class RandomContactFactory {

public static List <Contact> generateRandomContacts(Integer num, String lastName){
   List <Contact> contactList = new List <Contact>();
   for(Integer i = 1;i<=num;i++){
      Contact ct = new Contact(FirstName = 'Test '+i, LastName = lastName);
      contactList.add(ct);
   }
   return contactList;
}</pre>
```

# **Asynchronous Apex**

#### **AccountProcessor**

```
public class AccountProcessor {
    @future
    public static void countContacts(List<Id> accountIds){
        List<Account> accountsToUpdate = new List<Account>();

        List<Account> accounts = [Select Id,Name, (Select Id from Contacts) from Account Where Id in :accountIds];

        For(Account acc:accounts){
        List<Contact> contactList = acc.Contacts;
        acc.Number_Of_Contacts__c = contactList.size();
        accountsToUpdate.add(acc);
    }
}
```

```
}
update accountsToUpdate;
}
```

#### AccountProcessorTest

```
@lsTest
private class AccountProcessorTest {
  @lsTest
  private static void testCountContacts(){
    Account newAccount = new Account(Name='Test Account');
    insert newAccount;
    Contact newContact1 = new Contact(FirstName='John',LastName='Doe',AccountId
= newAccount.ld);
    insert newContact1;
    Contact newContact2 = new Contact(FirstName='Jane',LastName='Doe',AccountId
= newAccount.ld);
    insert newContact2;
    List<Id> accountIds = new List<Id>();
    accountIds.add(newAccount.Id);
    Test.startTest();
    AccountProcessor.countContacts(accountIds);
    Test.stopTest();
  }
LeadProcessor
```

global class LeadProcessor implements Database.Batchable<sObject> {

```
global Integer count = 0;
  global Database.QueryLocator start(Database.BatchableContext bc){
    return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
  }
  global void execute (Database.BatchableContext bc, List<Lead> L_list){
    List<lead> L_list_new = new List<lead>();
    for(lead L:L_list){
      L.leadsource = 'Dreamforce';
      L_list_new.add(L);
      count += 1;
    }
    update L_list_new;
  }
  global void finish(Database.BatchableContext bc){
    system.debug('count = '+ count);
  }
}
LeadProcessorTest
```

```
@isTest
public class LeadProcessorTest {
  @isTest
  public static void testit(){
    List<lead> L_list = new List<lead>();
    for(Integer i=0; i<200; i++){
      Lead L = new lead();
      L.LastName = 'name' + i;
```

```
L.Company = 'Company';
L.Status = 'Random Status';
L_list.add(L);
}
insert L_list;

Test.startTest();
LeadProcessor lp = new LeadProcessor();
Id batchId = Database.executeBatch(lp);
Test.stopTest();
}
```

# AddPrimaryContact

```
public class AddPrimaryContact implements Queueable {
  public contact c;
  public String state;
  public AddPrimaryContact(Contact c, String state) {
    this.c = c;
    this.state = state;
  }
  public void execute(QueueableContext qc) {
    system.debug('this.c = '+this.c+' this.state = '+this.state);
    List<Account> acc_lst = new List<account>([select id, name, BillingState from
account where account.BillingState = :this.state limit 200]);
    List<contact> c_lst = new List<contact>();
    for(account a: acc_lst) {
      contact c = new contact();
      c = this.c.clone(false, false, false, false);
      c.AccountId = a.Id;
      c_lst.add(c);
```

```
}
insert c_lst;
}
```

# AddPrimaryContactTest

```
@IsTest
public class AddPrimaryContactTest {
  @lsTest
  public static void testing() {
    List<account> acc_lst = new List<account>();
    for (Integer i=0; i<50;i++) {
      account a = new account(name=string.valueOf(i),billingstate='NY');
      system.debug('account a = '+a);
      acc_lst.add(a);
    }
    for (Integer i=0; i<50;i++) {
      account a = new account(name=string.valueOf(50+i),billingstate='CA');
      system.debug('account a = '+a);
      acc_lst.add(a);
    insert acc_lst;
    Test.startTest();
    contact c = new contact(lastname='alex');
    AddPrimaryContact apc = new AddPrimaryContact(c,'CA');
    system.debug('apc = '+apc);
    System.enqueueJob(apc);
    Test.stopTest();
    List<contact> c_lst = new List<contact>([select id from contact]);
    Integer size = c_lst.size();
    system.assertEquals(50, size);
```

```
}
```

# **DailyLeadProcessor**

```
global class DailyLeadProcessor implements Schedulable{
    global void execute(SchedulableContext ctx){
        List<Lead> leads = [SELECT Id, LeadSource FROM Lead WHERE LeadSource = "];

    if(leads.size() > 0){
        List<Lead> newLeads = new List<Lead>();

        for(Lead lead : leads){
            lead.LeadSource = 'DreamForce';
            newLeads.add(lead);
        }

        update newLeads;
    }
}
```

# ${\bf Daily Lead Processor Test}$

```
@isTest
private class DailyLeadProcessorTest{
   //Seconds Minutes Hours Day_of_month Month Day_of_week optional_year
   public static String CRON_EXP = '0 0 0 2 6 ? 2022';
```

```
static testmethod void testScheduledJob(){
    List<Lead> leads = new List<Lead>();
    for(Integer i = 0; i < 200; i++){
      Lead lead = new Lead(LastName = 'Test ' + i, LeadSource = ", Company = 'Test
Company ' + i, Status = 'Open - Not Contacted');
      leads.add(lead);
    }
    insert leads;
    Test.startTest();
    // Schedule the test job
    String jobId = System.schedule('Update LeadSource to DreamForce', CRON_EXP,
new DailyLeadProcessor());
    // Stopping the test will run the job synchronously
    Test.stopTest();
 }
}
```

# **Apex Integration Services**

## **AnimalLocator**

```
public class AnimalLocator
{

public static String getAnimalNameById(Integer id)
 {

   Http http = new Http();

   HttpRequest request = new HttpRequest();

   request.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/'+id);
   request.setMethod('GET');

   HttpResponse response = http.send(request);
```

```
String strResp = ";
      system.debug('****response '+response.getStatusCode());
      system.debug('*****response '+response.getBody());
    // If the request is successful, parse the JSON response.
    if (response.getStatusCode() == 200)
      // Deserializes the JSON string into collections of primitive data types.
      Map<String, Object> results = (Map<String, Object>)
JSON.deserializeUntyped(response.getBody());
      // Cast the values in the 'animals' key as a list
      Map<string,object> animals = (map<string,object>) results.get('animal');
      System.debug('Received the following animals:' + animals );
      strResp = string.valueof(animals.get('name'));
      System.debug('strResp >>>>' + strResp );
    return strResp;
 }
}
```

### **AnimalLocatorTest**

```
@isTest
private class AnimalLocatorTest{
    @isTest static void AnimalLocatorMock1() {
        Test.SetMock(HttpCallOutMock.class, new AnimalLocatorMock());
        string result=AnimalLocator.getAnimalNameById(3);
        string expectedResult='chicken';
        System.assertEquals(result, expectedResult);
    }
}
```

## **AnimalLocatorMock**

```
@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
    global HTTPResponse respond(HTTPRequest request) {
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody('{"animal":{"id":1,"name":"chicken","eats":"chicken food","says":"cluck cluck"}}');
        response.setStatusCode(200);
        return response;
    }
}
```

#### **ParkService**

```
public class ParkService {
  public class byCountryResponse {
    public String[] return_x;
    private String[] return_x_type_info = new
String[]{'return','http://parks.services/',null,'0','-1','false'};
     private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
    private String[] field_order_type_info = new String[]{'return_x'};
  }
  public class byCountry {
    public String arg0;
    private String[] arg0_type_info = new
String[]{'arg0','http://parks.services/',null,'0','1','false'};
     private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
    private String[] field_order_type_info = new String[]{'arg0'};
  public class ParksImplPort {
    public String endpoint_x = 'https://th-apex-soap-
service.herokuapp.com/service/parks';
```

```
public Map<String,String> inputHttpHeaders_x;
    public Map<String,String> outputHttpHeaders_x;
    public String clientCertName_x;
    public String clientCert_x;
    public String clientCertPasswd_x;
    public Integer timeout_x;
    private String[] ns_map_type_info = new String[]{'http://parks.services/',
'ParkService'};
    public String[] byCountry(String arg0) {
      ParkService.byCountry request_x = new ParkService.byCountry();
      request_x.arg0 = arg0;
      ParkService.byCountryResponse response_x;
      Map<String, ParkService.byCountryResponse> response_map_x = new
Map<String, ParkService.byCountryResponse>();
      response_map_x.put('response_x', response_x);
      WebServiceCallout.invoke(
       this,
       request_x,
       response_map_x,
       new String[]{endpoint_x,
       'http://parks.services/',
       'byCountry',
       'http://parks.services/',
       'byCountryResponse',
       'ParkService.byCountryResponse'}
      );
      response_x = response_map_x.get('response_x');
      return response_x.return_x;
 }
```

### **ParkLocator**

```
public class ParkLocator {
   public static String[] country(String country){
      ParkService.ParksImplPort parks = new ParkService.ParksImplPort();
      String[] parksname = parks.byCountry(country);
      return parksname;
   }
}
```

#### **ParkLocatorTest**

```
@isTest
private class ParkLocatorTest{
    @isTest
    static void testParkLocator() {
        Test.setMock(WebServiceMock.class, new ParkServiceMock());
        String[] arrayOfParks = ParkLocator.country('India');

        System.assertEquals('Park1', arrayOfParks[0]);
    }
}
```

#### ParkServiceMock

```
@isTest
global class ParkServiceMock implements WebServiceMock {
    global void doInvoke(
        Object stub,
        Object request,
        Map<String, Object> response,
        String endpoint,
        String soapAction,
```

```
String requestName,
      String responseNS,
      String responseName,
      String responseType) {
    ParkService.byCountryResponse response x = new
ParkService.byCountryResponse();
    List<String> lstOfDummyParks = new List<String> {'Park1','Park2','Park3'};
    response x.return x = IstOfDummyParks;
    response.put('response x', response x);
  }
}
AccountManager
@RestResource(urlMapping='/Accounts/*/contacts')
global with sharing class AccountManager {
  @HttpGet
  global static account getAccount() {
    RestRequest request = RestContext.request;
    String accountId =
request.requestURI.substring(request.requestURI.lastIndexOf('/')-18,
      request.requestURI.lastIndexOf('/'));
    List<Account> a = [select id, name, (select id, name from contacts) from account
where id = :accountId];
    List<contact> co = [select id, name from contact where account.id = :accountId];
    system.debug('** a[0] = '+ a[0]);
    return a[0];
  }
```

# **AccountManagerTest**

```
@istest
public class AccountManagerTest {
@istest static void testGetContactsByAccountId() {
Id recordId = createTestRecord();
// Set up a test request
RestRequest request = new RestRequest();
request.requestUri =
'https://yourInstance.salesforce.com/services/apexrest/Accounts/'+ recordId+'/Contacts';
request.httpMethod = 'GET';
RestContext.request = request;
// Call the method to test
Account this Account = Account Manager.get Account();
// Verify results
System.assert(thisAccount!= null);
System.assertEquals('Test record', thisAccount.Name);
}
// Helper method
static Id createTestRecord() {
// Create test record
Account accountTest = new Account(
Name='Test record');
insert accountTest;
Contact contactTest = new Contact(
FirstName='John',
LastName='Doe',
AccountId=accountTest.Id
);
return accountTest.ld;
```

} }

# **Apex Specialist Super Badge**

# MaintenanceRequestHelper

```
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
         if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
           validIds.add(c.Id);
        }
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle c,
Equipment c, Equipment r.Maintenance Cycle c,(SELECT
Id, Equipment c, Quantity c FROM Equipment Maintenance Items r)
                                FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance Request c,
MIN(Equipment r.Maintenance Cycle c)cycle FROM
Equipment Maintenance Item c WHERE Maintenance Request c IN: ValidIds
GROUP BY Maintenance Request c];
    for (AggregateResult ar : results){
```

```
maintenanceCycles.put((Id) ar.get('Maintenance Request c'), (Decimal)
ar.get('cycle'));
    }
      for(Case cc : closedCasesM.values()){
         Case nc = new Case (
           ParentId = cc.Id,
         Status = 'New',
           Subject = 'Routine Maintenance',
           Type = 'Routine Maintenance',
           Vehicle c = cc. Vehicle c,
           Equipment__c =cc.Equipment__c,
           Origin = 'Web',
           Date Reported c = Date.Today()
         );
         If (maintenanceCycles.containskey(cc.Id)){
           nc.Date Due c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.ld));
         }
         newCases.add(nc);
      }
      insert newCases;
      List<Equipment Maintenance Item c> clonedWPs = new
List<Equipment Maintenance Item c>();
      for (Case nc : newCases){
         for (Equipment Maintenance Item c wp:
closedCasesM.get(nc.ParentId).Equipment Maintenance Items r){
           Equipment Maintenance Item c wpClone = wp.clone();
           wpClone.Maintenance Request c = nc.ld;
           ClonedWPs.add(wpClone);
         }
```

```
}
  insert ClonedWPs;
}
}
```

# MaintenanceRequest

```
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
  }
}
```

### **WarehouseCalloutService**

```
public with sharing class WarehouseCalloutService {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-apex.herokuapp.com/equipment';

//@future(callout=true)
    public static void runWarehouseEquipmentSync(){
```

```
Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
       List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
       System.debug(response.getBody());
      for (Object eq : jsonResponse){
         Map<String,Object> mapJson = (Map<String,Object>)eq;
         Product2 myEq = new Product2();
         myEq.Replacement Part c = (Boolean) mapJson.get('replacement');
         myEq.Name = (String) mapJson.get('name');
         myEq.Maintenance Cycle c = (Integer) mapJson.get('maintenanceperiod');
         myEq.Lifespan Months c = (Integer) mapJson.get('lifespan');
         myEq.Cost c = (Decimal) mapJson.get('lifespan');
         myEq.Warehouse SKU c = (String) mapJson.get('sku');
         myEq.Current Inventory c = (Double) mapJson.get('quantity');
         warehouseEq.add(myEq);
      }
       if (warehouseEq.size() > 0){
         upsert warehouseEq;
         System.debug('Your equipment was synced with the warehouse one');
         System.debug(warehouseEq);
      }
    }
  }
```

## WarehouseSyncSchedule

```
global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {
        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}
```

### **MaintenanceRequestHelperTest**

```
@istest
public with sharing class MaintenanceRequestHelperTest {
  private static final string STATUS NEW = 'New';
  private static final string WORKING = 'Working';
  private static final string CLOSED = 'Closed';
  private static final string REPAIR = 'Repair';
  private static final string REQUEST ORIGIN = 'Web';
  private static final string REQUEST TYPE = 'Routine Maintenance';
  private static final string REQUEST_SUBJECT = 'Testing subject';
  PRIVATE STATIC Vehicle c createVehicle(){
    Vehicle c Vehicle = new Vehicle C(name = 'SuperTruck');
    return Vehicle;
  }
  PRIVATE STATIC Product2 createEq(){
    product2 equipment = new product2(name = 'SuperEquipment',
                        lifespan months C = 10,
                        maintenance cycle C = 10,
```

```
replacement part c = true);
    return equipment;
  }
  PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
              Status=STATUS_NEW,
              Origin=REQUEST ORIGIN,
               Subject=REQUEST SUBJECT,
              Equipment c=equipmentId,
              Vehicle c=vehicleId);
    return cs;
  }
  PRIVATE STATIC Equipment Maintenance Item c createWorkPart(id
equipmentId,id requestId){
    Equipment Maintenance Item c wp = new
Equipment Maintenance Item c(Equipment c = equipmentId,
                                           Maintenance Request c = requestId);
    return wp;
  }
  @istest
  private static void testMaintenanceRequestPositive(){
    Vehicle c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;
    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;
    Equipment Maintenance Item c workP =
```

```
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;
    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();
    Case newReq = [Select id, subject, type, Equipment c, Date Reported c,
Vehicle c, Date Due c
            from case
            where status =: STATUS NEW];
    Equipment Maintenance Item c workPart = [select id
                            from Equipment Maintenance Item c
                            where Maintenance Request c =: newReq.Id];
    system.assert(workPart != null);
    system.assert(newReq.Subject != null);
    system.assertEquals(newReq.Type, REQUEST TYPE);
    SYSTEM.assertEquals(newReg.Equipment c, equipmentId);
    SYSTEM.assertEquals(newReq.Vehicle c, vehicleId);
    SYSTEM.assertEquals(newReq.Date Reported c, system.today());
  }
  @istest
  private static void testMaintenanceRequestNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id:
    product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case emptyReg = createMaintenanceRequest(vehicleId,equipmentId);
    insert emptyReq;
```

```
Equipment Maintenance Item c workP = createWorkPart(equipmentId,
emptyReq.Id);
    insert workP;
    test.startTest();
    emptyReq.Status = WORKING;
    update emptyReq;
    test.stopTest();
    list<case> allRequest = [select id
                   from case];
    Equipment Maintenance Item c workPart = [select id
                              from Equipment Maintenance Item c
                              where Maintenance Request c = :emptyReq.Id];
    system.assert(workPart != null);
    system.assert(allRequest.size() == 1);
  }
  @istest
  private static void testMaintenanceRequestBulk(){
    list<Vehicle C> vehicleList = new list<Vehicle C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment Maintenance Item c> workPartList = new
list<Equipment Maintenance Item c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();
    for(integer i = 0; i < 300; i++){
      vehicleList.add(createVehicle());
       equipmentList.add(createEq());
    insert vehicleList;
    insert equipmentList;
```

```
for(integer i = 0; i < 300; i++){
       requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    insert requestList;
    for(integer i = 0; i < 300; i++){
       workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
    }
    insert workPartList;
    test.startTest();
    for(case req : requestList){
       reg.Status = CLOSED;
       oldRequestIds.add(req.Id);
    }
    update requestList;
    test.stopTest();
    list<case> allRequests = [select id
                    from case
                    where status =: STATUS_NEW];
    list<Equipment Maintenance Item c> workParts = [select id
                                  from Equipment Maintenance Item c
                                  where Maintenance Request c in: oldRequestIds];
    system.assert(allRequests.size() == 300);
  }
}
```

# MaintenanceRequestHelper

```
public with sharing class MaintenanceRequestHelper {
   public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
```

```
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
       if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
         if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
           validIds.add(c.Id);
         }
    }
    if (!validIds.isEmpty()){
       List<Case> newCases = new List<Case>();
       Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle c,
Equipment c, Equipment r.Maintenance Cycle c,(SELECT
Id, Equipment c, Quantity c FROM Equipment Maintenance Items r)
                                FROM Case WHERE Id IN :validIds]);
       Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance Request c,
MIN(Equipment r.Maintenance Cycle c)cycle FROM
Equipment Maintenance Item c WHERE Maintenance Request c IN: ValidIds
GROUP BY Maintenance Request c];
    for (AggregateResult ar : results){
       maintenanceCycles.put((Id) ar.get('Maintenance Request c'), (Decimal)
ar.get('cycle'));
    }
      for(Case cc : closedCasesM.values()){
         Case nc = new Case (
           ParentId = cc.Id,
         Status = 'New',
           Subject = 'Routine Maintenance',
           Type = 'Routine Maintenance',
```

```
Vehicle c = cc.Vehicle c,
           Equipment c =cc.Equipment c,
           Origin = 'Web',
           Date Reported c = Date.Today()
        );
         If (maintenanceCycles.containskey(cc.Id)){
           nc.Date Due c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
        }
         newCases.add(nc);
      }
      insert newCases;
      List<Equipment Maintenance Item c> clonedWPs = new
List<Equipment Maintenance Item c>();
      for (Case nc : newCases){
         for (Equipment Maintenance Item c wp:
closedCasesM.get(nc.Parentld).Equipment Maintenance Items r){
           Equipment Maintenance Item c wpClone = wp.clone();
           wpClone.Maintenance Request c = nc.ld;
           ClonedWPs.add(wpClone);
        }
      insert ClonedWPs;
    }
  }
}
```

# MaintenanceRequest

```
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
  }
}
```

```
WarehouseCalloutService
public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
  //@future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
       List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
       System.debug(response.getBody());
       for (Object eq : jsonResponse){
         Map<String,Object> mapJson = (Map<String,Object>)eq;
         Product2 myEq = new Product2();
         myEq.Replacement Part c = (Boolean) mapJson.get('replacement');
```

```
myEq.Name = (String) mapJson.get('name');
myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
myEq.Cost__c = (Decimal) mapJson.get('lifespan');
myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
warehouseEq.add(myEq);
}

if (warehouseEq.size() > 0){
    upsert warehouseEq;
    System.debug('Your equipment was synced with the warehouse one');
    System.debug(warehouseEq);
}

}

}

}
```

#### WarehouseCalloutServiceTest

```
@isTest

private class WarehouseCalloutServiceTest {
    @isTest
    static void testWareHouseCallout(){
        Test.startTest();
        // implement mock callout test here
        Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.runWarehouseEquipmentSync();
        Test.stopTest();
        System.assertEquals(1, [SELECT count() FROM Product2]);
    }
}
```

#### **WarehouseCalloutServiceMock**

```
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
  // implement http mock callout
  global static HttpResponse respond(HttpRequest request){
    System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
    System.assertEquals('GET', request.getMethod());
    // Create a fake response
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
response.setBody('[{" id":"55d66226726b611100aaf741","replacement":false,"quantity":
5,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}]');
    response.setStatusCode(200);
    return response;
  }
}
```

### WarehouseSyncSchedule

```
global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {
        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}
```

# **WarehouseSyncScheduleTest**

```
@isTest
public class WarehouseSyncScheduleTest {

@isTest static void WarehousescheduleTest(){
    String scheduleTime = '00 00 01 * * ?';
    Test.startTest();
    Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
    String jobID=System.schedule('Warehouse Time To Schedule to Test',
scheduleTime, new WarehouseSyncSchedule());
    Test.stopTest();
    //Contains schedule information for a scheduled job. CronTrigger is similar to a
cron job on UNIX systems.
    // This object is available in API version 17.0 and later.
    CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
    System.assertEquals(jobID, a.Id,'Schedule ');
}
```