

Salesforce Developer Catalyst

❖ Apex Specialist Superbadge

Automated Record Creation

MaintenanceRequestHelper.apxc :

```
public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case> nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }

        if (!validIds.isEmpty()){
            List<Case> newCases = new List<Case>();
            Map<Id,Case> closedCasesM = new Map<Id,Case>((SELECT Id, Vehicle__c, Equipment__c,
            Equipment__r.Maintenance_Cycle__c,(SELECT Id,Equipment__c,Quantity__c FROM
            Equipment_Maintenance_Items__r)
                                FROM Case WHERE Id IN :validIds));
            Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
            AggregateResult[] results = [SELECT Maintenance_Request__c,
            MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM Equipment_Maintenance_Item__c WHERE
            Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];

            for (AggregateResult ar : results){
                maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));
            }

            for(Case cc : closedCasesM.values()){
                Case nc = new Case (
                    ParentId = cc.Id,
                    Status = 'New',
                    Subject = 'Routine Maintenance',
                    Type = 'Routine Maintenance',
                    Vehicle__c = cc.Vehicle__c,
```

```

        Equipment__c = cc.Equipment__c,
        Origin = 'Web',
        Date_Reported__c = Date.Today()

    );

    If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
    } else {
        nc.Date_Due__c = Date.today().addDays((Integer) cc.Equipment__r.maintenance_Cycle__c);
    }

    newCases.add(nc);
}

insert newCases;

List<Equipment_Maintenance_Item__c> clonedWPs = new List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
        Equipment_Maintenance_Item__c wpClone = wp.clone();
        wpClone.Maintenance_Request__c = nc.Id;
        ClonedWPs.add(wpClone);

    }
}
insert ClonedWPs;
}
}
}

```

MaintenanceRequest.apxt :

```

trigger MaintenanceRequest on Case (before update, after update) {

    if (Trigger.isUpdate && Trigger.isAfter){

        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);

    }

}

```

Synchronize Salesforce data with an external system

WarehouseCalloutService.apxc :

```

public with sharing class WarehouseCalloutService implements Queueable {

    private static final String WAREHOUSE_URL = 'https://th-superbadge-apex.herokuapp.com/equipment';

```

//class that makes a REST callout to an external warehouse system to get a list of equipment that needs to be updated.

//The callout's JSON response returns the equipment records that you upsert in Salesforce.

@future(callout=true)

public static void runWarehouseEquipmentSync(){

 Http http = new Http();

 HttpRequest request = new HttpRequest();

 request.setEndpoint(WAREHOUSE_URL);

 request.setMethod('GET');

 HttpResponse response = http.send(request);

 List<Product2> warehouseEq = new List<Product2>();

 if (response.getStatusCode() == 200){

 List<Object> jsonResponse = (List<Object>)JSON.deserializeUntyped(response.getBody());

 System.debug(response.getBody());

 //class maps the following fields: replacement part (always true), cost, current inventory, lifespan, maintenance cycle, and warehouse SKU

 //warehouse SKU will be external ID for identifying which equipment records to update within Salesforce

 for (Object eq : jsonResponse){

 Map<String,Object> mapJson = (Map<String,Object>)eq;

 Product2 myEq = new Product2();

 myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');

 myEq.Name = (String) mapJson.get('name');

 myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');

 myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');

 myEq.Cost__c = (Integer) mapJson.get('cost');

 myEq.Warehouse_SKU__c = (String) mapJson.get('sku');

 myEq.Current_Inventory__c = (Double) mapJson.get('quantity');

 myEq.ProductCode = (String) mapJson.get('_id');

 warehouseEq.add(myEq);

 }

 if (warehouseEq.size() > 0){

 upsert warehouseEq;

 System.debug('Your equipment was synced with the warehouse one');

 }

 }

}

public static void execute (QueueableContext context){

 runWarehouseEquipmentSync();

}

}

Schedule synchronization using Apex code

WarehouseSyncShedule.apxc :

```
global with sharing class WarehouseSyncSchedule implements Schedulable{
    global void execute(SchedulableContext ctx){
        System.enqueueJob(new WarehouseCalloutService());
    }
}
```

Test automation logic

MaintenanceRequestHelperTest.apxc :-

```
@istest
public with sharing class MaintenanceRequestHelperTest {

    private static final string STATUS_NEW = 'New';
    private static final string WORKING = 'Working';
    private static final string CLOSED = 'Closed';
    private static final string REPAIR = 'Repair';
    private static final string REQUEST_ORIGIN = 'Web';
    private static final string REQUEST_TYPE = 'Routine Maintenance';
    private static final string REQUEST_SUBJECT = 'Testing subject';

    PRIVATE STATIC Vehicle__c createVehicle(){
        Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');
        return Vehicle;
    }

    PRIVATE STATIC Product2 createEq(){
        product2 equipment = new product2(name = 'SuperEquipment',
            lifespan_months__C = 10,
            maintenance_cycle__C = 10,
            replacement_part__c = true);
        return equipment;
    }

    PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
        case cs = new case(Type=REPAIR,
            Status=STATUS_NEW,
            Origin=REQUEST_ORIGIN,
            Subject=REQUEST_SUBJECT,
            Equipment__c=equipmentId,
            Vehicle__c=vehicleId);
        return cs;
    }

    PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id requestId){
        Equipment_Maintenance_Item__c wp = new Equipment_Maintenance_Item__c(Equipment__c =
            equipmentId,
            Maintenance_Request__c = requestId);
    }
}
```

```
    return wp;
}
```

```
@istest
```

```
private static void testMaintenanceRequestPositive(){
```

```
    Vehicle__c vehicle = createVehicle();
```

```
    insert vehicle;
```

```
    id vehicleId = vehicle.Id;
```

```
    Product2 equipment = createEq();
```

```
    insert equipment;
```

```
    id equipmentId = equipment.Id;
```

```
    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
```

```
    insert somethingToUpdate;
```

```
    Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,somethingToUpdate.id);
```

```
    insert workP;
```

```
    test.startTest();
```

```
    somethingToUpdate.status = CLOSED;
```

```
    update somethingToUpdate;
```

```
    test.stopTest();
```

```
    Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c, Vehicle__c, Date_Due__c
```

```
        from case
```

```
        where status =:STATUS_NEW];
```

```
    Equipment_Maintenance_Item__c workPart = [select id
```

```
        from Equipment_Maintenance_Item__c
```

```
        where Maintenance_Request__c =:newReq.Id];
```

```
    system.assert(workPart != null);
```

```
    system.assert(newReq.Subject != null);
```

```
    system.assertEquals(newReq.Type, REQUEST_TYPE);
```

```
    SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);
```

```
    SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);
```

```
    SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
```

```
}
```

```
@istest
```

```
private static void testMaintenanceRequestNegative(){
```

```
    Vehicle__C vehicle = createVehicle();
```

```
    insert vehicle;
```

```
    id vehicleId = vehicle.Id;
```

```
    product2 equipment = createEq();
```

```
    insert equipment;
```

```
    id equipmentId = equipment.Id;
```

```
    case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
```

```

insert emptyReq;

Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId, emptyReq.Id);
insert workP;

test.startTest();
emptyReq.Status = WORKING;
update emptyReq;
test.stopTest();

list<case> allRequest = [select id
                        from case];

Equipment_Maintenance_Item__c workPart = [select id
                                           from Equipment_Maintenance_Item__c
                                           where Maintenance_Request__c = :emptyReq.Id];

system.assert(workPart != null);
system.assert(allRequest.size() == 1);
}

@istest
private static void testMaintenanceRequestBulk(){
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();

    for(integer i = 0; i < 300; i++){
        vehicleList.add(createVehicle());
        equipmentList.add(createEq());
    }
    insert vehicleList;
    insert equipmentList;

    for(integer i = 0; i < 300; i++){
        requestList.add(createMaintenanceRequest(vehicleList.get(i).id, equipmentList.get(i).id));
    }
    insert requestList;

    for(integer i = 0; i < 300; i++){
        workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
    }
    insert workPartList;

    test.startTest();
    for(case req : requestList){
        req.Status = CLOSED;
        oldRequestIds.add(req.Id);
    }
    update requestList;

```

```

test.stopTest();

list<case> allRequests = [select id
                        from case
                        where status =: STATUS_NEW];

list<Equipment_Maintenance_Item__c> workParts = [select id
                                                from Equipment_Maintenance_Item__c
                                                where Maintenance_Request__c in: oldRequestIds];

system.assert(allRequests.size() == 300);
}
}

```

MaintenanceRequestHelper.apxc :

```

public with sharing class MaintenanceRequestHelper {

    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case> nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }

        if (!validIds.isEmpty()){
            List<Case> newCases = new List<Case>();
            Map<Id,Case> closedCasesM = new Map<Id,Case>((SELECT Id, Vehicle__c, Equipment__c,
            Equipment__r.Maintenance_Cycle__c,(SELECT Id,Equipment__c,Quantity__c FROM
            Equipment_Maintenance_Items__r)
            FROM Case WHERE Id IN :validIds));
            Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
            AggregateResult[] results = [SELECT Maintenance_Request__c,
            MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM Equipment_Maintenance_Item__c WHERE
            Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];

            for (AggregateResult ar : results){
                maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));
            }

            for(Case cc : closedCasesM.values()){
                Case nc = new Case (
                    ParentId = cc.Id,
                    Status = 'New',
                    Subject = 'Routine Maintenance',
                    Type = 'Routine Maintenance',

```

```

        Vehicle__c = cc.Vehicle__c,
        Equipment__c = cc.Equipment__c,
        Origin = 'Web',
        Date_Reported__c = Date.Today()

    );

    If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
    }

    newCases.add(nc);
}

insert newCases;

List<Equipment_Maintenance_Item__c> clonedWPs = new List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
        Equipment_Maintenance_Item__c wpClone = wp.clone();
        wpClone.Maintenance_Request__c = nc.Id;
        ClonedWPs.add(wpClone);

    }
}
insert ClonedWPs;
}
}
}

```

MaintenanceRequest.apxt :

```

trigger MaintenanceRequest on Case (before update, after update) {
    if (Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```

Test callout logic

WarehouseCalloutService.apxc :

```

public with sharing class WarehouseCalloutService {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-apex.herokuapp.com/equipment';

    //@future(callout=true)
    public static void runWarehouseEquipmentSync(){

        Http http = new Http();
        HttpRequest request = new HttpRequest();

        request.setEndpoint(WAREHOUSE_URL);
    }
}

```



```

request.setMethod('GET');
HttpResponse response = http.send(request);

List<Product2> warehouseEq = new List<Product2>();

if (response.getStatusCode() == 200){
    List<Object> jsonResponse = (List<Object>)JSON.deserializeUntyped(response.getBody());
    System.debug(response.getBody());

    for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost__c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
    }

    if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
    }

}
}
}

```

WarehouseCalloutServiceTest.apxc :

```

@isTest
private class WarehouseCalloutServiceTest {
    @isTest
    static void testWareHouseCallout(){
        Test.startTest();
        // implement mock callout test here
        Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.runWarehouseEquipmentSync();
        Test.stopTest();
        System.assertEquals(1, [SELECT count() FROM Product2]);
    }
}

```

WarehouseCalloutServiceMock.apxc :

```

@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request){

```

```

System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment', request.getEndpoint());
System.assertEquals('GET', request.getMethod());

// Create a fake response
HttpResponse response = new HttpResponse();
response.setHeader('Content-Type', 'application/json');

response.setBody('{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5,"name":"Generator
1000 kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}');
response.setStatusCode(200);
return response;
}
}

```

Test scheduling logic

WarehouseSyncSchedule.apxc :

```

global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

```

WarehouseSyncScheduleTest.apxc :

```

@isTest
public class WarehouseSyncScheduleTest {

    @isTest static void WarehousescheduleTest(){
        String scheduleTime = '00 00 01 * * ?';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String jobID=System.schedule('Warehouse Time To Schedule to Test', scheduleTime, new
WarehouseSyncSchedule());
        Test.stopTest();
        //Contains schedule information for a scheduled job. CronTrigger is similar to a cron job on UNIX systems.
        // This object is available in API version 17.0 and later.
        CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
        System.assertEquals(jobID, a.Id, 'Schedule ');
    }
}

```

Apex Triggers

Get Started with Apex Triggers

AccountAddressTrigger

```

trigger AccountAddressTrigger on Account (before insert,before update)
{
    List<Account> acclst=new List<Account>();
    for(account a:trigger.new)
    {
        if(a.Match_Billing_Address__c==true && a.BillingPostalCode!=null)
        {
            a.ShippingPostalCode=a.BillingPostalCode;
        }
    }
}

```

Bulk Apex Triggers

ClosedOpportunityTrigger

```

trigger ClosedOpportunityTrigger on Opportunity (after insert,after update)
{

    List<Opportunity> relatedOpps = [SELECT Id,OwnerId,StageName FROM Opportunity WHERE id in
:Trigger.New];

    List<Task> tasks = new List<Task>();
    for(Opportunity opp : relatedOpps)
    {
        if(opp.StageName == 'Closed Won')
        {
            Task tsk = new Task(whatID = Opp.ID, Ownerid = Opp.OwnerId, Subject='Follow Up  Test Task');
tasks.add(tsk);

        }
    }
    insert tasks;
}

```

Apex Testing.

Get Started with Apex Unit Tests

VerifyDate

```

public class VerifyDate {

    //method to handle potential checks against two dates
    public static Date CheckDates(Date date1, Date date2) {
        //if date2 is within the next 30 days of date1, use date2. Otherwise use the end of the month
        if(DateWithin30Days(date1,date2)) {
            return date2;
        }
    }
}

```

```

        } else {
            return SetEndOfMonthDate(date1);
        }
    }

    //method to check if date2 is within the next 30 days of date1
    private static Boolean DateWithin30Days(Date date1, Date date2) {
        //check for date2 being in the past
        if( date2 < date1) { return false; }

        //check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1
        if( date2 >= date30Days ) { return false; }
        else { return true; }
    }

    //method to return the end of the month of a given date
    private static Date SetEndOfMonthDate(Date date1) {
        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
        Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
        return lastDay;
    }
}

```

TestVerifyDate

```

@isTest
class TestVerifyDate {

    static testMethod void TestVerifyDate() {
        VerifyDate.CheckDates(System.today(),System.today()+10);
        VerifyDate.CheckDates(System.today(),System.today()+78);
    }
}

```

Test Apex Triggers

RestrictContactByName

```

trigger RestrictContactByName on Contact (before insert, before update) {

    //check contacts prior to insert or update for invalid data
    For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') { //invalidname is invalid
            c.AddError('The Last Name "'+c.LastName+'" is not allowed for DML');
        }
    }
}

```

TestRestrictContactByName

```
@istest
private class TestRestrictContactByName {
    @istest static void testname(){
        contact c = new contact(firstname='Satya',lastname='INVALIDNAME');
        test.startTest();
        database.SaveResult result = database.insert(c,false);
        test.stopTest();
        system.assertEquals('The Last Name "INVALIDNAME" is not allowed for DML',
result.getErrors()[0].getMessage());
    }
}
```

Create Test Data for Apex Tests

RandomContactFactory

```
public class RandomContactFactory {

    Public Static List<Contact> generateRandomContacts(integer noOfContact, String lastName)
    {
        List<Contact> con=New list<Contact>();
        for(Integer i=0;i<noOfContact;i++)
        {
            Contact c = new Contact(FirstName='Ank' + i,LastName=lastName);
            Con.add(c);
        }

        // insert con;

        Return con;
    }

}
```

Asynchronous Apex

Use Future Methods

AccountProcessor

```
public class AccountProcessor
{
    @future
    public static void countContacts(Set<id> setId)
    {
```

```

    List<Account> lstAccount = [select id,Number_of_Contacts__c , (select id from contacts ) from account where id
in :setId ];
    for( Account acc : lstAccount )
    {
        List<Contact> lstCont = acc.contacts ;

        acc.Number_of_Contacts__c = lstCont.size();
        system.debug(' acc.Number_of_Contacts__c ');
    }
    update lstAccount;
}
}

```

AccountProcessorTest

```

@Test
public class AccountProcessorTest {
    public static testmethod void TestAccountProcessorTest()
    {
        Account a = new Account();
        a.Name = 'Test Account';
        Insert a;

        Contact cont = New Contact();
        cont.FirstName ='Bob';
        cont.LastName ='Masters';
        cont.AccountId = a.Id;
        Insert cont;

        set<Id> setAccId = new Set<ID>();
        setAccId.add(a.id);

        Test.startTest();
        AccountProcessor.countContacts(setAccId);
        Test.stopTest();

        Account ACC = [select Number_of_Contacts__c from Account where id = :a.id];
        System.assertEquals ( Integer.valueOf(ACC.Number_of_Contacts__c ),1);
    }
}

```

Use Batch Apex

LeadProcessor

```

public class LeadProcessor implements
    Database.Batchable<sObject>, Database.Stateful {
    // instance member to retain state across transactions
    public Integer recordsProcessed = 0;

```

```

public Database.QueryLocator start(Database.BatchableContext bc) {
    return Database.getQueryLocator('SELECT ID, LeadSource from Lead');
}

public void execute(Database.BatchableContext bc, List<Lead> scope){
    // process each batch of records
    // List<Lead> llist = new List<Lead>();
    for (Lead llist : scope) {
        llist.leadsource='Dreamforce';

    }

    update scope;
}

public void finish(Database.BatchableContext bc){

}

}

```

LeadProcessorTest

```

@Test
public class LeadProcessorTest {
    @testSetup
    static void setup() {
        List<Lead> llist = new List<Lead>();
        // insert 10 accounts
        for (Integer i=0;i<200;i++) {
            llist.add(new Lead(FirstName='Lead '+i,LastName='last', Company ='demo'+i));
        }
        insert llist;
        // find the account just inserted. add contact for each
    }

    @isTest static void test() {
        Test.startTest();
        LeadProcessor lpt = new LeadProcessor();
        Id batchId = Database.executeBatch(lpt);
        Test.stopTest();
        // after the testing stops, assert records were updated properly
        System.assertEquals(200, [select count() from lead where Leadsource = 'Dreamforce']);
    }
}

```

Control Processes with Queueable Apex

AddPrimaryContact

public class AddPrimaryContact implements Queueable

```
{
    private Contact c;
    private String state;
    public AddPrimaryContact(Contact c, String state)
    {
        this.c = c;
        this.state = state;
    }
    public void execute(QueueableContext context)
    {
        List<Account> ListAccount = [SELECT ID, Name ,(Select id,FirstName,LastName from contacts ) FROM
ACCOUNT WHERE BillingState = :state LIMIT 200];
        List<Contact> lstContact = new List<Contact>();
        for (Account acc:ListAccount)
        {
            Contact cont = c.clone(false,false,false,false);
            cont.AccountId = acc.id;
            lstContact.add( cont );
        }

        if(lstContact.size() >0 )
        {
            insert lstContact;
        }

    }
}
```

AddPrimaryContactTest

@isTest

public class AddPrimaryContactTest

```
{
    @isTest static void TestList()
    {
        List<Account> Teste = new List <Account>();
        for(Integer i=0;i<50;i++)
        {
            Teste.add(new Account(BillingState = 'CA', name = 'Test'+i));
        }
        for(Integer j=0;j<50;j++)
        {
            Teste.add(new Account(BillingState = 'NY', name = 'Test'+j));
        }
        insert Teste;
    }
}
```



```

Contact co = new Contact();
co.FirstName='demo';
co.LastName = 'demo';
insert co;
String state = 'CA';

AddPrimaryContact apc = new AddPrimaryContact(co, state);
Test.startTest();
    System.enqueueJob(apc);
Test.stopTest();
}
}

```

Schedule Jobs Using the Apex Scheduler

DailyLeadProcessor

```

global class DailyLeadProcessor implements Schedulable {

    global void execute(SchedulableContext ctx) {
        List<Lead> lList = [Select Id, LeadSource from Lead where LeadSource = null];

        if(!lList.isEmpty()) {
            for(Lead l: lList) {
                l.LeadSource = 'Dreamforce';
            }
            update lList;
        }
    }
}

```

DailyLeadProcessorTest

```

@isTest
private class DailyLeadProcessorTest {
    static testMethod void testDailyLeadProcessor() {
        String CRON_EXP = '0 0 1 * * ?';
        List<Lead> lList = new List<Lead>();
        for (Integer i = 0; i < 200; i++) {
            lList.add(new Lead(LastName='Dreamforce'+i, Company='Test1 Inc.', Status='Open -
Not Contacted'));
        }
        insert lList;

        Test.startTest();
        String jobId = System.schedule('DailyLeadProcessor', CRON_EXP, new DailyLeadProcessor());
    }
}

```

Apex Integration Services

Apex REST Callouts

AnimalLocator

```
public with sharing class AnimalLocator {

    public static String getAnimalNameById(Integer animalNameId) {
        String animalName = "";
        //New Http 'GET' Request
        Http http = new Http();
        HttpRequest request = new HttpRequest();
        request.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/:id');
        request.setHeader('Content-Type', 'application/json;charset=UTF-8');
        request.setMethod('GET');
        //Get response
        HttpResponse response = Http.send(request);
        //Parse JSON from the response body
        JSONParser parser = JSON.createParser(response.getBody());
        while (parser.nextToken() != null) {
            // Read entire JSON object
            if (parser.getCurrentToken() == JSONToken.START_OBJECT) {
                AnimalLocator.AnimalList animalList = (AnimalLocator.AnimalList)
parser.readValueAs(ApexLocator.AnimalList.class);
                System.debug(animalList.animal.size());
                //Sort through the list of animals to find one with the matching ID
                //Set the animal name
                for (Integer i = 0; i < animalList.animal.size() ; i++) {
                    if (animalList.animal[i].id == animalNameId){
                        animalName = animalList.animal[i].name;
                        break;
                    } else{
                        animalName = 'Could not find an Animal with a matching ID';
                    }
                }
            }
        }
        return animalName;
    }

    public class AnimalList {
        public List<animal> animal; //This has to be the same name thats in the JSON file.
    }

    //animal Object Wrapper
    public class animal {
        public Integer id;
        public String name;
    }
}
```

```

        public String eats;
        public String says;
    }

}

```

AnimalLocatorTest

```

@Test
public with sharing class AnimalLocatorTest {
    @Test
    static void testGetCallout() {
        Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
        String result = AnimalLocator.getAnimalNameById(1);
        String expectedResult = 'Chicken';
        System.assertEquals(result, expectedResult);
        result = AnimalLocator.getAnimalNameById(4);
        expectedResult = 'Could not find an Animal with a matching ID';
        System.assertEquals(result, expectedResult);
    }
}

```

AnimalLocatorMock

```

@Test
global class AnimalLocatorMock implements HttpCalloutMock{
    global HttpResponse respond(HttpRequest request){
        //Create Fake Response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json;charset=UTF-8');
        response.getStatusCode(200);
        response.setBody('
{"animal":[{"id":1,"name":"Chicken","eats":"Grain","says":"Cluck"},{"id":2,"name":"Dog","eats":"Chicken","says":
"Woof"}]} ');
        return response;
    }
}

```

Apex SOAP Callouts

ParkLocator

```

public class ParkLocator {
    public static string[] country(String country) {
        parkService.parksImplPort park = new parkService.parksImplPort();
        return park.byCountry(country);
    }
}

```

ParkLocatorTest

```

@Test

```

```

private class ParkLocatorTest {
    @isTest static void testCallout() {
        // This causes a fake response to be generated
        Test.setMock(WebServiceMock.class, new ParkServiceMock());
        // Call the method that invokes a callout
        //Double x = 1.0;
        //Double result = AwesomeCalculator.add(x, y);

        String country = 'Germany';
        String[] result = ParkLocator.Country(country);

        // Verify that a fake result is returned
        System.assertEquals(new List<String>{'Hamburg Wadden Sea National Park', 'Hainich National Park',
'Bavarian Forest National Park'}, result);
    }
}

```

ParkServiceMock

```

@isTest
global class ParkServiceMock implements WebServiceMock {
    global void doInvoke(
        Object stub,
        Object request,
        Map<String, Object> response,
        String endpoint,
        String soapAction,
        String requestName,
        String responseNS,
        String responseName,
        String responseType) {
        // start - specify the response you want to send
        parkService.byCountryResponse response_x = new parkService.byCountryResponse();
        response_x.return_x = new List<String>{'Hamburg Wadden Sea National Park', 'Hainich National Park',
'Bavarian Forest National Park'};

        //calculatorServices.doAddResponse response_x = new calculatorServices.doAddResponse();
        //response_x.return_x = 3.0;
        // end
        response.put('response_x', response_x);
    }
}

```

Apex Web Services

AccountManager

```

@RestResource(urlMapping='/Accounts/*/contacts')
global with sharing class AccountManager {

```

```

@HttpGet
global static account getAccount() {

    RestRequest request = RestContext.request;

    String accountId = request.requestURI.substring(request.requestURI.lastIndexOf('/')-18,
        request.requestURI.lastIndexOf('/'));
    List<Account> a = [select id, name, (select id, name from contacts) from account where id = :accountId];
    List<contact> co = [select id, name from contact where account.id = :accountId];
    system.debug('** a[0]= ' + a[0]);
    return a[0];

}

}

```

AccountManagerTest

```

@istest
public class AccountManagerTest {
    @istest static void testGetContactsByAccountId() {
        Id recordId = createTestRecord();
        // Set up a test request
        RestRequest request = new RestRequest();
        request.requestUri =
            'https://yourInstance.salesforce.com/services/apexrest/Accounts/'+ recordId+'/Contacts';
        request.httpMethod = 'GET';
        RestContext.request = request;

        Account thisAccount = AccountManager.getAccount();
        System.assert(thisAccount!= null);
        System.assertEquals('Test record', thisAccount.Name);
    }

    // Helper method
    static Id createTestRecord() {

        // Create test record
        Account accountTest = new Account(
            Name='Test record');
        insert accountTest;
        Contact contactTest = new Contact(
            FirstName='John',
            LastName='Doe',
            AccountId=accountTest.Id
        );
        return accountTest.Id;
    }
}

```

PROCESS AUTOMATION SPECIALIST SUPERBADGE

Automata leads

error condition formula

```
OR(AND(LEN(State) > 2,  
NOT(CONTAINS("AL:AK:AZ:AR:CA:CO:CT:DE:DC:FL:GA:HI:ID:IL:IN:IA:KS:KY:LA:ME:MD:MA:MI:MN:MS:MO:MT:NE:NV:NH:NJ:NM:NY:NC:ND:OH:OK:OR:PA:RI:SC:SD:TN:TX:UT:VT:VA:WA:WV:WI:WY", State )) ), NOT(OR(Country = "US",Country = "USA",Country = "United States", ISBLANK(Country))))
```

Automate accounts

error condition formula1

```
OR(AND(LEN(BillingState) > 2,  
NOT(CONTAINS("AL:AK:AZ:AR:CA:CO:CT:DE:DC:FL:GA:HI:ID:IL:IN:IA:KS:KY:LA:ME:MD:MA:MI:MN:MS:MO:MT:NE:NV:NH:NJ:NM:NY:NC:ND:OH:OK:OR:PA:RI:SC:SD:TN:TX:UT:VT:VA:WA:WV:WI:WY", BillingState ))  
,AND(LEN(ShippingState) > 2,  
NOT(CONTAINS("AL:AK:AZ:AR:CA:CO:CT:DE:DC:FL:GA:HI:ID:IL:IN:IA:KS:KY:LA:ME:MD:MA:MI:MN:MS:MO:MT:NE:NV:NH:NJ:NM:NY:NC:ND:OH:OK:OR:PA:RI:SC:SD:TN:TX:UT:VT:VA:WA:WV:WI:WY", ShippingState))  
,NOT(OR(BillingCountry = "US",BillingCountry = "USA",BillingCountry = "United States", ISBLANK(BillingCountry))),  
NOT(OR(ShippingCountry = "US",ShippingCountry = "USA",ShippingCountry = "United States", ISBLANK(ShippingCountry))))  
error condition formula1  
ISCHANGED( Name ) && ( OR( ISPICKVAL( Type , 'Customer - Direct' ) ,ISPICKVAL( Type , 'Customer - Channel' ) ) )
```

Automata steps

formula

```
Case ( WEEKDAY( Date__c ),  
1, "Sunday",  
2, "Monday",  
3, "Tuesday",  
4, "Wednesday",  
5, "Thursday",  
6, "Friday",  
7, "Saturday",  
Text(WEEKDAY(Date__c)))
```

