

## APEX TRIGGERS

### \*GET STARTED WITH APEX TRIGGERS:

#### 1.AccountAddressTrigger.apxt

```
trigger AccountAddressTrigger on Account (before insert, before update) {  
    for(Account account:Trigger.New){  
        if(account.Match_Billing_Address__c == True){  
            account.ShippingPostalCode = account.BillingPostalCode;  
        }  
    }  
}
```

### \*BULK APEX TRIGGERS:

#### 1.ClosedOpportunityTrigger.apxt

```
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {  
  
    List<Task> tasklist = new List<Task>();  
  
    for(Opportunity opp : Trigger.New){  
        if(opp.StageName == 'Closed Won'){  
            taskList.add(new Task(Subject = 'Follow Up Test Task', WhatId =opp.Id ));  
        }  
    }  
    if(taskList.size()>0){  
        insert taskList;  
    }  
}
```

## APEX TESTING

### \*GET STARTED WITH APEX UNIT TEST:

#### 1. VerifyDate.apxc

```
public class VerifyDate {  
  
    //method to handle potential checks against two dates  
    public static Date CheckDates(Date date1, Date date2) {  
        //if date2 is within the next 30 days of date1, use date2. Otherwise use  
the end of the month  
        if(DateWithin30Days(date1,date2)) {  
            return date2;  
        } else {  
            return SetEndOfMonthDate(date1);  
        }  
    }  
  
    //method to check if date2 is within the next 30 days of date1  
    private static Boolean DateWithin30Days(Date date1, Date date2) {  
        //check for date2 being in the past  
        if( date2 < date1) { return false; }  
  
        //check that date2 is within (>=) 30 days of date1  
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1  
        if( date2 >= date30Days ) { return false; }  
        else { return true; }  
    }  
  
    //method to return the end of the month of a given date  
    private static Date SetEndOfMonthDate(Date date1) {
```

```

        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
        Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
        return lastDay;
    }
}

```

## 2.TestVerifyDate.apxc

@isTest

public class TestVerifyDate {

@isTest static void test1(){

Date d=

VerifyDate.CheckDates(Date.parse('01/01/2020'),Date.parse('01/03/2020'));

System.assertEquals(Date.parse('01/03/2020'), d);

}

@isTest static void test2(){

Date d=

VerifyDate.CheckDates(Date.parse('01/01/2020'),Date.parse('03/03/2020'));

System.assertEquals(Date.parse('01/31/2020'), d);

}

}

## \*TEST APEX TRIGGERS:

### 1.RestrictContactByName.apxt

trigger RestrictContactByName on Contact (before insert, before update) {

//check contacts prior to insert or update for invalid data

For (Contact c : Trigger.New) {

```

        if(c.LastName == 'INVALIDNAME') { //invalidname is invalid
            c.AddError('The Last Name "'+c.LastName+'" is not allowed for DML');
        }
    }
}

```

\*CREATE TEST DATA FOR APEX TESTS:

1.RandomContactFactory.apxc

```

public class RandomContactFactory {

    public static List<Contact> generateRandomContacts(Integer numcnt, string
lastname){
        List<Contact> contact = new List<Contact>();
        for(Integer i=0;i<numcnt;i++){
            Contact cnt = new Contact(Firstname = 'Test'+i, LastName = lastname);
            contact.add(cnt);
        }
        return contact;
    }
}

```

ASYNCHRONOUS APEX

\*USE FUTURE METHODS:

1.AccountProcessor.apxc

```

public class AccountProcessor
{
    @future
    public static void countContacts(Set<id> setId)
    {
        List<Account> lstAccount = [select id,Number_of_Contacts__c , (select id from
contacts ) from account where id in :setId ];
        for( Account acc : lstAccount )
        {
            List<Contact> lstCont = acc.contacts ;

            acc.Number_of_Contacts__c = lstCont.size();
        }
        update lstAccount;
    }
}

```

## 2.AccountProcessorTest.apxc

```

@IsTest
public class AccountProcessorTest {
    public static testmethod void TestAccountProcessorTest()
    {
        Account a = new Account();
        a.Name = 'Test Account';
        Insert a;

        Contact cont = New Contact();
        cont.FirstName = 'Bob';
        cont.LastName = 'Masters';
        cont.AccountId = a.Id;
        Insert cont;

        set<Id> setAcId = new Set<ID>();
        setAcId.add(a.id);

        Test.startTest();
        AccountProcessor.countContacts(setAcId);
    }
}

```

```

Test.stopTest();

Account ACC = [select Number_of_Contacts__c from Account where id = :a.id LIMIT
1];
System.assertEquals ( Integer.valueOf(ACC.Number_of_Contacts__c) ,1);
}

}

```

\*USE BATCH APEX:

```

1.LeadProcessor.apxc
global class LeadProcessor implements
Database.Batchable<sObject>, Database.Stateful {

    // instance member to retain state across transactions
    global Integer recordsProcessed = 0;

    global Database.QueryLocator start(Database.BatchableContext bc) {
        return Database.getQueryLocator('SELECT Id, LeadSource FROM Lead');
    }

    global void execute(Database.BatchableContext bc, List<Lead> scope){
        // process each batch of records
        List<Lead> leads = new List<Lead>();
        for (Lead lead : scope) {

            lead.LeadSource = 'Dreamforce';
            // increment the instance member counter
            recordsProcessed = recordsProcessed + 1;

        }
        update leads;
    }
}

```

```

global void finish(Database.BatchableContext bc){
    System.debug(recordsProcessed + ' records processed. Shazam!');
}
}

```

## 2.LeadProcessorTest.apxc

```

@isTest
public class LeadProcessorTest {
    @testSetup
    static void setup() {
        List<Lead> leads = new List<Lead>();
        // insert 200 leads
        for (Integer i=0;i<200;i++) {
            leads.add(new Lead(LastName='Lead '+i,
                               Company='Lead', Status='Open - Not Contacted'));
        }
        insert leads;
    }

    static testmethod void test() {
        Test.startTest();
        LeadProcessor lp = new LeadProcessor();
        Id batchId = Database.executeBatch(lp, 200);
        Test.stopTest();

        // after the testing stops, assert records were updated properly
        System.assertEquals(200, [select count() from lead where LeadSource =
'Dreamforce']);
    }
}

```

\*CONTROL PROCESSES WITH QUEUEABLE APEX:

## 1.AddPrimaryContact.apxc

```
public class AddPrimaryContact implements Queueable{
    Contact con;
    String state;

    public AddPrimaryContact(Contact con, String state){
        this.con = con;
        this.state = state;
    }
    public void execute(QueueableContext qc){
        List<Account> lstOfAccs = [SELECT Id FROM Account WHERE BillingState = :state
LIMIT 200];

        List<Contact> lstOfConts = new List<Contact>();
        for(Account acc : lstOfAccs){
            Contact conInst = con.clone(false,false,false,false);
            conInst.AccountId = acc.Id;

            lstOfConts.add(conInst);
        }

        INSERT lstOfConts;
    }
}
```

## 2.AddPrimaryContactTest.apxc

```
@isTest
public class AddPrimaryContactTest{
    @testSetup
    static void setup(){
        List<Account> lstOfAcc = new List<Account>();
        for(Integer i = 1; i <= 100; i++){
            if(i <= 50)
                lstOfAcc.add(new Account(name='AC'+i, BillingState = 'NY'));
            else
                lstOfAcc.add(new Account(name='AC'+i, BillingState = 'CA'));
        }
    }
}
```



```

        INSERT IstOfAcc;
    }

    static testmethod void testAddPrimaryContact(){
        Contact con = new Contact(LastName = 'TestCont');
        AddPrimaryContact addPCIns = new AddPrimaryContact(CON,'CA');

        Test.startTest();
        System.enqueueJob(addPCIns);
        Test.stopTest();

        System.assertEquals(50, [select count() from Contact]);
    }
}

```

\*SCHEDULE JOBS USING APEX SCHEDULER:

1.DailyLeadProcessor.apxc

```

global class DailyLeadProcessor implements Schedulable{
    global void execute(SchedulableContext ctx){
        List<Lead> leads = [SELECT Id, LeadSource FROM Lead WHERE LeadSource = "];

        if(leads.size() > 0){
            List<Lead> newLeads = new List<Lead>();

            for(Lead lead : leads){
                lead.LeadSource = 'DreamForce';
                newLeads.add(lead);
            }

            update newLeads;
        }
    }
}

```

```
}
```

2.DailyLeadProcessorTest.apxc

@isTest

```
private class DailyLeadProcessorTest{
```

```
    //Seconds Minutes Hours Day_of_month Month Day_of_week optional_year
```

```
    public static String CRON_EXP = '0 0 0 2 6 ? 2022';
```

```
    static testmethod void testScheduledJob(){
```

```
        List<Lead> leads = new List<Lead>();
```

```
        for(Integer i = 0; i < 200; i++){
```

```
            Lead lead = new Lead(LastName = 'Test ' + i, LeadSource = '', Company = 'Test  
Company ' + i, Status = 'Open - Not Contacted');
```

```
            leads.add(lead);
```

```
        }
```

```
        insert leads;
```

```
        Test.startTest();
```

```
        // Schedule the test job
```

```
        String jobId = System.schedule('Update LeadSource to DreamForce', CRON_EXP,  
new DailyLeadProcessor());
```

```
        // Stopping the test will run the job synchronously
```

```
        Test.stopTest();
```

```
    }
```

```
}
```

APEX INTEGRATION SERVICES

\*APEX REST CALLOUTS:

## 1. AnimalLocator.apxc

```
public class AnimalLocator
{

    public static String getAnimalNameById(Integer id)
    {
        Http http = new Http();
        HttpRequest request = new HttpRequest();
        request.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/'+id);
        request.setMethod('GET');
        HttpResponse response = http.send(request);
        String strResp = "";
        system.debug('*****response '+response.getStatusCode());
        system.debug('*****response '+response.getBody());
        // If the request is successful, parse the JSON response.
        if (response.getStatusCode() == 200)
        {
            // Deserializes the JSON string into collections of primitive data types.
            Map<String, Object> results = (Map<String, Object>)
JSON.deserializeUntyped(response.getBody());
            // Cast the values in the 'animals' key as a list
            Map<string,object> animals = (map<string,object>) results.get('animal');
            System.debug('Received the following animals:' + animals );
            strResp = string.valueOf(animals.get('name'));
            System.debug('strResp >>>>>' + strResp );
        }
        return strResp ;
    }

}
```

## 2. AnimalLocatorMock.apxc

```
@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
    global HTTPResponse respond(HTTPRequest request) {
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
```

```

        response.setBody("{\"animal\":{\"id\":1,\"name\":\"chicken\",\"eats\":\"chicken
food\",\"says\":\"cluck cluck\"}}");
        response.setStatusCode(200);
        return response;
    }
}

```

### 3. AnimalLocatorTest.apxc

@isTest

```

private class AnimalLocatorTest{
    @isTest static void AnimalLocatorMock1() {
        Test.SetMock(HttpCallOutMock.class, new AnimalLocatorMock());
        string result=AnimalLocator.getAnimalNameById(3);
        string expectedResult='chicken';
        System.assertEquals(result, expectedResult);
    }
}

```

\*APEX SOAP CALLOUTS:

### 1. ParkService.apxc

//Generated by wsdl2apex

```

public class ParkService {
    public class byCountryResponse {
        public String[] return_x;
        private String[] return_x_type_info = new
String[]{'return','http://parks.services/',null,'0','-1','false'};
        private String[] apex_schema_type_info = new
String[]{'http://parks.services/',false,false'};
        private String[] field_order_type_info = new String[]{'return_x'};
    }
    public class byCountry {
        public String arg0;
    }
}

```

```

        private String[] arg0_type_info = new
String[]{arg0,'http://parks.services/',null,'0','1','false'};
        private String[] apex_schema_type_info = new
String[]{http://parks.services/,'false','false'};
        private String[] field_order_type_info = new String[]{arg0};
    }
    public class ParksImplPort {
        public String endpoint_x = 'https://th-apex-soap-
service.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public Map<String,String> outputHttpHeaders_x;
        public String clientCertName_x;
        public String clientCert_x;
        public String clientCertPasswd_x;
        public Integer timeout_x;
        private String[] ns_map_type_info = new String[]{http://parks.services/,
'ParkService'};
        public String[] byCountry(String arg0) {
            ParkService.byCountry request_x = new ParkService.byCountry();
            request_x.arg0 = arg0;
            ParkService.byCountryResponse response_x;
            Map<String, ParkService.byCountryResponse> response_map_x = new
Map<String, ParkService.byCountryResponse>();
            response_map_x.put('response_x', response_x);
            WebServiceCallout.invoke(
                this,
                request_x,
                response_map_x,
                new String[]{endpoint_x,
                    "",
                    'http://parks.services/',
                    'byCountry',
                    'http://parks.services/',
                    'byCountryResponse',
                    'ParkService.byCountryResponse'}
            );
            response_x = response_map_x.get('response_x');

```

```

        return response_x.return_x;
    }
}

```

## 2.ParkServiceMock.apxc

@isTest

global class ParkServiceMock implements WebServiceMock {

```

    global void doInvoke(
        Object stub,
        Object request,
        Map<String, Object> response,
        String endpoint,
        String soapAction,
        String requestName,
        String responseNS,
        String responseName,
        String responseType) {
        ParkService.byCountryResponse response_x = new
ParkService.byCountryResponse();
        List<String> lstofDummyParks = new List<String> {'Park1','Park2','Park3'};
        response_x.return_x = lstofDummyParks;

        response.put('response_x', response_x);
    }
}

```

## 3.ParkLocatorTest.apxc

@isTest

private class ParkLocatorTest{

@isTest

```

    static void testParkLocator() {
        Test.setMock(WebServiceMock.class, new ParkServiceMock());
        String[] arrayOfParks = ParkLocator.country('India');

        System.assertEquals('Park1', arrayOfParks[0]);
    }
}

```

```
}
```

## \*APEX WEB SERVICES:

### 1.AccountManager.apxc

```
@RestResource(urlMapping='/Accounts/*/contacts')
global with sharing class AccountManager{
    @HttpGet
    global static Account getAccount(){
        RestRequest req = RestContext.request;
        String accId = req.requestURI.substringBetween('Accounts/', '/contacts');
        Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
                        FROM Account WHERE Id = :accId];

        return acc;
    }
}
```

### 2.AccountManagerTest.apxc

```
@IsTest
private class AccountManagerTest{
    @isTest static void testAccountManager(){
        Id recordId = getTestAccountId();
        // Set up a test request
        RestRequest request = new RestRequest();
        request.requestUri =
            'https://ap5.salesforce.com/services/apexrest/Accounts/'+ recordId +'/contacts';
        request.httpMethod = 'GET';
        RestContext.request = request;

        // Call the method to test
        Account acc = AccountManager.getAccount();
    }
}
```

```

        // Verify results
        System.assert(acc != null);
    }

    private static Id getTestAccountId(){
        Account acc = new Account(Name = 'TestAcc2');
        Insert acc;

        Contact con = new Contact(LastName = 'TestCont2', AccountId = acc.Id);
        Insert con;

        return acc.Id;
    }
}

```

## APEX SPECIALIST SUPERBADGE

### \*AUTOMATE RECORD CREATION:

```

1)MaintenanceRequest.apxt
trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```

```

2)MaintenanceRequestHelper.apxc
public with sharing class MaintenanceRequestHelper {
    public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){

```



```

        if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
            if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                validIds.add(c.Id);
            }
        }
    }

    if (!validIds.isEmpty()){
        List<Case> newCases = new List<Case>();
        Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
        Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
        AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds GROUP
BY Maintenance_Request__c];

        for (AggregateResult ar : results){
            maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
        }

        for(Case cc : closedCasesM.values()){
            Case nc = new Case (
                ParentId = cc.Id,
                Status = 'New',
                Subject = 'Routine Maintenance',
                Type = 'Routine Maintenance',
                Vehicle__c = cc.Vehicle__c,
                Equipment__c =cc.Equipment__c,
                Origin = 'Web',
                Date_Reported__c = Date.Today()

            );

```

```

        If (maintenanceCycles.containsKey(cc.Id)){
            nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
        }

        newCases.add(nc);
    }

    insert newCases;

    List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
    for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
            Equipment_Maintenance_Item__c wpClone = wp.clone();
            wpClone.Maintenance_Request__c = nc.Id;
            ClonedWPs.add(wpClone);

        }
    }
    insert ClonedWPs;
}
}
}

```

\*SYNCHRONIZATION SALESFORCE DATA WITH AN EXTERNAL SYSTEM:

1) WarehouseCalloutService.apxc

```
public with sharing class WarehouseCalloutService {
```

```

    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

```

```

//@future(callout=true)
public static void runWarehouseEquipmentSync(){

    Http http = new Http();
    HttpRequest request = new HttpRequest();

    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);

    List<Product2> warehouseEq = new List<Product2>();

    if (response.getStatusCode() == 200){
        List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
        System.debug(response.getBody());

        for (Object eq : jsonResponse){
            Map<String,Object> mapJson = (Map<String,Object>)eq;
            Product2 myEq = new Product2();
            myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
            myEq.Name = (String) mapJson.get('name');
            myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
            myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
            myEq.Cost__c = (Decimal) mapJson.get('lifespan');
            myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
            myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
            warehouseEq.add(myEq);
        }

        if (warehouseEq.size() > 0){
            upsert warehouseEq;
            System.debug('Your equipment was synced with the warehouse one');
            System.debug(warehouseEq);
        }
    }
}

```

```
    }  
  }  
}
```

#### \*SCHEDULE SYNCHRONIZATION USING APEX CODE:

```
1)WarehouseSyncSchedule.apxc  
global class WarehouseSyncSchedule implements Schedulable {  
    global void execute(SchedulableContext ctx) {  
  
        WarehouseCalloutService.runWarehouseEquipmentSync();  
    }  
}
```

#### \*TEST AUTOMATION LOGIC:

```
1)MaintenanceRequestHelperTest.apxc  
@istest  
public with sharing class MaintenanceRequestHelperTest {  
  
    private static final string STATUS_NEW = 'New';  
    private static final string WORKING = 'Working';  
    private static final string CLOSED = 'Closed';  
    private static final string REPAIR = 'Repair';  
    private static final string REQUEST_ORIGIN = 'Web';  
    private static final string REQUEST_TYPE = 'Routine Maintenance';  
    private static final string REQUEST_SUBJECT = 'Testing subject';  
  
    PRIVATE STATIC Vehicle__c createVehicle(){  
        Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');  
        return Vehicle;  
    }  
}
```

```

PRIVATE STATIC Product2 createEq(){
    product2 equipment = new product2(name = 'SuperEquipment',
        lifespan_months__C = 10,
        maintenance_cycle__C = 10,
        replacement_part__c = true);
    return equipment;
}

```

```

PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
        Status=STATUS_NEW,
        Origin=REQUEST_ORIGIN,
        Subject=REQUEST_SUBJECT,
        Equipment__c=equipmentId,
        Vehicle__c=vehicleId);
    return cs;
}

```

```

PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
    Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
        Maintenance_Request__c = requestId);
    return wp;
}

```

```

@istest
private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;

    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
}

```

```
insert somethingToUpdate;
```

```
Equipment_Maintenance_Item__c workP =  
createWorkPart(equipmentId,somethingToUpdate.id);  
insert workP;
```

```
test.startTest();  
somethingToUpdate.status = CLOSED;  
update somethingToUpdate;  
test.stopTest();
```

```
Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c,  
Vehicle__c, Date_Due__c  
from case  
where status =:STATUS_NEW];
```

```
Equipment_Maintenance_Item__c workPart = [select id  
from Equipment_Maintenance_Item__c  
where Maintenance_Request__c =:newReq.Id];
```

```
system.assert(workPart != null);  
system.assert(newReq.Subject != null);  
system.assertEquals(newReq.Type, REQUEST_TYPE);  
SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);  
SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);  
SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());  
}
```

```
@istest  
private static void testMaintenanceRequestNegative(){  
    Vehicle__C vehicle = createVehicle();  
    insert vehicle;  
    id vehicleId = vehicle.Id;  
  
    product2 equipment = createEq();  
    insert equipment;  
    id equipmentId = equipment.Id;
```

```
case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
insert emptyReq;
```

```
Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,
emptyReq.Id);
insert workP;
```

```
test.startTest();
emptyReq.Status = WORKING;
update emptyReq;
test.stopTest();
```

```
list<case> allRequest = [select id
                        from case];
```

```
Equipment_Maintenance_Item__c workPart = [select id
                                           from Equipment_Maintenance_Item__c
                                           where Maintenance_Request__c = :emptyReq.Id];
```

```
system.assert(workPart != null);
system.assert(allRequest.size() == 1);
}
```

```
@istest
```

```
private static void testMaintenanceRequestBulk(){
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();
```

```
    for(integer i = 0; i < 300; i++){
        vehicleList.add(createVehicle());
        equipmentList.add(createEq());
    }
```

```
    insert vehicleList;
    insert equipmentList;
```

```

    for(integer i = 0; i < 300; i++){
        requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    }
    insert requestList;

    for(integer i = 0; i < 300; i++){
        workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
    }
    insert workPartList;

    test.startTest();
    for(case req : requestList){
        req.Status = CLOSED;
        oldRequestIds.add(req.Id);
    }
    update requestList;
    test.stopTest();

    list<case> allRequests = [select id
                            from case
                            where status =: STATUS_NEW];

    list<Equipment_Maintenance_Item__c> workParts = [select id
                                                    from Equipment_Maintenance_Item__c
                                                    where Maintenance_Request__c in: oldRequestIds];

    system.assert(allRequests.size() == 300);
}
}

```

2)MaintenanceRequestHelper.apxc

```

public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();
    }
}

```



```

For (Case c : updWorkOrders){
    if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
            validIds.add(c.Id);
        }
    }
}

if (!validIds.isEmpty()){
    List<Case> newCases = new List<Case>();
    Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
    AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds GROUP
BY Maintenance_Request__c];

    for (AggregateResult ar : results){
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }

    for(Case cc : closedCasesM.values()){
        Case nc = new Case (
            ParentId = cc.Id,
            Status = 'New',
            Subject = 'Routine Maintenance',
            Type = 'Routine Maintenance',
            Vehicle__c = cc.Vehicle__c,
            Equipment__c =cc.Equipment__c,
            Origin = 'Web',
            Date_Reported__c = Date.Today()

```

```

);

    If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
    }

    newCases.add(nc);
}

insert newCases;

List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
        Equipment_Maintenance_Item__c wpClone = wp.clone();
        wpClone.Maintenance_Request__c = nc.Id;
        ClonedWPs.add(wpClone);
    }
}
insert ClonedWPs;
}
}
}

```

### 3)MaintenanceRequest.apxt

```

trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```

\*TEST CALLOUT LOGIC:

1)WarehouseCalloutService.apxc

```
public with sharing class WarehouseCalloutService {
```

```
    private static final String WAREHOUSE_URL = 'https://th-superbadge-  
apex.herokuapp.com/equipment';
```

```
    //@future(callout=true)
```

```
    public static void runWarehouseEquipmentSync(){
```

```
        Http http = new Http();
```

```
        HttpRequest request = new HttpRequest();
```

```
        request.setEndpoint(WAREHOUSE_URL);
```

```
        request.setMethod('GET');
```

```
        HttpResponse response = http.send(request);
```

```
        List<Product2> warehouseEq = new List<Product2>();
```

```
        if (response.getStatusCode() == 200){
```

```
            List<Object> jsonResponse =
```

```
(List<Object>)JSON.deserializeUntyped(response.getBody());
```

```
            System.debug(response.getBody());
```

```
            for (Object eq : jsonResponse){
```

```
                Map<String,Object> mapJson = (Map<String,Object>)eq;
```

```
                Product2 myEq = new Product2();
```

```
                myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
```

```
                myEq.Name = (String) mapJson.get('name');
```

```
                myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
```

```
                myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
```

```
                myEq.Cost__c = (Decimal) mapJson.get('lifespan');
```

```
                myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
```

```

        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
    }

    if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
    }

}
}
}

```

2)WarehouseCalloutServiceTest.apxc

@isTest

```

private class WarehouseCalloutServiceTest {
    @isTest
    static void testWareHouseCallout(){
        Test.startTest();
        // implement mock callout test here
        Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.runWarehouseEquipmentSync();
        Test.stopTest();
        System.assertEquals(1, [SELECT count() FROM Product2]);
    }
}

```

3)WarehouseCalloutServiceMock.apxc

@isTest

```

global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request){

        System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
        System.assertEquals('GET', request.getMethod());
    }
}

```

```

// Create a fake response
HttpResponse response = new HttpResponse();
response.setHeader('Content-Type', 'application/json');

response.setBody(['{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5
,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}']);
response.setStatusCode(200);
return response;
}
}

```

\*TEST SCHEDULING LOGIC:

```

1)WarehouseSyncSchedule.apxc
global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

```

```

2)WarehouseSyncScheduleTest.apxc
@isTest
public class WarehouseSyncScheduleTest {

    @isTest static void WarehousescheduleTest(){
        String scheduleTime = '00 00 01 * * ?';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String jobId=System.schedule('Warehouse Time To Schedule to Test',
scheduleTime, new WarehouseSyncSchedule());
        Test.stopTest();
        //Contains schedule information for a scheduled job. CronTrigger is similar to a

```

cron job on UNIX systems.

// This object is available in API version 17.0 and later.

CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];

System.assertEquals(jobID, a.Id,'Schedule ');

}

}