

APEX SPECIALIST SUPER BADGE CODES

APEX TRIGGERS

AccountAddressTrigger.apxt

```
trigger AccountAddressTrigger on Account (before insert, before update) {

    for(Account account: Trigger.new){

        if(account.Match_Billing_Addressc == True){
            account.ShippingPostalCode = account.BillingPostalCode;
        }
    }

}
```

Explanation: AccountAddressTrigger is a apex trigger that sets an account's Shipping Postal Code to match the Billing Postal Code if the Match Billing Address option is selected. Fire the trigger before inserting an account or updating an account.

ClosedOpportunityTrigger.apxt

```
trigger ClosedOpportunityTrigger on Opportunity (afterinsert, after
update){ List<Task> tasklist = new List<Task>();

    for(Opportunity opp: Trigger.New){
        if(opp.StageName == 'Closed Won'){
            tasklist.add(new Task(Subject = 'Follow Up Test Task',WhatId = opp.Id));
        }
    }
    if(tasklist.size()>0){
        insert tasklist;
    }
}
```

Explanation: ClosedOpportunityTrigger is a apex trigger which fire trigger after inserting or updating an opportunity.

APEX TESTING

VerifyDate.apxc

APEX SPECIALIST SUPER BADGE CODES

```
public class VerifyDate {

    / method to handle potential checks against two dates
    public static Date CheckDates(Date date1, Date date2)
    {
        / if date2 is within the next 30 days of date1, use date2. Otherwise use the end
        of the month

        if(DateWithin30Days(date1,date2)) {
            return date2;
        } else {
            return SetEndOfMonthDate(date1);
        }
    }

    / method to check if date2 is within the next 30 days of date1
    @TestVisible private static Boolean DateWithin30Days(Date date1, Date date2) {
        / check for date2 being in the
        past if( date2 < date1) { return false; }

        / check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); / create a date 30 days away from
        date1 if( date2 >= date30Days ) { return false; }
        else { return true; }
    }

    / method to return the end of the month of a given date
    @TestVisible private static Date SetEndOfMonthDate(Date date1)
    {
        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
        Date lastDay = Date.newInstance(date1.year(), date1.month(),
        totalDays); return lastDay;
    }
}
```

TestVerifyDate.apxc

```
@isTest
private class TestVerifyDate {
    @isTest static void Test_CheckDates_case1(){
        Date D = VerifyDate.CheckDates(date.parse('01/01/2020'), date.parse('01/05/2020'));
        System.assertEquals(date.parse('01/05/2020'), D);
    }
}
```

APEX SPECIALIST SUPER BADGE CODES

```
@isTest static void Test_CheckDates_case2(){
    Date D = VerifyDate.CheckDates(date.parse('01/01/2020'), date.parse('05/05/2020'));
    System.assertEquals(date.parse('01/31/2020'),D);
}

@isTest static void Test_DateWithin30Days_case1(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('12/30/2019'));
    System.assertEquals(false, flag);
}

@isTest static void Test_DateWithin30Days_case2(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('02/02/2020'));
    System.assertEquals(false, flag);
}

@isTest static void Test_DateWithin30Days_case3(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('01/15/2020'));
    System.assertEquals(true, flag);
}

@isTest static void Test_SetEndOfMonthDate(){
    Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2020'));
}

}
```

Explanation:TestVerifyDate is a apex class to test if a date is within a proper range, and if not, returns a date that occurs at the end of the month within the range.

RestrictContactByName.apxc

```
trigger RestrictContactByName on Contact (before insert, before update) {

    / check contacts prior to insert or update for invalid
    data For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') { / invalidname is invalid
            c.AddError('The Last Name "' +c.LastName+" is not allowed for DML');
        }
    }
}
```

APEX SPECIALIST SUPER BADGE CODES

TestRestrictContactByName.apxc

```
@isTest
public class TestRestrictContactByName {

    @isTest static void Test_insertupdateContact(){
        Contact cnt = new Contact();
        cnt.LastName = 'INVALIDNAME';

        Test.startTest();
        Database.SaveResult result = Database.insert(cnt, false);
        Test.stopTest();

        System.assert(!result.isSuccess());
        System.assert(result.getErrors().size() > 0);
        System.assertEquals('The Last Name "INVALIDNAME" is not allowed for
DML',result.getErrors()[0].getMessage());
    }

}
```

Explanation:TestRestrictContactByName is a Apex trigger which blocks inserts and updates to any contact with a last name of 'INVALIDNAME'.

RandomContactFactory.apxc

```
public class RandomContactFactory {

    public static List<Contact> generateRandomContacts(Integer numcnt, String lastname){
        List<Contact> contacts = new List<Contact>();
        for(Integer i=0;i<numcnt;i++){
            Contact cnt = new Contact(FirstName = 'Test '+i, LastName = lastname);
            contacts.add(cnt);
        }
        return contacts;
    }

}
```

Explanation:RandomContactFactory is an Apex class that returns a list of contacts based on two incoming parameters: the number of contacts to generate and the last name.

APEX SPECIALIST SUPER BADGE CODES

Asynchronous Apex

AccountProcessor.apxc

```
public class AccountProcessor {
    @future
    public static void countContacts(List<Id> accountIds){
        List<Account> accountsToUpdate = new List<Account>();
        List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from Account
Where Id in :accountIds];

        For(Account acc:accounts){
            List<Contact> contactList = acc.Contacts;
            acc.Number_Of_Contactsc = contactList.size();
            accountsToUpdate.add(acc);
        }
        update accountsToUpdate;
    }
}
```

AccountProcessorTest.apxc

```
@IsTest
private class AccountProcessorTest
{ @IsTest
    Private static void testCountContacts(){
        Account newAccount = new Account(Name = 'Test Account');
        insert newAccount;

        Contact newContact1 = new Contact(FirstName='John',LastName='Doe',AccountId =
newAccount.Id);
        insert newContact1;

        Contact newContact2 = new Contact(FirstName='Jane',LastName='Doe',AccountId =
newAccount.Id);
        insert newContact2;

        List<Id> accountIds = new List<Id>();
        accountIds.add(newAccount.Id);
```

APEX SPECIALIST SUPER BADGE CODES

```
Test.startTest();
AccountProcessor.countContacts(accountIds);
Test.stopTest();
}

}
```

LeadProcessor.apxc

```
global class LeadProcessor implements Database.Batchable<sObject> {
    global Integer count=0;
    global Database.QueryLocator start(Database.BatchableContext bc){
        return Database.getQueryLocator('SELECT ID, LeadSource FROM
        Lead');
    }

    global void execute (Database.BatchableContext bc, List<Lead> L_list){
        List<lead> L_list_new = new List<Lead>();
        for(lead L:L_list){
            L.leadsource = 'Dreamforce';
            L_list_new.add(L);
            count += 1;
        }
        update L_list_new;
    }

    global void finish(Database.BatchableContext bc){
        System.debug('count = '+count);
    }

}
```

LeadProcessorTest.apxc

```
@isTest
public class LeadProcessorTest {
    @isTest
    public static void testit(){
        List<lead> L_list = new List<lead>();
```

APEX SPECIALIST SUPER BADGE CODES

```
for(Integer i=0;i<200;i++){
    Lead L = new lead();
    L.LastName = 'name' + i;
    L.Company = 'Company';
    L.Status = 'Random
    Status'; L_list.add(L);
}
insert L_list;

Test.startTest();
LeadProcessor lp = new
LeadProcessor(); Id batchId =
Database.executeBatch(lp);
Test.stopTest();
}

}
```

AddPrimaryContact.apxc

public class AddPrimaryContact implements

```
Queueable{ private Contact con;

private String state;
public AddPrimaryContact(Contact con, String
    State){ this.con = con;
    this.state = state;
}

public void execute(QueueableContext context){
    List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id from
contacts) from Account where BillingState = :state Limit 200];
    List<Contact> primaryContacts = new List<Contact>();
    for(Account acc:accounts){
        Contact c = con.clone();
        c.AccountId = acc.Id;
        primaryContacts.add(c);
    }

    if(primaryContacts.size() > 0){
        insert primaryContacts;
    }
}
```

APEX SPECIALIST SUPER BADGE CODES

```
}  
}  
}
```

AddPrimaryContactTest.apxc

```
@isTest  
public class AddPrimaryContactTest {  
    static testmethod void  
    testQueueable(){  
        List<Account> testAccounts = new List<Account>();  
        for(Integer i=0;i<50;i++){  
            testAccounts.add(new Account(Name='Account '+i,BillingState='CA'));  
        }  
        for(Integer j=0;j<50;j++){  
            testAccounts.add(new Account(Name='Account '+j,BillingState='NY'));  
        }  
        insert testAccounts;  
  
        Contact testContact = new Contact(FirstName = 'John', LastName =  
        'Doe'); insert testContact;  
        AddPrimaryContact addit = new addPrimaryContact(testContact,  
  
        'CA'); Test.startTest();  
  
        System.enqueueJob(addit);  
        Test.stopTest();  
        System.assertEquals(50,[Select count() from Contact where accountId in (Select Id from  
Account where BillingState='CA')]);  
    }  
}
```

DailyLeadProcessor.apxc

```
global class DailyLeadProcessor implements Schedulable{  
    global void execute(SchedulableContext ctx) {  
        List<Lead> leadstoupdate = new List<Lead>();  
        List<Lead> leads = [Select id From Lead Where LeadSource = NULL Limit 200];  
        for(Lead l: leads) {
```


APEX SPECIALIST SUPER BADGE CODES

```
        l.LeadSource = 'Dreamforce';
        leadstoupdate.add(l);
    }
    update leadstoupdate;
}
}
```

DailyLeadProcessorTest.apxc

```
@isTest
private class DailyLeadProcessorTest {
    public static String CRON_EXP = '0 0 0 15 3 ?
2024'; static testmethod void testScheduledJob() {
    List<Lead> leads = new List<Lead>();
    for(Integer i = 0; i < 200; i++) {
        Lead l = new Lead(
            FirstName = 'First' + i,
            LastName =
            'LastName', Company =
            'The Inc'
        );
        leads.add(l);
    }
    insert leads;
    Test.startTest();
    String jobId = System.schedule('ScheduledApexTest',CRON_EXP,new
        DailyLeadProcessor()); Test.stopTest();
    List<Lead> checkleads = new List<Lead>();
    checkleads = [Select Id From Lead Where LeadSource = 'Dreamforce' and Company = 'The
Inc'];
    System.assertEquals(200,checkleads.size(),'Leads were not created');
    }
}
```

Apex Integration Services

AnimalLocator.apxc

```
public class AnimalLocator{
```

APEX SPECIALIST SUPER BADGE CODES

```
public static String getAnimalNameById(Integer x){
    Http http = new Http();
    HttpRequest req = new HttpRequest();

    req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' +
x); req.setMethod('GET');
    Map<String, Object> animal= new Map<String, Object>();
    HttpResponse res = http.send(req);
    if (res.getStatusCode() == 200) {
        Map<String, Object> results = (Map<String,
Object>).JSON.deserializeUntyped(res.getBody());
        animal = (Map<String, Object>)
results.get('animal');
    }
    return (String)animal.get('name');
}
}
```

AnimalLocatorMock.apxc

```
@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
    / Implement this interface method
    global HTTPResponse respond(HTTPRequest request) {
        / Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type',
'application/json');
        response.setBody('{"animals": ["majestic badger", "fluffy bunny", "scary bear", "chicken",
"mighty moose"]}');
        response.getStatusCode(200);
        return response;
    }
}
```

AnimalLocatorTest.apxc

```
@isTest
private class AnimalLocatorTest{
    @isTest static void AnimalLocatorMock1() {
        Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
        string result = AnimalLocator.getAnimalNameById(3);
        String expectedResult = 'chicken';
        System.assertEquals(result,expectedResult );
    }
}
```

APEX SPECIALIST SUPER BADGE CODES

```
}  
}
```

ParkLocator.apxc

```
public class ParkLocator {  
    public static string[] country(String country) {  
        parkService.parksImplPort park = new  
        parkService.parksImplPort(); return park.byCountry(country);  
    }  
}
```

ParkLocatorMock.apxc

```
@isTest  
global class ParkServiceMock implements WebServiceMock {  
    global void doInvoke(  
        Object stub,  
        Object request,  
        Map<String, Object> response,  
        String endpoint,  
        String soapAction,  
        String requestName,  
        String responseNS,  
        String  
        responseName,  
        String responseType)  
    {  
        parkService.byCountryResponse response_x = new parkService.byCountryResponse();  
        response_x.return_x = new List<String>{'Hamburg Wadden Sea National Park', 'Hainich  
National Park', 'Bavarian Forest National Park'};  
        response.put('response_x', response_x);  
    }  
}
```

ParkLocatorTest.apxc

```
@isTest  
private class ParkLocatorTest {  
    @isTest static void testCallout() {  
        Test.setMock(WebServiceMock.class, new ParkServiceMock());  
        String country = 'Germany';  
        String[] result = ParkLocator.Country(country);  
    }  
}
```

APEX SPECIALIST SUPER BADGE CODES

```
        System.assertEquals(new List<String>{'Hamburg Wadden Sea National Park', 'Hainich  
National Park', 'Bavarian Forest National Park'}, result);  
    }  
}
```

AccountManager.apxc

```
@RestResource(urlMapping='/Accounts/*/contacts')  
global with sharing class AccountManager {
```

```
    @HttpGet  
    global static account getAccount() {  
  
        RestRequest request =  
  
        RestContext.request;  
  
        String accountId = request.requestURI.substring(request.requestURI.lastIndexOf('/')-18,  
            request.requestURI.lastIndexOf('/'));  
        List<Account> a = [select id, name, (select id, name from contacts) from account where id  
            =  
            :accountId];  
        List<contact> co = [select id, name from contact where account.id = :accountId];  
        system.debug('** a[0]= '+ a[0]);  
        return a[0];  
    }  
}
```

AccountManagerTest.apxc

```
@istest  
public class AccountManagerTest {  
    @istest static void testGetContactsByAccountId()  
    { Id recordId = createTestRecord();  
    / Set up a test request  
    RestRequest request = new RestRequest();  
    request.requestUri =  
    'https://yourInstance.salesforce.com/services/apexrest/Accounts/'+ recordId+'/Contacts';  
    request.httpMethod = 'GET';  
    RestContext.request = request;
```

APEX SPECIALIST SUPER BADGE CODES

```
Account thisAccount = AccountManager.getAccount();
System.assert(thisAccount!= null);
System.assertEquals('Test record', thisAccount.Name);
}
```

/ Helper method

```
static Id createTestRecord() {
```

/ Create test record

```
Account accountTest = new Account(
Name='Test record');
insert accountTest;
Contact contactTest = new Contact(
FirstName='John',
LastName='Doe',
AccountId=accountTest.Id
);
return accountTest.Id;
}
}
```

Apex Specialist super badge

Challenge-1

MaintenanceRequestHelper.apxc

```
public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status ==
                'Closed'){ if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }
    }
}
```

APEX SPECIALIST SUPER BADGE CODES

```
    }
}

if (!validIds.isEmpty()){
    List<Case> newCases = new List<Case>();
    Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehiclec,
Equipmentc, Equipmentr.Maintenance_Cyclec,(SELECT Id,Equipmentc,Quantityc
FROM Equipment_Maintenance_Items_r
FROM Case WHERE Id IN :validIds]);
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
    AggregateResult[] results = [SELECT Maintenance_Requestc,
MIN(Equipmentr.Maintenance_Cyclec)cycle FROM Equipment_Maintenance_Itemc
WHERE Maintenance_Requestc IN :ValidIds GROUP BY Maintenance_Requestc];

    for (AggregateResult ar : results){
        maintenanceCycles.put((Id) ar.get('Maintenance_Requestc'), (Decimal) ar.get('cycle'));
    }

    for(Case cc : closedCasesM.values()){
        Case nc = new Case (
            ParentId = cc.Id,
            Status = 'New',
            Subject = 'Routine Maintenance',
            Type = 'Routine Maintenance',
            Vehiclec = cc.Vehiclec,
            Equipmentc =cc.Equipmentc,
            Origin = 'Web',
            Date_Reportedc = Date.Today()

        );
        If (maintenanceCycles.containsKey(cc.Id)){
            nc.Date_Duec = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
        }
        newCases.add(nc);
    }
    insert newCases;

    List<Equipment_Maintenance_Itemc> clonedWPs = new
```

APEX SPECIALIST SUPER BADGE CODES

```
List<Equipment_Maintenance_Itemc>();
    for (Case nc : newCases){
        for (Equipment_Maintenance_Itemc wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Itemsr){
            Equipment_Maintenance_Itemc wpClone = wp.clone();
            wpClone.Maintenance_Requestc = nc.Id;
            ClonedWPs.add(wpClone);

        }
    }
    insert ClonedWPs;
}
}
```

MaintenanceRequest.apxt

```
trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}
```

Challenge-2

WarehouseCalloutService.apxc

```
public with sharing class WarehouseCalloutService implements Queueable
{ private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

    / class that makes a REST callout to an external warehouse system to get a list of equipment
that needs to be updated.
    / The callout's JSON response returns the equipment records that you upsert in Salesforce.
    @future(callout=true)
    public static void runWarehouseEquipmentSync(){
        Http http = new Http();
        HttpRequest request = new HttpRequest();

        request.setEndpoint(WAREHOUSE_URL);
```

APEX SPECIALIST SUPER BADGE CODES

```
request.setMethod('GET');
HttpResponse response = http.send(request);

List<Product2> warehouseEq = new List<Product2>();

if (response.getStatusCode() == 200){
    List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
    System.debug(response.getBody());

    / class maps the following fields: replacement part (always true), cost, current inventory,
lifespan, maintenance cycle, and warehouse SKU
    / warehouse SKU will be external ID for identifying which equipment records to update
within Salesforce
    for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Month = (Integer) mapJson.get('lifespan');
        myEq.Cost = (Integer) mapJson.get('cost');
        myEq.Warehouse_SKU = (String) mapJson.get('sku');
        myEq.Current_Inventory = (Double) mapJson.get('quantity');
        myEq.ProductCode = (String) mapJson.get('_id');
        warehouseEq.add(myEq);
    }

    if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
    }
}

public static void execute (QueueableContext context){
    runWarehouseEquipmentSync();
}
}
```

Challenge-3

APEX SPECIALIST SUPER BADGE CODES

WarehouseSyncSchedule.apxc

```
global with sharing class WarehouseSyncSchedule implements Schedulable{
    global void execute(SchedulableContext ctx){
        System.enqueueJob(new WarehouseCalloutService());
    }
}
```

Challenge-4

MaintenanceRequestHelperTest.apxc

```
@istest
public with sharing class MaintenanceRequestHelperTest {

    private static final string STATUS_NEW = 'New';
    private static final string WORKING = 'Working';
    private static final string CLOSED = 'Closed';
    private static final string REPAIR = 'Repair';
    private static final string REQUEST_ORIGIN = 'Web';
    private static final string REQUEST_TYPE = 'Routine Maintenance';
    private static final string REQUEST_SUBJECT = 'Testing subject';

    PRIVATE STATIC VehicleC createVehicle(){
        VehicleC Vehicle = new VehicleC(name = 'SuperTruck');
        return Vehicle;
    }

    PRIVATE STATIC Product2 createEq(){
        product2 equipment = new product2(name = 'SuperEquipment',
            lifespan_monthsC = 10,
            maintenance_cycleC = 10,
            replacement_partc = true);
        return equipment;
    }

    PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id
        equipmentId){ case cs = new case(Type=REPAIR,
            Status=STATUS_NEW,
            Origin=REQUEST_ORIGIN,
```

APEX SPECIALIST SUPER BADGE CODES

```
        Subject=REQUEST_SUBJECT,
        Equipmentc=equipmentId,
        Vehiclec=vehicleId);
    return cs;
}

PRIVATE STATIC Equipment_Maintenance_Itemc createWorkPart(id equipmentId,id
requestId){
    Equipment_Maintenance_Itemc wp = new
Equipment_Maintenance_Itemc(Equipmentc = equipmentId,
                             Maintenance_Requestc = requestId);

    return wp;
}

@istest
private static void
testMaintenanceRequestPositive(){ Vehiclec
vehicle = createVehicle();
insert vehicle;
id vehicleId = vehicle.Id;

Product2 equipment =
createEq(); insert equipment;
id equipmentId = equipment.Id;

case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
insert somethingToUpdate;

Equipment_Maintenance_Itemc workP =
createWorkPart(equipmentId,somethingToUpdate.id);
insert workP;
test.startTest();
somethingToUpdate.status = CLOSED;
update somethingToUpdate;
test.stopTest();
Case newReq = [Select id, subject, type, Equipmentc, Date_Reportedc, Vehiclec,
Date_Duec
               from case
               where status =:STATUS_NEW];
```

APEX SPECIALIST SUPER BADGE CODES

```
Equipment_Maintenance_Itemc workPart = [select id
                                         from Equipment_Maintenance_Itemc
                                         where Maintenance_Requestc =:newReq.Id];

system.assert(workPart != null);
system.assert(newReq.Subject != null);
system.assertEquals(newReq.Type, REQUEST_TYPE);
SYSTEM.assertEquals(newReq.Equipmentc,
equipmentId); SYSTEM.assertEquals(newReq.Vehiclec,
vehicleId);
SYSTEM.assertEquals(newReq.Date_Reportedc, system.today());
}

@istest
private static void testMaintenanceRequestNegative(){
    VehicleC vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

    product2 equipment =
    createEq(); insert equipment;
    id equipmentId = equipment.Id;

    case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
    insert emptyReq;

    Equipment_Maintenance_Itemc workP = createWorkPart(equipmentId, emptyReq.Id);
    insert workP;

    test.startTest();
    emptyReq.Status = WORKING;
    update emptyReq;
    test.stopTest();

    list<case> allRequest = [select id
                           from case];

    Equipment_Maintenance_Itemc workPart = [select id
                                             from Equipment_Maintenance_Itemc
                                             where Maintenance_Requestc = :emptyReq.Id];
```

APEX SPECIALIST SUPER BADGE CODES

```
system.assert(workPart != null);
system.assert(allRequest.size() ==
1);
}
```

@istest

```
private static void testMaintenanceRequestBulk(){
    list<VehicleC> vehicleList = new list<VehicleC>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Itemc> workPartList = new
list<Equipment_Maintenance_Itemc>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();
    for(integer i = 0; i < 300; i++){
        vehicleList.add(createVehicle());
        equipmentList.add(createEq());
    }
    insert vehicleList;
    insert
    equipmentList;

    for(integer i = 0; i < 300; i++){
        requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
        equipmentList.get(i).id));
    }
    insert requestList;
    for(integer i = 0; i < 300; i++){
        workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
    }
    insert workPartList;
    test.startTest();
    for(case req : requestList){
        req.Status = CLOSED;
        oldRequestIds.add(req.Id);
    }
    update
    requestList;
    test.stopTest();

    list<case> allRequests = [select id
        from case
        where status =: STATUS_NEW];
```

APEX SPECIALIST SUPER BADGE CODES

```
list<Equipment_Maintenance_Itemc> workParts = [select id
                                                from Equipment_Maintenance_Itemc
                                                where Maintenance_Requestc in: oldRequestIds];

system.assert(allRequests.size() == 300);
}
}
```

MaintenanceRequestHelper.apxc

```
public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status ==
                'Closed'){ if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }

        if (!validIds.isEmpty()){
            List<Case> newCases = new List<Case>();
            Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehiclec,
Equipmentc, Equipmentr.Maintenance_Cyclec,(SELECT Id,Equipmentc,Quantityc
FROM Equipment_Maintenance_Items_r)
                FROM Case WHERE Id IN :validIds]);
            Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
            AggregateResult[] results = [SELECT Maintenance_Requestc,
MIN(Equipmenttr.Maintenance_Cyclec)cycle FROM Equipment_Maintenance_Itemc
WHERE Maintenance_Requestc IN :ValidIds GROUP BY Maintenance_Requestc];
            for (AggregateResult ar : results){
                maintenanceCycles.put((Id) ar.get('Maintenance_Requestc'), (Decimal) ar.get('cycle'));
            }
        }
    }
}
```

APEX SPECIALIST SUPER BADGE CODES

```
for(Case cc : closedCasesM.values()){
    Case nc = new Case (
        ParentId = cc.Id,
        Status = 'New',
        Subject = 'Routine Maintenance',
        Type = 'Routine Maintenance',
        Vehiclec = cc.Vehiclec,
        Equipmentc =cc.Equipmentc,
        Origin = 'Web',
        Date_Reportedc = Date.Today()

    );

    If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Duec = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
    }

    newCases.add(nc);
}

insert newCases;

List<Equipment_Maintenance_Itemc> clonedWPs = new
List<Equipment_Maintenance_Itemc>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Itemc wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Itemsr){
        Equipment_Maintenance_Itemc wpClone = wp.clone();
        wpClone.Maintenance_Requestc = nc.Id;
        ClonedWPs.add(wpClone);
    }
}
insert ClonedWPs;
}
}
```

MaintenanceRequest.apxt

APEX SPECIALIST SUPER BADGE CODES

```
trigger MaintenanceRequest on Case (before update, after update) {  
    if (Trigger.isUpdate && Trigger.isAfter) {  
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);  
    }  
}
```

Challenge-5

WarehouseCalloutService.apxc

```
public with sharing class WarehouseCalloutService implements Queueable  
{ private static final String WAREHOUSE_URL = 'https://th-superbadge-  
apex.herokuapp.com/equipment';
```

/ class that makes a REST callout to an external warehouse system to get a list of equipment that needs to be updated.

/ The callout's JSON response returns the equipment records that you upsert in Salesforce.

```
@future(callout=true)  
public static void runWarehouseEquipmentSync(){  
    Http http = new Http();  
    HttpRequest request = new HttpRequest();  
  
    request.setEndpoint(WAREHOUSE_URL);  
    request.setMethod('GET');  
    HttpResponse response = http.send(request);  
  
    List<Product2> warehouseEq = new List<Product2>();  
  
    if (response.getStatusCode() == 200){  
        List<Object> jsonResponse =  
(List<Object>)JSON.deserializeUntyped(response.getBody());  
        System.debug(response.getBody());  
  
        / class maps the following fields: replacement part (always true), cost, current inventory,  
        lifespan, maintenance cycle, and warehouse SKU  
        / warehouse SKU will be external ID for identifying which equipment records to update  
        within Salesforce  
        for (Object eq : jsonResponse){  
            Map<String, Object> mapJson = (Map<String, Object>)eq;  
            Product2 myEq = new Product2();
```

APEX SPECIALIST SUPER BADGE CODES

```
myEq.Replacement_Part = (Boolean) mapJson.get('replacement');
myEq.Name = (String) mapJson.get('name');
myEq.Maintenance_Cycle = (Integer) mapJson.get('maintenanceperiod');
myEq.Lifespan_Month = (Integer) mapJson.get('lifespan');
myEq.Cost = (Integer) mapJson.get('cost');
myEq.Warehouse_SKU = (String) mapJson.get('sku');
myEq.Current_Inventory = (Double) mapJson.get('quantity');
myEq.ProductCode = (String) mapJson.get('_id');
warehouseEq.add(myEq);
}

if (warehouseEq.size() > 0){
    upsert warehouseEq;
    System.debug('Your equipment was synced with the warehouse one');
}
}
}

public static void execute (QueueableContext context){
    runWarehouseEquipmentSync();
}

}
```

WarehouseCalloutServiceTest.apxc

```
@IsTest
private class WarehouseCalloutServiceTest {
    / implement your mock callout test here
    @isTest
    static void testWarehouseCallout() {
        test.startTest();
        test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.execute(null);
        test.stopTest();

        List<Product2> product2List = new List<Product2>();
        product2List = [SELECT ProductCode FROM Product2];

        System.assertEquals(3, product2List.size());
        System.assertEquals('55d66226726b611100aaf741', product2List.get(0).ProductCode);
    }
}
```


APEX SPECIALIST SUPER BADGE CODES

```
        System.assertEquals('55d66226726b611100aaf742', product2List.get(1).ProductCode);
        System.assertEquals('55d66226726b611100aaf743', product2List.get(2).ProductCode);
    }
}
```

WarehouseCalloutServiceMock.apxc

```
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    / implement http mock callout
    global static HttpResponse respond(HttpRequest request){

        System.assertEquals('https://th-superbadge-
apex.herokuapp.com/equipment', request.getEndpoint());
        System.assertEquals('GET', request.getMethod());

        / Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type',
            'application/json');

        response.setBody('{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5,"name
": "Generator 1000 kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}');
        response.setStatusCode(200);
        return response;
    }
}
```

Challenge-6

WarehouseSyncSchedule.apxc

```
global with sharing class WarehouseSyncSchedule implements Schedulable{
    global void execute(SchedulableContext ctx){
        System.enqueueJob(new WarehouseCalloutService());
    }
}
```

WarehouseSyncScheduleTest.apxc

APEX SPECIALIST SUPER BADGE CODES

```
@isTest
public class WarehouseSyncScheduleTest {

    @isTest static void WarehousescheduleTest(){
        String scheduleTime = '00 00 01 * * ?';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String jobId=System.schedule('Warehouse Time To Schedule to Test', scheduleTime, new
WarehouseSyncSchedule());
        Test.stopTest();

        / Contains schedule information for a scheduled job. CronTrigger is similar to a cron job
on UNIX systems.
        / This object is available in API version 17.0 and later.
        CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
        System.assertEquals(jobID, a.Id,'Schedule ');

    }
}
```