

CODES ARE AS FOLLOWING :-

AccountManagerTest.apxc :

@isTest

```
private class AccountManagerTest {
    private static testMethod void getAccountTest1() {
        Id recordId = createTestRecord();
        // Set up a test request
        RestRequest request = new RestRequest();
        request.requestUri = 'https://na1.salesforce.com/services/apexrest/Accounts/' +
recordId + '/contacts' ;
        request.httpMethod = 'GET';
        RestContext.request = request;
        // Call the method to test
        Account thisAccount = AccountManager.getAccount();
        // Verify results
        System.assert(thisAccount != null);
        System.assertEquals('Test record', thisAccount.Name);
    }
    // Helper method
    static Id createTestRecord() {
        // Create test record
        Account TestAcc = new Account(
            Name='Test record');
        insert TestAcc;
        Contact TestCon= new Contact(
            LastName='Test',
            AccountId = TestAcc.id);
        return TestAcc.Id
    }
};
```

ParkService.apxc :

//Generated by wsdl2apex

```
public class ParkService {
    public class byCountryResponse {
        public String[] return_x;
        private String[] return_x_type_info = new
String[]{'return','http://parks.services/',null,'0','-1','false'};
```

```

        private String[] apex_schema_type_info = new
String[]{"http://parks.services/","false","false"};

        private String[] field_order_type_info = new String[]{"return_x"};
    }
    public class byCountry {
        public String arg0;
        private String[] arg0_type_info = new
String[]{"arg0","http://parks.services/","null","0","1","false"};
        private String[] apex_schema_type_info = new
String[]{"http://parks.services/","false","false"};
        private String[] field_order_type_info = new String[]{"arg0"};
    }
    public class ParksImplPort {
        public String endpoint_x = 'https://th-apex-soapservice.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public Map<String,String> outputHttpHeaders_x;
        public String clientCertName_x;
        public String clientCert_x;
        public String clientCertPasswd_x;
        public Integer timeout_x;
        private String[] ns_map_type_info = new String[]{"http://parks.services/","ParkService"};
        public String[] byCountry(String arg0) {
            ParkService.byCountry request_x = new ParkService.byCountry();
            request_x.arg0 = arg0;
            ParkService.byCountryResponse response_x;
            Map<String, ParkService.byCountryResponse> response_map_x = new
Map<String, ParkService.byCountryResponse>();
            response_map_x.put('response_x', response_x);
            WebServiceCallout.invoke(
                this,
                request_x,
                response_map_x,
                new String[]{endpoint_x,
                    "",
                    'http://parks.services/',
                    'byCountry',
                    'http://parks.services/',
                    'byCountryResponse',
                    'ParkService.byCountryResponse'}
            )
        }
    }

```

```

        );
        response_x = response_map_x.get('response_x');
        return response_x.return_x;
    }
}
}
AsyncParkService.apxc :
//Generated by wsdl2apex
public class AsyncParkService {
    public class byCountryResponseFuture extends System.WebServiceCalloutFuture {
        public String[] getValue() {
            ParkService.byCountryResponse response =
(ParkService.byCountryResponse)System.WebServiceCallout.endInvoke(this);
            return response.return_x;
        }
    }
    public class AsyncParksImplPort {
        public String endpoint_x = 'https://th-apex-soapservice.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public String clientCertName_x;
        public Integer timeout_x;
        private String[] ns_map_type_info = new String[]{'http://parks.services/',
'ParkService'};
        public AsyncParkService.byCountryResponseFuture
beginByCountry(System.Continuation continuation,String arg0) {
            ParkService.byCountry request_x = new ParkService.byCountry();
            request_x.arg0 = arg0;
            return (AsyncParkService.byCountryResponseFuture)
System.WebServiceCallout.beginInvoke(
                this,
                request_x,
                AsyncParkService.byCountryResponseFuture.class,
                continuation,
                new String[]{endpoint_x,
                ",
                'http://parks.services/',
                'byCountry',
                'http://parks.services/',
                'byCountryResponse',
                'ParkService.byCountryResponse'}
                );

```

```

    }
}

```

AnimalLocator.apxc :

```

public class AnimalLocator{
    public static String getAnimalNameById(Integer x){
        Http http = new Http();
        HttpRequest req = new HttpRequest();
        req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/'
+ x);
        req.setMethod('GET');
        Map<String, Object> animal= new Map<String, Object>();
        HttpResponse res = http.send(req);
        if (res.getStatusCode() == 200) {

            Map<String, Object> results = (Map<String,
Object>)JSON.deserializeUntyped(res.getBody());
            animal = (Map<String, Object>) results.get('animal');
        }
        return (String)animal.get('name');
    }
}

```

AccountManager.apxc :

```

@RestResource(urlMapping='/Accounts/*/contacts')
global class AccountManager {
    @HttpGet
    global static Account getAccount() {
        RestRequest req = RestContext.request;
        String accId = req.requestURI.substringBetween('Accounts/', '/contacts');
        Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
            FROM Account WHERE Id = :accId];
        return acc;
    }
}

```

AnimalLocatorMock.apxc :

```

@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
    // Implement this interface method
    global HTTPResponse respond(HTTPRequest request) {
        // Create a fake response
        HttpResponse response = new HttpResponse();
    }
}

```

```

        response.setHeader('Content-Type', 'application/json');
        response.setBody("{\"animals\": [\"majestic badger\", \"fluffy bunny\", \"scary bear\",
\"chicken\", \"mighty moose\"]}");
        response.setStatusCode(200);
        return response;
    }
}

```

ParkLocatorTest.apxc :

```

@Test
private class ParkLocatorTest {
    @Test static void testCallout() {
        Test.setMock(WebServiceMock.class, new ParkServiceMock ());
        String country = 'United States';
        List<String> result = ParkLocator.country(country);
        List<String> parks = new List<String>{'Yellowstone', 'Mackinac National Park',
'Yosemite'};
        System.assertEquals(parks, result);
    }
}

```

AnimalLocatorTest.apxc :

```

@Test
private class AnimalLocatorTest{
    @Test static void AnimalLocatorMock1() {
        Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
        string result = AnimalLocator.getAnimalNameById(3);
        String expectedResult = 'chicken';
        System.assertEquals(result,expectedResult );
    }
}

```

NewCaseListController.apxc :

```

public class NewCaseListController {
    public List<Case> getNewCases(){
        List<Case> filterList = [Select Id, CaseNumber from Case where status = 'New'];
        return filterList;
    }
}

```

ParkLocator.apxc :

```

public class ParkLocator {
    public static string[] country(string theCountry) {
        ParkService.ParksImplPort parkSvc = new ParkService.ParksImplPort(); // remove
space
    }
}

```

```

        return parkSvc.byCountry(theCountry);
    }
}
ParkServiceMock.apxc :
@isTest
global class ParkServiceMock implements WebServiceMock {
    global void doInvoke(
        Object stub,
        Object request,
        Map<String, Object> response,
        String endpoint,
        String soapAction,
        String requestName,
        String responseNS,
        String responseName,
        String responseType) {
        // start - specify the response you want to send
        ParkService.byCountryResponse response_x = new
ParkService.byCountryResponse();
        response_x.return_x = new List<String>{'Yellowstone', 'Mackinac National Park',
'Yosemite'};
        // end
        response.put('response_x', response_x);
    }
}
PostPriceChangeToSlackTest.apxc :
@isTest
public class PostPriceChangeToSlackTest {
    static testMethod void testPost() {
        Boolean success = true;
        try {
            Property__c p = new Property__c(Name='test property', Price__c=200000);
            insert p;
            PostPriceChangeToSlack.postToSlack(new List<Id> { p.Id });
        } catch (Exception e) {
            System.debug(e);
            success = false;
        } finally {
            System.assert(success);
        }
    }
}

```

```
}
```

PropertyController.apxc :

```
global with sharing class PropertyController {
```

```
    @AuraEnabled
```

```
    public static PropertyPagedResult findAll(String searchKey, Decimal minPrice,  
Decimal maxPrice, Decimal pageSize, Decimal pageNumber) {
```

```
Integer pSize = (Integer)pageSize;
```

```
    String key = '%' + searchKey + '%';
```

```
    Integer offset = ((Integer)pageNumber - 1) * pSize;
```

```
    PropertyPagedResult r = new PropertyPagedResult();
```

```
    r.pageSize = pSize;
```

```
    r.page = (Integer) pageNumber;
```

```
    r.total = [SELECT count() FROM property__c
```

```
        WHERE (title__c LIKE :key OR city__c LIKE :key OR tags__c LIKE :key)
```

```
        AND price__c >= :minPrice
```

```
AND price__c <= :maxPrice];
```

```
    r.properties = [SELECT Id, title__c, city__c, description__c, price__c, baths__c,  
beds__c, thumbnail__c FROM property__c
```

```
        WHERE (title__c LIKE :key OR city__c LIKE :key OR tags__c LIKE :key)
```

```
        AND price__c >= :minPrice
```

```
AND price__c <= :maxPrice
```

```
        ORDER BY price__c LIMIT :pSize OFFSET :offset];
```

```
    System.debug(r);
```

```
    return r;
```

```
}
```

```
    @AuraEnabled
```

```
    public static Property__c findById(Id propertyId) {
```

```
        return [SELECT id, name, beds__c, baths__c, address__c, city__c, state__c,  
assessed_value__c, price__c, Date_Listed__c, Location__Latitude__s,  
Location__Longitude__s
```

```
            FROM Property__c
```

```
            WHERE Id=:propertyId];
```

```
}
```

```
    @RemoteAction @AuraEnabled
```

```
    public static Property__c[] getAvailableProperties() {
```

```
        return [SELECT id, name, address__c, city__c, price__c, Date_Listed__c,  
Days_On_Market__c, Date_Agreement__c, Location__Latitude__s,  
Location__Longitude__s
```

```
            FROM Property__c
```

```
            WHERE Date_Listed__c != NULL AND (Date_Agreement__c = NULL OR  
Date_Agreement__c = LAST_N_DAYS:90)];
```

```

    }
    @AuraEnabled
    public static List<Property__c> getSimilarProperties (Id propertyId, Decimal
    bedrooms, Decimal price, String searchCriteria) {
        if (searchCriteria == 'Bedrooms') {
            return [
                SELECT Id, Name, Beds__c, Baths__c, Price__c, Broker__c, Status__c,
                Thumbnail__c
                FROM Property__c WHERE Id != :propertyId AND Beds__c = :bedrooms
            ];
        } else {
            return [
                SELECT Id, Name, Beds__c, Baths__c, Price__c, Broker__c, Status__c,
                Thumbnail__c
                FROM Property__c WHERE Id != :propertyId AND Price__c > :price - 100000
                AND Price__c < :price + 100000
            ];
        }
    }
}

```

PropertyControllerTest.apxc :

```

@isTest
public class PropertyControllerTest {
    static testMethod void testFindAll() {
        Boolean success = true;
        try {
            Property__c p = new Property__c(Location__Latitude__s=-
71.110448,Location__Longitude__s=42.360642);
            insert p;
            PropertyPagedResult r = PropertyController.findAll("", 0, 1000000, 8, 1);
        } catch (Exception e) {
            success = false;
        } finally {
            System.assert(success);
        }
    }
    static testMethod void testFindById() {
        Boolean success = true;
        try {
            Property__c p = new Property__c(Location__Latitude__s=-
71.110448,Location__Longitude__s=42.360642);

```



```

        insert p;
        Property__c property = PropertyController.findById(p.Id);
    } catch (Exception e) {
        success = false;
    } finally {
        System.assert(success);
    }
}

static testMethod void getAvailableProperties() {
    Boolean success = true;
    try {
        Property__c p = new Property__c(Location__Latitude__s=-
71.110448,Location__Longitude__s=42.360642);
        insert p;
        Property__c[] r = PropertyController.getAvailableProperties();
    } catch (Exception e) {
        success = false;
    } finally {
        System.assert(success);
    }
}

static testMethod void getSimilarProperties() {
    Boolean success = true;
    try {
        Property__c p = new Property__c(Location__Latitude__s=-
71.110448,Location__Longitude__s=42.360642);
        insert p;
        Property__c[] r = PropertyController.getSimilarProperties(p.Id, 3, 500000,
'Bedrooms');
    } catch (Exception e) {
        success = false;
    } finally {
        System.assert(success);
    }
}
}

PropertyPagedResult.apxc :
public class PropertyPagedResult {
    @AuraEnabled
    public Integer pageSize { get;set; }
    @AuraEnabled

```

```

    public Integer page { get;set; }
    @AuraEnabled
    public Integer total { get;set; }
    @AuraEnabled
    public List<Property__c> properties { get;set; }
}

PushPriceChangeNotification.apxc :
public with sharing class PushPriceChangeNotification {
    @InvocableMethod(label='Push Price Change Notification')
    public static void pushNotification(List<Id> propertyId) {
        String pushServerURL;
        Dreamhouse_Settings__c settings = Dreamhouse_Settings__c.getOrgDefaults();
        if (!Test.isRunningTest()) {
            if (settings == null || settings.Push_Server_URL__c == null) {
                System.debug('Push_Server_URL not set. Aborting
PushPriceChangeNotification process action');
                return;
            } else {
                pushServerURL = settings.Push_Server_URL__c;
            }
        }
        Id propId = propertyId[0]; // If bulk, only post first to avoid spamming
        Property__c property = [SELECT Name, Price__c from Property__c WHERE
Id=:propId];
        String message = property.Name + ' . New Price: $' +
property.Price__c.setScale(0).format();
        Set<String> userIds = new Set<String>();
        List<Favorite__c> favorites = [SELECT user__c from favorite__c WHERE
property__c=:propId];
        for (Favorite__c favorite : favorites) {
            userIds.add(favorite.user__c);
        }
        Map<String,Object> payload = new Map<String,Object>();
        payload.put('message', message);
        payload.put('userIds', userIds);
        String body = JSON.serialize(payload);
        System.enqueueJob(new QueueablePushCall(pushServerURL, 'POST', body));
    }
    public class QueueablePushCall implements System.Queueable,
Database.AllowsCallouts {
        private final String url;

```

```

private final String method;
private final String body;
public QueueablePushCall(String url, String method, String body) {
    this.url = url;
    this.method = method;
    this.body = body;
}
public void execute(System.QueueableContext ctx) {
    HttpRequest req = new HttpRequest();
    req.setMethod(method);
    req.setHeader('Content-Type', 'application/json');
    req.setBody(body);
    Http http = new Http();
    HttpResponse res;
    if (!Test.isRunningTest()) {
        req.setEndpoint(url);
res = http.send(req);
    }
}
}
}
}
PushPriceChangeNotificationTest.apxc :
@isTest
public class PushPriceChangeNotificationTest {
    static testMethod void testPush() {
        Boolean success = true;
        try {
            Property__c p = new Property__c(Name='test property', Price__c=200000);
            insert p;
            PushPriceChangeNotification.pushNotification(new List<Id> { p.Id });
        } catch (Exception e) {
            success = false;
        } finally {
            System.assert(success);
        }
    }
}
RejectDuplicateFavoriteTest.apxc :
@isTest
public class RejectDuplicateFavoriteTest {
    public static String getUserNamePrefix(){

```

```

        return UserInfo.getOrganizationId() + System.now().millisecond();
    }
    public static User getTestUser(){
        Profile p = [SELECT Id FROM Profile WHERE Name='Standard User'];
        return new User(Alias='testuser', Email='test@user.com',
            EmailEncodingKey='UTF-8', LastName='test', LanguageLocaleKey='en_US',
            LocaleSidKey='en_US', ProfileId = p.Id,
            TimeZoneSidKey='America/Los_Angeles',
            UserName=getUserNamePrefix() + 'test@test.com');
    }
    static testMethod void acceptNonDuplicate() {
        Boolean success = true;
        try {
            Property__c p = new Property__c();
            insert p;
            User u = getTestUser();
            insert u;
            Favorite__c f1 = new Favorite__c(property__c=p.Id, user__c=u.Id);
            insert f1;
        } catch (Exception e) {
            System.debug(e);
            success = false;
        } finally {
            System.assert(success);
        }
    }
    static testMethod void rejectDuplicate() {
        Boolean success = true;
        try {
            Property__c p = new Property__c();
            insert p;
            User u = getTestUser();
            insert u;
            Favorite__c f1 = new Favorite__c(property__c=p.Id, user__c=u.Id);
            insert f1;
            Favorite__c f2 = new Favorite__c(property__c=p.Id, user__c=u.Id);
            insert f2;
        } catch (Exception e) {
            success = false;
        } finally {
            System.assert(!success);
        }
    }

```

```

    }
}
}
SlackOpportunityPublisher.apxc :
public with sharing class SlackOpportunityPublisher {
    private static final String slackURL =
Dreamhouse_Settings__c.getOrgDefaults().Slack_Opportunity_Webhook_URL__c;
    @InvocableMethod(label='Post to Slack')
    public static void postToSlack(List<Id> opportunityId) {
        Id oppld = opportunityId[0]; // If bulk, only post first to avoid overloading Slack
channel
        Opportunity opportunity = [SELECT Name, StageName from Opportunity WHERE
Id=:oppld];
        Map<String,Object> msg = new Map<String,Object>();
        msg.put('text', 'The following opportunity has changed:\n' + opportunity.Name +
'\nNew Stage: *'
            + opportunity.StageName + '*');
        msg.put('mrkdwn', true);
        String body = JSON.serialize(msg);
        System.enqueueJob(new QueueableSlackCall(slackURL, 'POST', body));
    }
    public class QueueableSlackCall implements System.Queueable,
Database.AllowsCallouts {
        private final String url;
        private final String method;
        private final String body;
        public QueueableSlackCall(String url, String method, String body) {
            this.url = url;
            this.method = method;
            this.body = body;
        }
        public void execute(System.QueueableContext ctx) {
            HttpRequest req = new HttpRequest();
            req.setMethod(method);
            req.setBody(body);
            Http http = new Http();
            HttpResponse res;
            if (!Test.isRunningTest()) {
                req.setEndpoint(url);
                res = http.send(req);
            }
        }
    }
}

```

```

    }
}
}
SlackOpportunityPublisherTest.apxc :
@isTest
public class SlackOpportunityPublisherTest {
    static testMethod void testPost() {
        Boolean success = true;
        try {
            Opportunity opp = new Opportunity(Name='test opportunity', StageName='Close
Won', CloseDate=date.today());
            insert opp;
            SlackOpportunityPublisher.postToSlack(new List<Id> { opp.Id });
        } catch (Exception e) {
            success = false;
        } finally {
            System.assert(success);
        }
    }
}
}

```

```

BotController.apxc :
public with sharing class BotController {
    class HandlerMapping {
        public String handlerClassName;
        public Pattern utterancePattern;
        public HandlerMapping(String handlerClassName, String patternStr) {
            this.handlerClassName = handlerClassName;
            this.utterancePattern = Pattern.compile(patternStr);
        }
    }
    static List<HandlerMapping> handlerMappings;
    static {
        List<Bot_Command__c> commands = [SELECT apex_class__c, pattern__c FROM
Bot_Command__c WHERE Active__c = True ORDER BY Name];
        System.debug(commands);
        List<HandlerMapping> mappings = new List<HandlerMapping>();
        for (Bot_Command__c command : commands) {
            mappings.add(new HandlerMapping(command.apex_class__c,
command.pattern__c));
        }
        handlerMappings = mappings;
    }
}

```

```

    }
    @AuraEnabled
    public static BotResponse submit(String utterance, Map<String, String> session,
    String fileName, String fileContent) {
        try {
            if (session != null) {
                String nextCommand = session.get('nextCommand');
                if (nextCommand != null) {
                    Type t = Type.forName("", nextCommand);
                    BotHandler h = (BotHandler)t.newInstance();
                    return h.handle(utterance, null, session, fileName, fileContent);
                }
            }
            for (HandlerMapping mapping : BotController.handlerMappings) {
                Matcher utteranceMatcher = mapping.utterancePattern.matcher(utterance);
                if (utteranceMatcher.matches()) {
                    Type t = Type.forName("", mapping.handlerClassName);
                    BotHandler h = (BotHandler)t.newInstance();
                    List<String> params = new List<String>();
                    for (Integer i=1; i<=utteranceMatcher.groupCount(); i=i+1) {
                        params.add(utteranceMatcher.group(i).trim());
                    }
                    return h.handle(utterance, params, session, fileName, fileContent);
                }
            }
            return new BotResponse(new BotMessage('Bot', 'I don\'t know how to answer
that'));
        } catch (Exception e) {
            System.debug(e);
            return new BotResponse(new BotMessage('Bot', 'Oops, something went wrong
invoking that command'));
        }
    }
}

```

BotField.apxc :

```

public class BotField {
    @AuraEnabled public String name { get;set; }
    @AuraEnabled public String value { get;set; }
    @AuraEnabled public String linkURL { get;set; }
    public BotField(String name, String value) {
        this.name = name;
    }
}

```

```

        this.value = value;
    }
    public BotField(String name, String value, string linkURL) {
        this.name = name;
        this.value = value;
        this.linkURL = linkURL;
    }
}

BotHandler.apxc :
public interface BotHandler {
    BotResponse handle(String utterance, String[] params, Map<String, String> session,
String fileName, String fileContent);
}

BotItem.apxc :
public class BotItem {
    @AuraEnabled public String name { get;set;}
    @AuraEnabled public String linkURL { get;set; }
    public BotItem(String name) {
        this.name = name;
    }
    public BotItem(String name, string linkURL) {
        this.name = name;
        this.linkURL = linkURL;
    }
}

BotMessage.apxc :
public virtual class BotMessage {
    @AuraEnabled public String author { get;set; }
    @AuraEnabled public String messageText { get;set; }
    @AuraEnabled public List<BotRecord> records { get;set; }
    @AuraEnabled public List<BotItem> items { get;set; }
    @AuraEnabled public List<BotMessageButton> buttons { get;set; }
    @AuraEnabled public String imageURL { get;set; }
    public BotMessage() {
    }
    public BotMessage(String author, String messageText) {
        this.author = author;
        this.messageText = messageText;
    }
    public BotMessage(String author, String messageText, List<BotRecord> records) {
        this.author = author;

```



```

        this.messageText = messageText;
        this.records = records;
    }
    public BotMessage(String author, String messageText, List<BotItem> items) {
        this.author = author;
        this.messageText = messageText;
        this.items = items;
    }
    public BotMessage(String author, String messageText, List<BotMessageButton>
buttons) {
        this.author = author;
        this.messageText = messageText;
        this.buttons = buttons;
    }
    public BotMessage(String author, String messageText, String imageURL) {
        this.author = author;
        this.messageText = messageText;
        this.imageURL = imageURL;
    }
}

```

BotMessageButton.apxc :

```

public class BotMessageButton {
    @AuraEnabled public String label { get;set; }
    @AuraEnabled public String value { get;set; }
    public BotMessageButton(String label, String value) {
        this.label = label;
        this.value = value;
    }
}

```

BotRecord.apxc :

```

public class BotRecord {
    @AuraEnabled
    public List<BotField> fields { get;set; }
    public BotRecord(List<BotField> fields) {
        this.fields = fields;
    }
}

```

BotResponse.apxc :

```

public class BotResponse {
    @AuraEnabled public List<BotMessage> messages { get; set; }
    @AuraEnabled public Map<String, String> session { get; set; }
}

```

```

public BotResponse() {
}
public BotResponse(BotMessage[] messages) {
    this.messages = messages;
}
public BotResponse(List<BotMessage> messages, Map<String, String> session) {
    this.messages = messages;
    this.session = session;
}
/**
 * Convenience constructor to create a response with a single message
 */
public BotResponse(BotMessage message) {
    this.messages = new BotMessage[]{message};
}
/**
 * Convenience constructor to create a response with a single message
 */
public BotResponse(BotMessage message, Map<String, String> session) {
    this.messages = new BotMessage[]{message};
    this.session = session;
}
}

BotTest.apxc :
@Test
public class BotTest {
    static testMethod void testBotController() {
Bot_Command__c bc = new Bot_Command__c(Sample_Utterance__c='help
lightning', apex_class__c='HandlerHelpTopic', pattern__c='help (.*)');
        insert bc;
        BotResponse response = BotController.submit('help lightning', null, null, null);
        Map<String, String> session = response.session;
        response = BotController.submit('Developer', session, null, null);
        System.assert(response.messages[0].items.size() > 0);
    }
    static testMethod void testHello() {
        BotHandler handler = new HandlerHello();
        BotResponse response = handler.handle("", null, null, null, null);
        System.assert(response.messages[0].messageText == 'Hi there!');
    }
    static testMethod void testAddTwoNumbers() {

```

```

    BotHandler handler = new HandlerAddTwoNumbers();
    BotResponse response = handler.handle("", null, null, null, null);
    Map<String, String> session = response.session;
    response = handler.handle('1', null, session, null, null);
    session = response.session;
    response = handler.handle('2', null, session, null, null);
    System.assert(response.messages[0].messageText == '1 + 2 = 3');
}

static testMethod void testCostCenter() {
    BotHandler handler = new HandlerCostCenter();
    BotResponse response = handler.handle("", null, null, null, null);
    System.assert(response.messages[0].messageText == 'Your cost center is 21852');
}

static testMethod void testEmployeeId() {
    BotHandler handler = new HandlerEmployeeId();
    BotResponse response = handler.handle("", null, null, null, null);
    System.assert(response.messages[0].messageText == 'Your employee id is 9854');
}

static testMethod void testFindAccount() {
    Account a = new Account(Name='TestAccount');
    insert a;
    BotHandler handler = new HandlerFindAccount();
    BotResponse response = handler.handle("", new String[]{'Test'}, null, null, null);
    System.assert(response.messages[0].records.size() == 1);
}

static testMethod void testFindContact() {
    Contact c = new Contact(LastName='TestContact');
    insert c;
    BotHandler handler = new HandlerFindContact();
    BotResponse response = handler.handle("", new String[]{'Test'}, null, null, null);
    System.assert(response.messages[0].records.size() == 1);
}

static testMethod void testHelp() {
    Bot_Command__c bc = new Bot_Command__c(Sample_Utterance__c='Hello',
    apex_class__c='HelloHandler', pattern__c='Hello');
    insert bc;
    BotHandler handler = new HandlerHelp();
    BotResponse response = handler.handle("", null, null, null, null);
    System.assert(response.messages[0].items.size() == 1);
}

static testMethod void testHelpTopic() {

```

```

        BotHandler handler = new HandlerHelpTopic();
        BotResponse response = handler.handle("", null, null, null, null);
        Map<String, String> session = response.session;
        handler.handle('User', null, session, null, null);
        response = handler.handle("", null, null, null, null);
        session = response.session;
        response = handler.handle('Admin', null, session, null, null);
        response = handler.handle("", null, null, null, null);
        session = response.session;
        response = handler.handle('Developer', null, session, null, null);
        System.assert(response.messages[0].items.size() > 0);
    }
    static testMethod void testMyOpenCases() {
        Case c = new Case(Subject='TestCase');
        insert c;
        BotHandler handler = new HandlerMyOpenCases();
        BotResponse response = handler.handle("", null, null, null, null);
        System.assert(response.messages[0].records.size() == 1);
    }
    static testMethod void testTopOpportunities() {
        Account a = new Account(Name='TestAccount');
        insert a;
        Opportunity o = new Opportunity(Name='TestOpportunity', AccountId=a.id,
        StageName='Prospecting', CloseDate=System.today().addMonths(1));
        insert o;
        BotHandler handler = new HandlerTopOpportunities();
        BotResponse response = handler.handle("", new String[]{ '3' }, null, null, null);
        System.assert(response.messages[0].records.size() == 1);
    }
    static testMethod void testTravelApproval() {
        BotHandler handler = new HandlerTravelApproval();
        BotResponse response = handler.handle("", null, null, null, null);
        Map<String, String> session = response.session;
        handler.handle('Boston', null, session, null, null);
        handler.handle('Customer Facing', null, session, null, null);
        handler.handle('02/23/2017', null, session, null, null);
        handler.handle('1000', null, session, null, null);
        handler.handle('1000', null, session, null, null);
        System.assert(response.messages[0].messageText.length() > 0);
    }
    static testMethod void testPipeline() {

```

```

        BotHandler handler = new HandlerPipeline();
        BotResponse response = handler.handle("", null, null, null, null);
        System.assert(response.messages[0].imageUrl != null);
    }
    static testMethod void testQuarter() {
        BotHandler handler = new HandlerQuarter();
        BotResponse response = handler.handle("", null, null, null, null);
        System.assert(response.messages[0].imageUrl != null);
    }
    static testMethod void testNext() {
Account a = new Account(Name='TestAccount');
insert a;
Opportunity o = new Opportunity(Name='TestOpportunity', AccountId=a.id,
StageName='Prospecting', CloseDate=System.today().addMonths(1));
insert o;
Case c = new Case(Subject='TestCase', Priority='High');
insert c;
        BotHandler handler = new HandlerNext();
        BotResponse response = handler.handle("", null, null, null, null);
        System.assert(response.messages.size() > 1);
    }
    static testMethod void testSOQL() {
Account a = new Account(Name='TestAccount');
insert a;
        BotHandler handler = new HandlerSOQL();
        BotResponse response = handler.handle('select id from account', null, null, null,
null);
        System.assert(response.messages[0].records.size() == 1);
    }
    static testMethod void testFindPropertiesByBedrooms() {
        Property__c p = new Property__c(Name='TestProperty', Beds__c=3,
City__c='Boston');
        insert p;
        BotHandler handler = new HandlerFindPropertiesByBedrooms();
        BotResponse response = handler.handle("", new String[]{ '3', 'Boston'}, null, null, null);
        System.assert(response.messages[0].records.size() == 1);
    }
    static testMethod void testFindProperties() {
        Property__c p = new Property__c(Name='TestProperty', Price__c=450000,
City__c='Boston');
        insert p;

```

```

    BotHandler handler = new HandlerFindProperties();
    Map<String, String> session = handler.handle("", null, null, null, null).session;
    session = handler.handle('Boston', null, session, null, null).session;
    session = handler.handle('Single Family', null, session, null, null).session;
    session = handler.handle('400000', null, session, null, null).session;
    BotResponse response = handler.handle('500000', null, session, null, null);
    System.assert(response.messages[0].records.size() == 1);
}
}

DreamHouseSampleDataController.apxc :
global with sharing class DreamHouseSampleDataController {
    @RemoteAction
    global static void deleteAll() {
        DELETE [SELECT ID FROM favorite__c];
        DELETE [SELECT ID FROM property__c];
        DELETE [SELECT ID FROM broker__c];
        DELETE [SELECT ID FROM bot_command__c];
    }
}

EinsteinVisionController.apxc :
global with sharing class EinsteinVisionController {
    public static String VISION_API = 'https://api.metamind.io/v1/vision';
    private static final Dreamhouse_Settings__c settings =
    Dreamhouse_Settings__c.getOrgDefaults();
    public class Prediction {
        @AuraEnabled
        public String label {get;set;}
        @AuraEnabled
        public Double probability {get;set;}
    }

    // You can upload the 'einstein_platform.pem' into your Salesforce org as 'File' sObject
    and read it as below
    private static String getAccessToken() {
        if (settings == null || String.isEmpty(settings.Einstein_Vision_Email__c)) {
            throw new AuraHandledException('Cannot create Einstein Vision token: "Einstein
            Vision Email" not defined in Custom Settings');
        }
        ContentVersion base64Content;
        try {
            base64Content = [SELECT Title, VersionData FROM ContentVersion where
            Title='einstein_platform' LIMIT 1];

```

```

    } catch (Exception e) {
        throw new AuraHandledException('Cannot create Einstein Vision token:
einstein_platform.pem file not found');
    }
    String keyContents = base64Content.VersionData.toString();
    keyContents = keyContents.replace('-----BEGIN RSA PRIVATE KEY-----', "");
    keyContents = keyContents.replace('-----END RSA PRIVATE KEY-----', "");
    keyContents = keyContents.replace('\n', "");
    // Get a new token
    JWT jwt = new JWT('RS256');
    jwt.pkcs8 = keyContents; // Comment this if you are using jwt.cert
    jwt.iss = 'developer.force.com';
    jwt.sub = settings.Einstein_Vision_Email__c;
    jwt.aud = 'https://api.metamind.io/v1/oauth2/token';
    jwt.exp = '3600';
    String access_token;
    if (!Test.isRunningTest()) {
        access_token =
    JWTBearerFlow.getAccessToken('https://api.metamind.io/v1/oauth2/token', jwt);
    }
    return access_token;
}

@AuraEnabled
public static List<Prediction> predict(String fileName, String content, String modelId) {
    if (String.isBlank(modelId)) {
        return EinsteinVisionController.predictDemo(fileName, content);
    } else {
return EinsteinVisionController.predictReal(fileName, content, modelId);
    }
}

@AuraEnabled
public static List<Prediction> predictReal(String fileName, String content, String
modelId) {
    String access_token;
    try {
access_token = EinsteinVisionController.getAccessToken();
    } catch (Exception e) {
throw new AuraHandledException('Cannot create Einstein Vision token.
Did you upload the einstein_platform.pem file and specify the Einstein Vision email
address to use in Custom Settings?');
    }
}

```

```

        List<Prediction> predictions = EinsteinVisionController.predictInternal(content,
access_token, modelId, true);
        return predictions;
    }
    @AuraEnabled
    public static List<Prediction> predictDemo(String fileName, String content) {
Integer pos = fileName.indexOf('_');
        String label;
        if (pos > 0) {
            // if the filename is like "victorian_01.jpg", we return "victorian"
label = fileName.substring(0, pos);
        } else {
            // else we return a category selected randomly
List<String> categories = new List<String>{'Victorian', 'Colonial', 'Contemporary'};
Integer index = Math.mod(Math.round(Math.random()*1000), 3);
label = categories[index];
        }
        List<Prediction> predictions = new List<Prediction>();
        Prediction prediction = new Prediction();
        prediction.label = label;
        prediction.probability = 1;
        predictions.add(prediction);
        return predictions;
    }
    @AuraEnabled
    public static String getDatasets() {
        String access_token = EinsteinVisionController.getAccessToken();
        HttpRequest req = new HttpRequest();
        req.setMethod('GET');
        req.setHeader('Authorization', 'Bearer ' + access_token);
        req.setHeader('Cache-Control', 'no-cache');
        req.setEndpoint(VISION_API + '/datasets');
try {
        Http http = new Http();
        if (!Test.isRunningTest()) {
            HTTPResponse res = http.send(req);
            return res.getBody();
        } else {
            return "";
        }
    } catch (Exception ex){

```



```

        return '{"error": "' + ex.getMessage() + '"}';
    }
}

@AuraEnabled
public static String getModelsByDataset(Integer datasetId) {
    String accessToken = EinsteinVisionController.getAccessToken();
    HttpRequest req = new HttpRequest();
    req.setMethod('GET');
    String endpoint = VISION_API + '/datasets/' + datasetId + '/models';
    req.setEndpoint(endpoint);
    req.setHeader('Authorization', 'Bearer ' + accessToken);
    req.setHeader('Cache-Control', 'no-cache');
    try {
        Http http = new Http();
        if (!Test.isRunningTest()) {
            HTTPResponse res = http.send(req);
        }
        return res.getBody();
    } else {
        return null;
    }
} catch (Exception ex) {
    return '{"error": "' + ex.getMessage() + '"}';
}

}

@AuraEnabled
public static String deleteDataset(Integer datasetId) {
    String accessToken = EinsteinVisionController.getAccessToken();
    String endpoint = VISION_API + '/datasets/' + datasetId;
    HttpRequest req = new HttpRequest();
    req.setMethod('DELETE');
    req.setEndpoint(endpoint);
    req.setHeader('Authorization', 'Bearer ' + accessToken);
    req.setHeader('Cache-Control', 'no-cache');
    try {
        Http http = new Http();
        if (!Test.isRunningTest()) {
            HTTPResponse res = http.send(req);
        }
        return res.getBody();
    } else {
        return null;
    }
}

```

```

    } catch(Exception ex){
        return '{"error": "' + ex.getMessage() + '"}';
    }
}

@AuraEnabled
public static String createDataset(String pathToZip) {
    System.debug(pathToZip);
    String accessToken = EinsteinVisionController.getAccessToken();
    String contentType = HttpFormBuilder.GetContentType();
    String form64 = "";
    form64 += HttpFormBuilder.WriteBoundary();
    form64 += HttpFormBuilder.WriteBodyParameter('path', pathToZip);
    form64 += HttpFormBuilder.WriteBoundary(HttpFormBuilder.EndingType.CrLf);
    Blob formBlob = EncodingUtil.base64Decode(form64);
    String contentLength = string.valueOf(formBlob.size());
    HttpRequest req = new HttpRequest();
    req.setBodyAsBlob(formBlob);
    req.setMethod('POST');
    req.setEndpoint(VISION_API + '/datasets/upload');
    req.setHeader('Authorization', 'Bearer ' + accessToken);
    req.setHeader('Connection', 'keep-alive');
    req.setHeader('Content-Length', contentLength);
    req.setHeader('Content-Type', contentType);
    try {
        Http http = new Http();
        if (!Test.isRunningTest()) {
            HTTPResponse res = http.send(req);
            return res.getBody();
        } else {
            return null;
        }
    } catch(Exception ex){
        return '{"error": "' + ex.getMessage() + '"}';
    }
}

@AuraEnabled
public static String trainModel(String modelName, Integer datasetId) {
    String accessToken = EinsteinVisionController.getAccessToken();
    String contentType = HttpFormBuilder.GetContentType();
    String form64 = "";
    form64 += HttpFormBuilder.WriteBoundary();

```

```

        form64 += HttpFormBuilder.WriteBodyParameter('name', modelName);
        form64 += HttpFormBuilder.WriteBoundary();
        form64 += HttpFormBuilder.WriteBodyParameter('datasetId', " + datasetId);
        form64 += HttpFormBuilder.WriteBoundary(HttpFormBuilder.EndingType.CrLf);
        blob formBlob = EncodingUtil.base64Decode(form64);
        string contentLength = string.valueOf(formBlob.size());
        HttpRequest req = new HttpRequest();
req.setBodyAsBlob(formBlob);
        req.setMethod('POST');
        req.setEndpoint(VISION_API + '/train');
        req.setHeader('Authorization', 'Bearer ' + accessToken);
req.setHeader('Connection', 'keep-alive');
req.setHeader('Content-Length', contentLength);
        req.setHeader('Content-Type', contentType);
req.setHeader('Cache-Control', 'no-cache');
req.setTimeout(120000);
try {
    Http http = new Http();
    if (!Test.isRunningTest()) {
        HTTPResponse res = http.send(req);
return res.getBody();
    } else {
        return null;
    }
} catch (Exception ex){
    return '{"error": "' + ex.getMessage() + '"}';
}
}

private static List<Prediction> predictInternal(String sample, String access_token,
String model, boolean isBase64) {
    string contentType = HttpFormBuilder.GetContentType();
    // Compose the form
    string form64 = "";
    form64 += HttpFormBuilder.WriteBoundary();
    form64 += HttpFormBuilder.WriteBodyParameter('modelId',
EncodingUtil.urlEncode(model, 'UTF-8'));
    form64 += HttpFormBuilder.WriteBoundary();
    if(isBase64) {
        form64 += HttpFormBuilder.WriteBodyParameter('sampleBase64Content',
sample);
    } else {

```

```

        form64 += HttpFormBuilder.WriteBodyParameter('sampleLocation', sample);
    }
    form64 += HttpFormBuilder.WriteBoundary(HttpFormBuilder.EndingType.CrLf);
    blob formBlob = EncodingUtil.base64Decode(form64);
    string contentLength = string.valueOf(formBlob.size());
    // Compose the http request
    HttpRequest httpRequest = new HttpRequest();
    httpRequest.setBodyAsBlob(formBlob);
    httpRequest.setHeader('Connection', 'keep-alive');
    httpRequest.setHeader('Content-Length', contentLength);
    httpRequest.setHeader('Content-Type', contentType);
    httpRequest.setMethod('POST');
    httpRequest.setTimeout(120000);
    httpRequest.setHeader('Authorization', 'Bearer ' + access_token);
    httpRequest.setEndpoint(VISION_API + '/predict');
    Http http = new Http();
    List<Prediction> predictions = new List<Prediction>();
    if (!Test.isRunningTest()) {
        try {
            HTTPResponse res = http.send(httpRequest);
            if (res.getStatusCode() == 200) {
                System.JSONParser parser = System.JSON.createParser(res.getBody());
                while (parser.nextToken() != null) {
                    if ((parser.getCurrentToken() == JSONToken.FIELD_NAME) &&
                        (parser.getText() == 'probabilities')) {
                        parser.nextToken();
                        if (parser.getCurrentToken() == JSONToken.START_ARRAY) {
                            while (parser.nextToken() != null) {
                                // Advance to the start object marker to
                                // find next probability object.
                                if (parser.getCurrentToken() == JSONToken.START_OBJECT) {
                                    // Read entire probability object
                                    Prediction probability =
                                    (Prediction)parser.readValueAs(Prediction.class);
                                    predictions.add(probability);
                                }
                            }
                        }
                    }
                    break;
                }
            }
        }
    }
}

```

```

        }
    } catch(System.CalloutException e) {
        System.debug('ERROR:' + e);
    }
}
return(predictions);
}
}
EinsteinVisionControllerTest.apxc :
@isTest
public class EinsteinVisionControllerTest {
    static testMethod void testPredict() {
        insert new Dreamhouse_Settings__c(Einstein_Vision_Email__c = 'user@host.com');
        Boolean success = true;
        try {
            ContentVersion cv = new ContentVersion(Title='einstein_platform',
PathOnClient='/', VersionData=Blob.valueOf('some key'));
            insert cv;
            EinsteinVisionController.predict('victorian.jpg', ", 'theModelId'");
            EinsteinVisionController.predict('victorian_01.jpg', ", ");
        } catch (Exception e) {
            success = false;
        } finally {
            System.assert(success);
        }
    }
    static testMethod void testGetDataSets() {
        insert new Dreamhouse_Settings__c(Einstein_Vision_Email__c = 'user@host.com');
        Boolean success = true;
        try {
            ContentVersion cv = new ContentVersion(Title='einstein_platform',
PathOnClient='/', VersionData=Blob.valueOf('some key'));
            insert cv;
            EinsteinVisionController.getDataSets();
        } catch (Exception e) {
            System.debug(e);
            success = false;
        } finally {
            System.assert(success);
        }
    }
}

```

```

static testMethod void testGetModelByDataset() {
    insert new Dreamhouse_Settings__c(Einstein_Vision_Email__c = 'user@host.com');
    Boolean success = true;
    try {
        ContentVersion cv = new ContentVersion(Title='einstein_platform',
PathOnClient='/', VersionData=Blob.valueOf('some key'));
        insert cv;
        EinsteinVisionController.getModelsByDataset(101);
    } catch (Exception e) {
        success = false;
    } finally {
        System.assert(success);
    }
}

static testMethod void testDeleteDataset() {
    insert new Dreamhouse_Settings__c(Einstein_Vision_Email__c = 'user@host.com');
    Boolean success = true;
    try {
        ContentVersion cv = new ContentVersion(Title='einstein_platform',
PathOnClient='/', VersionData=Blob.valueOf('some key'));
        insert cv;
        EinsteinVisionController.deleteDataset(101);
    } catch (Exception e) {
        success = false;
    } finally {
        System.assert(success);
    }
}

static testMethod void testCreateDataset() {
    insert new Dreamhouse_Settings__c(Einstein_Vision_Email__c = 'user@host.com');
    Boolean success = true;
    try {
        ContentVersion cv = new ContentVersion(Title='einstein_platform',
PathOnClient='/', VersionData=Blob.valueOf('some key'));
        insert cv;
        EinsteinVisionController.createDataset('path/to/zip');
    } catch (Exception e) {
        success = false;
    } finally {
        System.assert(success);
    }
}

```

```

    }
    static testMethod void testTrainModel() {
        insert new Dreamhouse_Settings__c(Einstein_Vision_Email__c = 'user@host.com');
        Boolean success = true;
        try {
            ContentVersion cv = new ContentVersion(Title='einstein_platform',
PathOnClient='/', VersionData=Blob.valueOf('some key'));
            insert cv;
            EinsteinVisionController.trainModel('theModelId', 101);
        } catch (Exception e) {
            success = false;
        } finally {
            System.assert(success);
        }
    }
    static testMethod void JWTIssue() {
        Boolean success = true;
        try {
            JWT jwt = new JWT('RS256');
            jwt.pkcs8 = 'some key';
            jwt.iss = 'developer.force.com';
            jwt.sub = 'user@server.com';
            jwt.aud = 'https://api.metamind.io/v1/oauth2/token';
            jwt.exp = '3600';
            try {
                String token = jwt.issue();
            } catch (Exception e1) {
            }
        } catch (Exception e2) {
            success = false;
        } finally {
            System.assert(success);
        }
    }
}

HandlerAddTwoNumbers.apxc :
public with sharing class HandlerAddTwoNumbers implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        if (session == null) {
            session = new Map<String, String>();

```

```

        session.put('nextCommand', 'HandlerAddTwoNumbers');
        session.put('step', 'askFirstNumber');
        return new BotResponse(new BotMessage('Bot', 'What\'s the first number?'),
session);
    }
    String step = session.get('step');
    if (step == 'askFirstNumber') {
        session.put('firstNumber', utterance);
        session.put('nextCommand', 'HandlerAddTwoNumbers');
        session.put('step', 'askSecondNumber');
        return new BotResponse(new BotMessage('Bot', 'What\'s the second number?'),
session);
    } else {
Integer firstNumber = Integer.valueOf(session.get('firstNumber'));
Integer secondNumber = Integer.valueOf(utterance);
Integer total = firstNumber + secondNumber;
BotMessage message = new BotMessage('Bot', " + firstNumber + ' + ' + secondNumber
+ ' = ' + total);
return new BotResponse(message);
    }
}
}
}

```

HandlerCostCenter.apxc :

```

public with sharing class HandlerCostCenter implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        return new BotResponse(new BotMessage('Bot', 'Your cost center is 21852'));
    }
}

```

HandlerEmployeeId.apxc :

```

public with sharing class HandlerEmployeeId implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        return new BotResponse(new BotMessage('Bot', 'Your employee id is 9854'));
    }
}

```

HandlerFileUpload.apxc :

```

public with sharing class HandlerFileUpload implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        try {

```



```

        ContentVersion v = new ContentVersion();
        v.versionData = EncodingUtil.base64Decode(fileContent);
        v.title = fileName;
        v.pathOnClient = fileName;
        insert v;
    ContentDocument doc = [SELECT Id FROM ContentDocument where
LatestPublishedVersionId = :v.Id];
    List<BotRecord> records = new List<BotRecord>();
        List<BotField> fields = new List<BotField>();
        fields.add(new BotField('Id', v.Id, '/sObject/ContentDocument/' + doc.Id));
        fields.add(new BotField('Name', v.title));
        records.add(new BotRecord(fields));
        return new BotResponse(new BotMessage('Bot', 'Your file was uploaded
successfully', records));
    } catch (Exception e) {
return new BotResponse(new BotMessage('Bot', 'An error occurred while
uploading the file'));
    }
}
}

HandlerFindAccount.apxc :
public with sharing class HandlerFindAccount implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        String key = '%' + params[0] + '%';
        List<Account> accounts =
            [SELECT Id, Name, Phone FROM Account
            WHERE Name LIKE :key
            ORDER BY Name
            LIMIT 5];
        List<BotRecord> records = new List<BotRecord>();
        for (Account a : accounts) {
            List<BotField> fields = new List<BotField>();
            fields.add(new BotField('Name', a.Name, '/sObject/' + a.Id + '/view' ));
            fields.add(new BotField('Phone', a.Phone, 'tel:' + a.Phone));
            records.add(new BotRecord(fields));
        }
        return new BotResponse(new BotMessage('Bot', 'Here is a list of accounts
matching "' + params[0] + "':", records));
    }
}

```

HandlerFindContact.apxc :

```
public with sharing class HandlerFindContact implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        String key = '%' + params[0] + '%';
        List<Contact> contacts =
            [SELECT Id, Name, MobilePhone FROM Contact
            WHERE Name LIKE :key
            ORDER BY Name
            LIMIT 5];
        List<BotRecord> records = new List<BotRecord>();
        for (Contact c : contacts) {
            List<BotField> fields = new List<BotField>();
            fields.add(new BotField('Name', c.Name, '#/sObject/' + c.Id + '/view'));
            fields.add(new BotField('Phone', c.MobilePhone, 'tel:' + c.MobilePhone));
            records.add(new BotRecord(fields));
        }
        return new BotResponse(new BotMessage('Bot', 'Here is a list of contacts matching
''' + params[0] + ''', records));
    }
}
```

HandlerFindProperties.apxc :

```
public class HandlerFindProperties implements BotHandler {
    private String formatCurrency(Decimal i) {
        if (i == null) return '0.00';
        i = Decimal.valueOf(Math.roundToLong(i * 100)) / 100;
        String s = (i.setScale(2) + (i >= 0 ? 0.001 : -0.001)).format();
        return s.substring(0, s.length() - 1);
    }

    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        if (session == null) {
            BotMessage message = new BotMessage('Bot', 'What City?');
            session = new Map<String, String>();
            session.put('nextCommand', 'HandlerFindProperties');
            session.put('step', 'city');
            return new BotResponse(message, session);
        }

        String step = session.get('step');
        if (step == 'city') {
            session.put('city', utterance);
        }
    }
}
```

```

List<BotMessageButton> buttons = new List<BotMessageButton>();
    buttons.add(new BotMessageButton('Single Family', 'Single Family'));
    buttons.add(new BotMessageButton('Condominium', 'Condominium'));
    BotMessage message = new BotMessage('Bot', 'What type of property?',
buttons);
    session.put('nextCommand', 'HandlerFindProperties');
    session.put('step', 'type');
    return new BotResponse(message, session);
} else if (step == 'type') {
    session.put('type', utterance);
    BotMessage message = new BotMessage('Bot', 'Price range from?');
    session.put('nextCommand', 'HandlerFindProperties');
    session.put('step', 'minPrice');
    return new BotResponse(message, session);
} else if (step == 'minPrice') {
    session.put('minPrice', utterance);
    BotMessage message = new BotMessage('Bot', 'Price range to?');
    session.put('nextCommand', 'HandlerFindProperties');
    session.put('step', 'maxPrice');
    return new BotResponse(message, session);
} else if (step == 'maxPrice') {
    session.put('maxPrice', utterance);
    String city = session.get('city');
    Decimal minPrice = Decimal.valueOf(session.get('minPrice'));
    Decimal maxPrice = Decimal.valueOf(session.get('maxPrice'));
    List<Property__c> properties =
        [SELECT Id, Name, Beds__c, Baths__c, Price__c FROM Property__c
        WHERE City__c = :city AND
        Price__c >= :minPrice AND
        Price__c <= :maxPrice
        ORDER BY Price__c
        LIMIT 5];
    List<BotRecord> records = new List<BotRecord>();
    for (Property__c p : properties) {
        List<BotField> fields = new List<BotField>();
        fields.add(new BotField('Name', p.Name, '#/sObject/' + p.Id + '/view'));
        fields.add(new BotField('Bedrooms', " + p.Beds__c));
        fields.add(new BotField('Baths', " + p.Baths__c));
        fields.add(new BotField('Price', " + this.formatCurrency(p.Price__c));
        records.add(new BotRecord(fields));
    }
}

```

```

        return new BotResponse(new BotMessage('Bot', 'Here is a list of properties in ' +
city + ' between ' + this.formatCurrency(minPrice) + ' and ' +
this.formatCurrency(maxPrice) + ': ', records));
    } else {
        return new BotResponse(new BotMessage('Bot', 'Sorry, I don\'t know how to
handle that'));
    }
}
}
}

```

HandlerFindPropertiesByBedrooms.apxc :

```

public with sharing class HandlerFindPropertiesByBedrooms implements BotHandler {
    private String formatCurrency(Decimal i) {
        if (i == null) return '0.00';
        i = Decimal.valueOf(Math.roundToLong(i * 100)) / 100;
        String s = (i.setScale(2) + (i >= 0 ? 0.001 : -0.001)).format();
        return s.substring(0, s.length() - 1);
    }
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        List<Property__c> properties =
            [SELECT Id, Name, Beds__c, Baths__c, Price__c FROM Property__c
            WHERE City__c = :params[1] AND
            Beds__c = :Decimal.valueOf(params[0])
            ORDER BY Price__c
            LIMIT 10];
        List<BotRecord> records = new List<BotRecord>();
        for (Property__c p : properties) {
            List<BotField> fields = new List<BotField>();
            fields.add(new BotField('Name', p.Name, '#/sObject/' + p.Id + '/view'));
            fields.add(new BotField('Bedrooms', " + p.Beds__c));
            fields.add(new BotField('Baths', " + p.Baths__c));
            fields.add(new BotField('Price', " + this.formatCurrency(p.Price__c));
            records.add(new BotRecord(fields));
        }
        return new BotResponse(new BotMessage('Bot', 'Here is a list of ' + params[0] + '
bedrooms in ' + params[1] + ': ', records));
    }
}
}

```

HandlerHello.apxc :

```

public with sharing class HandlerHello implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>

```

```

session, String fileName, String fileContent) {
    return new BotResponse(new BotMessage('Bot', 'Hi there!'));
}
}

```

HandlerHelp.apxc :

```

public with sharing class HandlerHelp implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
List<Bot_Command__c> commands =
    [SELECT Id, Sample_Utterance__c FROM Bot_Command__c
    WHERE Sample_Utterance__c != null And Active__C = True ORDER BY
Sample_Utterance__c];
List<BotItem> items = new List<BotItem>();
    for (Bot_Command__c c : commands) {
        items.add(new BotItem(c.Sample_Utterance__c));
    }
    BotMessage message = new BotMessage('Bot', 'You can ask me things like:',
items);
    return new BotResponse(message);
}
}

```

HandlerHelpTopic.apxc :

```

public with sharing class HandlerHelpTopic implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
    if (session == null) {
List<BotMessageButton> buttons = new List<BotMessageButton>();
        buttons.add(new BotMessageButton('User', 'User'));
        buttons.add(new BotMessageButton('Admin', 'Admin'));
        buttons.add(new BotMessageButton('Developer', 'Developer'));
        BotMessage message = new BotMessage('Bot', 'What best describes your role?',
buttons);
        session = new Map<String, String>();
        session.put('nextCommand', 'HandlerHelpTopic');
        return new BotResponse(message, session);
    }
List<BotItem> items = new List<BotItem>();
    if (utterance == 'User') {
        items.add(new BotItem('Salesforce User Tour',
'https://trailhead.salesforce.com/modules/lex_salesforce_tour'));
        items.add(new BotItem('Lightning Experience Features',

```

```

'https://trailhead.salesforce.com/modules/lex_migration_whatsnew'));
    items.add(new BotItem('Lightning Experience Chatter Basics',
'https://trailhead.salesforce.com/modules/lex_implementation_chatter'));
    } else if (utterance == 'Admin') {
        items.add(new BotItem('Lightning Experience Basics',
'https://trailhead.salesforce.com/modules/lex_migration_introduction'));
        items.add(new BotItem('Lightning Experience Features',
'https://trailhead.salesforce.com/modules/lex_migration_whatsnew'));
        items.add(new BotItem('Lightning Apps',
'https://trailhead.salesforce.com/modules/lightning_apps'));
        items.add(new BotItem('Lightning Experience Reports & Dashboards',
'https://trailhead.salesforce.com/modules/lex_implementation_reports_dashboards'));
    } else if (utterance == 'Developer') {
        items.add(new BotItem('Lightning Experience Development',
'https://trailhead.salesforce.com/modules/lex_dev_overview'));
        items.add(new BotItem('Lightning Components Basics',
'https://trailhead.salesforce.com/modules/lex_dev_lc_basics'));
        items.add(new BotItem('Visualforce & Lightning Experience',
'https://trailhead.salesforce.com/modules/lex_dev_visualforce'));
    }
    BotMessage message = new BotMessage('Bot', 'I recommend the following
Trailhead Modules:', items);
    return new BotResponse(message);
}
}

```

HandlerImageBasedSearch.apxc :

```

public with sharing class HandlerImageBasedSearch implements BotHandler {
    private String modelId = 'VNAIIMX543MNUEKPW6UWAJPKKY';
    private String formatCurrency(Decimal i) {
        if (i == null) return '0';
        i = Decimal.valueOf(Math.roundToLong(i * 100)) / 100;
        String s = (i.setScale(2) + (i >= 0 ? 0.001 : -0.001)).format();
        return '$' + s.substring(0, s.length() - 1);
    }
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        List<EinsteinVisionController.Prediction> predictions =
EinsteinVisionController.predict("", fileContent, modelId);
        List<BotRecord> records = new List<BotRecord>();
        for (EinsteinVisionController.Prediction p : predictions) {
            List<BotField> fields = new List<BotField>();

```

```

        fields.add(new BotField('House Type', p.label));
        fields.add(new BotField('Probability', " + (p.probability * 100).round() + '%'));
        records.add(new BotRecord(fields));
    }
    BotMessage predictionMessage = new BotMessage('DreamBot', null, records);
    String key = '%' + predictions[0].label + '%';
    List<Property__c> properties =
        [SELECT Id, Name, Beds__c, Baths__c, Tags__c, Price__c FROM Property__c
        WHERE tags__c LIKE :key
        ORDER BY Price__c
        LIMIT 5];
    List<BotRecord> propertyRecords = new List<BotRecord>();
    for (Property__c p : properties) {
        List<BotField> fields = new List<BotField>();
        fields.add(new BotField('Name', p.Name, '#/sObject/' + p.Id + '/view'));
        fields.add(new BotField('Bedrooms', " + p.Beds__c));
        fields.add(new BotField('Category', " + p.Tags__c));
        fields.add(new BotField('Price', " + this.formatCurrency(p.Price__c));
        propertyRecords.add(new BotRecord(fields));
    }
    BotMessage propertyMessage = new BotMessage('DreamBot', 'Here is a list of
houses that look similar:', propertyRecords);
    BotResponse r = new BotResponse();
    r.messages = new BotMessage[] {predictionMessage, propertyMessage};
    return r;
}
}
HandlerMyOpenCases.apxc :
public with sharing class HandlerMyOpenCases implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        List<Case> cases =
            [SELECT Id, CaseNumber, Subject, Status, Priority, Contact.Id, Contact.Name
            FROM Case WHERE OwnerId =:UserInfo.getUserId() AND Status != 'Closed'];
        List<BotRecord> records = new List<BotRecord>();
        for (Case c : cases) {
            List<BotField> fields = new List<BotField>();
            fields.add(new BotField('Case Number', c.CaseNumber, '#/sObject/' + c.Id +
'/view'));
            fields.add(new BotField('Subject', c.Subject));
            fields.add(new BotField('Priority', c.Priority));

```

```

        fields.add(new BotField('Status', c.Status));
        fields.add(new BotField('Contact', c.Contact.Name, '#/sObject/' + c.Contact.Id +
'/view'));
        records.add(new BotRecord(fields));
    }
    BotMessage message = new BotMessage('Bot', 'Here are your open cases:',
records);
    return new BotResponse(message);
}
}

```

HandlerNext.apxc :

```

public with sharing class HandlerNext implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        List<Opportunity> opportunities =
            [SELECT Id, Name, Amount, Probability, StageName, CloseDate FROM
Opportunity WHERE isClosed=false ORDER BY amount DESC LIMIT 1];
        List<BotRecord> opportunityRecords = new List<BotRecord>();
        for (Opportunity o : opportunities) {
            List<BotField> fields = new List<BotField>();
            fields.add(new BotField('Name', o.Name, '#/sObject/' + o.Id + '/view'));
            fields.add(new BotField('Amount', '$' + o.Amount));
            fields.add(new BotField('Probability', " + o.Probability + '%'));
            fields.add(new BotField('Stage', o.StageName));
            opportunityRecords.add(new BotRecord(fields));
        }
        BotMessage opportunityMessage = new BotMessage('Bot', 'You have an overdue
item for the following opportunity:', opportunityRecords);
        List<Case> cases =
            [SELECT Id, CaseNumber, Subject, Status, Priority, Contact.Id, Contact.Name
FROM Case WHERE OwnerId =:UserInfo.getUserId() AND Priority='High' AND Status !=
'Closed'];
        List<BotRecord> caseRecords = new List<BotRecord>();
        for (Case c : cases) {
            List<BotField> fields = new List<BotField>();
            fields.add(new BotField('Case Number', c.CaseNumber, '#/sObject/' + c.Id +
'/view'));
            fields.add(new BotField('Subject', c.Subject));
            fields.add(new BotField('Status', c.Status));
            fields.add(new BotField('Contact', c.Contact.Name, '#/sObject/' + c.Contact.Id +
'/view'));

```



```

        caseRecords.add(new BotRecord(fields));
    }
    BotMessage caseMessage = new BotMessage('Bot', 'You should work on these
high priority cases assigned to you:', caseRecords);
    BotResponse r = new BotResponse();
    r.messages = new BotMessage[] {opportunityMessage, caseMessage};
    return r;
}
}
HandlerPipeline.apxc :
public with sharing class HandlerPipeline implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        return new BotResponse(new BotMessage('Bot', 'Here is your pipeline:', 'https://s3-
us-west-1.amazonaws.com/sfdc-demo/charts/pipeline.png'));
    }
}
HandlerQuarter.apxc :
public with sharing class HandlerQuarter implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        return new BotResponse(new BotMessage('Bot', 'Your quarter so far:', 'https://s3-uswest-
1.amazonaws.com/sfdc-demo/charts/quarter2.png'));
    }
}
HandlerSOQL.apxc :
public with sharing class HandlerSOQL implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        SObject[] objects = Database.query(utterance);
        List<BotRecord> records = new List<BotRecord>();
        for (SObject o : objects) {
            List<BotField> fields = new List<BotField>();
            Map<String, Object> fieldMap = o.getPopulatedFieldsAsMap();
            for (String fieldName : fieldMap.keySet()) {
                String linkURL;
                if (fieldName == 'Id') {
                    linkURL = '#/sObject/' + o.Id + '/view';
                }
                fields.add(new BotField(fieldName, " + fieldMap.get(fieldName), linkURL));
            }
        }
    }
}

```

```

        records.add(new BotRecord(fields));
    }
    return new BotResponse(new BotMessage('Bot', 'Here is the result of your query:',
records));
    }
}

HandlerTopOpportunities.apxc :
public with sharing class HandlerTopOpportunities implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        Integer qty = Integer.valueOf(params[0]);
        List<Opportunity> opportunities =
            [SELECT Id, Name, Amount, Probability, StageName, CloseDate FROM
Opportunity where isClosed=false ORDER BY amount DESC LIMIT :qty];
        List<BotRecord> records = new List<BotRecord>();
        for (Opportunity o : opportunities) {
            List<BotField> fields = new List<BotField>();
            fields.add(new BotField('Name', o.Name, '#/sObject/' + o.Id + '/view'));
            fields.add(new BotField('Amount', '$' + o.Amount));
            fields.add(new BotField('Probability', " + o.Probability + '%'));
            fields.add(new BotField('Stage', o.StageName));
            records.add(new BotRecord(fields));
        }
        return new BotResponse(new BotMessage('Bot', 'Here are your top ' + params[0] + '
opportunities:', records));
    }
}

HandlerTravelApproval.apxc :
public class HandlerTravelApproval implements BotHandler {
    public BotResponse handle(String utterance, String[] params, Map<String, String>
session, String fileName, String fileContent) {
        if (session == null) {
            BotMessage message = new BotMessage('Bot', 'Where are you going?');
            session = new Map<String, String>();
            session.put('nextCommand', 'HandlerTravelApproval');
            session.put('step', 'destination');
            return new BotResponse(message, session);
        }
        String step = session.get('step');
        if (step == 'destination') {
            session.put('destination', utterance);

```

```

List<BotMessageButton> buttons = new List<BotMessageButton>();
    buttons.add(new BotMessageButton('Customer Facing', 'Customer Facing'));
    buttons.add(new BotMessageButton('Internal Meetings', 'Internal Meetings'));
    buttons.add(new BotMessageButton('Billable Work', 'Billable Work'));
    BotMessage message = new BotMessage('Bot', 'What\'s the reason for the trip?',
buttons);
    session.put('nextCommand', 'HandlerTravelApproval');
    session.put('step', 'reason');
    return new BotResponse(message, session);
} else if (step == 'reason') {
    session.put('reason', utterance);
    BotMessage message = new BotMessage('Bot', 'When are you leaving?');
    session.put('nextCommand', 'HandlerTravelApproval');
    session.put('step', 'travelDate');
    return new BotResponse(message, session);
} else if (step == 'travelDate') {
    session.put('travelDate', utterance);
    BotMessage message = new BotMessage('Bot', 'What\'s the estimated airfare
cost?');
    session.put('nextCommand', 'HandlerTravelApproval');
    session.put('step', 'airfare');
    return new BotResponse(message, session);
} else if (step == 'airfare') {
    session.put('airfare', utterance);
    BotMessage message = new BotMessage(' Bot', 'What\'s the estimated hotel
cost?');
    session.put('nextCommand', 'HandlerTravelApproval');
    session.put('step', 'hotel');
    return new BotResponse(message, session);
}
List<Botrecord> records = new List<BotRecord>();
List<BotField> fields = new List<BotField>();
fields.add(new BotField('Destination', session.get('destination')));
fields.add(new BotField('Reason', session.get('reason')));
fields.add(new BotField('Travel Date', session.get('travelDate')));
fields.add(new BotField('Airfare', session.get('airfare')));
fields.add(new BotField('Hotel', utterance));
records.add(new BotRecord(fields));
return new BotResponse(new BotMessage('Bot', 'OK, I submitted the following
travel approval request on your behalf:', records));
}

```

HttpFormBuilder.apxc :

```
public class HttpFormBuilder {  
    // The boundary is alligned so it doesn't produce padding characters when base64  
    encoded.
```

```
    private final static string Boundary = '1ff13444ed8140c7a32fc4e6451aa76d';
```

```
    /**
```

```
     * Returns the request's content type for multipart/form-data requests.
```

```
    */
```

```
    public static string GetContentType() {
```

```
        return 'multipart/form-data; charset="UTF-8"; boundary="' + Boundary + '"';
```

```
    }
```

```
    /**
```

```
     * Pad the value with spaces until the base64 encoding is no longer padded.
```

```
    */
```

```
    private static string SafelyPad(  
        string value,
```

```
        string valueCrLf64,
```

```
        string lineBreaks) {
```

```
        string valueCrLf = ";
```

```
        blob valueCrLfBlob = null;
```

```
        while (valueCrLf64.endsWith('=')) {
```

```
            value += ' ';
```

```
            valueCrLf = value + lineBreaks;
```

```
            valueCrLfBlob = blob.valueOf(valueCrLf);
```

```
            valueCrLf64 = EncodingUtil.base64Encode(valueCrLfBlob);
```

```
        }
```

```
        return valueCrLf64;
```

```
    }
```

```
    /**
```

```
     * Write a boundary between parameters to the form's body.
```

```
    */
```

```
    public static string WriteBoundary() {
```

```
        string value = '--' + Boundary + '\r\n';
```

```
        blob valueBlob = blob.valueOf(value);
```

```
        return EncodingUtil.base64Encode(valueBlob);
```

```
    }
```

```
    /**
```

```
     * Write a boundary at the end of the form's body.
```

```
    */
```

```
    public static string WriteBoundary(  
        EndingType ending) {
```

```
        EndingType ending) {
```

```

string value = "";
if (ending == EndingType.Cr) {
    // The file's base64 was padded with a single '=',
    // so it was replaced with '\r'. Now we have to
    // prepend the boundary with '\n' to complete
    // the line break.
    value += '\n';
} else if (ending == EndingType.None) {
    // The file's base64 was not padded at all,
    // so we have to prepend the boundary with
    // '\r\n' to create the line break.
    value += '\r\n';
}
// Else:
// The file's base64 was padded with a double '=',
// so they were replaced with '\r\n'. We don't have to
// do anything to the boundary because there's a complete
// line break before it.
value += '--' + Boundary + '--';
blob valueBlob = blob.valueOf(value);
return EncodingUtil.base64Encode(valueBlob);
}
/**
 * Write a key-value pair to the form's body.
 */
public static string WriteBodyParameter(
    string key,
    string value) {
    string contentDisposition = 'Content-Disposition: form-data; name="' + key + '"';
    string contentDispositionCrLf = contentDisposition + '\r\n\r\n';
    blob contentDispositionCrLfBlob = blob.valueOf(contentDispositionCrLf);
    string contentDispositionCrLf64 =
EncodingUtil.base64Encode(contentDispositionCrLfBlob);
    string content = SafelyPad(contentDisposition, contentDispositionCrLf64, '\r\n\r\n');
    string valueCrLf = value + '\r\n';
    blob valueCrLfBlob = blob.valueOf(valueCrLf);
    string valueCrLf64 = EncodingUtil.base64Encode(valueCrLfBlob);
    content += SafelyPad(value, valueCrLf64, '\r\n');
    return content;
}
/**

```

\* Helper enum indicating how a file's base64 padding was replaced.

\*/

```
public enum EndingType {  
    Cr,  
    CrLf,  
    None  
}  
}
```

JWT.apxc :

```
public class JWT {  
    public String alg {get;set;}  
    public String iss {get;set;}  
    public String sub {get;set;}  
    public String aud {get;set;}  
    public String exp {get;set;}  
    public String iat {get;set;}  
    public Map<String,String> claims {get;set;}  
    public Integer validFor {get;set;}  
    public String cert {get;set;}  
    public String pkcs8 {get;set;}  
    public String privateKey {get;set;}  
    public static final String HS256 = 'HS256';  
    public static final String RS256 = 'RS256';  
    public static final String NONE = 'none';  
    public JWT(String alg) {  
        this.alg = alg;  
        this.validFor = 300;  
    }  
    public String issue() {  
        String jwt = "  
        JSONGenerator header = JSON.createGenerator(false);  
        header.writeStartObject();  
        header.writeStringField('alg', this.alg);  
        header.writeEndObject();  
        String encodedHeader = base64URLencode(Blob.valueOf(header.getAsString()));  
        JSONGenerator body = JSON.createGenerator(false);  
        body.writeStartObject();  
        body.writeStringField('iss', this.iss);  
        body.writeStringField('sub', this.sub);  
        body.writeStringField('aud', this.aud);  
        Long rightNow = (dateTime.now().getTime()/1000)+1;
```

```

body.writeNumberField('iat', rightNow);
body.writeNumberField('exp', (rightNow + validFor));
if (claims != null) {
    for (String claim : claims.keySet()) {
        body.writeStringField(claim, claims.get(claim));
    }
}
body.writeEndObject();
jwt = encodedHeader + '.' + base64URLencode(Blob.valueOf(body.getAsString()));
if ( this.alg == HS256 ) {
    Blob key = EncodingUtil.base64Decode(privateKey);
    Blob signature = Crypto.generateMac('hmacSHA256',Blob.valueOf(jwt),key);
    jwt += '.' + base64URLencode(signature);
} else if ( this.alg == RS256 ) {
    Blob signature = null;
    if (cert != null ) {
        signature = Crypto.signWithCertificate('rsa-sha256', Blob.valueOf(jwt), cert);
    } else {
        Blob privateKey = EncodingUtil.base64Decode(pkcs8);
        signature = Crypto.sign('rsa-sha256', Blob.valueOf(jwt), privateKey);
    }
    jwt += '.' + base64URLencode(signature);
} else if ( this.alg == NONE ) {
    jwt += '.';
}
return jwt;
}

public String base64URLencode(Blob input){
    String output = encodingUtil.base64Encode(input);
    output = output.replace('+', '-');
    output = output.replace('/', '_');
    while ( output.endsWith('=')){
        output = output.substring(0,output.length()-1);
    }
    return output;
}
}

JWTBearerFlow.apxc :
public class JWTBearerFlow {
    public static String getAccessToken(String tokenEndpoint, JWT jwt) {
        String access_token = null;

```

```

String body = 'grant_type=urn%3Aietf%3Aparams%3Aoauth%3Agrant-
type%3Ajwtbearer&assertion=' + jwt.issue();
HttpRequest req = new HttpRequest();
req.setMethod('POST');
req.setEndpoint(tokenEndpoint);
req.setHeader('Content-type', 'application/x-www-form-urlencoded');
req.setBody(body);
Http http = new Http();
HTTPResponse res = http.send(req);
if ( res.getStatusCode() == 200 ) {
    System.JSONParser parser = System.JSON.createParser(res.getBody());
    while (parser.nextToken() != null) {
        if ((parser.getCurrentToken() == JSONToken.FIELD_NAME) &&
(parser.getText() == 'access_token')) {
            parser.nextToken();
            access_token = parser.getText();
            break;
        }
    }
}
return access_token;
}
}
}

```

```

LIFXController.apxc :
public with sharing class LIFXController {
    private static final Dreamhouse_Settings__c settings =
Dreamhouse_Settings__c.getOrgDefaults();
    @AuraEnabled
    public static String getLights() {
        HttpRequest req = new HttpRequest();
        Http http = new Http();
        req.setMethod('GET');
        req.setHeader('Authorization', 'Bearer ' + settings.LIFX_TOKEN__C);
        req.setEndpoint(settings.LIFX_URL__C + '/all');
try {
    HTTPResponse res = http.send(req);
return res.getBody();
} catch(Exception ex){
    return '{"error": "' + ex.getMessage() + '"}';
}
}

```



```

    }
    @AuraEnabled
    public static String setPower(String lightId, Boolean isOn) {
        return LIFXController.setState(lightId, '{"power": ' + (isOn == true ? 'on' : 'off') + '}');
    }
    @AuraEnabled
    public static String setBrightness(String lightId, Decimal brightness) {
        return LIFXController.setState(lightId, '{"brightness": ' + (brightness / 100) + '}');
    }
    public static String setState(String lightId, String state) {
        HttpRequest req = new HttpRequest();
        Http http = new Http();
        req.setMethod('PUT');
        req.setEndpoint(settings.LIFX_URL__C + '/' + lightId + '/state');
        req.setHeader('Authorization', 'Bearer ' + settings.LIFX_TOKEN__C);
        req.setHeader('Content-Type', 'application/json');
        req.setBody(state);
    try {
        HTTPResponse res = http.send(req);
    return res.getBody();
    } catch (Exception ex){
        return '{"error": ' + ex.getMessage() + '}';
    }
    }
}

LIFXControllerTest.apxc :
@isTest
public class LIFXControllerTest {
    static testMethod void testGetLights() {
        Boolean success = true;
        try {
            LIFXController.getLights();
        } catch (Exception e) {
            success = false;
        } finally {
            System.assert(success);
        }
    }
    static testMethod void testSetPower() {
        Boolean success = true;
        try {

```

```

        LIFXController.setPower('1', true);
    } catch (Exception e) {
        success = false;
    } finally {
        System.assert(success);
    }
}

static testMethod void testSetBrightness() {
    Boolean success = true;
    try {
        LIFXController.setBrightness('1', 1);
    } catch (Exception e) {
        success = false;
    } finally {
        System.assert(success);
    }
}
}

PostPriceChangeToSlack.apxc :
public class PostPriceChangeToSlack {
    @InvocableMethod(label='Post Price Change Notification to Slack')
    public static void postToSlack(List<Id> propertyId) {
String slackURL;
        Dreamhouse_Settings__c settings = Dreamhouse_Settings__c.getOrgDefaults();
        if (!Test.isRunningTest()) {
if (settings == null || settings.Slack_Property_Webhook_URL__c == null) {
            System.Debug('Slack_Property_Webhook_URL not set. Aborting
PostPriceChangeToSlack process action');
            return;
        } else {
slackURL = settings.Slack_Property_Webhook_URL__c;
        }
    }
        Id propId = propertyId[0]; // If bulk, only post first to avoid spamming
        Property__c property = [SELECT Address__c, City__c, State__c, Price__c from
Property__c WHERE Id=:propId];
        String message = 'Price change: ' + property.Address__c + ', ' + property.City__c + ' '
+ property.State__c + ' is now *$' + property.Price__c.setScale(0).format() + '*';
        System.Debug(message);
        Map<String,Object> payload = new Map<String,Object>();
        payload.put('text', message);

```

```

payload.put('mrkdwn', true);
    String body = JSON.serialize(payload);
    System.Debug(body);
    System.enqueueJob(new QueueableSlackCall(slackURL, 'POST', body));
}

public class QueueableSlackCall implements System.Queueable,
Database.AllowsCallouts {
    private final String url;
    private final String method;
    private final String body;
    public QueueableSlackCall(String url, String method, String body) {
        this.url = url;
        this.method = method;
        this.body = body;
    }
    public void execute(System.QueueableContext ctx) {
        HttpRequest req = new HttpRequest();
        req.setMethod(method);
        req.setBody(body);
        Http http = new Http();
        HttpResponse res;
        if (!Test.isRunningTest()) {
            req.setEndpoint(url);
            res = http.send(req);
        }
    }
}

VerifyDate.apxc :
public class VerifyDate {
    //method to handle potential checks against two dates
    public static Date CheckDates(Date date1, Date date2) {
        //if date2 is within the next 30 days of date1, use date2. Otherwise use the end
        of the month
        if(DateWithin30Days(date1,date2)) {
            return date2;
        } else {
            return SetEndOfMonthDate(date1);
        }
    }
    //method to check if date2 is within the next 30 days of date1

```

```

private static Boolean DateWithin30Days(Date date1, Date date2) {
//check for date2 being in the past
if( date2 < date1) { return false; }
//check that date2 is within (>=) 30 days of date1
Date date30Days = date1.addDays(30); //create a date 30 days away from date1
if( date2 >= date30Days ) { return false; }
else { return true; }
}
//method to return the end of the month of a given date
private static Date SetEndOfMonthDate(Date date1) {
Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
return lastDay;
}
}
TestVerifyDate.apxc :
@Test
public class TestVerifyDate {
    @Test static void test1(){
        Date d =
VerifyDate.CheckDates(Date.parse('01/01/2020'),Date.parse('01/03/2020'));
        System.assertEquals(Date.parse('01/03/2020'), d);
    }
    @Test static void test2(){
        Date d =
VerifyDate.CheckDates(Date.parse('01/01/2020'),Date.parse('03/03/2020'));
        System.assertEquals(Date.parse('01/31/2020'), d);
    }
}
AddPrimaryContactTest.apxc :
@Test
public class AddPrimaryContactTest {
    static testmethod void testQueueable(){
        List<Account> testAccounts = new List<Account>();
        for(Integer i=0;i<50;i++){
            testAccounts.add(new Account(Name='Account '+i,BillingState='CA'));
        }
        for(Integer j=0;j<50;j++){
            testAccounts.add(new Account(Name='Account '+j,BillingState='NY'));
        }
        insert testAccounts;
    }
}

```

```

    Contact testContact = new Contact(FirstName = 'john', LastName ='Doe');
    insert testContact;
    AddPrimaryContact addit = new addPrimaryContact(testContact,'CA');
    Test.startTest();
    system.enqueueJob(addit);
    Test.stopTest();
    System.assertEquals(50,[Select count() from Contact where accountId in (Select Id
from Account where BillingState='CA')]);
}
}

```

DailyLeadProcessor.apxc :

```

global class DailyLeadProcessor implements Schedulable{
    global void execute(SchedulableContext ctx){
        List<lead> leadstoupdate = new List<lead>();
        List<Lead> leads = [Select id From Lead Where LeadSource =NULL Limit 200];
        for(Lead l:leads){
            l.LeadSource = 'Dreamforce';
            leadstoupdate.add(l);
        }
        update leadstoupdate;
    }
}

```

DailyLeadProcessorTest.apxc :

```

@isTest
private class DailyLeadProcessorTest{
    //Seconds Minutes Hours Day_of_month Month Day_of_week optional_year
    public static String CRON_EXP = '0 0 0 2 6 ? 2022';
    static testmethod void testScheduledJob(){
        List<Lead> leads = new List<Lead>();
        for(Integer i = 0; i < 200; i++){
            Lead lead = new Lead(LastName = 'Test ' + i, LeadSource = "", Company = 'Test Company
' + i, Status = 'Open - Not Contacted');
            leads.add(lead);
        }
        insert leads;
        Test.startTest();
        // Schedule the test job
        String jobId = System.schedule('Update LeadSource to DreamForce', CRON_EXP, new
DailyLeadProcessor());
        // Stopping the test will run the job synchronously
        Test.stopTest();
    }
}

```

```
}  
}
```

AccountProcessor.apxc :

```
public class AccountProcessor {  
    @future  
    public static void countContacts(List<Id> accountIds){  
        List<Account> accountsToUpdate = new List<Account>();  
        List<Account> accounts = [Select Id, Name,(Select Id from Contacts) from Account  
Where Id in :accountIds];  
        For(Account acc:accounts){  
            List<Contact> contactList = acc.Contacts;  
            acc.Number_Of_Contacts__c = contactList.size();  
            accountsToUpdate.add(acc);  
        }  
        update accountsToUpdate;  
    }  
}
```

LeadProcessor.apxc :

```
global class LeadProcessor implements Database.Batchable<sObject> {  
    global Integer count = 0;  
    global Database.QueryLocator start(Database.BatchableContext bc){  
        return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');  
    }  
    global void execute(Database.BatchableContext bc, List<Lead> L_list){  
        List<lead> L_list_new = new List<lead>();  
        for(lead L:L_list){  
            L.leadsource = 'Dreamforce';  
            L_list_new.add(L);  
            count += 1;  
        }  
        update L_list_new;  
    }  
    global void finish(Database.BatchableContext bc){  
        System.debug('count = '+count);  
    }  
}
```

LeadProcessorTest.apxc :

```
@isTest  
public class LeadProcessorTest {  
    @isTest  
    public static void testit(){
```

```

List<lead> L_list = new List<lead>();
for (Integer i=0; i<200; i++){
    Lead L = new lead();
    L.LastName = 'name' + i;
    L.Company = 'Company';
    L.Status = 'Random Status';
    L_list.add(L);
}
insert L_list;
Test.startTest();
LeadProcessor lp = new LeadProcessor();
Id batchId = Database.executeBatch(lp);
Test.stopTest();
}
}

AccountProcessorTest.apxc :
@Test
private class AccountProcessorTest {
    @Test
    private static void testCountContacts(){
        Account newAccount = new Account(Name='Test Account');
        insert newAccount;
        Contact newContact1 = new Contact(FirstName='John',LastName='Doe',AccountId
= newAccount.Id);
        insert newContact1;
        Contact newContact2 = new Contact(FirstName='Jame',LastName='Doe',AccountId
= newAccount.Id);
        insert newContact2;
        List<Id> accountIds = new List<Id>();
        accountIds.add(newAccount.Id);
        Test.startTest();
        AccountProcessor.countContacts(accountIds);
        Test.stopTest();
    }
}

AddPrimaryContact.apxc :
public class AddPrimaryContact implements Queueable{
    private Contact con;
    private String state;
    public AddPrimaryContact(Contact con,String state){
        this.con=con;

```

```

        this .state = state;
    }
    public void execute (QueueableContext context){
        List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id from
contacts)
                                from Account where BillingState = :state Limit 200];
        List<Contact> primaryContacts = new List<Contact>();
        for(Account acc:accounts){
            Contact c = con.clone();
            c.AccountId = acc.Id;
            primaryContacts.add(c);
        }
        if(primaryContacts.size() > 0){
            insert primaryContacts;
        }
    }
}

```

TestRestrictContactByName.apxc :

@IsTest

public class TestRestrictContactByName {

@IsTest static void createBadContact(){

Contact c = new Contact(FirstName='John' ,LastName='INVALIDNAME');

Test.startTest();

Database.SaveResult result = Database.insert(c, false);

Test.stopTest();

System.assert(!result.isSuccess());

}

}

TestAccountDeletion.apxc :

@isTest

private class TestAccountDeletion {

@isTest static void TestDeleteAccountWithOneOpportunity() {

// Test data setup

// Create one account with one opportunity by calling a utility method

Account[] accts = TestDataFactory.createAccountsWithOpps(1,1);

// Perform test

Test.startTest();

Database.DeleteResult result = Database.delete(accts[0], false);

Test.stopTest();

// Verify that the deletion should have been stopped by the trigger,

// so check that we got back an error.



```

        System.assert(!result.isSuccess());
        System.assert(result.getErrors().size() > 0);
        System.assertEquals('Cannot delete account with related opportunities.',
            result.getErrors()[0].getMessage());
    }

    @isTest static void TestDeleteAccountWithNoOpportunities() {
        // Test data setup
        // Create one account with no opportunities by calling a utility method
        Account[] accts = TestDataFactory.createAccountsWithOpps(1,0);
        // Perform test
        Test.startTest();
        Database.DeleteResult result = Database.delete(accts[0], false);
        Test.stopTest();
        // Verify that the deletion was successful
        System.assert(result.isSuccess());
    }

    @isTest static void TestDeleteBulkAccountsWithOneOpportunity() {
        // Test data setup
        // Create accounts with one opportunity each by calling a utility method
        Account[] accts = TestDataFactory.createAccountsWithOpps(200,1);
        // Perform test
        Test.startTest();
        Database.DeleteResult[] results = Database.delete(accts, false);
        Test.stopTest();
        // Verify for each record.
        // In this case the deletion should have been stopped by the trigger,
        // so check that we got back an error.
        for(Database.DeleteResult dr : results) {
            System.assert(!dr.isSuccess());
            System.assert(dr.getErrors().size() > 0);
            System.assertEquals('Cannot delete account with related opportunities.',
                dr.getErrors()[0].getMessage());
        }
    }

    @isTest static void TestDeleteBulkAccountsWithNoOpportunities() {
        // Test data setup
        // Create accounts with no opportunities by calling a utility method
        Account[] accts = TestDataFactory.createAccountsWithOpps(200,0);
        // Perform test
        Test.startTest();
        Database.DeleteResult[] results = Database.delete(accts, false);
    }

```

```

        Test.stopTest();
        // For each record, verify that the deletion was successful
        for(Database.DeleteResult dr : results) {
            System.assert(dr.isSuccess());
        }
    }
}

VerifyDate.apxc :
public class VerifyDate {
    //method to handle potential checks against two dates
    public static Date CheckDates(Date date1, Date date2) {
        //if date2 is within the next 30 days of date1, use date2. Otherwise use the end
        //of the month
        if(DateWithin30Days(date1,date2)) {
            return date2;
        } else {
            return SetEndOfMonthDate(date1);
        }
    }

    //method to check if date2 is within the next 30 days of date1
    private static Boolean DateWithin30Days(Date date1, Date date2) {
        //check for date2 being in the past
        if( date2 < date1) { return false; }
        //check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1
        if( date2 >= date30Days ) { return false; }
        else { return true; }
    }

    //method to return the end of the month of a given date
    private static Date SetEndOfMonthDate(Date date1) {
        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
        Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
        return lastDay;
    }
}

TestDataFactory.apxc :
@isTest
public class TestDataFactory {
    public static List<Account> createAccountsWithOpps(Integer numAccts, Integer
numOppsPerAcct) {
        List<Account> accts = new List<Account>();

```

```

    for(Integer i=0;i<numAccts;i++) {
        Account a = new Account(Name='TestAccount' + i);
        accts.add(a);
    }
    insert accts;
    List<Opportunity> opps = new List<Opportunity>();
    for (Integer j=0;j<numAccts;j++) {
        Account acct = accts[j];
        // For each account just inserted, add opportunities
        for (Integer k=0;k<numOppsPerAcct;k++) {
            opps.add(new Opportunity(Name=acct.Name + ' Opportunity ' + k,
                                     StageName='Prospecting',
                                     CloseDate=System.today().addMonths(1),
                                     AccountId=acct.Id));
        }
    }
    // Insert all opportunities for all accounts.
    insert opps;
    return accts;
}
}

TestVerifyDate.apxc :
@isTest
public class TestVerifyDate {
    @isTest static void date2withn30daydate1(){
        Date returnDate1 = VerifyDate.CheckDates(date.valueOf('2022-05-04'),date.valueOf('2022-05-14'));
        System.assertEquals(date.valueOf('2022-05-14'), returnDate1);
    }
    @isTest static void date2NOTwithn30daydate1(){
        Date returnDate2 = VerifyDate.CheckDates(date.valueOf('2022-05-04'),date.valueOf('2022-06-14'));
        System.assertEquals(date.valueOf('2022-05-31'), returnDate2);
    }
}

RandomContactFactory.apxc :
public class RandomContactFactory {
    public static List<Contact> generateRandomContacts(Integer numOfContacts, String
lastName){
        List<Contact> contacts = new List<Contact>();
        for(Integer i=0;i<numOfContacts;i++) {

```

```

        Contact c = new Contact(FirstName='Test ' + i, LastName=lastName);
        contacts.add(c);
    }
    return contacts;
}
}

ContactsTodayController.apxc :
public class ContactsTodayController {
    @AuraEnabled
    public static List<Contact> getContactsForToday() {
        List<Task> my_tasks = [SELECT Id, Subject, Whold FROM Task WHERE OwnerId =
:UserInfo.getUserId() AND IsClosed = false AND Whold != null];
        List<Event> my_events = [SELECT Id, Subject, Whold FROM Event WHERE OwnerId
= :UserInfo.getUserId() AND StartDateTime >= :Date.today() AND Whold != null];
        List<Case> my_cases = [SELECT ID, ContactId, Status, Subject FROM Case WHERE
OwnerId = :UserInfo.getUserId() AND IsClosed = false AND ContactId != null];
        Set<Id> contactIds = new Set<Id>();
        for(Task tsk : my_tasks) {
            contactIds.add(tsk.Whold);
        }
        for(Event evt : my_events) {
            contactIds.add(evt.Whold);
        }
        for(Case cse : my_cases) {
            contactIds.add(cse.ContactId);
        }
        List<Contact> contacts = [SELECT Id, Name, Phone, Description FROM Contact
WHERE Id IN :contactIds];
        for(Contact c : contacts) {
            c.Description = "";
            for(Task tsk : my_tasks) {
                if(tsk.Whold == c.Id) {
                    c.Description += 'Because of Task "' + tsk.Subject + '"\n';
                }
            }
            for(Event evt : my_events) {
                if(evt.Whold == c.Id) {
                    c.Description += 'Because of Event "' + evt.Subject + '"\n';
                }
            }
            for(Case cse : my_cases) {

```

```

        if(cse.ContactId == c.Id) {
c.Description += 'Because of Case "' + cse.Subject + '"\n';
        }
    }
}
return contacts;
}
}

```

ContactsTodayControllerTest.apxc :

@IsTest

public class ContactsTodayControllerTest {

@IsTest

public static void testGetContactsForToday() {

Account acct = new Account(

Name = 'Test Account'

);

insert acct;

Contact c = new Contact(

AccountId = acct.Id,

FirstName = 'Test',

LastName = 'Contact'

);

insert c;

Task tsk = new Task(

Subject = 'Test Task',

Whold = c.Id,

Status = 'Not Started'

);

insert tsk;

Event evt = new Event(

Subject = 'Test Event',

Whold = c.Id,

StartDateTime = Date.today().addDays(5),

EndDateTime = Date.today().addDays(6)

);

insert evt;

Case cse = new Case(

Subject = 'Test Case',

ContactId = c.Id

);

insert cse;

```

        List<Contact> contacts = ContactsTodayController.getContactsForToday();
        System.assertEquals(1, contacts.size());
        System.assert(contacts[0].Description.containsIgnoreCase(tsk.Subject));
        System.assert(contacts[0].Description.containsIgnoreCase(evt.Subject));
        System.assert(contacts[0].Description.containsIgnoreCase(cse.Subject));
    }
    @IsTest
    public static void testGetNoContactsForToday() {
        Account acct = new Account(
            Name = 'Test Account'
        );
        insert acct;
        Contact c = new Contact(
            AccountId = acct.Id,
            FirstName = 'Test',
            LastName = 'Contact'
        );
        insert c;
        Task tsk = new Task(
            Subject = 'Test Task',
            WhoId = c.Id,
            Status = 'Completed'
        );
        insert tsk;
        Event evt = new Event(
            Subject = 'Test Event',
            WhoId = c.Id,
            StartDateTime = Date.today().addDays(-6),
            EndDateTime = Date.today().addDays(-5)
        );
        insert evt;
        Case cse = new Case(
            Subject = 'Test Case',
            ContactId = c.Id,
            Status = 'Closed'
        );
        insert cse;
        List<Contact> contacts = ContactsTodayController.getContactsForToday();
        System.assertEquals(0, contacts.size());
    }
}

```

CreateDefaultData.apxc :

```
public with sharing class CreateDefaultData{
    Static Final String TYPE_ROUTINE_MAINTENANCE = 'Routine Maintenance';
    //gets value from custom metadata How_We_Roll_Settings__mdt to know if Default
data was created
    @AuraEnabled
    public static Boolean isDataCreated() {
        How_We_Roll_Settings__c customSetting =
How_We_Roll_Settings__c.getOrgDefaults();
        return customSetting.Is_Data_Created__c;
    }
    //creates Default Data for How We Roll application
    @AuraEnabled
    public static void createDefaultData(){
        List<Vehicle__c> vehicles = createVehicles();
        List<Product2> equipment = createEquipment();
        List<Case> maintenanceRequest = createMaintenanceRequest(vehicles);
        List<Equipment_Maintenance_Item__c> joinRecords =
createJoinRecords(equipment, maintenanceRequest);
        updateCustomSetting(true);
    }
    public static void updateCustomSetting(Boolean isDataCreated){
        How_We_Roll_Settings__c customSetting =
How_We_Roll_Settings__c.getOrgDefaults();
        customSetting.Is_Data_Created__c = isDataCreated;
        upsert customSetting;
    }
    public static List<Vehicle__c> createVehicles(){
        List<Vehicle__c> vehicles = new List<Vehicle__c>();
        vehicles.add(new Vehicle__c(Name = 'Toy Hauler RV', Air_Conditioner__c = true,
Bathrooms__c = 1, Bedrooms__c = 1, Model__c = 'Toy Hauler RV'));
        vehicles.add(new Vehicle__c(Name = 'Travel Trailer RV', Air_Conditioner__c = true,
Bathrooms__c = 2, Bedrooms__c = 2, Model__c = 'Travel Trailer RV'));
        vehicles.add(new Vehicle__c(Name = 'Teardrop Camper', Air_Conditioner__c = true,
Bathrooms__c = 1, Bedrooms__c = 1, Model__c = 'Teardrop Camper'));
        vehicles.add(new Vehicle__c(Name = 'Pop-Up Camper', Air_Conditioner__c = true,
Bathrooms__c = 1, Bedrooms__c = 1, Model__c = 'Pop-Up Camper'));
        insert vehicles;
        return vehicles;
    }
    public static List<Product2> createEquipment(){
```

```

        List<Product2> equipments = new List<Product2>();
        equipments.add(new Product2(Warehouse_SKU__c =
'55d66226726b611100aaf741',name = 'Generator 1000 kW', Replacement_Part__c =
true, Cost__c = 100 ,Maintenance_Cycle__c = 100));
        equipments.add(new Product2(name = 'Fuse 20B',Replacement_Part__c =
true, Cost__c = 1000, Maintenance_Cycle__c = 30 ));
        equipments.add(new Product2(name = 'Breaker 13C',Replacement_Part__c =
true, Cost__c = 100 , Maintenance_Cycle__c = 15));
        equipments.add(new Product2(name = 'UPS 20 VA',Replacement_Part__c =
true, Cost__c = 200 , Maintenance_Cycle__c = 60));
        insert equipments;
        return equipments;
    }

    public static List<Case> createMaintenanceRequest(List<Vehicle__c> vehicles){
        List<Case> maintenanceRequests = new List<Case>();
        maintenanceRequests.add(new Case(Vehicle__c = vehicles.get(1).Id, Type =
TYPE_ROUTINE_MAINTENANCE, Date_Reported__c = Date.today()));
        maintenanceRequests.add(new Case(Vehicle__c = vehicles.get(2).Id, Type =
TYPE_ROUTINE_MAINTENANCE, Date_Reported__c = Date.today()));
        insert maintenanceRequests;
        return maintenanceRequests;
    }

    public static List<Equipment_Maintenance_Item__c>
createJoinRecords(List<Product2> equipment, List<Case> maintenanceRequest){
        List<Equipment_Maintenance_Item__c> joinRecords = new
List<Equipment_Maintenance_Item__c>();
        joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(0).Id, Maintenance_Request__c = maintenanceRequest.get(0).Id));
        joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(1).Id, Maintenance_Request__c = maintenanceRequest.get(0).Id));
        joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(2).Id, Maintenance_Request__c = maintenanceRequest.get(0).Id));
        joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(0).Id, Maintenance_Request__c = maintenanceRequest.get(1).Id));
        joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(1).Id, Maintenance_Request__c = maintenanceRequest.get(1).Id));
        joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(2).Id, Maintenance_Request__c = maintenanceRequest.get(1).Id));
        insert joinRecords;
        return joinRecords;
    }

```



```

}
CreateDefaultDataTest.apxc :
@isTest
private class CreateDefaultDataTest {
    @isTest
    static void createData_test(){
        Test.startTest();
        CreateDefaultData.createDefaultData();
        List<Vehicle__c> vehicles = [SELECT Id FROM Vehicle__c];
        List<Product2> equipment = [SELECT Id FROM Product2];
        List<Case> maintenanceRequest = [SELECT Id FROM Case];
        List<Equipment_Maintenance_Item__c> joinRecords = [SELECT Id FROM
Equipment_Maintenance_Item__c];
        System.assertEquals(4, vehicles.size(), 'There should have been 4 vehicles
created');
        System.assertEquals(4, equipment.size(), 'There should have been 4 equipment
created');
        System.assertEquals(2, maintenanceRequest.size(), 'There should have been 2
maintenance request created');
        System.assertEquals(6, joinRecords.size(), 'There should have been 6 equipment
maintenance items created');
    }
    @isTest
    static void updateCustomSetting_test(){
        How_We_Roll_Settings__c customSetting =
How_We_Roll_Settings__c.getOrgDefaults();
        customSetting.Is_Data_Created__c = false;
        upsert customSetting;
        System.assertEquals(false, CreateDefaultData.isDataCreated(), 'The custom setting
How_We_Roll_Settings__c.Is_Data_Created__c should be false');
        customSetting.Is_Data_Created__c = true;
        upsert customSetting;
        System.assertEquals(true, CreateDefaultData.isDataCreated(), 'The custom setting
How_We_Roll_Settings__c.Is_Data_Created__c should be true');
    }
}
WarehouseCalloutService.apxc :
public with sharing class WarehouseCalloutService {
    private static final String WAREHOUSE_URL = 'https://th-
superbadgeapex.herokuapp.com/equipment';
}

```

WarehouseCalloutServiceMock.apxc :

@isTest

global class WarehouseCalloutServiceMock implements HttpCalloutMock {

    // implement http mock callout

    global static HttpResponse respond(HttpRequest request){

        System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',

request.getEndpoint());

        System.assertEquals('GET', request.getMethod());

        // Create a fake response

        HttpResponse response = new HttpResponse();

        response.setHeader('Content-Type', 'application/json');

        response.setBody('{"\_id":"55d66226726b611100aaf741","replacement":false,"quantity":5  
,"name":"Generator 1000

kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}]');

        response.setStatusCode(200);

        return response;

    }

}

WarehouseCalloutServiceTest.apxc :

@isTest

private class WarehouseCalloutServiceTest {

    @isTest

    static void testWareHouseCallout(){

        Test.startTest();

        // implement mock callout test here

        Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());

        WarehouseCalloutService.runWarehouseEquipmentSync();

        Test.stopTest();

        System.assertEquals(1, [SELECT count() FROM Product2]);

    }

}

CreateDefaultData.apxc :

public with sharing class CreateDefaultData{

    Static Final String TYPE\_ROUTINE\_MAINTENANCE = 'Routine Maintenance';

    //gets value from custom metadata How\_We\_Roll\_Settings\_\_mdt to know if Default  
data was created

    @AuraEnabled

    public static Boolean isDataCreated() {

        How\_We\_Roll\_Settings\_\_c customSetting =

How\_We\_Roll\_Settings\_\_c.getOrgDefaults();

```

        return customSetting.Is_Data_Created__c;
    }
    //creates Default Data for How We Roll application
    @AuraEnabled
    public static void createDefaultData(){
        List<Vehicle__c> vehicles = createVehicles();
        List<Product2> equipment = createEquipment();
        List<Case> maintenanceRequest = createMaintenanceRequest(vehicles);
        List<Equipment_Maintenance_Item__c> joinRecords =
createJoinRecords(equipment, maintenanceRequest);
        updateCustomSetting(true);
    }
    public static void updateCustomSetting(Boolean isDataCreated){
        How_We_Roll_Settings__c customSetting =
How_We_Roll_Settings__c.getOrgDefaults();
        customSetting.Is_Data_Created__c = isDataCreated;
        upsert customSetting;
    }
    public static List<Vehicle__c> createVehicles(){
        List<Vehicle__c> vehicles = new List<Vehicle__c>();
        vehicles.add(new Vehicle__c(Name = 'Toy Hauler RV', Air_Conditioner__c = true,
Bathrooms__c = 1, Bedrooms__c = 1, Model__c = 'Toy Hauler RV'));
        vehicles.add(new Vehicle__c(Name = 'Travel Trailer RV', Air_Conditioner__c = true,
Bathrooms__c = 2, Bedrooms__c = 2, Model__c = 'Travel Trailer RV'));
        vehicles.add(new Vehicle__c(Name = 'Teardrop Camper', Air_Conditioner__c = true,
Bathrooms__c = 1, Bedrooms__c = 1, Model__c = 'Teardrop Camper'));
        vehicles.add(new Vehicle__c(Name = 'Pop-Up Camper', Air_Conditioner__c = true,
Bathrooms__c = 1, Bedrooms__c = 1, Model__c = 'Pop-Up Camper'));
        insert vehicles;
        return vehicles;
    }
    public static List<Product2> createEquipment(){
        List<Product2> equipments = new List<Product2>();
        equipments.add(new Product2(Warehouse_SKU__c =
'55d66226726b611100aaf741',name = 'Generator 1000 kW', Replacement_Part__c =
true, Cost__c = 100 ,Maintenance_Cycle__c = 100));
        equipments.add(new Product2(name = 'Fuse 20B',Replacement_Part__c =
true, Cost__c = 1000, Maintenance_Cycle__c = 30 ));
        equipments.add(new Product2(name = 'Breaker 13C',Replacement_Part__c =
true, Cost__c = 100 , Maintenance_Cycle__c = 15));
        equipments.add(new Product2(name = 'UPS 20 VA',Replacement_Part__c =

```

```

true, Cost__c = 200 , Maintenance_Cycle__c = 60));
    insert equipments;
    return equipments;
}

public static List<Case> createMaintenanceRequest(List<Vehicle__c> vehicles){
    List<Case> maintenanceRequests = new List<Case>();
    maintenanceRequests.add(new Case(Vehicle__c = vehicles.get(1).Id, Type =
TYPE_ROUTINE_MAINTENANCE, Date_Reported__c = Date.today()));
    maintenanceRequests.add(new Case(Vehicle__c = vehicles.get(2).Id, Type =
TYPE_ROUTINE_MAINTENANCE, Date_Reported__c = Date.today()));
    insert maintenanceRequests;
    return maintenanceRequests;
}

public static List<Equipment_Maintenance_Item__c>
createJoinRecords(List<Product2> equipment, List<Case> maintenanceRequest){
    List<Equipment_Maintenance_Item__c> joinRecords = new
List<Equipment_Maintenance_Item__c>();
    joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(0).Id, Maintenance_Request__c = maintenanceRequest.get(0).Id));
    joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(1).Id, Maintenance_Request__c = maintenanceRequest.get(0).Id));
    joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(2).Id, Maintenance_Request__c = maintenanceRequest.get(0).Id));
    joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(0).Id, Maintenance_Request__c = maintenanceRequest.get(1).Id));
    joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(1).Id, Maintenance_Request__c = maintenanceRequest.get(1).Id));
    joinRecords.add(new Equipment_Maintenance_Item__c(Equipment__c =
equipment.get(2).Id, Maintenance_Request__c = maintenanceRequest.get(1).Id));
    insert joinRecords;
    return joinRecords;
}
}

```

CreateDefaultDataTest.apxc :

@isTest

private class CreateDefaultDataTest {

@isTest

static void createData\_test(){

Test.startTest();

CreateDefaultData.createDefaultData();

List<Vehicle\_\_c> vehicles = [SELECT Id FROM Vehicle\_\_c];

```

        List<Product2> equipment = [SELECT Id FROM Product2];
        List<Case> maintenanceRequest = [SELECT Id FROM Case];
        List<Equipment_Maintenance_Item__c> joinRecords = [SELECT Id FROM
Equipment_Maintenance_Item__c];
        System.assertEquals(4, vehicles.size(), 'There should have been 4 vehicles
created');
        System.assertEquals(4, equipment.size(), 'There should have been 4 equipment
created');
        System.assertEquals(2, maintenanceRequest.size(), 'There should have been 2
maintenance request created');
        System.assertEquals(6, joinRecords.size(), 'There should have been 6 equipment
maintenance items created');
    }
    @isTest
    static void updateCustomSetting_test(){
        How_We_Roll_Settings__c customSetting =
How_We_Roll_Settings__c.getOrgDefaults();
        customSetting.Is_Data_Created__c = false;
        upsert customSetting;
        System.assertEquals(false, CreateDefaultData.isDataCreated(), 'The custom setting
How_We_Roll_Settings__c.Is_Data_Created__c should be false');
        customSetting.Is_Data_Created__c = true;
        upsert customSetting;
        System.assertEquals(true, CreateDefaultData.isDataCreated(), 'The custom setting
How_We_Roll_Settings__c.Is_Data_Created__c should be true');
    }
}

MaintenanceRequestHelper.apxc :
public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();
        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }
        if (!validIds.isEmpty()){
            List<Case> newCases = new List<Case>();

```

```

        Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
                FROM Case WHERE Id IN :validIds]);
        Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
        AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds GROUP
BY Maintenance_Request__c];
        for (AggregateResult ar : results){
            maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
        }
        for(Case cc : closedCasesM.values()){
            Case nc = new Case (
                ParentId = cc.Id,
                Status = 'New',
                Subject = 'Routine Maintenance',
                Type = 'Routine Maintenance',
                Vehicle__c = cc.Vehicle__c,
                Equipment__c =cc.Equipment__c,
                Origin = 'Web',
                Date_Reported__c = Date.Today()
            );
            If (maintenanceCycles.containsKey(cc.Id)){
                nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
            }
            newCases.add(nc);
        }
        insert newCases;
        List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
        for (Case nc : newCases){
            for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
                Equipment_Maintenance_Item__c wpClone = wp.clone();
                wpClone.Maintenance_Request__c = nc.Id;
                ClonedWPs.add(wpClone);
            }
        }
    }
}

```

```

        insert ClonedWPs;
    }
}
}
MaintenanceRequestHelperTest.apxc :
@istest
public with sharing class MaintenanceRequestHelperTest {
    private static final string STATUS_NEW = 'New';
    private static final string WORKING = 'Working';
    private static final string CLOSED = 'Closed';
    private static final string REPAIR = 'Repair';
    private static final string REQUEST_ORIGIN = 'Web';
    private static final string REQUEST_TYPE = 'Routine Maintenance';
    private static final string REQUEST_SUBJECT = 'Testing subject';
    PRIVATE STATIC Vehicle__c createVehicle(){
        Vehicle__c Vehicle = new Vehicle__c(name = 'SuperTruck');
        return Vehicle;
    }
    PRIVATE STATIC Product2 createEq(){
        product2 equipment = new product2(name = 'SuperEquipment',
            lifespan_months__C = 10,
            maintenance_cycle__C = 10,
            replacement_part__c = true);
        return equipment;
    }
    PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
        case cs = new case(Type=REPAIR,
            Status=STATUS_NEW,
            Origin=REQUEST_ORIGIN,
            Subject=REQUEST_SUBJECT,
            Equipment__c=equipmentId,
            Vehicle__c=vehicleId);
        return cs;
    }
    PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
        Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
Maintenance_Request__c = requestId);
        return wp;
    }
}

```

```

@istest
private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;
    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;
    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;
    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();
    Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c,
Vehicle__c, Date_Due__c
                    from case
                    where status =:STATUS_NEW];
    Equipment_Maintenance_Item__c workPart = [select id
                                                from Equipment_Maintenance_Item__c
                                                where Maintenance_Request__c =:newReq.Id];
    system.assert(workPart != null);
    system.assert(newReq.Subject != null);
    system.assertEquals(newReq.Type, REQUEST_TYPE);
    SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);
    SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);
    SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
}

@istest
private static void testMaintenanceRequestNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;
    product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
    insert emptyReq;

```



```

    Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,
emptyReq.Id);
    insert workP;
    test.startTest();
    emptyReq.Status = WORKING;
    update emptyReq;
    test.stopTest();
    list<case> allRequest = [select id
                            from case];
    Equipment_Maintenance_Item__c workPart = [select id
                                              from Equipment_Maintenance_Item__c
                                              where Maintenance_Request__c = :emptyReq.Id];
    system.assert(workPart != null);
    system.assert(allRequest.size() == 1);
}

@istest
private static void testMaintenanceRequestBulk(){
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();
    for(integer i = 0; i < 300; i++){
        vehicleList.add(createVehicle());
        equipmentList.add(createEq());
    }
    insert vehicleList;
    insert equipmentList;
    for(integer i = 0; i < 300; i++){
        requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    }
    insert requestList;
    for(integer i = 0; i < 300; i++){
        workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
    }
    insert workPartList;
    test.startTest();
    for(case req : requestList){
        req.Status = CLOSED;

```

```

        oldRequestIds.add(req.Id);
    }
    update requestList;
    test.stopTest();
    list<case> allRequests = [select id
                            from case
                            where status =: STATUS_NEW];
    list<Equipment_Maintenance_Item__c> workParts = [select id
                                                    from Equipment_Maintenance_Item__c
                                                    where Maintenance_Request__c in: oldRequestIds];
    system.assert(allRequests.size() == 300);
}
}

WarehouseCalloutService.apxc :
public with sharing class WarehouseCalloutService {
    private static final String WAREHOUSE_URL = 'https://th-
superbadgeapex.herokuapp.com/equipment';
    //@future(callout=true)
    public static void runWarehouseEquipmentSync(){
        Http http = new Http();
        HttpRequest request = new HttpRequest();
        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);
        List<Product2> warehouseEq = new List<Product2>();
        if (response.getStatusCode() == 200){
            List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
            System.debug(response.getBody());
            for (Object eq : jsonResponse){
                Map<String,Object> mapJson = (Map<String,Object>)eq;
                Product2 myEq = new Product2();
                myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
                myEq.Name = (String) mapJson.get('name');
                myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
                myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
                myEq.Cost__c = (Decimal) mapJson.get('lifespan');
                myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
                myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
                warehouseEq.add(myEq);
            }
        }
    }
}

```

```

        if (warehouseEq.size() > 0){
            upsert warehouseEq;
            System.debug('Your equipment was synced with the warehouse one');
            System.debug(warehouseEq);
        }
    }
}

WarehouseSyncSchedule.apxc :
global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {
        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

WarehouseSyncScheduleTest.apxc :
@isTest
private class WarehouseSyncScheduleTest {
    @isTest
    public static void WarehouseSyncScheduleTest(){
        String scheduleTime = '00 00 01 * * ?';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String jobId = System.schedule('jWarehouse Time To Schedule to
Test',scheduleTime, new WarehouseSyncSchedule());
        Test.stopTest();
        CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
        System.assertEquals(jobId,a.Id,'Schedule');
    }
}

RejectDuplicateFavorite.apxt :
trigger RejectDuplicateFavorite on Favorite__c (before insert) {
    // NOTE: this trigger needs to be bulkified
    Favorite__c favorite = Trigger.New[0];
    List<Favorite__c> dupes = [Select Id FROM Favorite__C WHERE Property__c =
:favorite.Property__c AND User__c = :favorite.User__c];
    if (!dupes.isEmpty()) {
        favorite.addError('duplicate');
    }
}

AccountAddressTrigger.apxt :
trigger AccountAddressTrigger on Account (before insert,before update) {

```

```

    for(Account account : Trigger.new){
        if((account.Match_Billing_Address__c == true) && (account.BillingPostalCode !=
NULL)){
            account.ShippingPostalCode = account.BillingPostalCode;
        }
    }
}

ClosedOpportunityTrigger.apxt :
trigger ClosedOpportunityTrigger on Opportunity (after insert,after update) {
    List<Task> tasklist = new List<Task>();
    for(Opportunity opp: Trigger.New){
        if(opp.StageName == 'Closed Won'){
            tasklist.add(new Task(Subject = 'Follow Up Test Task' , WhatId = opp.Id));
        }
    }
    if(tasklist.size()>0){
        insert tasklist;
    }
}

RestrictContactByName.apxt :
trigger RestrictContactByName on Contact (before insert, before update) {
    //check contacts prior to insert or update for invalid data
    For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') { //invalidname is invalid
            c.AddError('The Last Name "' + c.LastName + '" is not allowed for DML');
        }
    }
}

MaintenanceRequest.apxt :
trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```