APEX TRIGGERS

<u>AccountAddressTrigger.axpt:</u>

```
trigger Account Address Triggeron Account (before insert, beforeupdate) { for (Account
account:Trigger.New){
if(account.Match_Billing_Address c == True){ account.ShippingPostalCode =
account.BillingPostalCode;
}
}
<u>ClosedOpportunityTrigger.axpt:</u>
trigger ClosedOpportunityTrigger on Opportunity (afterinsert, afterupdate) { List<Task> tasklist=
new List<Task>();
for(Opportunity opp: Trigger.New){ if(opp.StageName == 'ClosedWon'){
tasklist.add(newTask(Subject = 'Follow Up Test Task', WhatId = opp.Id));
}
}
if(tasklist.size() > 0){
insert tasklist;
}
public class VerifyDate {
```

APEX TESTING

VerifyData.apxc:

```
public static Date CheckDates(Date date1, Date date2) {if(DateWithin30Days(date1,date2)) {
    return date2;
} else {
}
return SetEndOfMonthDate(date1);

@TestVisible privatestatic Boolean DateWithin30Days(Datedate1, Date date2){
/check for date2 being inthe past if( date2< date1) { returnfalse; }</pre>
```

APEXSPECIALIST SUPER BADGE CODES

/check that date2 is within (>=)30 days of date1

```
Date date 30 Days = date 1. addDays (30); /create a date 30 days away from date 1 if ( date 2 >=
date30Days ) { return false; }
else { return true; }
}
/method to return the end of the month of a given date
@TestVisible private staticDate SetEndOfMonthDate(Datedate1){
IntegertotalDays =Date.daysInMonth(date1.year(), date1.month());
Date lastDay = Date.newInstance(date1.year(), date1.month(),totalDays); return lastDay;
}
}
                                    TestVerifyData.apxc:
@isTest
private class TestVerifyDate {
@isTest static void Test_CheckDates_case1(){
Date D = VerifyDate.CheckDates(date.parse('01/01/2022'),date.parse('01/05/2022'));
System.assertEquals(date.parse('01/05/2022'), D);
@isTest static void Test_CheckDates_case2(){
Date D = VerifyDate.CheckDates(date.parse('01/01/2022'), date.parse('05/05/2022'));
System.assertEquals(date.parse('01/31/2022'), D);
}
@isTest static void Test_Within30Days_case1(){Boolean \( \text{lag} = \)
VerifyDate.DateWithin30Days(date.parse('01/01/2022'), date.parse('12/30/2021'));
System.assertEquals(false, [ag);
@isTest static void Test_Within30Days_case2(){Boolean \( \text{Boolean} \)
VerifyDate.DateWithin30Days(date.parse('01/01/2022'), date.parse('02/02/2021'));
```

```
System.assertEquals(false, [ag);
@isTest static void Test_Within30Days_case3(){
Boolean [ag =
VerifyDate.DateWithin30Days(date.parse('01/01/2022'), date.parse('01/15/2022'));
System.assertEquals(true, [ag);
}
@isTest static void Test_SetEndOfMonthDate(){
Datereturndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2022'));
}
RestrictContactByName.apxt:
trigger RestrictContactByName on Contact (beforeinsert, before update){
/check contacts prior to insertor update forinvalid data For (Contactc: Trigger.New) {
if(c.LastName == 'INVALIDNAME') { /invalidname is invalid c.AddError('The Last Name
"'+c.LastName+" is not allowedfor DML');
}
TestRestrictContactByName.apxc:
@isTest
private class TestRestrictContactByName
{ @isTeststatic void Test_insertupdateContact(){
Contact cnt = new Contact();cnt.LastName = 'INVALIDNAME';
Test.startTest(); Database.SaveResult result=
Database.insert(cnt,false);Test.stopTest();System.assert(!result.isSuccess());
System.assert(result.getErrors().size() > 0);
```

```
System.assertEquals('The Last Name"INVALIDNAME" is notallowed for DML', result.getErrors()[0].getMessage());
}
```

<u>RandomContactFactory.apxc:</u>

```
public class RandomContactFactory {
public static List<Contact> generateRandomContacts(Integer num_cnts, string lastname) {
List<Contact> contacts= new List<Contact>();
for(Integer i = 0; i < num_cnts; i++) {
Contact cnt = new Contact(FirstName = 'Test' +i,LastName = lastname); contacts.add(cnt);
}
return contacts;
}
</pre>
```

ASYNCHRONOUS APEX

<u>AccountProcessor.apxc</u>:

```
public class AccountProcessor {@future
public static void countContacts(List<Id> accountIds){List<Account> accountsToUpdate = new
List<Account>();
List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from Account Where Id in
:accountIds];
For(Account acc: accounts) {
List<Contact> contactList = acc.contacts;acc.Number_Of_Contacts c = contactList.size();
accountsToUpdate.add(acc);
}
update accountsToUpdate;
}
AccountProcessorTest.apxc:
@isTest
public class AccountProcessorTest {
@isTest
private static void testCountContacts() {
Account newAccount = new Account(Name = 'TestAccount'); insert newAccount;
ContactnewContact1 = new Contact(FirstName = 'John',LastName = 'Doe',AccountId =
```

newAccount.ld);

```
insert newContact1;
Contact newContact2 = new Contact(FirstName = 'John', LastName = 'Doe', AccountId =
newAccount.ld);
insert newContact2;
List<Id> accountIds = new List<Id>(); accountIds.add(newAccount.Id); Test.startTest();
AccountProcessor.countContacts(accountIds); Test.stopTest();
}
LeadProcessor.apxc:
global class LeadProcessor implements Database.Batchable<sObject>{ globalInteger count =0;
global Database.QueryLocator start(Database.BatchableContext bc) { return
Database.getQueryLocator('SELECT ID,LeadSource FROM Lead');
}
global void execute(Database.BatchableContext bc, List<Lead>L_list){ List<lead> L_list_new =
new List<lead>();
for(lead L: L_list){ L.leadSource = 'Dreamforce'; L_list_new.add(L);count += 1;
update L_list_new;
global void Inish(Database.BatchableContext bc){
system.debug('count=' + count);
<u>LeadProcessorTest.apxc</u>:
```

```
@isTest
public class LeadProcessorTest {@isTest
publicstatic voidtestit(){
```

```
List<lead> L_list = new List<lead>();for(Integer i = 0; i <200; i++) {
Lead L = new Lead();L.LastName = 'name'
+ i; L.Company = 'Company'; L.Status
= 'Random Status'; L_list.add(L);
}
insert L_list;Test.startTest();
LeadProcessor lp = new LeadProcessor(); Id batchId =Database.executeBatch(lp);
Test.stopTest();
}
</pre>
```

<u>AddPrimaryContact.apxc:</u>

```
public class AddPrimaryContact implementsQueueable{ private Contact con;
private String state;
public AddPrimaryContact(Contact con, Stringstate) { this.con = con;
this.state = state;
}
```

```
public void execute(QueueableContext context){
List<Account> accounts = [Select Id,Name,(Select FirstName,LastName, Id from contacts) from
Accountwhere BillingState = :state Limit 200];
List<Contact> primaryContacts = new List<Contact>();for(Account acc : accounts) {
Contact c = con.clone(); c.AccountId = acc.Id;primaryContacts.add(c);
}
if(primaryContacts.size() > 0) { insertprimaryContacts;
}
}
}
```

@isTest public class

APEX SPECIALIST SUPER BADGE CODES

<u>AddPrimaryContactTest.apxc:</u>

AddPrimaryContactTest { static

```
testmethod void testQueueable() {
List<Account> testAccounts = newList<Account>(); for(Integer i = 0; i < 50; i++) {</pre>
```

```
testAccounts.add(newAccount (Name = 'Account' + i,BillingState = 'CA'));
}
for(Integer j = 0; j < 50; j++) {
testAccounts.add(newAccount(Name = 'Account' + j, BillingState= 'NY'));
}
insert testAccounts;
Contact testContact = new Contact(FirstName = 'John', LastName = 'Doe'); insert testContact;
AddPrimaryContact addit = new AddPrimaryContact(testContact,'CA'); Test.startTest();
system.enqueueJob(ad
dit); Test.stopTest();
System.assertEquals(50, [Select count() from Contact where account Id in (Select Idfrom Account
where BillingState = 'CA')]);
}
DailyLeadProcessor.apxc:
global class DailyLeadProcessor implementsSchedulable{ global void
execute(SchedulableContext ctx) {
List<Lead> leadstoupdate = new List<Lead>();
List < Lead > leads = [Select id From LeadWhere LeadSource = NULL Limit200]; for (Lead l: leads) {
l.LeadSource = 'Dreamforce'; leadstoupdate.add(l);
}
update leadstoupdate;
}
}
```

<u>DailyLeadProcessorTest.apxc:</u>

```
@isTest
private class DailyLeadProcessorTest {
public static String CRON_EXP= '0 0 0 15 3?
2024'; static testmethod void testScheduledJob() { List<Lead> leads= new
List<Lead>(); for(Integer i =0; i < 200; i++) {
Lead I = new Lead( FirstName = 'First'
+ i, LastName = 'LastName', Company = 'TheInc'
);
leads.add(l);
}
insert leads;Test.startTest();
String jobId = System.schedule('ScheduledApexTest',CRON_EXP,new DailyLeadProcessor());
Test.stopTest();
List<Lead> checkleads = new List<Lead>();
checkleads = [SelectIdFrom Lead Where LeadSource = 'Dreamforce' and Company = 'TheInc'];
System.assertEquals(200,checkleads.size(),'Leads were not created');
}
```

public class AnimalLocator{

APEX INTEGRATION SERVICES

AnimalLocator.apxc:

```
public static String getAnimalNameById(Integer x){ Httphttp = new Http();
HttpRequest req =new HttpRequest();
req.setEndpoint('https: /th-apex-http-callout.herokuapp.com/animals/'
+x); req.setMethod('GET');
Map<String, Object> animal= new Map<String,Object>(); HttpResponse res = http.send(req);
if (res.getStatusCode() == 200) {
```

```
Map<String, Object> results = (Map<String, Object>)JSON.deserializeUntyped(res.getBody());
animal= (Map<String, Object>) results.get('animal');
}
return (String)animal.get('name');
```

```
}
}
@isTest
private class AnimalLocatorTest{
AnimalLocatorTest.apxc:
@isTest static void AnimalLocatorMock1() { Test.setMock(HttpCalloutMock.class, new
AnimalLocatorMock()); string result = AnimalLocator.getAnimalNameById(3); String
expectedResult = 'chicken'; System.assertEquals(result,expectedResult );
}
AnimalLocatorMock.apxc:
@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
/ Implementthis interface method
global HTTPResponse respond(HTTPRequest request) {
/ Create a fake response
HttpResponse response = new HttpResponse(); response.setHeader('Content-Type',
'application/json');
response.setBody('{"animals": ["majestic badger", "luffy bunny", "scary bear", "chicken", "mighty
moose"]}');
response.setStatusCode(200); return response;
}
}
```

_

ParkLocator.apxc:

```
public class ParkLocator {
public staticstring[] country(string theCountry) {
ParkService.ParksImplPort parkSvc = new ParkService.ParksImplPort(); / removespace return parkSvc.byCountry(theCountry);
}
}
```

@isTest private class

APEX SPECIALIST SUPER BADGE CODES

ParkLocatorTest.apxc:

```
ParkLocatorTest { @isTest staticvoidtestCallout() {
Test.setMock(WebServiceMock.class, new ParkServiceMock()); String country= 'United States';
List<String> result = ParkLocator.country(country);
List<String> parks = new List<String> {'Yellowstone', 'MackinacNationalPark', 'Yosemite'};
System.assertEquals(parks, result);
}
ParkServiceMock.apxc:
@isTest
global class ParkServiceMock implements WebServiceMock { global void doInvoke(
Object stub, Object request,
Map<String, Object>
response, String endpoint,
String soapAction, String requestName, String responseNS, String responseName,
StringresponseType) {
/start -specifythe response you want to send
ParkService.byCountryResponse response x = new ParkService.byCountryResponse();
response_x.return_x = new List<String>{'Yellowstone', 'Mackinac NationalPark', 'Yosemite'};
/ end response.put('response_x',response_x);
}
AccountManager.apxc:
@RestResource(urlMapping='/Accounts/*/contacts') global classAccountManager {
@HttpGet
global static Account getAccount() {RestRequest req = RestContext.request;
String accld =req.requestURI.substringBetween('Accounts/', '/contacts');
```

Account acc = [SELECTId, Name, (SELECTId, Name FROMContacts) FROM AccountWHERE Id = :accld];

```
return acc;
}

AccountManagerTest.apxc:
@isTest
private class AccountManagerTest {

private static testMethod voidgetAccountTest1() { Id recordId =createTestRecord();
  / Set up a test request

RestRequest request= new RestRequest();
request.requestUri= 'https: /na1.salesforce.com/services/apexrest/Accounts/'+ recordId
+'/contacts';
request.httpMethod = 'GET'; RestContext.request= request;
  / Call the method to test

Account thisAccount = AccountManager.getAccount();
  / Verify results System.assert(thisAccount !=null);
System.assertEquals('Test record',thisAccount.Name);
```

```
/ Helper method
static ld createTestRecord() {
/ Create test record
Account TestAcc = new Account(Name='Test record');
insert TestAcc;
Contact TestCon= new Contact(LastName='Test',

AccountId = TestAcc.id); return TestAcc.Id;
}
}
```

APEX SPECIALIST SUPER BADGE CODES APEX SPECIALIST SUPER BADGE

Challenge-1

<u>MaintenanceRequestHelper.apxc:</u>

```
public with sharing class MaintenanceRequestHelper {
public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) { Set<Id> validIds= new Set<Id>();

For (Case c: updWorkOrders){
  if (nonUpdCaseMap.get(c.Id).Status!='Closed' && c.Status =='Closed'){ if (c.Type == 'Repair'| | c.Type == 'Routine Maintenance'){
  validIds.add(c.Id);

}
}
if (!validIds.isEmpty()){
```

```
List<Case> newCases = new List<Case>();
Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle c, Equipment c,Equipment
r.Maintenance_Cycle c,(SELECT Id,Equipment c,Quantity c FROM Equipment_Maintenance_Items
r)
FROM Case WHERE Id IN :validIds]); Map<Id,Decimal> maintenanceCycles = new
Map<ID,Decimal>();AggregateResult[] results = [SELECT Maintenance_Request c,
MIN(Equipmentr.Maintenance_Cyclec)cycle FROM Equipment_Maintenance_Item c
WHEREMaintenance_Request c IN: ValidIds GROUP BY Maintenance_Request c];
for (AggregateResult ar : results){
maintenanceCycles.put((Id)ar.get('Maintenance_Request__c'),(Decimal) ar.get('cycle'));
}
for(Case cc : closedCasesM.values()){Case nc = new Case (
ParentId = cc.Id, Status
='New',
                  APEX SPECIALIST SUPER BADGE CODES
Subject = 'RoutineMaintenance', Type = 'Routine Maintenance', Vehicle c = cc.Vehicle c,
Equipment c
=cc.Equipment c, Origin ='Web',
Date_Reportedc = Date.Today());
If (maintenanceCycles.containskey(cc.ld)){
nc.Date_Due__c =Date.today().addDays((Integer)maintenanceCycles.get(cc.Id));
}
newCases.add(nc);
}
```

```
insert newCases;
List<Equipment_Maintenance_Item c> clonedWPs = newList<Equipment_Maintenance_Item
c>();
for (Casenc : newCases){
for (Equipment_Maintenance_Item c wp:
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items r){
Equipment_Maintenance_Item c wpClone = wp.clone(); wpClone.Maintenance_Request c =
nc.Id;ClonedWPs.add(wpClone);
}
}
insert ClonedWPs;
}
}
}
MaintenanceRequest.apxt:
trigger MaintenanceRequest on Case (before update, after update) {if(Trigger.isUpdate &&
Trigger.isAfter){
MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
}
}
MaintenanceRequestHelperTest.apxc:
@istest
public with sharing class MaintenanceRequestHelperTest {
private static Inal string STATUS_NEW ='New'; private static Inal string WORKING= 'Working';
private static Inal string CLOSED = 'Closed'; private static Inal string REPAIR = 'Repair'; private
static nal string REQUEST_ORIGIN = 'Web';
```

```
private static Inal string REQUEST_TYPE = 'RoutineMaintenance'; private static Inal string
REQUEST_SUBJECT = 'Testing subject';
PRIVATE STATICVehicle c createVehicle(){
Vehicle c Vehicle= new VehicleC(name ='SuperTruck'); return Vehicle;
}
PRIVATE STATIC Product2 createEq(){
product2equipment = new product2(name ='SuperEquipment',
lifespan_months C = 10, maintenance_cycle C
= 10,
replacement_part c =true);
return equipment;
}
PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, idequipmentId){  case cs = new
case(Type=REPAIR,
Status=STATUS_NEW, Origin=REQUEST_ORIGIN, Subject=REQUEST_SUBJECT,
Equipment_c=equipmentId,
```

Vehicle_c=vehicleId);

```
return cs;
}
PRIVATE STATIC Equipment_Maintenance_Item c createWorkPart(id equipmentId,id requestId){
Equipment_Maintenance_Item c wp = new Equipment_Maintenance_Item c(Equipment <u>c</u> =
equipmentld,
Maintenance_Request _c = requestId);
return wp;
}
@istest
private static void
testMaintenanceRequestPositive(){ Vehiclecvehicle= createVehicle();
insert vehicle;
id vehicleId = vehicle.Id;
Product2 equipment = createEq(); insert equipment; id equipmentId =equipment.Id;
case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
insertsomethingToUpdate;
Equipment_Maintenance_Item c workP =createWorkPart(equipmentId,somethingToUpdate.id);
insert workP;
test.startTest(); somethingToUpdate.status =CLOSED; update somethingToUpdate;
```

```
test.stopTest();

Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c, Vehicle__c,
Date_Due_c
from case
where status =:STATUS_NEW];
```

Equipment_Maintenance_Item_c workPart = [select id

@istest

```
from Equipment_Maintenance_Item c
where Maintenance_Request__c =:newReq.Id];

system.assert(workPart != null); system.assert(newReq.Subject != null);
system.assertEquals(newReq.Type, REQUEST_TYPE); SYSTEM.assertEquals(newReq.Equipment c, equipmentId); SYSTEM.assertEquals(newReq.Vehicle c, vehicleId);
SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
}
```

private static void testMaintenanceRequestNegative(){ Vehicle C vehicle=createVehicle();
insert vehicle;
id vehicleId = vehicle.Id;

product2 equipment = createEq(); insert equipment; id equipmentId = equipment.Id;

case emptyReq = createMaintenanceRequest(vehicleId,equipmentId); insertemptyReq;

Equipment_Maintenance_Item c workP = createWorkPart(equipmentId,emptyReq.Id); insertworkP;

test.startTest(); emptyReq.Status = WORKING; updateemptyReq; test.stopTest();

list<case> allRequest = [select id from case];

Equipment_Maintenance_Item _c workPart = [select id from Equipment_Maintenance_Item c

APEX SPECIALIST SUPER BADGE CODES

where Maintenance_Request <u>c</u> = :emptyReq.Id];

```
system.assert(workPart != null); system.assert(allRequest.size() == 1);
}
@istest
private static void testMaintenanceRequestBulk(){ list<Vehicle C> vehicleList = new
list<Vehicle C>();list<Product2> equipmentList = new list<Product2>();
list<Equipment_Maintenance_Item c>workPartList
= new list<Equipment_Maintenance_Item c>();
list<case> requestList = newlist<case>(); list<id> oldRequestIds =new list<id>();
for(integer i = 0; i < 300; i++){ vehicleList.add(createVehicle());equipmentList.add(createEq());</pre>
}
insert
vehicleList; insert equipmentList;
for(integer i = 0; i < 300; i++){ requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
insert requestList;
for(integer i = 0; i < 300; i++){ workPartList.add(createWorkPart(equipmentList.get(i).id,
requestList.get(i).id));
}
insert workPartList;
test.startTest();for(case req:
requestList){
```

```
req.Status =CLOSED;
oldRequestIds.add(req.Id);
}
update requestList;
```

```
test.stopTest();
list<case> allRequests = [select id

from case
where status=:STATUS_NEW];
list<Equipment_Maintenance_Item c> workParts = [select id
from Equipment_Maintenance_Item c
where Maintenance_Request c in: oldRequestIds];
system.assert(allRequests.size() == 300);
}
```

Challenge-2

<u>WarehouseCalloutService.apxc</u>:

public with sharingclass WarehouseCalloutService implements Queueable { private static Inal String WAREHOUSE_URL = 'https:

/th-superbadge- apex.herokuapp.com/equipment';

/class that makesaREST callout to an external warehouse system to get a list of equipment that needs to be updated.

/The callout's JSON response returns the equipment records that you upsert in Sales force.

@future(callout=true)public staticvoid
runWarehouseEquipmentSync(){ Httphttp= new Http();
HttpRequest request=new HttpRequest();

request.setEndpoint(WAREHOUSE_URL);request.setMethod('GET'); HttpResponse response =

http.send(request); List<Product2>warehouseEq = new List<Product2>();if

(response.getStatusCode() == 200){

List<Object> jsonResponse =(List<Object>)JSON.deserializeUntyped(response.getBody());

System.debug(response.getBody());

```
/class maps the following [elds:replacement part (alwaystrue), cost, currentinventory, lifespan,
maintenance cycle, and warehouse SKU
/warehouse SKU will be external ID for identifying which equipment records toupdate
withinSalesforce
for (Object eq: jsonResponse){
Map<String,Object> mapJson =(Map<String,Object>)eq;Product2 myEq = newProduct2();
myEq.Replacement_Part c = (Boolean)mapJson.get('replacement'); myEq.Name = (String)
mapJson.get('name');
myEq.Maintenance_Cycle c = (Integer) mapJson.get('maintenanceperiod'); myEq.Lifespan_Months
c = (Integer) mapJson.get('lifespan');
myEq.Cost c = (Integer) mapJson.get('cost'); myEq.Warehouse_SKU c = (String)
mapJson.get('sku'); myEq.Current_Inventory c = (Double) mapJson.get('quantity');
myEq.ProductCode = (String) mapJson.get('_id'); warehouseEq.add(myEq);
}
if
(warehouseEq.size()> 0){ upsertwarehouseEq;
System.debug('Your equipmentwas synced with the warehouse one');
}
}
}
```

```
public static void execute (QueueableContext context){runWarehouseEquipmentSync();
}

@isTest
```

WarehouseCalloutServiceMock.apxc:

```
global classWarehouseCalloutServiceMock implements HttpCalloutMock {
  / implement http mock callout
  global staticHttpResponse respond(HttpRequest request){
```

APEX SPECIALIST SUPER BADGE CODES

HttpResponse response = new HttpResponse(); response.setHeader('Content-Type',
'application/json');

```
response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5,"name" :"Gene rator 1000 kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"},{"_id":"55d66226726b61
```

```
1100a af742", "replacement": true, "quantity": 183, "name": "Cooling
Fan", "maintenanceperiod":0, "lifespan":0, "cost":300, "sku":"100004"}, {"_id":"55d66226726b611100
aaf743 ","replacement":true,"quantity":143,"name":"Fuse
20A","maintenanceperiod":0,"lifespan":0,"cost":22,"sku":"100005"}]');
response.setStatusCode(200);
return response;
}
WarehouseCalloutServiceTest.apxc:
@IsTest
private class WarehouseCalloutServiceTest {
/ implement your mock callout testhere @isTest
static void testWarehouseCallout() {test.startTest();
test.setMock(HttpCalloutMock.class,new WarehouseCalloutServiceMock());
WarehouseCalloutService.execute(null);
test.stopTest();
List<Product2> product2List = new List<Product2>();product2List = [SELECTProductCode FROM
Product2];
System.assertEquals(3, product2List.size()); System.assertEquals('55d66226726b611100aaf741',
product2List.get(0).ProductCode); System.assertEquals('55d66226726b611100aaf742',
product2List.get(1).ProductCode); System.assertEquals('55d66226726b611100aaf743',
product2List.get(2).ProductCode);
}
}
```

Challenge-3

<u>WarehouseSyncSchedule.apxc:</u>

global with sharing class WarehouseSyncSchedule implements Schedulable{

```
global void execute(SchedulableContext ctx){
System.enqueueJob(newWarehouseCalloutService());
}

WarehouseSyncScheduuleTest.apxc:
@isTest
public class WarehouseSyncScheduleTest {

@isTest static void WarehousescheduleTest(){ StringscheduleTime = '00 00 01 * * ?';
Test.startTest();
Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
String jobID=System.schedule('Warehouse Time To Scheduleto Test', scheduleTime, new WarehouseSyncSchedule());
```

Test.stopTest();

/Contains schedule information for a scheduledjob. CronTrigger is similar to a cron job on UNIX systems.

/ This object is available in API version 17.0 and later.

CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime >today]; System.assertEquals(jobID, a.Id,'Schedule');

}

Challenge-4

MaintenanceRequestHelperTest.apxc:

@istest

public with sharing class MaintenanceRequestHelperTest {

private static <code>Inal</code> string STATUS_NEW ='New'; private static <code>Inal</code> string WORKING= 'Working'; private static <code>Inal</code> string CLOSED = 'Closed'; private static <code>Inal</code> string REPAIR = 'Repair'; private static <code>Inal</code> string REQUEST_ORIGIN = 'Web';

private static <code>nal string REQUEST_TYPE = 'RoutineMaintenance'</code>; private static <code>nal string REQUEST_SUBJECT = 'Testing subject'</code>;

PRIVATE STATICVehicle c createVehicle(){

```
Vehicle c Vehicle= new VehicleC(name ='SuperTruck'); return Vehicle;
}
```

```
PRIVATE STATIC Product2 createEq(){
product2 equipment= new product2(name= 'SuperEquipment', lifespan_months C = 10,
maintenance_cycle C
= 10,
replacement_part c =true);
return equipment;
}
PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, idequipmentId){  case cs = new
case(Type=REPAIR,
Status=STATUS_NEW, Origin=REQUEST_ORIGIN, Subject=REQUEST_SUBJECT,
Equipment c=equipmentId, Vehicle c=vehicleId);
return cs;
}
PRIVATE STATIC Equipment_Maintenance_Item c createWorkPart(id equipmentId,id requestId){
Equipment_Maintenance_Item c wp = new Equipment_Maintenance_Item c(Equipment c =
equipmentId, Maintenance_Request c = requestId); return wp;
}
@istest
private static void testMaintenanceRequestPositive(){ Vehiclecvehicle= createVehicle();
insert vehicle;
id vehicleId = vehicle.Id;
```

Product2 equipment = createEq(); insert equipment; id equipmentId =equipment.ld;

```
case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
insertsomethingToUpdate;
Equipment_Maintenance_Item c workP =createWorkPart(equipmentId,somethingToUpdate.id);
insert workP;
test.startTest(); somethingToUpdate.status =CLOSED; update somethingToUpdate;
test.stopTest();
Case newReq = [Select id, subject, type, Equipment c, Date_Reported c, Vehicle c,
Date_Due_c
from case
where status =: STATUS_NEW];
Equipment_Maintenance_Item_c workPart = [select id
from Equipment_Maintenance_Item c
where Maintenance_Request c =: newReq. Id];
system.assert(workPart != null); system.assert(newReq.Subject != null);
system.assertEquals(newReq.Type, REQUEST_TYPE); SYSTEM.assertEquals(newReq.Equipment c,
equipmentId); SYSTEM.assertEquals(newReq.Vehicle c, vehicleId);
SYSTEM.assertEquals(newReq.Date_Reported___c, system.today());
```

```
@istest
private static void
testMaintenanceRequestNegative(){ Vehicle C vehicle=createVehicle();
insert vehicle;
id vehicleId = vehicle.Id;
product2 equipment = createEq(); insert equipment; id equipmentId =equipment.Id;
APEXSPECIALIST SUPER BADGE CODES
case emptyReq = createMaintenanceRequest(vehicleId,equipmentId); insertemptyReq;
Equipment_Maintenance_Item c workP =createWorkPart(equipmentId,emptyReq.Id);
insertworkP;
test.startTest(); emptyReq.Status =WORKING; updateemptyReq; test.stopTest();
list<case> allRequest = [select id
from case];
Equipment_Maintenance_Item_c workPart = [select id
from Equipment_Maintenance_Item c
where Maintenance_Request <u>c</u> = :emptyReq.ld];
system.assert(workPart != null); system.assert(allRequest.size() == 1);
}
@istest
private static void testMaintenanceRequestBulk(){ list<Vehicle C> vehicleList = new
list<Vehicle C>();list<Product2> equipmentList = new list<Product2>();
```

```
list<Equipment_Maintenance_Item c>workPartList
= new list<Equipment_Maintenance_Item c>();
list<case> requestList = newlist<case>(); list<id> oldRequestIds =new list<id>();
for(integer i = 0; i < 300; i++){ vehicleList.add(createVehicle());equipmentList.add(createEq());</pre>
}
insert vehicleList; insert equipmentList;
                    APEX SPECIALIST SUPER BADGE CODES
for(integer i = 0; i < 300; i++){ requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
insert requestList;
for(integer i = 0; i < 300; i++){ workPartList.add(createWorkPart(equipmentList.get(i).id,
requestList.get(i).id));
}
insert workPartList;
test.startTest();for(case req :
requestList){req.Status =CLOSED;
oldRequestIds.add(req.Id);
updaterequestList; test.stopTest();
list < case > all Requests = [select id
from case
where status=:STATUS_NEW];
list < Equipment_Maintenance_Item <a>c</a> workParts = [select id
```

```
from Equipment_Maintenance_Item c
where Maintenance_Request cin: oldRequestIds];
system.assert(allRequests.size() == 300);
}
MaintenanceRequestHelper.apxc:
public with sharing class MaintenanceRequestHelper {
public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) { Set<Id> validIds= new Set<Id>();
For (Case c : updWorkOrders){
if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
if (c.Type == 'Repair'||c.Type== 'Routine Maintenance'){validIds.add(c.Id);
}
}
if (!validIds.isEmpty()){
List<Case> newCases = new List<Case>();
Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle c, Equipment c,Equipment
r.Maintenance_Cycle c,(SELECT Id,Equipment c,Quantity c FROM Equipment_Maintenance_Items
r)
FROM Case WHERE Id IN :validIds]); Map<Id,Decimal> maintenanceCycles = new
Map<ID,Decimal>();AggregateResult[] results= [SELECT Maintenance_Request c,
MIN(Equipmentr.Maintenance_Cyclec)cycle FROM Equipment_Maintenance_Item cWHERE
Maintenance_Request c IN: ValidIds GROUP BY Maintenance_Request c];
for (AggregateResult ar : results){
```

```
maintenanceCycles.put((Id)ar.get('Maintenance_Request__c'),(Decimal) ar.get('cycle'));
}
for(Case cc : closedCasesM.values()){Case nc = new Case (
ParentId = cc.Id, Status
='New',
Subject = 'RoutineMaintenance', Type = 'Routine Maintenance', Vehicle c = cc.Vehicle c,
Equipment c
=cc.Equipment c, Origin = 'Web',
Date_Reportedc = Date.Today()

);

If (maintenanceCycles.containskey(cc.Id)){
nc.Date_Due__c = Date.today().addDays((Integer)maintenanceCycles.get(cc.Id));
```

```
newCases.add(nc);

}
insert newCases;
List<Equipment_Maintenance_Item c> clonedWPs = new
List<Equipment_Maintenance_Item c>();for (Casenc: newCases){
for (Equipment_Maintenance_Item c wp:
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items r){
Equipment_Maintenance_Item c wpClone = wp.clone(); wpClone.Maintenance_Request c = nc.Id;ClonedWPs.add(wpClone);
```

```
}
insert ClonedWPs;
}
```

Challenge-5

WarehouseCalloutService.apxc:

public with sharing classWarehouseCalloutService implements Queueable $\{$ private static In al String WAREHOUSE_URL = 'https:

/th-superbadge- apex.herokuapp.com/equipment';

/class that makesaREST callout to an external warehouse system to get a list of equipment that needs to be updated.

/The callout's JSON response returns the equipment records that you upsert in Sales force.

@future(callout=true)public staticvoid

```
runWarehouseEquipmentSync(){ Httphttp= new Http();
HttpRequest request = new HttpRequest();request.setEndpoint(WAREHOUSE_URL);
```

```
request.setMethod('GET'); HttpResponse response=
http.send(request); List<Product2>warehouseEq = new List<Product2>();
if (response.getStatusCode() == 200){
List<Object> jsonResponse =(List<Object>)JSON.deserializeUntyped(response.getBody());
System.debug(response.getBody());
/class maps the following [elds:replacement part (alwaystrue), cost, currentinventory, lifespan,
maintenance cycle, and warehouse SKU
/warehouse SKU will be external ID for identifying which equipment records toupdate
withinSalesforce
for (Object eq: jsonResponse){
Map<String,Object> mapJson =(Map<String,Object>)eq;Product2 myEq = newProduct2();
myEq.Replacement_Part c = (Boolean)mapJson.get('replacement'); myEq.Name = (String)
mapJson.get('name');
myEq.Maintenance_Cycle c = (Integer) mapJson.get('maintenanceperiod'); myEq.Lifespan_Months
c = (Integer) mapJson.get('lifespan');
myEq.Cost c = (Integer) mapJson.get('cost'); myEq.Warehouse_SKU c = (String)
mapJson.get('sku'); myEq.Current_Inventory c = (Double) mapJson.get('quantity');
myEq.ProductCode = (String) mapJson.get('_id'); warehouseEq.add(myEq);
}
if
(warehouseEq.size()> 0){ upsertwarehouseEq;
```

```
System.debug('Your equipmentwas synced with the warehouse one');
public static void execute (QueueableContext context){runWarehouseEquipmentSync();
}@isTest
APEXSPECIALIST SUPER BADGE CODES
WarehouseCalloutServiceMock.apxc:
global classWarehouseCalloutServiceMock implements HttpCalloutMock {
/ implement http mock callout
global staticHttpResponse respond(HttpRequest request){
HttpResponse response = new HttpResponse(); response.setHeader('Content-Type',
'application/json');
response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5,"na
me":"Gene
                    rator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"},{"_id":"55d6622672
6b611100aaf742", "replacement": true, "quantity": 183, "name": "Cooling
Fan", "maintenanceperiod": 0, "lifespan": 0, "cost": 300, "sku": "100004"}, {"_id": "55d66226726b611"
100aaf743 ","replacement":true,"quantity":143,"name":"Fuse
20A","maintenanceperiod":0,"lifespan":0,"cost":22,"sku":"100005"}]');
response.setStatusCode(200);
return response;
}
WarehouseCalloutServiceTest.apxc:
@isTest
```

```
global classWarehouseCalloutServiceMock implements HttpCalloutMock {
/ implement http mock callout
global staticHttpResponse respond(HttpRequest request){
HttpResponse response = new HttpResponse(); response.setHeader('Content-Type',
'application/json');
response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5,"na
me":"Gene
                     rator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"},{"_id":"55d6622672
6b611100aaf742", "replacement": true, "quantity": 183, "name": "Cooling"
Fan", "maintenanceperiod": 0, "lifespan": 0, "cost": 300, "sku": "100004"}, {"_id": "55d66226726b611"
100aaf743 ","replacement":true,"quantity":143,"name":"Fuse
20A","maintenanceperiod":0,"lifespan":0,"cost":22,"sku":"100005"}]');
response.setStatusCode(200);
return response;
}
}
```

Challenge-6

WarehouseSyncSchedule.apxc:

```
global with sharing class WarehouseSyncSchedule implementsSchedulable{ global void
execute(SchedulableContext ctx){
System.enqueueJob(new WarehouseCalloutService());
}
}
```

WarehouseSyncScheduleTest.apxc:

@isTest

public class WarehouseSyncScheduleTest {
@isTest static void WarehousescheduleTest(){ StringscheduleTime = '00 00 01 * * ?';
Test.startTest();
Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
String jobID=System.schedule('Warehouse Time To Scheduleto Test', scheduleTime, new WarehouseSyncSchedule());
Test.stopTest();
/Contains schedule information for a scheduledjob. CronTrigger is similarto a cron job on UNIX systems.
/This object is available in API version 17.0 and later.
CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
System.assertEquals(jobID, a.Id,'Schedule');}}