Apex Triggers

1.GET STARTED WITH APEX TRIGGERS:

```
trigger AccountAddressTrigger on Account (before insert, before update) {
    for(Account account:Trigger.New){
        if(account.Match_Billing_Address__c == True){
            account.ShippingPostalCode = account.BillingPostalCode;
        }
    }
}
```

2.BULK PEX TRIGGER UNIT:

```
trigger ClosedOpportunityTrigger on Opportunity (after insert,after update){
  List taskList = new List();
 for(Opportunity opp:Trigger.New) {
 if(opp.StageName == 'Closed Won'){
taskList.add(new Task(Subject = 'Follow Up Test Task',WhatId =opp.Id));
 }
}
f(taskList.size() > 0){
   insert taskList;
  }
 }
```

Apex Testing

1.GET STARTED WITH APEX UNIT TESTS:

```
public class VerifyDate {

    //method to handle potential checks against two dates
        public static Date CheckDates(Date date1, Date date2) {
                //if date2 is within the next 30 days of date1, use date2.  Otherwise use
```

```
the end of the month
                if(DateWithin30Days(date1,date2)) {
                        return date2;
                } else {
                        return SetEndOfMonthDate(date1);
                }
        }

        //method to check if date2 is within the next 30 days of date1
        private static Boolean DateWithin30Days(Date date1, Date date2) {
                //check for date2 being in the past
        if( date2 < date1) { return false; }

        //check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1
                if( date2 >= date30Days ) { return false; }
                else { return true; }
        }

        //method to return the end of the month of a given date
        private static Date SetEndOfMonthDate(Date date1) {
                Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
                Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
                return lastDay;
        }

}
@IsTest
public class TestVerifyDate {
    @isTest static void date2within30daydate1() {
      Date returnDate1 = VerifyDate.CheckDates(date.valueOf('2020-02-
14'),date.valueOf('2020-02-24'));
        // this should return feb2 24,2020 because feb 24 2020 is within 30 days of feb
14 2020
        System.assertEquals(date.valueOf('2020-02-24'), returnDate1);
     }
```

```
    @isTest static void date2NOTwithin30daydate1(){
        Date returnDate2 = VerifyDate.CheckDates(date.valueOf('2020-02-
14'),date.valueOf('2020-03-24'));
        // this should return feb 24,2020 because feb 24 2020 is within 30 days of feb 14
2020
        System.assertEquals(date.valueOf('2020-02-29'),returnDate2);
    }
  }
```

2.TEST APEX TRIGGERS:

RestrictContactByName Code:

```
trigger RestrictContactByName on Contact (before insert) {
  //check contacts prior to insert or update for invalid data
        For (Contact c : Trigger.New) {
                if(c.LastName == 'INVALIDNAME') {
           //invalidname is invalid
        c.AddError('The Last Name "'+c.LastName+'" is not allowed for DML');
                }
        }
}
```

TestRestrictContactByName Code:

```
@isTest
public class TestRestrictContactByName {
  @isTest static void Test_insertupdateContact(){
    Contact cnt = new Contact();
    cnt.LastName = 'INVALIDNAME';

    Test.startTest();
    Database.SaveResult result = Database.insert(cnt,false);
    Test.stopTest();

    System.assert(!result.isSuccess());
    System.assert(result.getErrors().size() > 0);
    System.assertEquals('The Last Name "INVALIDNAME"  is not allowed for DML',
```

```
result.getErrors()[0].getMessage());
    }


}
```

3.CREATE TEST DATA FOR APEX TESTS:

RandomContactFactory code:

```
public class RandomContactFactory {
 public static List generateRandomContacts(Integer numContactsToGenerate, String
FName) {
   List<Contact> contactList=new List<Contact>();
for(Integer i=0;i<numContactsToGenerate;i++){
Contact c=new Contact(FirstName=FName+' ' +i,LatName = ' Contact'+i);
contactList.add(c);
System.debug(c);
}
System.debug(contactList.size());
return contactList;
}
}
```

Asynchronous Apex

1.USE FUTURE METHODS:

AccountProcessor Code

```
public class AccountProcessor {
  @future
 public static void countContacts(List accountIds){
List accounts = [Select Id, Name from Account Where Id IN : accountIds];
 List updatedAccounts = new List();
 for(Account account : accounts){
account.Number_of_Contacts__c = [Select count() from Contact Where AccountId =:
```

```
account.Id];
 System.debug('No Of Contacts = ' + account.Number_of_Contacts__c);
updatedAccounts.add(account);
  }        update updatedAccounts;
 }
}
```

AccountProcessorTest code

```
@isTest
public class AccountProcessorTest {
 @isTest     public static void testNoOfContacts(){
 Account a = new Account();
 a.Name= 'Test Account';
 Insert a;         Contact c = new Contact();
  c.FirstName = 'Bob';
c.LastName =  'Willie';
  c.AccountId = a.Id;
    Contact c2 = new Contact();
  c2.FirstName = 'Tom';
  c2.LastName = 'Cruise';
 c2.AccountId = a.Id;
 List acctIds = new List();
 acctIds.add(a.Id);
 Test.startTest();
AccountProcessor.countContacts(acctIds);
 Test.stopTest();
 }
```

2.USE BATCH APEX

LeadProcessor code:

```
global class LeadProcessor implements Database.Batchable<sObject> {
   global Integer count=0;

   global Database.QueryLocator start(Database.BatchableContext bc){
```

```
        return Database.getQueryLocator('SELECT Id, LeadSource FROM Lead');
    }

    global void execute(Database.BatchableContext bc, List<Lead> L_list)
    {
        List<lead> L_list_new = new List<lead>();

        for(lead L:L_list){
            L.leadSource = 'Dreamforce';
            L_list_new.add(L);
            count += 1;
        }
        update L_list_new;
    }

       global  void finish(Database.BatchableContext bc){
            system.debug('count = ' + count);
        }
    }
```

LeadProcessorTest code:

```
@isTest
public class LeadProcessorTest {

    @isTest
    public static void testit(){
        List<lead> L_list = new List<lead>();

        for(Integer i=0; i<200; i++){
            Lead L = new lead();
            L.LastName = 'name' + i;
            L.Company = 'Company';
            L.Status = 'Random Status';
            L_list.add(L);
        }
        insert L_list;
```

```
        Test.startTest();
        LeadProcessor lp = new LeadProcessor();
        Id batchId = Database.executeBatch(lp);
         Test.stopTest();

    }

}
```

4.CONTROL PROCESSES WITH QUEUEABLE APEX:

AddPrimaryContact code:

```
public class AddPrimaryContact implements Queueable {
    private Contact con;
    private String state;

    public AddPrimaryContact(Contact con, String state){
        this.con = con;
        this.state = state;
    }
    public void execute(QueueableContext context){
        List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id from
contacts)
                                  from Account where BillingState = :state Limit 200];
        List<Contact> primaryContacts = new List<Contact>();

        for(Account acc:accounts){
            contact c = con.clone();
            c.AccountId  = acc.Id;
            primaryContacts.add(c);
        }

        if(primaryContacts.size() > 0){
            insert primaryContacts;
        }
    }
```

```
}
```
AddPrimaryContactTest code:

```
@isTest
public class AddPrimaryContactTest {
   static testmethod void testQueueable(){
      List<Account> testAccounts = new List<Account>();
      for(Integer i=0;i<50;i++){
         testAccounts.add(new Account(Name= 'Account '+i,BillingState='CA'));
      }
      for(Integer j=0;j<50;j++){
         testAccounts.add(new Account(Name='Account '+j,BillingState='NY'));
      }
      insert testAccounts;

      Contact testContact = new Contact(FirstName = 'John', LastName = 'Doe');
      insert testContact;

      AddPrimaryContact addit = new addPrimaryContact(testContact, 'CA');

      Test.startTest();
      system.enqueueJob(addit);
      Test.stopTest();

      System.assertEquals(50,[Select count() from Contact where accountId in(Select Id
from Account where BillingState='CA')]);
   }

}
```

5.SCHEDULE JOBS USING APEX:

DailyLeadProcessor Code

```
global class DailyLeadProcessor implements Schedulable {
```

```
    global void execute(SchedulableContext  ctx){
        List<Lead> lList = [Select id, LeadSource From Lead Where LeadSource = NULL];

        if(!lList.isEmpty()){
            for(Lead l:lList)
            {
            l.LeadSource = 'Dreamforce';
        }
        update lList;
        }
    }

}
```

DailyLeadProcessorTest code

```
@isTest
public class DailyLeadProcessorTest {

    public static String CRON_EXP = '0 0 0 2 6 ? 2022';
    static testmethod void testScheduledJob(){
        List<Lead> leads = new List<lead>();
        for(Integer i=0; i<200; i++){
            Lead lead = new Lead(LastName ='Test'+i, LeadSource ='',Company
='TestCompany'+i, Status ='Open-NotContacted');
                leads.add(lead);
            }
            insert leads;

            Test.startTest();

            String jobId = System.schedule('Update LeadSource to DreamForce',
CRON_EXP,new DailyLeadProcessor());
            Test.stopTest();
        }
    }
```

Apex Integration Services

1.APEX REST CALLOUTS:

AnimalLocator Code

```
public class AnimalLocator{
public static String getAnimalNameById(Integer x){
 Http http = new Http();
HttpRequest req = new HttpRequest();
req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + x);
req.setMethod('GET');
Map animal= new Map();
HttpResponse res = http.send(req);
if (res.getStatusCode() == 200) {
Map results = (Map)JSON.deserializeUntyped(res.getBody());
animal = (Map) results.get('animal');
 } return (String)animal.get('name');
  }
 }
```

AnimalLocatorTest Code

```
@isTest
private class AnimalLocatorTest{
  @isTest
static void AnimalLocatorMock1() {
   Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
string result = AnimalLocator.getAnimalNameById(3);
String expectedResult = 'chicken';
 System.assertEquals(result,expectedResult );
 }
 }
```

AnimalLocatorMock code

```
@isTest global class AnimalLocatorMock implements HttpCalloutMock {
  // Implement this interface method
 global HTTPResponse respond(HTTPRequest request) {
```

```
// Create a fake response
   HttpResponse response = new HttpResponse();
 response.setHeader('Content-Type', 'application/json');
response.setBody('{"animals": ["majestic badger", "fluffy bunny", "scary bear", "chicken",
"mighty moose"]}');
  response.setStatusCode(200);
 return response;
 }
 }
```

2.APEX SOAP CALLOUTS:

ParkService code

```
@isTest
global class ParkServiceMock implements WebServiceMock {
   global void doInvoke(
          Object stub,
          Object request,
          Map<String, Object> response,
          String endpoint,
          String soapAction,
          String requestName,
          String responseNS,
          String responseName,
          String responseType) {
       ParkService.byCountryResponse response_x = new
ParkService.byCountryResponse();
       List<String> lstOfDummyParks = new List<String> {'Park1','Park2','Park3'};
       response_x.return_x = lstOfDummyParks;

       response.put('response_x', response_x);
   }
}
```

ParkLocatorTest code

```
@isTest
private class ParkLocatorTest{
```

```
    @isTest
    static void testParkLocator() {
        Test.setMock(WebServiceMock.class, new ParkServiceMock());
        String[] arrayOfParks = ParkLocator.country('India');

        System.assertEquals('Park1', arrayOfParks[0]);
    }
}
```

ParkService code:

```
//Generated by wsdl2apex

public class ParkService {
    public class byCountryResponse {
        public String[] return_x;
        private String[] return_x_type_info = new
String[]{'return','http://parks.services/',null,'0','-1','false'};
        private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
        private String[] field_order_type_info = new String[]{'return_x'};
    }
    public class byCountry {
        public String arg0;
        private String[] arg0_type_info = new
String[]{'arg0','http://parks.services/',null,'0','1','false'};
        private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
        private String[] field_order_type_info = new String[]{'arg0'};
    }
    public class ParksImplPort {
        public String endpoint_x = 'https://th-apex-soap-
service.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public Map<String,String> outputHttpHeaders_x;
        public String clientCertName_x;
        public String clientCert_x;
```

```
        public String clientCertPasswd_x;
        public Integer timeout_x;
        private String[] ns_map_type_info = new String[]{'http://parks.services/',
'ParkService'};
        public String[] byCountry(String arg0) {
            ParkService.byCountry request_x = new ParkService.byCountry();
            request_x.arg0 = arg0;
            ParkService.byCountryResponse response_x;
            Map<String, ParkService.byCountryResponse> response_map_x = new
Map<String, ParkService.byCountryResponse>();
            response_map_x.put('response_x', response_x);
            WebServiceCallout.invoke(
              this,
              request_x,
              response_map_x,
              new String[]{endpoint_x,
              '',
              'http://parks.services/',
              'byCountry',
              'http://parks.services/',
              'byCountryResponse',
              'ParkService.byCountryResponse'}
            );
            response_x = response_map_x.get('response_x');
            return response_x.return_x;
        }
    }
}
```

ParkLocator Code

```
public class ParkLocator {
    public static String[] country(String country){
        ParkService.ParksImplPort parks = new ParkService.ParksImplPort();
        String[] parksname = parks.byCountry(country);
        return parksname;
    }
}
```

3.APEX WEB SERVICES:

AccountManager Code

```
@RestResource(urlMapping='/Accounts/*/contacts')
global with sharing class AccountManager{
   @HttpGet
   global static Account getAccount(){
      RestRequest req = RestContext.request;
      String accId = req.requestURI.substringBetween('Accounts/', '/contacts');
      Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
                  FROM Account WHERE Id = :accId];

      return acc;
   }
}
```

AccountManager Test:

```
@IsTest
private class AccountManagerTest{
   @isTest static void testAccountManager(){
      Id recordId = getTestAccountId();
      // Set up a test request
      RestRequest request = new RestRequest();
      request.requestUri =
         'https://ap5.salesforce.com/services/apexrest/Accounts/'+ recordId +'/contacts';
      request.httpMethod = 'GET';
      RestContext.request = request;

      // Call the method to test
      Account  acc = AccountManager.getAccount();

      // Verify results
      System.assert(acc != null);
   }
```

```
    private static Id getTestAccountId(){
        Account acc = new Account(Name = 'TestAcc2');
        Insert acc;

        Contact con = new Contact(LastName = 'TestCont2', AccountId = acc.Id);
        Insert con;

        return acc.Id;
    }
}
```

APEX SPECIALIST SUPERBADGE:

1.QUIZ

2.AUTOMATE RECORD CREATION:

MaintenanceRequestHelper code:

```
public with sharing class MaintenanceRequestHelper {
    public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();


        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);


                }
            }
        }
```

```
    if (!validIds.isEmpty()){
        List<Case> newCases = new List<Case>();
        Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
                                                FROM Case WHERE Id IN :validIds]);
        Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
        AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds GROUP
BY Maintenance_Request__c];

    for (AggregateResult ar : results){
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }

        for(Case cc : closedCasesM.values()){
            Case nc = new Case (
                ParentId = cc.Id,
            Status = 'New',
                Subject = 'Routine Maintenance',
                Type = 'Routine Maintenance',
                Vehicle__c = cc.Vehicle__c,
                Equipment__c =cc.Equipment__c,
                Origin = 'Web',
                Date_Reported__c = Date.Today()

            );

            If (maintenanceCycles.containskey(cc.Id)){
                nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
            }

            newCases.add(nc);
```

```
        }

        insert newCases;

        List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
        for (Case nc : newCases){
            for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
                Equipment_Maintenance_Item__c wpClone = wp.clone();
                wpClone.Maintenance_Request__c = nc.Id;
                ClonedWPs.add(wpClone);

            }
        }
        insert ClonedWPs;
      }
   }
}
```

MaintenanceRequest code:

```
trigger MaintenanceRequest on Case (before update, after update) {
   if(Trigger.isUpdate && Trigger.isAfter){
      MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
   }
}
```

3.SYNCHRONIZE SALESFORCE DATA:

WarehouseCallOutService code:

```
public with sharing class WarehouseCalloutService {

   private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

   //@future(callout=true)
```

```
    public static void runWarehouseEquipmentSync(){

        Http http = new Http();
        HttpRequest request = new HttpRequest();

        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);


        List<Product2> warehouseEq = new List<Product2>();

        if (response.getStatusCode() == 200){
            List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
            System.debug(response.getBody());

            for (Object eq : jsonResponse){
                Map<String,Object> mapJson = (Map<String,Object>)eq;
                Product2 myEq = new Product2();
                myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
                myEq.Name = (String) mapJson.get('name');
                myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
                myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
                myEq.Cost__c = (Decimal) mapJson.get('lifespan');
                myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
                myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
                warehouseEq.add(myEq);
            }

            if (warehouseEq.size() > 0){
                upsert warehouseEq;
                System.debug('Your equipment was synced with the warehouse one');
                System.debug(warehouseEq);
            }

        }
```

```
    }
}
```

4.SCHEDULE SYNCHRONIZATION:

WarehouseSyncSchedule:

```
global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}
```

5.TEST AUTOMATION LOGIC:

MaintenanceRequestHelperTest code:

```
@istest
public with sharing class MaintenanceRequestHelperTest {

    private static final string STATUS_NEW = 'New';
    private static final string WORKING = 'Working';
    private static final string CLOSED = 'Closed';
    private static final string REPAIR = 'Repair';
    private static final string REQUEST_ORIGIN = 'Web';
    private static final string REQUEST_TYPE = 'Routine Maintenance';
    private static final string REQUEST_SUBJECT = 'Testing subject';

    PRIVATE STATIC Vehicle__c createVehicle(){
        Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');
        return Vehicle;
    }

    PRIVATE STATIC Product2 createEq(){
        product2 equipment = new product2(name = 'SuperEquipment',
                                          lifespan_months__C = 10,
```

```
                        maintenance_cycle__C = 10,
                        replacement_part__c = true);
    return equipment;
  }

  PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
                Status=STATUS_NEW,
                Origin=REQUEST_ORIGIN,
                Subject=REQUEST_SUBJECT,
                Equipment__c=equipmentId,
                Vehicle__c=vehicleId);
    return cs;
  }

  PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
    Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
                                        Maintenance_Request__c = requestId);
    return wp;
  }


  @istest
  private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;

    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;
```

```
        Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
        insert workP;

        test.startTest();
        somethingToUpdate.status = CLOSED;
        update somethingToUpdate;
        test.stopTest();

        Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c,
Vehicle__c, Date_Due__c
                from case
                where status =:STATUS_NEW];

        Equipment_Maintenance_Item__c workPart = [select id
                                    from Equipment_Maintenance_Item__c
                                    where Maintenance_Request__c =:newReq.Id];

        system.assert(workPart != null);
        system.assert(newReq.Subject != null);
        system.assertEquals(newReq.Type, REQUEST_TYPE);
        SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);
        SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);
        SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
    }

    @istest
    private static void testMaintenanceRequestNegative(){
        Vehicle__C vehicle = createVehicle();
        insert vehicle;
        id vehicleId = vehicle.Id;

        product2 equipment = createEq();
        insert equipment;
        id equipmentId = equipment.Id;

        case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
```

```
        insert emptyReq;

        Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,
emptyReq.Id);
        insert workP;

        test.startTest();
        emptyReq.Status = WORKING;
        update emptyReq;
        test.stopTest();

        list<case> allRequest = [select id
                                 from case];

        Equipment_Maintenance_Item__c workPart = [select id
                                                  from Equipment_Maintenance_Item__c
                                                  where Maintenance_Request__c = :emptyReq.Id];

        system.assert(workPart != null);
        system.assert(allRequest.size() == 1);
    }

    @istest
    private static void testMaintenanceRequestBulk(){
        list<Vehicle__C> vehicleList = new list<Vehicle__C>();
        list<Product2> equipmentList = new list<Product2>();
        list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
        list<case> requestList = new list<case>();
        list<id> oldRequestIds = new list<id>();

        for(integer i = 0; i < 300; i++){
          vehicleList.add(createVehicle());
           equipmentList.add(createEq());
        }
        insert vehicleList;
        insert equipmentList;
```

```
        for(integer i = 0; i < 300; i++){
            requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
        }
        insert requestList;

        for(integer i = 0; i < 300; i++){
            workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
        }
        insert workPartList;

        test.startTest();
        for(case req : requestList){
            req.Status = CLOSED;
            oldRequestIds.add(req.Id);
        }
        update requestList;
        test.stopTest();

        list<case> allRequests = [select id
                                  from case
                                  where status =: STATUS_NEW];

        list<Equipment_Maintenance_Item__c> workParts = [select id
                                                         from Equipment_Maintenance_Item__c
                                                         where Maintenance_Request__c in: oldRequestIds];

        system.assert(allRequests.size() == 300);
    }
}
```

6.TEST CALLOUT LOGIC:

WarehouseCallOutService code

```
public with sharing class WarehouseCalloutService {
```

```
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

    //@future(callout=true)
    public static void runWarehouseEquipmentSync(){

        Http http = new Http();
        HttpRequest request = new HttpRequest();

        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);



        List<Product2> warehouseEq = new List<Product2>();

        if (response.getStatusCode() == 200){
            List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
            System.debug(response.getBody());

            for (Object eq : jsonResponse){
                Map<String,Object> mapJson = (Map<String,Object>)eq;
                Product2 myEq = new Product2();
                myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
                myEq.Name = (String) mapJson.get('name');
                myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
                myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
                myEq.Cost__c = (Decimal) mapJson.get('lifespan');
                myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
                myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
                warehouseEq.add(myEq);
            }

            if (warehouseEq.size() > 0){
                upsert warehouseEq;
```

```
            System.debug('Your equipment was synced with the warehouse one');
            System.debug(warehouseEq);
        }

    }
  }
}
```

WarehouseCallOutServiceTest code:

```
@isTest

private class WarehouseCalloutServiceTest {
  @isTest
  static void testWareHouseCallout(){
    Test.startTest();
    // implement mock callout test here
    Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
    WarehouseCalloutService.runWarehouseEquipmentSync();
    Test.stopTest();
    System.assertEquals(1, [SELECT count() FROM Product2]);
  }
}
```

WarehouseCallOutServiceMock Code

```
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
  // implement http mock callout
  global static HttpResponse respond(HttpRequest request){

    System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
    System.assertEquals('GET', request.getMethod());

    // Create a fake response
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
```

```
response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5
,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}]');
        response.setStatusCode(200);
        return response;
    }
}
```

7.TEST SCHEDULING LOGIC:

WarehouseSyncSchedule code:

```
@isTest
public class WarehouseSyncScheduleTest {

    @isTest static void WarehousescheduleTest(){
        String scheduleTime = '00 00 01 * * ?';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String jobID=System.schedule('Warehouse Time To Schedule to Test',
scheduleTime, new WarehouseSyncSchedule());
        Test.stopTest();
        //Contains schedule information for a scheduled job. CronTrigger is similar to a
cron job on UNIX systems.
        // This object is available in API version 17.0 and later.
        CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
        System.assertEquals(jobID, a.Id,'Schedule ');


    }
}
```