```
Apex Triggers >Get Started with Apex Triggers
trigger AccountAddressTrigger on Account (before insert,before update) {
  for (Account account : trigger.new){
    if(account.Match_Billing_Address__c==true){
      account.ShippingPostalCode=account.BillingPostalCode;
    }
 }
Apex Triggers >Bulk Apex Triggers
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {
  List<Task> taskList = new List <task>();
 for(Opportunity opp : Trigger.New){
    if(opp.StageName == 'Closed Won'){
      taskList.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));
   }
  if(taskList.size()>0){
    insert taskList;
 }
}
Apex Testing > Get Started with Apex Unit Tests
TestVerifyDate.apxc
@isTest
public class TestVerifyDate {
  @isTest static void test1(){
    Date d =
VerifyDate.CheckDates(Date.parse('06/06/2022'),Date.parse('06/09/2022'));
    System.assertEquals(Date.parse('06/09/2022'), d);
```

```
}
  @isTest static void test2(){
    Date d =
VerifyDate.CheckDates(Date.parse('06/06/2022'),Date.parse('09/09/2022'));
    System.assertEquals(Date.parse('06/31/2022'), d);
  }
}
Apex Testing > Test Apex Triggers
TestRestrictContactByName.apxc
@isTest
public class TestRestrictContactByName {
  @isTest
  public static void testContact(){
    Contact ct = new Contact();
    ct.LastName = 'INVALIDNAME';
    Database.SaveResult res = Database.insert(ct,false);
    System.assertEquals('The last Name "INVALIDNAME" is not allowed for
DML',res.getErrors()[0].getMessage());
  }
}
Apex Testing > Create Test Data for Apex Tests
RandomContactFactory.apxc
public class RandomContactFactory {
  public static List<Contact> generateRandomContacts(Integer num,String lastName){
      List<Contact> contactList=new List<Contact>();
    for(Integer i=1;i<=num;i++){</pre>
      Contact ct=new Contact(FirstName='Test'+i,LastName=lastName);
      contactList.add(ct);
    return contactList;
```

```
}
Asynchronous Apex >
Use Future Methods
AccountProcessor.apxc
public class AccountProcessor {
  @future
  public static void countContacts(List<Id> accountIds){
      List<Account> accList = [Select Id, Number_Of_Contacts__c, (Select Id from
Contacts) from Account where Id in :accountIds];
    for(Account acc : accList){
      acc.Number_Of_Contacts__c = acc.Contacts.size();
    }
    update accList;
 }
}
AccountProcessorTest.apxc
@isTest
public class AccountProcessorTest {
  public static testmethod void testAccountProcessor(){
    Account a = new Account();
    a.Name = 'Test Account';
    insert a;
    Contact con = new Contact();
    con.FirstName = 'Ravali';
```

```
con.LastName ='Chandaka';
    con.AccountId = a.Id;
    insert con;
    List<Id> accListId = new List<Id>();
    accListId.add(a.ld);
    Test.startTest();
    AccountProcessor.countContacts(accListId);
    Test.stopTest();
    Account acc = [Select Number_of_Contacts__c from Account where Id =: a.Id];
    System.assertEquals(Integer.valueof(acc.Number_Of_Contacts__c), 1);
  }
}
Asynchronous Apex
Use Batch Apex
LeadProcessor.apxc
global class LeadProcessor implements Database.Batchable<sObject> {
  global Integer count = 0;
  global Database.QueryLocator start (Database.BatchableContext bc) {
    return Database.getQueryLocator('Select Id, LeadSource from lead');
  }
  global void execute (Database.BatchableContext bc,List<Lead> l_lst) {
    List<lead> | lst_new = new List<lead>();
    for(lead I : I_lst) {
      l.leadsource = 'Dreamforce';
      l_lst_new.add(l);
      count+=1;
```

```
update l_lst_new;
  }
  global void finish (Database.BatchableContext bc) {
    system.debug('count = '+count);
 }
}
LeadProcessorTest.apxc
@isTest
public class LeadProcessorTest {
  @isTest
  public static void testit() {
    List<lead> | List = new List<lead>();
    for (Integer i = 0; i<200; i++) {
      Lead I = new lead();
      l.LastName = 'name'+i;
      l.company = 'company';
      I.Status = 'somestatus';
      l_lst.add(l);
    }
    insert l_lst;
    test.startTest();
    Leadprocessor lp = new Leadprocessor();
    Id batchId = Database.executeBatch(lp);
    Test.stopTest();
 }
}
Asynchronous Apex
Control Processes with Queueable Apex
```

AddPrimaryContact.apxc

```
public class AddPrimaryContact implements Queueable {
  public contact c;
  public String state;
  public AddPrimaryContact(Contact c, String state) {
    this.c = c;
    this.state = state;
  }
  public void execute(QueueableContext qc) {
    system.debug('this.c = '+this.c+' this.state = '+this.state);
    List<Account> acc_lst = new List<account>([select id, name, BillingState from
account where account.BillingState = :this.state limit 200]);
    List<contact> c_lst = new List<contact>();
    for(account a: acc_lst) {
      contact c = new contact();
      c = this.c.clone(false, false, false, false);
      c.AccountId = a.Id:
      c_lst.add(c);
    insert c_lst;
  }
}
AddPrimaryContactTest.apxc
@IsTest
public class AddPrimaryContactTest {
  @lsTest
  public static void testing() {
    List<account> acc_lst = new List<account>();
    for (Integer i=0; i<50;i++) {
       account a = new account(name=string.valueOf(i),billingstate='NY');
       system.debug('account a = '+a);
```

```
acc_lst.add(a);
    for (Integer i=0; i<50;i++) {
      account a = new account(name=string.valueOf(50+i),billingstate='CA');
      system.debug('account a = '+a);
      acc_lst.add(a);
    insert acc_lst;
    Test.startTest();
    contact c = new contact(lastname='alex');
    AddPrimaryContact apc = new AddPrimaryContact(c,'CA');
    system.debug('apc = '+apc);
    System.enqueueJob(apc);
    Test.stopTest();
    List<contact> c_lst = new List<contact>([select id from contact]);
    Integer size = c_lst.size();
    system.assertEquals(50, size);
  }
}
Asynchronous Apex
Schedule Jobs Using the Apex Scheduler
DailyLeadProcessor.apxc
global class DailyLeadProcessor implements Schedulable {
  global void execute(SchedulableContext ctx) {
    List<Lead> | List = [Select Id, LeadSource from Lead where LeadSource = null limit
200];
    list<lead> led = new list<lead>();
    if(!IList.isEmpty()) {
      for(Lead I: IList) {
         I.LeadSource = 'Dreamforce';
         led.add(l);
      }
      update led;
```

```
}
 }
DailyLeadProcessorTest.apxc
@isTest
public class DailyLeadProcessorTest{
  static testMethod void testMethod1()
        Test.startTest();
    List<Lead> lstLead = new List<Lead>();
    for(Integer i=0; i < 200; i++)
      Lead led = new Lead();
      led.FirstName ='FirstName';
      led.LastName ='LastName'+i;
      led.Company ='demo'+i;
      lstLead.add(led);
    }
    insert lstLead;
    DailyLeadProcessor ab = new DailyLeadProcessor();
    String jobId = System.schedule('jobName','0 5 * * * ? ',ab);
    Test.stopTest();
}
Apex Integration Services
Apex REST Callout
AnimalLocator.apxc
```

```
public class AnimalLocator {
       public class cls_animal {
             public Integer id;
             public String name;
             public String eats;
             public String says;
public class JSONOutput{
       public cls_animal animal;
      //public JSONOutput parse(String json){
      //return (JSONOutput) System.JSON.deserialize(json, JSONOutput.class);
      //}
}
  public static String getAnimalNameById (Integer id) {
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + id);
    //request.setHeader('id', String.valueof(id)); -- cannot be used in this challenge :)
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    system.debug('response: ' + response.getBody());
    //Map<String,Object> map_results = (Map<String,Object>)
JSON.deserializeUntyped(response.getBody());
    jsonOutput results = (jsonOutput) JSON.deserialize(response.getBody(),
jsonOutput.class);
    //Object results = (Object) map_results.get('animal');
             system.debug('results= ' + results.animal.name);
    return(results.animal.name);
  }
}
AnimalLocatorMock.apxc
@lsTest
global class AnimalLocatorMock implements HttpCalloutMock {
```

```
global HTTPresponse respond(HTTPreguest reguest) {
    Httpresponse response = new Httpresponse();
    response.setStatusCode(200);
    //-- directly output the JSON, instead of creating a logic
    //response.setHeader('key, value)
    //Integer id = Integer.valueof(request.getHeader('id'));
    //Integerid = 1;
    //List<String> lst_body = new List<String> {'majestic badger', 'fluffy bunny'};
    //system.debug('animal return value: ' + lst_body[id]);
    response.setBody('{"animal":{"id":1,"name":"chicken","eats":"chicken
food","says":"cluck cluck"}}');
    return response;
  }
}
AnimalLocatorTest.apxc
@IsTest
public class AnimalLocatorTest {
  @isTest
  public static void testAnimalLocator() {
    Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
    //Httpresponse response = AnimalLocator.getAnimalNameById(1);
    String s = AnimalLocator.getAnimalNameById(1);
    system.debug('string returned: ' + s);
  }
}
Apex Integration Services
Apex SOAP Callouts
ParkLocator.apxc
public class ParkLocator {
  public static String[] country(String country){
```

```
ParkService.ParksImplPort parks = new ParkService.ParksImplPort();
    String[] parksname = parks.byCountry(country);
    return parksname;
 }
}
ParkServiceMock.apxc
@isTest
global class ParkServiceMock implements WebServiceMock {
  global void doInvoke(
     Object stub,
     Object request,
     Map<String, Object> response,
     String endpoint,
     String soapAction,
     String requestName,
     String responseNS,
     String responseName,
     String responseType) {
    ParkService.byCountryResponse response_x = new
ParkService.byCountryResponse();
    List<String> lstOfDummyParks = new List<String> {'Park1', Park2', Park3'};
    response_x.return_x = lstOfDummyParks;
    response.put('response_x', response_x);
 }
}
ParkLocatorTest.apxc
@isTest
private class ParkLocatorTest{
  @isTest
  static void testParkLocator() {
    Test.setMock(WebServiceMock.class, new ParkServiceMock());
```

```
String[] arrayOfParks = ParkLocator.country('India');
    System.assertEquals('Park1', arrayOfParks[0]);
 }
}
Apex Integration Services
Apex Web Services
AccountManager.apxc
@RestResource(urlMapping='/Accounts/*/contacts')
global with sharing class AccountManager{
  @HttpGet
  global static Account getAccount(){
    RestRequest req = RestContext.request;
    String accld = req.requestURI.substringBetween('Accounts/', '/contacts');
    Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
            FROM Account WHERE Id = :accld];
    return acc;
 }
}
AccountManagerTest.apxc
@IsTest
private class AccountManagerTest{
  @isTest static void testAccountManager(){
    Id recordId = getTestAccountId();
    // Set up a test request
    RestRequest request = new RestRequest();
    request.requestUri =
      'https://ap5.salesforce.com/services/apexrest/Accounts/'+ recordId +'/contacts';
    request.httpMethod = 'GET';
    RestContext.request = request;
```

```
// Call the method to test
    Account acc = AccountManager.getAccount();
    // Verify results
    System.assert(acc!= null);
  }
  private static Id getTestAccountId(){
    Account acc = new Account(Name = 'TestAcc2');
    Insert acc;
    Contact con = new Contact(LastName = 'TestCont2', AccountId = acc.Id);
    Insert con;
    return acc.ld;
}
Automate record creation
MaintenanceRequestHelper.apxc:
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.ld);
        }
     }
```

```
if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment_c, Equipment_r.Maintenance_Cycle_c,(SELECT
Id,Equipment_c,Quantity_c FROM Equipment_Maintenance_Items_r)
                              FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment_r.Maintenance_Cycle_c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds GROUP
BY Maintenance_Request__c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }
      for(Case cc : closedCasesM.values()){
        Case nc = new Case (
          ParentId = cc.Id.
        Status = 'New',
          Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle_c = cc.Vehicle_c,
          Equipment_c =cc.Equipment_c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
        If (maintenanceCycles.containskey(cc.ld)){
          nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.ld));
        } else {
          nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipment__r.maintenance_Cycle__c);
        }
```

```
newCases.add(nc);
      }
     insert newCases;
     List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
     for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
          Equipment_Maintenance_Item__c wpClone = wp.clone();
          wpClone.Maintenance_Request__c = nc.ld;
          ClonedWPs.add(wpClone);
        }
      insert ClonedWPs;
MaitenanceRequest.apxt:-
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
 }
}
Synchronize Salesforce data with an external system
WarehouseCalloutService.apxc:-
public with sharing class WarehouseCalloutService implements Queueable {
```

```
private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
```

//class that makes a REST callout to an external warehouse system to get a list of equipment that needs to be updated.

//The callout's JSON response returns the equipment records that you upsert in Salesforce.

```
@future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
      List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      //class maps the following fields: replacement part (always true), cost, current
inventory, lifespan, maintenance cycle, and warehouse SKU
      //warehouse SKU will be external ID for identifying which equipment records to
update within Salesforce
      for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost_c = (Integer) mapJson.get('cost');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory_c = (Double) mapJson.get('quantity');
```

```
myEq.ProductCode = (String) mapJson.get('_id');
        warehouseEq.add(myEq);
      }
      if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
      }
    }
  }
  public static void execute (QueueableContext context){
    runWarehouseEquipmentSync();
  }
}
ctrl+e:- System.enqueueJob(new WarehouseCalloutService());
Schedule synchronization
WarehouseSyncShedule.apxc:-
global with sharing class WarehouseSyncSchedule implements Schedulable{
  global void execute(SchedulableContext ctx){
    System.enqueueJob(new WarehouseCalloutService());
 }
}
Test automation logic
MaintenanceRequestHelperTest.apxc:-
@istest
public with sharing class MaintenanceRequestHelperTest {
  private static final string STATUS_NEW = 'New';
```

```
private static final string WORKING = 'Working';
  private static final string CLOSED = 'Closed';
  private static final string REPAIR = 'Repair';
  private static final string REQUEST_ORIGIN = 'Web';
  private static final string REQUEST_TYPE = 'Routine Maintenance';
  private static final string REQUEST_SUBJECT = 'Testing subject';
  PRIVATE STATIC Vehicle_c createVehicle(){
    Vehicle_c Vehicle = new Vehicle_C(name = 'SuperTruck');
    return Vehicle:
 }
  PRIVATE STATIC Product2 createEq(){
    product2 equipment = new product2(name = 'SuperEquipment',
                     lifespan_months__C = 10,
                      maintenance_cycle__C = 10,
                      replacement_part__c = true);
    return equipment;
  }
  PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
             Status=STATUS_NEW,
             Origin=REQUEST_ORIGIN,
             Subject=REQUEST_SUBJECT,
             Equipment_c=equipmentId,
             Vehicle_c=vehicleId);
    return cs:
  }
  PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
    Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
                                        Maintenance_Request__c = requestId);
    return wp;
  }
```

```
@istest
  private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle:
    id vehicleId = vehicle.Id;
    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;
    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP:
    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();
    Case newReq = [Select id, subject, type, Equipment_c, Date_Reported_c,
Vehicle_c, Date_Due_c
           from case
           where status =:STATUS_NEW];
    Equipment_Maintenance_Item__c workPart = [select id
                         from Equipment_Maintenance_Item__c
                         where Maintenance_Request__c =:newReq.Id];
    system.assert(workPart != null);
    system.assert(newReq.Subject != null);
    system.assertEquals(newReq.Type, REQUEST_TYPE);
    SYSTEM.assertEquals(newReq.Equipment_c, equipmentId);
    SYSTEM.assertEquals(newReg.Vehicle_c, vehicleId);
    SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
```

```
}
  @istest
  private static void testMaintenanceRequestNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;
    product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
    insert emptyReq;
    Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,
emptyReq.Id);
    insert workP;
    test.startTest();
    emptyReq.Status = WORKING;
    update emptyReq;
    test.stopTest();
    list<case> allRequest = [select id
                  from casel;
    Equipment_Maintenance_Item__c workPart = [select id
                           from Equipment_Maintenance_Item__c
                           where Maintenance_Request__c = :emptyReq.Id];
    system.assert(workPart != null);
    system.assert(allRequest.size() == 1);
  }
  @istest
  private static void testMaintenanceRequestBulk(){
    list<Vehicle_C> vehicleList = new list<Vehicle_C>();
```

```
list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();
    for(integer i = 0; i < 300; i++){
      vehicleList.add(createVehicle());
      equipmentList.add(createEq());
    insert vehicleList;
    insert equipmentList;
    for(integer i = 0; i < 300; i++){
      requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    insert requestList;
    for(integer i = 0; i < 300; i++){
      workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
    insert workPartList;
    test.startTest();
    for(case req : requestList){
      req.Status = CLOSED;
      oldRequestIds.add(req.Id);
    update requestList;
    test.stopTest();
    list<case> allRequests = [select id
                  from case
                  where status =: STATUS_NEW];
    list<Equipment_Maintenance_Item__c> workParts = [select id
                               from Equipment_Maintenance_Item__c
```

```
where Maintenance_Request__c in: oldRequestIds];
    system.assert(allRequests.size() == 300);
 }
}
MaintenanceRequestHelper.apxc:-
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.Id);
       }
     }
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment_c, Equipment_r.Maintenance_Cycle_c,(SELECT
Id,Equipment_c,Quantity_c FROM Equipment_Maintenance_Items_r)
                             FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment_r.Maintenance_Cycle_c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds GROUP
BY Maintenance_Request__c];
```

```
for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }
      for(Case cc : closedCasesM.values()){
        Case nc = new Case (
          ParentId = cc.Id.
        Status = 'New'.
          Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle_c = cc.Vehicle_c,
          Equipment_c = cc.Equipment_c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
        If (maintenanceCycles.containskey(cc.ld)){
          nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.ld));
        }
        newCases.add(nc);
      }
     insert newCases;
     List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
     for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp:
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
          Equipment_Maintenance_Item__c wpClone = wp.clone();
          wpClone.Maintenance_Request__c = nc.ld;
          ClonedWPs.add(wpClone);
        }
```

```
}
      insert ClonedWPs;
  }
MaintenanceRequest.apxt:-
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
 }
}
Test callout logic
WarehouseCalloutService.apxc:-
public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
  //@future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
```

```
List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost_c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
      }
      if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
      }
    }
WarehouseCalloutServiceTest.apxc:-
@isTest
private class WarehouseCalloutServiceTest {
  @isTest
  static void testWareHouseCallout(){
    Test.startTest();
    // implement mock callout test here
```

```
Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
    WarehouseCalloutService.runWarehouseEquipmentSync();
    Test.stopTest();
    System.assertEquals(1, [SELECT count() FROM Product2]);
 }
}
WarehouseCalloutServiceMock.apxc:-
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
  // implement http mock callout
  global static HttpResponse respond(HttpRequest request){
    System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
    System.assertEquals('GET', request.getMethod());
    // Create a fake response
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5
"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}]');
    response.setStatusCode(200);
    return response;
 }
}
Test scheduling logic
WarehouseSyncSchedule.apxc:-
global class WarehouseSyncSchedule implements Schedulable {
  global void execute(SchedulableContext ctx) {
```

```
WarehouseCalloutService.runWarehouseEquipmentSync();
  }
}
WarehouseSyncScheduleTest.apxc:-
@isTest
public class WarehouseSyncScheduleTest {
  @isTest static void WarehousescheduleTest(){
    String scheduleTime = '00 00 01 * * ?';
    Test.startTest();
    Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
    String jobID=System.schedule('Warehouse Time To Schedule to Test',
scheduleTime, new WarehouseSyncSchedule());
    Test.stopTest();
    //Contains schedule information for a scheduled job. CronTrigger is similar to a
cron job on UNIX systems.
    // This object is available in API version 17.0 and later.
    CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
    System.assertEquals(jobID, a.ld,'Schedule ');
 }
```