Apex Specialist

1-Automate record creation

```
MaintenanceRequestHelper.apxc:-
public with sharing class MaintenanceRequestHelper {
public static void updateWorkOrders(List<Case> caseList) {
List<case> newCases = new List<Case>();
Map<String,Integer> result=getDueDate(caseList);
for(Case c : caseList){
if(c.status=='closed')
if(c.type=='Repair' || c.type=='Routine Maintenance'){
Case newCase = new Case();
newCase.Status='New';
newCase.Origin='web';
newCase.Type='Routine Maintenance';
newCase.Subject='Routine Maintenance of Vehicle';
newCase.Vehicle__c=c.Vehicle__c;
newCase.Equipment__c=c.Equipment__c;
newCase.Date_Reported__c=Date.today();
if(result.get(c.Id)!=null)
newCase.Date_Due__c=Date.today()+result.get(c.ld);
else
newCase.Date_Due__c=Date.today();
newCases.add(newCase);
}
insert newCases;
}
//
public static Map<String,Integer> getDueDate(List<case> CaseIDs){
Map<String,Integer> result = new Map<String,Integer>();
Map<ld, case> caseKeys = new Map<ld, case> (CaseIDs);
List<AggregateResult> wpc=[select Maintenance_Request__r.ID
cID,min(Equipment__r.Maintenance_Cycle__c)cycle
from Work_Part__c where Maintenance_Request__r.ID in :caseKeys.keySet() group by
Maintenance_Request__r.ID ];
for(AggregateResult res :wpc){
Integer addDays=0;
if(res.get('cycle')!=null)
addDays+=Integer.valueOf(res.get('cycle'));
```

```
result.put((String)res.get('cID'),addDays);
}
return result;
}
MaitenanceRequest.apxt:-
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
 }
}
2. Synchronize Salesforce data with an external system
WarehouseCalloutService.apxc:-
public with sharing class WarehouseCalloutService implements Queueable {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
  //class that makes a REST callout to an external warehouse system to get a list of equipment
that needs to be updated.
  //The callout's JSON response returns the equipment records that you upsert in Salesforce.
  @future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
      List<Object> jsonResponse =
```

```
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      //class maps the following fields: replacement part (always true), cost, current inventory,
lifespan, maintenance cycle, and warehouse SKU
      //warehouse SKU will be external ID for identifying which equipment records to update
within Salesforce
      for (Object eq: jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eg;
        Product2 myEq = new Product2();
        myEq.Replacement_Part_c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months_c = (Integer) mapJson.get('lifespan');
        myEq.Cost_c = (Integer) mapJson.get('cost');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        myEq.ProductCode = (String) mapJson.get('_id');
        warehouseEq.add(myEq);
      }
      if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
      }
    }
  }
  public static void execute (QueueableContext context){
    runWarehouseEquipmentSync();
  }
}
3. Schedule synchronization
```

WarehouseSyncShedule.apxc:-

```
global with sharing class WarehouseSyncSchedule implements Schedulable{
  global void execute(SchedulableContext ctx){
    System.enqueueJob(new WarehouseCalloutService());
 }
}
4. Test automation logic
MaintenanceRequestHelperTest.apxc:-
@istest
public with sharing class MaintenanceRequestHelperTest {
  private static final string STATUS_NEW = 'New';
  private static final string WORKING = 'Working';
  private static final string CLOSED = 'Closed';
  private static final string REPAIR = 'Repair';
  private static final string REQUEST_ORIGIN = 'Web';
  private static final string REQUEST_TYPE = 'Routine Maintenance';
  private static final string REQUEST_SUBJECT = 'Testing subject';
  PRIVATE STATIC Vehicle_c createVehicle(){
    Vehicle_c Vehicle = new Vehicle_C(name = 'SuperTruck');
    return Vehicle;
  }
  PRIVATE STATIC Product2 createEq(){
    product2 equipment = new product2(name = 'SuperEquipment',
                     lifespan_months__C = 10,
                      maintenance_cycle__C = 10,
                      replacement_part__c = true);
    return equipment;
  }
  PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
              Status=STATUS_NEW,
              Origin=REQUEST_ORIGIN,
              Subject=REQUEST_SUBJECT,
```

```
Equipment_c=equipmentId,
             Vehicle_c=vehicleId);
    return cs;
  }
  PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
    Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
                                        Maintenance_Request__c = requestId);
    return wp;
  }
  @istest
  private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle:
    id vehicleId = vehicle.Id;
    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;
    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;
    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();
    Case newReq = [Select id, subject, type, Equipment_c, Date_Reported_c, Vehicle_c,
Date Due c
           from case
           where status =:STATUS_NEW];
```

```
Equipment_Maintenance_Item__c workPart = [select id
                       from Equipment_Maintenance_Item__c
                       where Maintenance_Request__c =:newReq.Id];
  system.assert(workPart != null);
  system.assert(newReq.Subject != null);
  system.assertEquals(newReg.Type, REQUEST_TYPE);
  SYSTEM.assertEquals(newReq.Equipment_c, equipmentId);
  SYSTEM.assertEquals(newReq.Vehicle_c, vehicleId);
  SYSTEM.assertEquals(newReq.Date_Reported_c, system.today());
}
@istest
private static void testMaintenanceRequestNegative(){
  Vehicle__C vehicle = createVehicle();
  insert vehicle:
  id vehicleId = vehicle.Id;
  product2 equipment = createEq();
  insert equipment;
  id equipmentId = equipment.Id;
  case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
  insert emptyReg;
  Equipment_Maintenance_Item_c workP = createWorkPart(equipmentId, emptyReq.Id);
  insert workP;
  test.startTest();
  emptyReq.Status = WORKING;
  update emptyReq;
  test.stopTest();
  list<case> allRequest = [select id
               from casel;
  Equipment_Maintenance_Item__c workPart = [select id
                        from Equipment_Maintenance_Item__c
                        where Maintenance_Request__c = :emptyReq.Id];
  system.assert(workPart != null);
```

```
system.assert(allRequest.size() == 1);
  }
  @istest
  private static void testMaintenanceRequestBulk(){
    list<Vehicle_C> vehicleList = new list<Vehicle_C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();
    for(integer i = 0; i < 300; i++){
      vehicleList.add(createVehicle());
      equipmentList.add(createEq());
    }
    insert vehicleList;
    insert equipmentList;
    for(integer i = 0; i < 300; i++){
      requestList.add(createMaintenanceRequest(vehicleList.get(i).id, equipmentList.get(i).id));
    }
    insert requestList;
    for(integer i = 0; i < 300; i++){
      workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
    }
    insert workPartList;
    test.startTest();
    for(case req : requestList){
      req.Status = CLOSED;
      oldRequestIds.add(req.Id);
    }
    update requestList;
    test.stopTest();
    list<case> allRequests = [select id
                  from case
                  where status =: STATUS_NEW];
```

```
list<Equipment_Maintenance_Item__c> workParts = [select id
                             from Equipment_Maintenance_Item__c
                             where Maintenance_Request__c in: oldRequestIds];
    system.assert(allRequests.size() == 300);
 }
MaintenanceRequestHelper.apxc:-
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.Id);
       }
     }
    }
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment_c, Equipment_r.Maintenance_Cycle_c,(SELECT Id,Equipment_c,Quantity_c
FROM Equipment_Maintenance_Items__r)
                              FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment_r.Maintenance_Cycle_c)cycle FROM Equipment_Maintenance_Item_c
WHERE Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));
```

```
}
      for(Case cc : closedCasesM.values()){
        Case nc = new Case (
          ParentId = cc.Id,
        Status = 'New',
          Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle__c = cc.Vehicle__c,
          Equipment_c = cc. Equipment_c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
        If (maintenanceCycles.containskey(cc.ld)){
          nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
        }
        newCases.add(nc);
      }
      insert newCases:
      List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
      for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
          Equipment_Maintenance_Item__c wpClone = wp.clone();
          wpClone.Maintenance_Request__c = nc.ld;
          ClonedWPs.add(wpClone);
        }
      insert ClonedWPs;
    }
 }
}
```

```
MaintenanceRequest.apxt:-
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
 }
}
Test callout logic
WarehouseCalloutService.apxc:-
public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
  //@future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
      List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      for (Object eq: jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
```

```
Product2 myEq = new Product2();
        myEq.Replacement_Part_c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months_c = (Integer) mapJson.get('lifespan');
        myEq.Cost_c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
      }
      if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
      }
   }
WarehouseCalloutServiceTest.apxc:-
@isTest
private class WarehouseCalloutServiceTest {
  @isTest
  static void testWareHouseCallout(){
    Test.startTest();
    // implement mock callout test here
    Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
    WarehouseCalloutService.runWarehouseEquipmentSync();
    Test.stopTest();
    System.assertEquals(1, [SELECT count() FROM Product2]);
 }
}
```

WarehouseCalloutServiceMock.apxc:-

```
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
  // implement http mock callout
  global static HttpResponse respond(HttpRequest request){
    System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
    System.assertEquals('GET', request.getMethod());
    // Create a fake response
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5,"name":
"Generator 1000 kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}]');
    response.setStatusCode(200);
    return response;
 }
}
6.Test scheduling logic
WarehouseSyncSchedule.apxc:-
global class WarehouseSyncSchedule implements Schedulable {
  global void execute(SchedulableContext ctx) {
    WarehouseCalloutService.runWarehouseEquipmentSync();
  }
WarehouseSyncScheduleTest.apxc:-
@isTest
public class WarehouseSyncScheduleTest {
  @isTest static void WarehousescheduleTest(){
    String scheduleTime = '00 00 01 * * ?';
    Test.startTest();
    Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
    String jobID=System.schedule('Warehouse Time To Schedule to Test', scheduleTime, new
```

```
WarehouseSyncSchedule());
    Test.stopTest();
    //Contains schedule information for a scheduled job. CronTrigger is similar to a cron job on
UNIX systems.
    // This object is available in API version 17.0 and later.
    CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
    System.assertEquals(jobID, a.ld,'Schedule ');
 }
process Automation Specialist
1. Automate leads
 Error condition formula:-
OR(AND(LEN(State) > 2,
NOT(CONTAINS("AL:AK:AZ:AR:CA:CO:CT:DE:DC:FL:GA:HI:ID:IL:IN:IA:KS:KY:LA:ME:MD:MA:MI:M
N:MS:MO:MT:NE:NV:NH:NJ:NM:NY:NC:ND:OH:OK:OR:PA:RI:SC:SD:TN:TX:UT:VT:VA:WA:WV:WI:
WY", State )) ), NOT(OR(Country = "US", Country = "USA", Country = "United States",
ISBLANK(Country))))
1. Automate Accounts
 Error condition formula:-
OR(AND(LEN(BillingState) > 2,
NOT(CONTAINS("AL:AK:AZ:AR:CA:CO:CT:DE:DC:FL:GA:HI:ID:IL:IN:IA:KS:KY:LA:ME:MD:MA:MI:M
N:MS:MO:MT:NE:NV:NH:NJ:NM:NY:NC:ND:OH:OK:OR:PA:RI:SC:SD:TN:TX:UT:VT:VA:WA:WV:WI:
WY", BillingState ))
),AND(LEN(ShippingState) > 2,
```

NOT(CONTAINS("AL:AK:AZ:AR:CA:CO:CT:DE:DC:FL:GA:HI:ID:IL:IN:IA:KS:KY:LA:ME:MD:MA:MI:M N:MS:MO:MT:NE:NV:NH:NJ:NM:NY:NC:ND:OH:OK:OR:PA:RI:SC:SD:TN:TX:UT:VT:VA:WA:WV:WI: WY", ShippingState))

),NOT(OR(BillingCountry = "US",BillingCountry = "USA",BillingCountry = "United States", ISBLANK(BillingCountry))),

NOT(OR(ShippingCountry = "US",ShippingCountry = "USA",ShippingCountry = "United States", ISBLANK(ShippingCountry))))