

I Have completed developer catalyst in trialhead and I have finished "TWO" superbades they are :

### 1.APEX SPECIALIST

2.Process Automation Specialist so in this pdf iam going to mention all the codes related apex specialist super badge and apex modules

## APEX SPECIALIST

### 1-Automate record creation

#### MaintenanceRequestHelper

```
public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }

        if (!validIds.isEmpty()){
            List<Case> newCases = new List<Case>();
            Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT Id,Equipment__c,Quantity__c
FROM Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
            Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
            AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM Equipment_Maintenance_Item__c
WHERE Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];
```

```

    for (AggregateResult ar : results){
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));
    }

    for(Case cc : closedCasesM.values()){
        Case nc = new Case (
            ParentId = cc.Id,
            Status = 'New',
            Subject = 'Routine Maintenance',
            Type = 'Routine Maintenance',
            Vehicle__c = cc.Vehicle__c,
            Equipment__c = cc.Equipment__c,
            Origin = 'Web',
            Date_Reported__c = Date.Today()

        );

        If (maintenanceCycles.containsKey(cc.Id)){
            nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
        } else {
            nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipment__r.maintenance_Cycle__c);
        }

        newCases.add(nc);
    }

    insert newCases;

    List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
    for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
            Equipment_Maintenance_Item__c wpClone = wp.clone();
            wpClone.Maintenance_Request__c = nc.Id;
            ClonedWPs.add(wpClone);

        }
    }

```

```

    }
    insert ClonedWPs;
}
}
}

```

#### MaintenanceRequest.apxt :-

```

trigger MaintenanceRequest on Case (before update, after update) {

    if (Trigger.isUpdate && Trigger.isAfter){

        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);

    }

}

```

## 2. Synchronize Salesforce data with an external system

#### WarehouseCalloutService.apxc :-

```

public with sharing class WarehouseCalloutService implements Queueable {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

    @future(callout=true)
    public static void runWarehouseEquipmentSync(){
        Http http = new Http();
        HttpRequest request = new HttpRequest();

        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);

        List<Product2> warehouseEq = new List<Product2>();

        if (response.getStatusCode() == 200){
            List<Object> jsonResponse =

```

```

(List<Object>)JSON.deserializeUntyped(response.getBody());
    System.debug(response.getBody());
}

for (Object eq : jsonResponse){
    Map<String,Object> mapJson = (Map<String,Object>)eq;
    Product2 myEq = new Product2();
    myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
    myEq.Name = (String) mapJson.get('name');
    myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
    myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
    myEq.Cost__c = (Integer) mapJson.get('cost');
    myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
    myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
    myEq.ProductCode = (String) mapJson.get('_id');
    warehouseEq.add(myEq);
}

if (warehouseEq.size() > 0){
    upsert warehouseEq;
    System.debug('Your equipment was synced with the warehouse one');
}
}
}

public static void execute (QueueableContext context){
    runWarehouseEquipmentSync();
}
}
}

```

### 3. Schedule Synchronization

WarehouseSyncShedule.apxc :-

```

global with sharing class WarehouseSyncSchedule implements Schedulable{
    global void execute(SchedulableContext ctx){
        System.enqueueJob(new WarehouseCalloutService());
    }
}

```

```
}  
}
```

#### 4. Test automation logic

MaintenanceRequestHelperTest.apxc :-

```
@istest  
public with sharing class MaintenanceRequestHelperTest {  
  
    private static final string STATUS_NEW = 'New';  
    private static final string WORKING = 'Working';  
    private static final string CLOSED = 'Closed';  
    private static final string REPAIR = 'Repair';  
    private static final string REQUEST_ORIGIN = 'Web';  
    private static final string REQUEST_TYPE = 'Routine Maintenance';  
    private static final string REQUEST_SUBJECT = 'Testing subject';  
  
    PRIVATE STATIC Vehicle__c createVehicle(){  
        Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');  
        return Vehicle;  
    }  
  
    PRIVATE STATIC Product2 createEq(){  
        product2 equipment = new product2(name = 'SuperEquipment',  
                                            lifespan_months__C = 10,  
                                            maintenance_cycle__C = 10,  
                                            replacement_part__c = true);  
        return equipment;  
    }  
  
    PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){  
        case cs = new case(Type=REPAIR,  
                            Status=STATUS_NEW,  
                            Origin=REQUEST_ORIGIN,  
                            Subject=REQUEST_SUBJECT,  
                            Equipment__c=equipmentId,  
                            Vehicle__c=vehicleId);
```

```

    return cs;
}

PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
    Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
Maintenance_Request__c = requestId);

    return wp;
}

@istest
private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;

    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;

    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;

    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();

    Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c,
Vehicle__c, Date_Due__c
                  from case
                  where status =:STATUS_NEW];

```

[illegible]

```

        where Maintenance_Request__c = :emptyReq.Id];

    }

    @istest
    private static void testMaintenanceRequestBulk(){
        list<Vehicle__C> vehicleList = new list<Vehicle__C>();
        list<Product2> equipmentList = new list<Product2>();
        list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
        list<case> requestList = new list<case>();
        list<id> oldRequestIds = new list<id>();

        for(integer i = 0; i < 300; i++){
            vehicleList.add(createVehicle());
            equipmentList.add(createEq());
        }
        insert vehicleList;
        insert equipmentList;

        for(integer i = 0; i < 300; i++){
            requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
        }
        insert requestList;

        for(integer i = 0; i < 300; i++){
            workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
        }
        insert workPartList;

        test.startTest();
        for(case req : requestList){
            req.Status = CLOSED;
            oldRequestIds.add(req.Id);
        }
        update requestList;
    }

```



```

test.stopTest();

list<case> allRequests = [select id
                        from case
                        where status =: STATUS_NEW];

list<Equipment_Maintenance_Item__c> workParts = [select id
                                                from Equipment_Maintenance_Item__c
                                                where Maintenance_Request__c in: oldRequestIds];

system.assert(allRequests.size() == 300);
}
}

```

**MaintenanceRequestHelper.apxc :-**

```

public with sharing class MaintenanceRequestHelper {
    public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }

        if (!validIds.isEmpty()){
            List<Case> newCases = new List<Case>();
            Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT

```

```

Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
        FROM Case WHERE Id IN :validIds]);
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
    AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM Equipment_Maintenance_Item__c
WHERE Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];

    for (AggregateResult ar : results){
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }

    for(Case cc : closedCasesM.values()){
        Case nc = new Case (
            ParentId = cc.Id,
            Status = 'New',
            Subject = 'Routine Maintenance',
            Type = 'Routine Maintenance',
            Vehicle__c = cc.Vehicle__c,
            Equipment__c =cc.Equipment__c,
            Origin = 'Web',
            Date_Reported__c = Date.Today()

        );

        If (maintenanceCycles.containsKey(cc.Id)){
            nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
        }

        newCases.add(nc);
    }

    insert newCases;

    List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
    for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){

```

```

        Equipment_Maintenance_Item__c wpClone = wp.clone();
        wpClone.Maintenance_Request__c = nc.Id;
        ClonedWPs.add(wpClone);

    }
}
insert ClonedWPs;
}
}
}

```

#### MaintenanceRequest.apxt :-

```

trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```

### 5. Test Callout Logic

#### WarehouseCalloutService.apxc :-

```

public with sharing class WarehouseCalloutService {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

```

```

    public static void runWarehouseEquipmentSync(){

```

```

        Http http = new Http();
        HttpRequest request = new HttpRequest();

        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);

```

```

List<Product2> warehouseEq = new List<Product2>();

if (response.getStatusCode() == 200){
    List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
    System.debug(response.getBody());

    for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost__c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
    }

    if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
    }

}
}
}

```

WarehouseCalloutServiceTest.apxc :-

@isTest

```
private class WarehouseCalloutServiceTest {
```

```

@isTest
static void testWareHouseCallout(){
    Test.startTest();

    Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
    WarehouseCalloutService.runWarehouseEquipmentSync();
    Test.stopTest();
    System.assertEquals(1, [SELECT count() FROM Product2]);
}
}

```

**WarehouseCalloutServiceMock.apxc :-**

```

@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request){

        System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
        System.assertEquals('GET', request.getMethod());

        // Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');

        response.setBody('{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5
,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}');
        response.setStatusCode(200);
        return response;
    }
}

```

## 6. [Test Scheduling Login](#)

#### WarehouseSyncSchedule.apxc :-

```
global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}
```

#### WarehouseSyncScheduleTest.apxc :-

```
@isTest
public class WarehouseSyncScheduleTest {

    @isTest static void WarehousescheduleTest(){
        String scheduleTime = '00 00 01 * * ?';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String jobID=System.schedule('Warehouse Time To Schedule to Test', scheduleTime,
new WarehouseSyncSchedule());
        Test.stopTest();
        //Contains schedule information for a scheduled job. CronTrigger is similar to a cron
job on UNIX systems.
        // This object is available in API version 17.0 and later.
        CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
        System.assertEquals(jobID, a.Id,'Schedule ');

    }
}
```

#### HERE IT STARTS WITH APEX MODULES

##### Apex Triggers

##### 1.Get Started with Apex Triggers

```
trigger AccountAddressTrigger on Account (before insert,before update) {
```

```

for(Account account : Trigger.New){
if((account.Match_Billing_Address__c == true) && (account.BillingPostalCode !=NULL)){
account.ShippingPostalCode = account.BillingPostalCode;
}
}
}

```

## 2.Bulk Apex Triggers

```

trigger ClosedOpportunityTrigger on Opportunity (after insert,after update) {
List<Task> tasklist = new List<Task>();
for(Opportunity opp : Trigger.New){
if(opp.StageName == 'Closed Won'){
taskList.add(new Task(subject ='Follow Up Test Task',WhatId = opp.Id));
}
}
if(taskList.size()>0){
insert taskList;
}
}

```

## Apex Testing

### 1.Get Started with Apex Unit Tests

```

public class VerifyDate {
public static Date CheckDates(Date date1, Date date2) {
if(DateWithin30Days(date1,date2)) {
return date2;
} else {
return SetEndOfMonthDate(date1);
}
}
private static Boolean DateWithin30Days(Date date1, Date date2) {
if( date2 < date1) { return false; }
Date date30Days = date1.addDays(30); //create a date 30 days away from date1
if( date2 >= date30Days ) { return false; }
else { return true; }
}
private static Date SetEndOfMonthDate(Date date1) {

```

```

Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
return lastDay;
}
}

```

## 2. Test Apex Triggers

```

trigger RestrictContactByName on Contact (before insert, before update) {

    //check contacts prior to insert or update for invalid data
    For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') { //invalidname is invalid
            c.AddError('The Last Name "' + c.LastName + '" is not allowed for DML');
        }
    }
}

```

## 3. Create Test Date For Apex Test

```

public class RandomContactFactory {

    public static List<Contact> generateRandomContacts(Integer num, String lastName){
        List<Contact> contactList = new List <contact>();
        for (Integer i = 1; i <= num; i++){
            Contact ct = new Contact(FirstName = 'Test'+i, LastName = lastName);
            contactList.add(ct);
        }
        return contactList;
    }
}

```

## 1. Asynchronous Apex

```

public class AccountProcessor {

    @future
    public static void countContacts(List<Id> accountIds){

        List<Account> accList = [Select Id, Number_Of_Contacts__c, (select Id from Contacts) from
        Account where Id in :accountIds];
    }
}

```



```

        For(Account acc : accList){

            acc.Number_Of_Contacts__c =acc.Contacts.size();
        }
        update accList;
    }
}

```

Test Class

@isTest

```
public class AccountProcessorTest {
```

```
    public static testmethod void testAccountProcesssor(){
```

```
        Account a = new Account();
```

```
        a.Name = 'Test Account';
```

```
        insert a;
```

```
        Contact con = new Contact();
```

```
        con.firstName = 'Binary';
```

```
        con.lastName = 'Programming';
```

```
        con.AccountId =a.Id;
```

```
        insert con;
```

```
        List<Id> accListId = new List<Id>();
```

```
        accListId.add(a.Id);
```

```
        Test.startTest();
```

```
        AccountProcessor.countContacts(accListId);
```

```
        Test.stopTest();
```

```
        Account acc =[select Number_Of_Contacts__c from Account where Id =: a.Id];
```

```
        System.assertEquals(Integer.valueOf(acc.Number_Of_Contacts__c),1);
```

```
    }
}

```

## 2. Use Batch Apex

global class LeadProcessor implements

```
Database.Batchable<sObject>, Database.Stateful {
```

```

global Integer recordsProcessed = 0;

global Database.QueryLocator start(Database.BatchableContext bc) {
    return Database.getQueryLocator('SELECT Id, LeadSource FROM Lead');
}

global void execute(Database.BatchableContext bc, List<Lead> scope){

    List<Lead> leads = new List<Lead>();
    for (Lead lead : scope) {

        lead.LeadSource = 'Dreamforce';

        recordsProcessed = recordsProcessed + 1;

    }
    update leads;
}

global void finish(Database.BatchableContext bc){
    System.debug(recordsProcessed + ' records processed. Shazam!');
}
}

```

Test Class

```

@isTest
public class LeadProcessorTest {
    @testSetup
    static void setup() {
        List<Lead> leads = new List<Lead>();
        for (Integer i=0;i<200;i++) {
            leads.add(new Lead(LastName='Lead '+i,
                Company='Lead', Status='Open - Not Contacted'));
        }
        insert leads;
    }

    static testmethod void test() {

```

```

Test.startTest();
LeadProcessor lp = new LeadProcessor();
Id batchId = Database.executeBatch(lp, 200);
Test.stopTest();

    System.assertEquals(200, [select count() from lead where LeadSource = 'Dreamforce']);
}
}

```

### 3. Control Processes With Queueable Apex

```

public class AddPrimaryContact implements Queueable{
    Contact con;
    String state;

    public AddPrimaryContact(Contact con, String state){
        this.con = con;
        this.state = state;
    }
    public void execute(QueueableContext qc){
        List<Account> lstOfAccs = [SELECT Id FROM Account WHERE BillingState = :state LIMIT
200];

        List<Contact> lstOfConts = new List<Contact>();
        for(Account acc : lstOfAccs){
            Contact conInst = con.clone(false,false,false,false);
            conInst.AccountId = acc.Id;

            lstOfConts.add(conInst);
        }

        INSERT lstOfConts;
    }
}

```

Test Class

```

@isTest
public class AddPrimaryContactTest{
    @testSetup
    static void setup(){

```

```

List<Account> lstOfAcc = new List<Account>();
for(Integer i = 1; i <= 100; i++){
    if(i <= 50)
        lstOfAcc.add(new Account(name='AC'+i, BillingState = 'NY'));
    else
        lstOfAcc.add(new Account(name='AC'+i, BillingState = 'CA'));
}

INSERT lstOfAcc;
}

static testmethod void testAddPrimaryContact(){
    Contact con = new Contact(LastName = 'TestCont');
    AddPrimaryContact addPCIns = new AddPrimaryContact(CON, 'CA');

    Test.startTest();
    System.enqueueJob(addPCIns);
    Test.stopTest();

    System.assertEquals(50, [select count() from Contact]);
}
}

```

#### 4. Schedule Jobs Using The Apex Scheduler

```

global class DailyLeadProcessor implements Schedulable{
    global void execute(SchedulableContext ctx){
        List<Lead> leads = [SELECT Id, LeadSource FROM Lead WHERE LeadSource = "];

        if(leads.size() > 0){
            List<Lead> newLeads = new List<Lead>();

            for(Lead lead : leads){
                lead.LeadSource = 'DreamForce';
                newLeads.add(lead);
            }

            update newLeads;
        }
    }
}

Test Class

```

```

global class DailyLeadProcessor implements Schedulable{
    global void execute(SchedulableContext ctx){
        List<Lead> leads = [SELECT Id, LeadSource FROM Lead WHERE LeadSource = "];

        if(leads.size() > 0){
            List<Lead> newLeads = new List<Lead>();

            for(Lead lead : leads){
                lead.LeadSource = 'DreamForce';
                newLeads.add(lead);
            }

            update newLeads;
        }
    }
}

```

## Apex Intergration Serives

### 1.Apex REST Callouts

```

global class DailyLeadProcessor implements Schedulable{
    global void execute(SchedulableContext ctx){
        List<Lead> leads = [SELECT Id, LeadSource FROM Lead WHERE LeadSource = "];

        if(leads.size() > 0){
            List<Lead> newLeads = new List<Lead>();

            for(Lead lead : leads){
                lead.LeadSource = 'DreamForce';
                newLeads.add(lead);
            }

            update newLeads;
        }
    }
}

```

Test Class

@isTest

private class AnimalLocatorTest{

@isTest static void AnimalLocatorMock1() {

Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());

```

        string result = AnimalLocator.getAnimalNameById(3);
        String expectedResult = 'chicken';
        System.assertEquals(result,expectedResult );
    }
}

```

Mock Class

@isTest

global class AnimalLocatorMock implements HttpCalloutMock {

```

    global HTTPResponse respond(HTTPRequest request) {

        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody('{ "animals": ["majestic badger", "fluffy bunny", "scary bear", "chicken",
"mighty moose"]}');
        response.setStatusCode(200);
        return response;
    }
}

```

## 2.Apex SOAP Callouts

ParkLocator2 Class

```

public class ParkLocator2 {
    public static string[] country(String country) {
        parkService.parksImplPort park = new parkService.parksImplPort();
        return park.byCountry(country);
    }
}

```

Park Service Class

```

public class ParkService {
    public class byCountryResponse {
        public String[] return_x;
        private String[] return_x_type_info = new String[]{'return','http://parks.services/',null,'0','-
1','false'};
        private String[] apex_schema_type_info = new String[]{'http://parks.services/',false,false};
        private String[] field_order_type_info = new String[]{'return_x'};
    }
    public class byCountry {
        public String arg0;
        private String[] arg0_type_info = new String[]{'arg0','http://parks.services/',null,'0','1','false'};
    }
}

```

```

    private String[] apex_schema_type_info = new String[]{'http://parks.services/', 'false', 'false'};
    private String[] field_order_type_info = new String[]{'arg0'};
}

public class ParksImplPort {
    public String endpoint_x = 'https://th-apex-soap-service.herokuapp.com/service/parks';
    public Map<String,String> inputHttpHeaders_x;
    public Map<String,String> outputHttpHeaders_x;
    public String clientCertName_x;
    public String clientCert_x;
    public String clientCertPasswd_x;
    public Integer timeout_x;
    private String[] ns_map_type_info = new String[]{'http://parks.services/', 'ParkService'};
    public String[] byCountry(String arg0) {
        ParkService.byCountry request_x = new ParkService.byCountry();
        request_x.arg0 = arg0;
        ParkService.byCountryResponse response_x;
        Map<String, ParkService.byCountryResponse> response_map_x = new Map<String,
ParkService.byCountryResponse>();
        response_map_x.put('response_x', response_x);
        WebServiceCallout.invoke(
            this,
            request_x,
            response_map_x,
            new String[]{endpoint_x,
                "",
                'http://parks.services/',
                'byCountry',
                'http://parks.services/',
                'byCountryResponse',
                'ParkService.byCountryResponse'}
        );
        response_x = response_map_x.get('response_x');
        return response_x.return_x;
    }
}
}

```

Test Class

```

@isTest
private class ParkLocatorTest2 {

```

```

@Test static void testCallout() {
    // This causes a fake response to be generated
    Test.setMock(WebServiceMock.class, new ParkServiceMock());
    // Call the method that invokes a callout
    //Double x = 1.0;
    //Double result = AwesomeCalculator.add(x, y);

    String country = 'Germany';
    String[] result = ParkLocator2.Country(country);

    // Verify that a fake result is returned
    System.assertEquals(new List<String>{'Hamburg Wadden Sea National Park', 'Hainich
National Park', 'Bavarian Forest National Park'}, result);
}
}

```

Mock class

```

@Test
global class ParkServiceMock2 implements WebServiceMock {
    global void doInvoke(
        Object stub,
        Object request,
        Map<String, Object> response,
        String endpoint,
        String soapAction,
        String requestName,
        String responseNS,
        String responseName,
        String responseType) {
        // start - specify the response you want to send
        parkService.byCountryResponse response_x = new parkService.byCountryResponse();
        response_x.return_x = new List<String>{'Hamburg Wadden Sea National Park', 'Hainich
National Park', 'Bavarian Forest National Park'};

        //calculatorServices.doAddResponse response_x = new
calculatorServices.doAddResponse();
        //response_x.return_x = 3.0;
        // end
        response.put('response_x', response_x);
    }
}

```



```
}
```

### 3.Apex Web Services

```
@RestResource(urlMapping='/Accounts/*/contacts')
global class AccountManager {
    @HttpGet
    global static Account getAccount() {
        RestRequest req = RestContext.request;
        String accId = req.requestURI.substringBetween('Accounts/', '/contacts');
        Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
                       FROM Account WHERE Id = :accId];
        return acc;
    }
}

Test Class
@isTest
private class AccountManagerTest {

    private static testMethod void getAccountTest1() {
        Id recordId = createTestRecord();

        RestRequest request = new RestRequest();
        request.requestUri = 'https://na1.salesforce.com/services/apexrest/Accounts/'+ recordId
        +'/contacts';
        request.httpMethod = 'GET';
        RestContext.request = request;

        Account thisAccount = AccountManager.getAccount();

        System.assert(thisAccount != null);
        System.assertEquals('Test record', thisAccount.Name);
    }

    static Id createTestRecord() {

        Account TestAcc = new Account(
            Name='Test record');
        insert TestAcc;
    }
}
```

```
    Contact TestCon= new Contact(  
        LastName='Test',  
        AccountId = TestAcc.id);  
    return TestAcc.Id;  
}  
}
```