

Apex Basics and Database

- AccountHandler.apxc

```
public class AccountHandler {  
    public static Account insertNewAccount(String AccountName){  
        try {  
            Account newacct = new Account(Name=AccountName);  
            insert newacct;  
            return newacct;  
        } catch (DmlException e) {  
            System.debug('A DML exception has occurred: ' +  
                e.getMessage());  
            return null;  
        }  
    }  
}
```

- ContactAndLeadSearch.apxc

```
public class ContactAndLeadSearch {  
  
    //a public static method that accepts an incoming string as a parameter  
    public static List<List<sObject>> searchContactsAndLeads (String incoming) {  
        //write a SOSQL query to search by lead or contact name fields for the incoming string.  
        List<List<sObject>> searchList = [FIND :incoming IN NAME FIELDS  
            RETURNING Contact(FirstName,LastName),Lead(FirstName,LastName)];  
        //return the list of the same kind  
        return searchList;  
    }  
}
```

- ContactSearch.apxc

```
public class ContactSearch{
    public static list<Contact> searchForContacts(string name1, string name2){
        List <Contact> con = new List<contact>();
        con = [SELECT ID,FirstName from Contact where LastName =:name1 and
MailingPostalCode=:name2];
        return con;
    }
}
```

- StringArrayTest.apxc

```
public class StringArrayTest {
    public static List<String> generateStringArray(Integer N){
        List<String> TestList = new List<String>();
        for(Integer i=0;i<N;i++){
            TestList.add("Test ' + i);
            system.debug(TestList[i]);
        }
        return TestList;
    }
}
```

Apex Integration Services

AccountManager.apxc

```
@RestResource(urlMapping='/Accounts/*/contacts')
global with sharing class AccountManager{
    @HttpGet
    global static Account getAccount(){
        RestRequest req = RestContext.request;
        String accId = req.requestURI.substringBetween('Accounts/', '/contacts');
        Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
                        FROM Account WHERE Id = :accId];

        return acc;
    }
}
```

AccountManagerTest.apxc

@IsTest

```
private class AccountManagerTest{
    @isTest static void testAccountManager(){
        Id recordId = getTestAccountId();
        // Set up a test request
        RestRequest request = new RestRequest();
        request.requestUri =
            'https://ap5.salesforce.com/services/apexrest/Accounts/'+ recordId +'/contacts';
        request.httpMethod = 'GET';
        RestContext.request = request;

        // Call the method to test
        Account acc = AccountManager.getAccount();

        // Verify results
        System.assert(acc != null);
    }

    private static Id getTestAccountId(){
        Account acc = new Account(Name = 'TestAcc2');
        Insert acc;

        Contact con = new Contact(LastName = 'TestCont2', AccountId = acc.Id);
        Insert con;

        return acc.Id;
    }
}
```

AnimalLocator.apxc

```
public class AnimalLocator
{
    public static String getAnimalNameById(Integer id)
    {
        Http http = new Http();
        HttpRequest request = new HttpRequest();
        request.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/'+id);
        request.setMethod('GET');
        HttpResponse response = http.send(request);
        String strResp = "";
        system.debug('*****response '+response.getStatusCode());
        system.debug('*****response '+response.getBody());
        // If the request is successful, parse the JSON response.
        if (response.getStatusCode() == 200)
        {
            // Deserializes the JSON string into collections of primitive data types.
            Map<String, Object> results = (Map<String, Object>)
JSON.deserializeUntyped(response.getBody());
            // Cast the values in the 'animals' key as a list
            Map<string,object> animals = (map<string,object>) results.get('animal');
            System.debug('Received the following animals:' + animals );
            strResp = string.valueOf(animals.get('name'));
            System.debug('strResp >>>>>' + strResp );
        }
        return strResp ;
    }
}
```

AnimalLocatorMock.apxc

@isTest

```
global class AnimalLocatorMock implements HttpCalloutMock {  
    // Implement this interface method  
    global HTTPResponse respond(HTTPRequest request) {  
        // Create a fake response  
        HttpResponse response = new HttpResponse();  
        response.setHeader('Content-Type', 'application/json');  
        response.setBody('{"animal":{"id":1,"name":"chicken","eats":"chicken food","says":"cluck  
cluck"}}');  
        response.setStatusCode(200);  
        return response;  
    }  
}
```

AnimalLocatorTest.apxc

@isTest

```
public class AnimalLocatorTest {  
    @isTest public static void AnimalLocatorMock() {  
        Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());  
        string result = AnimalLocator.getAnimalNameById(1);  
        system.debug(result);  
        String expectedResult = 'chicken';  
        System.assertEquals(result, expectedResult );  
    }  
}
```

AsyncParksService.apxc

```
public class AsyncParksService {
    public class byCountryResponseFuture extends System.WebServiceCalloutFuture {
        public String[] getValue() {
            parksService.byCountryResponse response =
(parksService.byCountryResponse)System.WebServiceCallout.endInvoke(this);
            return response.return_x;
        }
    }
    public class AsyncParksImplPort {
        public String endpoint_x = 'https://th-apex-soap-service.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public String clientCertName_x;
        public Integer timeout_x;
        private String[] ns_map_type_info = new String[]{'http://parks.services/', 'parksService'};
        public AsyncParksService.byCountryResponseFuture
beginByCountry(System.Continuation continuation,String arg0) {
            parksService.byCountry request_x = new parksService.byCountry();
            request_x.arg0 = arg0;
            return (AsyncParksService.byCountryResponseFuture)
System.WebServiceCallout.beginInvoke(
                this,
                request_x,
                AsyncParksService.byCountryResponseFuture.class,
                continuation,
                new String[]{endpoint_x,
                    "",
                    'http://parks.services/',
                    'byCountry',
                    'http://parks.services/',
                    'byCountryResponse',
                    'parksService.byCountryResponse'}
```

```
    );  
    }  
}  
}
```

ParkLocator.apxc

```
public class ParkLocator {  
    public static String[] country(String country){  
        ParkService.ParksImplPort parks = new ParkService.ParksImplPort();  
        String[] parksname = parks.byCountry(country);  
        return parksname;  
    }  
}
```

ParkLocatorTest.apxc

```
@isTest  
private class ParkLocatorTest{  
    @isTest  
    static void testParkLocator() {  
        Test.setMock(WebServiceMock.class, new ParkServiceMock());  
        String[] arrayOfParks = ParkLocator.country('India');  
  
        System.assertEquals('Park1', arrayOfParks[0]);  
    }  
}
```


ParkService.apxc

```
public class ParkService {
    public class byCountryResponse {
        public String[] return_x;
        private String[] return_x_type_info = new String[]{'return','http://parks.services/',null,'0','-1','false'};
        private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
        private String[] field_order_type_info = new String[]{'return_x'};
    }
    public class byCountry {
        public String arg0;
        private String[] arg0_type_info = new
String[]{'arg0','http://parks.services/',null,'0','1','false'};
        private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
        private String[] field_order_type_info = new String[]{'arg0'};
    }
    public class ParksImplPort {
        public String endpoint_x = 'https://th-apex-soap-service.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public Map<String,String> outputHttpHeaders_x;
        public String clientCertName_x;
        public String clientCert_x;
        public String clientCertPasswd_x;
        public Integer timeout_x;
        private String[] ns_map_type_info = new String[]{'http://parks.services/', 'ParkService'};
        public String[] byCountry(String arg0) {
            ParkService.byCountry request_x = new ParkService.byCountry();
            request_x.arg0 = arg0;
            ParkService.byCountryResponse response_x;
            Map<String, ParkService.byCountryResponse> response_map_x = new Map<String,
ParkService.byCountryResponse>();
            response_map_x.put('response_x', response_x);
            WebServiceCallout.invoke(
                this,
```

```
request_x,  
response_map_x,  
new String[]{endpoint_x,  
",  
'http://parks.services/',  
'byCountry',  
'http://parks.services/',  
'byCountryResponse',  
'ParkService.byCountryResponse'}  
);  
response_x = response_map_x.get('response_x');  
return response_x.return_x;  
}  
}  
}
```

ParkServiceMock.apxc

@isTest

```
global class ParkServiceMock implements WebServiceMock {  
    global void doInvoke(  
        Object stub,  
        Object request,  
        Map<String, Object> response,  
        String endpoint,  
        String soapAction,  
        String requestName,  
        String responseNS,  
        String responseName,  
        String responseType) {  
        // start - specify the response you want to send  
        ParkService.byCountryResponse response_x =  
            new ParkService.byCountryResponse();  
        List<String> myStrings = new List<String> {'Park1','Park2','Park3'};  
        response_x.return_x = myStrings;  
        // end  
        response.put('response_x', response_x);  
    }  
}
```

Apex Testing

RandomContactFactory.apxc

```
public class RandomContactFactory {  
  
    public static List<Contact> generateRandomContacts(Integer num, String lastName){  
        List<Contact> contactList = new List<Contact>();  
        for(Integer i = 1; i <= num; i++){  
            Contact ct = new Contact(FirstName = 'Test '+i, LastName = lastname);  
            contactList.add(ct);  
        }  
        return contactList;  
    }  
}
```

RestrictContactByName.apxt

```
trigger RestrictContactByName on Contact (before insert, before update) {  
  
    //check contacts prior to insert or update for invalid data  
    For (Contact c : Trigger.New) {  
        if(c.LastName == 'INVALIDNAME') {    //invalidname is invalid  
            c.AddError("The Last Name '"+c.LastName+"' is not allowed for DML");  
        }  
    }  
}
```

TestRestrictContactByName.apxc

```
@isTest
public class TestRestrictContactByName {
    @isTest static void testContact(){
        Contact ct = new Contact();
        ct.LastName = 'INVALIDNAME';
        Database.SaveResult res = Database.insert(ct, false);
        System.assertEquals("The Last Name \"INVALIDNAME\" is not allowed for DML",
res.getErrors()[0].getMessage());
    }
}
```

TestVerifyDate.apxc

```
@isTest
public class TestVerifyDate {
    @isTest static void Test_CheckDates_case1(){
        Date d = VerifyDate.CheckDates(Date.parse('01/01/2020'), Date.parse('01/03/2020'));
        System.assertEquals(Date.parse('01/03/2020'), d);
    }
    @isTest static void Test_CheckDates_case2(){
        Date d = VerifyDate.CheckDates(Date.parse('01/01/2020'), Date.parse('03/03/2020'));
        System.assertEquals(Date.parse('01/31/2020'), d);
    }
}
```

VerifyDate.apxc

```
public class VerifyDate {

    //method to handle potential checks against two dates
    public static Date CheckDates(Date date1, Date date2) {
        //if date2 is within the next 30 days of date1, use date2. Otherwise use the end of the
month
        if(DateWithin30Days(date1,date2)) {
            return date2;
        } else {
            return SetEndOfMonthDate(date1);
        }
    }

    //method to check if date2 is within the next 30 days of date1
    private static Boolean DateWithin30Days(Date date1, Date date2) {
        //check for date2 being in the past
        if( date2 < date1) { return false; }

        //check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1
        if( date2 >= date30Days ) { return false; }
        else { return true; }
    }

    //method to return the end of the month of a given date
    private static Date SetEndOfMonthDate(Date date1) {
        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
```

```
        Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);  
        return lastDay;  
    }  
  
}
```

Apex Triggers

AccountAddressTrigger.apxt

```
trigger AccountAddressTrigger on Account (before insert, before update) {
    for(Account account:Trigger.New){
        if(account.Match_Billing_Address__c == True){
            account.ShippingPostalCode = account.BillingPostalCode;
        }
    }
}
```

ClosedOpportunityTrigger.apxt

```
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {
    List<Task> tasklist = new List<Task>();

    for(Opportunity op: Trigger.New){
        if(op.StageName == 'Closed Won'){
            tasklist.add(new Task(Subject = 'Follow Up Test Task', WhatId = op.Id));
        }
    }
    if(tasklist.size() > 0){
        insert tasklist;
    }
}
```


Asynchronous Apex

AccountProcessor.apxc

```
public class AccountProcessor {

    @future
    public static void countContacts(List<Id> accountsIds){
        List<Account> accList = [Select Id, Number_Of_Contacts__c, (Select Id from Contacts)
from Account where Id in :accountsIds];

        for(Account acc: accList){
            acc.Number_Of_Contacts__c = acc.Contacts.size();
        }

        update accList;
    }
}
```

AccountProcessorTest.apxc

@isTest

public class AccountProcessorTest {

public static testmethod void testAccountProcessor(){

Account a = new Account();

a.Name = 'Test Account';

insert a;

Contact con = new Contact();

con.FirstName = 'Yash';

con.LastName = 'Kalola';

con.AccountId = a.Id;

insert con;

List<Id> accListId = new List<Id>();

accListId.add(a.Id);

Test.startTest();

AccountProcessor.countContacts(accListId);

Test.stopTest();

Account acc = [Select Number_Of_Contacts__c from Account where Id =: a.Id];

System.assertEquals(Integer.valueOf(acc.Number_Of_Contacts__c), 1);

}

}

AddPrimaryContact.apxc

```
public class AddPrimaryContact implements Queueable {
    public contact c;
    public String state;

    public AddPrimaryContact(Contact c, String state) {
        this.c = c;
        this.state = state;
    }

    public void execute(QueueableContext qc) {
        system.debug('this.c = '+this.c+' this.state = '+this.state);
        List<Account> acc_lst = new List<account>([select id, name, BillingState from account
where account.BillingState = :this.state limit 200]);
        List<contact> c_lst = new List<contact>();
        for(account a: acc_lst) {
            contact c = new contact();
            c = this.c.clone(false, false, false, false);
            c.AccountId = a.Id;
            c_lst.add(c);
        }
        insert c_lst;
    }
}
```

AddPrimaryContactTest.apxc

@IsTest

public class AddPrimaryContactTest {

 @IsTest

 public static void testing() {

 List<account> acc_lst = new List<account>();

 for (Integer i=0; i<50;i++) {

 account a = new account(name=string.valueOf(i),billingstate='NY');

 system.debug('account a = '+a);

 acc_lst.add(a);

 }

 for (Integer i=0; i<50;i++) {

 account a = new account(name=string.valueOf(50+i),billingstate='CA');

 system.debug('account a = '+a);

 acc_lst.add(a);

 }

 insert acc_lst;

 Test.startTest();

 contact c = new contact(lastname='alex');

 AddPrimaryContact apc = new AddPrimaryContact(c,'CA');

 system.debug('apc = '+apc);

 System.enqueueJob(apc);

 Test.stopTest();

 List<contact> c_lst = new List<contact>([select id from contact]);

 Integer size = c_lst.size();

 system.assertEquals(50, size);

 }

}

DailyLeadProcessor.apxc

```
global class DailyLeadProcessor implements Schedulable {
```

```
    global void execute(SchedulableContext ctx) {
```

```
        //Retrieving the 200 first leads where lead source is in blank.
```

```
        List<Lead> leads = [SELECT ID, LeadSource FROM Lead where LeadSource = " LIMIT  
200];
```

```
        //Setting the LeadSource field the 'Dreamforce' value.
```

```
        for (Lead lead : leads) {
```

```
            lead.LeadSource = 'Dreamforce';
```

```
        }
```

```
        //Updating all elements in the list.
```

```
        update leads;
```

```
    }
```

```
}
```

DailyLeadProcessorTest.apxc

@isTest

private class DailyLeadProcessorTest {

 @isTest

 public static void testDailyLeadProcessor(){

 //Creating new 200 Leads and inserting them.

 List<Lead> leads = new List<Lead>();

 for (Integer x = 0; x < 200; x++) {

 leads.add(new Lead(lastname='lead number ' + x, company='company number ' + x));

 }

 insert leads;

 //Starting test. Putting in the schedule and running the DailyLeadProcessor execute method.

 Test.startTest();

 String jobId = System.schedule('DailyLeadProcessor', '0 0 12 * * ?', new

DailyLeadProcessor());

 Test.stopTest();

 //Once the job has finished, retrieve all modified leads.

 List<Lead> listResult = [SELECT ID, LeadSource FROM Lead where LeadSource =
'Dreamforce' LIMIT 200];

 //Checking if the modified leads are the same size number that we created in the start of this
method.

 System.assertEquals(200, listResult.size());

 }

}

LeadProcessor.apxc

```
global class LeadProcessor implements Database.Batchable<sObject> {
    global Integer count = 0;

    global Database.QueryLocator start(Database.BatchableContext bc){
        return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
    }

    global void execute(Database.BatchableContext bc, List<Lead> L_list){
        List<lead> L_list_new = new List<lead>();

        for(lead L:L_list){
            L.leadsource = 'Dreamforce';
            L_list_new.add(L);
            count += 1;
        }
        update L_list_new;
    }
    global void finish(Database.BatchableContext bc){
        System.debug('count = '+count);
    }
}
```

LeadProcessorTest.apxc

```
@isTest
public class LeadProcessorTest {
    @isTest
    public static void testit(){
        List<lead> L_list = new List<lead>();

        for(Integer i=0; i<200; i++){
            Lead L = new lead();
            L.LastName = 'name' + i;
            L.Company = 'Company';
            L.Status = 'Random Status';
            L_list.add(L);
        }
        insert L_list;

        Test.startTest();
        LeadProcessor lp = new LeadProcessor();
        Id batchId = Database.executeBatch(lp);
        Test.stopTest();
    }
}
```


Superbadge Apex Specialist

Challenge 1 : Automate Record Creation

1. MaintenanceRequest.apxt

```
trigger MaintenanceRequest on Case (before update, after update) {  
    // ToDo: Call MaintenanceRequestHelper.updateWorkOrders  
    if(Trigger.isAfter)  
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New);  
}
```

MaintenanceRequestHelper.apxc

```
public with sharing class MaintenanceRequestHelper {  
    public static void updateWorkOrders(List<Case> caseList) {  
        List<case> newCases = new List<Case>();  
        Map<String,Integer> result=getDueDate(caseList);  
        for(Case c : caseList){  
            if(c.status=='closed')  
                if(c.type=='Repair' || c.type=='Routine Maintenance'){
```

```

Case newCase = new Case();
newCase.Status='New';
newCase.Origin='web';
newCase.Type='Routine Maintenance';
newCase.Subject='Routine Maintenance of Vehicle';
newCase.Vehicle__c=c.Vehicle__c;
newCase.Equipment__c=c.Equipment__c;
newCase.Date_Reported__c=Date.today();
if(result.get(c.Id)!=null)
newCase.Date_Due__c=Date.today()+result.get(c.Id);
else
newCase.Date_Due__c=Date.today();
newCases.add(newCase);
}
}
insert newCases;
}
//
public static Map<String,Integer> getDueDate(List<case> CaseIDs){
Map<String,Integer> result = new Map<String,Integer>();
Map<Id, case> caseKeys = new Map<Id, case> (CaseIDs);
List<AggregateResult> wpc=[select Maintenance_Request__r.ID
cID,min(Equipment__r.Maintenance_Cycle__c)cycle
from Work_Part__c where Maintenance_Request__r.ID in :caseKeys.keySet() group by
Maintenance_Request__r.ID ];
for(AggregateResult res :wpc){
Integer addDays=0;
if(res.get('cycle')!=null)
addDays+=Integer.valueOf(res.get('cycle'));
result.put((String)res.get('cID'),addDays);
}
return result;
}
}

```

Challenge - 2 : Synchronize Salesforce data with an external system

Anonymous Window Code:

```
WarehouseCalloutService.runWarehouseEquipmentSync();
```

WarehouseCalloutService.apxc

```
public with sharing class WarehouseCalloutService {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
    apex.herokuapp.com/equipment';
    @future(callout=true)
    public static void runWarehouseEquipmentSync() {
        //ToDo: complete this method to make the callout (using @future) to the
        //    REST endpoint and update equipment on hand.
        HttpResponse response = getResponse();
        if(response.getStatusCode() == 200)
        {
            List<Product2> results = getProductList(response); //get list of products from Http callout
            response
            if(results.size() >0)
            upsert results Warehouse_SKU__c; //Upsert the products in your org based on the external ID
            SKU
        }
    }
    //Get the product list from the external link
    public static List<Product2> getProductList(HttpResponse response)
    {
        List<Object> externalProducts = (List<Object>) JSON.deserializeUntyped(response.getBody());
        //desrialize the json response
    }
}
```

```

List<Product2> newProducts = new List<Product2>();
for(Object p : externalProducts)
{
    Map<String, Object> productMap = (Map<String, Object>) p;
    Product2 pr = new Product2();
    //Map the fields in the response to the appropriate fields in the Equipment object
    pr.Replacement_Part__c = (Boolean)productMap.get('replacement');
    pr.Cost__c = (Integer)productMap.get('cost');
    pr.Current_Inventory__c = (Integer)productMap.get('quantity');
    pr.Lifespan_Months__c = (Integer)productMap.get('lifespan') ;
    pr.Maintenance_Cycle__c = (Integer)productMap.get('maintenanceperiod');
    pr.Warehouse_SKU__c = (String)productMap.get('sku');
    pr.ProductCode = (String)productMap.get('_id');
    pr.Name = (String)productMap.get('name');
    newProducts.add(pr);
}
return newProducts;
}

// Send Http GET request and receive Http response
public static HttpResponse getResponse() {
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    return response;
}
}

```

Challenge - 3 : Schedule Synchronization

Anonymous Window Code

```
WarehouseSyncSchedule scheduleInventoryCheck();
```

WarehouseSyncSchedule.apxc

```
global class WarehouseSyncSchedule implements Schedulable{
// implement scheduled code here
global void execute (SchedulableContext sc){
WarehouseCalloutService.runWarehouseEquipmentSync();
//optional this can be done by debug mode
String sch = '00 00 01 * * ?';//on 1 pm
System.schedule('WarehouseSyncScheduleTest', sch, new WarehouseSyncSchedule());
}
}
```

Challenge - 4 : Test automation logic

InstallationTests.apxc

@IsTest

```
private class InstallationTests {
private static final String STRING_TEST = 'TEST';
private static final String NEW_STATUS = 'New';
private static final String WORKING = 'Working';
private static final String CLOSED = 'Closed';
private static final String REPAIR = 'Repair';
private static final String REQUEST_ORIGIN = 'Web';
private static final String REQUEST_TYPE = 'Routine Maintenance';
private static final String REQUEST_SUBJECT = 'AMC Spirit';
public static String CRON_EXP = '0 0 1 * * ?';
static testmethod void testMaintenanceRequestNegative() {
Vehicle__c vehicle = createVehicle();
insert vehicle;
Id vehicleId = vehicle.Id;
Product2 equipment = createEquipment();
insert equipment;
Id equipmentId = equipment.Id;
Case r = createMaintenanceRequest(vehicleId, equipmentId);
insert r;
Work_Part__c w = createWorkPart(equipmentId, r.Id);
insert w;
Test.startTest();
r.Status = WORKING;
update r;
Test.stopTest();
List<case> allRequest = [SELECT Id
FROM Case];
Work_Part__c workPart = [SELECT Id
```

```

FROM Work_Part__c
WHERE Maintenance_Request__c =: r.Id];
System.assert(workPart != null);
System.assert(allRequest.size() == 1);
}

static testmethod void testWarehouseSync() {
Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
Test.startTest();
String jobId = System.schedule('WarehouseSyncSchedule',
CRON_EXP,
new WarehouseSyncSchedule());
CronTrigger ct = [SELECT Id, CronExpression, TimesTriggered, NextFireTime
FROM CronTrigger
WHERE id = :jobId];
System.assertEquals(CRON_EXP, ct.CronExpression);
System.assertEquals(0, ct.TimesTriggered);
Test.stopTest();
}

private static Vehicle__c createVehicle() {
Vehicle__c v = new Vehicle__c(Name = STRING_TEST);
return v;
}

private static Product2 createEquipment() {
Product2 p = new Product2(Name = STRING_TEST,
Lifespan_Months__c = 10,
Maintenance_Cycle__c = 10,
Replacement_Part__c = true);
return p;
}

private static Case createMaintenanceRequest(Id vehicleId, Id equipmentId) {
Case c = new Case(Type = REPAIR,
Status = NEW_STATUS,
Origin = REQUEST_ORIGIN,
Subject = REQUEST_SUBJECT,
Equipment__c = equipmentId,
Vehicle__c = vehicleId);
return c;
}

```

```

}
private static Work_Part__c createWorkPart(Id equipmentId, Id requestId) {
Work_Part__c wp = new Work_Part__c(Equipment__c = equipmentId,
Maintenance_Request__c = requestId);
return wp;
}
}

```

MaintenanceRequest.apxt

```

trigger MaintenanceRequest on Case (before update, after update) {
if(Trigger.isUpdate && Trigger.isAfter)
MaintenanceRequestHelper.updateWorkOrders(Trigger.New);
}

```

MaintenanceRequestHelper.apxc

```

public with sharing class MaintenanceRequestHelper {
public static void updateWorkOrders(List<case> caseList) {
List<case> newCases = new List<case>();
Map<String,Integer> result=getDueDate(caseList);
for(Case c : caseList){
if(c.status=='closed')
if(c.type=='Repair' || c.type=='Routine Maintenance'){
Case newCase = new Case();
newCase.Status='New';
newCase.Origin='web';
newCase.Type='Routine Maintenance';
newCase.Subject='Routine Maintenance of Vehicle';
newCase.Vehicle__c=c.Vehicle__c;
newCase.Equipment__c=c.Equipment__c;
newCase.Date_Reported__c=Date.today();
if(result.get(c.Id)!=null)
newCase.Date_Due__c=Date.today()+result.get(c.Id);
}
}
}
}

```



```

else
newCase.Date_Due__c=Date.today();
newCases.add(newCase);
}
}
insert newCases;
}
//
public static Map<String,Integer> getDueDate(List<case> CaseIDs){
Map<String,Integer> result = new Map<String,Integer>();
Map<Id, case> caseKeys = new Map<Id, case> (CaseIDs);
List<aggregateresult> wpc=[select Maintenance_Request__r.ID
cID,min(Equipment__r.Maintenance_Cycle__c)cycle
from Work_Part__c where Maintenance_Request__r.ID in :caseKeys.keySet() group by
Maintenance_Request__r.ID ];
for(AggregateResult res :wpc){
Integer addDays=0;
if(res.get('cycle')!=null)
addDays+=Integer.valueOf(res.get('cycle'));
result.put((String)res.get('cID'),addDays);
}
return result;
}
}

```

MaintenanceRequestTest.apxc

```
@isTest
public class MaintenanceRequestTest {
    static List<case> caseList1 = new List<case>();
    static List<product2> prodList = new List<product2>();
    static List<work_part__c> wpList = new List<work_part__c>();
    @testSetup
    static void getData(){
        caseList1= CreateData( 300,3,3,'Repair');
    }
    public static List<case> CreateData( Integer numOfcase, Integer numofProd, Integer
    numofVehicle,
    String type){
        List<case> caseList = new List<case>();
        //Create Vehicle
        Vehicle__c vc = new Vehicle__c();
        vc.name='Test Vehicle';
        upsert vc;
        //Create Equiment
        for(Integer i=0;i<numofProd;i++){
            Product2 prod = new Product2();
            prod.Name='Test Product'+i;
            if(i!=0)
                prod.Maintenance_Cycle__c=i;
            prod.Replacement_Part__c=true;
            prodList.add(prod);
        }
        upsert prodlist;
        //Create Case
        for(Integer i=0;i< numOfcase;i++){
            Case newCase = new Case();
            newCase.Status='New';
            newCase.Origin='web';
            if( math.mod(i, 2) ==0)
```

```

newCase.Type='Routine Maintenance';
else
newCase.Type='Repair';
newCase.Subject='Routine Maintenance of Vehicle' +i;
newCase.Vehicle__c=vc.Id;
if(i<numofProd)
newCase.Equipment__c=prodList.get(i).ID;
else
newCase.Equipment__c=prodList.get(0).ID;
caseList.add(newCase);
}
upsert caseList;
for(Integer i=0;i<numofProd;i++){
Work_Part__c wp = new Work_Part__c();
wp.Equipment__c =prodlist.get(i).Id ;
wp.Maintenance_Request__c=caseList.get(i).id;
wplist.add(wp) ;
}
upsert wplist;
return caseList;
}

public static testmethod void testMaintenanceHelper(){
Test.startTest();
getData();
for(Case cas: caseList1)
cas.Status ='Closed';
update caseList1;
Test.stopTest();
}
}

```

Challenge - 5 : Test Callout Logic

WarehouseCalloutServiceMock.apxc

```
@isTest
public class WarehouseCalloutServiceMock implements HTTPCalloutMock {
// implement http mock callout
public HTTPResponse respond (HttpRequest request){
    HTTPResponse response = new HTTPResponse();
    response.setHeader('Content-type','application/json');
    response.setBody(['{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5,"name":"Generator 1000 kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}',{'_id":"55d66226726b611100aaf742","replacement":true,"quantity":183,"name":"Cooling Fan","maintenanceperiod":0,"lifespan":0,"cost":300,"sku":"100004"}',{'_id":"55d66226726b611100aaf743","replacement":true,"quantity":143,"name":"Fuse 20A","maintenanceperiod":0,"lifespan":0,"cost":22,"sku":"100005"}]');
    response.setStatusCode(200);
    return response;
}
}
```

WarehouseCalloutServiceTest.apxc

```
@IsTest
private class WarehouseCalloutServiceTest {
// implement your mock callout test here
@isTest
static void testWareHouseCallout(){
    Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
    WarehouseCalloutService.runWarehouseEquipmentSync();
}
}
```

Challenge - 6 : Test Scheduling Logic

WarehouseSyncScheduleTest.apxc

```
@isTest
private class WarehouseSyncScheduleTest {
    public static String CRON_EXP = '0 0 0 15 3 ? 2022';
    static testmethod void testjob(){
        MaintenanceRequestTest.CreateData( 5,2,2,'Repair');
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        String joBID= System.schedule('TestScheduleJob', CRON_EXP, new WarehouseSyncSchedule());
        // List<Case> caselist = [Select count(id) from case where case]
        Test.stopTest();
    }
}
```

WarehouseSyncSchedule.apxc :-

```
global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}
```