Apex Triggers

```
Get started with Apex Triggers:
AccountAddressTrigger.apxt:
trigger AccountAddressTrigger on Account (before insert, before update) {
  for(Account account:Trigger.New){
    if(account.Match_Billing_Address__c == True){
      account.ShippingPostalCode = account.BillingPostalCode;
    }
 }
Bulk Apex Triggers:
ClosedOpportunityTrigger.apxt:
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {
  List<Task> tasklist = new List<Task>();
  for(Opportunity opp: Trigger.New){
    if(opp.StageName == 'Closed Won'){
      tasklist.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));
    }
  }
  if(tasklist.size()>0){
    insert tasklist;
  }
Apex Testing
Get started with Apex unit tests
VerifyDate.apxc:
public class VerifyDate {
      //method to handle potential checks against two dates
       public static Date CheckDates(Date date1, Date date2) {
             //if date2 is within the next 30 days of date1, use date2. Otherwise use
the end of the month
             if(DateWithin30Days(date1,date2)) {
                    return date2;
```

```
} else {
                    return SetEndOfMonthDate(date1);
             }
      }
      //method to check if date2 is within the next 30 days of date1
      @TestVisible private static Boolean DateWithin30Days(Date date1, Date date2) {
             //check for date2 being in the past
      if( date2 < date1) { return false; }
      //check that date2 is within (>=) 30 days of date1
      Date date30Days = date1.addDays(30); //create a date 30 days away from date1
             if( date2 >= date30Days ) { return false; }
             else { return true; }
      }
      //method to return the end of the month of a given date
      @TestVisible private static Date SetEndOfMonthDate(Date date1) {
             Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
             Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
             return lastDay;
      }
TestVerifyDate.apxc:
@isTest
private class TestVerifyDate {
  @isTest static void Test_CheckDates_case1(){
    Date D = VerifyDate.CheckDates(date.parse('01/01/2022'),
date.parse('01/05/2022'));
    System.assertEquals(date.parse('01/05/2022'), D);
  }
  @isTest static void Test_CheckDates_case2(){
    Date D = VerifyDate.CheckDates(date.parse('01/01/2022'),
date.parse('05/05/2022'));
    System.assertEquals(date.parse('01/31/2022'), D);
```

```
}
  @isTest static void Test_DateWithin30Days_caes1(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2022'),
date.parse('12/30/2021'));
    System.assertEquals(false, flag);
  }
  @isTest static void Test_DateWithin30Days_caes2(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2022'),
date.parse('02/02/2021'));
    System.assertEquals(false, flag);
  }
  @isTest static void Test_DateWithin30Days_caes3(){
    Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2022'),
date.parse('01/15/2022'));
    System.assertEquals(true, flag);
}
  @isTest static void Test_SetEndOfMonthDate(){
    Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2022'));
  }
}
Test Apex Triggers
RestrictContactByName.apxt:
trigger RestrictContactByName on Contact (before insert, before update) {
      //check contacts prior to insert or update for invalid data
      For (Contact c : Trigger.New) {
             if(c.LastName == 'INVALIDNAME') {
                                                    //invalidname is invalid
                   c.AddError('The Last Name "+c.LastName+" is not allowed for
DML');
             }
TestRestrictContactByName.apxc:
```

```
@isTest
public class TestRestrictContactByName {
  @isTest static void Test_insertupdateContact(){
    Contact cnt = new Contact();
    cnt.Lastname = 'INVALIDNAME';
    Test.startTest();
    Database.SaveResult result = Database.insert(cnt, false);
    Test.stopTest();
    System.assert(!result.isSuccess());
    System.assert(result.getErrors().size()>0);
    System.assertEquals('The Last Name "INVALIDNAME" is not allowed for DML',
result.getErrors()[0].getMessage());
  }
}
Create Test data for Apex Tests
RandomContactFactory.apxc:
public class RandomContactFactory {
  public static List<Contact> generateRandomContacts(Integer nument, string
lastname){
   List<Contact> contacts = new List<Contact>();
    for(Integer i=0;i<numcnt;i++){
      Contact cnt = new Contact(FirstName = 'Test '+i, LastName = lastname);
      contacts.add(cnt);
    return contacts;
Asynchronous Apex
Use Future Methods
AccountProcessor.apxc:
public class AccountProcessor {
 @future
```

```
public static void countContacts(List<Id> accountIds){
    List<Account> accountsToUpdate = new List<Account>();
    List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from Account
Where Id in :accountIds];
    For(Account acc:accounts){
      List<Contact> contactList = acc.Contacts;
      acc.Number_Of_Contacts__c = contactList.size();
      accountsToUpdate.add(acc);
    update accountsToUpdate;
  }
AccountProcessorTest.apxc:
@IsTest
private class AccountProcessorTest {
  @lsTest
  private static void testCountContacts(){
    Account newAccount = new Account(Name='Test Account');
    insert newAccount:
    Contact newContact1 = new Contact(FirstName='John',LastName='Doe',AccountId
= newAccount.ld);
    insert newContact1;
    Contact newContact2 = new Contact(FirstName='Jane',LastName='Doe',AccountId
= newAccount.ld);
    insert newContact2;
    List<ld> accountlds = new List<ld>();
    accountIds.add(newAccount.Id);
    Test.startTest();
    accountProcessor.countContacts(accountIds);
    Test.stopTest();
```

```
}
<u>Use Batch Apex</u>
LeadProcessor.apxc:
global class LeadProcessor implements Database.Batchable<sObject> {
  global Integer count = 0;
  global Database.QueryLocator start(Database.BatchableContext bc){
    return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
    }
  global void execute (Database.BatchableContext bc, List<Lead> L_list){
    List<lead> L_list_new = new List<lead>();
    for(lead L:L_list){
      L.leadsource = 'Dreamforce';
      L_list_new.add(L);
      count += 1;
    update L_list_new;
  }
  global void finish(Database.BatchableContext bc){
    system.debug('count = ' +count);
 }
LeadProcessorTest.apxc:
@isTest
public class LeadProcessorTest {
  @isTest
  public static void testit(){
    List<lead> L_list = new List<lead>();
    for(Integer i=0; i<200; i++){
      Lead L= new lead();
      L.LastName = 'name' + i;
```

```
L.Company = 'Company';
      L.Status = 'Random Status';
      L_list.add(L);
    insert L_list;
    Test.startTest();
    LeadProcessor lp = new LeadProcessor();
    Id batchId = Database.executeBatch(lp);
    Test.stopTest();
 }
Control Processes with Queueable Apex
AddPrimaryContact.apxc:
public class AddPrimaryContact implements Queueable {
  private Contact con;
  private String state;
  public AddPrimaryContact(Contact con, String state){
    this.con = con;
    this.state = state;
  }
  public void execute(QueueableContext context){
    List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id from
contacts)
                  from Account where BillingState = :state Limit 200];
    List<Contact> primaryContacts = new List<Contact>();
    for(Account acc:accounts){
      Contact c = con.clone();
      c.AccountId = acc.Id;
      primaryContacts.add(c);
    }
    if(primaryContacts.size() > 0){
```

```
insert primaryContacts;
   }
 }
AddPrimaryContactTest.apxc
@isTest
public class AddPrimaryContactTest {
  static testmethod void testQueueable(){
    List<Account> testAccounts = new List<Account>();
    for(Integer i=0;i<50;i++){
      testAccounts.add(new Account(Name='Account '+i,BillingState='CA'));
    for(Integer j=0;j<50;j++){
      testAccounts.add(new Account(Name='Account '+j,BillingState='NY'));
    insert testAccounts;
    Contact testContact = new Contact(FirstName = 'John',LastName = 'Doe');
    AddPrimaryContact addit = new addPrimaryContact(testContact, 'CA');
    Test.startTest();
    system.enqueueJob(addit);
    Test.stopTest();
    System.assertEquals(50,[Select count() from Contact where accounted in (Select Id
from Account where BillingState='Ca')]);
 }
Schedule Jobs using Apex Scheduler
DailyLeadProcessor.apxc:
global class DailyLeadProcessor implements Schedulable{
  global void execute(SchedulableContext ctx){
    List<Lead> leads = [SELECT Id, LeadSource FROM Lead WHERE LeadSource = "];
    if(leads.size() > 0){
      List<Lead> newLeads = new List<Lead>();
```

```
for(Lead lead : leads){
        lead.LeadSource = 'DreamForce';
        newLeads.add(lead);
      }
      update newLeads;
    }
 }
DailyLeadProcessorTest.apxc:
@isTest
private class DailyLeadProcessorTest{
  //Seconds Minutes Hours Day_of_month Month Day_of_week optional_year
  public static String CRON_EXP = '0 0 0 2 6 ? 2022';
  static testmethod void testScheduledJob(){
    List<Lead> leads = new List<Lead>();
    for(Integer i = 0; i < 200; i++){
      Lead lead = new Lead(LastName = 'Test ' + i, LeadSource = ", Company = 'Test
Company ' + i, Status = 'Open - Not Contacted');
      leads.add(lead);
    }
    insert leads;
    Test.startTest();
    // Schedule the test job
    String jobId = System.schedule('Update LeadSource to DreamForce', CRON_EXP,
new DailyLeadProcessor());
    // Stopping the test will run the job synchronously
    Test.stopTest();
 }
}
```

Apex Integration Services

Apex REST Callouts

```
AnimalLocator.apxc:
public class AnimalLocator {
  public static String getAnimalNameById (Integer i) {
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/'+i);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    //If the request is successful, parse the JSON response.
    Map<String, Object> result = (Map<String,
Object>)JSON.deserializeUntyped(response.getBody());
    Map<String, Object> animal = (Map<String, Object>)result.get('animal');
    System.debug('name: '+string.valueOf(animal.get('name')));
    return string.valueOf(animal.get('name'));
 }
AnimalLocatorTest.apxc:
@isTest
private class AnimalLocatorTest {
  @isTest
  static void animalLocatorTest1(){
    Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
    String actual = AnimalLocator.getAnimalNameByld(1);
    String expected = 'moose';
    System.assertEquals(actual, expected);
 }
AnimalLocatorMock.apxc:
@isTest
global class AnimalLocatorMock implements HttpCalloutMock{
  global HttpResponse respond(HttpReguest reguest){
    HttpResponse response = new HttpResponse();
```

```
response.setHeader('contactType', 'application/json');
response.setBody('{"animal":{"id":1,"name":"moose","eats":"plants","says":"bellows"}}');
    response.setStatusCode(200);
    return response;
  }
}
Apex SOAP Callouts
ParkLocator.apxc:
public class ParkLocator {
  public static List < String > country(String country) {
     ParkService.ParksImplPort prkSvc = new ParkService.ParksImplPort();
    return prkSvc.byCountry(country);
  }
ParkService.apxc:
public class ParkService {
  public class byCountryResponse {
    public String[] return_x;
    private String[] return_x_type_info = new
String[]{'return','http://parks.services/',null,'0','-1','false'};
     private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
    private String[] field_order_type_info = new String[]{'return_x'};
  }
  public class byCountry {
    public String arg0;
    private String[] arg0_type_info = new
String[]{'arg0','http://parks.services/',null,'0','1','false'};
     private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
    private String[] field_order_type_info = new String[]{'arg0'};
  public class ParksImplPort {
    public String endpoint_x = 'https://th-apex-soap-
service.herokuapp.com/service/parks';
```

```
public Map<String,String> inputHttpHeaders_x;
    public Map<String,String> outputHttpHeaders_x;
    public String clientCertName_x;
    public String clientCert_x;
    public String clientCertPasswd_x;
    public Integer timeout_x;
    private String[] ns_map_type_info = new String[]{'http://parks.services/',
'ParkService'};
    public String[] byCountry(String arg0) {
      ParkService.byCountry request_x = new ParkService.byCountry();
      request_x.arg0 = arg0;
      ParkService.byCountryResponse response_x;
      Map<String, ParkService.byCountryResponse> response_map_x = new
Map<String, ParkService.byCountryResponse>();
      response_map_x.put('response_x', response_x);
      WebServiceCallout.invoke(
       this,
       request_x,
       response_map_x,
       new String[]{endpoint_x,
       'http://parks.services/',
       'byCountry',
       'http://parks.services/',
       'byCountryResponse',
       'ParkService.byCountryResponse'}
      );
      response_x = response_map_x.get('response_x');
      return response_x.return_x;
    }
 }
ParkLocatorTest.apxc:
@isTest
private class ParkLocatorTest {
  @isTest static void testCallout () {
```

```
Test.setMock(WebServiceMock.class, new ParkServiceMock());
    String country = 'United States';
    List<String> expectedParks = new List<String>{'Yosemite', 'Sequoia', 'Crater Lake'};
    System.assertEquals(expectedParks,ParkLocator.country(country));
  }
}
ParkServiceMock.apxc:
@isTest
global class ParkServiceMock implements WebServiceMock {
  global void doInvoke(
  Object stub,
  Object request,
  Map<String, Object> response,
  String endpoint,
  String soapAction,
  String requestName,
  String responseNS,
  String responseName,
    String responseType) {
    // start - specify the response you want to send
    parkService.byCountryResponse response_x = new
parkService.byCountryResponse();
  response_x.return_x = new List<String>{'Yosemite','Sequoia','Crater Lake'};
    response.put('response_x', response_x);
}
Apex Web Services
AccountManager.apxc:
@RestResource(urlMapping = '/Accounts/*/contacts')
global with sharing class AccountManager {
  @HttpGet
  global static Account getAccount(){
    RestRequest request = RestContext.request;
    String accountId = request.requestURI.substringBetween('Accounts/','/contacts');
```

```
Account result = [SELECT Id, Name, (Select Id, Name from Contacts) from Account
where Id=:accountId Limit 1];
    return result:
 }
AccountManagerTest.apxc:
@lsTest
private class AccountManagerTest {
  @isTest static void testGetContactsByAccountId(){
    Id recordId = createTestRecord();
    RestRequest request = new RestRequest();
    request.requestUri =
'https://yourInstance.my.salesforce.com/services/apexrest/Accounts/'+
recordId+'/contacts':
    request.httpMethod = 'GET';
    RestContext.request = request;
    Account this Account = Account Manager.get Account();
    System.assert(thisAccount != null);
    System.assertEquals('Test reord', thisAccount.Name);
  }
  static Id createTestRecord(){
    Account accountTest = new Account(
    Name= 'Test Record');
    insert accountTest;
    Contact contactTest = new Contact(
    FirstName='John'.
    LastName='Doe',
    AccountId=accountTest.Id);
    insert contactTest;
    return accountTest.ld;
 }
```

Apex Specialist

<u>Automate record creation using Apex triggers</u>

```
MaintenanceRequestHelper.apxc:
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.Id);
        }
     }
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment_c, Equipment_r.Maintenance_Cycle_c,(SELECT
Id,Equipment_c,Quantity_c FROM Equipment_Maintenance_Items_r)
                             FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment_r.Maintenance_Cycle_c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN: ValidIds GROUP
BY Maintenance_Request__c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
      for(Case cc : closedCasesM.values()){
        Case nc = new Case (
```

```
ParentId = cc.Id,
        Status = 'New',
          Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle_c = cc.Vehicle_c,
          Equipment_c =cc.Equipment_c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
        If (maintenanceCycles.containskey(cc.ld)){
          nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.ld));
        } else {
          nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipment__r.maintenance_Cycle__c);
        }
        newCases.add(nc);
      }
      insert newCases;
      List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
      for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp:
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
          Equipment_Maintenance_Item__c wpClone = wp.clone();
          wpClone.Maintenance_Request__c = nc.ld;
          ClonedWPs.add(wpClone);
        }
      insert ClonedWPs;
```

```
}
MaitenanceRequest.apxt:
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
 }
Synchronize Salesforce data with an external system using REST Callouts
WarehouseCalloutService.apxc:
public with sharing class WarehouseCalloutService implements Queueable {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
  //class that makes a REST callout to an external warehouse system to get a list of
equipment that needs to be updated.
  //The callout's JSON response returns the equipment records that you upsert in
Salesforce.
  @future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
      List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
```

```
//class maps the following fields: replacement part (always true), cost, current
inventory, lifespan, maintenance cycle, and warehouse SKU
      //warehouse SKU will be external ID for identifying which equipment records to
update within Salesforce
      for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eg;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost_c = (Integer) mapJson.get('cost');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory_c = (Double) mapJson.get('quantity');
        myEq.ProductCode = (String) mapJson.get('_id');
        warehouseEq.add(myEq);
      }
      if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
      }
    }
  }
  public static void execute (QueueableContext context){
    runWarehouseEquipmentSync();
  }
In Execute anonymous window:
System.enqueueJob(new WarehouseCalloutService());
Schedule Synchronization using Apex code:
WarehouseSyncShedule.apxc:
global with sharing class WarehouseSyncSchedule implements Schedulable{
  global void execute(SchedulableContext ctx){
    System.enqueueJob(new WarehouseCalloutService());
  }
```

```
}
<u>Test Automate logic to confirm Apex trigger side effects</u>
MaintenanceRequestHelperTest.apxc:
@istest
public with sharing class MaintenanceRequestHelperTest {
  private static final string STATUS_NEW = 'New';
  private static final string WORKING = 'Working';
  private static final string CLOSED = 'Closed';
  private static final string REPAIR = 'Repair';
  private static final string REQUEST_ORIGIN = 'Web';
  private static final string REQUEST_TYPE = 'Routine Maintenance';
  private static final string REQUEST_SUBJECT = 'Testing subject';
  PRIVATE STATIC Vehicle_c createVehicle(){
    Vehicle_c Vehicle = new Vehicle_C(name = 'SuperTruck');
    return Vehicle;
  }
  PRIVATE STATIC Product2 createEq(){
    product2 equipment = new product2(name = 'SuperEquipment',
                      lifespan_months__C = 10,
                      maintenance_cycle__C = 10,
                      replacement_part__c = true);
    return equipment;
  }
  PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
              Status=STATUS_NEW,
              Origin=REQUEST_ORIGIN,
              Subject=REQUEST_SUBJECT,
              Equipment_c=equipmentId,
              Vehicle_c=vehicleId);
    return cs;
  }
```

```
PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
    Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
                                        Maintenance_Request__c = requestId);
    return wp;
  }
  @istest
  private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id:
    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;
    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;
    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();
    Case newReq = [Select id, subject, type, Equipment_c, Date_Reported_c,
Vehicle__c, Date_Due__c
           from case
           where status =:STATUS_NEW];
    Equipment_Maintenance_Item__c workPart = [select id
```

```
from Equipment_Maintenance_Item__c where Maintenance_Request__c =:newReq.Id];
```

```
system.assert(workPart != null);
    system.assert(newReq.Subject != null);
    system.assertEquals(newReg.Type, REQUEST_TYPE);
    SYSTEM.assertEquals(newReq.Equipment_c, equipmentId);
    SYSTEM.assertEquals(newReq.Vehicle_c, vehicleId);
    SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
  }
  @istest
  private static void testMaintenanceRequestNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;
    product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
    insert emptyReq;
    Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,
emptyReq.Id);
    insert workP;
    test.startTest();
    emptyReq.Status = WORKING;
    update emptyReq;
    test.stopTest();
    list<case> allRequest = [select id
                 from casel;
    Equipment_Maintenance_Item__c workPart = [select id
```

```
from Equipment_Maintenance_Item__c
where Maintenance_Request__c = :emptyReq.Id];
```

```
system.assert(workPart != null);
    system.assert(allRequest.size() == 1);
  }
  @istest
  private static void testMaintenanceRequestBulk(){
    list<Vehicle_C> vehicleList = new list<Vehicle_C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();
    for(integer i = 0; i < 300; i++){
      vehicleList.add(createVehicle());
      equipmentList.add(createEq());
    insert vehicleList;
    insert equipmentList;
    for(integer i = 0; i < 300; i++){
      requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    }
    insert requestList;
    for(integer i = 0; i < 300; i++){
      workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
    insert workPartList;
    test.startTest();
    for(case req : requestList){
      req.Status = CLOSED;
```

```
oldRequestIds.add(req.Id);
    }
    update requestList;
    test.stopTest();
    list<case> allRequests = [select id
                 from case
                 where status =: STATUS_NEW];
    list<Equipment_Maintenance_Item__c> workParts = [select id
                              from Equipment_Maintenance_Item__c
                              where Maintenance_Request__c in: oldRequestIds];
    system.assert(allRequests.size() == 300);
  }
MaintenanceRequestHelper.apxc:-
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.Id);
    if (!validIds.isEmpty()){
```

```
List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment_c, Equipment_r.Maintenance_Cycle_c,(SELECT
Id,Equipment_c,Quantity_c FROM Equipment_Maintenance_Items_r)
                              FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment_r.Maintenance_Cycle_c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds GROUP
BY Maintenance_Request__c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance_Reguest__c'), (Decimal)
ar.get('cycle'));
    }
      for(Case cc : closedCasesM.values()){
        Case nc = new Case (
          ParentId = cc.Id,
        Status = 'New',
          Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle_c = cc.Vehicle_c,
          Equipment_c = cc.Equipment_c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
        If (maintenanceCycles.containskey(cc.ld)){
          nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.ld));
        }
        newCases.add(nc);
      }
```

```
insert newCases;
     List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
     for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
          Equipment_Maintenance_Item__c wpClone = wp.clone();
          wpClone.Maintenance_Request__c = nc.ld;
          ClonedWPs.add(wpClone);
        }
      insert ClonedWPs;
 }
MaintenanceRequest.apxt:
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
 }
<u>Test Integration logic using callout mocks:</u>
WarehouseCalloutService.apxc:
public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
  //@future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
```

```
request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
      List<Object> isonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eg;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost_c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
      }
      if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEg);
      }
    }
 }
WarehouseCalloutServiceTest.apxc:
@isTest
private class WarehouseCalloutServiceTest {
```

```
@isTest
  static void testWareHouseCallout(){
    Test.startTest();
    // implement mock callout test here
    Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
    WarehouseCalloutService.runWarehouseEquipmentSync();
    Test.stopTest();
    System.assertEquals(1, [SELECT count() FROM Product2]);
 }
WarehouseCalloutServiceMock.apxc:
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
  // implement http mock callout
  global static HttpResponse respond(HttpReguest reguest){
    System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
    System.assertEquals('GET', request.getMethod());
    // Create a fake response
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5
"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}]');
    response.setStatusCode(200);
    return response;
 }
<u>Test Scheduling logic to confirm action gets queued:</u>
WarehouseSyncSchedule.apxc:
global class WarehouseSyncSchedule implements Schedulable {
  global void execute(SchedulableContext ctx) {
    WarehouseCalloutService.runWarehouseEquipmentSync();
```

```
}
}
WarehouseSyncScheduleTest.apxc:
@isTest
public class WarehouseSyncScheduleTest {
  @isTest static void WarehousescheduleTest(){
    String scheduleTime = '00 00 01 * * ?';
    Test.startTest();
    Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
    String jobID=System.schedule('Warehouse Time To Schedule to Test',
scheduleTime, new WarehouseSyncSchedule());
    Test.stopTest();
    //Contains schedule information for a scheduled job. CronTrigger is similar to a
cron job on UNIX systems.
    // This object is available in API version 17.0 and later.
    CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
    System.assertEquals(jobID, a.ld,'Schedule ');
}
}
```