```
Apex Triggers:
https://trailhead.salesforce.com/content/learn/modules/apex_triggers?trailmix_creator
_id=trailblazerconnect&trailmix_slug=salesforce-developer-catalyst
1) Get Started with Apex Trigger
AccountAddressTrigger Code:
trigger AccountAddressTrigger on Account (before insert, before update) {
      for (Account a: Trigger.new) {
             if (a.Match_Billing_Address__c == TRUE){
                    a.ShippingPostalCode = a.BillingPostalCode;
             }
      }
}
2) Bulk Apex Triggers Unit
ClosedOpportunityTrigger Code:
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {
  List<Task> taskList = new List<Task>();
  for (Opportunity o :[SELECT Id,Name FROM Opportunity
             WHERE Id IN :Trigger.New]){
    taskList.add(new Task(Subject='Follow Up Test Task',
                WhatId=o.Id,
                Status='Not Started',
                Priority='Normal'));
  if (taskList.size() > 0){
    insert taskList;
  }
}
```

## Apex Testing:

https://trailhead.salesforce.com/content/learn/modules/apex\_testing?trailmix\_creator\_

```
id=trailblazerconnect&trailmix_slug=salesforce-developer-catalyst
1)Get Started with Apex Unit Testing
VerifyDate Code:
public class VerifyDate {
      //method to handle potential checks against two dates
       public static Date CheckDates(Date date1, Date date2) {
             //if date2 is within the next 30 days of date1, use date2. Otherwise use
the end of the month
             if(DateWithin30Days(date1,date2)) {
                    return date2;
             } else {
                    return SetEndOfMonthDate(date1);
             }
      }
      //method to check if date2 is within the next 30 days of date1
       private static Boolean DateWithin30Days(Date date1, Date date2) {
             //check for date2 being in the past
       if( date2 < date1) { return false; }
      //check that date2 is within (>=) 30 days of date1
       Date date30Days = date1.addDays(30); //create a date 30 days away from date1
             if( date2 >= date30Days ) { return false; }
             else { return true; }
      }
      //method to return the end of the month of a given date
       private static Date SetEndOfMonthDate(Date date1) {
             Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
             Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
             return lastDay;
      }
}
```

```
TestVerifyDate Code:
@isTest
private class TestVerifyDate {
  @isTest static void testCheckDates() {
    Date now = Date.today();
    Date lastOfTheMonth = Date.newInstance(now.year(), now.month(),
Date.daysInMonth(now.year(), now.month()));
    Date plus60 = Date.today().addDays(60);
             Date d1 = VerifyDate.CheckDates(now, now);
    System.assertEquals(now, d1);
    Date d2 = VerifyDate.CheckDates(now, plus60);
    System.assertEquals(lastOfTheMonth, d2);
  }
}
2) Test Apex Triggers Unit
RestrictContactByName Code:
trigger RestrictContactByName on Contact (before insert, before update) {
      //check contacts prior to insert or update for invalid data
      For (Contact c : Trigger.New) {
             if(c.LastName == 'INVALIDNAME') {
                                                    //invalidname is invalid
                   c.AddError('The Last Name "'+c.LastName+" is not allowed for
DML');
             }
      }
```

```
}
TestRestrictContactByName Code:
@isTest
private class TestRestrictContactByName {
  @isTest
  static void invalidName() {
    try {
      Contact c = new Contact(LastName='INVALIDNAME');
      insert c;
    catch (Exception e) {
                   System.assert(true);
    }
  }
}
3) Create Test Data for Apex Tests:
RandomContactFactory Code:
public class RandomContactFactory {
  public static List<Contact> generateRandomContacts(Integer num, String lastName) {
    List<Contact> contacts = new List<Contact>();
    for (Integer i = 0; i < num; i++) {
      Contact c = new Contact(FirstName=i.format(), LastName=lastName);
      contacts.add(c);
    return contacts;
```

```
Asynchronous Apex:
https://trailhead.salesforce.com/content/learn/modules/asynchronous_apex?trailmix_c
reator_id=trailblazerconnect&trailmix_slug=salesforce-developer-catalyst
1)Quiz
2)Use Future Methods
AccountProcessor Code:
public class AccountProcessor {
  @future
  public static void countContacts(List<Id> accountIds) {
    List<Account> accounts = [SELECT Id,
                     Name.
                     Number_of_Contacts__c,
                       SELECT Contact.Id
                        FROM Contacts
                  FROM Account
                  WHERE Id in :accountIds];
    for (Account a : accounts) {
      a.Number_of_Contacts__c = a.Contacts.size();
    update accounts;
}
AccountProcessorTest Code:
@isTest
```

private class AccountProcessorTest {

static TestMethod void myTest() {

for (Integer i=0; i<100; i++) {

List<Account> accounts = new List<Account>();

```
Account account = new Account();
      account.Name = 'AccountProcessorTest Account ' + i;
      accounts.add(account);
    insert accounts;
    List<Id> accountIds = new List<Id>();
    List<Contact> contacts = new List<Contact>();
    for (Account a : accounts) {
      accountIds.add(a.ld);
      for (Integer i=0; i<5; i++) {
        Contact contact = new Contact();
        contact.FirstName = 'AccountProcessor Test Contact';
        contact.LastName = String.valueOf(i);
        contact.AccountId = a.Id;
        contacts.add(contact);
      }
    insert contacts;
    Test.startTest();
    AccountProcessor.countContacts(accountIds);
    Test.stopTest();
    List<Account> results = [SELECT Id, Number_of_Contacts_c
                  FROM Account
                  WHERE Id in :accountIds];
    for (Account a : results) {
      System.AssertEquals(5, a.Number_of_Contacts__c);
    }
 }
}
3)Use Batch Apex
LeadProcessor Code:
global class LeadProcessor implements Database.Batchable<sObject>,
```

```
Database.Stateful {
  global Integer recs_processed = 0;
  global Database.QueryLocator start(Database.BatchableContext bc) {
    String sQuery = ";
    sQuery += 'SELECT Id, Name, Status,';
    sQuery += 'LeadSource';
    sQuery += 'FROM Lead ';
    sQuery += 'LIMIT 100000';
    return Database.getQueryLocator(sQuery);
 }
  global void execute(Database.BatchableContext bc, List<Lead> scope) {
    for (Lead I: scope) {
      I.LeadSource = 'Dreamforce';
      recs_processed += 1;
    }
    update scope;
  }
  global void finish(Database.BatchableContext bc) {
    AsyncApexJob job = [SELECT Id,
                   Status.
                   NumberOfErrors.
                   TotalJobItems.
                   JobltemsProcessed,
                   CreatedBy.Email
                FROM AsyncApexJob
               WHERE Id = :bc.getJobId()];
    String s = ";
    s += job.JobItemsProcessed + ' job items processed ';
    s += 'out of ' + job.TotalJobItems + ' total job items. ';
    s += job.NumberOfErrors + 'error(s) encountered. ';
    System.debug(s);
    s = recs_processed + 'record(s) processed.';
    System.debug(s);
```

```
}
LeadProcessorTest Code:
@isTest
private class LeadProcessorTest {
  @testSetup
  static void createLeads() {
    List<Lead> leads = new List<Lead>();
    for (Integer i=0; i<200; i++) {
      Lead I = new Lead();
      I.FirstName = 'Test';
      l.LastName = 'Lead';
      l.Company = 'Test Lead ' + i;
      leads.add(I);
    }
    insert leads;
  }
  static TestMethod void myTest() {
    Test.startTest();
    LeadProcessor lp = new LeadProcessor();
    Id batchId = Database.executeBatch(lp);
    Test.stopTest();
    System.assertEquals(200, [SELECT Count()
                   FROM Lead
                   WHERE Name = 'Test Lead'
                    AND LeadSource = 'Dreamforce']);
 }
4)Controp Processes with Queueable Apex
AddPrimaryContact Code:
```

```
public class AddPrimaryContact implements Queueable {
  private Contact contactObj;
  private String state_code;
  public AddPrimaryContact(Contact c, String s) {
    this.contactObj = c;
    this.state_code = s;
  }
  public void execute(QueueableContext context) {
    List<Account> accounts = [SELECT Id
                   FROM Account
                   WHERE BillingState = :this.state_code
                   LIMIT 200];
    List<Contact> contacts = new List<Contact>();
    for (Account a : accounts) {
      Contact c = this.contactObj.clone(false, false, false, false);
      c.AccountId = a.Id;
      contacts.add(c);
    }
    if (contacts.size() > 0) {
     insert contacts:
AddPrimaryContactTest Code:
@isTest
private class AddPrimaryContactTest {
  @testSetup
  static void setup() {
    List<Account> accounts = new List<Account>();
    for (Integer i=0; i<50; i++) {
      Account ny = new Account();
```

```
ny.Name = 'Test Account (NY)';
      ny.BillingState = 'NY';
      accounts.add(ny);
      Account ca = new Account();
      ca.Name = 'Test Account (CA)';
      ca.BillingState = 'CA';
      accounts.add(ca);
    insert accounts;
  }
  static TestMethod void myTest() {
    Contact contactObj = new Contact(
      FirstName = 'California',
      LastName = 'Bob'
    );
    String state_abbrev = 'CA';
    Test.startTest();
    AddPrimaryContact apc = new AddPrimaryContact(contactObj, state_abbrev);
    Id jobId = System.enqueueJob(apc);
    Test.stopTest();
    List<Account> accounts = [SELECT Id, (SELECT Contact.Name FROM
Account.Contacts) FROM Account WHERE BillingState = 'CA'];
    System.assertEquals(50, accounts.size());
    for (Account a : accounts) {
      System.assertEquals(a.Contacts.size(), 1);
    }
 }
5) Schedule Jobs Using the Apex Scheduler
DailyLeadProcessor Code:
global class DailyLeadProcessor implements Schedulable {
```

}

```
global void execute(SchedulableContext ctx) {
    List<Lead> leads = [SELECT Id,
                LeadSource
             FROM Lead
            WHERE LeadSource = " OR LeadSource = null
            LIMIT 200];
    for (Lead I: leads) {
      I.LeadSource = 'Dreamforce';
    }
    if (leads.size() > 0) {
      update leads;
    }
 }
DailyLeadProcessorTest Code:
@isTest
private class DailyLeadProcessorTest {
  @testSetup
  static void setup() {
    List<Lead> leads = new List<Lead>();
    for (Integer i=0; i<200; i++) {
      Lead I = new Lead();
      I.FirstName = 'Test';
      I.LastName = 'Lead ' + i;
      I.Company = 'Test Company ' + i;
      leads.add(I);
    insert leads;
 }
  static TestMethod void myTest() {
```

```
String jobName = 'Daily Lead Processor - Test';
    String CRON_EXP = '0 0 0 15 3 ? 2017'; // dummy cron entry
    test.startTest();
    DailyLeadProcessor dp = new DailyLeadProcessor();
    String JobId = System.schedule(jobName, CRON_EXP, dp);
    test.stopTest();
    List<Lead> results = [SELECT Id FROM Lead WHERE LeadSource = 'Dreamforce'];
    System.assertEquals(200, results.size());
 }
}
Apex Integration Services
:https://trailhead.salesforce.com/content/learn/modules/apex_integration_services?trai
lmix_creator_id=trailblazerconnect&trailmix_slug=salesforce-developer-catalyst
1)Quiz
2) Apex REST Callouts
AnimalLocator Code:
public class AnimalLocator {
 public static HttpResponse makeGetCallout {
   Http http = new Http();
   HttpRequest request = new HttpRequest();
   request.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/:id');
   request.setMethod('GET');
   HttpResponse response = http.send(request);
   // If the request is successful, parse the JSON response.
   if (response.getStatusCode() == 200) {
    // Deserialize the JSON string into collections of primitive data types.
    Map<Integer, Object> Results
```

```
}
}
AnimalLocatorTest Code:
@isTest
private class AnimalLocatorTest{
  @isTest static void AnimalLocatorMock1() {
    Test.SetMock(HttpCallOutMock.class, new AnimalLocatorMock());
    string result=AnimalLocator.getAnimalNameById(3);
    string expectedResult='chicken';
    System.assertEquals(result, expectedResult);
 }
}
AnimalLocatorMock Code:
@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
  global HTTPResponse respond(HTTPRequest request) {
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
    response.setBody('{"animal":{"id":1,"name":"chicken","eats":"chicken
food","says":"cluck cluck"}}');
    response.setStatusCode(200);
    return response;
 }
}
2) Apex SOAP Callouts
ParkService Code:
//Generated by wsdl2apex
public class ParkService {
  public class byCountryResponse {
    public String[] return_x;
    private String[] return_x_type_info = new
String[]{'return','http://parks.services/',null,'0','-1','false'};
```

```
private String apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
    private String[] field_order_type_info = new String[]{'return_x'};
  }
  public class byCountry {
    public String arg0;
    private String[] arg0_type_info = new
String[]{'arg0','http://parks.services/',null,'0','1','false'};
    private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
    private String[] field_order_type_info = new String[]{'arg0'};
  public class ParksImplPort {
    public String endpoint_x = 'https://th-apex-soap-
service.herokuapp.com/service/parks';
    public Map<String,String> inputHttpHeaders_x;
    public Map<String,String> outputHttpHeaders_x;
    public String clientCertName_x;
    public String clientCert_x;
    public String clientCertPasswd_x;
    public Integer timeout_x;
    private String[] ns_map_type_info = new String[]{'http://parks.services/',
'ParkService'};
    public String[] byCountry(String arg0) {
      ParkService.byCountry request_x = new ParkService.byCountry();
      request_x.arg0 = arg0;
      ParkService.byCountryResponse response_x;
      Map<String, ParkService.byCountryResponse> response_map_x = new
Map<String, ParkService.byCountryResponse>();
      response_map_x.put('response_x', response_x);
      WebServiceCallout.invoke(
       this,
       request_x,
       response_map_x,
       new String[[{endpoint_x,
        'http://parks.services/',
```

```
'byCountry',
       'http://parks.services/',
       'byCountryResponse',
       'ParkService.byCountryResponse'}
      );
      response_x = response_map_x.get('response_x');
      return response_x.return_x;
  }
ParkLocator Code:
public class ParkLocator {
  public static String[] country(String country){
    ParkService.ParksImplPort parks = new ParkService.ParksImplPort();
    String[] parksname = parks.byCountry(country);
    return parksname;
  }
}
ParkLocatorTest Code:
@isTest
private class ParkLocatorTest{
  @isTest
  static void testParkLocator() {
    Test.setMock(WebServiceMock.class, new ParkServiceMock());
    String[] arrayOfParks = ParkLocator.country('India');
    System.assertEquals('Park1', arrayOfParks[0]);
 }
ParkServiceMock Code:
@isTest
global class ParkServiceMock implements WebServiceMock {
```

```
global void dolnvoke(
      Object stub,
      Object request,
      Map<String, Object> response,
      String endpoint,
      String soapAction,
      String requestName,
      String responseNS,
      String responseName,
      String responseType) {
    ParkService.byCountryResponse response_x = new
ParkService.byCountryResponse();
    List<String> lstOfDummyParks = new List<String> {'Park1', Park2', Park3'};
    response_x.return_x = lstOfDummyParks;
    response.put('response_x', response_x);
  }
}
4) Apex Web Services
AccountManager Code:
@RestResource(urlMapping='/Accounts/*/contacts')
global with sharing class AccountManager {
  @HttpGet
  global static account getAccount() {
    RestRequest request = RestContext.request;
    String accountId =
request.requestURI.substring(request.requestURI.lastIndexOf('/')-18,
     request.requestURI.lastIndexOf('/'));
    List<Account> a = [select id, name, (select id, name from contacts) from account
where id = :accountId];
    List<contact> co = [select id, name from contact where account.id = :accountId];
    system.debug('** a[0] = '+ a[0]);
    return a[0];
 }
}
```

```
AccountManagerTest Code:
@lstest(SeeAllData=true)
public class AccountManagerTest {
  @lsTest
  public static void testaccountmanager() {
    RestRequest request = new RestRequest();
    request.requestUri = 'https://mannharleen-dev-
ed.my.salesforce.com/services/apexrest/Accounts/00190000016cw4tAAA/contacts';
    request.httpMethod = 'GET';
    RestContext.request = request;
             system.debug('test account result = '+ AccountManager.getAccount());
  }
}
APEX SPECIALIST SUPERBADGE:
https://trailhead.salesforce.com/content/learn/modules/apex_integration_services?trail
mix_creator_id=trailblazerconnect&trailmix_slug=salesforce-developer-catalyst
1)Quiz
2) Automate Record Creation
MaintenanceRequestHelper Code:
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.Id);
```

```
}
     }
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle_c,
Equipmentc, Equipmentr. Maintenance_Cyclec, (SELECT Id, Equipmentc, Quantityc FROM
Equipment_Maintenance_Items_r)
                              FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request_c,
MIN(Equipmentr.Maintenance_Cyclec)cycle FROM Equipment_Maintenance_Itemc
WHERE Maintenance_Requestc IN :ValidIds GROUP BY Maintenance_Request_c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }
      for(Case cc : closedCasesM.values()){
        Case nc = new Case (
          ParentId = cc.Id.
        Status = 'New',
          Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle_c = cc.Vehicle_c,
          Equipment_c = cc. Equipment_c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
        If (maintenanceCycles.containskey(cc.ld)){
          nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.ld));
        }
```

```
newCases.add(nc);
      }
     insert newCases;
     List<Equipment_Maintenance_Item_c> clonedWPs = new
List<Equipment_Maintenance_Item_c>();
     for (Case nc : newCases){
        for (Equipment_Maintenance_Item_c wp:
closedCasesM.get(nc.Parentld).Equipment_Maintenance_Items_r){
          Equipment_Maintenance_Item__c wpClone = wp.clone();
          wpClone.Maintenance_Request__c = nc.ld;
          ClonedWPs.add(wpClone);
        }
      insert ClonedWPs;
MaitenanceRequest Code:
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
 }
}
```

3) Synchronize Salesforce Data

```
WarehouseCalloutService Code:
public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
  //@future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
      List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost_c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory_c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
      }
```

```
if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
      }
    }
4) Schedule Synchronization
WarehouseSyncSchedule Code:
global class WarehouseSyncSchedule implements Schedulable {
  global void execute(SchedulableContext ctx) {
    WarehouseCalloutService.runWarehouseEquipmentSync();
 }
5)Test Automatic Logic
MaintenanceRequestHelperTest Code:
@istest
public with sharing class MaintenanceRequestHelperTest {
  private static final string STATUS_NEW = 'New';
  private static final string WORKING = 'Working';
  private static final string CLOSED = 'Closed';
  private static final string REPAIR = 'Repair';
  private static final string REQUEST_ORIGIN = 'Web';
  private static final string REQUEST_TYPE = 'Routine Maintenance';
  private static final string REQUEST_SUBJECT = 'Testing subject';
  PRIVATE STATIC Vehicle_c createVehicle(){
    Vehicle_c Vehicle = new Vehicle_C(name = 'SuperTruck');
```

```
return Vehicle;
 }
  PRIVATE STATIC Product2 createEq(){
    product2 equipment = new product2(name = 'SuperEquipment',
                     lifespan_months__C = 10,
                     maintenance_cycle__C = 10,
                     replacement_part__c = true);
    return equipment;
 }
  PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
             Status=STATUS_NEW,
             Origin=REQUEST_ORIGIN,
             Subject=REQUEST_SUBJECT,
             Equipment_c=equipmentId,
             Vehicle_c=vehicleId);
    return cs;
  }
  PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
    Equipment_Maintenance_Item_c wp = new
Equipment_Maintenance_Itemc(Equipment_c = equipmentId,
                                       Maintenance_Request__c = requestId);
    return wp;
 }
MaintenanceRequestHelper Code:
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
```

```
if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.Id);
        }
     }
    }
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle_c,
Equipmentc, Equipmentr. Maintenance_Cyclec, (SELECT Id, Equipmentc, Quantityc FROM
Equipment_Maintenance_Items_r)
                              FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request_c,
MIN(Equipmentr.Maintenance_Cyclec)cycle FROM Equipment_Maintenance_Itemc
WHERE Maintenance_Requestc IN :ValidIds GROUP BY Maintenance_Request_c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }
      for(Case cc : closedCasesM.values()){
        Case nc = new Case (
          ParentId = cc.Id,
        Status = 'New',
          Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle_c = cc.Vehicle_c,
          Equipment_c = cc. Equipment_c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
```

```
If (maintenanceCycles.containskey(cc.ld)){
          nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.ld));
        newCases.add(nc);
      }
     insert newCases;
     List<Equipment_Maintenance_Item_c> clonedWPs = new
List<Equipment_Maintenance_Item_c>();
     for (Case nc : newCases){
        for (Equipment_Maintenance_Item_c wp:
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items_r){
          Equipment_Maintenance_Item__c wpClone = wp.clone();
          wpClone.Maintenance_Request__c = nc.ld;
          ClonedWPs.add(wpClone);
        }
      insert ClonedWPs;
MaintenanceRequest Code:
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
}
6) Test Callout Logic
WarehouseCalloutService Code:
```

```
public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
  //@future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
      List<Object> isonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost_c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory_c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
      }
      if (warehouseEq.size() > 0){
        upsert warehouseEg;
```

```
System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
      }
    }
}
WarehouseCalloutServiceTest Code:
@isTest
private class WarehouseCalloutServiceTest {
  @isTest
  static void testWareHouseCallout(){
    Test.startTest();
    // implement mock callout test here
    Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
    WarehouseCalloutService.runWarehouseEquipmentSync();
    Test.stopTest();
    System.assertEquals(1, [SELECT count() FROM Product2]);
 }
}
WarehouseCalloutServiceMock Code:
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
  // implement http mock callout
  global static HttpResponse respond(HttpRequest request){
    System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
    System.assertEquals('GET', request.getMethod());
    // Create a fake response
    HttpResponse response = new HttpResponse();
    response.setHeader('Content-Type', 'application/json');
```

```
response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5
,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}]');
    response.setStatusCode(200);
    return response;
}
7) Test Scheduling Logic
WarehouseSyncSchedule Code:
global class WarehouseSyncSchedule implements Schedulable {
  global void execute(SchedulableContext ctx) {
    WarehouseCalloutService.runWarehouseEquipmentSync();
 }
}
WarehouseSyncScheduleTest Code:
@isTest
public class WarehouseSyncScheduleTest {
  @isTest static void WarehousescheduleTest(){
    String scheduleTime = '00 00 01 * * ?';
    Test.startTest();
    Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
    String jobID=System.schedule('Warehouse Time To Schedule to Test',
scheduleTime, new WarehouseSyncSchedule());
    Test.stopTest();
    //Contains schedule information for a scheduled job. CronTrigger is similar to a
cron job on UNIX systems.
    // This object is available in API version 17.0 and later.
    CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
    System.assertEquals(jobID, a.Id,'Schedule');
```

}