```
Apex Triggers :
https://trailhead.salesforce.com/content/learn/modules/apex_triggers?t
railmix_creator_id=trailblazerconnect&trailmix_slug=salesforce-
developer-catalyst
1) Get Started with Apex Trigger
AccountAddressTrigger Code:
trigger AccountAddressTrigger on Account (before insert, before update) {
  for(Account account:Trigger.New){
    if(account.Match_Billing_Address__c == True){
     account.ShippingPostalCode = account.BillingPostalCode;
   }
 }
}
2) Bulk Apex Triggers Unit
ClosedOpportunityTrigger Code:
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {
  List<Task> tasklist = new List<Task>();
  for(Opportunity opp: Trigger.New){
    if(opp.StageName == 'Closed Won'){
      tasklist.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));
    }
  }
  if(tasklist.size()>0){
   insert tasklist;
  }
}
Apex Testing:
https://trailhead.salesforce.com/content/learn/modules/apex_testing?trailmix_creator_id=trail
```

```
blazerconnect&trailmix_slug=salesforce-developer-catalyst
1)Get Started with Apex Unit Testing
VerifyDate Code:
public class VerifyDate {
        //method to handle potential checks against two dates
        public static Date CheckDates(Date date1, Date date2) {
                 //if date2 is within the next 30 days of date1, use date2. Otherwise use the
end of the month
                 if(DateWithin30Days(date1,date2)) {
                          return date2;
                 } else {
                          return SetEndOfMonthDate(date1);
                 }
        }
        //method to check if date2 is within the next 30 days of date1
         @TestVisible private static Boolean DateWithin30Days(Date date1, Date date2) {
                 //check for date2 being in the past
        if( date2 < date1) { return false; }</pre>
        //check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1
                 if( date2 >= date30Days ) { return false; }
                 else { return true; }
        }
        //method to return the end of the month of a given date
         @TestVisible private static Date SetEndOfMonthDate(Date date1) {
                 Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
                 Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
                 return lastDay;
        }
```

```
}
TestVerifyDate Code:
@isTest
private class TestVerifyDate {
  @isTest static void Test_CheckDates_case1(){
    Date D = VerifyDate.CheckDates(date.parse('01/01/2020'),date.parse('01/05/2020'));
    System.assertEquals(date.parse('01/05/2020'), D);
 }
   @isTest static void Test CheckDates case2(){
    Date D = VerifyDate.CheckDates(date.parse('01/01/2020'),date.parse('05/05/2020'));
    System.assertEquals(date.parse('01/31/2020'), D);
  }
    @isTest static void Test_DateWithin30Days_case1(){
      Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('12/30/2019'));
       System.assertEquals(false, flag);
     }
       @isTest static void Test_DateWithin30Days_case2(){
      Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('02/02/2020'));
       System.assertEquals(false, flag);
     }
      @isTest static void Test_DateWithin30Days_case3(){
      Boolean flag = VerifyDate.DateWithin30Days(date.parse('01/01/2020'),
date.parse('01/15/2020'));
       System.assertEquals(true, flag);
     }
       @isTest Static void Test_SetEndOfMonthDate(){
```

```
Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2020'));
               }
       }
2) Test Apex Triggers Unit
RestrictContactByName Code:
trigger RestrictContactByName on Contact (before insert, before update) {
        //check contacts prior to insert or update for invalid data
        For (Contact c : Trigger.New) {
                if(c.LastName == 'INVALIDNAME') {  //invalidname is invalid
                         c.AddError('The Last Name "'+c.LastName+'" is not allowed
for DML');
                }
        }
}
TestRestrictContactByName Code:
@isTest
public class TestRestrictContactByName {
  @isTest static void Test_insertupdatecontact(){
    Contact cnt = new Contact();
    cnt.LastName = 'INVALIDNAME';
    Test.startTest();
    Database.SaveResult result = Database.insert(cnt,false);
    Test.stopTest();
```

```
system.assert(!result.isSuccess());
    system.assert(result.getErrors().size() > 0);
    system.assertEquals('The Last Name "INVALIDNAME"is not allowed for
DML',result.getErrors()[0].getMessage());
}
3) Create Test Data for Apex Tests:
RandomContactFactory Code:
public class RandomContactFactory {
  public static List<Contact> generateRandomContacts(Integer nument, string lastname){
    List<Contact> contact=new list<Contact>();
    for(Integer i=0;i<numcnt;i++){</pre>
       Contact cnt = new Contact(FirstName = 'Test '+i, Lastname = lastname);
       contact.add(cnt);
    }
    return contact;
 }
}
Asynchronous Apex
:https://trailhead.salesforce.com/content/learn/modules/asynchronous_apex?trailmix_creator_id=trailb
lazerconnect&trailmix_slug=salesforce-developer-catalyst
1)Quiz
2)Use Future Methods
AccountProcessor Code:
public class AccountProcessor {
```

```
@future
  public static void countContacts(List<Id> accountIds){
    List<Account> accountsToUpdate = new List<Account>();
    List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from Account
Where Id in :accountIds];
    For(Account acc:accounts){
      List<Contact> contactList = acc.Contacts;
      acc.Number_Of_Contacts__c = contactList.size();
      accountsToUpdate.add(acc);
    }
    update accountsToUpdate;
 }
}
AccountProcessorTest Code:
@IsTest
private class AccountProcessorTest {
  @IsTest
  private static void testCountContacts(){
    Account newAccount = new Account(Name='Test Account');
    insert newAccount;
    Contact newContact1 = new Contact(FirstName='John',LastName='Doe',AccountId =
newAccount.Id);
    insert newContact1;
    Contact newContact2 = new Contact(FirstName='Jane',LastName='Doe',AccountId =
newAccount.Id);
    insert newContact2;
```

```
List<Id> accountIds = new List<Id>();
    accountIds.add(newAccount.Id);
    Test.startTest();
    AccountProcessor.countContacts(accountIds);
    Test.stopTest();
  }
}
3)Use Batch Apex
LeadProcessor Code:
global class LeadProcessor implements Database.Batchable<sObject> {
  global Integer count = 0;
  global Database.QueryLocator start(Database.BatchableContext bc){
    return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
  }
  global void execute (Database.BatchableContext bc, List<Lead> L_list){
    List<lead> L_list_new = new List<lead>();
    for(lead L:L_list){
      L.leadsource ='Dreamforce';
      L_list_new.add(L);
      count += 1;
    }
    update L_list_new;
  }
  global void finish(Database.BatchableContext bc){
    system.debug('count =' + count);
  }
```

```
}
LeadProcessorTest Code:
@isTest
public class LeadProcessorTest {
  @isTest
  public static void testit(){
    List<lead> L_list = new List<lead>();
    for(Integer i=0; i<200; i++){
       Lead L = new lead();
      L.LastName ='name' + i;
      L.Company = 'Company';
      L.Status = 'Random Status';
      L_list.add(L);
    }
    insert L_list;
    Test.startTest();
    LeadProcessor lp = new LeadProcessor();
    Id batchId = Database.executeBatch(lp);
    Test.stopTest();
  }
}
4)Controp Processes with Queueable Apex
AddPrimaryContact Code:
public class AddPrimaryContact implements Queueable{
  private Contact con;
  private string state;
```

```
public AddPrimaryContact(Contact con, String state){
    this.con = con;
    this.state = state;
  }
  public void execute(QueueableContext context){
    List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id from
contacts)
                  from Account where BillingState = :state Limit 200];
    List<Contact> primaryContacts = new List<Contact>();
    for(Account acc:accounts){
      Contact c = con.clone();
      c.AccountId = acc.Id;
      primaryContacts.add(c);
    }
    if(primaryContacts.size() > 0){
      insert primaryContacts;
    }
  }
}
AddPrimaryContactTest Code:
@isTest
public class AddPrimaryContactTest {
  static testmethod void testQueueable(){
    List<Account> testAccounts = new List<Account>();
    for(Integer i=0;i<50;i++){
      testAccounts.add(new Account(Name='Account '+i,BillingState='CA'));
    }
```

```
for(Integer j=0; j<50; j++){
      testAccounts.add(new Account(Name='Account '+j,BillingState='NY'));
    }
    insert testAccounts;
    Contact testContact = new Contact(FirstName = 'John', LastName = 'Doe');
    insert testContact;
    AddPrimaryContact addit = new addPrimaryContact(testContact, 'CA');
    Test.startTest();
    system.enqueueJob(addit);
    Test.stopTest();
    System.assertEquals(50,[Select count() from Contact where accountId in (Select Id
from Account where BillingState='CA')]);
  }
}
5) Schedule Jobs Using the Apex Scheduler
DailyLeadProcessor Code:
public without sharing class DailyLeadProcessor implements schedulable{
  public void execute(SchedulableContext ctx)
    List<lead> leads=[SELECT Id,LeadSource FROM Lead WHERE Leadsource = null
LIMIT 200];
    for(Lead l: leads)
      l.LeadSource='Dreamforce';
    update leads;
 }
}
```

```
DailyLeadProcessorTest Code:
@isTest
public class DailyLeadProcessorTest{
  private static String CRON EXP='0 0 0 ? * * *';
  @isTest
  private static void testschedulabelClass(){
    List<Lead> leads=new List<Lead>();
    for(Integer i=0;i<500;i++){
      if(i<250){
        leads.add(new Lead(LastName='connock',Company='Salesforce'));
      }
      else{
        leads.add(new
Lead(LastName='Connock',Company='Salesforce',LeadSource='Other'));
      }
    insert leads:
    Test.startTest();
    String jobId=System.schedule('Process Leads', CRON_EXP, new
DailyLeadProcessor());
    Test.stopTest();
    List<lead> updatedLeads=[select Id,LeadSource from Lead where
LeadSource='Dreamforce'];
    System.assertEquals(200,updatedLeads.size(), 'ERROR: at least 1 record not updated
correctly');
    List<CronTrigger> cts=[select Id, TimesTriggered ,NextFireTime from CronTrigger
where Id=:jobId];
    System.debug('Next Fire Time '+cts[0].NextFireTime);
 }
}
```

```
Apex Integration Services
:https://trailhead.salesforce.com/content/learn/modules/apex_integration_services?trailmix_cr
eator_id=trailblazerconnect&trailmix_slug=salesforce-developer-catalyst
1)Quiz
2)Apex REST Callouts
AnimalLocator Code:
public class AnimalLocator {
 public class AnimalLocator {
  public static String getAnimalNameById (Integer i) {
   Http http = new Http();
   HttpRequest request = new HttpRequest();
   request.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/'+i);
   request.setMethod('GET');
   HttpResponse response = http.send(request);
   // If the request is successful, parse the JSON response.
   Map<String, Object> result = (Map<String,
Object>)JSON.deserializeUntyped(response.getBody());
   Map<String, Object> animal = (Map<String, Object>)result.get('animal');
   System.debug('name: '+string.valueOf(animal.get('name')));
   return string.valueOf(animal.get('name'));
}
AnimalLocatorTest Code:
@isTest
private class AnimalLocatorTest {
```

```
@isTest
  static void animalLocatorTest() {
    Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
    String actual = AnimalLocator.getAnimalNameById(1);
    String expected = 'moose';
    System.assertEquals(actual, expected);
 }
}
AnimalLocatorMock Code:
@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
  global HttpResponse respond(HttpRequest request) {
    HttpResponse response = new HttpResponse();
    response.setHeader('ContentType', 'application/json');
    response.setBody('{"animal":{"id":1,"name":"moose","eats":"plants","says":"bellows"}}');
    response.setStatusCode(200);
    return response;
      }
}
```

2)Apex SOAP Callouts

ParkService Code:

```
//Generated by wsdl2apex
public class ParkService {
  public class byCountryResponse {
     public String[] return_x;
     private String[] return_x_type_info = new String[]{'return','http://parks.services/',null,'0','-
1','false'};
     private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
     private String[] field_order_type_info = new String[]{'return_x'};
  }
  public class byCountry {
     public String arg0;
     private String[] arg0_type_info = new
String[]{'arg0','http://parks.services/',null,'0','1','false'};
     private String[] apex_schema_type_info = new
String[]{'http://parks.services/','false','false'};
     private String[] field_order_type_info = new String[]{'arg0'};
  }
  public class ParksImplPort {
     public String endpoint_x = 'https://th-apex-soap-service.herokuapp.com/service/parks';
     public Map<String,String> inputHttpHeaders_x;
```

```
public Map<String,String> outputHttpHeaders_x;
    public String clientCertName_x;
    public String clientCert_x;
    public String clientCertPasswd_x;
    public Integer timeout_x;
    private String[] ns_map_type_info = new String[]{'http://parks.services/', 'ParkService'};
    public String[] byCountry(String arg0) {
       ParkService.byCountry request_x = new ParkService.byCountry();
       request_x.arg0 = arg0;
       ParkService.byCountryResponse response_x;
       Map<String, ParkService.byCountryResponse> response_map_x = new Map<String,
ParkService.byCountryResponse>();
       response_map_x.put('response_x', response_x);
       WebServiceCallout.invoke(
        this,
        request_x,
        response_map_x,
        new String[]{endpoint_x,
        'http://parks.services/',
        'byCountry',
        'http://parks.services/',
```

```
'byCountryResponse',
      'ParkService.byCountryResponse'}
     );
     response_x = response_map_x.get('response_x');
     return response_x.return_x;
   }
  }
}
ParkLocator Code :
public class ParkLocator {
    public static String[] country(String country){
         ParkService.ParksImplPort parks = new
ParkService.ParksImplPort();
         String[] parksname = parks.byCountry(country);
         return parksname;
    }
}
ParkLocatorTest Code :
```

```
@isTest
private class ParkLocatorTest {
   @IsTest static void testCallOut(){
        Test.setMock(WebServiceMock.class, new
ParkServiceMock());
        String country = 'United States';
       List<String> expectedPark = new List<String>{'Yosemite',
'Sequoia', 'Crater Lake'};
            System.assertEquals(new
List<String>{'Me', 'You', 'Him'}, ParkLocator.country(country));
    }
}
ParkServiceMock Code:
@isTest
global class ParkServiceMock implements WebServiceMock {
   global void doInvoke(
           Object stub,
           Object request,
           Map<String, Object> response,
           String endpoint,
           String soapAction,
           String requestName,
           String responseNS,
```

```
String responseName,
           String responseType) {
              ParkService.byCountryResponse response_x = new
ParkService.byCountryResponse();
                response_x.return_x = new
List<String>{'Me','You','Him'};
             response.put('response_x', response_x);
   }
}
4) Apex Web Services
AccountManager Code :
@RestResource(urlMapping='/Accounts/*/contacts')
global with sharing class AccountManager{
    @HttpGet
    global static Account getAccount(){
       RestRequest req = RestContext.request;
       String accId = req.requestURI.substringBetween('Accounts/',
'/contacts');
       Account acc = [SELECT Id, Name, (SELECT Id, Name FROM
Contacts)
                      FROM Account WHERE Id = :accId];
```

return acc;

```
}
}
AccountManagerTest Code :
@IsTest
private class AccountManagerTest{
  @isTest static void testAccountManager(){
    Id recordId = getTestAccountId();
    // Set up a test request
    RestRequest request = new RestRequest();
    request.requestUri =
       'https://ap5.salesforce.com/services/apexrest/Accounts/'+ recordId +'/contacts';
    request.httpMethod = 'GET';
    RestContext.request = request;
    // Call the method to test
    Account acc = AccountManager.getAccount();
    // Verify results
    System.assert(acc != null);
  }
  private static Id getTestAccountId(){
    Account acc = new Account(Name = 'TestAcc2');
```

```
Insert acc;
     Contact con = new Contact(LastName = 'TestCont2', AccountId = acc.Id);
     Insert con;
     return acc.Id;
  }
}
APEX SPECIALIST SUPERBADGE:
https://trailhead.salesforce.com/content/learn/modules/apex_integration_services?trailmix_creator_id=
trailblazer connect \& trailmix\_slug = sales force-developer-catalyst
1)Quiz
2) Automate Record Creation
MaintenanceRequestHelper Code :
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case> nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.Id);
```

```
}
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c, Equipment__c,
Equipment_r.Maintenance_Cycle_c,(SELECT Id,Equipment_c,Quantity_c FROM
Equipment_Maintenance_Items__r)
                                FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment_r.Maintenance_Cycle_c)cycle FROM Equipment_Maintenance_Item_c WHERE
Maintenance_Request__c IN :ValidIds GROUP BY Maintenance_Request__c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));
      for(Case cc : closedCasesM.values()){
        Case nc = new Case (
           ParentId = cc.Id,
         Status = 'New',
           Subject = 'Routine Maintenance',
           Type = 'Routine Maintenance',
           Vehicle__c = cc.Vehicle__c,
           Equipment__c =cc.Equipment__c,
           Origin = 'Web',
           Date\_Reported\__c = Date.Today()
        );
```

```
If (maintenanceCycles.containskey(cc.Id)){
           nc.Date_Due__c = Date.today().addDays((Integer) maintenanceCycles.get(cc.Id));
         }
         newCases.add(nc);
      insert newCases;
      List<Equipment_Maintenance_Item__c> clonedWPs = new List<Equipment_Maintenance_Item__c>();
      for (Case nc : newCases){
         for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
           Equipment_Maintenance_Item__c wpClone = wp.clone();
           wpClone.Maintenance_Request__c = nc.Id;
           ClonedWPs.add(wpClone);
         }
      insert ClonedWPs;
  }
```

MaitenanceRequest Code :

trigger MaintenanceRequest on Case (before update, after update) {

```
if(Trigger.isUpdate && Trigger.isAfter){
   MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
 }
}
3) Synchronize Salesforce Data
WarehouseCalloutService Code :
public with sharing class WarehouseCalloutService {
    private static final String WAREHOUSE URL = 'https://th-
superbadge-apex.herokuapp.com/equipment';
    //@future(callout=true)
    public static void runWarehouseEquipmentSync() {
        Http http = new Http();
        HttpRequest request = new HttpRequest();
        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);
        List<Product2> warehouseEq = new List<Product2>();
        if (response.getStatusCode() == 200) {
            List<Object> jsonResponse =
(List<Object>) JSON.deserializeUntyped(response.getBody());
            System.debug(response.getBody());
            for (Object eq : jsonResponse) {
                Map<String,Object> mapJson =
(Map<String, Object>) eq;
                Product2 myEq = new Product2();
                myEq.Replacement_Part__c = (Boolean)
```

```
mapJson.get('replacement');
                myEq.Name = (String) mapJson.get('name');
                myEq.Maintenance_Cycle__c = (Integer)
mapJson.get('maintenanceperiod');
                myEq.Lifespan\_Months\_c = (Integer)
mapJson.get('lifespan');
                myEq.Cost\_c = (Decimal)
mapJson.get('lifespan');
                myEq.Warehouse_SKU__c = (String)
mapJson.get('sku');
                myEq.Current_Inventory__c = (Double)
mapJson.get('quantity');
                warehouseEq.add(myEq);
            }
            if (warehouseEq.size() > 0) {
                upsert warehouseEq;
                System.debug('Your equipment was synced with the
warehouse one');
                System.debug(warehouseEq);
            }
        }
    }
}
4) Schedule Synchronization
WarehouseSyncSchedule Code :
global class WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {
        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}
```

```
5) Test Automatic Logic
MaintenanceRequestHelperTest Code :
@istest
public with sharing class MaintenanceRequestHelperTest {
  private static final string STATUS_NEW = 'New';
  private static final string WORKING = 'Working';
  private static final string CLOSED = 'Closed';
  private static final string REPAIR = 'Repair';
  private static final string REQUEST_ORIGIN = 'Web';
  private static final string REQUEST_TYPE = 'Routine Maintenance';
  private static final string REQUEST SUBJECT = 'Testing subject';
  PRIVATE STATIC Vehicle_c createVehicle(){
    Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');
    return Vehicle;
  }
  PRIVATE STATIC Product2 createEq(){
    product2 equipment = new product2(name = 'SuperEquipment',
                     lifespan months C = 10,
                     maintenance_cycle__C = 10,
                     replacement_part__c = true);
    return equipment;
  }
  PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
             Status=STATUS NEW,
             Origin=REQUEST_ORIGIN,
             Subject=REQUEST_SUBJECT,
             Equipment_c=equipmentId,
             Vehicle__c=vehicleId);
    return cs;
  }
```

```
PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id
equipmentId,id requestId){
    Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
                                         Maintenance_Request__c = requestId);
    return wp;
  }
  @istest
  private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;
    Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;
    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;
    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();
    Case newReq = [Select id, subject, type, Equipment_c, Date_Reported_c,
Vehicle_c, Date_Due_c
           from case
            where status =: STATUS NEW];
```

```
Equipment_Maintenance_Item_c workPart = [select id
                          from Equipment_Maintenance_Item__c
                          where Maintenance_Request__c =:newReq.Id];
    system.assert(workPart != null);
    system.assert(newReq.Subject != null);
    system.assertEquals(newReq.Type, REQUEST TYPE);
    SYSTEM.assertEquals(newReq.Equipment_c, equipmentId);
    SYSTEM.assertEquals(newReq.Vehicle_c, vehicleId);
    SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
  }
  @istest
  private static void testMaintenanceRequestNegative(){
    Vehicle C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;
    product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
    insert emptyReq;
    Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,
emptyReq.Id);
    insert workP;
    test.startTest();
    emptyReq.Status = WORKING;
    update emptyReq;
    test.stopTest();
    list<case> allRequest = [select id
                  from case];
```

```
Equipment_Maintenance_Item_c workPart = [select id
                            from Equipment_Maintenance_Item__c
                             where Maintenance_Request__c = :emptyReq.Id];
    system.assert(workPart != null);
    system.assert(allRequest.size() == 1);
  }
  @istest
  private static void testMaintenanceRequestBulk(){
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment Maintenance Item c>();
    list<case> requestList = new list<case>();
    list<id> oldRequestIds = new list<id>();
    for(integer i = 0; i < 300; i++){
      vehicleList.add(createVehicle());
      equipmentList.add(createEq());
    }
    insert vehicleList;
    insert equipmentList;
    for(integer i = 0; i < 300; i++){
      requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    insert requestList;
    for(integer i = 0; i < 300; i++){
      workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
    }
    insert workPartList;
    test.startTest();
    for(case req : requestList){
```

```
req.Status = CLOSED;
      oldRequestIds.add(req.Id);
    }
    update requestList;
    test.stopTest();
    list<case> allRequests = [select id
                  from case
                  where status =: STATUS_NEW];
    list<Equipment_Maintenance_Item__c> workParts = [select id
                               from Equipment_Maintenance_Item__c
                               where Maintenance_Request_c in: oldRequestIds];
    system.assert(allRequests.size() == 300);
 }
}
MaintenanceRequest Code:
trigger MaintenanceRequest on Case (before update, after update) {
  if(Trigger.isUpdate && Trigger.isAfter){
    MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
  }
}
6) Test Callout Logic
WarehouseCalloutService Code:
public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
```

```
apex.herokuapp.com/equipment';
  //@future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
      List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        myEq.Cost__c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse SKU c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
      }
      if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
```

```
}
   }
 }
WarehouseCalloutServiceTest Code:
@isTest
private class WarehouseCalloutServiceTest {
  @isTest
  static void testWareHouseCallout(){
    Test.startTest();
    // implement mock callout test here
    Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
    WarehouseCalloutService.runWarehouseEquipmentSync();
    Test.stopTest();
    System.assertEquals(1, [SELECT count() FROM Product2]);
 }
}
WarehouseCalloutServiceMock Code :
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
  // implement http mock callout
  global static HttpResponse respond(HttpRequest request){
    System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
    System.assertEquals('GET', request.getMethod());
    // Create a fake response
    HttpResponse response = new HttpResponse();
```

```
response.setHeader('Content-Type', 'application/json');
response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":
5,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}]');
    response.setStatusCode(200);
    return response;
 }
}
7) Test Scheduling Logic
WarehouseSyncSchedule Code:
global class WarehouseSyncSchedule implements Schedulable {
  global void execute(SchedulableContext ctx) {
    WarehouseCalloutService.runWarehouseEquipmentSync();
 }
}
WarehouseSyncScheduleTest Code :
@isTest
public class WarehouseSyncScheduleTest {
  @isTest static void WarehousescheduleTest(){
    String scheduleTime = '00 00 01 * * ?';
    Test.startTest();
    Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
    String jobID=System.schedule('Warehouse Time To Schedule to Test', scheduleTime,
new WarehouseSyncSchedule());
    Test.stopTest();
    //Contains schedule information for a scheduled job. CronTrigger is similar to a cron
job on UNIX systems.
    // This object is available in API version 17.0 and later.
    CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
```

```
System.assertEquals(jobID, a.Id,'Schedule ');
}
```