Salesforce Developer Catalyst Self-Learning & Super Badges

APEX TRIGGERS -->

1. Get Started With Apex Triggers

```
///AccountAddressTrigger////
trigger AccountAddressTrigger on Account (before insert, before update) {
 for(Account account:Trigger.New){
   if(account.Match_Billing_Address__c == True){
              account.ShippingPostalCode = account.BillingPostalCode;
    }
}
```

2. Bulk Apex Triggers

```
///ClosedOpportunityTrigger///
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update){
  List<Task> tasklist = new List<Task>();
      for(Opportunity opp: Trigger.New){
    if(opp.StageName == 'Closed Won'){
                    tasklist.add(new Task(Subject = 'Follow Up Test Task', WhatId =
opp.ld));
  }
      if(tasklist.size()>0){
```

```
insert tasklist;
}
}
```

Apex Testing--->

1. Get Started with Apex Unit Tests

```
///VerifyDate///
public class VerifyDate {
      //method to handle potential checks against two dates
       public static Date CheckDates(Date date1, Date date2) {
             //if date2 is within the next 30 days of date1, use date2. Otherwise use
the end of the month
             if(DateWithin30Days(date1,date2)) {
                    return date2:
             } else {
                    return SetEndOfMonthDate(date1);
             }
      }
      //method to check if date2 is within the next 30 days of date1
       @TestVisible private static Boolean DateWithin30Days(Date date1, Date date2) {
             //check for date2 being in the past
       if( date2 < date1) { return false; }
      //check that date2 is within (>=) 30 days of date1
      Date date30Days = date1.addDays(30); //create a date 30 days away from date1
             if( date2 >= date30Days ) { return false; }
             else { return true; }
      }
```

```
//method to return the end of the month of a given date
      @TestVisible private static Date SetEndOfMonthDate(Date date1) {
            Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
            Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
            return lastDay;
      }
}
///TestVerifyDate///
@isTest
private class TestVerifyDate{
  @istest static void Test_CheckDates_case1(){
    Date D = VerifyDate.CheckDates(date.parse('01/01/2020'),
date.parse('01/05/2020'));
    System.assertEquals(date.parse('01/05/2020'), D);
  }
      @isTest static void Test_CheckDates_case2(){
    Date D = VerifyDate.CheckDates (date.parse('01/01/2020'),
date.parse('05/05/2020'));
    System.assertEquals(date.parse('01/31/2020'), D);
  }
      @isTest static void Test_DateWithin30Days_case1() {
    Boolean flag = VerifyDate.DateWithin30Days (date.parse('01/01/2020'), date.parse(
'12/30/2019'));
            System.assertEquals(false, flag);
  }
      @istest static void Test_DateWithin30Days_case2(){
```

```
Boolean flag = VerifyDate.DateWithin30Days (date.parse('01/01/2020'),
date.parse('02/02/2020'));
           System.assertEquals(false, flag);
 }
      @isTest static void Test_DateWithin30Days_case3() {
    Boolean flag = VerifyDate.DateWithin30Days (date.parse('01/01/2020'),
date.parse('01/15/2020'));
   System.assertEquals(true, flag);
 }
      @isTest static void Test_SetEndOfMonthDate(){
           Date returndate =
VerifyDate.SetEndOfMonthDate(date.parse('01/01/2020'));
  }
}
                             2. Test Apex Triggers
///RestrictContactByName///
trigger RestrictContactByName on Contact (before insert, before
update) {
     //check contacts prior to insert or update for invalid data
     For (Contact c : Trigger.New) {
           if(c.LastName == 'INVALIDNAME') { //invalidname is
invalid
                 c.AddError('The Last Name "'+c.LastName+'" is not
allowed for DML');
```

}

3. Create Test Data for Apex Tests

Asynchronous Apex--->

1. Use Future Methods

```
///AccountProcessor///
public class AccountProcessor{
      @future
  public static void countContacts(List<Id> accountIds){
    List<Account> accountsToUpdate = new List<Account>();
            List<Account> accounts = [Select Id, Name, (Select Id from Contacts) from
Account Where Id in :accountIdsl:
            For(Account acc:accounts){
                  List<Contact> contactList = acc.Contacts;
      acc.Number_Of_Contacts__c = contactList.size();
      accountsToUpdate.add(acc);
            update accountsToUpdate;
   }
///AccountProcessorTest///
@IsTest
private class AccountProcessorTest{
     @IsTest
    private static void testCountContacts() {
```

```
Account newAccount = new Account(Name = 'Test Account');
insert newAccount;

Contact newContact1 = new Contact(FirstName='John',
LastName='Doe', AccountId = newAccount.id);
insert newContact1;

Contact newContact2 = new Contact(FirstName='Jane',
LastName='Doe', AccountId = newAccount.id);
insert newContact2;

List<Id> accountIds = new List<Id>();
accountIds.add(newAccount.Id);

Test.startTest();
AccountProcessor.countContacts(accountIds);
Test.stopTest();
}
```

2. Use Batch Apex

```
///LeadProcessor///
global class LeadProcessor implements Database.Batchable<sObject> {
    global Integer count = 0;

    global Database.Querylocator start(Database.BatchableContext bc) {
        return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
    }

    global void execute (Database.BatchableContext bc, List<Lead> L_list){
        List<lead> L_list_new = new List<lead>();
    }
}
```

```
for(lead L:L_list){
      L.leadsource = 'Dreamforce';
      L_list_new.add(L);
     count += 1;
    }
    update L_list_new;
  }
  global void finish(Database.BatchableContext bc){
    system.debug('count = ' + count);
 }
}
************************************
///LeadProcessorTest///
@isTest
public class LeadProcessorTest {
      @isTest
      public static void testit(){
            List<lead> L_list = new List<lead>();
            for(Integer i=0; i<200; i++){
                  Lead L = new lead();
                  L.LastName = 'name' + i;
                  L.Company = 'Company';
                  L.Status = 'Random Status';
                  L_list.add(L);
   }
            insert L_list;
            Test.startTest();
            LeadProcessor();
            Id batchId = Database.executeBatch(Ip);
```

3. Control Processes with Queueable Apex

```
///AddPrimaryContact///
public class AddPrimaryContact implements Queueable{
  private Contact con;
  private String state;
  public AddPrimaryContact (Contact con, String state){
    this.con = con;
    this.state = state;
 }
  public void execute(QueueableContext context){
    List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id from
contacts)
                                                     from Account where BillingState
= :state Limit 200];
    List<Contact> primaryContacts = new List<Contact>();
    for (Account acc:accounts){
      Contact c = con.clone();
       c.AccountId = acc.Id;
       primaryContacts.add(c);
    }
    if(primaryContacts.size() > 0){
      insert primaryContacts;
  }
```

```
}
**************************************
///AddPrimaryContactTest///
@isTest
public class AddPrimaryContactTest{
  static testmethod void testQueueable(){
    List<Account> testAccounts=new List<Account>();
   for(Integer i=0;i<50;i++){
     testAccounts.add(new Account (Name='Account '+i,BillingState='CA'));
   for(Integer j=0;j<5;j++){
     testAccounts.add(new Account (Name='Account '+j, BillingState='NY'));
   insert testAccounts;
   Contact testContact=new Contact(FirstName='John', LastName ='Doe');
    insert testContact;
   AddPrimaryContact addit=new addPrimaryContact(testContact, 'CA');
   Test.startTest();
    system.enqueueJob(addit);
   Test.stopTest();
           System.assertEquals(50,[Select count() from Contact where accountld in
(Select Id from Account where BillingState='CA')]);
```

4. Schedule Jobs Using the Apex Scheduler

```
///DailyLeadProcessor///
global class DailyLeadProcessor implements Schedulable{
  global void execute(SchedulableContext ctx){
    List<Lead> leads = [SELECT Id, LeadSource FROM Lead WHERE LeadSource = "];
    if(leads.size() > 0){
      List<Lead> newLeads = new List<Lead>();
      for(Lead lead : leads){
        lead.LeadSource = 'DreamForce':
        newLeads.add(lead);
      update newLeads;
 }
************************************
///DailyLeadProcessorTest///
@isTest
private class DailyLeadProcessorTest{
  //Seconds Minutes Hours Day_of_month Month Day_of_week optional_year
  public static String CRON_EXP = '0 0 0 2 6 ? 2022';
  static testmethod void testScheduledJob(){
    List<Lead> leads = new List<Lead>();
    for(Integer i = 0; i < 200; i++){
      Lead lead = new Lead(LastName = 'Test ' + i, LeadSource = ", Company = 'Test
Company ' + i, Status = 'Open - Not Contacted');
      leads.add(lead);
    insert leads;
    Test.startTest();
    // Schedule the test job
    String jobId = System.schedule('Update LeadSource to DreamForce', CRON_EXP,
new DailyLeadProcessor());
    // Stopping the test will run the job synchronously
    Test.stopTest();
  }
```

Apex Integration Services--->

}

2. Apex REST Callouts

```
///AnimalLocator///
public class AnimalLocator{
 public static String getAnimalNameById(Integer x){
   Http http = new Http();
   HttpRequest req = new HttpRequest();
   req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + x);
   req.setMethod('GET');
   Map<String, Object> animal= new Map<String, Object>();
    HttpResponse res = http.send(reg);
     if (res.getStatusCode() == 200) {
    Map<String, Object> results = (Map<String,
Object>)JSON.deserializeUntyped(res.getBody());
   animal = (Map<String, Object>) results.get('animal');
return (String)animal.get('name');
///AnimalLocatorTest///
@isTest
private class AnimalLocatorTest{
 @isTest static void AnimalLocatorMock1() {
    Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
    string result = AnimalLocator.getAnimalNameById(3);
    String expectedResult = 'chicken';
```

```
System.assertEquals(result,expectedResult);
///AnimalLocatorMock///
@isTest
global class AnimalLocatorMock implements HttpCalloutMock {
  // Implement this interface method
 global HTTPResponse respond(HTTPRequest request) {
   // Create a fake response
   HttpResponse response = new HttpResponse();
   response.setHeader('Content-Type', 'application/json');
   response.setBody('{"animals": ["majestic badger", "fluffy bunny", "scary bear",
"chicken", "mighty moose"]}');
   response.setStatusCode(200);
   return response;
                    3. Apex SOAP Callouts
///ParkLocator///
public class ParkLocator {
 public static string[] country(string theCountry){
   ParkService.ParksImplPort parkSvc = new ParkService.ParksImplPort();
   return parkSvc.byCountry(theCountry);
 }
///ParkLocatorTest///
```

```
@isTest
private class ParkLocatorTest {
  @isTest static void testCallout() {
    Test.setMock(WebServiceMock.class, new ParkServiceMock ());
    String country = 'United States';
    List<String> result = ParkLocator.country(country);
    List<String> parks = new List<String>{'Yellowstone', 'Mackinac National Park',
'Yosemite'};
    System.assertEquals(parks, result);
 }
}
///ParkServiceMock///
@isTest
global class ParkServiceMock implements WebServiceMock {
 global void doInvoke(
     Object stub,
     Object request,
     Map<String, Object> response,
     String endpoint,
     String soapAction,
     String requestName,
     String responseNS,
     String responseName,
     String responseType) {
    // start - specify the response you want to send
    ParkService.byCountryResponse response_x = new
ParkService.byCountryResponse();
    response_x.return_x = new List<String>{'Yellowstone', 'Mackinac National Park',
'Yosemite'};
   // end
    response.put('response_x', response_x);
 }
}
```

4. Apex Web Services

```
///AccountManager///
@RestResource(urlMapping = '/Accounts/*/contacts')
global with sharing class AccountManager {
  @HttpGet
  global static Account getAccount(){
    RestRequest request = RestContext.request;
    string accountId = request.requestURI.substringBetween('Accounts/','/contacts');
    Account result = [SELECT Id, Name, (Select Id, Name from Contacts) from Account
where Id=:accountId Limit 1];
    return result:
 }
///AccountManagerTest///
@IsTest
private class AccountManagerTest {
  @isTest static void testGetContactsByAccountId(){
    Id recordId = createTestRecord();
    RestRequest request = new RestRequest();
    request.requestUri =
'https://yourInstance.my.salesforce.com/services/apexrest/Accounts/'
                  + recordId+'/contacts':
    request.httpMethod = 'GET';
    RestContext.request = request;
    Account this Account = Account Manager.get Account();
    System.assert(thisAccount != null);
    System.assertEquals('Test record', thisAccount.Name);
```

```
static Id createTestRecord(){
    Account accountTest = new Account(
        Name ='Test record');
    insert accountTest;

Contact contactTest = new Contact(
        FirstName='John',
        LastName = 'Doe',
        AccountId = accountTest.Id
    );
    insert contactTest;

return accountTest.Id;
}
```

Apex Specialist SuperBadges--->

Challenge 1-Automated Record Creation

```
Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.Id);
       }
     }
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment_c, Equipment_r.Maintenance_Cycle_c,(SELECT
Id,Equipment_c,Quantity_c FROM Equipment_Maintenance_Items_r)
                              FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment_r.Maintenance_Cycle_c)cycle FROM
Equipment_Maintenance_Item_c WHERE Maintenance_Request_c IN :ValidIds GROUP
BY Maintenance_Request__c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }
      for(Case cc : closedCasesM.values()){
        Case nc = new Case (
          ParentId = cc.Id.
        Status = 'New',
          Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle_c = cc.Vehicle_c,
```

```
Equipment_c = cc. Equipment_c,
         Origin = 'Web',
         Date_Reported__c = Date.Today()
       );
       If (maintenanceCycles.containskey(cc.ld)){
         nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.ld));
       }
       newCases.add(nc);
     }
     insert newCases;
     List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
     for (Case nc : newCases){
       for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
         Equipment_Maintenance_Item__c wpClone = wp.clone();
         wpClone.Maintenance_Request__c = nc.ld;
         ClonedWPs.add(wpClone);
       }
     insert ClonedWPs;
 }
```

Challenge 2-Synchronize Salesforce data with an external system

///WarehouseCalloutService///

```
public with sharing class WarehouseCalloutService {
  private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
  //@future(callout=true)
  public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();
    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);
    List<Product2> warehouseEq = new List<Product2>();
    if (response.getStatusCode() == 200){
      List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
      System.debug(response.getBody());
      for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part_c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months_c = (Integer) mapJson.get('lifespan');
        myEq.Cost_c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
      }
      if (warehouseEq.size() > 0){
```

```
upsert warehouseEg;
       System.debug('Your equipment was synced with the warehouse one');
       System.debug(warehouseEq);
     }
Challenge 3-Schedule synchronization using Apex code
///WarehouseSyncShedule///
global class WarehouseSyncSchedule implements Schedulable {
 global void execute(SchedulableContext ctx) {
   WarehouseCalloutService.runWarehouseEquipmentSync();
 }
}
**************************************
                  Challenge 4-Test automation logic
///MaintenanceRequestHelperTest///
@istest
public with sharing class MaintenanceRequestHelperTest {
 private static final string STATUS_NEW = 'New';
 private static final string WORKING = 'Working';
 private static final string CLOSED = 'Closed';
 private static final string REPAIR = 'Repair';
 private static final string REQUEST_ORIGIN = 'Web';
```

private static final string REQUEST_TYPE = 'Routine Maintenance'; private static final string REQUEST_SUBJECT = 'Testing subject';

```
PRIVATE STATIC Vehicle_c createVehicle(){
    Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');
    return Vehicle;
  }
  PRIVATE STATIC Product2 createEq(){
    product2 equipment = new product2(name = 'SuperEquipment',
                     lifespan_months__C = 10,
                     maintenance_cycle__C = 10,
                     replacement_part__c = true);
    return equipment;
  }
  PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
    case cs = new case(Type=REPAIR,
             Status=STATUS_NEW,
             Origin=REQUEST_ORIGIN,
             Subject=REQUEST_SUBJECT,
             Equipment_c=equipmentId,
             Vehicle_c=vehicleId);
    return cs;
 }
  PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
    Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
                                        Maintenance_Request__c = requestId);
    return wp;
  }
  @istest
  private static void testMaintenanceRequestPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle:
    id vehicleId = vehicle.Id:
```

```
Product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);
    insert somethingToUpdate;
    Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
    insert workP;
    test.startTest();
    somethingToUpdate.status = CLOSED;
    update somethingToUpdate;
    test.stopTest();
    Case newReq = [Select id, subject, type, Equipment_c, Date_Reported_c,
Vehicle_c, Date_Due_c
           from case
           where status =:STATUS_NEW];
    Equipment_Maintenance_Item__c workPart = [select id
                         from Equipment_Maintenance_Item__c
                         where Maintenance_Request__c =:newReq.Id];
    system.assert(workPart != null);
    system.assert(newReg.Subject != null);
    system.assertEquals(newReq.Type, REQUEST_TYPE);
    SYSTEM.assertEquals(newReq.Equipment_c, equipmentId);
    SYSTEM.assertEquals(newReq.Vehicle_c, vehicleId);
    SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
  }
  @istest
  private static void testMaintenanceRequestNegative(){
    Vehicle__C vehicle = createVehicle();
```

```
insert vehicle;
    id vehicleId = vehicle.Id;
    product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
    case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
    insert emptyReq;
    Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId,
emptyReq.ld);
    insert workP;
    test.startTest();
    emptyReq.Status = WORKING;
    update emptyReq;
    test.stopTest();
    list<case> allRequest = [select id
                 from casel;
    Equipment_Maintenance_Item__c workPart = [select id
                           from Equipment_Maintenance_Item__c
                           where Maintenance_Request__c = :emptyReq.Id];
    system.assert(workPart != null);
    system.assert(allRequest.size() == 1);
  }
  @istest
  private static void testMaintenanceRequestBulk(){
    list<Vehicle_C> vehicleList = new list<Vehicle_C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> workPartList = new
list<Equipment_Maintenance_Item__c>();
    list<case> requestList = new list<case>();
```

```
list<id> oldRequestIds = new list<id>();
    for(integer i = 0; i < 300; i++){
      vehicleList.add(createVehicle());
      equipmentList.add(createEq());
    insert vehicleList;
    insert equipmentList;
    for(integer i = 0; i < 300; i++){
      requestList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    insert requestList;
    for(integer i = 0; i < 300; i++){
      workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
    insert workPartList;
    test.startTest();
    for(case req : requestList){
      req.Status = CLOSED;
      oldRequestIds.add(req.ld);
    update requestList;
    test.stopTest();
    list<case> allRequests = [select id
                  from case
                  where status =: STATUS_NEW];
    list<Equipment_Maintenance_Item__c> workParts = [select id
                               from Equipment_Maintenance_Item__c
                               where Maintenance_Request_c in: oldRequestIds];
    system.assert(allRequests.size() == 300);
```

```
}
///MaintenanceRequestHelper///
public with sharing class MaintenanceRequestHelper {
  public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
    Set<Id> validIds = new Set<Id>();
    For (Case c : updWorkOrders){
      if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
          validIds.add(c.Id);
    if (!validIds.isEmpty()){
      List<Case> newCases = new List<Case>();
      Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment_c, Equipment_r.Maintenance_Cycle_c,(SELECT
Id,Equipment_c,Quantity_c FROM Equipment_Maintenance_Items_r)
                              FROM Case WHERE Id IN :validIds]);
      Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
      AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment_r.Maintenance_Cycle_c)cycle FROM
Equipment_Maintenance_Item_c WHERE Maintenance_Request_c IN: ValidIds GROUP
BY Maintenance_Request__c];
    for (AggregateResult ar : results){
      maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
    }
```

```
for(Case cc : closedCasesM.values()){
        Case nc = new Case (
          ParentId = cc.Id,
        Status = 'New',
          Subject = 'Routine Maintenance',
          Type = 'Routine Maintenance',
          Vehicle_c = cc.Vehicle_c,
          Equipment_c = cc.Equipment_c,
          Origin = 'Web',
          Date_Reported__c = Date.Today()
        );
        If (maintenanceCycles.containskey(cc.Id)){
          nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.ld));
        }
        newCases.add(nc);
      }
     insert newCases;
     List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
     for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
          Equipment_Maintenance_Item__c wpClone = wp.clone();
          wpClone.Maintenance_Request__c = nc.ld;
          ClonedWPs.add(wpClone);
        }
      insert ClonedWPs;
```

```
}
///MaintenanceRequest///
trigger MaintenanceRequest on Case (before update, after update) {
 if(Trigger.isUpdate && Trigger.isAfter){
   MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
 }
*************************************
                     Challenge 5-Test callout logic
///WarehouseCalloutService///
public with sharing class WarehouseCalloutService {
 private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';
 //@future(callout=true)
 public static void runWarehouseEquipmentSync(){
   Http http = new Http();
   HttpRequest request = new HttpRequest();
   request.setEndpoint(WAREHOUSE_URL);
   request.setMethod('GET');
   HttpResponse response = http.send(request);
   List<Product2> warehouseEq = new List<Product2>();
   if (response.getStatusCode() == 200){
     List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
     System.debug(response.getBody());
```

```
for (Object eq : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)eq;
        Product2 myEq = new Product2();
        myEq.Replacement_Part_c = (Boolean) mapJson.get('replacement');
        myEq.Name = (String) mapJson.get('name');
        myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
        myEq.Lifespan_Months_c = (Integer) mapJson.get('lifespan');
        myEq.Cost_c = (Decimal) mapJson.get('lifespan');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
       myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
     }
      if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
     }
*************************************
///WarehouseCalloutServiceTest///
@isTest
private class WarehouseCalloutServiceTest {
  @isTest
  static void testWareHouseCallout(){
    Test.startTest();
   // implement mock callout test here
    Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
    WarehouseCalloutService.runWarehouseEquipmentSync();
    Test.stopTest();
```

```
System.assertEquals(1, [SELECT count() FROM Product2]);
 }
}
///WarehouseCalloutServiceMock///
@isTest
global class WarehouseCalloutServiceMock implements HttpCalloutMock {
 // implement http mock callout
 global static HttpResponse respond(HttpRequest request){
   System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
   System.assertEquals('GET', request.getMethod());
   // Create a fake response
   HttpResponse response = new HttpResponse();
   response.setHeader('Content-Type', 'application/json');
response.setBody('[{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5
."name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}]');
   response.setStatusCode(200);
   return response;
************************************
                   Challenge 6-Test scheduling logic
///WarehouseSyncSchedule///
global class WarehouseSyncSchedule implements Schedulable {
 global void execute(SchedulableContext ctx) {
   WarehouseCalloutService.runWarehouseEquipmentSync();
```

```
}
///WarehouseSyncScheduleTest///
@isTest
public class WarehouseSyncScheduleTest {
 @isTest static void WarehousescheduleTest(){
   String scheduleTime = '00 00 01 * * ?';
   Test.startTest();
   Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
   String jobID=System.schedule('Warehouse Time To Schedule to Test',
scheduleTime, new WarehouseSyncSchedule());
   Test.stopTest();
   //Contains schedule information for a scheduled job. CronTrigger is similar to a
cron job on UNIX systems.
   // This object is available in API version 17.0 and later.
   CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
   System.assertEquals(jobID, a.Id,'Schedule');
}
```

COMPLETED ALL APEX RELATED MODULES