

NAME : NAVDEEP SINGH
SBID : SB20220194879

Get Started with Apex Triggers

Here's the code :

```
trigger AccountAddressTrigger on Account (before insert,before update) {
```

```
List<Account> acclst=new List<Account>();
for(account a:trigger.new){
    if(a.Match_Billing_Address__c==true && a.BillingPostalCode!=null){
        a.ShippingPostalCode=a.BillingPostalCode;
    }
}
}
```

Bulk Apex Triggers

Here's the code :

```
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {
```

```
List<Task> taskList = new List<Task>();

for(Opportunity opp : Trigger.new) {

    //Only create Follow Up Task only once when Opp StageName is to 'Closed Won' on Create
    if(Trigger.isInsert) {
        if(Opp.StageName == 'Closed Won') {
            taskList.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));
        }
    }

    //Only create Follow Up Task only once when Opp StageName changed to 'Closed Won' on
    Update
    if(Trigger.isUpdate) {
```

```

    if(Opp.StageName == 'Closed Won'
    && Opp.StageName != Trigger.oldMap.get(opp.Id).StageName) {
        taskList.add(new Task(Subject = 'Follow Up Test Task', WhatId = opp.Id));
    }
}
}

if(taskList.size()>0) {
    insert taskList;
}
}

```

Get Started with Apex Unit Tests

VerifyDate class :

```

public class VerifyDate {

    //method to handle potential checks against two dates
    public static Date CheckDates(Date date1, Date date2) {
        //if date2 is within the next 30 days of date1, use date2. Otherwise use the end of the month
        if(DateWithin30Days(date1,date2)) {
            return date2;
        } else {
            return SetEndOfMonthDate(date1);
        }
    }

    //method to check if date2 is within the next 30 days of date1
    private static Boolean DateWithin30Days(Date date1, Date date2) {
        //check for date2 being in the past
        if( date2 < date1) { return false; }

        //check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1
        if( date2 >= date30Days ) { return false; }
        else { return true; }
    }

    //method to return the end of the month of a given date
    private static Date SetEndOfMonthDate(Date date1) {
        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
    }
}

```

```

        Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
        return lastDay;
    }

}

```

TestVerifyDate :

```

@isTest
public class TestVerifyDate
{
    static testMethod void testMethod1()
    {
        Date d = VerifyDate.CheckDates(System.today(),System.today()+1);
        Date d1 = VerifyDate.CheckDates(System.today(),System.today()+60);
    }
}

```

Test Apex Triggers

Here's the code :

RestrictContactByName :

```

trigger RestrictContactByName on Contact (before insert, before update) {

    //check contacts prior to insert or update for invalid data
    For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') { //invalidname is invalid
            c.AddError('The Last Name "'+c.LastName+'" is not allowed for DML');
        }

    }

}

```

TestRestrictContactByName :

@isTest

private class TestRestrictContactByName {

```
    static testMethod void metodoTest()
    {
```

```
        List<Contact> listContact= new List<Contact>();
```

```
        Contact c1 = new Contact(FirstName='Francesco', LastName='Riggio' ,
email='Test@test.com');
```

```
        Contact c2 = new Contact(FirstName='Francesco1', LastName =
'INVALIDNAME',email='Test@test.com');
```

```
        listContact.add(c1);
```

```
        listContact.add(c2);
```

```
        Test.startTest();
```

```
        try
```

```
        {
```

```
            insert listContact;
```

```
        }
```

```
        catch(Exception ee)
```

```
        {
```

```
        }
```

```
        Test.stopTest();
```

```
    }
```

```
}
```

Create Test Data for Apex Tests

Here's the code :

RandomContactFactory class :

```
//@isTest
public class RandomContactFactory {
    public static List<Contact> generateRandomContacts(Integer numContactsToGenerate, String
FName) {
        List<Contact> contactList = new List<Contact>();

        for(Integer i=0;i<numContactsToGenerate;i++) {
            Contact c = new Contact(FirstName=FName + ' ' + i, LastName = 'Contact ' + i);
            contactList.add(c);
            System.debug(c);
        }
        //insert contactList;
        System.debug(contactList.size());
        return contactList;
    }
}
```

Use Future Methods

Here's the code :

```
public class AccountProcessor {
    @future
    public static void countContacts(List<Id> accountIds){
        List<Account> accounts = [Select Id, Name from Account Where Id IN : accountIds];
        List<Account> updatedAccounts = new List<Account>();
        for(Account account : accounts){
            account.Number_of_Contacts__c = [Select count() from Contact Where AccountId =:
account.Id];
            System.debug('No Of Contacts = ' + account.Number_of_Contacts__c);
            updatedAccounts.add(account);
        }
        update updatedAccounts;
    }
}
```

```
test class///
```

```
@isTest
public class AccountProcessorTest {
    @isTest
    public static void testNoOfContacts(){
        Account a = new Account();
        a.Name = 'Test Account';
        Insert a;

        Contact c = new Contact();
        c.FirstName = 'Bob';
        c.LastName = 'Willie';
        c.AccountId = a.Id;

        Contact c2 = new Contact();
        c2.FirstName = 'Tom';
        c2.LastName = 'Cruise';
        c2.AccountId = a.Id;

        List<Id> acctIds = new List<Id>();
        acctIds.add(a.Id);

        Test.startTest();
        AccountProcessor.countContacts(acctIds);
        Test.stopTest();
    }
}
```

Use Batch Apex

Here's the code :

```
public class LeadProcessor implements Database.Batchable<sObject> {

    public Database.QueryLocator start(Database.BatchableContext bc) {
```

```

        // collect the batches of records or objects to be passed to execute
        return Database.getQueryLocator([Select LeadSource From Lead ]);
    }
    public void execute(Database.BatchableContext bc, List<Lead> leads){
        // process each batch of records
        for (Lead lead : leads) {
            lead.LeadSource = 'Dreamforce';
        }
        update leads;
    }
    public void finish(Database.BatchableContext bc){
    }
}

```

test class//

```

@isTest
public class LeadProcessorTest {

    @testSetup
    static void setup() {
        List<Lead> leads = new List<Lead>();
        for(Integer counter=0 ;counter <200;counter++){
            Lead lead = new Lead();
            lead.FirstName = 'FirstName';
            lead.LastName = 'LastName'+counter;
            lead.Company = 'demo'+counter;
            leads.add(lead);
        }
        insert leads;
    }

    @isTest static void test() {
        Test.startTest();
        LeadProcessor leadProcessor = new LeadProcessor();
        Id batchId = Database.executeBatch(leadProcessor);
        Test.stopTest();
    }
}

```

```
}
```

Control Processes with Queueable Apex

Here's the code :

```
public class AddPrimaryContact implements Queueable
{
    private Contact c;
    private String state;
    public AddPrimaryContact(Contact c, String state)
    {
        this.c = c;
        this.state = state;
    }
    public void execute(QueueableContext context)
    {
        List<Account> ListAccount = [SELECT ID, Name ,(Select id,FirstName,LastName from
contacts ) FROM ACCOUNT WHERE BillingState = :state LIMIT 200];
        List<Contact> lstContact = new List<Contact>();
        for (Account acc:ListAccount)
        {
            Contact cont = c.clone(false,false,false,false);
            cont.AccountId = acc.id;
            lstContact.add( cont );
        }

        if(lstContact.size() >0 )
        {
            insert lstContact;
        }

    }
}

test class///
```



```

@isTest
public class AddPrimaryContactTest
{
    @isTest static void TestList()
    {
        List<Account> Teste = new List <Account>();
        for(Integer i=0;i<50;i++)
        {
            Teste.add(new Account(BillingState = 'CA', name = 'Test'+i));
        }
        for(Integer j=0;j<50;j++)
        {
            Teste.add(new Account(BillingState = 'NY', name = 'Test'+j));
        }
        insert Teste;

        Contact co = new Contact();
        co.FirstName='demo';
        co.LastName ='demo';
        insert co;
        String state = 'CA';

        AddPrimaryContact apc = new AddPrimaryContact(co, state);
        Test.startTest();
        System.enqueueJob(apc);
        Test.stopTest();
    }
}

```

Schedule Jobs Using the Apex Scheduler

Here's the code :

```

public class DailyLeadProcessor implements Schedulable {
    Public void execute(SchedulableContext SC){
        List<Lead> LeadObj=[SELECT Id from Lead where LeadSource=null limit 200];
        for(Lead l:LeadObj){
            l.LeadSource='Dreamforce';
        }
    }
}

```

```

        update l;
    }
}
}

```

test class ///

```

@isTest
private class DailyLeadProcessorTest {
    static testMethod void testDailyLeadProcessor() {
        String CRON_EXP = '0 0 1 * * ?';
        List<Lead> lList = new List<Lead>();
        for (Integer i = 0; i < 200; i++) {
            lList.add(new Lead(LastName='Dreamforce'+i, Company='Test1 Inc.',
Status='Open - Not Contacted'));
        }
        insert lList;

        Test.startTest();
        String jobId = System.schedule('DailyLeadProcessor', CRON_EXP, new
DailyLeadProcessor());
    }
}

```

Apex REST Callouts

Here's the code :

Class AnimalLocator

```

public class AnimalLocator{
    public static String getAnimalNameById(Integer x){
        Http http = new Http();
        HttpRequest req = new HttpRequest();
        req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + x);
        req.setMethod('GET');
        Map<String, Object> animal= new Map<String, Object>();
        HttpResponse res = http.send(req);
        if (res.getStatusCode() == 200) {

```

```

        Map<String, Object> results = (Map<String,
Object>)JSON.deserializeUntyped(res.getBody());
        animal = (Map<String, Object>) results.get('animal');
    }
    return (String)animal.get('name');
}
}

```

AnimalLocatorTest

@isTest

```

private class AnimalLocatorTest{
    @isTest static void AnimalLocatorMock1() {
        Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
        string result = AnimalLocator.getAnimalNameById(3);
        String expectedResult = 'chicken';
        System.assertEquals(result,expectedResult );
    }
}

```

AnimalLocatorMock

@isTest

```

global class AnimalLocatorMock implements HttpCalloutMock {
    // Implement this interface method
    global HTTPResponse respond(HTTPRequest request) {
        // Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');
        response.setBody('{ "animals": ["majestic badger", "fluffy bunny", "scary bear", "chicken",
"mighty moose"]}');
        response.setStatusCode(200);
        return response;
    }
}

```

Apex SOAP Callouts

Here's the codec:

ParkLocator class/////

```
public class ParkLocator {  
    public static string[] country(string theCountry) {  
        ParkService.ParksImplPort parkSvc = new ParkService.ParksImplPort(); // remove space  
        return parkSvc.byCountry(theCountry);  
    }  
}
```

ParkLocatorTest class/////

```
@isTest  
private class ParkLocatorTest {  
    @isTest static void testCallout() {  
        Test.setMock(WebServiceMock.class, new ParkServiceMock ());  
        String country = 'United States';  
        List<String> result = ParkLocator.country(country);  
        List<String> parks = new List<String>{'Yellowstone', 'Mackinac National Park', 'Yosemite'};  
        System.assertEquals(parks, result);  
    }  
}
```

ParkServiceMock class /////

```
@isTest  
global class ParkServiceMock implements WebServiceMock {  
    global void doInvoke(  

```

```

    Object stub,
    Object request,
    Map<String, Object> response,
    String endpoint,
    String soapAction,
    String requestName,
    String responseNS,
    String responseName,
    String responseType) {
    // start - specify the response you want to send
    ParkService.byCountryResponse response_x = new ParkService.byCountryResponse();
    response_x.return_x = new List<String>{'Yellowstone', 'Mackinac National Park', 'Yosemite'};
    // end
    response.put('response_x', response_x);
}
}

```

Apex Web Services

Here's the code :

AccountManagerTest/////

```

@isTest
private class AccountManagerTest {

    private static testMethod void getAccountTest1() {
        Id recordId = createTestRecord();
        // Set up a test request
        RestRequest request = new RestRequest();
        request.requestUri = 'https://na1.salesforce.com/services/apexrest/Accounts/'+ recordId
        +'/contacts' ;
        request.httpMethod = 'GET';
        RestContext.request = request;
        // Call the method to test
        Account thisAccount = AccountManager.getAccount();
        // Verify results
        System.assert(thisAccount != null);
    }
}

```

```

        System.assertEquals('Test record', thisAccount.Name);
    }

    // Helper method
    static Id createTestRecord() {
        // Create test record
        Account TestAcc = new Account(
            Name='Test record');
        insert TestAcc;
        Contact TestCon= new Contact(
            LastName='Test',
            AccountId = TestAcc.id);
        return TestAcc.Id;
    }
}

AccountManager/////

@RestResource(urlMapping='/Accounts/*/contacts')
global class AccountManager {
    @HttpGet
    global static Account getAccount() {
        RestRequest req = RestContext.request;
        String accId = req.requestURI.substringBetween('Accounts/', '/contacts');
        Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
            FROM Account WHERE Id = :accId];
        return acc;
    }
}

```