

Salesforce Developer Catalyst Self Learning & Super Badges

Salesforce Developer-Self Learning

1. Salesforce Fundamentals & User Setup
2. Relationships & ProcessAutomation
3. Flows & Security
4. Apex,Testing And Debugging
5. Integration

1. Apex Triggers

1. Get started with apex triggers

Code :

```
trigger AccountAddressTrigger on Account (before insert,before update) {  
    for(Account a:Trigger.New){        if(a.Match_Billing_Address__c==true){  
        a.ShippingPostalCode=a.BillingPostalCode;  
        }  
    }  
}
```

2. Bulk Apex Triggers Code :

```

trigger ClosedOpportunityTrigger on Opportunity (before insert, before update) {
List<Task> taskList = new List<Task>();
//If an opportunity is inserted or updated with a stage of 'Closed Won'
    // add a task created with the subject 'Follow Up Test Task'.
for (Opportunity opp : Trigger.new)
{    //add a task with subject 'Follow Up Test Task'.
    if(opp.StageName == 'Closed Won')
        taskList.add(new Task(Subject='Follow Up Test Task', WhatId = opp.id ));    }    if
(taskList.size() > 0)
    {    insert taskList;
    }
}

```

2. Apex Testing

1. Get Started With Apex Triggers

```

Code :    @isTest private class
    TestVerifyDate {
static testMethod void TestVerifyDate() {
    VerifyDate.CheckDates(System.today(),System.today().addDays(10));
    VerifyDate.CheckDates(System.today(),System.today().addDays(78));
}
}

```

2. Test Apex Triggers Code :

```

    @IsTest
public class TestRestrictContactByName {    @IsTest
static void createBadContact(){

```

```

    Contact c=new Contact(Firstname='John',LastName='INVALIDNAME');

```

```

    Test.startTest();
    Database.SaveResult result = Database.insert(c, false);
    Test.stopTest();

```

```

    System.assert(!result.isSuccess());

```

```
}
}
```

3. Creating Test Data For Apex

Tests Code :

```
public class RandomContactFactory{
public static List<Contact> generateRandomContacts(integer n,stringLastName){
integer n1=n;
List<contact> c1 = new list<contact>();
list<contact> c2 =new list<contact>();
c1 = [select FirstName from Contact Limit : n1];
integer i=0;
for(contact cnew : c1){
contact cnew1 = new contact();
cnew1.firstname = cnew.firstname + i;
c2.add(cnew1);
i++;
}
return c2;
}
}
```

3. Asynchronous Apex

● Use Future Methods Code :

```
//AccountProcessor class

public class AccountProcessor {
@future
public static void countContacts(List<Id> accountIds){
List<Account> accounts = [Select Id, Name from Account Where Id IN : ];
List<Account> updatedAccounts = new List<Account>();
for(Account account : accounts){
account.Number_of_Contacts__c = [Select count() from Contact Where AccountId =:
account.Id];
System.debug('No Of Contacts = ' + account.Number_of_Contacts__c);
}
```

```

updatedAccounts.add(account);
    }
    update updatedAccounts;
}
}

```

//AccountProcessorTest Class

```

@Test
public class AccountProcessorTest {
    @Test
    public static void testNoOfContacts(){
        Account a = new Account();
        a.Name
= 'Test Account';
        Insert a;
        Contact c = new Contact();
        c.FirstName = 'Bob';
        c.LastName = 'Willie';
        c.AccountId = a.Id
;
        Contact c2 = new Contact();
        c2.FirstName = 'Tom';
        c2.LastName = 'Cruise';
        c2.AccountId = a.Id
;
        List<Id> acctIds = new List<Id>();
        acctIds.add(a.Id);
        Test.startTest();
        AccountProcessor.countContacts(acctIds);
        Test.stopTest();
    }
}

```

- **Use Batch Apex**

Code :

```
global class LeadProcessor implements Database.Batchable<sObject> { global
    Integer count = 0;

    global Database.QueryLocator start(Database.BatchableContext bc){
        return Database.getQueryLocator('SELECT ID, LeadSource FROM Lead');
    }

    global void execute(Database.BatchableContext bc, List<Lead> L_list){
        List<lead> L_list_new = new List<lead>();

        for(lead L:L_list){
            L.leadsource = 'Dreamforce';
            L_list_new.add(L);
            count += 1;
        }
        update L_list_new;
    }
    global void finish(Database.BatchableContext bc){
        System.debug('count = '+count);
    }
}
```

- **Control Processes With Queueable Apex Code :**

```
public class AddPrimaryContact implements Queueable {
    public contact c;
    public String state;

    public AddPrimaryContact(Contact c, String state) {
        this.c = c;
        this.state = state;
    }

    public void execute(QueueableContext qc) {
        system.debug('this.c = '+this.c+' this.state = '+this.state);
    }
}
```

```

    List<Account> acc_lst = new List<account>([select id, name, BillingState from account
where account.BillingState = :this.state limit 200]);
    List<contact> c_lst = new List<contact>();
    for(account a: acc_lst) {
        contact c = new contact();
        c = this.c.clone(false, false, false, false);
        c.AccountId = a.Id;
        c_lst.add(c);
    }
    insert c_lst;
}
}

```

Add primaryContactTest :

```

    public class AddPrimaryContact implements Queueable {
    public contact c;
    public String state;

    public AddPrimaryContact(Contact c, String state) {
        this.c = c;
        this.state = state;
    }
    public void execute(QueueableContext qc) {
        system.debug('this.c = '+this.c+' this.state = '+this.state);
        List<Account> acc_lst = new List<account>([select id, name, BillingState from account
where account.BillingState = :this.state limit 200]);
        List<contact> c_lst = new List<contact>();
        for(account a: acc_lst) {
            contact c = new contact();
            c = this.c.clone(false, false, false, false);
            c.AccountId = a.Id;
            c_lst.add(c);
        }
        insert c_lst;
    }
}
}

```

- Schedule Jobs Using the Apex Scheduler Code :

Apex Class

```
global class DailyLeadProcessor implements Schedulable{
    global void execute(SchedulableContext ctx){
        List<Lead> leads = [SELECT Id, LeadSource FROM Lead WHERE LeadSource = ""];

        if(leads.size() > 0){
            List<Lead> newLeads = new List<Lead>();

            for(Lead lead : leads){
                lead.LeadSource = 'DreamForce';
                newLeads.add(lead);
            }

            update newLeads;
        }
    }
}
```

Apex Test Class

@isTest

```
private class DailyLeadProcessorTest{
    //Seconds Minutes Hours Day_of_month Month Day_of_week optional_year
    public static String CRON_EXP = '0 0 0 2 6 ? 2022';

    static testmethod void testScheduledJob(){
        List<Lead> leads = new List<Lead>();

        for(Integer i = 0; i < 200; i++){
            Lead lead = new Lead(LastName = 'Test ' + i, LeadSource = '', Company = 'Test Company ' +
i, Status = 'Open - Not Contacted');
            leads.add(lead);
        }
    }
}
```

```

insert leads;

Test.startTest();
// Schedule the test job
String jobId = System.schedule('Update LeadSource to DreamForce', CRON_EXP, new
DailyLeadProcessor());

// Stopping the test will run the job synchronously
Test.stopTest();
}
}

```

4. Apex Integration Services

- **Apex REST Callouts Code :**

```

AnimalLocator
public class AnimalLocator {
    public class cls_animal { public
        Integer id;      public String
        name; public String eats;
        public String says;
    }
}

public class JSONOutput{ public
    cls_animal animal;

    //public JSONOutput parse(String json){
    //return (JSONOutput) System.JSON.deserialize(json, JSONOutput.class);
    //}
}

public static String getAnimalNameById (Integer id) {
    Http http = new Http();
    HttpRequest request = new HttpRequest();

```



```

        request.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + id);
        //request.setHeader('id', String.valueOf(id)); -- cannot be used in this challenge :)
        request.setMethod('GET');
        HttpResponse response = http.send(request);
        system.debug('response: ' + response.getBody());
        //Map<String,Object> map_results = (Map<String,Object>)
JSON.deserializeUntyped(response.getBody());
        jsonOutput results = (jsonOutput) JSON.deserialize(response.getBody(), jsonOutput.class);
        //Object results = (Object) map_results.get('animal'); system.debug('results= ' +
            results.animal.name);
        return(results.animal.name);
    }
}

```

AnimalLocatorMock

@IsTest

global class AnimalLocatorMock implements HttpCalloutMock {

```

    global HTTPResponse respond(HTTPRequest request) {
        HttpResponse response = new HttpResponse();
        response.setStatusCode(200);
        //-- directly output the JSON, instead of creating a logic
        //response.setHeader('key, value)
        //Integer id = Integer.valueOf(request.getHeader('id'));
        //Integer id = 1;
        //List<String> lst_body = new List<String> {'majestic badger', 'fluffy bunny'};
        //system.debug('animal return value: ' + lst_body[id]);
        response.setBody('{"animal":{"id":1,"name":"chicken","eats":"chicken food","says":"cluck
cluck"}}');
        return response;
    }
}

```

AnimalLocatorTest.cls

@IsTest

public class AnimalLocatorTest {

@isTest

public static void testAnimalLocator() {

```

Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
//HttpResponse response = AnimalLocator.getAnimalNameById(1);
String s = AnimalLocator.getAnimalNameById(1);
system.debug('string returned: ' + s);
}
}

```

● Apex Soap Callouts Code :

```

Apex Service
//Generated by wsdl2apex

public class ParkService {
    public class byCountryResponse {
        public String[] return_x;
        private String[] return_x_type_info = new
String[['return','http://parks.services/',null,'0','-1','false'];
        private String[] apex_schema_type_info = new
String[['http://parks.services/','false','false'];
        private String[] field_order_type_info = new String[['return_x'];
    }
    public class byCountry {
        public String arg0;
        private String[] arg0_type_info = new
String[['arg0','http://parks.services/',null,'0','1','false'];
        private String[] apex_schema_type_info = new
String[['http://parks.services/','false','false'];
        private String[] field_order_type_info = new String[['arg0'];
    }
    public class ParksImplPort {
        public String endpoint_x = 'https://th-apex-soapservice.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public Map<String,String> outputHttpHeaders_x;
        public String clientCertName_x;
        public String clientCert_x;
        public String clientCertPasswd_x;
        public Integer timeout_x;
    }
}

```

```

        private String[] ns_map_type_info = new String[]{'http://parks.services/',
'ParkService'};

        public String[] byCountry(String arg0) {
            ParkService.byCountry request_x = new ParkService.byCountry();
            request_x.arg0 = arg0;
            ParkService.byCountryResponse response_x;
            Map<String, ParkService.byCountryResponse> response_map_x = new
Map<String, ParkService.byCountryResponse>();
            response_map_x.put('response_x', response_x);
            WebServiceCallout.invoke(
                this,
                request_x,
                response_map_x,
                new String[]{endpoint_x,
                "",
                'http://parks.services/',
                'byCountry',
                'http://parks.services/',
                'byCountryResponse',
                'ParkService.byCountryResponse'}
            );
            response_x = response_map_x.get('response_x');
            return response_x.return_x;
        }
    }
}

```

Apex Class

```

public class ParkLocator {
    public static String[] country(String country){
        ParkService.ParksImplPort parks = new ParkService.ParksImplPort();
        String[] parksname = parks.byCountry(country);
        return parksname;
    }
}

```

Apex Test Class

@isTest

```
private class ParkLocatorTest{
    @isTest
    static void testParkLocator() {
        Test.setMock(WebServiceMock.class, new ParkServiceMock());
        String[] arrayOfParks = ParkLocator.country('India');

        System.assertEquals('Park1', arrayOfParks[0]);
    }
}
```

Apex Mock Test Class

@isTest

```
global class ParkServiceMock implements WebServiceMock {
    global void doInvoke(
        Object stub,
        Object request,
        Map<String, Object> response,
        String endpoint,
        String soapAction,
        String requestName,
        String responseNS,
        String responseName,
        String responseType) {
        ParkService.byCountryResponse response_x = new
ParkService.byCountryResponse();
        List<String> lstOfDummyParks = new List<String> {'Park1','Park2','Park3'};
        response_x.return_x = lstOfDummyParks;

        response.put('response_x', response_x);
    }
}
```

● **Apex Web Services Code :**

```
AccountManagerTest/////
@isTest
private class AccountManagerTest {
private static testMethod void getAccountTest1() {
    Id recordId = createTestRecord();
    // Set up a test request
    RestRequest request = new RestRequest();
    request.requestUri = 'https://na1.salesforce.com/services/apexrest/Accounts/'+
recordId +'/contacts' ;
    request.httpMethod = 'GET';
    RestContext.request = request;
    // Call the method to test
    Account thisAccount = AccountManager.getAccount();
    // Verify results
    System.assert(thisAccount != null);
    System.assertEquals('Test record', thisAccount.Name);

}
// Helper method
static Id createTestRecord() {
    // Create test record
    Account TestAcc = new Account(
        Name='Test record');
    insert TestAcc;
    Contact TestCon= new Contact(
        LastName='Test',
        AccountId = TestAcc.id);
    return TestAcc.Id
;
}
}
```

AccountManager/////

```

@RestResource(urlMapping='/Accounts/*/contacts') global class
AccountManager {
    @HttpGet
    global static Account getAccount() {
        RestRequest req = RestContext.request;
        String accId = req.requestURI.substringBetween('Accounts/', '/contacts');
        Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
                        FROM Account WHERE Id = :accId];
        return acc;
    }
}

```

Skills Learnt During Completion Of The Superbadge

- How to Automate record creation using Apex triggers

Code :

[MaintenanceRequestHelper.apxc](#)

```

public with sharing class MaintenanceRequestHelper {
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
                    validIds.add(c.Id);
                }
            }
        }
    }
}

```

```
    }  
  }  
}
```

```
if (!validIds.isEmpty()){  
    List<Case> newCases = new List<Case>();  
    Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,  
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT  
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)  
FROM Case WHERE Id IN :validIds]);  
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();  
    AggregateResult[] results = [SELECT Maintenance_Request__c,  
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM  
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds GROUP  
BY Maintenance_Request__c];  
  
    for (AggregateResult ar : results){  
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));  
    }  
  
    for(Case cc : closedCasesM.values()){  
        Case nc = new Case (  
            ParentId = cc.Id,  
            Status = 'New',  
            Subject = 'Routine Maintenance',  
            Type = 'Routine Maintenance',  
            Vehicle__c = cc.Vehicle__c,  
            Equipment__c =cc.Equipment__c,  
            Origin = 'Web',  
            Date_Reported__c = Date.Today()  
  
        );  
  
        If (maintenanceCycles.containsKey(cc.Id)){  
            nc.Date_Due__c = Date.today().addDays((Integer)  
maintenanceCycles.get(cc.Id));
```

```

        } else {
            nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipment__r.maintenance_Cycle__c);
        }

        newCases.add(nc);
    }

    insert newCases;

    List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
    for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
            Equipment_Maintenance_Item__c wpClone = wp.clone();
            wpClone.Maintenance_Request__c = nc.Id;
            ClonedWPs.add(wpClone);

        }
    }
    insert ClonedWPs;
}
}
}

```

MaitenanceRequest.apxt

```

trigger MaintenanceRequest on Case (before update, after update) {
    if(Triiger.isUpdate && Trigger.isAfter)
MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap); }

```

- **Synchronize Salesforce data with an external system using asynchronous REST callouts.**

Code:

WarehouseCalloutService.apxc :- public with sharing class WarehouseCalloutService implements Queueable { private static final String WAREHOUSE_URL = 'https://th-superbadgeapex.herokuapp.com/equipment';

//class that makes a REST callout to an external warehouse system to get a list of equipment that needs to be updated.

//The callout's JSON response returns the equipment records that you upsert in Salesforce.

```
@future(callout=true)
public static void runWarehouseEquipmentSync(){
    Http http = new Http();
    HttpRequest request = new HttpRequest();

    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);

    List<Product2> warehouseEq = new List<Product2>();

    if (response.getStatusCode() == 200){
        List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
        System.debug(response.getBody());

        //class maps the following fields: replacement part (always true), cost, current inventory,
lifespan, maintenance cycle, and warehouse SKU

        //warehouse SKU will be external ID for identifying which equipment records to update
within Salesforce
        for (Object eq : jsonResponse){
            Map<String,Object> mapJson = (Map<String,Object>)eq;
            Product2 myEq = new Product2();
            myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
            myEq.Name = (String) mapJson.get('name');
            myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
            myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
```

```

        myEq.Cost__c = (Integer) mapJson.get('cost');
        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        myEq.ProductCode = (String) mapJson.get('_id');
        warehouseEq.add(myEq);
    }

    if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
    }
}

public static void execute (QueueableContext context){
    runWarehouseEquipmentSync();
}

}

execute anonymous window ( CTRL+E ) ,System.enqueueJob(new WarehouseCalloutService());

```

- **Schedule synchronization using Apex code.**

Code:

WarehouseSyncSchedule.apxc :-

```

global with sharing class WarehouseSyncSchedule implements Schedulable{
    global void execute(SchedulableContext ctx){
        System.enqueueJob(new WarehouseCalloutService());
    }
}

```

- **Test automation logic to confirm Apex trigger side effects**

Code:

MaintenanceRequestHelperTest.apxc :-

@istest

```
public with sharing class MaintenanceRequestHelperTest {

    private static final string STATUS_NEW = 'New';
    private static final string WORKING = 'Working';
    private static final string CLOSED = 'Closed';
    private static final string REPAIR = 'Repair';
    private static final string REQUEST_ORIGIN = 'Web';
    private static final string REQUEST_TYPE = 'Routine Maintenance';
    private static final string REQUEST_SUBJECT = 'Testing subject';

    PRIVATE STATIC Vehicle__c createVehicle(){
        Vehicle__c Vehicle = new Vehicle__C(name = 'SuperTruck');
        return Vehicle;
    }

    PRIVATE STATIC Product2 createEq(){
        product2 equipment = new product2(name = 'SuperEquipment',
            lifespan_months__C = 10,
            maintenance_cycle__C = 10,
            replacement_part__c = true);
        return equipment;
    }

    PRIVATE STATIC Case createMaintenanceRequest(id vehicleId, id equipmentId){
        case cs = new case(Type=REPAIR,
            Status=STATUS_NEW,
            Origin=REQUEST_ORIGIN,
            Subject=REQUEST_SUBJECT,
            Equipment__c=equipmentId,
            Vehicle__c=vehicleId);
    }
}
```

```

        return cs;
    }

    PRIVATE STATIC Equipment_Maintenance_Item__c createWorkPart(id equipmentId,id
requestId){
        Equipment_Maintenance_Item__c wp = new
Equipment_Maintenance_Item__c(Equipment__c = equipmentId,
                                Maintenance_Request__c = requestId);    return
wp;
    }

    @istest
    private static void testMaintenanceRequestPositive(){
        Vehicle__c vehicle = createVehicle();
        insert vehicle;
        id vehicleId = vehicle.Id;

        Product2 equipment = createEq();
        insert equipment;
        id equipmentId = equipment.Id;

        case somethingToUpdate = createMaintenanceRequest(vehicleId,equipmentId);    insert
somethingToUpdate;

        Equipment_Maintenance_Item__c workP =
createWorkPart(equipmentId,somethingToUpdate.id);
        insert workP;

        test.startTest();
        somethingToUpdate.status = CLOSED;
        update somethingToUpdate;
        test.stopTest();

        Case newReq = [Select id, subject, type, Equipment__c, Date_Reported__c,

```

```
Vehicle__c, Date_Due__c
    from case
    where status =:STATUS_NEW];
```

```
Equipment_Maintenance_Item__c workPart = [select id
    from Equipment_Maintenance_Item__c
    where Maintenance_Request__c =:newReq.Id];
```

```
system.assert(workPart != null);
system.assert(newReq.Subject != null);
system.assertEquals(newReq.Type, REQUEST_TYPE);
SYSTEM.assertEquals(newReq.Equipment__c, equipmentId);
SYSTEM.assertEquals(newReq.Vehicle__c, vehicleId);
SYSTEM.assertEquals(newReq.Date_Reported__c, system.today());
}
```

@istest

```
private static void testMaintenanceRequestNegative(){
```

```
    Vehicle__C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;
```

```
    product2 equipment = createEq();
    insert equipment;
    id equipmentId = equipment.Id;
```

```
    case emptyReq = createMaintenanceRequest(vehicleId,equipmentId);
    insert emptyReq;
```

```
    Equipment_Maintenance_Item__c workP = createWorkPart(equipmentId, emptyReq.Id);
    insert workP;
```

```
    test.startTest();
    emptyReq.Status = WORKING;
    update emptyReq;
```

```
test.stopTest();
```

```
list<case> allRequest = [select id  
                        from case];
```

```
Equipment_Maintenance_Item__c workPart = [select id  
                                           from Equipment_Maintenance_Item__c  
                                           where Maintenance_Request__c = :emptyReq.Id];
```

```
system.assert(workPart != null);  
system.assert(allRequest.size() == 1);  
}
```

```
@istest
```

```
private static void testMaintenanceRequestBulk(){  
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();  
    list<Product2> equipmentList = new list<Product2>();  
list<Equipment_Maintenance_Item__c> workPartList = new  
list<Equipment_Maintenance_Item__c>();    list<case> requestList =  
new list<case>();  
    list<id> oldRequestIds = new list<id>();  
  
    for(integer i = 0; i < 300; i++){  
        vehicleList.add(createVehicle());  
        equipmentList.add(createEq());  
    }  
    insert vehicleList;  
    insert equipmentList;  
  
    for(integer i = 0; i < 300; i++){  
        requestList.add(createMaintenanceRequest(vehicleList.get(i).id, equipmentList.get(i).id));  
    }  
    insert requestList;  
  
    for(integer i = 0; i < 300; i++){
```

```

        workPartList.add(createWorkPart(equipmentList.get(i).id, requestList.get(i).id));
    }
    insert workPartList;

    test.startTest();
    for(case req : requestList){
        req.Status = CLOSED;
        oldRequestIds.add(req.Id);
    }
    update requestList;
    test.stopTest();

    list<case> allRequests = [select id
                            from case
                            where status =: STATUS_NEW];

    list<Equipment_Maintenance_Item__c> workParts = [select id
                                                    from Equipment_Maintenance_Item__c
                                                    where Maintenance_Request__c in: oldRequestIds];

    system.assert(allRequests.size() == 300);
}
}

```

MaintenanceRequestHelper.apxc :-

```

public with sharing class MaintenanceRequestHelper {
    public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

        For (Case c : updWorkOrders){
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){

```

```
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
validIds.add(c.Id);
```

```
    }
}
}
```

```
if (!validIds.isEmpty()){
    List<Case> newCases = new List<Case>();
    Map<Id,Case> closedCasesM = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,(SELECT
Id,Equipment__c,Quantity__c FROM Equipment_Maintenance_Items__r)
FROM Case WHERE Id IN :validIds]);
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
    AggregateResult[] results = [SELECT Maintenance_Request__c,
MIN(Equipment__r.Maintenance_Cycle__c)cycle FROM
Equipment_Maintenance_Item__c WHERE Maintenance_Request__c IN :ValidIds GROUP
BY Maintenance_Request__c];

    for (AggregateResult ar : results){
        maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal) ar.get('cycle'));
    }
}
```

```
for(Case cc : closedCasesM.values()){
    Case nc = new Case (
        ParentId = cc.Id,
        Status = 'New',
        Subject = 'Routine Maintenance',
        Type = 'Routine Maintenance',
        Vehicle__c = cc.Vehicle__c,
        Equipment__c =cc.Equipment__c,
        Origin = 'Web',
        Date_Reported__c = Date.Today()

    );
}
```



```

        If (maintenanceCycles.containsKey(cc.Id)){
            nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
        }

        newCases.add(nc);
    }

    insert newCases;

    List<Equipment_Maintenance_Item__c> clonedWPs = new
List<Equipment_Maintenance_Item__c>();
    for (Case nc : newCases){
        for (Equipment_Maintenance_Item__c wp :
closedCasesM.get(nc.ParentId).Equipment_Maintenance_Items__r){
            Equipment_Maintenance_Item__c wpClone = wp.clone();
            wpClone.Maintenance_Request__c = nc.Id;
            ClonedWPs.add(wpClone);

        }
    }
    insert ClonedWPs;
}
}
}

```

MaintenanceRequest.apxt :-

```

trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```

- **Test integration logic using callout mocks**

Code:

WarehouseCalloutService.apxc :-

```
public with sharing class WarehouseCalloutService {
    private static final String WAREHOUSE_URL = 'https://th-
superbadgeapex.herokuapp.com/equipment';

    //@future(callout=true)
    public static void runWarehouseEquipmentSync(){

        Http http = new Http();
        HttpRequest request = new HttpRequest();

        request.setEndpoint(WAREHOUSE_URL);
        request.setMethod('GET');
        HttpResponse response = http.send(request);

        List<Product2> warehouseEq = new List<Product2>();

        if (response.getStatusCode() == 200){
            List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
            System.debug(response.getBody());

            for (Object eq : jsonResponse){
                Map<String,Object> mapJson = (Map<String,Object>)eq;
                Product2 myEq = new Product2();
                myEq.Replacement_Part__c = (Boolean) mapJson.get('replacement');
                myEq.Name = (String) mapJson.get('name');
                myEq.Maintenance_Cycle__c = (Integer) mapJson.get('maintenanceperiod');
                myEq.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
                myEq.Cost__c = (Decimal) mapJson.get('lifespan');
```

```

        myEq.Warehouse_SKU__c = (String) mapJson.get('sku');
        myEq.Current_Inventory__c = (Double) mapJson.get('quantity');
        warehouseEq.add(myEq);
    }

    if (warehouseEq.size() > 0){
        upsert warehouseEq;
        System.debug('Your equipment was synced with the warehouse one');
        System.debug(warehouseEq);
    }

}
}
}

```

WarehouseCalloutServiceTest.apxc :-

```

@isTest

private class WarehouseCalloutServiceTest {
    @isTest
    static void testWareHouseCallout(){
        Test.startTest();
        // implement mock callout test here
        Test.setMock(HTTPCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.runWarehouseEquipmentSync();
        Test.stopTest();
        System.assertEquals(1, [SELECT count() FROM Product2]);
    }
}

```

WarehouseCalloutServiceMock.apxc :-

```

@isTest

global class WarehouseCalloutServiceMock implements HttpCalloutMock {
    // implement http mock callout
    global static HttpResponse respond(HttpRequest request){

```

```

        System.assertEquals('https://th-superbadge-apex.herokuapp.com/equipment',
request.getEndpoint());
        System.assertEquals('GET', request.getMethod());

        // Create a fake response
        HttpResponse response = new HttpResponse();
        response.setHeader('Content-Type', 'application/json');

response.setBody('{"_id":"55d66226726b611100aaf741","replacement":false,"quantity
":5,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"}');
        response.getStatusCode(200);
        return response;
    }
}

```

- **Test scheduling logic to confirm action gets queued**

Code:

```

    WarehouseSyncSchedule.apxc :- global class
WarehouseSyncSchedule implements Schedulable {
    global void execute(SchedulableContext ctx) {

        WarehouseCalloutService.runWarehouseEquipmentSync();
    }
}

```

WarehouseSyncScheduleTest.apxc :-

```

@isTest
public class WarehouseSyncScheduleTest {

    @isTest static void WarehousescheduleTest(){
        String scheduleTime = '00 00 01 * * ?';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());    String
jobID=System.schedule('Warehouse Time To Schedule to Test',

```

```

scheduleTime, new WarehouseSyncSchedule());
    Test.stopTest();
    //Contains schedule information for a scheduled job. CronTrigger is similar to a cron job on
    UNIX systems.
    // This object is available in API version 17.0 and later.
    CronTrigger a=[SELECT Id FROM CronTrigger where NextFireTime > today];
    System.assertEquals(jobID, a.Id,'Schedule ');

}
}

```

Process Automation Specialist - SuperBadge

- 1)Formulas And Validations
- 2)Salesforce Flow
- 3)Leads & Opportunities For Lightning Experience

Skills Learnt During Completion Of Super badge

1. Automate lead ownership using assignment rules
2. Enforce data integrity with formula fields and validation rules
3. Create a custom object in a master-detail relationship to a standard object
4. Define an opportunity sales process using stages, record types, and validation rules
5. Automate business processes to send emails, create related records, and submit opportunities for approval
6. Create a flow to display dynamic information on a Lightning record page
7. Create a process to evaluate and update records