

Apex Specialist SuperBadge -1

Apex Triggers

1. Get Started with Apex Triggers

1. RandomContactFactory.apxc

```
public class RandomContactFactory {  
  
    public static List<Contact> generateRandomContacts(Integer numcnt, string  
lastname){  
        List<Contact> contacts = new List<Contact>();  
        for(Integer i=0; i<numcnt ; i++){  
            Contact cnt = new Contact(FirstName = 'Test '+i, LastName = lastname);  
            contacts.add(cnt);  
        }  
        return contacts;  
    }  
}
```

2. AccountAddressTrigger.apxt

```
trigger AccountAddressTrigger on Account (before insert, beforeupdate) {  
    for(Account account : Trigger.New){  
        if(account.Match_Billing_Address__c == True){  
            account.ShippingPostalCode = account.BillingPostalCode;  
        }  
    }  
}
```

2. Bulk Apex Triggers

1. ClosedOpportunityTrigger.apxt

```
trigger ClosedOpportunityTrigger on Opportunity (after insert, after update) {  
    List<Task> tasklist = new List<Task>();  
    for(Opportunity opp: Trigger.New){
```

```

    if(opp.StageName == 'Closed Won'){
        tasklist.add(new Task(Subject = 'Follow Up Test Task',WhatId = opp.Id));
    }
}
if(tasklist.size()>0){
    insert tasklist;
}
}

```

Apex Testing

1.Get Started with Apex Unit Tests

1.VerifyDate.apxc

```

public class VerifyDate {

    //method to handle potential checks against two dates
    public static Date CheckDates(Date date1, Date date2) {
        //if date2 is within the next 30 days of date1, use date2. Otherwise use
the end of the month
        if(DateWithin30Days(date1,date2)) {
            return date2;
        } else {
            return SetEndOfMonthDate(date1);
        }
    }

    //method to check if date2 is within the next 30 days of date1
    @TestVisible private static Boolean DateWithin30Days(Date date1, Date date2) {
        //check for date2 being in the past
        if( date2 < date1) { return false; }

        //check that date2 is within (>=) 30 days of date1
        Date date30Days = date1.addDays(30); //create a date 30 days away from date1
        if( date2 >= date30Days ) { return false; }
    }
}

```

```

        else { return true; }
    }

    //method to return the end of the month of a given date
    @TestVisible private static Date SetEndOfMonthDate(Date date1) {
        Integer totalDays = Date.daysInMonth(date1.year(), date1.month());
        Date lastDay = Date.newInstance(date1.year(), date1.month(), totalDays);
        return lastDay;
    }
}

```

2.TestVerifyDate.apxc

```

@Test
private class TestVerifyDate {
    @isTest static Void Test_CheckDates_case1(){
        Date D
        =VerifyDate.CheckDates(date.parse('01/01/2020'),date.parse('01/05/2020'));
        System.assertEquals(date.parse('01/05/2020'),D);
    }
    @isTest static void Test_CheckDates_case2(){
        Date D
        =VerifyDate.CheckDates(date.parse('01/01/2020'),date.parse('05/05/2020'));
        System.assertEquals(date.parse('01/31/2020'),D);
    }
    @isTest static void Test_DateWithin30Days_case1(){
        Boolean flag =
        VerifyDate.DateWithin30Days(date.parse('01/01/2020'),date.parse('12/30/2019'));
        System.assertEquals(false,flag);
    }
    @isTest static void Test_DateWithin30Days_case2(){
        Boolean flag =
        VerifyDate.DateWithin30Days(date.parse('01/01/2020'),date.parse('02/02/2020'));
        System.assertEquals(false,flag);
    }
    @isTest static void Test_DateWithin30Days_case3(){

```

```

        Boolean flag =
VerifyDate.DateWithin30Days(date.parse('01/01/2020'),date.parse('01/15/2020'));
        System.assertEquals(true,flag);
    }
    @isTest static void Test_SetEndOfMonthDate(){
        Date returndate = VerifyDate.SetEndOfMonthDate(date.parse('01/01/2020'));
    }
}

```

2.Test Apex Triggers

1.RestrictContactByName.apxt

```

trigger RestrictContactByName on Contact (before insert, before update) {

    //check contacts prior to insert or update for invalid data
    For (Contact c : Trigger.New) {
        if(c.LastName == 'INVALIDNAME') {    //invalidname is invalid
            c.AddError('The Last Name '"+c.LastName+"' is not allowed for
DML');
        }
    }
}

```

2.TestRestrictContactByName.apxc

```

    @isTest
public class TestRestrictContactByName {
    @isTest static void Test_insertupdateContact(){
        Contact cnt =new Contact();
        cnt.LastName ='INVALIDNAME';
        Test.startTest();
        Database.SaveResult result = Database.insert(cnt,false);
        Test.stopTest();
        System.assert(!result.isSuccess());
        System.assert(result.getErrors().size() > 0);
    }
}

```

```

        System.assertEquals('The Last Name "INVALIDNAME" is not allowed for
DML',result.getErrors()[0].getMessage());
    }
}

```

3.Create Test Data for Apex Tests

1.RandomContactFactory.apxc

```

public class RandomContactFactory {

    public static List<Contact> generateRandomContacts(Integer numcnt,string
lastname){
        List<Contact> contacts = new List<Contact>();
        for(Integer i=0;i<numcnt ; i++){
            Contact cnt = new Contact(FirstName = 'Test '+i, LastName = lastname);
            contacts.add(cnt);
        }
        return contacts;
    }
}

```

Asynchronous Apex

2.Use Future Methods

1.AccountProcessor.apxc

```

public class AccountProcessor {
    @future
    public static void countContacts(List<Id> accountIds){
        List<Account> accountsToUpdate = new List<Account>();
        List<Account> accounts =[Select Id, Name, (Select Id from Contacts) from Account
Where Id in : accountIds ];
        For(Account acc: accounts){
            List<Contact> contactList = acc.Contacts;
            acc.Number_of_Contacts__c = contactList.size();
        }
    }
}

```

```

        accountsToUpdate.add(acc);
    }
    update accountsToUpdate;
}
}

```

2.AccountProcessorTest.apxc

```

@IsTest
private class AccountProcessorTest {
    @IsTest
    private static void testCountContacts(){
        Account newAccount = new Account(Name='Test Account');
        insert newAccount;
        Contact newContact1 =new Contact(FirstName = 'John', LastName
='Doe',AccountId = newAccount.Id);
        insert newContact1;
        Contact newContact2 =new Contact(FirstName = 'John', LastName
='Doe',AccountId = newAccount.Id);
        insert newContact2;
        List<Id> accountIds = new List<Id>();
        accountIds.add(newAccount.Id);
        Test.startTest();
        AccountProcessor.countContacts(accountIds);
        Test.stopTest();
    }
}

```

3.Use Batch Apex

1.LeadProcessor.apxc

```

global class LeadProcessor implements Database.Batchable<sObject>{
    global Integer count = 0;
    global Database.QueryLocator start(Database.BatchableContext bc){
        return Database.getQueryLocator('SELECT ID,LeadSource FROM Lead');
    }
}

```

```

global void execute (Database.BatchableContext bc, List<Lead> L_list){
    List<lead> L_list_new = new List<lead>();
    for(lead L: L_list){
        L.leadsource = 'Dreamforce';
        L_list_new.add(L);
        count += 1;
    }
    update L_list_new;
}
global void finish(Database.BatchableContext bc){
    system.debug('count = '+ count);
}
}

```

2.LeadProcessorTest.apxc

```

@isTest
public class LeadProcessorTest {
    @isTest
    public static void testit(){
        List<lead> L_list = new List<lead>();
        for(Integer i=0; i<200; i++){
            Lead L =new lead();
            L.LastName = 'name' + i;
            L.Company = 'Company';
            L.Status = 'Random Status';
            L_list.add(L);
        }
        insert L_list;
        Test.startTest();
        LeadProcessor lp = new LeadProcessor();
        Id batchId = Database.executeBatch(lp);
        Test.stopTest();
    }
}

```

4.Control Processes with Queueable Apex

1.AddPrimaryContact.apxc

```
public class AddPrimaryContact implements Queueable{
    private Contact con;
    private String state;
    public AddPrimaryContact(Contact con,String state){
        this.con = con;
        this.state = state;
    }
    public void execute(QueueableContext context){
        List<Account> accounts = [Select Id, Name, (Select FirstName, LastName, Id from
contacts )
                                from Account where Billingstate = :state Limit 200];
        List<Contact> primaryContacts = new List<Contact>();
        for(Account acc:accounts){
            contact c = con.clone();
            c.AccountId = acc.Id;
            primaryContacts.add(c);
        }
        if(primaryContacts.size() > 0){
            insert primaryContacts;
        }
    }
}
```

2.AddPrimaryContactTest.apxc

```
@isTest
public class AddPrimaryContactTest {
    static testmethod void testQueueable(){
        List<Account> testAccounts = new List<Account>();
        for(Integer i=0;i<50;i++){
            testAccounts.add(new Account(Name = 'Account' +i,BillingState ='CA'));
        }
    }
}
```



```

    for(Integer j=0;j<50;j++){
        testAccounts.add(new Account(Name='Account' +j,BillingState='NY'));
    }
    insert testAccounts;
    Contact testContact = new Contact(FirstName='John',LastName = 'Doe');
    insert testContact;

    AddPrimaryContact addit = new addPrimaryContact(testContact,'CA');

    Test.startTest();
    system.enqueueJob(addit);
    Test.stopTest();
    System.assertEquals(50,[Select count() from Contact where accountId in (Select Id
from Account where BillingState ='CA' )]);
    }
}

```

5.Schedule Jobs Using the Apex Scheduler

1.DailyLeadProcessor.apxc

```

global class DailyLeadProcessor implements Schedulable {
    global void execute(SchedulableContext ctx) {
        List<lead> leadstoupdate = new List<lead>();
        List<lead> leads = [SELECT Id
        FROM lead
        WHERE LeadSource = NULL Limit 200
        ];
        for(Lead l:leads){
            l.LeadSource = 'Dreamforce';
            leadstoupdate.add(l);
        }
        update leadstoupdate;
    }
}

```

2.DailyLeadProcessorTest.apxc

```
@isTest
private class DailyLeadProcessorTest {

    public static String CRON_EXP = '0 0 0 15 3 ? 2022';

    static testmethod void testScheduledJob(){
        List<Lead> leads = new List<Lead>();

        for(Integer i=0; i<200; i++){
            Lead l = new Lead(
                FirstName = 'First ' + i,
                LastName= 'LastName',
                Company = 'The Inc'
            );
            leads.add(l);
        }

        insert leads;

        Test.startTest();
        // Schedule the test job
        DailyLeadProcessor ab = new DailyLeadProcessor();
        String jobId = System.schedule('jobName', '0 5 * * * ?',ab);

        // Stopping the test will run the job synchronously
        Test.stopTest();
        List<Lead> checkleads = new List<Lead>();
        checkleads = [SELECT Id
            FROM Lead
            WHERE LeadSource = 'Dreamforce' and Company = 'The Inc'];
        System.assertEquals(200,
            checkleads.size(),
            'Leads were not created');
    }
}
```

```
}
```

Apex Integration Services

2.Apex REST Callouts

1.AnimalLocator.apxc

```
    public class AnimalLocator{
public static String getAnimalNameById(Integer x){
    Http http = new Http();
    HttpRequest req = new HttpRequest();
    req.setEndpoint('https://th-apex-http-callout.herokuapp.com/animals/' + x);
    req.setMethod('GET');
    Map<String, Object> animal= new Map<String, Object>();
    HttpResponse res = http.send(req);
    if (res.getStatusCode() == 200) {
        Map<String, Object> results = (Map<String, Object>)JSON.deserializeUntyped
(res.getBody());
        animal = (Map<String, Object>) results.get('animal');
    }
    return (String) animal.get('name');
}
}
```

2. AnimalLocatorTest.apxc

```
    @isTest
private class AnimalLocatorTest{
    @isTest static void AnimalLocatorMock1() {
        Test.setMock(HttpCalloutMock.class, new AnimalLocatorMock());
        string result = AnimalLocator.getAnimalNameById(3);
        String expectedResult = 'chicken';
        System.assertEquals(result, expectedResult );
    }
}
```

3.AnimalLocatorMock.apxc

```

    @isTest
    global class AnimalLocatorMock implements HttpCalloutMock {
        // Implement this interface method
        global HTTPResponse respond (HTTPRequest request) {
            // Create a fake response
            HTTPResponse response = new HTTPResponse();
            response.setHeader('Content-Type', 'application/json');
            response.setBody('{ "animals": ["majestic badger", "fluffy bunny", "scary bear",
"chicken", "mighty moose"]}');
            response.setStatusCode(200);
            return response;
        }
    }
}

```

3.Apex SOAP Callouts

1.ParkLocator.apxc

```

public class ParkLocator {
    public static String[] country(String country){
        ParkService.ParksImplPort parks = new ParkService.ParksImplPort();
        String[] parksname = parks.byCountry(country);
        return parksname;
    }
}

```

2.ParkLocatorTest.apxc

```

@isTest
private class ParkLocatorTest{
    @isTest
    static void testParkLocator() {
        Test.setMock(WebServiceMock.class, new ParkServiceMock());
        String[] arrayOfParks = ParkLocator.country('India');

        System.assertEquals('Park1', arrayOfParks[0]);
    }
}

```

```
}
```

3.ParkServiceMock.apxc

@isTest

global class ParkServiceMock implements WebServiceMock {

global void doInvoke(

Object stub,

Object request,

Map<String, Object> response,

String endpoint,

String soapAction,

String requestName,

String responseNS,

String responseName,

String responseType) {

ParkService.byCountryResponse response_x = new

ParkService.byCountryResponse();

List<String> lstOfDummyParks = new List<String> {'Park1','Park2','Park3'};

response_x.return_x = lstOfDummyParks;

response.put('response_x', response_x);

}

```
}
```

4.AsyncParkService.apxc

//Generated by wsdl2apex

public class AsyncParkService {

public class byCountryResponseFuture extends System.WebServiceCalloutFuture {

public String[] getValue() {

ParkService.byCountryResponse response =

(ParkService.byCountryResponse)System.WebServiceCallout.endInvoke(this);

return response.return_x;

}

}

public class AsyncParksImplPort {

```

        public String endpoint_x = 'https://th-apex-soap-
service.herokuapp.com/service/parks';
        public Map<String,String> inputHttpHeaders_x;
        public String clientCertName_x;
        public Integer timeout_x;
        private String[] ns_map_type_info = new String[]{'http://parks.services/',
'ParkService'};
        public AsyncParkService.byCountryResponseFuture
beginByCountry(System.Continuation continuation,String arg0) {
            ParkService.byCountry request_x = new ParkService.byCountry();
            request_x.arg0 = arg0;
            return (AsyncParkService.byCountryResponseFuture)
System.WebServiceCallout.beginInvoke(
                this,
                request_x,
                AsyncParkService.byCountryResponseFuture.class,
                continuation,
                new String[]{endpoint_x,
                ",
                'http://parks.services/',
                'byCountry',
                'http://parks.services/',
                'byCountryResponse',
                'ParkService.byCountryResponse'}
            );
        }
    }
}

```

4.Apex Web Services

1.AccountManager.apxc

```

        @RestResource(urlMapping='/Accounts/*/contacts')
global class AccountManager {
    @HttpGet
    global static Account getAccount() {
        RestRequest req = RestContext.request;
        String acctId = req.requestURI.substringBetween('Accounts/', '/contacts');
    }
}

```

```

        Account acc = [SELECT Id, Name, (SELECT Id, Name FROM Contacts)
                        FROM Account WHERE Id = :accId];
        return acc;
    }
}

```

2.AccountManagerTest.apxc

```

@isTest
private class AccountManagerTest {
    private static testMethod void getAccountTest1() {
        Id recordId = createTestRecord();
        // Set up a test request
        RestRequest request = new RestRequest();
        request.requestUri = 'https://na1.salesforce.com/services/apexrest/Accounts/'+
recordId + '/contacts';
        request.httpMethod = 'GET';
        RestContext.request = request;
        // Call the method to test
        Account thisAccount = AccountManager.getAccount();
        // Verify results
        System.assert(thisAccount != null);
        System.assertEquals('Test record', thisAccount.Name);
    }

    // Helper method
    static Id createTestRecord() {
        Account TestAcc = new Account (
            Name='Test record');
        insert TestAcc;
        Contact TestCon= new Contact(
            LastName='Test',
            AccountId = TestAcc.id);
        return TestAcc.Id;
    }
}

```

Apex Specialist

Step2 : Automate record creation

1.MaintenanceRequest.apxt

```
trigger MaintenanceRequest on Case (before update, after update) {  
    if(Trigger.isUpdate && Trigger.isAfter){  
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);  
    }  
}
```

2.MaintenanceRequestHelper.apxc

```
public with sharing class MaintenanceRequestHelper {  
    public static void updateWorkOrders(List<Case> updWorkOrders, Map<Id,Case>  
nonUpdCaseMap) {  
        Set<Id> validIds = new Set<Id>();  
        For (Case c : updWorkOrders){  
            if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){  
                if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){  
                    validIds.add(c.Id);  
                }  
            }  
        }  
    }  
}
```

//When an existing maintenance request of type Repair or Routine Maintenance is closed,

//create a new maintenance request for a future routine checkup.

```
if (!validIds.isEmpty()){  
    Map<Id,Case> closedCases = new Map<Id,Case>([SELECT Id, Vehicle__c,  
Equipment__c, Equipment__r.Maintenance_Cycle__c,  
                (SELECT Id,Equipment__c,Quantity__c FROM  
Equipment_Maintenance_Items__r)  
                FROM Case WHERE Id IN :validIds]);  
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();
```

//calculate the maintenance request due dates by using the maintenance cycle defined on the related equipment records.

```
AggregateResult[] results = [SELECT Maintenance_Request__c,
```



```

        MIN(Equipment__r.Maintenance_Cycle__c)cycle
        FROM Equipment_Maintenance_Item__c
        WHERE Maintenance_Request__c IN :ValidIds GROUP BY
Maintenance_Request__c];

```

```

        for (AggregateResult ar : results){
            maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
        }

```

```

List<Case> newCases = new List<Case>();
for(Case cc : closedCases.values()){
    Case nc = new Case (
        ParentId = cc.Id,
        Status = 'New',
        Subject = 'Routine Maintenance',
        Type = 'Routine Maintenance',
        Vehicle__c = cc.Vehicle__c,
        Equipment__c =cc.Equipment__c,
        Origin = 'Web',
        Date_Reported__c = Date.Today()
    );

```

```

        //If multiple pieces of equipment are used in the maintenance request,
        //define the due date by applying the shortest maintenance cycle to today's
date.

```

```

        //If (maintenanceCycles.containsKey(cc.Id)){
            nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
        //} else {
        //    nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipment__r.maintenance_Cycle__c);
        //}

```

```

        newCases.add(nc);
    }

```

```

insert newCases;

```

```

        List<Equipment_Maintenance_Item__c> clonedList = new
List<Equipment_Maintenance_Item__c>();
        for (Case nc : newCases){
            for (Equipment_Maintenance_Item__c clonedListItem :
closedCases.get(nc.ParentId).Equipment_Maintenance_Items__r){
                Equipment_Maintenance_Item__c item = clonedListItem.clone();
                item.Maintenance_Request__c = nc.Id;
                clonedList.add(item);
            }
        }
        insert clonedList;
    }
}
}

```

Step 3 :Synchronize Salesforce Data With an External Organization

1.WarehouseCalloutService.apxc

```

public with sharing class WarehouseCalloutService implements Queueable {
    private static final String WAREHOUSE_URL = 'https://th-superbadge-
apex.herokuapp.com/equipment';

```

//Write a class that makes a REST callout to an external warehouse system to get a list of equipment that needs to be updated.

//The callout's JSON response returns the equipment records that you upsert in Salesforce.

```

@future(callout=true)
public static void runWarehouseEquipmentSync(){
    System.debug('go into runWarehouseEquipmentSync');
    Http http = new Http();
    HttpRequest request = new HttpRequest();

    request.setEndpoint(WAREHOUSE_URL);
    request.setMethod('GET');
    HttpResponse response = http.send(request);

```

```

List<Product2> product2List = new List<Product2>();
System.debug(response.getStatusCode());
if (response.getStatusCode() == 200){
    List<Object> jsonResponse =
(List<Object>)JSON.deserializeUntyped(response.getBody());
    System.debug(response.getBody());

    //class maps the following fields:
    //warehouse SKU will be external ID for identifying which equipment records to
update within Salesforce
    for (Object jR : jsonResponse){
        Map<String,Object> mapJson = (Map<String,Object>)jR;
        Product2 product2 = new Product2();
        //replacement part (always true),
        product2.Replacement_Part__c = (Boolean) mapJson.get('replacement');
        //cost
        product2.Cost__c = (Integer) mapJson.get('cost');
        //current inventory
        product2.Current_Inventory__c = (Double) mapJson.get('quantity');
        //lifespan
        product2.Lifespan_Months__c = (Integer) mapJson.get('lifespan');
        //maintenance cycle
        product2.Maintenance_Cycle__c = (Integer)
mapJson.get('maintenanceperiod');
        //warehouse SKU
        product2.Warehouse_SKU__c = (String) mapJson.get('sku');

        product2.Name = (String) mapJson.get('name');
        product2.ProductCode = (String) mapJson.get('_id');
        product2List.add(product2);
    }

    if (product2List.size() > 0){
        upsert product2List;
        System.debug('Your equipment was synced with the warehouse one');
    }
}

```

```

    }
}

public static void execute (QueueableContext context){
    System.debug('start runWarehouseEquipmentSync');
    runWarehouseEquipmentSync();
    System.debug('end runWarehouseEquipmentSync');
}

}

```

Step 4 :Schedule Synchronization

1.WarehouseSyncSchedule.apxc

```

    global with sharing class WarehouseSyncSchedule implements Schedulable {
// implement scheduled code here
    global void execute (SchedulableContext ctx){
        System.enqueueJob(new WarehouseCalloutService());
    }
}

```

Step 5 : Test Automation Logic

1.MaintenanceRequest.apxt

```

trigger MaintenanceRequest on Case (before update, after update) {
    if(Trigger.isUpdate && Trigger.isAfter){
        MaintenanceRequestHelper.updateWorkOrders(Trigger.New, Trigger.OldMap);
    }
}

```

2.MaintenanceRequestHelper.apxc

```

    public with sharing class MaintenanceRequestHelper {
    public static void updateworkOrders(List<Case> updWorkOrders, Map<Id,Case>
nonUpdCaseMap) {
        Set<Id> validIds = new Set<Id>();

```

```

For (Case c : updWorkOrders){
    if (nonUpdCaseMap.get(c.Id).Status != 'Closed' && c.Status == 'Closed'){
        if (c.Type == 'Repair' || c.Type == 'Routine Maintenance'){
            validIds.add(c.Id);
        }
    }
}

```

//When an existing maintenance request of type Repair or Routine Maintenance is closed,

```

//create a new maintenance request for a future routine checkup.
if (!validIds.isEmpty()){
    Map<Id,Case> closedCases = new Map<Id,Case>([SELECT Id, Vehicle__c,
Equipment__c, Equipment__r.Maintenance_Cycle__c,
                (SELECT Id,Equipment__c,Quantity__c FROM
Equipment_Maintenance_Items__r)
                FROM Case WHERE Id IN :validIds]);
    Map<Id,Decimal> maintenanceCycles = new Map<ID,Decimal>();

```

//calculate the maintenance request due dates by using the maintenance cycle defined on the related equipment records.

```

AggregateResult[] results = [SELECT Maintenance_Request__c,
                MIN(Equipment__r.Maintenance_Cycle__c)cycle
                FROM Equipment_Maintenance_Item__c
                WHERE Maintenance_Request__c IN :ValidIds GROUP BY
Maintenance_Request__c];

```

```

for (AggregateResult ar : results){
    maintenanceCycles.put((Id) ar.get('Maintenance_Request__c'), (Decimal)
ar.get('cycle'));
}

```

```

List<Case> newCases = new List<Case>();
for(Case cc : closedCases.values()){
    Case nc = new Case (
        ParentId = cc.Id,
        Status = 'New',

```

```

        Subject = 'Routine Maintenance',
        Type = 'Routine Maintenance',
        Vehicle__c = cc.Vehicle__c,
        Equipment__c = cc.Equipment__c,
        Origin = 'Web',
        Date_Reported__c = Date.Today()
    );

    //If multiple pieces of equipment are used in the maintenance request,
    //define the due date by applying the shortest maintenance cycle to today's
date.
    //If (maintenanceCycles.containsKey(cc.Id)){
        nc.Date_Due__c = Date.today().addDays((Integer)
maintenanceCycles.get(cc.Id));
    //} else {
    //    nc.Date_Due__c = Date.today().addDays((Integer)
cc.Equipment__r.maintenance_Cycle__c);
    //}

    newCases.add(nc);
}

insert newCases;

List<Equipment_Maintenance_Item__c> clonedList = new
List<Equipment_Maintenance_Item__c>();
for (Case nc : newCases){
    for (Equipment_Maintenance_Item__c clonedListItem :
closedCases.get(nc.ParentId).Equipment_Maintenance_Items__r){
        Equipment_Maintenance_Item__c item = clonedListItem.clone();
        item.Maintenance_Request__c = nc.Id;
        clonedList.add(item);
    }
}
insert clonedList;
}
}

```

```
}
```

3.MaintenanceRequestHelperTest.apxc

```
@isTest
```

```
public with sharing class MaintenanceRequestHelperTest {
```

```
    // createVehicle
```

```
    private static Vehicle__c createVehicle(){
```

```
        Vehicle__c vehicle = new Vehicle__C(name = 'Testing Vehicle');
```

```
        return vehicle;
```

```
    }
```

```
    // createEquipment
```

```
    private static Product2 createEquipment(){
```

```
        product2 equipment = new product2(name = 'Testing equipment',
```

```
            lifespan_months__c = 10,
```

```
            maintenance_cycle__c = 10,
```

```
            replacement_part__c = true);
```

```
        return equipment;
```

```
    }
```

```
    // createMaintenanceRequest
```

```
    private static Case createMaintenanceRequest(id vehicleId, id equipmentId){
```

```
        case cse = new case(Type='Repair',
```

```
            Status='New',
```

```
            Origin='Web',
```

```
            Subject='Testing subject',
```

```
            Equipment__c=equipmentId,
```

```
            Vehicle__c=vehicleId);
```

```
        return cse;
```

```
    }
```

```
    // createEquipmentMaintenanceItem
```

```
    private static Equipment_Maintenance_Item__c createEquipmentMaintenanceItem(id  
equipmentId,id requestId){
```

```
        Equipment_Maintenance_Item__c equipmentMaintenanceItem = new  
Equipment_Maintenance_Item__c(
```

```

        Equipment__c = equipmentId,
        Maintenance_Request__c = requestId);
    return equipmentMaintenanceItem;
}

```

@isTest

```

private static void testPositive(){
    Vehicle__c vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

```

```

    Product2 equipment = createEquipment();
    insert equipment;
    id equipmentId = equipment.Id;

```

```

    case createdCase = createMaintenanceRequest(vehicleId,equipmentId);
    insert createdCase;

```

```

    Equipment_Maintenance_Item__c equipmentMaintenanceItem =
    createEquipmentMaintenanceItem(equipmentId,createdCase.id);
    insert equipmentMaintenanceItem;

```

```

    test.startTest();
    createdCase.status = 'Closed';
    update createdCase;
    test.stopTest();

```

```

Case newCase = [Select id,
                    subject,
                    type,
                    Equipment__c,
                    Date_Reported__c,
                    Vehicle__c,
                    Date_Due__c
                from case
                where status ='New'];

```

```

Equipment_Maintenance_Item__c workPart = [select id

```



```

        from Equipment_Maintenance_Item__c
        where Maintenance_Request__c =:newCase.Id];
list<case> allCase = [select id from case];
system.assert(allCase.size() == 2);

system.assert(newCase != null);
system.assert(newCase.Subject != null);
system.assertEquals(newCase.Type, 'Routine Maintenance');
SYSTEM.assertEquals(newCase.Equipment__c, equipmentId);
SYSTEM.assertEquals(newCase.Vehicle__c, vehicleId);
SYSTEM.assertEquals(newCase.Date_Reported__c, system.today());
}

```

@isTest

```

private static void testNegative(){
    Vehicle__C vehicle = createVehicle();
    insert vehicle;
    id vehicleId = vehicle.Id;

    product2 equipment = createEquipment();
    insert equipment;
    id equipmentId = equipment.Id;

    case createdCase = createMaintenanceRequest(vehicleId,equipmentId);
    insert createdCase;

    Equipment_Maintenance_Item__c workP =
createEquipmentMaintenanceItem(equipmentId, createdCase.Id);
    insert workP;

    test.startTest();
    createdCase.Status = 'Working';
    update createdCase;
    test.stopTest();

    list<case> allCase = [select id from case];

    Equipment_Maintenance_Item__c equipmentMaintenanceItem = [select id

```

```
from Equipment_Maintenance_Item__c
where Maintenance_Request__c = :createdCase.Id];
```

```
system.assert(equipmentMaintenanceItem != null);
system.assert(allCase.size() == 1);
}
```

```
@isTest
```

```
private static void testBulk(){
    list<Vehicle__C> vehicleList = new list<Vehicle__C>();
    list<Product2> equipmentList = new list<Product2>();
    list<Equipment_Maintenance_Item__c> equipmentMaintenanceItemList = new
list<Equipment_Maintenance_Item__c>();
    list<case> caseList = new list<case>();
    list<id> oldCaseIds = new list<id>();

    for(integer i = 0; i < 300; i++){
        vehicleList.add(createVehicle());
        equipmentList.add(createEquipment());
    }
    insert vehicleList;
    insert equipmentList;

    for(integer i = 0; i < 300; i++){
        caseList.add(createMaintenanceRequest(vehicleList.get(i).id,
equipmentList.get(i).id));
    }
    insert caseList;

    for(integer i = 0; i < 300; i++){

equipmentMaintenanceItemList.add(createEquipmentMaintenanceItem(equipmentList.
get(i).id, caseList.get(i).id));
    }
    insert equipmentMaintenanceItemList;

    test.startTest();
    for(case cs : caseList){
```

```

        cs.Status = 'Closed';
        oldCaseIds.add(cs.Id);
    }
    update caseList;
    test.stopTest();

    list<case> newCase = [select id
                        from case
                        where status ='New'];

    list<Equipment_Maintenance_Item__c> workParts = [select id
                                                    from Equipment_Maintenance_Item__c
                                                    where Maintenance_Request__c in: oldCaseIds];

    system.assert(newCase.size() == 300);

    list<case> allCase = [select id from case];
    system.assert(allCase.size() == 600);
}
}

```

Step 6 :Test Callout Logic

1.WarehouseCalloutServiceMock.apxc

```

    @isTest
    global class WarehouseCalloutServiceMock implements HttpCalloutMock {
        // implement http mock callout
        global static HttpResponse respond(HttpRequest request) {

            HttpResponse response = new HttpResponse();
            response.setHeader('Content-Type', 'application/json');

            response.setBody('{"_id":"55d66226726b611100aaf741","replacement":false,"quantity":5

```

```

,"name":"Generator 1000
kW","maintenanceperiod":365,"lifespan":120,"cost":5000,"sku":"100003"},{"_id":"55d66226
726b611100aaf742","replacement":true,"quantity":183,"name":"Cooling
Fan","maintenanceperiod":0,"lifespan":0,"cost":300,"sku":"100004"},{"_id":"55d66226726b6
11100aaf743","replacement":true,"quantity":143,"name":"Fuse
20A","maintenanceperiod":0,"lifespan":0,"cost":22,"sku":"100005"}]]);
    response.setStatusCode(200);

    return response;
}
}

```

2. WarehouseCalloutServiceTest.apxc

```

@IsTest
private class WarehouseCalloutServiceTest {
    // implement your mock callout test here
    @isTest
    static void testWarehouseCallout() {
        test.startTest();
        test.setMock(HttpCalloutMock.class, new WarehouseCalloutServiceMock());
        WarehouseCalloutService.execute(null);
        test.stopTest();

        List<Product2> product2List = new List<Product2>();
        product2List = [SELECT ProductCode FROM Product2];

        System.assertEquals(3, product2List.size());
        System.assertEquals('55d66226726b611100aaf741',
product2List.get(0).ProductCode);
        System.assertEquals('55d66226726b611100aaf742',
product2List.get(1).ProductCode);
        System.assertEquals('55d66226726b611100aaf743',
product2List.get(2).ProductCode);
    }
}

```

Step 7 :Test Scheduling Logic

1.WarehouseSyncScheduleTest.apxc

```
@isTest
public with sharing class WarehouseSyncScheduleTest {
    // implement scheduled code here
    //
    @isTest static void test() {
        String scheduleTime = '00 00 00 * * ? *';
        Test.startTest();
        Test.setMock(HttpCalloutMock.class, new
WarehouseCalloutServiceMock());
        String jobId = System.schedule('Warehouse Time to Schedule to test',
scheduleTime, new WarehouseSyncSchedule());
        CronTrigger c = [SELECT State FROM CronTrigger WHERE Id =: jobId];
        System.assertEquals('WAITING', String.valueOf(c.State), 'JobId does not match');

        Test.stopTest();
    }
}
```