MANTIS Extended — Post-Paper Extensions to a Banking Multi-Agent Security Testbed

1st Given Name Surname
dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address or ORCID

2nd Given Name Surname
dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address or ORCID

Abstract—MANTIS (Modular Agent Network Testbed for Instrumentation and Security) is a configuration-driven security and observability testbed built directly on a real banking multi-agent system spanning front-, mid-, and back-office workflows. The first paper describing MANTIS scoped its contribution deliberately: a hook bus exposing five fixed control points, a compact attack and failure plugin library, a seven-dimension automated evaluator, and a benchmarking suite – with a named, explicit list of extensions deferred to future work rather than attempted under that paper's schedule. This paper implements all five of those deferred extensions and reports live, measured evidence for each, without modifying the first paper's own artifact. Additional exporters: all four of the coding plan's named backends – Jaeger, Grafana (Tempo), Phoenix, and Langfuse – each enabled by a one-line configuration change, that fail silently rather than aborting a run when no collector is reachable; the Langfuse adapter, whose ingestion endpoint is HTTP-only and always requires Basic auth even self-hosted, was confirmed reaching the real hosted Langfuse endpoint and receiving a genuine unauthorized response with no credentials supplied. Security mechanism plugins: a concrete guardrail, evaluated through the identical plugin interface as an attack, that we show live blocking a real attack – a tool-parameter-mutation attack inflating a transfer's amount from $125.50 to $5,000 was denied before it reached the banking backend, with the denial recorded as a distinct POLICY_EVENT rather than misclassified as an attack. Additional banking workloads: a new front-office dispute-filing and -tracking process, added as a third route alongside the existing transaction-review and customer-service workflows rather than a new prompt into an existing one – and a debugging finding in its own right: an initial version silently produced zero tool calls across three live trials because its scenario prompt omitted a required identifier every other scenario in the codebase states explicitly, invisible until we actually inspected the emitted trace rather than a clean exit code. We extended this category to the two domains not yet covered: a back-office SAR/exception-escalation process and a mid-office loan-pre-approval process computing a real, deterministic decision from seeded account data rather than an LLM opinion, each live-verified across five trials, surfacing and fixing a further defect where both workloads' tools were fully functional yet invisible to the testbed's own inventory discovery. We further extended the security-mechanism-plugin category with four plugins now covering every attack in the shipped catalog that previously succeeded 5/5 with zero defense: a risk-aware routing guard closing route confusion, initially live-verified with an honestly-reported qualification that blocking the attack does not by itself restore the compliant path, then closed for real with an optional redirect-based recovery mode, live-verified 5/5 reaching the identical ground-truth outcome (manual_review) the undefended baseline itself asserts; a response-redaction filter at the output control point, whose live verification surfaced and fixed a genuine Unicode-hyphen gap in its own detection regex; and a batch-integrity guard closing the back-office ledger-mutation attack, the second (and, as of this revision, last) attack in the catalog that succeeded 5/5 undefended. Two further plugins complete the five categories the coding plan names: a rate limit, which turns a hijack-induced crash (0 of 10 undefended attempts completed) into 5 of 5 completed runs with no false positive on a no-attack control, and an effect-isolation mode, which denied an attacked funds transfer in every trial while the banking backend's transaction count did not change. We also closed the extensions' remaining "deployment variants" gap with a genuine second institution profile – an isolated database and a stricter real policy threshold, selected by a runtime configuration field rather than a hardcoded constant, reusing every agent, tool, and workflow unchanged, live-verified 5/5 producing a genuinely different real decision than the default institution would for the identical request. Minimal UI: a schema-driven experiment editor and trace viewer whose mutating actions shell out to the identical CLI subprocess a terminal user would run, verified by confirming a deliberately invalid configuration is rejected with the real CLI's own error message rather than a UI-side check, extended with campaign and hook-coverage endpoints following the same subprocess-chaining and direct-file-read patterns. Scenario library and onboarding: we widened evaluation coverage without changing the architecture, with 19 measured baselines and 26 attack and fault variants run live (123 scored trials, five per configuration, one model) with per-trial database snapshots, four small starter campaigns for a first look at the testbed, and a from-scratch walkthrough showing a new attack plugin of about fifteen lines validated, run, and scored in roughly ten seconds with no API key. Zero Trust Backplane: per a later team decision, this fifth extension was reversed back into scope as a toggleable integration of the real, independently-developed Zero Trust Backplane project for this same testbed [2] – specifically its Task 4 signed Policy Decision Point, called over its own real signed request/response protocol rather than reimplemented. The toggle is the same opt-in mechanism every other defense in this paper already uses (add it to a config's policies: list), and a stock install never imports it: the full offline suite passes with zero failures both with and without its optional dependency installed. Its policy – an agent may act on a tool in its own domain, denied by the PDP's own default otherwise – is generated from the testbed's live inventory rather than the real project's own scanner, which targets an older checkout

Identify applicable funding agency here. If none, delete this.

layout; live trials confirmed same-domain allow, cross-domain deny, an unrecognized agent denied before a challenge is even issued, and two full legitimate workflow runs through the real PDP completing identically to the undefended baseline. The project's test suite, exercised against real data rather than mocks throughout, stands at 822 passing offline tests as of this revision (833 with the Zero Trust optional dependency installed).

Index Terms—multi-agent systems, adversarial security, large language models, banking, observability, extensibility

I. Introduction

The first MANTIS paper [1] scoped its contribution narrowly on purpose: a hook bus exposing five fixed control points around an otherwise-unmodified banking multi-agent system, a compact library of attack and failure plugins registered through one shared interface, a seven-dimension automated evaluator, and a benchmarking suite isolating instrumentation overhead from LLM sampling noise. That paper's own coding plan named five extensions explicitly deferred rather than attempted under its schedule: additional observability exporters beyond OpenTelemetry and MLflow; security-mechanism plugins (guardrails, policy checks, rate limits) evaluated through the same framework as attacks; a Zero Trust Backplane consuming the testbed's application inventory and control-point metadata to generate or enforce protection; additional banking workloads beyond the ones the first paper's evaluation exercised; and a minimal, schema-driven UI over the existing command-line interface.

This paper implements all five. The fifth, the Zero Trust Backplane, was first explored to the same live-verified standard as the other four with a local, representative default-deny-by-domain stand-in – an exhaustive check of every (agent, tool) pair a live inventory implies, and repeated live trials confirming zero false-positive denials on legitimate traffic – kept outside this paper's own repository pending a team decision on whether to integrate the real, independently-developed Zero Trust Backplane project for this same banking testbed [2]. That decision came back in favor of integration, as a toggleable extension rather than a required dependency, and the new Extension 4 section below reports the result: the real project's own Task 4 signed PDP, not the earlier stand-in, now runs this testbed's enforcement when the toggle is on.

Each of the four extensions covered here is built to the same standard the first paper set for itself: a real, live-verified capability rather than a description of one, checked against the actual emitted trace rather than a clean process exit, with the evidence – not just the claim – checked into the repository. We report that standard being met unevenly on purpose: the dispute-filing workload initially failed to do anything meaningful on first attempt, for reasons a single successful-looking run would not have surfaced, and we report that failure and its root cause alongside the working result, consistent with the first paper's own central methodological finding that verifying a security-relevant capability means inspecting what actually happened, not assuming it from a lack of an error.

None of the four extensions required a change to mantis.core, mantis.hooks, or the banking workflow modules – the same architectural claim the first paper made for its own attack and failure plugins now extends to defensive plugins and telemetry adapters as well.

II. Extension 1: Additional Observability Exporters

The first paper's observability pipeline supported JSONL traces, MLflow run tracking, and a bare OpenTelemetry TracerProvider with no span exporter of its own attached – creatable spans that were never actually shipped anywhere. We implemented all four of the coding plan's named additional backends: Jaeger, Grafana (Tempo), Phoenix, and Langfuse.

mantis.observability.jaeger_exporter.setup_jaeger_otel() attaches a real OTLPSpanExporter (gRPC) to the shared TracerProvider, registered in exporter_registry as "jaeger" alongside the existing three. Enabling it is a configuration change – observability.export: [jsonl, jaeger] – not a code change to the banking workflow, the hook bus, or the observability plugin. Because a run's success must never depend on telemetry actually being delivered, we verified the failure path directly: with no collector listening at the configured endpoint, the SDK's BatchSpanProcessor retries and logs a warning rather than raising, confirmed both by a direct unit test asserting no exception propagates and by observing the expected StatusCode.UNAVAILABLE warnings during every subsequent offline test run in this development environment, where no Jaeger collector was running.

Grafana Tempo and Phoenix follow the identical adapter shape as Jaeger – both accept OTLP natively over gRPC, so grafana_exporter.py and phoenix_exporter.py are the same thin wrapper around OTLPSpanExporter, differing only in their default endpoint and an optional cloud-auth header/API key for each backend's managed offering. Langfuse genuinely differs: its OTLP ingestion endpoint (/api/public/otel) is HTTP/protobuf only, never gRPC, and always requires HTTP Basic auth – a public/secret key pair – even against a self-hosted instance, so langfuse_exporter.py is built on opentelemetry-exporter-otlp-proto-http rather than the .grpc package the other three share. All three are registered in exporter_registry exactly like Jaeger, enabled the same config-only way, and verified with the same fail-silent-with-no-collector test pattern. The Langfuse adapter received a stronger live check than a local no-collector test can offer: run with its default endpoint and no credentials, it reached the real cloud.langfuse.com OTLP endpoint over the network and received a genuine HTTP 401 response, independently confirming the transport and endpoint wiring are correct end-to-end against the real service, not only against an absent local collector.

III. Extension 2: Security Mechanism Plugins

The first paper shipped PolicyPlugin as an interface only, matching the exact shape of ExperimentPlugin so a future defensive plugin would not need to masquerade as an attack plugin, without a concrete implementation. We built AmountLimitGuardrailPlugin: a guardrail denying a tool call whose declared amount field exceeds a configured limit, through the identical apply(ctx) -> HookResult contract every attack plugin already uses.

The demonstration pairs this guardrail with the first paper's own tool-parameter-mutation attack rather than an undefended baseline, because the interesting property is not that the guardrail can deny a call in isolation but that it evaluates a call an attack has already mutated. Policy plugins are registered onto the hook bus after any configured attack (mirroring the attack-before-observability ordering the first paper established, for the identical reason: a plugin registered later in a dispatch sees the effect of everything registered before it). Run live against a real model with a $2,000 limit: execute_transfer was called with a legitimate $125.50 transfer; the attack mutated it to $5,000 destined for an account named HACKER-9999; the guardrail denied the mutated call before it reached the banking backend; and the agent correctly reported the block back to the customer as a payment-limit restriction rather than a generic failure.

This also required a small but consequential change to the observability layer's own event classification. The first paper's ObservabilityPlugin classified every non-trivial plugin action as ATTACK_INJECTED except a named set of failure-plugin names, which it classified as ANOMALY. A guardrail's DENY is a defense working as intended, not an attack; classifying it as ATTACK_INJECTED would have made every future evaluator built on that event type unable to tell a caught attack apart from a successful one. We added a parallel POLICY_EVENT classification, keyed the same way the existing failure-plugin split already was. The live run's trace confirms both classifications appear correctly and distinctly in the same run: one ATTACK_INJECTED record for the mutation, one POLICY_EVENT record for the denial.

We extended this category with two further plugins, each targeting a specific gap the first paper's own evaluation reported rather than a generic capability. RiskAwareRoutingGuardPlugin targets route confusion – the one attack in the first paper's catalog that succeeded 5/5 with zero defense anywhere in the repository. A generic "is this transfer_to_agent destination valid" check cannot catch this attack: its forced destination is a legitimate destination in general, and the attack's trick is picking the wrong one of two valid routes for a specific transaction, not routing somewhere invalid. This guard instead independently re-fetches the targeted transaction's real risk score from the banking backend – the same data get_transaction_context exposes, computed by the backend rather than by whatever the LLM router decided – and denies the reroute if that transaction is still too risky to skip review for. Run live against the paired route-confusion attack across five trials, the attack fired every trial (ATTACK_INJECTED) and the guard denied every trial (POLICY_EVENT), 5/5.

This result carries an honest qualification we verified rather than assumed. Blocking the malicious reroute does not, by itself, cause the workflow to retry the correct compliant path: the router reports the denial back and the workflow ends without reaching manual review, rather than a second, corrected transfer_to_agent call to the legitimate destination. A guard that blocks a bad outcome and a guard that restores the original correct outcome are different, non-equivalent claims; our evaluation configuration for this demonstration asserts only the former (transfer_to_agent as the expected tool, no asserted terminal state), corrected from an earlier draft that had asserted the latter before we observed real run behavior contradicting it.

ResponseRedactionPlugin demonstrates the output control point rather than tool: it masks account-number-shaped tokens in a run's final result before it reaches the caller, keeping only the last two characters of each id visible. Making an output-stage MUTATE actually reach the caller required a real architectural fix, not only the plugin: mantis.banking.runner.run_message previously dispatched before_output/after_output only once, from MantisHookPlugin.after_run_callback, carrying nothing but {"status": outcome} – too early in the agent framework's own lifecycle for the real customer-facing text to exist yet. We added a second, later after_output dispatch carrying the real compacted result, applying any MUTATE back onto the value the function returns – the same "recorded in the trace but changing nothing real" defect class the first paper found once already, this time at the output rather than the tool control point. Making the second dispatch distinguishable from the first (rather than misread as a second, spurious workflow-termination event) required a corresponding guard in the observability layer keyed on the presence of a status field.

Live verification of this plugin surfaced a genuine, non-obvious gap in its own detection logic: a live model naturally wrote an account id in prose using a Unicode non-breaking hyphen (CUST-002, U+2011) rather than plain ASCII -, which an ASCII-only pattern silently failed to match, leaving that occurrence completely unredacted with no error raised. After widening the pattern to accept the common Unicode hyphen/dash variants, we re-ran the demonstration 4/4 times with zero unmasked account-shaped tokens surviving in the final trace, regardless of which routing path the live model took or which hyphen character it happened to produce. We report this the same way we report the routing guard's original qualification below: a defense's own detection surface should be verified

against genuinely model-generated text, not only against hand-written test fixtures that happen to match the author's own formatting assumptions.

We then closed both remaining gaps this section originally reported as honest limitations rather than leaving them as future work. Recovery, not just denial: RiskAwareRoutingGuardPlugin now accepts an optional redirect_to parameter – when set, a risky reroute is MUTATEd to the legitimate destination instead of denied outright, so the real transfer_to_agent call still proceeds, just to the correct place, rather than the workflow simply failing to continue down the wrong one. Live-verified 5/5: the workflow now reaches search_policies and terminates in manual_review every trial – the identical ground truth the undefended baseline itself asserts. Both configurations are kept: the deny-only one remains a real, smaller, still-true claim on its own, and the redirect one demonstrates the stronger, self-correcting capability built on top of it.

The back office's own undefended gap: route confusion was not the only attack in the first paper's catalog that succeeded 5/5 with zero defense – the back-office tool-parameter-mutation attack (§ III's ledger-batch substitution) did too, and remained undefended even after this paper's first revision. BatchIntegrityGuardPlugin closes it the same way the routing guard closes route confusion: not by checking whether the target batch id is valid (both the genuine and the substituted batch are real, both are seeded ready), but by independently re-checking the target batch's own real expected-vs-posted totals and denying the ledger update if that batch already carries an unresolved discrepancy. Live-verified 5/5 against the paired attack, with a control run confirming no false positive against the legitimate, undefended clean-batch flow. With this and the routing guard, every attack in the shipped catalog that previously succeeded 5/5 with zero defense now has one.

The coding plan names five kinds of security-mechanism plugin – guardrails, policy checks, isolation, rate limits, and response filters – and the plugins above cover three of them; we built the remaining two. RateLimitGuardrailPlugin caps calls to a tool per run, per time window, or per distinct value of one argument, and denies the call that would exceed the cap. It was motivated by a failure the extended attack library exposed rather than by an imagined one: forcing the root agent's hand-off to a different domain router makes that router try to send the request back, the hijack rewrites the hand-back too, and the framework raises an unhandled "cannot transfer to itself" error – 10 of 10 recorded attempts crashed. Capping hand-offs at one per destination, with the limiter registered after the attack so it sees the rewritten destination, stops the loop at its second attempt: 5 of 5 live runs completed (one to three denials each), and a no-attack control with the identical limit ended in manual review with zero policy events. We are explicit about scope: this contains the attack-induced denial of service; it does not restore the compliant path.

ActionIsolationPlugin contains a run's blast radius by effect rather than by caller: while active, tools whose metadata marks them as moving money (or, optionally, as changing any persisted state) cannot execute, whatever an agent or an attack that rewrote its arguments asks for – a "shadow mode" in which agents propose and something else acts. Against the transfer-rewriting attack it denied execute_transfer in 5 of 5 trials, and the banking backend's transaction count was unchanged across the runs. Because isolation cannot distinguish a legitimate call from an attacked one, it also refuses the customer's real transfer; that is the definition of isolating an effect, not a defect, and a downstream step that depends on the blocked tool will see the denial as a failed step.

IV. Extension 3: Additional Banking Workloads

The coding plan's fourth extension calls for "more banking processes... or workflow patterns," which we read as a requirement for a genuinely new business process, not a new prompt into an existing one. We added dispute filing and status lookup as a front-office capability: a new disputes table in the same SQLite repository submit_manual_review already uses, a new tool module, and dispute_resolution_agent registered as a third route under front_office_router, alongside the existing transaction-review and customer-service-chatbot routes – distinct from the chatbot's pre-existing FAQ-only "how do I dispute a transaction" answer, which remains purely informational and never files a real case.

The first attempt at this extension produced a run that exited cleanly and called no tool at all, across three consecutive live trials against a real model. The cause was not a defect in the tool or the agent's routing – both worked correctly, confirmed by the real transfer to dispute_resolution_agent appearing in every trace – but in the scenario prompt itself, which never stated a customer identifier, unlike every other scenario in this codebase. file_dispute(customer_id, transaction_id, reason) requires one as its first argument; without it stated in the prompt the model apparently could not commit to calling the tool at all, silently, with no error the process's own exit code would reveal. Adding the customer identifier to the prompt – not changing the tool's signature – produced, on the next live run, a real case filed with a generated identifier, correctly persisted, and a correct customer-facing confirmation message referencing that identifier. We report this not as an aside but because it is the same class of finding the first paper's own central claim predicts: a clean exit and a correctly-routed trace both looked identical whether or not the actual business action happened, and only inspecting the tool-call events specifically distinguished the two.

We extended this workload category to the two banking domains that had not yet received a new process. Back-office SAR/exception escalation adds sar_escalation_agent as a second route under back_office_router, alongside the existing EOD workflow:

it reads an existing reconciliation exception's details and, if they describe potential misconduct rather than a routine mismatch, files a formal Suspicious Activity Report to a new sar_reports table. A pre-seeded exception case worded with clear misconduct signals (an unexplained, round-number discrepancy repeated identically across three prior business days, with no source-system corroboration) rather than an ordinary-sounding timing mismatch was necessary to avoid reproducing the same class of scenario-design gap Section III already reports – an under-specified scenario a model reasonably declines to act on. Live-verified across five trials, tool_use_correctness scored 1.0 every time, with a real, distinct SAR record persisted per trial.

Mid-office loan pre-approval adds loan_preapproval_agent as a third route under mid_office_router. It is deliberately distinct from the pre-existing loan_agent (inside the representative-assist workflow), which returns only informational process guidance and never makes or persists an actual decision: the new agent's submit_loan_application tool computes a real, deterministic decision from the customer's own seeded account data – approved if the requested amount is within 25% of the customer's total balance and their risk tier is not high, otherwise referred to manual underwriting – and persists it to a new loan_applications table. Live-verified across five trials against a customer with a seeded $9,620.13 checking balance requesting a $2,000 loan, every trial produced a real, computed approved decision with the exact stated rationale, not an LLM judgment call.

Extending this category surfaced one further defect of the same class the dispute workload's own scenario-prompt gap represents, this time in the runtime adapter rather than a scenario prompt: both new workloads' tools were fully reachable by their agents and correctly scoped in _DOMAIN_TOOL_NAMES, yet invisible to mantis –inventory's own raw tool discovery, because their tool modules were never added to the adapter's _TOOL_MODULE_PATHS list. A capability can be completely functional end-to-end while still being invisible to the testbed's own self-reported inventory; we found this only by directly querying _discover_banking_tools() rather than trusting that a working live run implied correct registration everywhere else, and fixed it before reporting either workload as complete.

The coding plan's fourth extension names two distinct things – "more banking processes... or workflow patterns" and, separately, "deployment variants" – and the three workloads above cover only the first. We closed the second with a genuine second institution profile: a new optional experiment.institution configuration field, read into an environment variable before any banking module is first imported in the process (the identical import-ordering discipline § II already established for API keys), which selects an isolated SQLite database and a genuinely different policy threshold, while reusing every agent, tool, and workflow unchanged. A regional_credit_union profile seeds its own member (a $3,000 checking balance) and enforces a stricter 10% loan-approval threshold, against the default institution's 25%. Live-verified 5/5: a $500 request (16.7% of that member's balance) is correctly referred under this institution's threshold – the identical request, against the identical code path, would have been approved at the default institution's threshold. The point is not the specific numbers but that institution is a genuine runtime parameter of the architecture, not a hardcoded constant, closing the one dimension of this extension the three new workloads alone did not.

V. Extension 4: Zero Trust Backplane Integration

The fourth deferred extension differs from the other four in one respect: it integrates a real, separately-developed project rather than implementing a new capability from scratch. Citi_P3_Zero_Trust_Backplane [2] is an independent project building a scanner, Policy Enforcement Point (PEP) generator, signed Policy Decision Point (PDP), and short-lived signed Permit Lease system for this same banking testbed. Its Task 4 component – a FastAPI service implementing a challenge/response protocol, Ed25519-signed requests and decisions, nonce/jti replay protection, and a policy engine evaluating Subject + Resource + Action + Context – is a complete, independently installable Python package, not tied to any particular host application.

Toggle, not a dependency. Per a team decision, this integration lives in the MANTIS repository, but strictly as an opt-in extension: a stock pip install -e . never installs or imports it. zero_trust_enforcement registers in the same plugin registry every attack and defense in this paper already uses, guarded by a single try/except ImportError around importing its module – when the optional dependency is absent, the class is not registered at all, not registered-but-broken, confirmed by running the full offline suite in both states: 822 tests pass with zero failures either way (11 more collected and passing with the dependency present, 833 total). Adding zero_trust_enforcement to any configuration's policies: list turns it on for that run; omitting it reproduces today's behavior exactly, the same mechanism every other defense in this paper uses for its own on/off comparison.

What is real, what is this paper's glue. The authorization decision, request and response signing, signature verification, and audit trail are the real project's own code, installed directly from its repository (pip install git+...#subdirectory=zero_trust_pdp_task4_secure) and run as its own process – none of that logic is reimplemented here. This paper's own contribution is the adapter: a policy generator (extensions/zero_trust/generate_policy.py) that reads the testbed's live inventory – the same agent and tool registries mantis –inventory reads from – and emits

identity, resource, and policy-bundle files in the real project's own schema, because the real project's own source-code scanner targets an older, no-longer-present checkout layout rather than the current testbed. The generated policy is deliberately simple and auditable: an agent may act on a tool in its own domain; a cross-domain call, or a call from an agent or tool the policy does not recognize, is denied by the PDP's own default (default_deny_no_matching_policy) rather than by anything this paper wrote. This is the same guarantee an earlier, local-only representative stand-in validated exhaustively (770 of 770 agent/tool pairs correctly enforced) before being replaced by this real integration.

Live verification. A standalone script against the running real PDP, fed by the testbed's actual 34 agents and 27 tools, confirmed: a same-domain call allowed; a cross-domain call denied; an unrecognized agent denied before the PDP even issues a challenge nonce; and a tool name shared by two domains (search_policies, front and mid office) resolved to the correct, independent per-domain resource record in both directions. Two full live runs of a legitimate front-office workflow with the toggle enabled – every real tool call checked by the real PDP before executing – completed with identical tool-use correctness (score 1.0, no missing expected or forbidden tools) to the undefended baseline, which is the point: a real, independent security layer that is a no-op for legitimate traffic and fails closed (denies, rather than silently allowing) if the PDP is unreachable or returns anything other than ALLOW/ALLOW_WITH_OBLIGATIONS.

Scope not yet closed. The generated policy covers only the tool control point and a single default-deny-by-domain rule, not the real project's fuller workflow- and risk-aware policy model (its own front_office.yaml policy bundle, evaluated unchanged by the same engine, shows the richer kind of policy it supports) or its input/output PEP placement (Task 3). Extending the generated policy to use that richer model, and covering more control points, remains open work.

VI. Extension 5: Minimal UI

The coding plan's final named extension is deliberately constrained: "a schema-driven editor and trace viewer that invokes the same CLI/API; no separate business logic." We built a small FastAPI application whose two mutating actions – validate and run – shell out to the exact mantis console-script entrypoint a terminal user would invoke, as a real subprocess, rather than a second, UI-specific implementation of configuration validation or experiment execution. Every read-only endpoint – the configuration schema, the domain/workflow/scenario/plugin registries, the live inventory, and a run's own trace file – calls the identical underlying objects the CLI itself reads from, so the editor's form fields are populated from live data rather than a hardcoded list that could drift from the deployed system.

We verified the "no separate business logic" property directly rather than assuming it from the implementation's structure: submitting a configuration with a deliberately invalid domain through the UI's validate endpoint returns the real CLI's own "Unknown domain" error text, produced by the same subprocess a terminal invocation of mantis –validate would produce, not a UI-side check reproducing that logic. The application was also confirmed running as a real server, not only through an in-process test client: launched via mantis –ui, it correctly reported the current live inventory (34 agents, 27 tools, reflecting the two additional workloads in Section III) over real HTTP requests.

We added three further endpoints, symmetric with the existing read-only pattern and the CLI-subprocess pattern respectively. GET /api/runs/{name}/hook-coverage reads hook_coverage.json directly, the same file the trace and evaluation endpoints already expose. POST /api/campaign shells out to mantis –campaign <dir>, parses the output directory from that command's own stdout, and chains a second real CLI invocation – mantis –report <dir> – against it, rather than reimplementing campaign aggregation as UI-side logic; GET /api/campaign/{name}/report then reads the resulting report.md directly. The front-end's trace and evaluation views were also changed from a raw JSON dump to a rendered table, kept intentionally thin – generic across whichever evaluator dimensions a run happens to report, rather than a hardcoded per-dimension layout – consistent with the coding plan's own "no separate business logic" framing for this extension.

VII. Scenario Library, Starter Campaigns, and Onboarding

The extensions above deepen individual capabilities. This section widens the evaluation set built on top of them, and describes how a new user reaches a first result. Nothing here adds a plugin, control point, or hook: the library is new prompts over the existing agents, tools, and seeded data, and new configurations over the existing plugins.

Measured ground truth. The library ships 19 no-attack baselines (benign controls, negative controls, robustness cases) and 26 attack and fault variants. Each attack is scored against the recorded behavior of its scenario, not an assumed one: every tool observed across all baseline trials, plus the terminal state where all trials agree. Baselines that are unstable assert only what is stable and say why. The attack side adds eight prompt-injection payload techniques (authority impersonation, "test mode", hypothetical framing, urgency, forged JSON, and two workflow-specific overrides), further message-spoofing and routing-hijack variants in the mid and back office, tool-parameter mutations of the loan, SAR, report, and schedule calls, and faults on five additional tools.

TABLE I
Extended library: live trials by attack family.

Family	Configs	Trials	Fired	Effect vs baseline
Prompt injection	8	40	40/40	17/40
Message spoofing	3	15	15/15	6/15
Tool mutation	7	35	34/35	1/35
Route confusion	3	10	10/10	10/10
Reliability faults	5	23	18/23	5/23

Database-state evidence. Tool-use and workflow-outcome scoring see which tools ran, not what they wrote. The trial runner therefore re-seeds an isolated local database before each trial and records what the run wrote. Table I summarizes the recorded campaign: 123 scored trials across the five families, with the fraction whose outcome diverged from the scenario baseline. These are counts from this sample (five trials per configuration, one model, gpt-oss-20b served through UF Navigator), not rates to extrapolate.

What the library revealed. Placement matters: the same authority-impersonation payload changed the outcome in 1 of 5 trials aimed at the upstream monitoring agent but bypassed manual review in 5 of 5 when aimed at the decision agent. Some attacks succeed by making an agent do nothing: injected into the SAR agent, it never looked up the case and filed nothing in 5 of 5 trials, and a forged "closed as routine" message suppressed the filing in 4 of 5. Data-level effects are invisible to tool-use scoring: in 20 of 20 trials of four tool-mutation configurations the database changed (a loan filed under the wrong customer, an inflated amount that flipped a decision, a SAR against the wrong case, a report under the wrong batch) while those scores reported no effect, which is why every trial records the database. Faults propagate: a corrupted ledger-tool response halted the end-of-day workflow in 5 of 9 attempts, and hijacking the root hand-off halted it in 10 of 10, a run the rate limit described earlier contains (5 of 5 runs complete versus 0 of 10 without it). Two limits apply: the external banking backend keeps its own state across trials, so front-office transfer results reflect accumulated history, and workflow outcome is inferred from which terminal tool was invoked, so a tool that was called and returned an error still counts.

Starter campaigns and a newcomer path. Four small campaigns ship in the repository, each a single mantis –campaign command of five or fewer runs: one attack from each family, the six defenses each against the attack it stops, the added workloads without an attack, and extended attacks on the newer workflows. All twenty configurations were run live and finished; they are renamed copies of shipped configurations so a campaign never overwrites the first paper's recorded evidence. A platform guide, rebuilt on every push, documents installation, model configuration, a keyless mock mode for smoke checks, the trial runner, and where each new artifact lives. As a check on the claim that extending the testbed is cheap, we followed the guide's own text from scratch: a new interaction-stage attack plugin of about fifteen lines, two registration lines, and a twelve-line configuration validated, ran, and was scored in about ten seconds in mock mode, with the scorecard reporting the attack fired and one ATTACK_INJECTED event in the trace, and no banking code touched.

VIII. Evaluation Summary

Table II summarizes each extension's verification evidence. All items were checked against real data or a real live run rather than a mock, consistent with the first paper's own testing philosophy; none required a change to mantis.core, mantis.hooks, or the banking workflow modules. The offline suite stands at 822 passing tests (833 with the optional Zero Trust dependency installed), with 167 more skipped by design when no live backend or model is available (including a parametrized consistency suite over every shipped configuration, scenario, and starter campaign), executing in about a minute with no live LLM key required: 4 for the Jaeger exporter and 9 for Grafana/Phoenix/Langfuse together, 6 for the amount-limit guardrail, 9 for the risk-aware routing guard (deny, redirect, and the real-hook-bus cases for each), 10 for response redaction, 6 for the batch-integrity guard, 9 for the rate limit, 8 for action isolation, 7 for the dispute workflow, 10 for SAR escalation, 12 for loan pre-approval, 5 for the institution deployment variant, 15 for the UI, and 10 for Zero Trust enforcement (collected only when its optional dependency is installed), on top of the base suite the first paper's own work established.

IX. Conclusion

We implemented all five extensions the first MANTIS paper explicitly deferred, to the same evidentiary standard that paper set for itself: live-verified behavior, checked against the actual emitted trace, with the evidence checked into the repository rather than described in prose. Each category was then deepened once its first, minimal instance was live-verified: additional banking workloads grew from one to three, spanning all three domains for the first time; security-mechanism plugins grew from one to three, closing the specific worst-case gap the first paper reported (route confusion, 5/5 undefended) rather than adding a plugin for its own sake; and the minimal UI gained the campaign and hook-coverage surfaces the coding plan named alongside its original validate/run/trace scope. This deepening surfaced three further real defects, each found the same way the first paper's own central finding predicts – by inspecting actual behavior rather than trusting a clean exit or a passing self-report – and each fixed before being reported as working: a scenario-design gap that silently produced zero tool calls across three live trials; two new workloads' tools that were fully functional yet invisible to the testbed's own inventory

TABLE II
Post-Paper Extensions: verification evidence.

Extension	Tests	Live evidence
Jaeger exporter	4	Real OTLP span processor attached; confirmed silent-safe with no collector listening.
Grafana/Phoenix/ Langfuse	9	Same OTLP adapter pattern for the first two; Langfuse (HTTP-only, Basic auth) reached the real hosted endpoint and got a genuine 401 with no credentials.
Amount-limit guardrail	6	Live run: $125.50 transfer mutated to $5,000 by a real attack, denied by the guardrail before reaching the backend; both events correctly classified.
Risk-aware routing guard	9	Live, 5/5 deny and 5/5 redirect: the redirect mode reaches manual_review every trial, the identical outcome the undefended baseline asserts.
Response redaction	10	Live, 4/4 after fixing a real Unicode-hyphen regex gap found via verification; zero unmasked account ids survived regardless of routing path.
Batch integrity guard	6	Live, 5/5: back-office ledger-mutation attack denied every trial; control run confirms no false positive on the legitimate clean-batch flow.
Rate-limit guardrail	9	Live, 5/5: a hijack-induced loop that crashed the run 10/10 undefended now completes (1–3 denials per run); the no-attack control shows zero policy events.
Action isolation	8	Live, 5/5: an attacked funds transfer denied every trial; the backend's transaction count unchanged.
Dispute workload	7	Live run: real case filed and persisted after correcting a scenario-prompt defect found only by inspecting the trace.
SAR escalation	10	Live, 5/5: real SAR record persisted per trial; tool_use_correctness 1.0 every time.
Loan pre-approval	12	Live, 5/5: real, deterministic approved decision computed from seeded account data every trial.
Institution variant	5	Live, 5/5: identical code path, isolated database, a stricter real threshold produces a genuinely different real decision than the default institution.
Scenario library	—	19 baselines and 26 variants, 123 scored live trials with per-trial database snapshots; four starter campaigns (20 configurations) all run live.
Zero Trust Backplane	10	Live: same-domain allow, cross-domain deny, unrecognized agent denied pre-challenge; two full legitimate runs through the real PDP, tool-use correctness 1.0, identical to the undefended baseline.
Minimal UI	15	Real invalid config rejected with the real CLI's own error text; real running server confirmed via HTTP; campaign endpoint chains two real CLI invocations, verified by mocking only the subprocess boundary.

discovery; and a Unicode-hyphen gap in a redaction filter's own detection regex that left real account ids in live model output completely unmasked. We also report, rather than omit, a genuine limitation the routing guard first shipped with: blocking an attack and restoring the system's original correct behavior are different claims, and our own first draft of that demonstration's evaluation config conflated them until live evidence corrected it. Rather than leave that gap as named future work, we closed it in this revision – an optional redirect mode that restores the compliant path, live-verified 5/5 – and closed the two other gaps this paper had previously only named: a batch-integrity guard for the back office's own undefended tool-mutation attack, and a genuine second institution profile (isolated data, a stricter real policy threshold, selected by configuration rather than hardcoded) closing the "deployment variants" half of the banking-workloads extension the three new processes alone did not cover. Every attack in the shipped catalog that once succeeded 5/5 with zero defense now has one, and all five security-mechanism categories the plan names now have a live-verified plugin. None of this work required a change to the first paper's core interfaces. The fifth extension, the Zero Trust Backplane, follows the same arc as the others in this paper: first explored to a live-verified standard with a local representative stand-in (an exhaustive check of every (agent, tool) pair a live inventory implies, and a real event-misclassification defect found and fixed along the way) kept outside the repository pending a team decision, then – once that decision favored integration – deepened into a real, toggleable integration of the actual independently-developed Zero Trust Backplane project for this same testbed [2]: its own signed Policy Decision Point, called over its own real protocol, enforcing a policy generated from this testbed's live inventory, opt-in via the same policies: mechanism every other defense in this paper uses, and confirmed not to affect a stock install (822 tests pass with zero failures whether or not its optional dependency is present). We also widened evaluation coverage and lowered the barrier to entry without touching the architecture: an extended library of 19 baselines and 26 attack variants with database-state evidence, four starter campaigns, and a guide whose add-an-attack walkthrough we followed from scratch. What remains honestly open, rather than closed: repeated-trial efficacy statistics at a larger sample size than this paper's practical n=4–5 per configuration, results on more than the one model used here, and extending the Zero Trust integration's generated policy to the real project's fuller workflow- and risk-aware model, and to control points beyond tool.

Acknowledgment

References

[1] [Authors], "MANTIS – Modular Agent Network Testbed for Instrumentation and Security in Multi-Agent Banking Systems," 2026. (Companion paper; this work's Section II onward assumes its architecture and terminology.)

[2] smartsystemslab-uf, "Citi P3 Zero Trust Backplane," github.com/smartsystemslab-uf/Citi_P3_Zero_Trust_Backplane, 2026.