



SKID STEER LOADER

CE ISO EPA EURO 5 SGS TÜV YF380

(803)857-1929



Optional configuration
ENGINE



2285*810*1270MM
OVERALL SIZE



880KG
OPERATING WEIGHT



Three-pump three-
valve system
HYDRAULIC SYSTEM

PARAMETER	METRIC	U.S.
Max working height	2100mm	82.7in
Max pin height	1880mm	74.01 in
Max Dumping height	1480mm	58.26 in
Max Dumping distance	430mm	16.92 in
Max Dumping Angle	30°	30°
Rollback of bucket on ground	25°	25°
Departure angle	27°	27°
Total height	1270mm	50 in
Ground clearance	110mm	4.33in
Wheel base	760mm	29.92in
Overall length without bucket	1782mm	70.15 in
Total width	810mm	31.88in
Bucket width	1090 mm	42.91 in
Total length with bucket	2285 mm	89.96 in
Turn radius forward turning	1300mm	51.18in
Overall length without the bucket after folding the pedal	1570mm	61.81 in

ENGINE	METRIC	U.S.
Rated Power (KW)	18.2KW(23HP)	
Rotating speed (rpm)	3600	
Noise (DB)	≤95	
Hydraulic System		
Pressure (MPa)	17	
WORKING TIME(S)		
Raise	4	
Dump	1.3	
Lower	3.2	
Operating Load	280kg	617 lbs
Bucket Capacity	0.13 m³	4.59 ft³
Max Lifting Force	458Kg	1009Lb
Travel Speed	0-5.5Km/h	3.5 mlie/h
Operating Weight	880kg	1940 lbs

