

Applet : Applet are small java programs that are primarily used in internet computing. They can be transported over the internet from one computer to another and run using the Applet viewer or any web browser that supports Java. An applet, like any application program, can do many Things for us. It can perform arithmetic operations, display graphics, play sounds, accept user input, create animation, and play interactive games.

We can embed applets into web pages in two ways. One, we can write our own applets and embed them into web pages. Second, we can download an applet from a remote computer system and then embed it into a web pages.

When we need something dynamic to be included in the display of a web page. For example, an applet that displays daily sensitivity index would be useful on a page that lists share prices of various companies or an applet that displays a bar chart .

Way to use Applet :

1. Building an applet code (.java file)
 2. Creating an executable applet(.class file)
 3. Designing a web page using HTML tags
 4. preparing <APPLET> tag
 5. Incorporating <APPLET> tag into the web page
 6. Create HTML file
 7. Testing the applet code
-

Building The Applet Code :

```
import java.awt.*;
import java.applet.*;
public class appletclass extends Applet
{
    public void paint(Graphics g)
    {
        //applet operation code;
    }
}
```

APPLET TAG :

```
<applet code="" width=300 height=400></applet>
```

Limitations of awt : (abstract window toolkit) :

because of platform dependent and heavy weight it is not in use today. At the place of awt, swing class is used.

Life cycle of applet :

1. initialization state(at the time of making applet)

```
public void init()  
{  
  
  
}
```

2. Running state(at the time of applet is being start to run)

```
public void start()  
{  
  
  
}
```

3. Idle or stopped state(at the time of applet is stopped)

```
public void stop()  
{  
  
  
}
```

4. dead state(at the time of applet is destroyed)

```
public void destroy()  
{  
  
  
}
```

5. Display state(Applet moves to display state whenever it has to perform some output operations on the screen)

```
public void paint(Graphics g)
{

}
```

