

Decision-Tree for Classification

MACHINE LEARNING WITH TREE-BASED MODELS IN PYTHON



Elie Kawerk
Data Scientist

Course Overview

- **Chap 1:** Classification And Regression Tree (CART)
- **Chap 2:** The Bias-Variance Tradeoff
- **Chap 3:** Bagging and Random Forests
- **Chap 4:** Boosting
- **Chap 5:** Model Tuning


Classification-tree

- Sequence of if-else questions about individual features.
- **Objective:** infer class labels.
- Able to capture non-linear relationships between features and labels.
- Don't require feature scaling (ex: Standardization, ..)

Breast Cancer Dataset in 2D



Decision-tree Diagram



Classification-tree in scikit-learn

```
# Import DecisionTreeClassifier
from sklearn.tree import DecisionTreeClassifier

# Import train_test_split
from sklearn.model_selection import train_test_split

# Import accuracy_score
from sklearn.metrics import accuracy_score

# Split the dataset into 80% train, 20% test
X_train, X_test, y_train, y_test= train_test_split(X, y,
                                                    test_size=0.2,
                                                    stratify=y,
                                                    random_state=1)

# Instantiate dt
dt = DecisionTreeClassifier(max_depth=2, random_state=1)
```

Classification-tree in scikit-learn

```
# Fit dt to the training set
dt.fit(X_train, y_train)

# Predict the test set labels
y_pred = dt.predict(X_test)


# Evaluate the test-set accuracy
accuracy_score(y_test, y_pred)
```

```
0.90350877192982459
```



Decision Regions

Decision region: region in the feature space where all instances are assigned to one class label.

Decision Boundary: surface separating different decision regions.



Decision Regions: CART vs. Linear Model



Let's practice!

MACHINE LEARNING WITH TREE-BASED MODELS IN PYTHON

Classification-Tree Learning

MACHINE LEARNING WITH TREE-BASED MODELS IN PYTHON



Elie Kawerk
Data Scientist

Building Blocks of a Decision-Tree


- **Decision-Tree:** data structure consisting of a hierarchy of nodes.
- **Node:** question or prediction.

Building Blocks of a Decision-Tree


Three kinds of nodes:

- **Root:** *no* parent node, question giving rise to *two* children nodes.
- **Internal node:** *one* parent node, question giving rise to *two* children nodes.
- **Leaf:** *one* parent node, *no* children nodes --> *prediction*.

Prediction



Information Gain (IG)



Information Gain (IG)

$$IG(\underbrace{f}_{\text{feature}}, \underbrace{sp}_{\text{split-point}}) = I(\text{parent}) - \left(\frac{N_{\text{left}}}{N} I(\text{left}) + \frac{N_{\text{right}}}{N} I(\text{right}) \right)$$

Criteria to measure the impurity of a node $I(\text{node})$:

- gini index,
- entropy. ...

Classification-Tree Learning

- Nodes are grown recursively.
- At each node, split the data based on:
 - feature f and split-point sp to maximize $IG(\text{node})$.
- If $IG(\text{node}) = 0$, declare the node a leaf. ...

```
# Import DecisionTreeClassifier
from sklearn.tree import DecisionTreeClassifier
# Import train_test_split
from sklearn.model_selection import train_test_split
# Import accuracy_score
from sklearn.metrics import accuracy_score
# Split dataset into 80% train, 20% test
X_train, X_test, y_train, y_test= train_test_split(X, y,
                                                    test_size=0.2,
                                                    stratify=y,
                                                    random_state=1)

# Instantiate dt, set 'criterion' to 'gini'
dt = DecisionTreeClassifier(criterion='gini', random_state=1)
```

Information Criterion in scikit-learn

```
# Fit dt to the training set
dt.fit(X_train,y_train)

# Predict test-set labels
y_pred= dt.predict(X_test)

# Evaluate test-set accuracy
accuracy_score(y_test, y_pred)
```

```
0.92105263157894735
```

Let's practice!

MACHINE LEARNING WITH TREE-BASED MODELS IN PYTHON

Decision-Tree for Regression

MACHINE LEARNING WITH TREE-BASED MODELS IN PYTHON




Elie Kawerk
Data Scientist

Auto-mpg Dataset

	mpg	displ	hp	weight	accel	origin	size
0	18.0	250.0	88	3139	14.5	US	15.0
1	9.0	304.0	193	4732	18.5	US	20.0
2	36.1	91.0	60	1800	16.4	Asia	10.0
3	18.5	250.0	98	3525	19.0	US	15.0
4	34.3	97.0	78	2188	15.8	Europe	10.0
5	32.9	119.0	100	2615	14.8	Asia	10.0

Auto-mpg with one feature



Regression-Tree in scikit-learn

```
# Import DecisionTreeRegressor
from sklearn.tree import DecisionTreeRegressor
# Import train_test_split
from sklearn.model_selection import train_test_split
# Import mean_squared_error as MSE
from sklearn.metrics import mean_squared_error as MSE
# Split data into 80% train and 20% test
X_train, X_test, y_train, y_test= train_test_split(X, y,
                                                    test_size=0.2,
                                                    random_state=3)

# Instantiate a DecisionTreeRegressor 'dt'
dt = DecisionTreeRegressor(max_depth=4,
                           min_samples_leaf=0.1,
                           random_state=3)
```


Regression-Tree in scikit-learn

```
# Fit 'dt' to the training-set
dt.fit(X_train, y_train)
# Predict test-set labels
y_pred = dt.predict(X_test)
# Compute test-set MSE
mse_dt = MSE(y_test, y_pred)
# Compute test-set RMSE
rmse_dt = mse_dt**(1/2)
# Print rmse_dt
print(rmse_dt)
```

```
5.1023068889
```

Information Criterion for Regression-Tree



$$I(\text{node}) = \underbrace{\text{MSE}(\text{node})}_{\text{mean-squared-error}} = \frac{1}{N_{\text{node}}} \sum_{i \in \text{node}} (y^{(i)} - \hat{y}_{\text{node}})^2$$

$$\underbrace{\hat{y}_{\text{node}}}_{\text{mean-target-value}} = \frac{1}{N_{\text{node}}} \sum_{i \in \text{node}} y^{(i)}$$

Prediction

$$\hat{y}_{pred}(\text{leaf}) = \frac{1}{N_{\text{leaf}}} \sum_{i \in \text{leaf}} y^{(i)}$$

Linear Regression vs. Regression-Tree



Let's practice!

MACHINE LEARNING WITH TREE-BASED MODELS IN PYTHON