

Frontend Audit — Sep 2026

2026-09-18 · @Someone

The monthly-commission frontend (`main` at d75592f) builds and typechecks clean. The reference-data pages are solid and well specified; the commission workflow itself does not exist yet, and the pages that feed it disagree with each other in a few places. Everything below is design and logic, not compile errors.

Top view

What is here: a well-built reference-data app (Agents, Carriers, Contracts, Logins, Users, Agency) with consistent server-only data boundaries, automatic change notes, and a thorough spec in `docs/entity-page-pattern.md`.

What is not here: the commission workflow the repo is named for. `Overview` renders a fake matrix from `lib/commissions.ts`, which has its own carrier list keyed by codes (`HUMANA`, `UHC`) that never touches `data/carriers.json` IDs. `Rulebook` is an empty state. Nothing imports a statement or matches rows to agents. The matching keys were clearly designed for that step (agent `aliases` “seen on statements”, login `writingNumber`) but nothing consumes them. Two carrier models exist today, `Carrier {code, name}` and `CarrierRecord {id, ...}`, and they will have to be reconciled before statements land.

The operational flow (add agent → licence states → carrier footprint → appointment → login) exists, but the user has to discover the order:

Step	What breaks
Carrier footprint	The appointment dialog blocks with “Add its states on Carriers before...” and no link; in-progress work is lost on navigation.
Appointment entry points	Agent profile has Add carrier ; carrier profile has no Add agent . By-state’s Add contract ignores the selected state.

Step	What breaks
Appointment → login	Neither Contracts page shows whether a login exists. “Appointed but no login” is computed only inside one agent’s profile (<code>pendingItems</code>). No agency-wide to-do view.
By-state map	Shows who <i>can</i> write, never who is <i>missing</i> (carriers available in TX with no agent, agents licensed in TX with no appointment).
Inactive agents	Deactivating an agent silently removes their contracts from both Contracts pages, with no “include inactive” toggle.

Logic disruptions (verified)

- Dialog closes on inside clicks.** `components/modal-dialog.tsx:41` now has `p-6`, but every form still carries its own `p-6` (`agent-dialog.tsx:199`, `agency-dialog.tsx:171`, `appointment-dialog.tsx:290`, `user-dialog.tsx:218`, `carrier-dialog.tsx:200`). The backdrop handler (`event.target === event.currentTarget`) fires on the 24px ring inside the dialog. Regression from commit `6212bf4`. Doc §8 still documents `p-0` and `max-w-lg`.
- Inactive agents follow three different rules.** Both Contracts pages drop them server-side (`contracts/page.tsx:28`, `by-carriers/page.tsx:25`). The carrier profile shows them (`carriers/[id]/page.tsx:42`). The agent profile lets you **appoint** one (`agent-profile.tsx:406`), creating a contract no Contracts page can show or edit. Humana reads “5 agents” on its profile and “4/4” on by-carriers.
- “Appointed” means different things on the two Contracts pages.** By-state counts agents with at least one *writable* state (`contracts-view.tsx:217`); by-carriers counts any contract row (`carrier-contracts-view.tsx:150`). Contract 13 (`appointedStates: []`) earns HealthSpring a 1/4 card while adding nothing to the map.
- `data/users.json` breaks its own rules.** User 1 has `role: "agent"` and no `agentId`; the loader does not warn, and Edit cannot save him without linking an agent that does not exist. Users 5 and 6 carry `agentId` on non-agent roles and are dropped **silently** (`lib/users.ts:97`). `data/user-notes.json` describes a different users list (wrong emails, wrong statuses).

5. **Users edits never reach the session.** `UsersView` keeps users in React state; `getSessionUser` and the login page re-read JSON. Marking a user inactive or changing a password has no effect on sign-in. Expected at dummy stage, but nothing in the UI says so beyond the generic banner.
6. **Appointment edit lets agent and carrier change** (`appointment-dialog.tsx:310-350`), reassigning a contract's identity while keeping its ID and note history. The by-carriers hidden-row notice checks only the *new* carrier.
7. **Entity dialogs disagree on validation.** `saveAgent` returns one error at a time (NPN, then licence numbers); `saveCarrier` returns all at once. Carrier **alias** uniqueness is never checked, only the name, though `lib/carriers.ts:35` says both. Save-result shapes differ across `saveAgent` / `saveCarrier` / `saveAgency` although the doc says they match.
8. **Smaller.** Agent switcher goes stale on rename (`agent-profile.tsx:232` keeps server order; the carrier one re-sorts). Carrier profile keeps two copies of the record in state (`carrier-profile.tsx:87-88`). Licence-number note diff is order-dependent and records the whole list for one changed number. `agencyLicenseNumbers` is shown on the by-state panel as a bare unlabelled number, contradicting the doc's "not a participant in contracts". Orphan contracts (unknown carrier ID) are fabricated on by-state and dropped on by-carriers.

Duplication

Roughly 600–800 lines could go. The pattern, not one-offs:

What	Where	Size
<code>agency-dialog.tsx</code> is a copy of <code>agent-dialog.tsx</code> with org labels	<code>agency/agency-dialog.tsx</code> vs <code>agents/agent-dialog.tsx</code>	~230 lines
Profile page markup: name row, header card, 3-column entity table, logins table, notes wrapper, <code>PANEL_BUTTON_CLASS</code>	<code>agent-profile.tsx</code> , <code>carrier-profile.tsx</code> , <code>agency-profile.tsx</code>	~150 lines × 3
Hydration-gated notes list	<code>agent-notes.tsx</code> , <code>carrier-notes.tsx</code> , inline <code>AgencyNotes</code>	15 lines × 3
Entity switcher	<code>agent-switcher.tsx</code> , <code>carrier-switcher.tsx</code>	50 lines × 2

What	Where	Size
Logins dialog and save kept inline while Users/Agents/Carriers extracted theirs	<code>logins-view.tsx:254-334, 414-561</code>	~240 lines
Contracts: <code>saveContract</code> wrapper, lookup closures, <code>contract → {agent, carrier, writable}</code> derivation	<code>contracts-view.tsx</code> , <code>carrier-contracts-view.tsx</code> , <code>agent-carrier-list.tsx</code> , both profiles	~150–200 lines
Unsaved banner	9 files	8 lines × 9
<code>byName</code> comparator	9 files	—
<code>initials()</code>	<code>profile-shell.tsx</code> , <code>fake-session.ts</code> , <code>agent-carrier-list.tsx</code> , <code>carrier-contracts-view.tsx</code>	× 4
<code>AgentOption</code> type in 3 different shapes	5 files	—
Expand chevron SVG and 20×20 icon boilerplate	8 files; <code>credential-value.tsx</code> already has a private <code>Icon</code> wrapper	—
Icon-button class string not in <code>classes.ts</code>	<code>navbar.tsx</code> , <code>theme-toggle.tsx</code> , <code>app-shell.tsx</code> , <code>credential-value.tsx</code>	× 4

Extractions that pay off: a `ProducerForm` (agent + agency), profile-shell header/table pieces, `HydratedNoteList`, `EntitySwitcher`, a `useAppointments` hook, `LoginDialog`, and `byName` / `initials` in one `lib/text.ts`.

Loose ends

Repo hygiene

- `.claude/worktrees/licensed-states-pagination` is committed to `main` as a gitlink (mode 160000, no `.gitmodules`, since commit `7f5b2fb`). The branch it points at is 40 files and ~2,900 deletions behind main. It pollutes every grep. Fix: `git rm --cached` and `git worktree remove`.
- No ESLint config, no `lint` script, `noUnusedLocals` off. That is why the unused imports below survive.

- `@supabase/supabase-js` in `package.json` and `.env.example` are not imported or read anywhere.

Dead code

- `normalizeStates` import in `carrier-contracts-view.tsx:15`.
- `components/inline-script.tsx` is never imported; the root layout inlines the theme script by hand.
- `AddCarrierResult` export and a stale header comment in `carrier-dialog.tsx` describe a “New carrier” flow from the contract dialog that does not exist; its `description` prop is never passed.
- `hiddenNotice.loginId` in `logins-view.tsx:157` is written, never read.
- `accent` colour token has zero uses; `charcoal` has one, on an always-empty span.
- `SessionUser.role` is threaded through `session` → `layout` → `shell` → `navbar` and read nowhere.
- `title=""` is passed through `AppShell` → `Navbar` and rendered in three empty spans.

Placeholders and half-wired

- Notifications bell is a focusable no-op. Rulebook is an empty state.
- `await connection()` in Overview and Logins is redundant: the layout’s `cookies()` read already makes every route dynamic (the build shows all routes as `f`).
- Contract notes are visible in exactly one place (by-state expanded row); both profiles’ comments claim otherwise.
- The agent profile’s Pending item “Finish the X contract” links to `/contracts` although the same `AppointmentDialog` is mounted on the page in edit mode.
- `credential-value.tsx` lives under `app/(dashboard)/logins/` but is imported by `app/login/` and `users/`. It is a shared component in a route folder.
- `role` is stored and shown but gates nothing: nav, routes, Add/Edit buttons, and the Logins and Users password columns are open to every signed-in user.

Doc drift and polish

- Doc §8 dialog classes, §9 banner wording, §13 “still copied per view” (now 9 copies), the Contracts section (by-carriers extras undocumented), the token table (`charcoal`, `accent` missing), the shared table (`credential-value.tsx` missing).
- Fixtures cover no out-of-ceiling contract and no missing `appointedStates`, so the “Saving removes...” path and the loader warnings are untested by data.

- Typos: `test-start class ( agent-switcher.tsx:22 )`; chart headed “Policy Type” (`agents-per-carrier-chart.tsx:36`); trailing spaces in classNames; “license” in identifiers vs “licence” in UI; three names for one record (Contract / Appointment / CarrierContractRecord); “Licensed States” title case vs sentence case elsewhere.

Suggested order

1. Fix the dialog padding: one owner of the inset, form or dialog, not both. Five minutes, user-visible.
2. Decide the inactive-agent rule once and apply it on all four surfaces; fix `users.json` and its notes fixtures; add a loader warning for an agent-role user with no `agentId`.
3. Remove the worktree gitlink, dead imports and exports, the unused dependency. Add ESLint or turn on `noUnusedLocals`.
4. Extract the shared pieces listed under Duplication, roughly in that table's order (largest wins first).
5. Flow work: a login column or chip on the Appointments table, **Add agent** on the carrier profile, links from the appointment dialog's blocking hints, pre-select the map's state in Add contract.
6. Before statements land: decide how `lib/commissions.ts` carriers map to `CarrierRecord` (one carrier model, or a stored code on `CarrierRecord`), and where alias / writing-number matching lives.