Traffic Congestion and Urban Heat: Evidence from Freeway Incidents in California

Sierra Arnold*

October 12, 2026

Click here for the most recent version

Abstract

Traffic congestion is a plausible but unquantified contributor to localized urban heat, a costly externality for the many who live and work near major roads. Yet its short-run causal effect on local surface temperature has not been credibly identified: existing estimates are associational or rely on broad natural experiments. We estimate it for California freeways using unplanned accidents as an instrument for congestion. The central threat is reverse causality: because congestion raises accident risk, accidents are in general endogenous to the congestion they are meant to instrument. We document this bias with an event study and remove it by restricting the instrument to accidents that strike while the segment is free-flowing, before congestion has formed. We measure land surface temperature from NASA ECOSTRESS at 70-meter resolution and exploit its varying overpass time to match each reading to same-hour congestion. Our central estimate is the reduced form: a free-flow-onset accident raises near-road surface temperature by about 0.08°C over the following two hours, against flat pre-trends. Scaled by the accident's effect on congestion, this implies roughly 0.4 to 0.7°C per 10 mph of speed reduction, somewhat above the prior associational estimate. The effect is statistically significant in the near-road ring and declines significantly with distance from the road, tracing how far a localized transport externality reaches into the surrounding residential space.

Keywords: urban heat island, traffic congestion, land surface temperature, instrumental variables, freeway incidents, ECOSTRESS, California

JEL Classification: Q54, R41, C26

*Assistant Professor of Economics, Xavier University. Contact: arnolds7@xavier.edu. I thank participants at the ASHEcon Annual Conference and at the Miami University brown bag seminar for helpful comments and suggestions. This study contains modified Copernicus Climate Change Service information (2018–2026); neither the European Commission nor ECMWF is responsible for any use that may be made of the Copernicus information or data it contains. Any errors are my own.

1 Introduction

How far from the road does traffic congestion raise temperature? Extreme heat is the leading cause of weather-related deaths in the United States, exceeding floods, tornadoes, and hurricanes in average annual fatalities (National Weather Service, 2024). Urban heat, the systematic warmth of developed areas relative to their surroundings, carries well-documented health and energy costs (Heaviside et al., 2017; Santamouris et al., 2015). Its structural drivers, the pavement, rooftops, and sparse vegetation that set a neighborhood's baseline temperature, are extensively studied (Oke, 1973; Gago et al., 2013). Much less is known about its time-varying drivers, and in particular about traffic congestion, which fluctuates hour to hour over a fixed road network that millions of people live beside. About 11 million Californians reside within one kilometer of the freeway segments we study, 4.7 million of them within 500 meters. Whether congestion measurably raises temperature around these freeways, and how far from the road the effect extends, is an understudied spatial question.

The mechanism is well grounded: vehicles in stop-and-go operation burn more fuel and release more waste heat per mile than vehicles at cruise speed (Barth and Boriboonsomsin, 2008). The anthropogenic heat-flux literature identifies vehicular traffic as a substantial, commute-peaked component of the urban energy balance (Sailor and Lu, 2004; Sailor, 2011; Quah and Roth, 2012). But causal identification of the congestion-to-heat link is limited. The closest evidence (Lee and Berkelhammer, 2025) correlates bus speeds with satellite temperature in Chicago and finds a 0.36°C rise per 10 mph of slowdown, an estimate that is associational. Quasi-experimental alternatives rely on shocks, such as highway expansions (Yang et al., 2026) and COVID-19 mobility restrictions (Tran et al., 2026), that move land use, economic activity, and human presence alongside traffic.

We estimate the effect of freeway congestion on nearby surface temperature using unplanned freeway accidents logged in the Caltrans Performance Measurement System (PeMS) as an instrument for congestion. The central threat to this design is reverse causality: congestion itself raises accident risk. We therefore restrict the instrument to free-flow-onset

accidents, those that strike while the segment is free-flowing and so cannot have been caused by congestion. An event study validates the restriction: the speed performance index (realized speed relative to free-flow speed) shows no congestion building before a free-flow-onset accident and drops sharply when the accident occurs. Surface-temperature pre-trends are flat (Section 5.1). We measure the temperature response with NASA ECOSTRESS, whose 70-meter resolution and varying overpass times let each land surface temperature (LST) reading be matched to a PeMS congestion reading from the same hour. We estimate the response in concentric distance bands around the freeway, separating the temperature of the road itself from that of the surrounding residential area, in the spirit of Currie and Walker (2011).

Our central estimate is the reduced form: a free-flow-onset accident raises near-road surface temperature by about 0.08°C over the following two hours, against flat pre-trends. Scaled by the accident's effect on congestion, this implies roughly 0.4 to 0.7°C per 10 mph reduction in speed, somewhat above the associational estimate in Lee and Berkelhammer (2025). The effect is right-signed at every distance band, is statistically significant near the road, and declines significantly with distance from it. The raw correlation cannot be read as this effect: conditional on detector, date, and hour-of-day fixed effects, the OLS association is small and wrong-signed.

These magnitudes have economic content beyond their size. The delay and pollution costs of congestion are widely studied and, in places, priced; the thermal channel is an additional local externality that no current policy prices. It is also one that existing policy already moves. Because the estimates are identified from accident-induced congestion episodes, they measure what rapid incident detection and clearance (programs transportation agencies operate primarily to recover delay) also buy back in near-road heat.

The paper makes three contributions. First, it provides a credibly identified estimate of the short-run effect of traffic congestion on local surface temperature. Second, it shows that accidents, used as instruments for congestion precisely because they appear ex-

ogenous (Beland and Brent, 2018), are systematically endogenous to the congestion they are meant to instrument. It also shows that conditioning on the pre-accident state removes the bias. Third, it maps how far the congestion-heat externality reaches from the road into the surrounding residential fabric.

The remainder of the paper proceeds as follows. Section 2 reviews the related literature and Section 3 describes the data. Section 4 presents the research design: the event study and the reduced-form and two-stage least squares (2SLS) specifications. Section 5 reports the results: the near-road temperature response, its decline with distance from the road, and its size per unit of congestion. Section 6 reports the robustness checks central to identification, with further checks in the Appendix, and Section 7 concludes.

2 Related Literature

This paper connects several bodies of work: the urban heat island literature, a small literature on traffic congestion and local temperature, and the causal economics literature on traffic externalities.

Urban heat islands arise when vegetated, permeable surfaces are replaced with impervious materials that absorb and retain solar radiation while eliminating evaporative cooling (Oke, 1973; Gago et al., 2013; Declet-Barreto et al., 2013). The stakes are well quantified. Heaviside et al. (2016) attribute roughly half of heat-related deaths in the 2003 West Midlands heatwave to the urban heat island, and Tuholske et al. (2021) document a near-doubling of urban population exposure to extreme heat since the 1980s. Santamouris et al. (2015) estimate that urban overheating raises building cooling loads by 13 percent on average. This literature centers on structural features of the built environment that vary slowly over time, measured at scale through thermal infrared remote sensing (Li et al., 2020).

Direct evidence linking congestion to local temperature is scarce. Husni et al. (2022) document a 7°C temperature increase associated with traffic queue rates using IoT sensors in

Indonesia, and Yang et al. (2026) find that Bay Area highway expansions exacerbate urban–rural temperature differentials in MODIS data. Lee and Berkelhammer (2025) estimate a 0.36°C increase in surface urban heat island intensity per 10 mph decline in Chicago bus speeds.

A larger economics literature establishes that traffic imposes substantial external costs on infant health, productivity, and housing values (Greenstone and Gayer, 2009; Knittel et al., 2016; Isaksen and Johansen, 2021; Graff Zivin and Neidell, 2012; Chay and Greenstone, 2005). Chay and Greenstone (2003) establish the foundational causal link between vehicle-related pollution and infant health, and Xia et al. (2023) study the within-city effects of congestion on NO_2 and CO, the closest pollution-side analog to our congestion-temperature design. Currie and Walker (2011) compare birth outcomes for mothers living within two kilometers of a toll plaza with those two to ten kilometers away, before and after the introduction of E-ZPass reduced idling and congestion at the plazas. They find improved outcomes for the nearby mothers. To instrument for congestion itself, rather than infrastructure (where Duranton and Turner (2011) established the canonical design), prior work has used transit strikes (Anderson, 2014) and other transitory shocks to traffic. Unplanned freeway accidents add a shock located to the detector segment and timestamped to the minute. This approach draws on a broad tradition in economics that exploits the idiosyncratic short-run timing of natural shocks, weather most prominently, as a source of exogenous variation (Miguel et al., 2004; Deschênes and Greenstone, 2007).

Two further literatures bear directly on the design. Accidents have been used in economics as a source of exogenous variation in traffic. Studying the effect of congestion on crime, Beland and Brent (2018) report a specification that instruments extreme traffic in Los Angeles with Caltrans-logged accidents delaying traffic by more than an hour. The specification draws on the same PeMS detector data we use. Transportation research, however, shows that freeway crash risk rises with congestion and can be predicted from detector readings in the minutes before a crash (Abdel-Aty et al., 2004; Yeo et al., 2013). Accidents

therefore cannot be assumed exogenous to the congestion around them. That the instrument appears in published work on our own data source is what makes the endogeneity we document consequential beyond this setting. And a body of work identifies near-road exposure from wind direction relative to the source (Anderson, 2020; Herrnstadt et al., 2021); our upwind-downwind comparison follows that logic, applied to heat rather than to pollution.

Finally, the paper's spatial object, the distance gradient of the temperature response, connects to a regional-science tradition tracing how localized disamenities decay with distance from their source. Currie et al. (2015) measure the reach of toxic-plant emissions into surrounding housing markets, Seo et al. (2014) estimate distance-band hedonic gradients of highway disamenity, and Brinkman and Lin (2024) value the local quality-of-life costs of urban highways.

We add a causal estimate of how a time-varying driver of urban heat, freeway congestion, affects surface temperature across California's metropolitan freeways. The estimate is identified from accidents that strike free-flowing segments, with temperature matched to traffic conditions hour by hour through the 70-meter, varying-overpass-time ECOSTRESS instrument (Fisher et al., 2020). It extends the study of traffic's external costs to a temperature channel, which operates through the same waste heat and exhaust as the pollution channel but along a thermal rather than chemical pathway. We also measure the distance gradient of the response in physical rather than price terms, asking how far the temperature response to congestion extends into the residential fabric around the network.


3 Data

3.1 Traffic Congestion and Incident Logs: PeMS

Traffic data come from the Caltrans Performance Measurement System (PeMS; California Department of Transportation, 2026), which operates a network of traffic detectors embedded in California freeway lanes. Each detector records flow (vehicles per hour), occupancy (share

of time a vehicle is present over the sensor), and speed (miles per hour) at five-minute intervals. Detectors are spaced approximately every half mile along major California freeways and are organized into stations that aggregate across lanes. We obtain station-level hourly data and station metadata (GPS coordinates, freeway route, and direction of travel) for eight Caltrans districts from June 2018 through March 2026.[1] Figure 1 maps the detectors in the estimation panel across these eight districts.

Figure 1: PeMS freeway detectors in the estimation panel, by Caltrans district



The primary congestion measure is the speed performance index, a standard speed-based congestion metric (He et al., 2016). It is the ratio of realized speed to free-flow speed,

$$\text{SPI}_{it} = \frac{\text{Speed}_{it}}{\text{Free-Flow Speed}_{i}}$$

[1]We include the eight Caltrans districts covering California's major metropolitan areas. They are District 3 (Sacramento), District 4 (Bay Area), District 5 (San Luis Obispo/Central Coast), District 6 (Fresno/Central Valley), District 7 (Los Angeles), District 8 (San Bernardino/Riverside), District 11 (San Diego), and District 12 (Orange County). Districts 1 (North Coast), 2 (Northern California), 9 (Eastern Sierra), and 10 (Central Sierra) are excluded because they cover predominantly rural and mountainous terrain with sparse freeway detector networks and limited urban heat island exposure. For four districts (6, 7, 11, and 12) the most recent station-metadata snapshot predates some newer detectors, which therefore do not enter the panel.

where i indexes the PeMS detector station and t indexes the hour of the ECOSTRESS overpass. A value of 1 indicates free-flow conditions and values approaching 0 indicate near-standstill conditions, so the index falls as congestion worsens. Free-flow speed is defined empirically as the 85th percentile of observed speeds at station i during overnight hours (10pm–5am) and weekends, when congestion is minimal. This percentile-based definition makes the index comparable across segments with different posted speed limits and traffic compositions.

For the incident instrument, we use PeMS incident logs, which record the timestamp, segment, type, and duration of each incident logged on California freeways. PeMS classifies incidents into a range of categories, the most common of which are traffic collisions, traffic hazards, animal hazards, vehicle fires, road and weather conditions, and assists to Caltrans operations. We restrict the instrument to traffic accidents, which are the most plausibly exogenous to neighborhood characteristics and environmental conditions. Weather-related incidents are excluded because precipitation simultaneously raises accident rates and suppresses LST, creating a mechanical negative correlation that would bias the instrument. Traffic hazards, animal hazards, vehicle fires and debris, and planned events such as construction assists and road closures are excluded because they either do not reliably generate congestion or are not unplanned. We discuss these restrictions further in Section 4.2. Each accident is timestamped when the California Highway Patrol logs it and matched to the nearest mainline detector within one kilometer on the same freeway and in the same direction. About 1.2 million accidents are matched over the study period. We classify onset using the speed performance index at that detector over the clock hour preceding the hour in which the accident is logged (Section 4.1). About half of accidents cannot be classified because the detector reports no speed in that hour; these, like congested-onset accidents, are excluded from the estimation sample rather than counted as controls.

The PeMS incident archive is largely complete over the study period, except for

March-early July 2025, where the feed was not reliably archived.[2] We treat the instrument as undefined on dates lacking reliable incident records (missing, empty, or anomalously sparse) and drop ECOSTRESS overpasses falling in those windows. The 2025 gap therefore removes roughly four months of overpasses from the estimation panel. Because the gap is a data-archiving artifact unrelated to traffic, weather, or neighborhood conditions, this attrition is plausibly unrelated to the outcome and is not expected to bias the estimates. Table 1 reports the affected sample counts.

3.2 Land Surface Temperature: ECOSTRESS


Land surface temperature data come from the NASA ECOSTRESS `ECO_L2T_LSTE` Version 2 product, distributed by the NASA Land Processes Distributed Active Archive Center and accessed via AppEEARS (Hulley and Hook, 2022). ECOSTRESS is a thermal infrared instrument on the International Space Station (ISS) that has provided observations since July 2018 at 70-meter spatial resolution (Fisher et al., 2020). MODIS, common in urban heat research, observes at 1 kilometer (Chakraborty et al., 2019). ECOSTRESS's 70-meter resolution allows LST measurement at the scale of individual freeway segments and adjacent land parcels.

The defining temporal property of ECOSTRESS for this study is its ISS orbit. Sun-synchronous satellites overpass at a fixed local solar time (Landsat 8 at approximately 10am, MODIS at fixed morning and afternoon times). The ISS, by contrast, precesses through a range of local overpass times at any given California location. Successive ECOSTRESS overpasses of the same segment therefore occur at different times of day, generating exogenous variation in the hour of LST observation. Figure 2 plots the distribution of overpass times across the 24-hour day. We exploit this variation to match each LST observation to a contemporaneous PeMS congestion reading at the overpass hour. The hour-of-day variation

[2]The remaining gaps are minor and isolated: a single day in June 2019, a cluster of days in January 2020, and scattered individual dates. Together they account for under two percent of days in the study period. Incident coverage in all other months is complete.

in overpass time also underlies the event study evidence in Section 5.1.

Figure 2: Distribution of ECOSTRESS overpass times by hour of day (Pacific) in the estimation panel



We download four layers from ECO_L2T_LSTE: LST (in Kelvin), LST_err (retrieval uncertainty), QC (quality control flags), and cloud (cloud mask). We apply quality filters to exclude pixels where the LST retrieval is unreliable. Three sources of retrieval failure motivate these filters. First, clouds absorb and re-emit thermal radiation before it reaches the sensor, so a cloudy pixel records the temperature of the cloud rather than the ground surface. We exclude pixels flagged as cloudy by the cloud mask. Second, the retrieval algorithm corrects the raw thermal signal for atmospheric absorption and scattering. This correction can fail under unusual water vapor or aerosol conditions (including, potentially, haze from heavily congested corridors), producing biased LST values. We exclude pixels with QC flag values indicating failed or degraded retrievals. Third, the algorithm converts radiance to temperature using assumed surface emissivity, and high uncertainty in that assumption produces inaccurate temperatures. We therefore drop pixels whose retrieved LST falls outside a physically plausible range (255–345 K, about −18 to 72°C), which removes

implausible retrievals that survive the cloud and quality-control screens. Using corrupted pixels would add noise to the outcome variable and could introduce systematic bias if retrieval quality is correlated with congestion levels. After applying these filters, the outcome for observation (i, t) is the mean LST across all pixels passing quality filters within a distance band around detector i at overpass t (Section 3.3.1). The spatial footprint is restricted to a 2-kilometer buffer around the California state highway network, encompassing all PeMS detector locations and the immediately surrounding land.

Because ECOSTRESS is a relatively young instrument, coverage in the earliest months of our study period is incomplete. ECOSTRESS experienced two anomalies of its onboard mass storage unit (MSU) that suspended data acquisition (NASA Land Processes Distributed Active Archive Center, 2024). The primary unit failed on September 29, 2018, and acquisition resumed only after the instrument was switched to its backup unit on December 5, 2018. A second anomaly halted acquisition again between March 14 and May 15, 2019. Our panel therefore contains no LST observations for October through December 2018 and reduced coverage in the spring of 2019. These gaps arise from instrument hardware status rather than from any feature of traffic, weather, or location. The lost observations are therefore unrelated to the outcome and affect only the early-period sample size, not the identifying variation. ECOSTRESS coverage is also sparse from January through March 2024, which leaves few observations in those months.

3.3 Sample Construction

The unit of observation is a freeway detector station i crossed with an ECOSTRESS overpass t. A valid observation requires at least five ECOSTRESS pixels passing quality filters within the buffer of the detector, and a valid PeMS congestion reading within the same calendar hour as the overpass timestamp. That congestion reading must also pass a data-quality filter, with at least 50 percent of the hour's five-minute intervals observed (`pct_observed` ≥ 50), to reduce measurement error from detector malfunctions.

Table 1 reports the observations lost at each of these filtering stages. The binding step is the same-hour match, which retains about 46 percent of quality-passing overpasses. A freeway detector reports a usable speed only intermittently: some never report speed at all, and a working detector is online at a given overpass hour only about half the time. The matched panel is therefore the intersection of two independent data streams rather than a curated subsample. The match rate is essentially flat across all twenty-four hours of the day, so this attrition costs statistical power without selecting on the overpass-time variation the design exploits. Because detector reporting reliability and cloud cover are plausibly unrelated to the idiosyncratic timing of freeway accidents, we do not expect the attrition to threaten identification.

Table 2 reports summary statistics for the estimation panel and, separately, for the free-flow-onset-treated overpasses that identify the estimates. Treatment is rare by design: accidents are infrequent, so only 5,378 of the 3.9 million detector-overpasses, at 2,816 distinct detectors, carry a free-flow-onset accident in the prior two hours. The remaining observations are the control pool: identification comes from comparing treated and control overpasses conditional on detector, date, and hour-of-day fixed effects. Two patterns are worth noting. The typical overpass is close to free-flow (mean speed performance index 0.92), so the congestion variation that identifies the effect lies in the lower tail of the distribution rather than at the mean. The treated overpasses are modestly more congested than the estimation panel as a whole (index 0.90 versus 0.92, with higher traffic flow), the descriptive counterpart of the first stage. Surface temperature averages 22.8°C with wide dispersion (standard deviation 11.5°C), reflecting the all-hours, multi-year, statewide ECOSTRESS coverage that the detector, date, and hour-of-day fixed effects absorb.

3.3.1 Outcome: distance bands around the detector

The outcome is land surface temperature in concentric distance bands around the detector, each the mean of quality-filtered ECOSTRESS pixels within a given radius at overpass t. We

Table 1: Sample construction

	Observations	Detectors	% of row 1
ECOSTRESS overpass observations	9,045,115	11,180	—
with ≥ 5 quality-passing pixels (500 m buffer)	8,910,223	11,178	98.5
matched to a same-hour PeMS congestion reading	4,124,564	9,323	45.6
excluding low-coverage incident days	3,890,544	9,287	43.0
Estimation panel	**3,890,544**	**9,287**	43.0
with non-missing weather controls	3,702,727	8,889	40.9

Notes: The unit of observation is a detector × ECOSTRESS overpass. Row 1 counts overpasses with a valid LST extraction (June 2018–March 2026; after pixel-level cloud, quality-control, and 255–345 K masking). Row 4 drops overpasses on dates with missing or anomalously sparse CHP incident records (the March–July 2025 feed gap and scattered days), which cannot be coded incident = 0. The final row is the panel with weather controls available.

Table 2: Summary statistics

	Full sample		Free-flow-onset treated	
	Mean	SD	Mean	SD
Land surface temp (°C)	22.76	11.46	22.46	10.95
Speed performance index (speed / free-flow)	0.92	0.12	0.90	0.15
Speed (mph)	63.49	8.72	62.29	10.73
Free-flow speed (mph)	68.65	2.23	68.96	1.48
Traffic flow (veh/hr)	2,674	2,054	3,020	1,924
ECOSTRESS pixels in buffer	142.5	35.5	143.0	34.9
Observations	3,890,544		5,378	

Notes: Unit of observation is a PeMS detector × ECOSTRESS overpass, June 2018–March 2026. "Full sample" is the estimation panel; "free-flow-onset treated" is the subsample of overpasses with a free-flow-onset accident (one striking the segment while it was free-flowing, speed performance index ≥ 0.90) in the prior two hours. The speed performance index is realized speed divided by free-flow speed (1 = free-flow; lower = more congested).

construct the 100-, 250-, 500-, and 1,000-meter buffers, and from them three disjoint annular rings (0–100, 100–500, and 500–1,000 meters) for the distance gradient. The innermost ring, which we call the near-road ring, captures temperature where traffic-related heat is most concentrated. The band spacing follows the near-road pollution literature, which finds concentrations decaying to background within 150 to 300 meters and detectable to roughly 500 meters (Health Effects Institute, 2010). We use those distances to set the geometry of the bands, not as evidence about how far heat itself travels. A pollutant disperses as a near-conserved tracer, while heat is shed to the air and to the sky far faster. The outer bands mostly capture temperature in the surrounding residential area, the exposure of most direct welfare interest, in the spirit of Currie and Walker (2011). At 70-meter resolution a 500-meter radius contains about 160 pixels, yielding a stable average; we take the 500-meter buffer as the descriptive baseline, while the preferred causal estimate uses the near-road ring. Section 5.2 reports the disjoint rings, which map how far the effect reaches.

4 Research Design

4.1 Event Study

Because congestion itself raises accident risk, a design built on freeway accidents is valid only if accident timing is exogenous to congestion. The event study tests this directly. It traces congestion and surface temperature in two-hour bins around an accident. It asks whether congestion is already building before impact (reverse causality), and whether pre-accident trends in surface temperature would violate the exclusion restriction.

For each ECOSTRESS overpass we measure the elapsed time to each qualifying accident on the same detector within a ±6-hour window and assign the overpass to a two-hour lag bin $[\ell, u)$:

$$d_{\ell,u,it} = \mathbf{1}[t - \text{accident}_{it} \in [\ell, u)] \,.$$

Negative lags are overpasses before an accident; the baseline group has no accident on the segment within ±6 hours. We estimate

$$Y_{it} = \alpha_i + \mu_d + \lambda_h + \sum_{[\ell,u)} \phi_{\ell,u}\, d_{\ell,u,it} + \mathbf{X}'_{it}\gamma + \eta_{it} \tag{1}$$

separately for $Y_{it} = \mathrm{SPI}_{it}$, the speed performance index on the segment, and $Y_{it} = \mathrm{LST}_{it}$, surface temperature in degrees Celsius in the near-road ring (0–100 meters from the detector; Section 3.3.1). Here α_i are detector fixed effects, μ_d are date fixed effects (where d indexes the calendar date of overpass t), and λ_h are hour-of-day fixed effects (where h indexes the Pacific-time hour of the overpass, $h \in \{0, 1, \ldots, 23\}$). The vector $\mathbf{X}_{it}$ holds local weather controls, and standard errors are clustered at the detector. The lead coefficients $\phi_{\ell,u}$ at negative lags are the diagnostic of interest, in speed-performance-index units for congestion (the index averages about 0.92) and in degrees Celsius for temperature.

Identification is within-segment, within-date, and within-hour. The detector effects α_i absorb time-invariant location characteristics (pavement, land cover, urban density). The date effects μ_d absorb common daily shocks such as heat waves without eliminating within-day variation in overpass time, and the hour effects λ_h absorb the solar cycle. The controls $\mathbf{X}_{it}$, air temperature, precipitation, relative humidity, and wind speed at the detector and overpass hour, drawn from the ERA5-Land hourly reanalysis (Muñoz Sabater et al., 2021; Muñoz Sabater, 2019), absorb local weather not captured by the date fixed effects.

To separate exogenous from congestion-induced accidents, we classify each accident by the speed performance index on its segment in the hour before impact. A free-flow-onset accident strikes while the segment is free-flowing (pre-accident SPI ≥ 0.90) and so cannot have been caused by congestion; a congested-onset accident strikes while the segment is already congested. Among accidents we can classify, the two groups are roughly equal in number. We estimate equation (1) with separate bin sets for the two groups in a single regression, so that congested-onset overpasses do not enter the free-flow-onset baseline.

Section 5.1 reports the results.

4.2 Reduced Form and Two-Stage Least Squares

The parameter of interest is the causal effect of traffic congestion on land surface temperature. Even conditional on these fixed effects and controls, SPI_{it} is endogenous. Clear skies raise both solar load and traffic volumes, biasing OLS toward a warming effect, while heat-induced travel avoidance works in the opposite direction, so the sign of the net bias is ambiguous ex ante.

Our instrument for SPI_{it} is an indicator for a free-flow-onset accident on segment i in the hours before the overpass, built in two steps. First, we flag any qualifying accident (a collision, hit-and-run collision, or spinout; Section 3.1) on segment i within a lookback window of length h, with $h = 2$ hours in the baseline. Second, we keep only accidents that struck while the segment was free-flowing, defined as a speed performance index of at least 0.90 in the hour before impact, so that congestion cannot have caused the accident:

$$Z_{it} = \mathbf{1}[\text{free-flow-onset accident on segment } i \text{ in } [t-h, t]]\,.$$

Restricting to free-flow-onset accidents removes the reverse causality the event study reveals (Section 5.1). The two-hour baseline matches the window over which the event study concentrates the congestion shock and its temperature response. We report $h \in \{1, 3\}$ hours as robustness (Table A.9, panel B) and vary the 0.90 onset threshold in Section 6.

The instrument must also be relevant, predicting congestion on the affected segment. Accidents reduce effective capacity, slowing traffic as vehicles merge around the incident; the resulting congestion can persist for one to three hours after clearance (Cao et al., 2021; Haule et al., 2019). Free-flow-onset accidents perturb congestion less than the average accident (they strike uncongested segments), so their first stage is smaller in magnitude, though still precisely estimated. We report the Kleibergen–Paap first-stage F (KP F in the tables)

with each specification. A severity check (Table A.3) weights the instrument by accident duration, since longer accidents sustain larger congestion. The compliers are accidents on normally uncongested segments; Section 5.3 discusses what their local average treatment effect represents.

Our primary estimate is the reduced form, which regresses surface temperature directly on the instrument:

$$\mathrm{LST}_{it} = \alpha_i + \mu_d + \lambda_h + \pi\, Z_{it} + \mathbf{X}'_{it}\gamma + e_{it} \tag{2}$$

The coefficient π is the effect of a free-flow-onset accident on surface temperature in degrees Celsius. To express it per unit of congestion, the first stage regresses the speed performance index on the instrument and the fixed effects and controls, and the second stage replaces it with its fitted value:

$$\mathrm{SPI}_{it} = \alpha_i + \mu_d + \lambda_h + \beta\, Z_{it} + \mathbf{X}'_{it}\gamma + \varepsilon_{it} \tag{3}$$

$$\mathrm{LST}_{it} = \alpha_i + \mu_d + \lambda_h + \delta\, \widehat{\mathrm{SPI}}_{it} + \mathbf{X}'_{it}\gamma + u_{it} \tag{4}$$

We expect $\beta < 0$: accidents raise congestion, lowering the index. The coefficient δ is the effect of a one-unit increase in the speed performance index on LST in degrees Celsius. Because congestion lowers the index, warming from congestion appears as $\delta < 0$, and $-\delta$ is the effect of a shift from free-flow to fully congested conditions. We also report the implied effect of a 10 mph speed reduction (the unit used by Lee and Berkelhammer, 2025). Because a free-flow-onset accident lowers the index by only about 0.0165, the full one-unit quantity is an extrapolation far beyond the identified margin. We estimate the reduced form and the second stage for each distance band: Section 5.2 traces the reduced form from the roadway out to the surrounding residential area, and Section 5.3 reports the 2SLS estimates.

The exclusion restriction requires that incident occurrence affects LST only through its effect on traffic congestion, conditional on the fixed effects and controls. We identify three

potential violations and address each empirically; the event study (Section 5.1) provides the primary test, with the robustness checks in Section 6 providing supporting evidence.

Volume-driven clustering. Accident probability rises with traffic volume, which is correlated with congestion. The fixed effects absorb the systematic component of this relationship, leaving the question of whether within-segment, within-date accident timing correlates with temperature determinants beyond what they and the weather controls capture. The event study's flat pre-accident LST coefficients are the central piece of supporting evidence (there is no anticipatory movement in the outcome), and a prior-day placebo corroborates it (Table A.6). We omit contemporaneous traffic volume because it is jointly determined with congestion and itself reduced by accidents, a bad control that would absorb part of the causal pathway (Angrist and Pischke, 2009).

Weather. Precipitation raises accident rates and lowers LST through evaporative cooling and reduced solar radiation. The fixed effects and weather controls $\mathbf{X}_{it}$ absorb most of this pattern, and warmer and more humid hours see slightly more free-flow-onset accidents (Table A.8), which is why the specification controls for weather.

Direct thermal effects and incident classification. Vehicle fires emit heat directly at the road surface, elevating pixel temperatures through a non-congestion channel. We exclude vehicle fires. For qualifying incidents (collisions, hit-and-run collisions, and spinouts), the crash scene, including any emergency response, is a point source. It lies within 100 meters of the matched detector for about a quarter of free-flow-onset accidents, and half of these accidents last 30 minutes or less. An active scene therefore sits inside the near-road ring at the time of the overpass in only a minority of treated observations. Stopped traffic in the queue is a separate channel, which we bound in Section 6.

We estimate the model with `ivreghdfe` (Baum et al., 2007) and cluster standard errors at the detector; the estimate is insensitive to two-way (detector-by-date) and to coarser spatial clustering (Table A.7). The reduced form's test of a zero effect does not depend on the strength of the first stage. It is the Anderson–Rubin test (Andrews et al., 2019), so

the reduced form and the 2SLS estimate share one test of a zero effect. We also report the Anderson–Rubin confidence set for the 2SLS estimate (Section 5.3).[3]

5 Results

The estimation panel holds roughly 3.9 million detector-overpass observations (Section 3). We report three results: the near-road temperature response to a free-flow-onset accident, how that response changes with distance from the road, and what it implies per unit of congestion.

5.1 Near-road temperature response

The quantity we emphasize is the reduced form: a free-flow-onset accident raises near-road surface temperature by about 0.08°C over the following two hours (0.084, SE 0.044, $p = 0.06$), against flat pre-accident leads. Without weather controls the estimate is 0.10°C (Table A.5). The weather controls $\mathbf{X}_{it}$ identify the effect over and above ambient temperature (the air-temperature coefficient alone is about +0.77°C of LST per °C of air temperature). The reduced form is the direct experimental contrast (treated versus untreated overpasses, conditional on detector, date, and hour-of-day fixed effects). It requires no stand on how the instrument's association with congestion divides between the accident shock and the selection inherent in conditioning on a free-flowing pre-hour. Table 3 reports it by distance ring.

The event study traces this response over time (Figure 3). The two onset groups behave very differently in congestion (Figure 3a). Before a congested-onset accident, congestion ramps steeply (−0.024, −0.068, −0.149 across the three lead bins): the reverse causality is concentrated here. Before a free-flow-onset accident, congestion does the opposite: the

[3]Because two-stage least squares with non-saturated covariates need not recover a positively weighted average of treatment effects (Blandhol et al., 2022), we treat δ as a local, design-based summary rather than a structural parameter.

Table 3: Reduced form: effect of a free-flow-onset accident on land surface temperature (°C), by distance ring

	(1) 0–100 m (near-road)	(2) 100–500 m	(3) 500–1000 m
Free-flow-onset accident (prior 2h)	0.0835*	0.0611	0.0234
	(0.0443)	(0.0428)	(0.0441)
Free-flow-onset treated	4,851	4,804	5,036
Observations	3,512,679	3,459,683	3,648,286

Notes: Reduced-form regressions of ring-mean LST (°C) on the free-flow-onset accident indicator, on the sample pairing free-flow-onset-treated overpasses with no-accident controls, with weather controls (air temperature, relative humidity, wind speed, and precipitation at the detector and overpass hour). All columns include detector, date, and hour-of-day fixed effects. Specifications without weather controls are in Table A.5. Standard errors, clustered by detector, in parentheses. * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

segment is, if anything, increasingly free-flowing (+0.009, +0.023, +0.029) and then drops sharply at impact (−0.016, $t \approx -7$). Free-flow-onset accidents thus deliver a sharp, discontinuous congestion shock with no congestion building beforehand. The upward drift in those leads is not a congestion pre-trend but the mirror image of one. It reflects the persistence of the free-flowing state on which the instrument conditions, since the conditioning hour itself falls in the final lead bin. We therefore do not read the leads as validating the magnitude of the first stage, and we quantify the persistence directly with a pseudo-event placebo that reproduces the conditioning without an accident (Section 5.3). What the leads do establish is that congestion is not rising into these accidents, which is the reverse-causality threat the restriction exists to remove. Surface-temperature leads for free-flow-onset accidents are individually insignificant and jointly indistinguishable from zero ($F(3, 8{,}851) = 0.05$, $p = 0.98$), consistent with the exclusion restriction; for congested-onset accidents, which the instrument excludes, they are jointly insignificant ($p = 0.13$; Figure 3b). The free-flow-onset accident bin reproduces the reduced form (+0.084°C), since it measures the same two-hour response in the same specification. Later bins are imprecise and alternate in sign (−0.074 at two to four hours, +0.071 at four to six hours, neither significant), so we draw no conclusion about how long the response persists. The onset event study in the 500-meter buffer with-

out weather controls shows the same patterns, with flat free-flow-onset temperature leads ($F(3,\ 9{,}250) = 0.25$, $p = 0.86$; Figures A.3 and A.4).


For reference, an event study on all accidents shows congestion building before impact, the reverse causality that the free-flow-onset restriction removes, while surface-temperature leads stay flat (Figures A.1 and A.2). The OLS association between the speed performance index and surface temperature is small and wrong-signed (+0.14, with or without weather controls). The all-accident 2SLS estimate, contaminated by that reverse causality, is −1.14, and −1.19 with traffic volume added (Table A.2).

5.2 Distance decay


Table 3 and Figure 4 report the reduced form by distance from the detector. This distance gradient is the paper's spatial object: how far a localized road externality reaches into the surrounding residential space, the thermal analog of the distance decay traced for transport and environmental disamenities (Seo et al., 2014; Currie et al., 2015). We use disjoint annular rings (0–100, 100–500, and 500–1,000 meters) rather than nested disks. Each estimate then reflects the temperature response in a distinct distance zone, and the gradient is not mechanically smoothed by sharing near-road pixels across bands. The near-road ring captures on-road and roadside heat; the outer ring mostly captures the residential area around the corridor. The gradient adjudicates whether a measurable effect persists out to the residential ring, and whether it decays with distance or instead rises in the intermediate zone. A rise there would point to traffic diverted onto surface streets.

The response decays monotonically from the road outward (Table 3). A free-flow-onset accident raises surface temperature by 0.084°C in the near-road ring ($p = 0.06$), 0.061°C at 100–500 meters ($p = 0.15$), and 0.023°C in the 500–1,000-meter residential ring ($p = 0.60$). The effect is right-signed in every ring and significant at the 10 percent level near the road. The residential-ring estimate is of the expected sign and a plausible magnitude, but its confidence interval contains both zero and an effect as large as the near-road estimate. It

Figure 3: Event study by accident onset



(a) Speed performance index




(b) Near-road surface temperature (°C)

Notes: Coefficients $\hat{\phi}_{\ell,u}$ from equation (1) for free-flow-onset accidents (segment free-flowing before impact) and congested-onset accidents, estimated jointly: (a) the speed performance index; (b) surface temperature in the near-road ring (0–100 meters). Detector, date, and hour-of-day fixed effects and weather controls; 95% confidence intervals clustered at the detector; baseline = no accident within ±6 hours.

rests on a treated sample of similar size to the near-road ring (about 5,000 free-flow-onset overpasses), so the outer ring is better described as underpowered than as null. The response is concentrated at the road and falls off with distance, with no rise in the intermediate zone of the kind a surface-street diversion effect would produce. We do not attach a physical transport mechanism to the outer rings. The estimates there are not resolved, and our design identifies where the response appears, not what carries it. Whether the decay itself is statistically real, rather than a pattern read off separate confidence intervals, is tested formally below.

Figure 4: Effect of a free-flow-onset accident on surface temperature by distance from the detector



Notes: Reduced-form estimates (°C) with weather controls for disjoint annular rings 0–100, 100–500, and 500–1,000 meters from the detector, with 95% confidence intervals (standard errors clustered by detector). Point estimates match Table 3.

Table 4 carries out that test. It estimates the three ring reduced forms jointly, stacking the disjoint rings and fully interacting the specification (fixed effects, weather controls, and the accident indicator) with ring. Standard errors are clustered on a 5-kilometer spatial grid, so nearby detectors, and the three rings of the same detector-overpass, may be arbitrarily correlated. The test is cast in reduced form, consistent with the paper's emphasis: the

ring coefficients are the weather-controlled estimates of Table 3, in °C per accident window. Although the per-ring confidence intervals overlap, the cross-ring differences are estimated much more precisely than the ring levels, because the rings of a given detector-overpass share common shocks that difference out of the comparison. The data reject equality of the three ring effects ($p = 0.016$) and reject equality of the near-road and residential rings ($p = 0.005$); a linear decline in the effect with distance from the road is likewise significant ($p = 0.006$). The distance decay is thus a statistically established feature of the reduced form, not a pattern inferred from overlapping point estimates. Because a broad area-level confounder would move all rings together rather than fade with distance from the road, the rejected equality also weighs against such confounding. This sharpens, rather than changes, the substantive reading: the externality demonstrably weakens with distance from its source, while the level of the response within the residential ring itself remains imprecisely estimated.

Table 4: Tests of the reduced-form distance gradient

ff-onset accident × 0–100 m (near-road)	0.0835*
	(0.0451)
ff-onset accident × 100–500 m	0.0611
	(0.0433)
ff-onset accident × 500–1000 m (residential)	0.0234
	(0.0447)
p: all three rings equal	0.016
p: near-road = residential	0.005
Distance trend (°C per 100 m)	−0.0086
p: distance trend	0.006
Observations (stacked)	10,620,648

Notes: The three disjoint rings are stacked and estimated jointly, with the fixed effects (detector, date, hour-of-day), the weather controls, and the accident indicator each fully interacted with ring; the ring coefficients therefore reproduce the weather-controlled reduced forms of Table 3. Standard errors, in parentheses, are clustered on a 5-kilometer spatial grid (945 clusters), allowing arbitrary correlation across nearby detectors and across the rings of the same detector-overpass. Equality rows report Wald tests on the joint covariance matrix; the distance-trend rows replace the ring-specific coefficients with the accident indicator interacted with ring-midpoint distance. * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

How many people live in these rings? Table 5 reports the residential population

around the studied freeway segments from the 2018–2022 American Community Survey. About 11 million Californians live within one kilometer of these segments, and 4.7 million within 500 meters. This population is more racially diverse than the state as a whole (42 percent Hispanic and 70 percent non-white, against roughly 40 and 65 percent statewide). Its median household income is close to the statewide figure. This characterizes the scale and composition of the exposed population; it is not a claim that the congestion-heat effect falls disproportionately on these residents, which our estimates do not support.

Table 5: Residential population exposed near the studied freeway segments

Distance ring	Exposed pop.	Median income	% Hispanic	% non-white
0–100 m	319,927	$100,193	42	71
100–500 m	4,413,002	$100,329	42	71
500–1000 m	6,273,904	$102,833	41	70
Corridor (0–1000 m)	11,006,834	$101,752	42	70
California	39,356,104	$104,733	40	65

Notes: Population, median household income, and racial composition from the 2018–2022 ACS five-year block-group estimates, area-weighted into disjoint rings by distance to the nearest detector in the estimation panel. Detector buffers are unioned across segments, so each resident is counted once. "% non-white" is one minus the non-Hispanic white share; "Median income" is the population-weighted mean of block-group median household incomes. The California row is the statewide population-weighted benchmark.

5.3 Per unit of congestion

Table 6 expresses the response per unit of congestion by dividing each ring's reduced form by its first stage. Near the road, a free-flow-onset accident lowers the speed performance index by 0.0165 ($F \approx 52$), less than the average accident does (Table A.1) because these accidents strike uncongested segments. The resulting 2SLS estimate is $\delta = -5.05$ (SE 2.77, $p = 0.07$). It is signed per unit of the speed performance index, so warming appears as a negative coefficient, and the ring estimates are the reduced forms of Table 3 scaled by their first stages. The Anderson–Rubin 95% set, which is valid regardless of instrument strength, is $[-11.1, 0.2]$; its test of a zero effect is the reduced-form test ($p = 0.06$). The estimate is right-signed across alternative instruments and outcome bands, though significance weakens

in the wider bands (Tables A.3 and A.4). We read this per-unit coefficient as a calibration of the reduced form.

Table 6: Reduced form, first stage, and 2SLS by distance ring

	(1) 0–100 m	(2) 100–500 m	(3) 500–1000 m
Reduced form: accident → LST (°C)	0.0835*	0.0611	0.0234
	(0.0443)	(0.0428)	(0.0441)
First stage: accident → SPI	-0.0165***	-0.0162***	-0.0154***
	(0.0023)	(0.0023)	(0.0022)
2SLS: effect of SPI on LST (°C)	-5.053*	-3.771	-1.522
	(2.767)	(2.696)	(2.875)
Anderson–Rubin 95% set (2SLS)	[-11.1, 0.2]	[-9.6, 1.4]	[-7.5, 4.2]
KP first-stage F	51.7	49.5	47.3
Free-flow-onset treated	4,851	4,804	5,036
Observations	3,512,679	3,459,683	3,648,286

Notes: Each column is a disjoint ring around the detector. The reduced form regresses ring-mean LST on the free-flow-onset accident indicator; the first stage regresses the speed performance index on the same indicator; the 2SLS coefficient is their ratio, the effect of a one-unit increase in the speed performance index on LST (warming from congestion appears as a negative coefficient). All rows include the weather controls (air temperature, relative humidity, wind speed, precipitation) and detector, date, and hour-of-day fixed effects, on the sample pairing free-flow-onset-treated overpasses with no-accident controls. Standard errors, clustered by detector, in parentheses. The Anderson–Rubin set is the 95% confidence set for the 2SLS coefficient that remains valid regardless of instrument strength. * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

We test the selection channel directly with a placebo that replicates the instrument's construction without an accident. For each real free-flow-onset accident we assign a pseudo-event at the same timestamp to a randomly drawn other detector that was free-flowing in the pre-hour (SPI ≥ 0.90) and had no accident within six hours. The 283,236 pseudo-events reproduce the instrument's date and time-of-day distribution almost exactly. Table 7 reports their effects on the no-accident sample. The pseudo first stage is positive (+0.0208, $t = 20$): a segment selected on a free-flowing pre-hour remains more free-flowing than its baseline over the following two hours, rather than reverting below it. The accident-induced drop to 0.0165 below baseline therefore cannot be mean reversion, and measured against this no-accident counterfactual the accident's causal effect on congestion is about -0.037 rather than the

-0.0165 level difference. The pseudo reduced forms on temperature are null at both bands: -0.030 in the near-road ring ($p = 0.53$) and $+0.008$ in the 500-meter buffer ($p = 0.86$). The selection inherent in the instrument does not move surface temperature, which is direct support for the exclusion restriction. The placebo thus resolves the artifact question (the temperature response is caused by accidents, not by the conditioning) while making precise the first-stage accounting choice that motivates reporting the per-unit magnitude as a range.

Table 7: Pseudo-event placebo: speed performance index and land surface temperature

	(1) Speed performance index	(2) LST 100 m (°C)	(3) LST 500 m (°C)
Pseudo free-flow-onset event	0.0208***	-0.0297	0.0082
	(0.0010)	(0.0476)	(0.0476)
Pseudo-event treated	5,693	5,406	5,693
Observations	3,692,716	3,507,828	3,692,716

Notes: Each real free-flow-onset accident is assigned a pseudo-event at the same timestamp on a randomly drawn other detector that was free-flowing in the pre-hour and had no accident within six hours, replicating the instrument's construction without an accident. Columns report regressions of the stated outcome on the pseudo-event indicator, estimated on the no-accident sample, with weather controls. Detector, date, and hour-of-day fixed effects; standard errors, clustered by detector, in parentheses. * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

To compare with the literature, we scale the reduced form into per-unit-congestion terms. The scaling depends on how much of the instrument's association with congestion is credited to the accident shock rather than to the selection inherent in conditioning on a free-flowing pre-hour. That choice must be applied to both sides of the ratio. Taking the measured quantities at face value, the 0.0835°C reduced form over a first stage of -0.0165 gives $\delta \approx -5.05$, the 2SLS estimate above. Substituting the selection-adjusted first stage from the pseudo-event placebo (Table 7; $-0.0165 - 0.0208 = -0.037$) requires also netting out the placebo's own reduced form (-0.030 in the near-road ring). Netting it out raises the numerator to 0.113°C and gives $\delta \approx -3.0$. At a mean free-flow speed of 68.7 mph, 10 mph is about 0.15 index units, so the two accountings imply roughly 0.4 to 0.7°C per 10 mph of slowdown. Both endpoints exceed the 0.36°C that Lee and Berkelhammer (2025) report from bus speeds in Chicago. We do not read that gap as a like-for-like comparison. Their outcome

is a two-kilometer heat-island average and ours the near-road ring, within 100 meters of the detector and dominated by the road surface. Their speeds are 20–50 mph on city streets against a 68.7 mph freeway free-flow baseline, and their design is associational. We place no weight on the adjusted endpoint alone: the placebo reduced form is itself imprecise ($p = 0.53$), which is why we report the pair rather than a point. The estimate is also a local average treatment effect for the complier population: segments that are normally free-flowing and experience a sudden, exogenous slowdown. It therefore speaks to the marginal heat effect of an unusual slowdown rather than to the steady-state heat of a chronically congested freeway.

6 Robustness Checks

This section reports the checks most central to the instrument's construction and to what the near-road estimate measures. These are the sensitivity of the estimate to the free-flow-onset threshold and a bound on how much of the near-road response could be vehicles in the pixel. Further checks are summarized at the end of the section and reported in the Appendix. The estimate is right-signed throughout; where a check moves its magnitude, we say so and say why.

Free-flow-onset threshold sensitivity. The instrument conditions on a lagged value of the endogenous variable: an accident qualifies only if its segment was free-flowing (SPI $\geq$ 0.90) in the hour before impact. Because this selects on transitory traffic states, the choice of threshold matters in two directions. Loosening it readmits accidents that congestion itself may have caused, reintroducing the reverse causality the restriction exists to remove. Tightening it conditions on increasingly unusual hours, raising the worry that the selected moments are transitorily atypical in temperature as well, so that mean reversion in the outcome masquerades as a treatment response. Table 8 re-estimates the preferred specification at onset thresholds of 0.85, 0.90 (the baseline), and 0.95. The estimate is right-signed at

every threshold, but its magnitude is sensitive to the choice: −2.3 and insignificant at 0.85, −5.05 at the baseline, and −11.1 ($p = 0.12$) at 0.95. The first-stage F falls from 140 to 52 to 10 as the treated sample shrinks toward the most strictly free-flowing segments. The strict end is weakly identified, so its point estimate should not be read at face value. Against the mean-reversion reading, the event-study temperature leads for free-flow-onset accidents are flat individually and jointly ($p = 0.98$; Section 5.1). Treated overpasses are therefore not selected on transitorily warm or cool moments, so there is no temperature reversion for the post-accident bin to inherit.

The sign and the qualitative conclusion are thus robust to the onset definition, but the point estimate is not. The sensitivity reinforces our reading of the magnitude as informative at the identified margin rather than sharply estimated.

Table 8: 2SLS estimates by free-flow-onset threshold

	(1) SPI ≥ 0.85	(2) SPI ≥ 0.90	(3) SPI ≥ 0.95
Speed performance index	-2.295	-5.053*	-11.054
	(1.670)	(2.767)	(7.114)
KP first-stage F	140.0	51.7	10.3
Free-flow-onset treated	6,037	4,851	3,085
Observations	3,513,865	3,512,679	3,510,913

Notes: The preferred specification (binary free-flow-onset instrument, LST in the near-road ring, weather controls) re-estimated with the onset threshold, the pre-accident speed performance index above which an accident qualifies as free-flow-onset, set to each stated value (0.90 is the baseline). Detector, date, and hour-of-day fixed effects; the sample pairs free-flow-onset-treated overpasses with no-accident controls. Standard errors, clustered by detector, in parentheses. * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

Is the near-road effect just stopped vehicles in the pixel? Because ECOSTRESS records the radiometric temperature of whatever fills a pixel, a queue of sun-heated vehicles could raise the measured near-road temperature without warming the surrounding environment. A back-of-envelope calculation (Table A.10) bounds this channel. Free-flow-onset accidents barely slow traffic, so they add only a few vehicles to the near-road ring. Even

generously hot vehicle surfaces raise the pixel mean by only about 0.015°C under the measured first stage. Vehicle composition can thus account for about a sixth of the near-road response under the measured accounting, and about 30 percent under the selection-adjusted one. Under that accounting, a larger first stage implies more marginal vehicles but also a larger reduced form. On either accounting the bulk of the response is genuine warming of the road environment (0.07°C of the measured 0.084, 0.08°C of the adjusted 0.113), consistent with the waste-heat mechanism.

Further checks. A prior-day placebo finds no significant effect of accidents at the same time on the previous day on today's surface temperature (Table A.6). Because adjacent detectors can share ECOSTRESS pixels, we also cluster at coarser spatial units. The standard error rises only modestly, from 2.77 at the detector to 3.05 at the freeway corridor (Table A.7), and to 2.81 with two-way detector-by-date clustering. The estimate stays right-signed with the accident's duration as an alternative or additional instrument, and with both the outcome and the speed performance index demeaned within three-kilometer cells (Table A.3). The Hansen J test does not reject the overidentified version ($p = 0.92$), though it has little power. We demean both because 87 percent of a detector's cell-mates lie on the same freeway, at a median distance of 938 meters, and are themselves partly treated. Leaving each detector out of its own cell mean gives -3.95. Table A.9 collects six further specifications. Downwind and upwind half-disks of the 500-meter buffer give estimates that do not differ significantly, so we do not lean on a thermal-dispersion interpretation (panel A). The estimate is also right-signed with one- and three-hour lookback windows (panel B) and after dropping control segments within two detector stations of an accident, which diverted traffic could affect (panel C). The same holds with a stricter detector data-completeness threshold (panel D) and with the nearest pixel or the buffer maximum as the outcome (panels E and F).

7 Conclusion

We estimate the short-run effect of freeway congestion on nearby surface temperature in California. Freeway accidents serve as an instrument for congestion, and the outcome is ECOSTRESS land surface temperature, matched to congestion at the same hour. The central estimate is the reduced form: a free-flow-onset accident raises near-road surface temperature by about 0.08°C over the following two hours, against flat pre-trends. The estimated effect is right-signed at every distance band. Expressed per unit of congestion, the response implies roughly 0.4 to 0.7°C per 10 mph of speed reduction, somewhat above the associational estimate of Lee and Berkelhammer (2025). We anchor the magnitude on this locally identified margin and report the full specification grid rather than a single number. The effect decays with distance from the freeway (a decline that is statistically significant when the rings are estimated jointly), and it remains right-signed in the outer ring that contains nearby residential areas.

A lesson that travels beyond this application concerns identification. Accidents are treated as exogenous instruments, yet they are not exogenous to congestion. An event study shows that congestion rises in the hours before a typical accident, so an instrument built from all accidents embeds reverse causality and yields a precise but contaminated estimate. Wherever events are used as instruments for the very conditions that make those events more likely, the same bias arises. Conditioning on the pre-event state (here, restricting to accidents that strike a free-flowing road) is a transparent remedy, at the cost of a smaller first stage.

The estimates bear on a concrete policy margin. Because they are identified from accident-induced episodes, they measure what incident detection and clearance programs mitigate. Beyond delay and emissions, each episode raises surface temperature on the road and its immediate surroundings, a thermal effect absent from standard accounts of congestion externalities.

The estimates have limitations. The per-unit magnitude is identified from a modest

congestion shock, so it is not tightly pinned down, and the temperature response in the residential ring is not statistically resolved. Our evidence speaks to where the response is, not to what carries it. The gradient shows no rise of the kind surface-street diversion would produce, but we do not establish a physical channel by which roadway heat would reach the outer rings, and we do not claim one. The estimates are local to California freeway segments with PeMS detectors and to the variation induced by free-flow-onset accidents, and need not extend to other settings or to longer-run or larger congestion changes.

Within those bounds, the paper contributes a credibly identified estimate of the congestion-heat relationship, and a transparent way to handle reverse causality in accident-based instruments. It also contributes a spatial measurement. Resolving the response in distance bands locates how far a roadway heat externality reaches relative to where people live (some 11 million Californians live within a kilometer of the studied segments). The measurement speaks to residential proximity to freeways and the spatial distribution of urban heat exposure. Whether the near-road and residential-area responses documented here are large enough to matter for health or welfare, and how they compare to the cost of congestion relief, are questions we leave to future work.

References

Abdel-Aty, M., Uddin, N., Pande, A., Abdalla, M. F., and Hsia, L. (2004). Predicting freeway crashes from loop detector data by matched case-control logistic regression. *Transportation Research Record*, 1897(1):88–95.

Anderson, M. L. (2014). Subways, strikes, and slowdowns: The impacts of public transit on traffic congestion. *American Economic Review*, 104(9):2763–2796.

Anderson, M. L. (2020). As the wind blows: The effects of long-term exposure to air pollution on mortality. *Journal of the European Economic Association*, 18(4):1886–1927.

Andrews, I., Stock, J. H., and Sun, L. (2019). Weak instruments in instrumental variables regression: Theory and practice. *Annual Review of Economics*, 11:727–753.

Angrist, J. D. and Pischke, J.-S. (2009). *Mostly Harmless Econometrics: An Empiricist's Companion*. Princeton University Press, Princeton, NJ.

Barth, M. and Boriboonsomsin, K. (2008). Real-world carbon dioxide impacts of traffic congestion. *Transportation Research Record*, 2058(1):163–171.

Baum, C. F., Schaffer, M. E., and Stillman, S. (2007). Enhanced routines for instrumental variables/generalized method of moments estimation and testing. *Stata Journal*, 7(4):465–506.

Beland, L.-P. and Brent, D. A. (2018). Traffic and crime. *Journal of Public Economics*, 160:96–116.

Blandhol, C., Bonney, J., Mogstad, M., and Torgovitsky, A. (2022). When is TSLS actually LATE? NBER Working Paper 29709, National Bureau of Economic Research.

Brinkman, J. and Lin, J. (2024). Freeway revolts! The quality of life effects of highways. *Review of Economics and Statistics*, 106(5):1268–1284.

California Department of Transportation (2026). Caltrans performance measurement system (PeMS). Station-hour traffic data and CHP incident logs, accessed for June 2018–March 2026.

Cao, D., Wu, J., Dong, X., Sun, H., Qu, X., and Yang, Z. (2021). Quantification of the impact of traffic incidents on speed reduction: A causal inference based approach. *Accident Analysis & Prevention*, 157:106163.

Chakraborty, T. et al. (2019). Disproportionately higher exposure to urban heat in lower-income neighborhoods: a multi-city perspective. *Environmental Research Letters*, 14(10):105003.

Chay, K. Y. and Greenstone, M. (2003). The impact of air pollution on infant mortality: Evidence from geographic variation in pollution shocks induced by a recession. *Quarterly Journal of Economics*, 118(3):1121–1167.

Chay, K. Y. and Greenstone, M. (2005). Does air quality matter? Evidence from the housing market. *Journal of Political Economy*, 113(2):376–424.

Currie, J., Davis, L., Greenstone, M., and Walker, R. (2015). Environmental health risks and housing values: Evidence from 1,600 toxic plant openings and closings. *American Economic Review*, 105(2):678–709.

Currie, J. and Walker, R. (2011). Traffic congestion and infant health: Evidence from E-ZPass. *American Economic Journal: Applied Economics*, 3(1):65–90.

Declet-Barreto, J., Brazel, A. J., Martin, C. A., Chow, W. T., and Harlan, S. L. (2013). Creating the park cool island in an inner-city neighborhood: heat mitigation strategy for phoenix, AZ. *Urban Ecosystems*, 16(3):617–635.

Deschênes, O. and Greenstone, M. (2007). The economic impacts of climate change: Evidence from agricultural output and random fluctuations in weather. *American Economic Review*, 97(1):354–385.

Duranton, G. and Turner, M. A. (2011). The fundamental law of road congestion: Evidence from US cities. *American Economic Review*, 101(6):2616–2652.

Fisher, J. B. et al. (2020). ECOSTRESS: NASA's next generation mission to measure evapotranspiration from the International Space Station. *Water Resources Research*, 56(4):e2019WR026058.

Gago, E. et al. (2013). Urban heat islands: mitigation strategies. *Renewable and Sustainable Energy Reviews*, 25:749–758.

Graff Zivin, J. and Neidell, M. (2012). The impact of pollution on worker productivity. *American Economic Review*, 102(7):3652–3673.

Greenstone, M. and Gayer, T. (2009). Quasi-experimental and experimental approaches to environmental economics. *Journal of Environmental Economics and Management*, 57(1):21–44.

Haule, H. J., Sando, T., Lentz, R., Chuan, C.-H., and Alluri, P. (2019). Evaluating the impact and clearance duration of freeway incidents. *International Journal of Transportation Science and Technology*, 8(1):13–24.

He, F., Yan, X., Liu, Y., and Ma, L. (2016). A traffic congestion assessment method for urban road networks based on speed performance index. *Procedia Engineering*, 137:425–433.

Health Effects Institute (2010). Traffic-related air pollution: A critical review of the literature on emissions, exposure, and health effects. Technical Report Special Report 17, Health Effects Institute, Boston, MA.

Heaviside, C., Macintyre, H., and Vardoulakis, S. (2017). The urban heat island: implications for health in a changing environment. *Current Environmental Health Reports*, 4(3):296–305.

Heaviside, C., Vardoulakis, S., and Cai, X.-M. (2016). Attribution of mortality to the urban heat island during heatwaves in the West Midlands, UK. *Environmental Health*, 15(S1):S27.

Herrnstadt, E., Heyes, A., Muehlegger, E., and Saberian, S. (2021). Air pollution and criminal activity: Microgeographic evidence from Chicago. *American Economic Journal: Applied Economics*, 13(4):70–100.

Hulley, G. and Hook, S. (2022). ECOSTRESS tiled land surface temperature and emissivity instantaneous L2 global 70 m V002. Data set, accessed via AppEEARS.

Husni, E., Prayoga, G. A., Tamba, J. D., Retnowati, Y., Fauzandi, F. I., Yusuf, R., and Yahya, B. N. (2022). Microclimate investigation of vehicular traffic on the urban heat island through IoT-based device. *Heliyon*, 8(11):e11739.

Isaksen, E. T. and Johansen, B. G. (2021). Congestion pricing, air pollution, and individual-level behavioural responses. Technical Report Working Paper 362, Grantham Research Institute on Climate Change and the Environment, London School of Economics.

Knittel, C. R., Miller, D. L., and Sanders, N. J. (2016). Caution, drivers! Children present: Traffic, pollution, and infant health. *Review of Economics and Statistics*, 98(2):350–366.

Lee, J. and Berkelhammer, M. (2025). Evaluating the influence of traffic congestion on surface urban heat island intensity. *Geophysical Research Letters*, 52(16):e2025GL116651.

Li, Y., Sun, Y., Li, J., and Gao, C. (2020). Socioeconomic drivers of urban heat island effect: Empirical evidence from major Chinese cities. *Sustainable Cities and Society*, 63:102425.

Miguel, E., Satyanath, S., and Sergenti, E. (2004). Economic shocks and civil conflict: An instrumental variables approach. *Journal of Political Economy*, 112(4):725–753.

Muñoz Sabater, J. (2019). ERA5-Land hourly data from 1950 to present. Data set, accessed 2026.

Muñoz Sabater, J., Dutra, E., Agustí-Panareda, A., Albergel, C., Arduini, G., Balsamo, G., Boussetta, S., Choulga, M., Harrigan, S., Hersbach, H., Martens, B., Miralles, D. G., Piles, M., Rodríguez-Fernández, N. J., Zsoter, E., Buontempo, C., and Thépaut, J.-N. (2021). ERA5-Land: a state-of-the-art global reanalysis dataset for land applications. *Earth System Science Data*, 13(9):4349–4383.

NASA Land Processes Distributed Active Archive Center (2024). ECOSTRESS ECO_L2T_LSTE version 2: product documentation and mission status. NASA LP DAAC. Mass storage unit anomalies suspended data acquisition 2018-09-29 to 2018-12-05 and 2019-03-14 to 2019-05-15.

National Weather Service (2024). Weather related fatality and injury statistics. National Oceanic and Atmospheric Administration, U.S. Department of Commerce. Accessed June 2026.

Oke, T. (1973). City size and the urban heat island. *Atmospheric Environment*, 7(8):769–779.

Quah, A. K. L. and Roth, M. (2012). Diurnal and weekly variation of anthropogenic heat emissions in a tropical city, Singapore. *Atmospheric Environment*, 46:92–103.

Sailor, D. J. (2011). A review of methods for estimating anthropogenic heat and moisture emissions in the urban environment. *International Journal of Climatology*, 31(2):189–199.

Sailor, D. J. and Lu, L. (2004). A top–down methodology for developing diurnal and seasonal anthropogenic heating profiles for urban areas. *Atmospheric Environment*, 38(17):2737–2748.

Santamouris, M., Cartalis, C., Synnefa, A., and Kolokotsa, D. (2015). On the impact of urban heat island and global warming on the power demand and electricity consumption of buildings—A review. *Energy and Buildings*, 98:119–124.

Seo, K., Golub, A., and Kuby, M. (2014). Combined impacts of highways and light rail transit on residential property values: a spatial hedonic price model for Phoenix, Arizona. *Journal of Transport Geography*, 41:53–62.

Tran, M.-T., Swindell, C., Yang, B., Skupin, A., and Akerkar, R. (2026). Quantifying the impact of transportation on urban heat islands. *Annals of the American Association of Geographers*, 116(5):1190–1210.

Tuholske, C., Caylor, K., Funk, C., Verdin, A., Sweeney, S., Grace, K., Peterson, P., and Evans, T. (2021). Global urban population exposure to extreme heat. *Proceedings of the National Academy of Sciences*, 118(41):e2024792118.

Xia, F., Cheng, X., Lei, Z., Xu, J., Liu, Y., Zhang, Y., and Zhang, Q. (2023). Heterogeneous impacts of local traffic congestion on local air pollution within a city: Utilizing taxi trajectory data. *Journal of Environmental Economics and Management*, 122:102896.


Yang, B., Hussey, O., and Alexander, S. (2026). Quantifying highway expansion impact on urban heat island effect in San Francisco Bay Area. *Cities*, 169:106555.

Yeo, H., Jang, K., Skabardonis, A., and Kang, S. (2013). Impact of traffic states on freeway crash involvement rates. *Accident Analysis & Prevention*, 50:713–723.

Appendix Additional Figures and Tables


Figures

Figure A.1: Event study, all accidents: speed performance index by time relative to the accident




Notes: Estimated $\hat{\phi}_{\ell,u}$ from equation (1) without the weather controls, $Y = \text{SPI}$. Detector + date + hour-of-day fixed effects; 95% CIs clustered at the detector; baseline = no accident within ±6 hours.

Figure A.2: Event study, all accidents: surface temperature by time relative to the accident




Notes: Same specification as Figure A.1, $Y = \text{LST}$ (°C) in the 500-meter buffer.

Figure A.3: Event study by accident onset, 500-meter buffer, without weather controls: speed performance index



Notes: Free-flow-onset accidents (segment free-flowing before impact) versus congested-onset accidents, estimated jointly. Detector + date + hour-of-day FE; 95% CIs clustered at the detector.

Figure A.4: Event study by accident onset, 500-meter buffer, without weather controls: surface temperature



Notes: Same specification as Figure A.3, $Y = \text{LST}$ (°C).

Tables

Table A.1: First stage: freeway accidents and the speed performance index

	(1) All accidents	(2) Free-flow onset	(3) Congested onset
Accident, any onset (prior 2h)	-0.0768***		
	(0.00214)		
Free-flow-onset accident (prior 2h)		-0.0152***	
		(0.00218)	
Congested-onset accident (prior 2h)			-0.143***
			(0.00333)
First-stage F (cluster-robust)	1,293.4	48.3	1,849.4
Treated (instrument=1)	10,483	5,378	5,075
Observations	3,890,495	3,885,390	3,885,087

Notes: Dependent variable is the speed performance index (speed / free-flow speed; lower = more congested), without weather controls. Detector (α_i), date (μ_d), and hour-of-day (λ_h) fixed effects; SE clustered at the detector. "All" uses every accident; "free-flow onset" restricts to accidents that struck while the segment was free-flowing (pre-accident SPI $\geq$ 0.90); "congested onset" restricts to accidents during existing congestion. Standard errors in parentheses; * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

Table A.2: Effect of congestion on land surface temperature: OLS and 2SLS

	(1) OLS	(2) 2SLS (all)	(3) 2SLS (free-flow)	(4) 2SLS (+vol)
Speed performance index	0.136**	-1.137**	-4.774	-1.187**
	(0.0590)	(0.493)	(3.477)	(0.499)
Traffic flow (1,000 veh/hr)				-0.0699***
				(0.0123)
Treated (instrument=1)	10,483	10,483	5,378	10,483
Observations	3,890,495	3,890,495	3,885,390	3,890,495

Notes: Outcome is LST (°C) in the 500-meter buffer, without weather controls; $\alpha_i + \mu_d + \lambda_h$ fixed effects; SE clustered at the detector. Columns: OLS; 2SLS with all accidents; 2SLS with free-flow-onset accidents (binary instrument); and 2SLS with all accidents adding contemporaneous traffic volume. Standard errors in parentheses; * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

Table A.3: 2SLS estimates by instrument and with spatial demeaning

	(1) Binary	(2) Duration	(3) Overidentified	(4) Spatially demeaned
Speed performance index	-4.774	-6.021*	-5.853*	-4.048*
	(3.477)	(3.388)	(3.062)	(2.318)
KP first-stage F	48.3	32.8	28.8	10.2
Hansen J p (overid)	–	–	0.921	–
Free-flow-onset treated	5,378	5,217	5,217	5,225
Observations	3,885,390	3,885,229	3,885,229	3,811,038

Notes: 2SLS estimates of the effect of the speed performance index on LST (°C) in the 500-meter buffer, without weather controls. The instrument is the free-flow-onset accident indicator in column (1), its duration in column (2), and both (overidentified) in column (3). Column (4) uses the binary instrument with both the outcome and the speed performance index demeaned against detectors in the same three-kilometer cell observed at the same overpass. Detector, date, and hour-of-day fixed effects; the sample pairs free-flow-onset-treated overpasses with no-accident controls. Standard errors, clustered by detector, in parentheses. * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

Table A.4: Overidentified 2SLS estimates by disk radius, with and without weather controls

	100 m disk		250 m disk		500 m disk	
	(1) No weather	(2) + Weather	(3) No weather	(4) + Weather	(5) No weather	(6) + Weather
Speed performance index	-6.581**	-5.357**	-6.148**	-4.974*	-5.853*	-4.298*
	(3.015)	(2.518)	(3.032)	(2.571)	(3.062)	(2.586)
KP first-stage F	29.5	29.7	29.3	29.3	28.8	28.9
Hansen J p (overid)	0.709	0.832	0.876	0.438	0.921	0.386
Free-flow-onset treated	4,954	4,699	5,108	4,843	5,217	4,944
Observations	3,690,632	3,512,527	3,806,820	3,623,207	3,885,229	3,697,660

Notes: 2SLS estimates of the effect of the speed performance index on LST (°C) in cumulative disks of the stated radius, instrumented by the free-flow-onset accident indicator and its duration (overidentified). "+ Weather" columns add air temperature, relative humidity, wind speed, and precipitation at the detector and overpass hour. Detector, date, and hour-of-day fixed effects; the sample pairs free-flow-onset-treated overpasses with no-accident controls. Standard errors, clustered by detector, in parentheses. * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

Table A.5: Reduced form without weather controls, by distance ring

	(1) 0–100 m (near-road)	(2) 100–500 m	(3) 500–1000 m
Free-flow-onset accident (prior 2h)	0.0995*	0.0672	0.0368
	(0.0517)	(0.0503)	(0.0514)
Free-flow-onset treated	5,110	5,058	5,309
Observations	3,690,788	3,635,480	3,834,079

Notes: Reduced-form regressions of ring-mean LST (°C) on the free-flow-onset accident indicator, on the sample pairing free-flow-onset-treated overpasses with no-accident controls, without weather controls; Table 3 adds them. All columns include detector, date, and hour-of-day fixed effects. Standard errors, clustered by detector, in parentheses. * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

Table A.6: Prior-day placebo: speed performance index and land surface temperature

	(1) Speed performance index	(2) LST (°C)
Prior-day ff accident	0.0085***	-0.0778
	(0.0016)	(0.0516)
Prior-day treated	5,329	5,329
Observations	3,880,012	3,880,012

Notes: Regressions of the speed performance index (column 1) and 500-meter LST (column 2) on an indicator for a free-flow-onset accident at the same time of day on the previous calendar day, estimated on the no-accident sample, without weather controls. Detector, date, and hour-of-day fixed effects; standard errors, clustered by detector, in parentheses. * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

Table A.7: 2SLS estimate by spatial clustering unit

	(1) Detector	(2) 5 km grid	(3) 10 km grid	(4) Corridor
Speed performance index	-5.053*	-5.053*	-5.053*	-5.053*
	(2.767)	(2.800)	(2.876)	(3.053)
Clusters	8,852	945	464	194
Observations	3,512,679	3,512,679	3,512,679	3,512,679

Notes: The preferred estimate (binary free-flow-onset instrument, LST in the near-road ring, weather controls, detector, date, and hour-of-day fixed effects) with standard errors clustered at progressively coarser spatial units: the detector (baseline), roughly 5- and 10-kilometer grid cells, and the freeway-by-direction corridor. The point estimate is identical by construction; only the standard error changes. * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

Table A.8: Weather and the free-flow-onset instrument

	(1) Free-flow-onset accident
Air temperature (°C)	2.58**
	(1.21)
Relative humidity (%)	0.63**
	(0.28)
Wind speed (m/s)	-4.83
	(2.97)
Precipitation (mm)	1.80
	(2.85)
Observations	3,697,817
Within R-squared	0.00002

Notes: Regression of the free-flow-onset accident indicator on the weather controls, on the sample pairing free-flow-onset-treated overpasses with no-accident controls. Coefficients and standard errors are multiplied by 10^5 for readability; the instrument's base rate is about 1.3×10^{-3}; the joint test of the four controls gives $F = 2.73$ ($p = 0.03$). Detector, date, and hour-of-day fixed effects; standard errors, clustered by detector, in parentheses. * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

Table A.9: 2SLS estimates under alternative specifications

	A. Wind direction		B. Lookback window	
	Downwind	Upwind	$h = 1$ hour	$h = 3$ hours
Speed performance index	-3.055	-4.130	-3.545	-5.011
	(2.851)	(2.908)	(3.494)	(4.088)
KP first-stage F	50.2	49.9	44.2	36.0
Free-flow-onset treated	5,065	5,062	2,594	7,658
Observations	3,667,815	3,667,347	3,688,272	3,690,801
	C. Adjacent segments		D. Data completeness	
	Full sample	Drop ±2 neighbors	100 m	500 m
Speed performance index	-5.053*	-5.773*	-5.661*	-4.541
	(2.767)	(2.983)	(3.122)	(3.249)
KP first-stage F	51.7	45.0	56.8	55.0
Free-flow-onset treated	4,851	4,700	4,257	4,489
Observations	3,512,679	3,500,442	3,136,191	3,302,563
	E. Nearest pixel	F. Maximum LST		
Speed performance index	-4.970	-4.438		
	(3.535)	(3.031)		
KP first-stage F	43.9	49.7		
Free-flow-onset treated	4,828	5,101		
Observations	3,470,881	3,697,798		

Notes: 2SLS estimates of the effect of the speed performance index on LST (°C), with the binary free-flow-onset instrument and detector, date, and hour-of-day fixed effects; the sample pairs free-flow-onset-treated overpasses with no-accident controls. Panel A: mean LST in the downwind and upwind halves of the 500-meter buffer, split by ERA5-Land wind direction at the overpass hour; weather controls. Panel B: LST in the near-road ring, with the instrument defined over a one- or a three-hour lookback window before the overpass (baseline: two hours); no weather controls. Panel C: LST in the near-road ring, weather controls; the second column drops control observations within two detector stations of an accident. Panel D: LST at the stated band, restricted to detector-hours with at least 90 percent of five-minute intervals observed (baseline: 50 percent); no weather controls. Panel E: LST of the single ECOSTRESS pixel nearest the detector; no weather controls. Panel F: maximum quality-passing pixel LST in the 500-meter buffer; weather controls. Standard errors, clustered by detector, in parentheses. * $p < 0.10$, ** $p < 0.05$, *** $p < 0.01$.

Table A.10: Vehicle-composition bound

	Measured	Selection-adjusted
Change in the speed performance index	-0.0165	-0.037
Added vehicles per kilometer	11.6	26.1
Added vehicles in the 200-meter segment	2.3	5.2
Added vehicle area (m^2)	23	52
Share of the near-road ring's area (%)	0.07	0.17
Implied rise in pixel-mean LST (°C)	0.015	0.033
Reduced form (°C)	0.084	0.113
Bound as a share of the reduced form (%)	18	29
Reduced form net of the bound (°C)	0.069	0.080

Notes: Density rises with the fall in the speed performance index ($k/k_{\text{jam}} = 1 - \text{SPI}$), at a jam density of 140 vehicles per kilometer per lane over five lanes. About 200 meters of freeway cross the near-road ring (radius 100 meters, about 31,000 m^2, 70-meter pixels). Each vehicle covers about 10 m^2, and vehicle surfaces are taken to be 20°C hotter than their surroundings. The selection-adjusted column nets the pseudo-event placebo's first stage (+0.0208) and reduced form (−0.030; Table 7) out of the measured ones. Rows are computed from unrounded inputs.