

**GLOBAL FLUX** S.A.S.SOLUCIONES PARA FLUIDOS
www.globalflux.com.co

FICHA TECNICA ROCIADORES N/X SEP 2017

** FIRE SPRINKLER**

Styles	Upright ,Pendent ,sidewall	
Bulb Nominal Dia. & Response	Standard Response,5mm	Quick Response,3mm
Thread Size [Optional]	NPT 1/2 or R1/2	
Nominal Orifice Size	1/2 Inch	
Nominal K-Factor	5.6 (U.S.)/80 (metric)	
Max. Working Pressure	175 psig/1.2 mpa (12 bar)	
Factory Hydrostatic Test	100% @ 500psig (3.4 mpa)	
Min. Operating Pressure	7 psig/0.048 mpa (0.48 bar)	
Sprinkler Finish [Optional]	Natural Brass, Chrome Plated or White Color Coated	
Escutcheon Finish	Chrome Plated or Color Coated In Any Color	
Listings and Approvals	ISO9001:2000/UL/FM/CCCF	

AVAILABLE TEMPERATURE RATING

Temp. Classification	Ordinary	Ordinary	Intermediate	Intermediate
Nominal Temp. Rating	135°F/57°C	155°F/68°C	175°F/79°C	200°F/93°C
Max. Ambient Temp. Allowed	115°F/46°C	135°F/57°C	155°F/68°C	180°F/82°C
Max. Recommended Ambient Temp.	100°F/38°C	100°F/38°C	150°F/65°C	150°F/65°C
Glass Bulb Color	Orange	Red	Yellow	Green

SPRINKLER MATERIALS

Frame	Bronze Forging DZR
Deflector	Brass UNS-28000
Glass Bulb	Glass with Glycerin Solution, JOB® G5 or F3
Set Screw	Brass UNS-28000
Button	Brass UNS-28000
Spring	Stainless Steel
Seal	Teflon® Tape
Standard Escutcheon	Cold Rolled Steel



www.globalflux.com.co

Tel: (4) 233-3915

Info@globalflux.com.co

Calle 86 No 50D-52 | Bodega 101 Barrio Aranjuez | Medellín