



GLOBAL FLUX

TIANJIN BAOLAI FORTUNE TRADE CO.,LTD

ADDRESS: 04, 9TH FLOOR, NINGTAI PLAZA, NO.1 XIAGUANG ROAD,

NANKAI DISTRICT, TIANJIN, CHINA

## MILL TEST CERTIFICATES

GLOBAL FLUX S.A.S.

SOLUCIONES PARA FLUIDOS  
www.globalflux.com.co

REF NO: BLHJYPO91C

DATE OF ISSUE: 22/Dec/2024

GOODS: ERW FIRE PIPES

SPECIFICATION: ASTM A795

INVOICE NO.: HJYPO91-GLOBAL

| HEAT NO. | SIZE    |         |          |            | AMOUNT PCS | THEORETICAL WEIGHT (MT) | CHEMICAL COMPOSITION (%) |      |      |       |       |       |       |       |       |       |       |       |         |       | TENSION TEST |      |      | PRESSURE | FLATTENING /BENDING TEST | NON-DESTRUCTIVE TEST | VISUAL DIMENSION |
|----------|---------|---------|----------|------------|------------|-------------------------|--------------------------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|---------|-------|--------------|------|------|----------|--------------------------|----------------------|------------------|
|          | SIZE MM | SIZE IN | W.T. SCH | LENGTH (M) |            |                         | C                        | Mn   | Si   | P     | S     | Cu    | Ni    | V     | Ti    | Cr    | Mo    | Ni+V  | Ni+V+Ti | Ce    | T.S.         | Y.P. | E.L. |          |                          |                      |                  |
|          |         |         |          |            |            |                         | Mpa                      | Mpa  | (%)  | PSI   |       |       |       |       |       |       |       |       |         |       |              |      |      |          |                          |                      |                  |
| 4B-08219 | 33.4    | 1"      | SCH40    | 5.80       | 1523       | 22.080                  | 0.29                     | 1.1  | 0.14 | 0.013 | 0.013 | 0.005 | 0.003 | 0.006 | 0.005 | 0.007 | 0.005 | 0.009 | 0.014   | 0.179 | 423          | 251  | 33   | 700      | G                        | G                    | G                |
| 4C-07318 | 42.2    | 1-1/4"  | SCH40    | 5.80       | 50         | 0.980                   | 0.29                     | 1.15 | 0.11 | 0.008 | 0.013 | 0.004 | 0.004 | 0.008 | 0.006 | 0.007 | 0.004 | 0.012 | 0.018   | 0.181 | 441          | 253  | 33   | 1000     | G                        | G                    | G                |
| 4A-09725 | 168.63  | 6"      | SCH40    | 5.80       | 50         | 8.210                   | 0.27                     | 1.08 | 0.11 | 0.015 | 0.011 | 0.005 | 0.002 | 0.008 | 0.003 | 0.007 | 0.005 | 0.01  | 0.013   | 0.164 | 449          | 245  | 31   | 1200     | G                        | G                    | G                |

## COATING TEST (EPOXY POWDER)

| Coating thickness<br>≥100μm | TEST ITEM                         | Cure time,min<br>(232°C±3°C) |                                             | Gel time, s<br>(205°C±3°C) |                                                       | Paricle size<br>//150μm,% |                            | Paricle size<br>//250μm,% |                                                                                                             | Thermal characteristics<br>//Tg1, °C<br>(20°C/min, N2) |                                     | Thermal characteristics<br>//Tg2, °C<br>(20°C/min, N2) |                                                                  | Thermal characteristics<br>ΔH, J/g<br>(20°C/min, N2) |   |
|-----------------------------|-----------------------------------|------------------------------|---------------------------------------------|----------------------------|-------------------------------------------------------|---------------------------|----------------------------|---------------------------|-------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|-------------------------------------|--------------------------------------------------------|------------------------------------------------------------------|------------------------------------------------------|---|
| 105                         | TEST METHOD                       | CSA<br>Z245.20-2018/12.1     |                                             | CSA<br>Z245.20-2018/12.2   |                                                       | CSA<br>Z245.20-2018/12.5  |                            | CSA<br>Z245.20-2018/12.5  |                                                                                                             | CSA<br>Z245.20-2018/12.7                               |                                     | CSA<br>Z245.20-2018/12.7                               |                                                                  | CSA<br>Z245.20-2018/12.7                             |   |
|                             | TEST RESULT                       | 0.5                          | G                                           | 14.90                      | G                                                     | 0.46                      | G                          | 0                         | G                                                                                                           | 63.9                                                   | G                                   | 101.2                                                  | G                                                                | 42.4                                                 | G |
| TEST ITEM                   | Bending resistance<br>(-30°C±3°C) |                              | Abrasive resistance<br>(CS-17, 1000g/1000r) |                            | Chemical Resistance<br>(PH2.5~3.0)<br>(20°C±3°C, 90d) |                           | Density, g/cm <sup>3</sup> |                           | Cathodic Disbondment, mm<br>(24h,65°C±3°C, -<br>3.5±0.15V,3%NaCl, Saturated<br>calomel reference electrode) |                                                        | Adhesion, Rating<br>(24h, 75°C±3°C) |                                                        | Moisture content of the epoxy powder-Mass loss<br>(105°C±3°C,2h) |                                                      |   |
| TEST METHOD                 | SY/T4113.3-2019                   |                              | GB/T 1768-2006                              |                            | SY/T4113.9-2020                                       |                           | CSA<br>Z245.20-2018/12.6   |                           | CSA<br>Z245.20-2018/12.8                                                                                    |                                                        | CSA<br>Z245.20-2018/12.14           |                                                        | CSA<br>Z245.20-2018/12.4                                         |                                                      |   |
| TEST RESULT                 | G                                 |                              | 69                                          | G                          | G                                                     |                           | 1.466                      | G                         | 1.1                                                                                                         | G                                                      | I                                   | G                                                      | 0.38                                                             | G                                                    |   |

WE HEREBY CERTIFY THAT:

1. THE MATERIAL HEREIN HAS BEEN TESTED IN ACCORDANCE WITH ABOVE SPECIFICATIONS AND THE RESULTS OF ALL TESTS ARE ACCEPTABLE.
2. TESTING RESULTS SHOWED THAT THE COAT WAS EXCELLENT IN ABRASION RESISTANCE, CORROSION RESISTANCE, STAIN RESISTANCE AND SLIP RESISTANCE.
3. UNDER NORMAL CIRCUMSTANCES, THE LIFE OF THE GOODS IS 15 YEARS.

SIGNATURE

天津宝来富特  
国际贸易有限公司

Typed by: 贾莹莹

Approved by: 张立

Date: 2024-12-22

GLOBAL FLUX S.A.S.

SOLUCIONES PARA FLUIDOS

GLOBAL FLUX S.A.S.

SOLUCIONES PARA FLUIDOS