


New Companies



Amber's conglomerate corporation just acquired some new companies. Each of the companies follows this hierarchy:



Given the table schemas below, write a query to print the *company_code*, *founder* name, total number of *lead* managers, total number of *senior* managers, total number of *managers*, and total number of *employees*. Order your output by ascending *company_code*.

Note:

- The tables may contain duplicate records.
- The *company_code* is string, so the sorting should not be **numeric**. For example, if the *company_codes* are *C_1*, *C_2*, and *C_10*, then the ascending *company_codes* will be *C_1*, *C_10*, and *C_2*.

Input Format

The following tables contain company data:

- Company*: The *company_code* is the code of the company and *founder* is the founder of the company.

Column	Type
company_code	String
founder	String

- Lead_Manager*: The *lead_manager_code* is the code of the lead manager, and the *company_code* is the code of the working company.

Column	Type
lead_manager_code	String
company_code	String

- Senior_Manager*: The *senior_manager_code* is the code of the senior manager, the *lead_manager_code* is the code of its lead manager, and the *company_code* is the code of the working company.

Column	Type
senior_manager_code	String
lead_manager_code	String
company_code	String

- Manager*: The *manager_code* is the code of the manager, the *senior_manager_code* is the code of its senior manager, the *lead_manager_code* is the code of its lead manager, and the *company_code* is the code of the working company.

Column	Type
manager_code	String
senior_manager_code	String
lead_manager_code	String
company_code	String

- *Employee*: The *employee_code* is the code of the employee, the *manager_code* is the code of its manager, the *senior_manager_code* is the code of its senior manager, the *lead_manager_code* is the code of its lead manager, and the *company_code* is the code of the working company.

Column	Type
employee_code	String
manager_code	String
senior_manager_code	String
lead_manager_code	String
company_code	String

Sample Input

Company Table:

company_code	founder
C1	Monika
C2	Samantha

Lead_Manager Table:

lead_manager_code	company_code
LM1	C1
LM2	C2

Senior_Manager Table:

senior_manager_code	lead_manager_code	company_code
SM1	LM1	C1
SM2	LM1	C1
SM3	LM2	C2

Manager Table:

manager_code	senior_manager_code	lead_manager_code	company_code
M1	SM1	LM1	C1
M2	SM3	LM2	C2
M3	SM3	LM2	C2

Employee Table:

employee_code	manager_code	senior_manager_code	lead_manager_code	company_code
E1	M1	SM1	LM1	C1
E2	M1	SM1	LM1	C1
E3	M2	SM3	LM2	C2
E4	M3	SM3	LM2	C2

Sample Output

```
C1 Monika 1 2 1 2
C2 Samantha 1 1 2 2
```

Explanation

In company *C1*, the only lead manager is *LM1*. There are two senior managers, *SM1* and *SM2*, under *LM1*. There is one manager, *M1*, under senior manager *SM1*. There are two employees, *E1* and *E2*, under manager *M1*.

In company *C2*, the only lead manager is *LM2*. There is one senior manager, *SM3*, under *LM2*. There are two managers, *M2* and *M3*, under senior manager *SM3*. There is one employee, *E3*, under manager *M2*, and another employee, *E4*, under manager, *M3*.

```
select
  company_code
, founder
, (
    select
      count(distinct lead_manager_code)
    from
      Lead_Manager
    where
      company_code=c.company_code
  )
, (
    select
      count(distinct senior_manager_code)
    from
      Senior_Manager
    where
      company_code=c.company_code
  )
, (
    select
      count(distinct manager_code)
    from
      Manager
    where
      company_code=c.company_code
  )
, (
    select
      count(distinct employee_code)
    from
      Employee
    where
      company_code=c.company_code
  )
from
  Company c
order by
  company_code
;
```