```c
/* creation of singly linked list & Operations On Singly Linked List
    ->insertion
        ->at begning
        ->at end
        ->at specificposition
    -> Deletion
        ->at begning
        ->at end
        ->at specificposition
    ->find the length of list
    ->reverce the list
// Created By SMIT
*/
#include<stdio.h>
#include<conio.h>
#include<stdlib.h>


//Global Declaractions
int count=0;
struct node{
    int data;
    struct node *next;
};
struct node *head=0,*temp;  //Global Pointers
void CreateList();  //To Create Link LIst
void InsAtBeg();    //To Insert Data At Beginig
void InsAtPos();    //This Function will Insert Data At Given Position
void InsAtEnd();    //To Insert Data At The End Of List
void DelAtBeg();    //To delete first Element/Node Of link list
void DelAtPos();    //To delete Spasific Node Of Link LIst
void DelAtEnd();    //To delete Last Node Of List
void FindLength();  //To find the length Of Link list
void ReverseList(); //To reverse The Link List
void Display();     //To Display Link LIst

int main(){
    int choice;
    while(choice!=11){      //This Loop Will Run Untill You Give 11 As an Input
        printf("\n**************MAIN MENU**************\n");
        //choice Must Beatween 1 To 11
        printf("1.Create a list\n");
        printf("2.insert at begning\n");
        printf("3.insert at  n(th) position\n");
        printf("4.insert at end\n");
        printf("5.delete from begning\n");
        printf("6.delete from n(th) position\n");
        printf("7.delete from end\n");
        printf("8.Find the length\n");
        printf("9.Reverse the Linked list\n");
        printf("10.Display Linked List\n");
        printf("11.exit\n");
        scanf("%d",&choice);

        //To Ran Spacific Function According To choice
    switch(choice){
        case 1:
            CreateList();
            break;
        case 2:
            InsAtBeg();
            break;
        case 3:
            InsAtPos();
            break;
        case 4:
            InsAtEnd();
            break;
        case 5:
```

```
            DelAtBeg();
            break;
        case 6:
            DelAtPos();
            break;
        case 7:
            DelAtEnd();
            break;
        case 8:
            FindLength();
            break;
        case 9:
            ReverseList();
            break;
        case 10:
            Display();
            break;
        case 11:
            exit(0);
            break;
        default:
            printf("\n\n\nEnter valid choice\n\n\n");
    }
}
    return 0;
// Created By SMIT
}

//This Function Will Create A Linked List
void CreateList(){
struct node *newnode;
int choice=1;
while(choice){
newnode=(struct node*)malloc(sizeof(struct node));
printf("Enter Data ");
scanf("%d",&newnode->data);
newnode->next=0;
if(head==0){
head=temp=newnode;
}
else{
    temp->next=newnode;
    temp=newnode;
}
printf("\nPress 0 to exit Press 1 To Add ");
scanf("%d",&choice);
count++;
}
printf("\n\n\n%d nodes created successfully\n\n\n",count);
}

//This Function Will Display The List
void Display(){
    if(head==0){
        printf("\n\n\nI Think You should Create A list First\n\n\n");
    }
    else{
        temp=head;
        printf("\n\n\nThe List is");
        while(temp!=0){
            printf("\n%d\n",temp->data);
            temp=temp->next;
        }
    }
}

//To Insert Node At Begning
void InsAtBeg(){
    if(head==0){
```

```
139             printf("\n\n\nPlease Create a List First\n\n\n");
140         }
141         else{
142         struct node *newnode;
143         newnode=(struct node *)malloc(sizeof(struct node));
144         printf("Enter data");
145         scanf("%d",&newnode->data);
146         newnode->next=head;
147         head=newnode;
148         }
149     }
150 
151     //To Insert Node At spacific Positon
152     void InsAtPos(){
153         if(head==0){
154             printf("\n\n\nPlease Create a List First\n\n\n");
155         }
156         else{
157             int pos,i=1;
158             printf("Enter Position");
159             scanf("%d",&pos);
160             if(pos>count){
161                 printf("Invalid Position");
162             }
163             else{
164                 struct node *newnode;
165                 temp=head;
166                 while(i<pos){
167                     temp=temp->next;
168                     i++;
169                 }
170                 newnode=(struct node*)malloc(sizeof(struct node));
171                 printf("Enter Data");
172                 scanf("%d",&newnode->data);
173                 newnode->next=temp->next;
174                 temp->next=newnode;
175             }
176         }
177     }
178 
179     //To Insert Node At The End Of List
180     void InsAtEnd(){
181         if(head==0){
182             printf("\n\n\nPlease Create a List First\n\n\n");
183         }
184         else{
185             struct node *newnode;
186             temp=head;
187             while(temp->next!=0){
188                 temp=temp->next;
189             }
190             newnode=(struct node*)malloc(sizeof(struct node));
191             printf("Enter Data");
192             scanf("%d",&newnode->data);
193             newnode->next=0;
194             temp->next=newnode;
195         }
196     }
197 
198     //To Delete First Node
199     void DelAtBeg(){
200         if(head==0){
201             printf("\n\n\nPlease Create a List First\n\n\n");
202         }
203         else{
204             temp=head;
205             head=temp->next;
206             free(temp);
207             printf("\n\n\nDeleted successfully..\n\n\n");
```

```
    }
}
// Created By Smit
//To Delete Node AT Spacific Position
void DelAtPos(){
    int pos,i=1;
    if(head==0){
        printf("\n\n\nPlease Create A list First\n\n\n");
    }
    else{
        struct node *deletethis;
        temp=head;
        printf("Enter Position ");
        scanf("%d",&pos);
        if(pos>count){
            printf("\n\nInvalid Position\n\n");
        }
        else{
            while(i<pos-1){
                temp=temp->next;
                i++;
            }
            deletethis=temp->next;
            temp->next=deletethis->next;
            free(deletethis);
            printf("\n\n\nDeleted successfully...\n\n\n");
        }
    }
}

//To Delete Last Node
void DelAtEnd(){
    if(head==0){
        printf("\n\n\nPlease Create A List First\n\n\n");
    }
    else{
        struct node *prev;
        temp=head;
        while(temp->next!=0){
            prev=temp;
            temp=temp->next;
        }
        free(temp);
        prev->next=0;
        printf("\n\n\nDeleted Successfully...\n\n\n");
    }
}

//To Find The Lenth Of List
void FindLength(){
    if(head==0){
        printf("\n\n\nYou can't find length Without Creating List\n\n\n");
    }
    else{
    temp=head;
    count=0;
    while(temp!=0)  {
        temp=temp->next;
        count++;
    }
    printf("\n\n\nThe Length Of Linked List Is %d \n\n\n",count);
    }
}

//To Reverse The List
void ReverseList(){
    if(head==0){
        printf("\n\n\nThere Is No List To Reverse\n\n\n");
    }
```

```
277       else{
278           struct node *previousnode,*currentnode,*nextnode;
279           previousnode=0;
280           currentnode=nextnode=head;
281           while(nextnode!=0){
282           nextnode=nextnode->next;
283           currentnode->next=previousnode;
284           previousnode=currentnode;
285           currentnode=nextnode;
286           }
287           head=previousnode;
288           printf("\n\n\nList Reversed Successfully..\n\n\n");
289       }
290   }
291   // Created By SMIT
292
```