

over the following questions based on Polymorphism in C++

What is the output of the following code?

```
#include<iostream>
using namespace std;
```

```
int grades(int a = 0, int b = 0, int c)
{ return (a + b + c); }
```

```
int main()
{
    cout << grades(10);
    return 0;
}
```

- a. 10
- b. 20
- c. 0
- d. Compile time error

OPTIONS

a

SKIP

SUBMIT AN

following questions based on Inheritance:

```
#include<iostream>
using namespace std;
```

```
class A
{
    int x;
public:
    void setX(int i) {x = i;}
    void print() { cout << x; }
};
```

```
class B: public A
{
public:
    B() { setX(10); }
};
```

```
class C: public A
{
public:
    C() { setX(20); }
};
```

```
class D: public B, public C {
};
```

```
int main()
{
    D d;
    d.print();
    return 0;
}
```

- a. 10
- b. 20
- c. 0
- d. error

Following questions based on Polymorphism in C++

Which class/set of classes can demonstrate polymorphism in the following code?

```
abstract class student
{
    public : int grades;
    calc_marks();
}
class student1:public student
{
    public : calc_marks()
    {
        return 20;
    }
};
class student2:public student
{
    public : calc_marks()
    {
        return 30;
    }
};
class fail{ int grades;
};
```

- a) Only class student can show polymorphism
- b) Only class student and student1 together can show polymorphism
- c) All class student, student1 and student2 together can show polymorphism
- d) Class fail should also inherit class student for this code to work for polymorphism

OPTIONS

SKIP

SUBMIT ANSWER

Choose correct option(1-marks)

Predict the output:

```
#include<iostream>
```

```
using namespace std;
```

```
int main()
```

```
{
```

```
    int arr[] = {10, 20, 30, 40, 50};
```

```
    int *p = arr;
```

```
    p += 3;
```

```
    cout<<*p;
```

```
    return 0;
```

```
}
```

a) 10

b) 20

c) 30

d) 40

OPTIONS

a

b

Choose correct option(2-marks)

Find the output for the following code?

```
#include <iostream>
using namespace std;
class student {
private:
    int age;
public:
    student() {
        age = 20;
    }
    student(int a) {
        age = a;
    }
    int getAge() {
        return age;
    }
};
int main() {
    student stu1, stu2(25);
    cout << "student1 Age = " << stu1.getAge() << endl;
    cout << "student2 Age = " << stu2.getAge() << endl;

    return 0;
}
```

- a. student1 Age=20
- b. student1 Age=20 student2 Age=25
- c. run time error
- d. student2 Age=25

OPTIONAL

SKIP

ed on Inheritance:

Choose correct option(1-marks)

What is the correct output of the following code in bytes?

```
#include <iostream>
using namespace std;
```

```
class Base {
    int ABC;
};
class Derived1 : Base {
};
class Derived2 : Derived1 {
};
int main()
{
    Derived2 D;

    cout << sizeof(D);

    return 0;
}
```

- a. 4
- b. 8
- c. 16
- d. Error

OPTIONS

Choose correct option(2-marks)

What is the output of the following program?

```
#include <iostream>
using namespace std;
class ABC {
private:
    int x;
```

```
public:
```

```
    ABC() : x(10) {}
```

```
    void operator ++() {
        x = x + 2;
```

```
    }
```

```
    void Print() {
```

```
        cout << "count: " << x;
```

```
    }
```

```
};
```

```
int main() {
```

```
    ABC obj;
```

```
    ++obj;
```

```
    obj.Print();
```

```
    return 0;
```

```
}
```

- a. count: 2
- b. count: 12
- c. count: 10
- d. count: 14

OPTIONS

Choose correct option(2-marks)

Which operator should be overloaded in the following code to make error free?

```
#include <iostream>
#include <string>
using namespace std;
class Box{
    int capacity;
public:
    Box(){}
    Box(double capacity){
        this->capacity = capacity;
    }
};
int main()
{
    Box b1(10);
    Box b2 = Box(14);
    if(b1 == b2){
        cout<<"Equal";
    }
    else{
        cout<<"Not Equal";
    }
    return 0;
}
```

- a. 0
- b. =
- c. ==
- d. +

Choose correct option(2-marks)

What will be the output of the following C++ code? #include using namespace std; class Test { protected: int x; public: Test (int i):x(i) { } void fun() const { cout << "fun() const " << endl; } void fun() { cout << "fun() " << endl; } }; int main() { Test t1 (10); const Test t2 (20); t1.fun(); t2.fun(); return 0; }

OPTIONS

fun() --- fun() const

fun() const --- fun()

fun() --- c) fun()

fun() const --- fun() const

SKIP

ing Language:

Choose correct option(2-marks)

What will be the output of the following C++ code? #include using namespace std; namespace first { int x = 5; int y = 10; } namespace second { double x = 3.1416; double y = 2.7183; } int main () { using first::x; using second::y; bool a, b; a = x > y; b = first::y < second::x; cout << a << b; return 0; }

OPTIONS

11

1

0

10

SKIP

Choose correct option(2-marks)

What will be the output of the following C++ code? #include <iostream> using namespace std; class B { int b; public: B(int i){ b = i; }; class C { B b; public: C(int i){ b = B(i); } friend void show(); }; void show() { C c(10); cout<<"value of b is: "<< c.b.b << endl; } int main(){ show(); return 0; }

OPTIONS

value of b is: 10

value of b is: 12345435

Error

Segmentation fault

SKIP



Questions:

Choose correct option(2-marks)

What will be the output of the following code: `#include using namespace std; class Box { private: int length; public: Box(); length(0) { } friend int printLength(Box); }; int printLength(Box b) { b.length += 10; return b.length; } int main() { Box b; cout << printLength(b) << endl; return 0; }`

OPTIONS

9

20

10

Error

SKIP





Choose correct option(2-marks)

ons:

What will be the output of the following C++ code? #include #include using namespace std; class Box { int capacity; public: Box(int cap){ capacity = cap; } friend void show(); }; void show() { Box b(10); cout<<"Value of capacity is: "<< b.capacity << endl; } int main() { show(); return 0; }

OPTIONS

Value of capacity is: 10

Value of capacity is: 100

Error

Segmentation fault

SKIP

Submit Answer

Choose correct option(2-marks)

ons:

What will be the output of the following code if two input values taken are 10 & 20.
`#include using namespace std; class base { int val1, val2; public: void get() { cout << "Enter two values: "; cin >> val1 >> val2; } friend float mean(base ob); }; float mean(base ob) { return float(ob.val1 + ob.val2) / 2; } int main() { base obj; obj.get(); cout << "Mean value is : " << mean(obj); return 0; }`

OPTIONS

10

20

15

SKIP

PASSAGE

Analyse the code based on Constructor and Destructor in C++ language and answer the following questions:

Choose correct option(1-marks)

What is the Output of the following program? #include using namespace std; class Point { Point() { cout << "Constructor called"; } }; int main() { Point t1; return 0; }

OPTIONS

No output

Compiler Error

Runtime Error

Constructor Called

Question 1

SKIP

SUBMIT ANSWER

Type here to search



03:04



15:01

15-03-2021

Choose correct option(2-marks)

What will be the output of the following C++ code? #include #include using namespace std; class Box { int capacity; public: Box(int cap){ capacity = cap; } friend void show(); }; void show() { Box b(10); cout<<"Value of capacity is: "<< b.capacity << endl; } int main() { show(); return 0; }

OPTIONS

Value of capacity is: 10

Value of capacity is: 100

Error

Segmentation fault

SKIP

SUBMIT ANSWER



INS

DEL

HOM

0

-

+

←

BACK
SPACE

Choose correct option(2-marks)

What will be the output of the following code if two input values take
#include using namespace std; class base { int val1, val2; public: void
"Enter two values:"; cin >> val1 >> val2; } friend float mean(base ob;
ob) { return float(ob.val1 + ob.val2) / 2; } int main() { base ob; ob.g
value is : " << mean(ob); return 0; }

OPTIONS

10

20

15

Error



Choose correct option(1-marks)

What is the output of this program? #include using namespace std; class TEMP { int x; public: TEMP(); ~TEMP(); void Show() const; }; TEMP::TEMP() { x = 50; } void TEMP::Show() const { cout<< x; } int main() { TEMP obj; obj.Show(); return 0; }


OPTIONS

50

Garbage value

Compile time error

run time error



Timer



Information

Question

Q4 / 40
▼**Choose correct option(1-marks)**

What will be the output of the following C++ code?
`#include using namespace std; int main() { int i; for(i=0; i < 10; i++); { cout << i; } return 0; }`

OPTIONS

123456789

10

12345678910

compile time error

SKIP

SUBMIT ANSWER