



CODERS LODGE

OBJECT ORIENTED PROGRAMMING USING C++

OOPS CONCEPT(CL1.1C++)

Kindly read the instructions carefully

1. All these questions are important for examination point of view, so practice them well.
2. If you have any doubt or facing any problem regarding these questions you can mail us at coderslodgeofficial@gmail.com or drop a message in our WhatsApp or telegram group.
3. If you want to support us, give your valuable feedback so that next time we can improve while interacting with you.
4. **Reminder**-Practice all questions well it will build your concept clear, and you can easily score good in your exams.

Connect with us

- If you want to join our **WhatsApp** community then mail us at:- coderslodgeofficial@gmail.com with your preferred branch(with year) and college name.
- Join our **Telegram** group:- <https://t.me/coderslodgeofficial>
- Like our **Facebook** page :- <https://www.facebook.com/coderslodge>
- Follow us on **Instagram**:-<https://www.instagram.com/coderslodge/>
- Follow us on **Twitter**:- <https://twitter.com/CodersLodge>
- Follow us on **Linkedin**:- <https://www.linkedin.com/company/coderslodge>

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

1. Predict the output of following C++ program.

```
#include<iostream>

using namespace std;

class A
{
    public:
    virtual void fun() {cout << "A" << endl ;}
};

class B: public A
{
    public:
    virtual void fun() {cout << "B" << endl;}
};

class C: public B
{
    public:
    virtual void fun() {cout << "C" << endl;}
};

int main()
{
    A *a = new C;
    A *b = new B;
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
a->fun();  
b->fun();  
return 0;  
}
```

**Output: C
B**

2. Predict the output of following C++ program.

```
#include<iostream>  
using namespace std;  
class A  
{  
    public :  
        int x=20;  
};  
class B  
{  
    public :  
        int x=10;  
};  
int main()  
{  
    A obj1;  
    B obj2;
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
obj1 = obj2;  
cout<< obj1.x;  
cout<<endl;  
return 0;  
}
```

Output: The program will not generate output due to compilation error.

3. Predict the output of following C++ program.

```
#include<iostream>  
using namespace std;  
  
int main()  
{  
    int *ptr = new int(5);  
    cout << *ptr;  
    return 0;  
}
```

Output: 5

4. What will be the output of the following C++ code?

```
#include <iostream>  
using namespace std;  
int main()  
{  
    int a = 5, b = 6, c;
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
c = (a > b) ? a : b;
```

```
cout << c;
```

```
return 0;
```

```
}
```

a) 6

b) 5

c) 4

d) 7

Answer: a

5. What will be the output of the following C++ code?

```
#include <iostream>
```

```
using namespace std;
```

```
int main()
```

```
{
```

```
    int n = 15;
```

```
    for ( ; ; )
```

```
        cout << n;
```

```
    return 0;
```

```
}
```

a) error

b) 15

c) infinite times of printing n

d) none of the mentioned

Answer: c

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



6. Predict the output of following C++ program.

```
#include<iostream>

using namespace std;

class Test
{
private:
    int x;
public:
    void setX (int x) { Test::x = x; }
    void print() { cout << "x = " << x << endl; }
};

int main()
{
    Test obj;
    int x = 40;
    obj.setX(x);
    obj.print();
    return 0;
}
```

Output: x=40



7. What will be the output of the following C++ code?

```
#include <iostream>

using namespace std;

int fun(int=0, int = 0);

int main()
{
    cout << fun(5);
    return 0;
}

int fun(int x, int y) { return (x+y); }
```

- a) -5
- b) 0
- c) 10
- d) 5

Answer: d

8. What will be the output of the following C++ code?

```
#include <iostream>

using namespace std;

int operate (int a, int b)
{
    return (a * b);
}

float operate (float a, float b)
```



CODERS LODGE

```
{  
    return (a / b);  
}  
  
int main()  
{  
    int x = 5, y = 2;  
    float n = 5.0, m = 2.0;  
    cout << operate(x, y) << "\\t";  
    cout << operate (n, m);  
    return 0;  
}
```

- a) 10.0 5.0
- b) 5.0 2.5
- c) 10.0 5
- d) 10 2.5

Answer: d

9. Predict the output of following C++ program

```
#include <iostream>  
  
using namespace std;  
  
class A  
{  
    int id;  
    static int count;
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
public:
    A()
    {
        count++;
        id = count;
        cout << "constructor called " << id << endl;
    }
    ~A()
    {
        cout << "destructor called " << id << endl;
    }
};

int A::count = 0;

int main()
{
    A a[2];
    return 0;
}
```

Output: constructor called 1
constructor called 2
destructor called 2
destructor called 1

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

10. What will be the output of the following C++ code?

```
#include <iostream>

using namespace std;

struct a
{
    int count;
};

struct b
{
    int* value;
};

struct c : public a, public b
{
};

int main()
{
    c* p = new c;
    p->value = 0;
    cout << "Inherited";
    return 0;
}
```

- a) Inherited
- b) Error

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

- c) Runtime error
- d) inherited

Answer: a

11. Predict the output of following C++ program.

```
#include <iostream>
using namespace std;
class A
{
public:
    void print() { cout << "A::print()"; }
};

class B : private A
{
public:
    void print() { cout << "B::print()"; }
};

class C : public B
{
public:
    void print() { A::print(); }
};
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
int main()
{
    C b;
    b.print();
}
```

Output: Compiler Error: 'A' is not an accessible base of 'C'

12. What will be the output of the following C++ code?

```
#include <iostream>
#include <string>
using namespace std;
class A
{
    int a, b;
    float d;
public:
    void change(int i){
        a = i;
    }
    void value_of_a(){
        cout<<a;
    }
}
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
};
```

```
class B: private A
```

```
{
```

```
};
```

```
int main(int argc, char const *argv[])
```

```
{
```

```
    B b;
```

```
    cout<<sizeof(B);
```

```
    return 0;
```

```
}
```

a) 8

b) 12

c) Error

d) Segmentation fault

Answer: b

13. What will be the output of the following C++ code?

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
class A{
```

```
    float d;
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
public:
    virtual void func(){
        cout<<"Hello this is class A\n";
    }
};

class B: public A{
    int a = 15;
public:
    void func(){
        cout<<"Hello this is class B\n";
    }
};

int main(int argc, char const *argv[])
{
    B b;
    b.func();
    return 0;
}
```

- a) Hello this is class B
- b) Hello this is class A
- c) Error
- d) Segmentation fault

Answer: a

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



14. Predict the output of following C++ program.

```
#include<iostream>

using namespace std;

class Base {
protected:
    int x;
public:
    Base (int i){ x = i;}
};

class Derived : public Base {
public:
    Derived (int i):Base(i) { }
    void print() { cout << x; }
};

int main()
{
    Derived d(10);
    d.print();
}
```

Output: 10

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



15. What will be the output of the following C++ code?

```
#include <iostream>

#include <string>

using namespace std;

class Mammal
{
public:
    virtual void Define(){
        cout<<"I'm a Mammal\n";
    }
};

class Human: public Mammal
{
private:
    void Define(){
        cout<<"I'm a Human\n";
    }
};

int main(int argc, char const *argv[])
{
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
Mammal *M = new Mammal();  
Human H;  
M = &H;  
M->Define();  
return 0;  
}
```

- a) Error
- b) Segmentation fault
- c) I'm a Human
- d) Garbage Value

Answer: c

16. Predict the output of following C++ program.

```
#include <iostream>  
using std::cout;  
class Test  
{  
public:  
    Test();  
    ~Test();  
};  
Test::Test()  
{  
    cout << "Constructor is executed\n";
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
}  
Test::~Test()  
{  
    cout << "Destructor is executed\n";  
}  
int main()  
{  
    delete new Test();  
    return 0;  
}
```

Output: Constructor is executed
Destructor is executed

17. What will be the output of the following C++ code?

```
#include <iostream>  
#include <string>  
using namespace std;
```

```
class A
```

```
{  
    int a;  
public:  
    A(){  
        a = 0;  
    }  
}
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
void show(){  
    a++;  
    cout<<"a: "<<a<<endl;  
}  
};  
  
class B: public A  
{  
    public:  
};  
  
int main(int argc, char const *argv[])  
{  
    B b;  
    b.show();  
    return 0;  
}
```

- a) a: 1
- b) a: 0
- c) Error
- d) Segmentation fault

Answer: a

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



18. What will be the output of the following C++ code?

```
#include <iostream>

#include <string>

#include <cstdlib>

using namespace std;

void func(int a, int b)
{

    if(b == 0){
        throw "This value of b will make the product zero. "
            "So please provide positive values.\n";
    }
    else{
        cout<<"Product of "<<a<<" and "<<b<<" is:
"<<a*b<<endl;
    }
}

int main()
{

    try{
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
func(5,0);  
  
}  
  
catch(const char* e){  
  
    cout<<e;  
  
}  
  
}
```

a) 0

b) 5

c) This value of b will make the product zero. So please provide positive values.

d) Product of 5 and 0 is: 0

Answer: c

19. What will be the output of this program?

```
#include <iostream>  
using namespace std;  
int a = 90;  
  
int fun(int x, int *y = &a)  
{  
    *y = x + *y;  
    return x + *y;  
}
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
int main()
{
    int a = 5, b = 10;

    a = fun(a);
    cout << a << " " << b << endl;

    b = fun(::a,&a);
    cout << a << " " << b << endl;

    return 0;
}
```

Output: 100 10
195 290

20. What will be the output of the following C++ code?

```
#include <iostream>
#include <string>
#include <cstdlib>
using namespace std;
class A
{
    int a;
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
public:  
    A(){}  
};
```

```
class B: public A  
{  
    int b;  
    public:  
    B(){}  
};  
  
void func()  
{  
    B b;  
    throw b;  
}
```

```
int main()  
{  
    try{  
        func();  
    }
```

```
    catch(A a){
```

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com



CODERS LODGE

```
        cout<<"Caught A Class\n";  
    }  
    catch(B b){  
        cout<<"Caught B Class\n";  
    }  
}
```

- a) Caught B Class
- b) Caught A Class
- c) Compile-time error
- d) Run-time error

Answer: b

CODERS LODGE

Kindly share your valuable feedback on
coderslodgeofficial@gmail.com