



MITx 6.86x

Machine Learning with Python-From Linear Models to Deep Learning

[Help](#)

smitha_kannur ▾

[Course](#)

[Progress](#)

[Dates](#)

[Discussion](#)

[Resources](#)

[Home](#) [Course](#) / [Unit 2 Nonlinear Classification, Linear regression, Collaborative Filtering \(2 weeks\)](#) / [Lecture 6. Nonlinear Classification](#)

[< Previous](#)



[Next >](#)

4. Motivation for Kernels: Computational Efficiency

[Bookmark this page](#)

Motivation for Kernels: Computational Efficiency

[Start of transcript. Skip to the end.](#)


The idea is that you can take inner products between high dimensional feature vectors and evaluate that inner product very cheaply.

And then, we can turn our algorithms into operating only in terms of these inner products.

Video

[Download video file](#)

Transcripts

[Download SubRip \(.srt\) file](#)
[Download Text \(.txt\) file](#)

Kernels as Dot Products 1

1/1 point (graded)

Let us go through the computation in the video above. Assume we map x and $x' \in \mathbb{R}^2$ to feature vectors $\phi(x)$ and $\phi(x')$ given by

$$\begin{aligned}\phi(x) &= [x_1, x_2, x_1^2, \sqrt{2}x_1x_2, x_2^2] \\ \phi(x') &= [x'_1, x'_2, x'^2_1, \sqrt{2}x'_1x'_2, x'^2_2].\end{aligned}$$

Which of the following equals the dot product $\phi(x) \cdot \phi(x')$?

☐ $x \cdot x'$

☒ $x \cdot x' + (x \cdot x')^2$

☐ $(x \cdot x')^2$

☐ $2(x \cdot x')^2$

☐ None of the above



Solution:

Expand $\phi(x) \cdot \phi(x')$ to get

$$\phi(x) \cdot \phi(x') = x_1x'_1 + x_2x'_2 + x_1^2x'^2_1 + 2x_1x'_1x_2x'_2 + x_2^2x'^2_2$$

$$\begin{aligned}
 &= (x_1 x'_1 + x_2 x'_2) + (x_1 x'_1 + x_2 x'_2)^2 \\
 &= x \cdot x' + (x \cdot x')^2.
 \end{aligned}$$

Remark: Notice the coefficient $\sqrt{2}$ of the $x_1 x_2$ terms is necessary for rewriting $\phi(x) \cdot \phi(x')$ as the function above of $x \cdot x'$.

Submit

You have used 1 of 1 attempt

i Answers are displayed within the problem

Kernels as Dot Products 2

1/1 point (graded)

Which of the following feature vectors $\phi(x)$ produces the kernel

$$K(x, x') = \phi(x) \cdot \phi(x') = x_1 x'_1 + x_2 x'_2 + x_3 x'_3 + x_2 x'_3 + x_3 x'_2$$

☐ $\phi(x) = [x_1, x_2, x_3]$

☐ $\phi(x) = [x_1 + x_2 + x_3]$

☒ $\phi(x) = [x_1, x_2 + x_3]$

☐ $\phi(x) = [x_1 + x_3, x_1 + x_2]$



Solution:

Directly expand to see the answer. The fact that there are mixed terms in the kernel, e.g. $x_2 x'_3$, indicates that some coordinates of the feature vector must be mixed, i.e. contain different x_i 's.

Submit

You have used 1 of 1 attempt

i Answers are displayed within the problem

Discussion

Hide Discussion

Topic: Unit 2 Nonlinear Classification, Linear regression, Collaborative Filtering (2 weeks): Lecture 6. Nonlinear Classification / 4. Motivation for Kernels: Computational Efficiency

Add a Post

Show all posts

by recent activity

? [why kernel is called kernel?](#)

10

[Hi, In kernel function, what is the meaning of kernel? Why it is called kernel?](#)

? [What does x' mean?](#)

2

[According to the last question, if we know phi x then we know about phi x'?](#)

💬 [Why Kernel?](#)

1

[Why do we calculate kernel with two feature vectors? where is this applied?](#)

? [Potential issue with the question "Kernels as Dot Products 1"](#)

2

Shouldn't the vectors in question "Kernels as Dot Products 1" be transposed in order for the answer you point as correct, to be correct? I...

? technical problem: mistakenly clicked on "save" after submitting a correct answer

After submitting a correct answer using my one available attempt, I mistakenly hit the "save" button to see what it would do. It seems to...

< Previous

Next >

© All Rights Reserved



edX

[About](#)

[Affiliates](#)

[edX for Business](#)

[Open edX](#)

[Careers](#)

[News](#)

Legal

[Terms of Service & Honor Code](#)

[Privacy Policy](#)

[Accessibility Policy](#)

[Trademark Policy](#)

[Sitemap](#)

Connect

[Blog](#)

[Contact Us](#)

[Help Center](#)

[Media Kit](#)

[Donate](#)



© 2020 edX Inc. All rights reserved.

深圳市恒宇博科技有限公司 [粤ICP备17044299号-2](#)