Frontiers of VR I

Cinematic VR, spatial sound, and the vestibular system

Gordon Wetzstein
Stanford University

EE 267 Virtual Reality

Lecture 13

stanford.edu/class/ee267/

Panoramic Imaging and Cinematic VR

Jaunt VR

Jaunt VR

Lytro

Lytro

Google

Nokia

Facebook

see Brian Cabral's SCIEN talk @ talks.stanford.edu


facebook
SURROUND360
facebook
SURROUND360

Red



Samsung

Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

center of projection



Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Stereo

stereo & no head rotation



Stereo Panorama

stereo & head rotation

Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Stereo

stereo & no head rotation



2 centers of projection!

Stereo Panorama

stereo & head rotation

Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Stereo

stereo & no head rotation



2 centers of projection!

Stereo Panorama

stereo & head rotation

Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Stereo

stereo & no head rotation



2 centers of projection!

Stereo Panorama

stereo & head rotation

Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Stereo

stereo & no head rotation



2 centers of projection!

Stereo Panorama

stereo & head rotation

Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Stereo

stereo & no head rotation



2 centers of projection!

Stereo Panorama

stereo & head rotation

Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Stereo

stereo & no head rotation



2 centers of projection!

Stereo Panorama

stereo & head rotation



Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Stereo

stereo & no head rotation



2 centers of projection!

Stereo Panorama

stereo & head rotation



Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Stereo

stereo & no head rotation



2 centers of projection!

Stereo Panorama

stereo & head rotation



Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Stereo

stereo & no head rotation



2 centers of projection!

Stereo Panorama

stereo & head rotation



Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Stereo

stereo & no head rotation



2 centers of projection!

Stereo Panorama

stereo & head rotation



multiple centers of projection

Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Stereo

stereo & no head rotation



2 centers of projection!

Stereo Panorama

stereo & head rotation



multiple centers of projection

Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation



1 center of projection!

Stereo

stereo & no head rotation



2 centers of projection!

Stereo Panorama

stereo & head rotation



multiple centers of projection

Panorama v Stereo Movie v Stereo Panorama

Light Field!

Stereo Panorama

stereo & head rotation



multiple centers of projection

Panorama v Stereo Movie v Stereo Panorama

Panorama

mono & head rotation

Ricoh Theta

Stereo

stereo & no head rotation

Stereo Panorama

stereo & head rotation

horizontal-only parallax

Panoramas

Slides from Marc Levoy's excellent CS 178 course

Stitching images together to make a mosaic

©Marc Levoy

Panoramas

Slides from Marc Levoy's excellent CS 178 course

What kind of transformation do we need?

translation?

rotation?

perspective!

©Marc Levoy

Panoramas

Slides from Marc Levoy's excellent CS 178 course

Stitching images together to make a mosaic

- step 1: find corresponding features in a pair of image
- step 2: compute perspective from 2nd to 1st image
- step 3: warp 2nd image so it overlays 1st image
- step 4: blend images where they overlap one another
- repeat for 3rd image and mosaic of first two, etc.

©Marc Levoy

Panoramas

Slides from Marc Levoy's excellent CS 178 course

Stitching images together to make a mosaic

- step 1: find corresponding features in a pair of image
- step 2: compute perspective from 2nd to 1st i
- step 3: warp 2nd image so it overlays 1st imag
- step 4: blend images where they overlap one another
- repeat for 3rd image and mosaic of first two, etc.

take CS 131, EE 368, EE 367!

©Marc Levoy

Panoramas

Slides from Marc Levoy's excellent CS 178 course

Example: the Matterhorn

common picture plane of mosaic image

perspective projection

©Marc Levoy

Panoramas

Slides from Marc Levoy's excellent CS 178 course

Using 4 shots instead of 3



perspective projection

© Marc Levoy

Slides from Marc Levoy's excellent CS 178 course

Cylindrical panoramas

- even works for 360° panorama



- project each image onto a cylinder
- a cylindrical image can be stored as a rectangular image

©Marc Levoy

Slides from Marc Levoy's excellent CS 178 course

Cylindrical panoramas

(FLASH DEMO)

http://graphics.stanford.edu/courses/cs178/applets/projection.html

- even works for 360° panorama



- project each image onto a cylinder
- a cylindrical image can be stored as a rectangular image
- to view without distortion, reproject part of the cylinder onto a picture plane representing the display screen
  - if your FOV is narrow, this view won't be too distorted

©Marc Levoy

Panoramas

Slides from Marc Levoy's excellent CS 178 course

Back to the Matterhorn

cylindrical projection

© Marc Levoy

Panoramas

Slides from Marc Levoy's excellent CS 178 course

Back to the Matterhorn

surface of cylinder

blended

©Marc Levoy

Panoramas

Slides from Marc Levoy's excellent CS 178 course

Spherical panoramas



- projections are to a sphere instead of a cylinder
- can't store as rectangular image without extreme stretching

©Marc Levoy

Panoramas

- see CS 178 and EE 368 course material for more detail

- now common in every image processing software and cellphone

A Pair of Mono Panoramas



side by Hari Lakshman (EE 368)

Head Rotation



could be IPD
Inter Pupillary Distance



side by Hari Lakshman (EE 368)

Image Pair for Each Direction



Store image pair for each direction → Problem: Too much data

side by Hari Lakshman (EE 368)

Approximation: Store only Middle Ray



Approximation: store only middle ray for L and R eyes for each direction

Omnistereo Panoramas



side by Hari Lakshman (EE 368)

Capture using Single Camera



Peleg et al. 2001

side by Hari Lakshman (EE 368)

Comparison: Mono and Stereo Panoramas



Central,
a.k.a. Mono

Omnistereo,
Multiperspective

Peleg et al. 2001

side by Hari Lakshman (EE 368)

Omnistereo example



Left panorama

Sphere-to-plane distortions

Right panorama

Disparity

side by Hari Lakshman (EE 368)

Multiperspective Projection

Jingyi Yu

Omnidirectional Stereo



Left Eye

Right Eye

widely used by YouTube VR, Google Daydream, Facebook, ...

Existing VR Cameras

Recorded Videos ~ 17 Gb/sec

Facebook's Surround 360

RAW Data: 17 Gb/sec

Compute time: days to weeks on conventional computer,
minutes to hours on data center

Facebook's Surround 360

RAW Data: 17 Gb/sec

Compute time: days to weeks on conventional computer,
minutes to hours on data center



Konrad et al., SIGGRAPH Asia 2017



Konrad et al., SIGGRAPH Asia 2017



Konrad et al., SIGGRAPH Asia 2017



Konrad et al., SIGGRAPH Asia 2017



Konrad et al., SIGGRAPH Asia 2017

Introduction to Spatial Sound

Overview

- what is sound? how do we synthesize it?
- the human auditory system
- stereophonic sound
- spatial audio of point sound sources
- surround sound
- ambisonics

What is Sound?

- “sound” is a pressure wave propagating in a medium

- speed of sound is $c = \sqrt{K/\rho}$ where c is velocity, ρ is density of medium and K is elastic bulk modulus

- in air, speed of sound is 340 m/s
- in water, speed of sound is 1,483 m/s

How do we Synthesize Sound?

https://www.youtube.com/watch?v=aDrs6EieFCM

Producing Sound

- Sound is longitudinal vibration of air particles
- Speakers create wavefronts by physically compressing the air, much like one could a slinky







The Human Auditory System

pinna





wikipedia

The Human Auditory System

- hair receptor cells pick up vibrations



wikipedia

The Human Auditory System

- Human hearing range: ~20–20,000 Hz
- Variation between individuals
- Degrades with age

Hearing Threshold in Quiet



D. W. Robinson and R. S. Dadson, 1957

The Human Auditory System

- human hearing range: ~20 – 20,000 Hz
- variation between individuals and changes with age



wikipedia

Bone Conduction

- can stimulate eardrum mechanically to create the illusion of audio, e.g. with bone conduction



http://www.goldendance.co.jp/English/boneconduct/01.html

the verge

Stereophonic Sound

- mainly captures differences between the ears:
  - interaural time difference
  - amplitude differences from body shape (nose, head, neck, shoulders, …)



wikipedia



Stereophonic Sound Recording

- use two microphones

- A-B techniques captures differences in time-of-arrival

Olympus



wikipedi

- other configurations work too, capture differences in amplitude


Rode

X-Y technique

Head-related Impulse Response (HRIR)

- models phase and amplitude differences for all possible sound directions parameterized by azimuth θ and elevation ϕ
- can be measured with two microphones in ears of mannequin & speakers all around

Zhong and Xie, “Head-Related Transfer Functions and Virtual Auditory Display”



Head-related Impulse Response (HRIR)

- CIPIC HRTF database: http://interface.cipic.ucdavis.edu/sound/hrtf.html
- elevation: -45° to 230.625° , azimuth: -80° to 80°
- need to interpolate between discretely sampled directions





Head-related Impulse Response (HRIR)

- measuring the HRIR
  - ideal case: scaled & shifted Dirac peaks





Head-related Impulse Response (HRIR)

- measuring the HRIR
  - ideal case: scaled & shifted Dirac peaks
  - in practice: more complicated, includes scattering in the ear, sholders etc.





Head-related Impulse Response (HRIR)

- measuring the HRIR
  - need one temporally-varying function for each angle
  - total of $2 \cdot N_\theta \cdot N_\phi \cdot N_t$ samples, where $N_{\theta,\phi,t}$ is the number of samples for azimuth, elevation, and time, respectively

$$hrir\_l(\theta,\phi,t)$$

$$hrir\_r(\theta,\phi,t)$$

Head-related Impulse Response (HRIR)

applying the HRIR:

- given a mono sound source $s(t)$ and it's 3D position

1. compute (θ_L, ϕ_L) and (θ_R, ϕ_R) relative to center of listener



Head-related Impulse Response (HRIR)

applying the HRIR:

- given a mono sound source $s(t)$ and it's 3D position

1. compute (θ_L, ϕ_L) and (θ_R, ϕ_R) relative to center of listener
2. look up measured HRIR for left and right ear at these angles



Head-related Impulse Response (HRIR)

applying the HRIR:

- given a mono sound source $s(t)$ and it's 3D position

1. compute (θ_L, ϕ_L) and (θ_R, ϕ_R) relative to center of listener
2. look up measured HRIR for left and right ear at these angles
3. convolve signal with HRIRs to get response for each ear as

$$s_L(t) = hrir\_l(\theta_L, \phi_L, t) * s(t)$$
$$s_R(t) = hrir\_r(\theta_R, \phi_R, t) * s(t)$$



Head-related Transfer Function (HRTF)

- HRTF is Fourier transform of HRIR! (you'll find the term HRTF more often that HRIR)

$$s_L(t) = hrir\_l(\theta_L, \phi_L, t) * s(t)$$
$$s_R(t) = hrir\_r(\theta_R, \phi_R, t) * s(t)$$

$$s_L(t) = F^{-1}\left\{hrtf\_l(\theta_L, \phi_L, \omega_t) \cdot F\{s(t)\}\right\}$$
$$s_R(t) = F^{-1}\left\{hrtf\_r(\theta_R, \phi_R, \omega_t) \cdot F\{s(t)\}\right\}$$





Head-related Transfer Function (HRTF)

- HRTF is Fourier transform of HRIR! (you'll find the term HRTF more often that HRIR)

$$s_L(t) = hrir\_l(\theta_L, \phi_L, t) * s(t)$$
$$s_R(t) = hrir\_r(\theta_R, \phi_R, t) * s(t)$$

convolution theorem

$$s_L(t) = F^{-1}\left\{hrtf\_l(\theta_L, \phi_L, \omega_t) \cdot F\{s(t)\}\right\}$$
$$s_R(t) = F^{-1}\left\{hrtf\_r(\theta_R, \phi_R, \omega_t) \cdot F\{s(t)\}\right\}$$





Head-related Transfer Function (HRTF)

- HRTF is Fourier transform of HRIR! (you'll find the term HRTF more often that HRIR)

$$s_L(t) = hrir\_l(\theta_L, \phi_L, t) * s(t)$$
$$s_R(t) = hrir\_r(\theta_R, \phi_R, t) * s(t)$$

$$s_L(t) = F^{-1}\left\{hrtf\_l(\theta_L, \phi_L, \omega_t) \cdot F\left\{s(t)\right\}\right\}$$
$$s_R(t) = F^{-1}\left\{hrtf\_r(\theta_R, \phi_R, \omega_t) \cdot F\left\{s(t)\right\}\right\}$$

- properties of HRTF:
  - complex-valued
  - symmetric (because HRIR is real-valued)



Head-related Transfer Function (HRTF)

$$s_L(t) = F^{-1}\left\{hrtf\_l(\theta_L, \phi_L, \omega_t) \cdot F\{s(t)\}\right\}$$
$$s_R(t) = F^{-1}\left\{hrtf\_r(\theta_R, \phi_R, \omega_t) \cdot F\{s(t)\}\right\}$$

Spatial Sound of 1 Point Sound Source

- given *s(t)* and 3D position, follow instructions from last slides by convolving Fourier transform of *s* with HRTFs for each each



Spatial Sound of N Point Sound Sources

- superposition principle holds, so just sum the contributions of each

$$s_L(t) = \sum_{i=1}^{N} F^{-1}\left\{ hrtf\_l\left(\theta_L^i, \phi_L^i, \omega_t\right) \cdot F\left\{ s_i(t) \right\} \right\}$$

$$s_R(t) = \sum_{i=1}^{N} F^{-1}\left\{ hrtf\_r\left(\theta_R^i, \phi_R^i, \omega_t\right) \cdot F\left\{ s_i(t) \right\} \right\}$$



Surround Sound

- approximate continuous wave field with discrete set of speakers

- most common:
  5.1 surround sound =
  5 (channels) . 1 (bass)

→ 6 channels total

Surround Sound

- approximate continuous wave field with discrete set of speakers
- can also use more speakers for “wave field synthesis” (i.e. audio hologram)





http://spatialaudio.net/

Surround Sound

- approximate continuous wave field with discrete set of speakers
- can also use more speakers for “wave field synthesis” (i.e. audio hologram)
- for wave field synthesis, phase of speakers needs to be synchronized, i.e. a phased array!

Surround Sound & HRTF

- for all speaker-based (surround) sound, we don't need an HRTF because the ears of the listener will apply them!
- speaker setup usually needs to be calibrated

Spatial Audio for VR

- VR/AR requires us to re-think audio, especially spatial audio!

- could use 5.1 surround sound and set up “virtual speakers” in the virtual environment – can use existing content, but not super easy to capture new content; also doesn’t capture directionality from above/below

Spatial Audio for VR

Two primary approaches:

1. Real-time sound engine
    - render 3D sound sources via HRTF in real-time, just as discussed in the previous slides
    - used for games and synthetic virtual environments
    - a lot of libraries available: FMOD, OpenAL, …

Spatial Audio for VR

Two primary approaches:

2. Spatial sound recorded from real environments
    - most widely used format now: ambisonics
    - simple microphones exist
    - relatively easy mathematical model
    - only need 4 channels for starters
    - used in YouTube VR and many other platforms

Ambisonics

- idea: represent sound incident at a point (i.e. the listener) with some directional information

- using all angles θ,ϕ is impractical – need too many sound channels (one for each direction)

- some lower-frequency (in direction) components may be sufficient → directional basis representation to the rescue!

Ambisonics – Spherical Harmonics

- use spherical harmonics!
- orthogonal basis functions on a sphere, i.e. full-sphere surround sound
- think Fourier transform acting on the directions of a sphere

Ambisonics – Spherical Harmonics



Ambisonics – Spherical Harmonics



1st order approximation

→ 4 channels: W, X, Y, Z

Ambisonics – Spherical Harmonics

- can easily convert a point sound source to the 4-channel ambisonics representation
- given azimuth and elevation θ, ϕ, compute W,X,Y,Z as

$$W = S \cdot \frac{1}{\sqrt{2}}$$ ← omnidirectional component (angle-independent)

$$X = S \cdot \cos\theta \cos\phi$$ ← "stereo in x"

$$Y = S \cdot \sin\theta \cos\phi$$ ← "stereo in y"

$$Z = S \cdot \sin\phi$$ ← "stereo in z"

Ambisonics – Spherical Harmonics

- can also record 4-channel ambisonics via special microphone
- same format supported by YouTube VR and other platforms

http://www.oktava-shop.com/

Ambisonics – Spherical Harmonics

- easiest way to render ambisonics: convert W,X,Y,Z channels into 4 virtual speaker positions
- for a regularly-spaced square setup, this results in

$$LF = (2W + X + Y)\sqrt{8}$$
$$LB = (2W - X + Y)\sqrt{8}$$
$$RF = (2W + X - Y)\sqrt{8}$$
$$RB = (2W - X - Y)\sqrt{8}$$



The Vestibular System

or “What else is happening in the inner ear?”

The Inner Ear



what's this?

hearing

wikipedia

Brief Overview of the Vestibular System

- provides sense of balance & gravity
- like IMUs – one in each ear!
- in each ear, sense linear (3 dof from otolithic organs) and angular (3 dof from 3 semicircular canals) acceleration via hair cells

Vestibulo-Ocular Reflex (VOR)



- vestibular system and ocular system are directly coupled in a feedback system
- enables low-latency “optical image stabilization” of the visual system with head motion

Motion Sickness

3 types of motion sickness (all related to visual-vestibular conflict theory):

1. Motion sickness caused by motion that is felt but not seen
2. Motion sickness caused by motion that is seen but not felt
3. Motion sickness caused when both systems detect motion but they do not correspond.

Motion Sickness

3 types of motion sickness (all related to visual-vestibular conflict theory):

1. Motion sickness caused by motion that is felt but not seen
2. Motion sickness caused by motion that is seen but not felt
3. Motion sickness caused when both systems detect motion but they do not correspond.

Example: car and sea sickness

Motion Sickness

3 types of motion sickness (all related to visual-vestibular conflict theory):

1. Motion sickness caused by motion that is felt but not seen
2. Motion sickness caused by motion that is seen but not felt
3. Motion sickness caused when both systems detect motion but they do not correspond.

Example: VR sickness or visually-induced motion sickness (VIMS)

Motion Sickness

3 types of motion sickness (all related to visual-vestibular conflict theory):

1. Motion sickness caused by motion that is felt but not seen
2. Motion sickness caused by motion that is seen but not felt
3. Motion sickness caused when both systems detect motion but they do not correspond.

Example: motion in low gravity

References and Further Reading

Panoramic Imaging and VR

- M. Brown, D. Lowe “Automatic Panoramic Image Stitching using Invariant Features”, IJCV 2007
- autostitch: http://matthewalunbrown.com/autostitch/autostitch.html
- S. Peleg, M. Ben-Ezra, Y. Pritch “Omnistereo: Panoramic Stereo Imaging” IEEE PAMI 2001
- Konrad et al. “SpinVR: Towards Live Streaming VR Video”, ACM SIGGRAPH Asia 2017

References and Further Reading - Spatial Sound

- Google's take on spatial audio: https://developers.google.com/vr/concepts/spatial-audio

HRTF:

- Algazi, Duda, Thompson, Avendado "The CIPIC HRTF Database", Proc. 2001 IEEE Workshop on Applications of Signal Processing to Audio and Electroacoustics
- download CIPIC HRTF database here: http://interface.cipic.ucdavis.edu/sound/hrtf.html

Resources by Google:

- https://github.com/GoogleChrome/omnitone
- https://developers.google.com/vr/concepts/spatial-audio
- https://opensource.googleblog.com/2016/07/omnitone-spatial-audio-on-web.html
- http://googlechrome.github.io/omnitone/#home
- https://github.com/google/spatial-media/