

# State of the Practice for Lattice Boltzmann Method Software

Spencer Smith<sup>a</sup>, Peter Michalski<sup>a</sup>, Jacques Carette<sup>a</sup>, Zahra Motamed<sup>b</sup>

<sup>a</sup>McMaster University, Computing and Software Department, 1280 Main Street West, Hamilton, L8S 4K1, Ontario, Canada

<sup>b</sup>McMaster University, Mechanical Engineering, 1280 Main Street West, Hamilton, L8S 4K1, Ontario, Canada

---

## Abstract

We analyze the state of software development practice for Lattice Boltzmann solvers by quantitatively and qualitatively measuring and comparing 24 software packages for 10 software qualities (installability, correctness/verifiability, reliability, robustness, usability, maintainability, reusability, understandability, visibility/transparency and reproducibility). Our reproducible analysis method employs a measurement template (containing 103 measures that are manually and automatically extracted from the project repository) and developer interviews (consisting of a set of 20 questions). From the measurement results, we ranked the software using the Analytic Hierarchy Process (AHP). Our ranking was roughly consistent with ranking the repositories by the number of GitHub stars, although the number one project by star count (Sailfish) is ranked 9th by our methodology. Our top three packages were ESPResSo, Ludwig, and Palabos (all in the top 10 by star count). We interviewed 4 developers to gain insight into their current pain points. Identified challenges include lack of development time, lack of funding, and difficulty with ensuring correctness. Based on our assessment, we make the following recommendations for current and future LBM projects: provide a detailed user manual and tutorials, explicitly state the limits of the software, use user-friendly programming languages, consider a peer review process, communicate development and contribution information, and use continuous integration and project management tools. [\[Change the abstract to discuss how LBM compares to common practices and best practices. Highlight some future practices. \[Follow the general research software trend of increasing use of version control systems and project management on GitHub or similar. —SS\] —SS\]](#)

**Keywords:** Lattice Boltzmann Method (LBM), scientific computing, software engineering, software quality, Analytic Hierarchy Process

---

## 1. Introduction

We analyze the development of Computational Fluid Dynamics (CFD) software packages that use the Lattice Boltzmann Method (LBM). LBM packages form a family of algorithms for simulating single-phase and multiphase fluid flows, often incorporating additional physical complexities (Chen and Doolen, 1998), such as reflective and non-reflective boundaries. LBM considers the behaviour of a collection of particles as a single unit at the mesoscopic scale, which lies between the nanoscopic and microscopic scales. LBM solvers predict the positional probability of a collection of particles moving through a lattice structure following a two step process: i) streaming, where the particles move along the lattice via links; and, ii) colliding, where energy and momentum is transferred among particles that collide (Bao and Meskas, 2011). As an example of the output of LBM, Figure 1 presents the streamlines of converged flow past a stationary circular cylinder with varying Reynolds numbers. [\[Zahra can likely provide a better example. —SS\]](#) LBM has several advantages over conventional CFD methods, including a simple calculation procedure, improved parallelization, and robust handling of complex geometries (Ganji and Kachapi, 2015).

A small sample of important applications of LBM include the following: designing fuel cells (Zhang et al., 2018), modelling groundwater flow (Anwar and Sukop, 2009), and analyzing the flow of blood in the cardiovascular system (Sadeghi et al., 2020). As these examples illustrate, LBM can be used for tackling problems that impact such areas as environmental policy, manufacturing, and health and safety. Given the important applications of LBM, users of the libraries will be concerned with software qualities like reliability, robustness, reproducibility, performance, correctness and verifiability. Since their time is valuable, developers that create or modify LBM libraries will have additional quality concerns, including maintainability, reusability, and understandability. With the quality considerations in




Figure 1: Streamlines of flow past a stationary circular cylinder at Reynolds number = 10, 20, and 40 (Chen et al., 2021)

mind, and the potentially overwhelming number of choices for existing LBM libraries, the time is right to assess the state of the practice. The goal of this report is to analyze the current state of LBM software development and compare it to the development practices employed for research software in general. We want to highlight success stories that LBM developers can share amongst their community, and with the broader research software community, while at the same time watching for areas for potential future improvement.

To focus our efforts, we devised 11 research questions. The questions are used to structure the discussion in the paper, so for each research question below we point to the section that contains our answer. The questions are inspired by the research questions that underpin our data collection methodology (Smith et al., 2021). We start with identifying the examples of LBM software where we have access to the source code:

RQ1: What LBM software projects exist, with the constraint that the source code must be available for all identified projects? (Section 2)

We next wish to assess the representative software to determine how well they apply current software development best practices. At this point in the process, to remove potential user/developer bias, we will base our assessment only on publicly available artifacts, where artifacts are the documents, scripts and code that we find in a project's public repository. Example artifacts include requirements, specifications, user manuals, unit test cases, system tests, usability tests, build scripts, API (Application Programming Interface) documentation, READMEs, license documents, process documents, and code. Following best practices does not guarantee popularity, so we will also compare our ranking to how the user community itself ranks the identified projects.

RQ2: Which of the projects identified in RQ1 follow current best practices, based on evidence found by experimenting with the software and searching the artifacts available in each project's repository? (Section 3)

RQ3: How similar is the list of top projects identified in RQ2 to the most popular projects, as viewed by the scientific community? (Section 4)

To understand the state of the practice we wish to learn the frequency with which different artifacts appear, the types of development tools used and the methodologies used for software development. With this data, we can ask questions about how LBM software compares to other research software. That is, in what ways does LBM follow the trends from other developer communities, and in which ways is it different?

RQ4: How do LBM projects compare to research software in general with respect to the artifacts present in their repositories? (Section 5)

RQ5: How do LBM projects compare to research software in general with respect to the use of tools (Section 6) for:

RQ5.a development; and,

RQ5.b project management?

RQ6: How do LBM projects compare to research software in general with respect to principles, processes and methodologies used? (Section 7)

Only so much information can be gleaned by looking at software repositories. To gain additional insight, we need to interview developers. We need to learn their concerns, how they deal with these concerns; we need to learn

what pain points exist for them. We wish to know what practices are used by the top LBM projects, so that others can potentially emulate these practices. We also wish to identify new practices by borrowing successful ideas from other domains. For LBM developers interested in future cutting edge practices, ideas that are proposed, but not yet in practice, should also be identified. The above points are covered by the questions outlined below:

RQ7: What are the pain points for developers working on LBM software projects? (Section 8)

RQ8: How do the pain points of developers from LBM compare to the pain points for research software in general? (Section 8)

RQ9: For LBM developers what specific best practices are taken to address the pain points and software quality concerns? (Section 9)

RQ10: What research software development practice could potentially address the pain point concerns identified in RQ7). (Section 10)

We investigated the research questions by applying the general methodology summarized in Smith et al. (2021). The specific application of the methodology to LBM is reviewed in Section 2, with the full details in (Michalski, 2021). The current methodology updates the approach used in prior assessments of domains like Geographic Information Systems (Smith et al., 2018b), Mesh Generators (Smith et al., 2016b), Oceanographic Software (Smith et al., 2015), Seismology software (Smith et al., 2018e), statistical software for psychology (Smith et al., 2018d) and medical image analysis software (Dong, 2021). [\[add citation to medical imaging software, if it is an option —SS\]](#)

With our methodology we start by identifying 24 LBM software packages. We then approximately measure the application of best practices for each package by filling in a grading template. Compared with our previous methodology (as used in (Smith et al., 2016b) for instance), the new methodology also includes repository based metrics, such as the number of files, number of lines of code, percentage of issues that are closed, etc. With the quantitative data in the grading template, we rank the software with the Analytic Hierarchy Process (AHP). After this, as another addition to our previous methodology, we interview some of the development teams to further understand the status of their development process. The quantitative and qualitative data is then used to answer the research questions (Sections 2 to 9). Finally, we summarize the threats to validity (Section 11) and the final conclusions and recommendations (Section 12).

## 2. Methodology

We developed a methodology for evaluating the state of the practice of scientific software (Smith et al., 2021). This methodology can be instantiated for a specific domain of scientific software, which in the current case is LBM software. Since we group best practices around conventional software qualities, the first section below provides definitions for the qualities of interest (Section 2.1), along with information on how we assessed these qualities. The following section (Section 2.2) provides an overview of the steps we used to select, measure and compare LBM software. The remaining sections provide details on each step of the steps in the methodology.

### 2.1. Software Qualities

We adopt software quality definitions from various researchers and subject matter experts. The following are the software quality definitions used in this exercise, along with comments regarding their measurement.

**Installability** Installability is measured by the effort required for the installation, uninstallation or reinstallation of a software product in a specified environment (ISO/IEC, 2011; Lenhard et al., 2013). A good measure of installability correlates with scenarios when low or moderate effort is required to gather and prepare software for its general use on a system for which it was designed. In our case effort includes the time spent finding and understanding the installation instructions, the person-time and resources spent performing the installation procedure, and the absence or ease of overcoming system compatibility issues. An installability score improves if the software has a means to validate the installation and instructions for uninstallation.

**Correctness** A software program is correct if it behaves according to its stated specifications (Ghezzi et al., 2003). This requires that the specification is available. Scientific software is unlikely to have an explicit specification, since this is not common practice in the field. As a consequence, the correctness of software cannot often be measured directly. We assess correctness indirectly by looking for the following: availability of a requirements specification, reference to domain theory, and explicit use of tools and/or techniques for building confidence, such as documentation generators and software analysis tools.

**Verifiability** An artifact (like code, or a theory manual) is verifiable if, and only if, every statement therein is verifiable. A statement is verifiable if, and only if, there exists some finite cost-effective process with which a person or machine can check that each statement is correct (adapted from recommended practice for requirements specifications (IEEE, 1998)). Similarly to correctness, verifiability is correlated with the availability of a specification and with reference to domain knowledge. A good measure of verifiability is further correlated with the availability of well written tutorials that include expected output, with software unit testing, and with evidence of continuous integration. In our process we measure correctness and verifiability together.

**Reliability** Reliability is measured by the probability of failure-free operation of a computer program in a specified environment for a specified time (Ghezzi et al., 2003; Musa et al., 1987). Reliability is thus positively correlated with the absence of errors during installation and use. Recoverability from errors also improves reliability.

**Robustness** Software possesses the characteristic of robustness if it behaves “reasonably” in two situations: i) when it encounters circumstances not anticipated in the requirements specification; and ii) when the assumptions in its requirements specification are violated (Boehm, 2007; Ghezzi et al., 1991). A good measure of robustness correlates with a reasonable reaction to unexpected input, including data of the wrong type, empty input, or missing files or links. Examples of reasonable reaction include an appropriate error message and the ability to recover the system.

**Performance** Performance is measured by the degree to which a system or component accomplishes its designated functions within given constraints, such as speed (database response times, for instance), throughput (transactions per second), capacity (concurrent usage loads), and timing (hard real-time demands) (IEEE, 1991; Wiegers, 2003). In this state of the practice assessment performance was not directly quantitatively measured. Instead the documentation of each software package was observed for information alluding to consideration of performance, such testing results, or parallelization instructions.

**Usability** Usability is measured by the extent to which a software product can be used by specified users to achieve specified goals with effectiveness, efficiency, and satisfaction in a specified context of use (Nielsen, 2012). We assumed that high usability correlates with the presence of documentation, including tutorials, manuals, defined user characteristics, and user support. Preferably the user support model will have avenues to contact developers and report issues.

**Maintainability** A measure of maintainability is the effort with which a software system or component can be modified to correct faults, improve performance or other attributes, and satisfy new requirements (IEEE, 1991; Boehm, 2007). In the current work maintainability is measured by the quality of documentation artifacts, and the presence of version control and issue tracking. These artifacts can greatly decrease the effort needed to modify software. There are many documentation artifacts that can improve maintainability, including user and developer manuals, specifications, README files, change logs, release notes, publications, forums, and instructional websites.

**Modifiability** Modifiability refers to the ease with which stable changes can be made to a system and the flexibility of the system to adopt such changes (801, 2017). We did not directly measure modifiability. Instead, developers were asked in interviews if they considered the ease of future changes when developing the software packages, specifically changes to the structure of the system, modules and code blocks. A follow up question is asked if any measures had been taken.

**Reusability** Reusability refers to the extent to which components of a software package can be used with or without adaptation in other software packages (Kalagiakos, 2003). A good measure of reusability results from a large

number of easily reusable components. Increased software modularization, defined as the presence of smaller components with well defined interfaces, is important. For this state of the practice assessment, we assumed that a good measure of reusability correlates with an increased number of code files, and the availability of API documentation.

**Understandability** Understandability is measured by the capability of the software package to enable the user to understand its suitability and function (ISO/IEC, 2001). It is an artifact-dependent quality. Understandability is different for the user-interface, source code, and documentation. In this state of the practice analysis, understandability focuses on the source code. It is measured by the consistency of a formatting style, the extend of modularization, the explicit identification of coding standards, the presence of meaningful identifiers, and the clarity of comments.

**Traceability** Traceability refers to the ability to link the software implementation and the software artifacts, especially the requirement specification (McCall et al., 1977). Similar to the quality of correctness, this requires the availability of some form of specification. This quality refers to keeping track of information as it changes forms or relates between artifacts. We did not quantitatively measure traceability. Instead, developers were asked in interviews how documentation fits into their development process.

**Visibility and Transparency** Visibility and transparency refer to the extent to which all of the steps of a software development process, and the current status of it, are conveyed clearly (Ghezzi et al., 1991). In this state of the practice assessment a good measure of visibility and transparency correlates with a well defined development process, documentation of the development process and environment and software package version release notes.

**Reproducibility** Software achieves reproducibility if another developer can take the requirements documentation and re-obtain the same software artifacts (Benureau and Rougier, 2017). This includes the output of the software, where the scientific results are compared between software implementations, or between software implementations and manually calculated results. We measured reproducibility qualitatively by asking developers if they have any concern that their computational results won't be reproducible, and if they have taken any steps to ensure reproducibility.

**Unambiguity** Unambiguity refers to the extent to which two readers have similar interpretations when reading software artifacts. In other words, artifacts are unambiguous if, and only if, they only have one interpretation (IEEE, 1998). This state of the practice assessment did not quantitatively measure unambiguity, but we did ask developers if they think that the current documentation can clearly convey all necessary knowledge to the users, and how they achieved this or what improvements are needed to achieve it.

## 2.2. Overall Process

The assessment was conducted via the following steps:

1. List candidate software packages for the domain. (Section 2.3)
2. Filter the software package list. (Section 2.4)
3. Gather the source code and documentation for each software package.
4. Collect quantitative measures from the project repositories. (Section 2.5)
5. Measure using the measurement template. The full measurement template can be found in Smith et al. (2021). (Section 2.5)
6. Survey the developers. (Section 2.7)
7. Use AHP to rank the software packages. (Section 2.6)
8. Analyze the results and answer the research questions.

The above steps depend on interaction with a Domain Expert partner, as discussed in Section 2.8.

### 2.3. Identify Candidate Software

To answer RQ1 we needed to identify existing LBM projects. The candidate software was found through search engine queries targeting authoritative lists of software. We found LBM software listed on GitHub and swMATH, as well as through scholarly articles. The Domain Expert (Section 2.8) was also engaged in selecting the candidate software.

The following properties were considered when creating the list and reviewing the candidate software:

1. The software functionality must fall within the identified domain.
2. The source code must be viewable.
3. The empirical measures should be available, which implies a preference for GitHub-style repositories.
4. The software cannot be marked as incomplete or in an initial state of development.

The initial list had 45 packages, including a few that were later found to not have publicly available source code, or to be incomplete projects.

### 2.4. Filter the Software List

To reduce the length of the list of software packages and to answer RQ1, we filter the initial list of 45. The following filters were applied in the priority order listed.

1. Scope: Software is removed by narrowing what functionality is considered to be within the scope of the domain.
2. Usage: Software packages were eliminated if their installation procedure was missing or not clear and easy to follow.
3. Age: The older software packages (age being measured by the last date when a change was made) were eliminated, except in the cases where an older software package appears to be highly recommended and currently in use.

For the third item in the above filter, software packages were characterized as ‘alive’ if their related documentation had been updated within the last 18 month. Packages were categorized as ‘dead’ if the last update of this information was more than 18 month ago.

Filtering by scope, usage, and age decreased the size of the list to 23 packages. Many of the 22 packages that were removed could not be tested as there was no installation guide, they were incomplete, source code was not publicly available, a license was needed, or the project was out of scope or not up to a standard that would support incorporating them into this study. These eliminated software packages are listed in the Appendix of Michalski (2021). Of the remaining 23 packages that were studied, some were kept on the list despite being marked as dead due to their prevalence on authoritative lists on LBM software and due to their surface excellence. After the initial measurement exercise, which took place in mid 2020, we added one more package in January 2022: Musubi. Musubi did not come up in our initial search, but once we learned of it, we felt that this report is incomplete without including it. With the addition of Musubi we did not update the manual collection of data for the previous packages, due to time constraints, but we did redo all data collection that was automated by tools.

The final list of 24 software packages that were analyzed in this project can be found in two tables. Table 1 lists packages that fell into the ‘alive’ category as of mid 2020 (January 2022 for Musubi), and Table 2 lists packages that were ‘dead’ at that time. The tables include a hyperlink to each project and, when available, citations for relevant publications. The final list of software packages shows considerable variation in purpose, size, user interfaces, and programming languages. For example, the OpenLB software package is predominantly a C++ package that makes use of hybrid parallelization and was designed to address a range of CFD problems (Heuveline et al., 2009). The software package pyLBM is an all-in-one Python language package for numerical simulations (Graille and Gouarin, 2017). ESPResSo is an extensible simulation package that is specifically for research on soft matter, and is written in C++ and Python (Weik et al., 2019). The HemeLB package is used for efficient simulation of fluid flow in several medical domains, and is written predominantly in C, C++, and Python (Mazzeo and Coveney, 2008).

Name	Released	Updated	Relevant Publication
DL_MESO (LBE)	unclear	2020 Mar	(Seaton et al., 2013)
ESPresSo	2010 Nov	2020 Jun	(Weik et al., 2019)
ESPresSo++	2011 Feb	2020 Apr	(Halverson et al., 2013)
lbmpy	unclear	2020 Jun	(Bauer et al., 2021b)
lettuce	2019 May	2020 Jul	(Bedrunka et al., 2021)
Ludwig	2018 Aug	2020 Jul	(Desplat et al., 2001)
LUMA	2016 Nov	2020 Feb	(Harwood et al., 2018)
MechSys	2008 Jun	2021 Oct	(Galindo-Torres, 2013)
Musubi	2013 Sep	2019 Aug	(Hasert et al., 2014)
OpenLB	2007 Jul	2019 Oct	(Heuveline and Krause, 2010)
Palabos	unclear	2020 Jul	(Latt et al., 2021)
pyLBM	2015 Jun	2020 Jun	
Sailfish	2012 Nov	2019 Jun	(Januszewski and Kostur, 2014)
TCLB	2013 Jun	2020 Apr	(Rokicki and Laniewski-Wollk, 2016)
waLBerla	2008 Aug	2020 Jul	(Bauer et al., 2021a)

Table 1: Alive Software Packages

Name	Released	Updated	Relevant Publication
HemeLB	2007 Jun	2018 Aug	(Mazzeo and Coveney, 2008)
laboetie	2014 Nov	2018 Aug	(Levesque et al., 2013)
LatBo.jl	2014 Aug	2017 Feb	
LB2D-Prime	2005	2012 Apr	
LB3D	unclear	2012 Mar	(Schmieschek et al., 2017)
LB3D-Prime	2005	2011 Oct	
LIMBES	2010 Nov	2014 Dec	
MP-LABS	2008 Jun	2014 Oct	
SunlightLB	2005 Sep	2012 Nov	

Table 2: Dead Software Packages

## 2.5. Quantitative Measures

We rank the projects by how well they follow best practices (RQ2) via a measurement template, as described in Smith et al. (2021). For each software package (each column in the template), we fill-in the rows of the template. This process takes about 2 hours per package, with a cap of 4 hours. The time constraint is necessary so that the work load is feasible for a team as small as one, given our aim to cap the measurement phase at 160 person hours (Smith et al., 2021). An excerpt of the template, in spreadsheet form, is shown in Figure 2.

Summary Information								
Software name?	DL_MESO	SunlightLB	MP-LABS	LIMBES	LB3D-Prime	LB2D-Prime	laboetie	Musubi
Number of developers	unclear	2	1	unclear	1	1	2	unknown
License?	terms of use	GNU GPL	GNU GPL	GNU GPL	unclear	unclear	GNU GPL	BSD
Platforms?	Windows, OS X,	Linux	Linux	Unix	Windows,	Windows,	Linux	Windows,
Software Category?	private	public	public	public	Linux	Linux	public	OS X, Linux
Development model?	freeware	open source	freeware	freeware	freeware	freeware	unclear	freeware
Programming language(s)?	FORTRAN, C++, Java	C, Perl, Python	FORTRAN, Markdown	FORTRAN	C	C, Shell	FORTRAN, Wolfram Markdown	Fortran
...	...	...	...	...	...	...	...	...
Installability								
Installation instructions?	yes	yes	yes	yes	yes	yes	yes	yes
Instructions in one place?	yes	yes	yes	yes	yes	yes	yes	yes
Linear instructions?	yes	yes	yes	yes	yes	yes	yes	yes
Installation automated?	yes, makefile	yes, makefile	yes, makefile	yes, makefile	yes, makefile	yes, makefile	yes, makefile	yes
Descriptive error messages?	yes	yes	no	n/a	n/a	no	n/a	n/a
Number of steps to install?	8	6	6	4	2	4	4	10
Number extra packages?	4	4	3	1	2	2	2	5
Package versions listed?	yes	no	no	no	no	no	no	no
Problems with uninstall?	unavail	unavail	unavail	unavail	unavail	unavail	unavail	unavail
...	...	...	...	...	...	...	...	...
Overall impression (1..10)?	9	7	6	8	7	5	7	8
...	...	...	...	...	...	...	...	...
Surface Reliability								
...	...	...	...	...	...	...	...	...

Figure 2: Excerpt of the Top Sections of the Measurement Template

The full template consists of 108 questions categorized under 9 qualities: (i) installability; (ii) correctness and verifiability; (iii) surface reliability; (iv) surface robustness; (v) surface usability; (vi) maintainability; (vii) reusability; (viii) surface understandability; and, (ix) visibility/transparency.

The questions were designed to be unambiguous, quantifiable and measurable with limited time and domain knowledge. The measures are grouped under headings for each quality, and one for summary information (Figure 2). The summary section provides general information, such as the software name, number of developers, etc. We follow the definitions given by Gewaltig and Cannon (2012) for the software categories. Public means software intended for public use. Private means software aimed only at a specific group, while the concept category is used for software written simply to demonstrate algorithms or concepts. The three categories of development models are: open source, where source code is freely available under an open source license; free-ware, where a binary or executable is provided for free; and, commercial, where the user must pay for the software product.

Several of the qualities use the word “surface”. This is to highlight that, for these qualities in particular, the best that we can do is a shallow measure. For instance, we do not conduct experiments to measure usability. Instead, we are looking for an indication that usability was considered by the developers by looking for cues in the documentation, such as getting started instructions, a user manual or documentation of expected user characteristics.

Tools were used to find some of the measurements, such as the number of files, number of lines of code (LOC), percentage of issues that are closed, etc. The tool GitStats was used to measure each software package’s GitHub



repository for the number of binary files, the number of added and deleted lines, and the number of commits over varying time intervals. The tool Sloc Cloc and Code (scc) was used to measure the number of text based files as well as the number of total, code, comment, and blank lines in each GitHub repository.

As in Smith et al. (2016b), Virtual machines (VMs) were used to provide an optimal testing environments for each package. VMs were used because it is easier to start with a fresh environment without having to worry about existing libraries and conflicts. Moreover, when the tests are complete the VM can be deleted, without any impact on the host operating system. The most significant advantage of using VMs is to level the playing field. Every software install starts from a clean slate, which removes “works-on-my-computer” errors.

## *2.6. Analytical Hierarchy Process*

Once we have measured each package, we still need to rank them to answer RQ2. To do this, we used the Analytical Hierarchy Process (AHP), a decision-making technique that is used to compare multiple options by multiple criteria. AHP was used for comparing and ranking the LBM software packages using the overall impression quality scores that were gathered in the measurement template. AHP performs a pairwise analysis using a matrix and generates an overall score as well as individual quality scores for each software package. (Smith et al., 2016b) shows how AHP is applied to ranking software based on quality measures.

This project used a tool for conducting this process. The tool includes a sensitivity analysis that was used to ensure that the software package rankings are appropriate with respect to the uncertainty of the quality scores. For the sensitivity analysis we modified the score by 10% for each package and verified that the overall ranking was stable. The README file of the tool includes requirements and usage information.

## *2.7. Interview Developers*

Several of the research question (RQ5, RQ6, RQ7, RQ9 and RQ10) require going beyond the quantitative data from the measurement template. To gain the required insight, we interviewed developers using a list of 20 questions from Smith et al. (2021). The questions cover the background of the development teams, the interviewees, and the software itself. We ask the developers how they organize their projects. We also ask them about their understanding of the users. Some questions focus on the current and past difficulties, and the solutions the team has found, or will try. We also discuss the importance of, and the current situation for, documentation. A few questions are about specific software qualities, such as maintainability, understandability, usability, and reproducibility. The interviews are semi-structured based on the question list; we ask follow-up questions when necessary. Based on our experience, the interviewees often bring up exciting and unexpected ideas.

We requested interviews with developers for all 24 packages, except Munubi, since Munubi was added after our ethics approved had expired. We were able to recruit 4 developers to participate in our study. Our potential interview subjects were found from project websites, code repositories, publications, and biographic information on institution web-pages. Meeting were held using on-line meeting software (either Zoom or Teams), which facilitated recording and automatic transcription of the meetings. Each meeting lasted about an hour. The interview process was approved by the McMaster University Research Ethics Board under the application number MREB#: 5219.

## *2.8. Interaction With Domain Expert*

We partnered with a Domain Expert to vet our list of projects (RQ1) and our ranking (RQ2). The Domain Expert is an important member of the state of the practice assessment team. Pitfalls exist if non-experts attempt to acquire an authoritative list of software, or try to definitively rank the software. Non-experts have the problem that they can only rely on information available on-line, which has the following drawbacks: i) the on-line resources could have false or inaccurate information; and, ii) the on-line resources could leave out relevant information that is so in-grained with experts that nobody thinks to explicitly record it. For the current assessment, our Domain Expert (and paper co-author) is Dr. Zahra Motamed, Assistant Professor of Mechanical Engineering at McMaster University, Hamilton, Ontario, Canada.

The Domain Expert has an important role with verifying the list of LBM packages. In advance of the first meeting with the Domain Expert, they were asked to create a list of top software packages in the domain. This is done to help the expert get in the right mind set in advance of the meeting. Moreover, by doing the exercise in advance, we avoid the potential pitfall of the expert approving the discovered list of software without giving it adequate thought. The

Name	Dim	Pll	Com	Rflx	MFl	Turb	CGE	OS
DL_MESO (LBE)	2, 3	MPI/OMP	Y	Y	Y	Y	Y	W, M, L
ESPResSo	1, 2, 3	CUDA/MPI	Y	Y	Y	Y	Y	M, L
ESPResSo++	1, 2, 3	MPI	Y	Y	Y	Y	Y	L
HemeLB	3	MPI	Y	Y	Y	Y	Y	L
laboetie	2, 3	MPI	Y	Y	Y	Y	Y	L
LatBo.jl	2, 3	-	Y	Y	Y	N	Y	L
LB2D-Prime	2	MPI	Y	Y	Y	Y	Y	W, L
LB3D	3	MPI	N	Y	Y	Y	Y	L
LB3D-Prime	3	MPI	Y	Y	Y	Y	Y	W, L
lbmpy	2, 3	CUDA	Y	Y	Y	Y	Y	L
lettuce	2, 3	CUDA	Y	Y	Y	Y	Y	W, M, L
LIMBES	2	OMP	Y	Y	N	N	Y	L
Ludwig	2, 3	MPI	Y	Y	Y	Y	Y	L
LUMA	2, 3	MPI	Y	Y	Y	Y	Y	W, M, L
MechSys	2, 3	-	Y	Y	Y	Y	Y	L
MP-LABS	2, 3	MPI/OMP	N	Y	Y	N	N	L
Musubi	2, 3	MPI	Y	Y	Y	Y	Y	W, L
OpenLB	1, 2, 3	MPI	Y	Y	Y	Y	Y	W, M, L
Palabos	2, 3	MPI	Y	Y	Y	Y	Y	W, L
pyLBM	1, 2, 3	MPI	Y	Y	N	Y	Y	W, M, L
Sailfish	2, 3	CUDA	Y	Y	Y	Y	Y	M, L
SunlightLB	3	-	Y	Y	N	N	Y	L
TCLB	2, 3	CUDA/MPI	Y	Y	Y	Y	Y	L
waLBerla	2, 3	MPI	Y	Y	Y	Y	Y	L

Table 3: Features of Software Packages (Dim for Dimension (1, 2, 3), Pll for Parallel (CUDA, MPI, OpenMP (OMP)), Com for Compressible (Yes or No), Rflx for Reflexive Boundary Condition (Yes or No), MFl for Multi-fluid (Yes or No), Turb for Turbulent (Yes or No), CGE for Complex Geometries (Yes or No), OS for Operating System (Windows (W), macOS (M), Linux (L)))

Domain Expert was also asked to vet the collected data and analysis. In particular, they were asked to vet the proposed list of software packages and the AHP ranking. These interactions were done via virtual meetings.

### 3. Ranking Projects Based on Quality Measures

In this section we answer RQ2 by using AHP to rank the identified LBM software against best practices. Before discussing quality differences between the packages and the results of the AHP ranking, we will contrast the different packages based on their features, as shown in Table 3. The set of LBM programs form a program family, or a software product line. The packages all have the commonality of using LBM techniques to simulate the motion of fluids, but there are also variabilities between them. LBM packages can be distinguished by the dimension of problems they simulate, whether or not (and how) they support parallel computation, whether or not compressibility can be considered, whether reflexive boundaries can be employed, whether the simulation handles multi-fluids, whether the simulations handles turbulence, and whether complex geometries can be simulated. All of these variabilities are listed as columns in Table 3 with the software listed in alphabetical order. A more complete analysis of the commonalities and variabilities between LBM packages is provided in Michalski (2021).

The sections below summarize how the software packages compare based on the qualities discussed in Section 2.1, as measured via the measurement template (Section 2.5). For the purpose of discussion, the last subsection combines all the qualities into one “global” ranking.

### 3.1. Installability

All of the 24 software packages that were tested have installation instructions. Most have their installation instructions located in one place, often in an instruction manual or on a web-page. Sometimes, like with Ludwig, incomplete installation instructions are found on a home page, with more detailed instructions located on another web-page, or within the documentation. Installability of the software, and maintainability and correctness of the instructions themselves, are improved if all the instructions are in one location.

All 24 packages on the short list can be installed on a Unix-like system. Eight packages could be installed on Windows, and five on macOS. Operating system requirements are listed in the documentation of 20 software packages, but compatible operating system versions are only specified in four packages (ESPResSo, LUMA, Mechsys, Sailfish). All but one of the software packages (TCLB) were tested on Ubuntu for this state of the practice assessment. TCLB was tested on CentOS, since CentOS is mentioned in its installation instructions.

All but one of the software packages (LatBo.jl) have automated at least some of the installation process. Most of these packages, such as waLBerla and SunlightLB, use Make to automate the installation, and a few of them, like lbmpy, use custom scripts.

Errors encountered during the installation process were often quickly fixed thanks to descriptive error messages. Systems that provided vague error messages, such as messages that did not specify which action or file was at fault, were more difficult to troubleshoot. Only three software packages (HemeLB, LB3D, lbmpy) that displayed a descriptive error message were not recoverable, and most of these instances were due to hardware and operating system incompatibility, such as the requirement of CUDA. Fourteen software packages broke during installation. Some packages, such as LB2D-Prime and LB3D-Prime, did not provide a definitive message of the success or failure of installation. In these instances, validating the installation required performing a tutorial or running a script, as described below, if these were available.

About half of the installation instructions are written as if the person doing the installation has none of the dependent packages installed. Unfortunately, software packages, like ESPResSo++, Ludwig, and LUMA, frequently don't list all of their dependencies, or provide only a partial list. Sometimes only an error message during the installation process informs the user of the requirement of these additional packages. A detailed rewrite of the installation instructions from the point of view of installation on a clean operating system is suggested. A clean environment can be achieved for testing purposes by using a virtual machine.

Seventeen software packages require less than 10 dependencies to be installed. All but one software package (LatBo.jl) require less than 20 dependencies. Some packages may automatically install additional dependencies in the background. Twenty of the software packages do not explicitly indicate the versions of software dependencies. Some software package installation issues, specifically those occurring when manual installation of dependencies is required, may be avoided if versions of dependencies are specified. Sixteen software packages do not have detailed instructions for installing dependencies. Sixteen software packages have less than 10 manual installation steps. If dependencies are installed in one command then none of the software packages take more than 20 steps to install. The average number of steps is about eight, and the fewest is two (LB3D-Prime).

All but six (ESPResSo, HemeLB, laboetie, LB3D-Prime, lbmpy, waLBerla) of the software packages have a way to verify the installation. Most have some sort of tutorial examples that can be run by the user. Some other ways of installation validation include validation scripts (LB2D-Prime, lettuce, Ludwig, LUMA), automatic validation after the installation (LatBo.jl), and instructions to manually review the file system (LIMBES). Uninstallation instructions were found for only one of the software packages: pyLBM.

Figure 3 shows the installability ranking of the software packages. Software packages with a higher score (ESPResSo, MechSys, OpenLB, DL\_MESO, Palabos) tend to have one set of linear installation instructions written as if the person doing the installation has none of the dependencies installed. The instructions often list compatible operating system versions and include instructions for the installation of dependencies. The top ranked packages often incorporate some sort of automation of the installation process and have fewer manual installation steps. The number of dependencies a package has does not correlate with a higher score. The ability to validate the installation process, often through tutorials or test examples that include expected output, is correlated with a higher score. Active work on a project seems to improve installability, since the top seven ranked packages are all classified as alive.




Figure 3: AHP Installability Score

### 3.2. Surface Correctness and Verifiability

Seventeen of the software packages explicitly reference domain theory, but a full and rigorous requirements specification, in the software engineering sense (IEEE, 1998; Robertson and Robertson, 1999; ESA, 1991), is absent from all of the projects. Software packages that include a subset of a requirements specification, such as DL\_MESO (LBE), keep the information brief and include it within other documents. When present, theory related information is generally found within a user manual, on a web-page, or in a cited publication. In the latter case significant time may be needed to track down the information.

Document generation tools are explicitly used by 13 software packages. Sphinx is used by eight of them, and Doxygen is used by eight. Several of the packages use both.

Tutorials are available for 19 of the software packages. Generally they are linearly written and easy to follow. However, only eight tutorials provide an expected output. It is not possible to verify the correctness of the output of the software packages that are missing this key information. In these cases the user may need to assume correctness if there are no visible errors. A particularly detailed tutorial that include expected output is provided by waLBerla.

Unit tests are only explicitly available for two of the software packages, Ludwig and Musubi. Code modularization of most packages allow for users to create tests with varying degrees of effort. These tests allow developers and users to verify the correctness of fragments of the source code, and in doing so better assess the correctness of the entire package.

The use of continuous integration tools and techniques alludes to a more refined development process where faults are isolated and better recognized. Only three of the packages (ESPResSo, Ludwig, Musubi) mentioned applying the practice of continuous integration in their development process.




Figure 4: AHP Surface Correctness and Verifiability Score

Figure 4 shows the ranking for surface correctness and verifiability. Software packages with a higher score tend to

have theory documentation. They also explicitly use at least one document generation tool that helps with verification, thus building confidence in correctness. The top ranked software packages all include an easy to follow getting started tutorial, and most of these include expected output. The two top ranked packages, Ludwig and Musubi, indicate the use of unit testing in their documentation. They also incorporated continuous integration in the development process. Furthermore, eight of the top 10 ranked packages are noted as being alive.

### 3.3. Surface Reliability

The analysis of surface reliability focused on package installation and tutorials. Errors occurred when installing 16 of the software packages. Every instance prompted an error message. These messages indicated unrecognized commands (even when following the installation guide), missing links, missing dependencies, and syntax errors in code files. In some instances the error messages were vague. Several automatic installation processes could not find and load dependencies. In these instances the installation tried to access outdated external repositories. Seven of the installations were recovered and verified, and one of the installations (LB3D-Prime) was assumed to be recovered due to the absence of any way to verify it. The installation of eight of the software packages could not be recovered. Most of these broken installations could not find external dependencies, encountered system incompatibilities, or displayed vague error messages.

Of the 14 software packages that installed correctly and also have tutorials, four (pyLBM, ESPResSo++, LIMBES, Ludwig) broke during tutorial testing. All of these instances resulted in an error message being displayed. One error (pyLBM) was due to a missing tutorial dependency, another (Ludwig) was due to an invalid command despite following the tutorial, and the final two errors were vague execution errors. Of the four broken tutorial instances, only the one that was missing a dependency was recoverable.




Figure 5: AHP Surface Reliability Score

Figure 5 shows the surface reliability ranking of the software packages. Software packages with a high score either did not break during installation, or the broken installation was recoverable. All of the top five ranked packages have tutorials. The package pyLBM broke during tutorial testing, but a descriptive error message helped in recovery. Nine of the top 10 ranked packages are noted as being alive.

### 3.4. Surface Robustness

The software packages were tested for handling unexpected input, including incorrect data types, empty input, and missing files or links. Success is predicated on a reasonable response from the system, including appropriate error messages and an absence of unrecoverable system failures.

Figure 6 shows the surface robustness ranking of the software packages. Software packages with a high score behaved reasonably in response to unexpected input as described above. All of the software packages that installed correctly passed this test. They output descriptive error messages or at least do not crash. Software packages with a lower surface robustness score did not install correctly, so their robustness score may not be a true reflection of runtime robustness. All successfully installed software packages that require a plain text input file correctly handled an unexpected change to these input files, including a replacement of new lines with carriage returns. Furthermore, nine of the top 10 ranked packages are noted as being alive.




Figure 6: AHP Surface Robustness Score

### 3.5. Surface Performance

Although the software packages all apply LBM to solve scientific computing problems, the packages focus on varied CFD problems, with varying parameters, and are technically different from each other (as shown in Table 3). Due to this, a comparison of run-time performance is not appropriate. Instead we looked through each software package’s artifacts for evidence that performance was considered. The artifacts of 18 software packages mentioned parallelization. This included GPU processing and the CUDA parallel computing platform, which were mentioned in the artifacts of 6 packages (ESPResSo, lbmpy, lettuce, pyLBM, Sailfish, TCLB). When a high degree of parallelization is possible GPUs provide superior speed compared to CPUs. The software package TCLB is implemented in a highly efficient multi-GPU code to achieve performance suitable for model optimization (Rutkowski et al., 2020). In the Ludwig package, a so-called mixed mode approach is used where fine-grained parallelism is implemented on the GPU, and MPI is used for even larger scale parallelism (Gray and Stratford, 2013). While one software package (Sailfish) required CUDA and GPU processing, some (ESPResSo, lbmpy, lettuce, pyLBM, TCLB) have the option of using either the GPU or the CPU. In general, the packages that require GPU and CUDA have better performance at the expense of installability and surface reliability.

### 3.6. Surface Usability

Software package artifacts were reviewed for the presence of a tutorial, a user manual, documented user characteristics, and a user support model. In total 19 software packages have a tutorial, 13 have a user manual, and 11 have both. The tutorials vary in scope and substance, and eight include expected output. Most user manuals are in the form of a file that can be downloaded, while some are rendered on a web-page. Some packages (waLBerla) do not have a user manual, but do have useful documentation distributed throughout their web-pages. Expected user characteristics are documented in five software packages (laboetie, LIMBES, Ludwig, Musubi, Palabos). Users are typically scientists or engineers. Their background is often physics, chemistry, biophysics, or mathematics. All but one of the packages (LIMBES) have a user support model, and many of them have multiple avenues of user support. The most popular avenue of support is Git, followed by email and forums. One software package (OpenLB) has an FAQ page.

Figure 7 shows the surface usability ranking of the software packages. Software packages with a high score have a tutorial and user manual, sometimes have documented user characteristics, and have at least one user support model. Many packages have several user support models. Furthermore, four of the top five packages are noted as being alive.

### 3.7. Maintainability

Software packages were reviewed for the presence of artifacts. Every type of artifact or file that is not a code file was recorded. The software packages were also reviewed for software release and documentation version numbers. This information can be used to troubleshoot issues and organize documentation. All but three software packages (LatBo.jl, LB3D-Prime, MechSys) have source code release and documentation version numbers.




Figure 7: AHP Surface Usability Score

When present, information on how code is reviewed, or how to contribute to the project was also noted. In total, 11 software packages have this information, which was found in various artifacts, including in developer guides, contributor guides, user guides, developer web-pages, and README files.

Issue tracking is used in 23 software packages, 15 of which use GitHub or GitLab to host their git repository, seven use email, and one (SunlightLB) uses SourceForge. Most software packages that use GitHub/GitLab have most of their issues closed, and only three (laboetie, lettuce, Sailfish) have less than 50 percent of their issues closed. All of the top five overall ranked packages have most of their issues closed. Alive packages (11 use issue tracking) have 64% of their issues closed, while dead packages (3 use issue tracking) have 71% of their issues closed. This information is presented in Table 4. With respect to the host for the git repository, 13 packages use GitHub and two (Palabos, walBerla) use GitLab. Of the other packages, one package (SunlightLB) uses CVS for issue tracking and version control, and seven packages do not appear to use any issue tracking system.

Software package code files were further measured for the percentage of code that is comments. The findings are presented in Table 4, sorted by the percentage. Packages with a higher percentage of comments were assumed to be more maintainable. Comments represent more than 10 percent of code files in 16 packages, and the average percentage of code comments is about 14 percent. All of the top five overall ranked packages have more than the average. LUMA has only 0.2 percent comments, the fewest of any package. This package has the most lines of source code, with over four million. The next largest package is ESPResSo++ with one million.




Figure 8: AHP Maintainability Score

Figure 8 shows the maintainability ranking of the software packages. Software packages with a high score provide version numbers on documents and source code releases, have an abundance of high quality artifacts, and use an issue tracking tool and version control system. These packages also appear to manage their issue tracking, having most of their issues closed. Their code files are well commented with more than 10 percent of the code being comments. Four

Name	% Issues Closed	% Code Comments	Status
MP-LABS	100.00	26.67	Dead
Musubi	Not Git	24.19	Alive
waLBerla	72.90	22.62	Alive
OpenLB	Not Git	22.43	Alive
ESPResSo	89.26	21.78	Alive
Ludwig	60.00	20.70	Alive
Palabos	89.47	17.76	Alive
SunlightLB	Not Git	17.67	Dead
LIMBES	Not Git	17.39	Dead
ESPResSo++	66.28	17.10	Alive
HemeLB	No Issues	16.68	Dead
pyLBM	66.67	16.12	Alive
MechSys	Not Git	15.11	Alive
LB3D-Prime	Not Git	14.34	Dead
LB3D	Not Git	13.76	Dead
LB2D-Prime	Not Git	13.61	Dead
Sailfish	22.22	9.26	Alive
lettuce	33.33	8.19	Alive
DL_MESO (LBE)	Not Git	8.06	Alive
TCLB	60.32	6.02	Alive
laboetie	18.75	2.47	Dead
lbmpy	58.33	2.03	Alive
LatBo.jl	93.33	0.40	Dead
LUMA	85.71	0.20	Alive

Table 4: Git Repository Data, Sorted by Percentage of Code that is Comments



of the top 5 ranked packages are noted as being alive.

### 3.8. Reusability

We measured the total number of source code files for each project. We assume that a large number of source files is associated with increased reusability, due to our assumption that this indicates increased modularization. Some packages have more features than others. This is assumed to contribute to reusability, since they have more source code for potential reuse. The software packages were also reviewed for the presence of API documentation, which indicates that a software package was developed with interaction between other software applications in mind.




Figure 9: AHP Reusability Score

Figure 9 shows the reusability ranking of the software packages. Software packages with a high score have thousands of source code files and API documentation. The highest scoring packages, ESPResSo and waLBerla, have extensive functionality, including graphical visualizations and non-LBM modelling. For this reason, a comparison with other software packages is not on a level field. However, these packages do have an abundance of reusable components. Nine of the top 10 ranked packages are noted as being alive.

Table 5 shows file and Lines Of Code (LOC) data for the software packages. Packages with a high reusability score do not have as many LOC per text file, generally having a few hundred lines or less. This suggests that the source code of these packages is likely functionally modularized, and modules could be reused in other projects.

The package waLBerla scored high on reusability because of its focus on modularity. The modularity in the waLBerla framework was included to enhance productivity, reusability, and maintainability (Bauer et al., 2021a). The design of waLBerla has enabled it to be successfully applied in several projects as a basis for various extensions (Bauer et al., 2021a).

### 3.9. Surface Understandability

Ten random source code files of each software package were reviewed for several measures. This assessment of surface understandability may not perfectly reflect each package, due to the practical limitation of only examining 10 files.

All of the packages appear to have consistent indentation and formatting. Only HemeLB, LUMA, and Musubi explicitly identify coding standards that are used during development. Generally, the software packages use consistent, distinctive, and meaningful code identifiers. Only four packages (LB2D-Prime, LB3D-Prime, LIMBES, MP-LABS) appear to use vague identifiers, such as single letters for variables. Symbolic constants were observed in the source code of 13 packages. The constants are used for various parameters, mathematical constants, and matrix definitions. All of the packages are reasonably well commented, with the comments clearly indicating what is being done (as opposed to how it is being done). Domain algorithms are noted in the source code of 11 packages. Table 5 suggests that the software packages are modularized to various degrees. When observing the source code files, it was found that 14 of the packages have a consistent style and order of function parameters.

Figure 10 shows the surface understandability ranking of the software packages. Software packages with a high score have a consistent indentation and formatting style, and consistent, distinctive, and meaningful code identifiers.

Name	Text Files	Binary Files	LOC	Avg. LOC / Text File
LUMA	314	19	4399723	14011
LatBo.jl	41	0	42172	1029
LB2D-Prime	82	19	54755	668
LB3D-Prime	23	6	12944	563
DL_MESO (LBE)	310	51	170223	549
LB3D	99	76	39766	402
laboetie	133	1	48403	364
waLBerla	2643	69	873988	331
MechSys	333	3	95707	287
Palabos	1974	71	563841	286
lbmpy	250	29	61632	247
SunlightLB	36	1	7646	212
Musubi	1347	1839	281879	209
LIMBES	26	1	4872	187
Ludwig	954	32	162518	170
OpenLB	1438	7	218406	152
ESPresSo	1390	83	195083	140
MP-LABS	307	3	43124	140
pyLBM	272	108	37234	137
ESPresSo++	1406	30	165194	118
HemeLB	1102	44	123806	112
Sailfish	632	11	69398	110
lettuce	73	1	7660	105
TCLB	594	7	49156	83

Table 5: Module Data




Figure 10: AHP Understandability Score

They also have symbolic constants, and explicitly identify mathematical and LBM algorithms. Their comments are clear and indicate what is being done in the source code. The source code is well modularized and structured. All of the top five ranked packages are noted as being alive.

### 3.10. Visibility and Transparency

Software package artifacts were reviewed for the identification of a specific development model, like a waterfall or agile development model, and the presence of documentation recording the development process and standard. They were also reviewed for the identification of the development environment, and the presence of release notes. The packages tended to not explicitly use well-known development models. This was also noted in the interviews with developers (Section 7). The development teams of these packages are fairly small and easily organized without the need for such processes. Seven of the software packages did have some artifacts outlining the general development process, how to contribute, and the status of the package or its components. Eight of the packages have artifacts that note the development environment. While this information could help developers, and would improve transparency, the small close-knit nature of the development teams make explicitly publicly specifying this information practically unnecessary. Version release notes were found in nine of the software packages.




Figure 11: AHP Visibility and Transparency Score

Figure 11 shows the visibility and transparency ranking of the software packages. Software packages with a high score have an explicit development model and defined development process. They also had detailed and easy to access notes accompanying software releases. Four of the top five ranked packages are noted as being alive.




Figure 12: AHP Overall Score

### 3.11. Overall Quality

Figure 12 shows the overall ranking of the software packages. In the absence of other information on priorities, the overall ranking was calculated by assuming an equal weighting between all qualities. If the qualities were weighed differently, the overall software package ranking would change. Software packages with an overall high score ranked high in at least several of the individual qualities that were quantitatively measured.

Looking at the top three ranked packages: ESPResSo achieved a relatively high score in installability, surface usability, maintainability, reusability, and visibility and transparency. Ludwig scored high in surface correctness and verifiability, surface robustness, surface usability, maintainability, and visibility and transparency. Palabos scored high in installability, surface reliability, surface robustness, maintainability, understandability, and visibility and transparency.

## 4. Comparison to Community Ranking

To address RQ3, Table 6 compares our LBM software package rankings against their popularity in the research community, as estimated by repository stars and watches. Nine packages do not use GitHub, so they do not have a measure of repository stars. Looking at the repository stars of the other 15 packages, we can observe a pattern where packages that have been highly ranked by our assessment tend to have more stars than lower ranked packages. Our best ranked package (ESPResSo) has the second most stars, while our ninth ranked package (Sailfish) has the highest number of stars. The same correlation is observed in the repository watch column, although this column contains less data, since two of the packages (Palabos, waLBerla) use GitLab, which does not track watches. Consistent with the star measure, our ninth ranked package (Sailfish) has the highest number of watches and our best ranked package (ESPResSo) has the second most watches. Packages designated as lower quality often do not use GitHub or GitLab, or have only a few stars/watches. Although the details of the rankings differ, our measures show that following best practices tends to correlate with increased popularity in the scientific community.

Notable exceptions to this trend occur for three projects that rank high by star count, but relatively low in the “follow best practices” ranking: TCLB (star rank 3, our rank 12), lettuce (star rank 4, our rank 14) and ESPResSo++ (star rank 5, our rank 15). Part of the discrepancy is because all projects are ranked by our process, but not all projects are measured by stars. Also, our process equally weights all qualities (Section 3.11), but for real users some qualities will be more important than others. Discrepancies between our measures and the star measures may also be due to inaccuracy with using stars to approximate popularity, since stars and watches tend to increase over time. Older packages (like ESPResSo++ and TCLB) have had more time to accumulate stars and watches. Young projects have less time to accumulate stars, like HemeLB, which only 12 stars (at the time of measurement) having recently moved from a different GitHub repository. Lettuce is a young project (released in 2019) with a relatively high number of stars. The discrepancy in rankings here may be due to a mismatch between the time when lettuce was manually measured by our template and when the stars were counted. The late addition of Musubi meant a large gap between when projects were manually measured and the time when our automated data (like stars) was collected.

Name	Our Ranking	Repository Stars	Repository Star Rank	Repository Watches	Repository Watch Rank
ESPresSo	1	145	2	19	2
Ludwig	2	27	8	6	7
Palabos	3	34	6	GitLab	GitLab
OpenLB	4	No Git	No Git	No Git	No Git
LUMA	5	33	7	12	4
pyLBM	6	95	3	10	5
DL_MESO (LBE)	7	No Git	No Git	No Git	No Git
Musubi	8	No Git	No Git	No Git	No Git
Sailfish	9	186	1	41	1
waLBerla	10	20	9	GitLab	GitLab
laboetie	11	4	13	5	8
TCLB	12	95	3	16	3
MechSys	13	No Git	No Git	No Git	No Git
lettuce	14	48	4	5	8
ESPresSo++	15	35	5	12	4
MP-LABS	16	12	11	2	9
SunlightLB	17	No Git	No Git	No Git	No Git
LB3D	18	No Git	No Git	No Git	No Git
LIMBES	19	No Git	No Git	No Git	No Git
LB2D-Prime	20	No Git	No Git	No Git	No Git
HemeLB	21	12	11	12	4
lbmpy	22	11	12	2	9
LB3D-Prime	23	No Git	No Git	No Git	No Git
LatBo.jl	24	17	10	8	6

Table 6: Repository Ranking Metrics

Common	Less Common	Rare
Authors / Developers List	Change Log / Release Notes	API Documentation
Issue Tracker	Design Documentation	Developer / Contributor Manual
Library Dependency List	Functional Spec. / Notes	FAQ / Forum
Installation Guide / Instructions	Performance Information	Verification and Validation Plan
Theory Notes	Test Plan / Script / Cases	Video Guide (including YouTube)
List of Related Publications	User Manual / Guide	Requirements Spec.
Makefile / Build File		
README File		
License		
Tutorial		
Version Control		

Table 7: Artifacts Present in LBM Packages, Classified by Frequency

Although our ranking and the estimate of the community’s ranking are not perfect measures, they do suggest a correlation between best practices and popularity. We do not know which comes first, the use of best practices or popularity, but we do know that the top ranked packages tend to incorporate best practices. The next sections will explore how the practices of the LBM community compare to the broader research software community. We will also investigate the practices from the top projects that others within the LBM community, and within the broader research software community, can potentially adopt.

## 5. Comparison Between LBM and Research Software for Artifacts

As part of filling in the measurement template the LBM packages were examined for the presence of artifacts, which were then categorized by frequency. We have grouped them into common, less common, and rare artifacts in Table 7. Common artifacts were found in 16 to 24 (>63%) of the software packages. Less common artifacts were found in 8 to 15 (30-63%) of the software packages. Rare artifacts were found in 1 to 7 (<30%) of the software packages. In this section we answer RQ4 by comparing the artifacts that we observed in LBM repositories to those observed and recommended for research software in general. Our comparison may point out areas where some LBM software packages fall short of current best practices. This is not intended to be a criticism of any existing packages, especially since in practice not every project needs to achieve the highest possible quality. However, rather than delve into the nuances of which software can justify compromising which practices we will write our comparison under the ideal assumption that every project has sufficient resources to match best practices.

The top four packages, ESPREsSo, Ludwig, Palabos, and OpenLB, have all of the common artifacts, except Palabos does not have theory notes and only three of them (ESPREsSo, Ludwig, Palabos) appear to use a version control system. The top four packages also have most of the less common artifacts. At the time of data collection, only one of the four packages (Palabos) did not have a user manual or guide, but there was a broken link on the package website indicating that such an artifact might exist. This broken link was later fixed, but this is not reflected in our data because it was not present at the time of data collection (mid 2020). Despite the broken link, Palabos does have a detailed and informative website. As far as we could observe, Ludwig does not appear to have publicly visible design and OpenLB does not appear to use a version control system. However, OpenLB’s use of version numbers suggests that version control may be used privately by the developers.

The top four ranked packages do not have many of the rare artifacts. None of the top four packages have any explicit API documentation. Three of these packages (ESPREsSo, Ludwig, Palabos) have information on contributing to the project. Two of them (OpenLB, Palabos) have a FAQ section or forum. One (OpenLB) has verification and validation notes, and a video guide for the software.

The majority of LBM generated artifacts correspond to general recommendations from research software developers. A union of the three columns in Table 7 mostly corresponds to recommendations made by the research software

community. Most of the items in Table 7 are included in guidelines for writing research software, such as the DLR (German Aerospace Centre) Software Engineering Guidelines (Schlauch et al., 2018), xSDK (Extreme-scale Scientific Software Development Kit) Community Package Policies (Smith et al., 2018a), the EURISE (European Research Infrastructure Software Engineers’) Network Technical Reference Thiel (2020) and CLARIAH (Common Lab Research Infrastructure for the Arts and Humanities) Guidelines for Software Quality (van Gompel et al., 2016). As an example, LBM developers list the external libraries on which the software depends as recommended by Brett et al. (2021), Smith et al. (2018a) and van Gompel et al. (2016). Although in the rare column, some LBM developers include an FAQ (Frequently Asked Questions) document as recommended by (Orviz et al., 2017), (Thiel, 2020) and (van Gompel et al., 2016). LBM developers also follow the ubiquitous recommendation to have a README file, although, as for other software, the content of README files is not standardized (Prana et al., 2018).

Three of the items that appear in Table 7 do not explicitly appear in the software development guidelines: i) list of related publications, ii) performance information and iii) video guides. The occurrence of the first two items in this list are likely more a consequence of how we collected our list of LBM artifacts, rather than being a unique practice of LBM developers. We highlighted publications and performance information because we were explicitly looking for both as part of filling in our measurement template. Related publications and performance information certainly appear in other research software projects; the practices just aren’t highlighted in guidelines because they are implicit in other documentation recommendations, such as theory documentation and user guides. The observation of a video guide artifact is more novel. Fogel (2005) recommends videos for open source projects, and other projects likely use them, but the practice has apparently not yet made it into research software community’s guidelines. Putting aside the debate of the effectiveness of learning from print versus video, video documentation is growing in popularity, with a majority of Generation Z learners preferring video to print (Genota, 2018).

Although the LBM community participates in most of the practices we found listed in the general research software guidelines, some recommended practices were not observed or rarely observed. For instance API documentation was rarely observed for LBM software, but it is a frequently recommended artifact (Smith et al., 2018a; Thiel, 2020; van Gompel et al., 2016; Orviz et al., 2017; Institute, 2022; Zadka, 2018). In addition to the items in the last column of Table 7, we can add the following community recommended items that we rarely, if ever, observed:

- A roadmap showing what is planned for the future (Yehudi, 2021; Thiel, 2020; van Gompel et al., 2016). We did see this information mentioned in some repos, but we did not observe a specific artifact devoted to this purpose.
- A code of conduct to explicitly say how developers should treat one another (Yehudi, 2021; Thiel, 2020). We did not observe a policy of this sort, possibly because the number of developers for each LBM project is small.
- Programming style guidelines so that programming labels and formatting are consistent (Schlauch et al., 2018; Thiel, 2020; Orviz et al., 2017; Zadka, 2018; van Gompel et al., 2016; Wilson et al., 2014). We saw this information as part of some developer guides, but only rarely.
- Checklists can be used in projects to ensure that best practices are followed by all developers. Some examples include checklists merging branches into master (Brown, 2015), checklists for saving and sharing changes to the project (Wilson et al., 2016), checklists for new and departing team members (Heroux and Bernholdt, 2018), checklists for processes related to commits and releases (Heroux et al., 2008) and checklists for overall software quality (Thiel, 2020; Institute, 2022). For LBM software, ESPResSo has a checklist for managing releases, but otherwise they are used only rarely for LBM.
- Uninstall instructions (van Gompel et al., 2016) were not observed for any of the LBM projects.

The above discussion shows that, taken together, LBM projects fall short of recommended best practices for research software. However, LBM software is not alone in this. Many, if not most, research projects fall short of best practices. Software requirements documentation provides a good example of the common deviation between recommendations and practice. Although requirements documentation is recommended by some (Schlauch et al., 2018; Heroux et al., 2008; Smith and Koothoor, 2016), in practice scientific software developers often do not produce a proper requirements specification (Heaton and Carver, 2015). Sanders and Kelly (2008) interviewed 16 scientists from 10 disciplines and found that none of the scientists created requirements specifications, unless regulations in their field

Development Tools	Dependencies	Project Management Tools
Continuous Integration	Build Automation Tools	Collaboration Tools
Code Editors	Technical Libraries	Email
Development Environments	Domain Specific Libraries	Change Tracking Tools
Runtime Environments		Version Control Tools
Compilers		Document Generation Tools
Unit Testing Tools		
Correctness Verification Tools		

Table 8: Observed development tools, dependencies and project management tools

mandated such a document. Nguyen-Hoan et al. (2010) showed requirements are the least commonly produced type of documentation for scientific software in general. When looking at the pain points for research software developers, Wiese et al. (2019) found that software requirements and management is the software engineering discipline that most hurts scientific developers, accounting for 23 % of the technical problems reported by study participants. The lack of support for requirements is likely due to the perception that up-front requirements are impossible for research software (Carver et al., 2007; Segal and Morris, 2008), but when the instance on “up-front” requirements is dropped, allowing the requirements to be written iteratively and incrementally, requirements are feasible (Smith, 2016).

Requirements documentation is feasible, as shown by the prevalence of theory documents in LBM software. Table 7 shows that theory documentation is common. We observed 17 of 24 packages had at least some theory documentation. Templates for scientific requirements, like Smith et al. (2007b); Smith and Lai (2005a), show theory is a significant part of the requirements documentation. With the addition of some extra information, the theory documents can be transformed into requirements specification. The key extra information includes explicitly stating user characteristics, explicitly stating how the user interacts with the software in terms of input data requirements, and listing likely and unlikely changes. Explicit statements about likely changes are invaluable in the design stage, since they provide developers guidance on how general the software needs to be. For those wishing to maximize the value of a requirement specification, information could be added like prioritizing the nonfunctional requirements (to show the relative importance between qualities like portability, reliability and performance) and traceability information (to show the consequences of any changes to the assumptions).

## 6. Comparison of Tool Usage Between LBM and Other Research Software

Software tools are used to support the development, verification, maintenance, and evolution of software, software processes, and artifacts (Ghezzi et al., 2003, p. 501). Many tools are used by LBM software packages, as summarized in Table 8. The tools are subdivided into development tools, dependencies, and project management tools. In this section we answer RQ5 by comparing aspects of the tool usage in LBM to their utilization in the research software community in general.

Development tools support the development of end products, but do not become part of them, unlike dependencies that remain in the application once it is released (Ghezzi et al., 2003, p. 506). Although not shown in Table 8, debuggers were also likely used. Only three (ESPreSo, Ludwig and Musubi) packages mentioned continuous integration tools, like Travis CI. Code editors and compilers were explicitly noted to have been used by several packages, and were likely used by all of them. One of the packages (Ludwig) explicitly noted the use of proprietary unit testing code written in C. Likewise, the use of proprietary code for verifying the correctness of output was noted by one of the developers (pyLBM). Similar tools were likely used when developing the other software packages.

For the dependency tools (Table 8), we observed that most of the software packages use some sort of build automation tools, most commonly Make. They all use various technical and domain specific libraries. Technical libraries include visualization (e.g. Matplotlib, ParaView, Pygame, VTK), data analysis (e.g. Anaconda, Torch), and message passing libraries (e.g. MPICH, Open MPI, PyZMQ). Domain specific libraries include scientific computing libraries (e.g. SciPy).



Many of the software packages that were assessed were developed by teams of two or more people. Their work needed to be coordinated and managed. Table 8 shows the types of project management tools that were explicitly noted in the artifacts, web-pages, or interviews with the developers. As with development tools and dependencies, it is possible that other types of project management tools are used, but they were not visible in the artifacts to which we had access. Collaboration tools, most often email and video, are noted as being used when developing the software projects. Project management software was not explicitly mentioned, but it is possible that some of the projects use such software. Many of the projects are located on GitHub, where the developers use the platform to help manage their projects, especially bug related issues. Most of the projects appear to use change tracking and version control tools. Document generation tools are mentioned in 12 of the 24 projects. The tools Sphinx and Doxygen are explicitly used in this capacity.

The poor adoption of version control tools that Wilson lamented in 2006 (Wilson, 2006) has greatly improved in the intervening years. From Section 3.7, 67% of LBM packages use version control (GitHub, GitLab or CVS). (From Table 4, 11/15 or 73% of alive packages use version control.) The proliferation of version control tools for LBM matches the increase in the broader research software community. A little over 10 years ago version control was estimated to be used in only 50% of research software projects (Nguyen-Hoan et al., 2010), but even at that time Nguyen-Hoan et al. (2010) noted an increase from previous usage levels. A survey in 2018 shows 81% of developers use a version control system (AlNoamany and Borghi, 2018). Smith (2018) has similar results, showing version control usage for alive projects in mesh generation, geographic information systems and statistical software for psychiatry increasing from 75%, 89% and 17% (respectively) to 100%, 95% and 100% (respectively) over a four year period ending in 2018. (For completeness the same study showed a decrease in version control usage for seismology software over the same time period, from 41% down to 36%). Almost every software guide cited in Section 5 includes the advice to use version control. The high usage of version control tools in LBM software matches the trend in research software in general.

As mentioned in Section 3.2, continuous integration is rarely used in LBM (3 of 24 packages or 12.5%). This contrasts with the frequency with which continuous integration is recommended in research software development guidelines (Brett et al., 2021; Brown, 2015; Thiel, 2020; Zadka, 2018; van Gompel et al., 2016). We could not find published data on the frequency with which continuous integration is used in general research software. Our impression is that like LBM software, other research software packages lag behind the recommended best practice of employing continuous integration tools.

Interviews with the developers revealed a potentially more frequent use of both unit testing and continuous integration, compared to what was observed from studying the repository artifacts.

## **7. Comparison of Principles, Process and Methodologies to Research Software in General**

This section answers research question RQ6 by comparing the principles, processes and methodologies used for LBM software to what can be gleaned from the literature on research software in general. In our data collection for LBM software, the software development process is not explicitly indicated in the artifacts for most of the packages. However, during our interviews one developer (ESPResSo) told us their non-rigorous development model is like a combination of agile and waterfall. Employing a loosely defined process makes sense for LBM software, given that the teams are generally small and self-contained. Although eleven of the packages explicitly convey that they would accept outside contributors, generally the teams are centralized, often working at the same institution. Working at the same institution means that an informal process can show success, since informal conversations are relatively easy to have.

Interviews with developers confirmed a similar project management processes. In teams of only a couple of developers, additions of new features or major changes are discussed with the entire team. Projects with more than a couple developers have lead developer roles. These lead developers review potential additions to the software. One of the developers (ESPResSo) that was interviewed noted that an ad hoc peer review process is used to assess major changes and additions. Using peer review (also called technical review) matches with recommended practice for research software (Heroux et al., 2008; Givler, 2020; Orviz et al., 2017; USGS, 2019).

Two types of software changes were discussed during interviews with developers. One is feature additions, which arise from a scientific or functional need. These changes involve formal discussions within the development team, and

lead developer participation is mandatory. The other change type is code refactoring, which only sometimes involves formal discussions with the development team. New developers were noted to play an increased role in these changes compared to the former changes. Software bugs are typically addressed in a similar fashion as code refactoring. Issue tracking is commonly used to manage these changes.

Our observations of an informally defined process, with elements of agile methods, matches what has been observed for research software in general. Scientific developers naturally use an agile philosophy (Ackroyd et al., 2008; Carver et al., 2007; Easterbrook and Johns, 2009; Segal, 2005; Heaton and Carver, 2015), or an amethodical process (Kelly, 2013), or a knowledge acquisition driven process (Kelly, 2015).

Most of the software packages do not explicitly state the motivations or design principles that were considered when developing the software. One package, Sailfish, indicates in its artifacts that shortening the development time was considered in early stages of design, with the developers using Python and CUDA/OpenCL to achieve this without sacrificing performance. The Sailfish goals are explicitly listed as performance, scalability, agility and extendability, maintenance, and ease of use. The project scored well in these categories during our assessment. The quality priorities for Sailfish roughly match the priorities observed for research software in general. Nguyen-Hoan et al. (2010) surveyed developers to find the following list of qualities, in decreasing order of importance: reliability, functionality, maintainability, availability, performance, flexibility, testability, usability, reusability, traceability, and portability. The Sailfish list does not list reliability or functionality, but we can safely assume those are implicitly high priorities for any scientific project. In earlier studies Kelly and Sanders (2008) and Carver et al. (2007) both highlight how important correctness is for research software.

During our interviews, documentation was noted as playing a significant role in the development process, specifically with on-boarding new developers. A goal of documentation is to lower the entry barrier for these new contributors. The documentation provides information on how to get started, orients the user to artifacts and the source code, and explains how the system works, including the so-called simulation engine and interface. This emphasis on documentation, especially for new developers, is echoed in research software guidelines. Multiple guidelines recommend a document explaining how to contribute to a project, often named CONTRIBUTING (Yehudi, 2021; Brett et al., 2021; Wilson et al., 2016; Thiel, 2020; van Gompel et al., 2016; Orviz et al., 2017; Free/Libre and Software, 2022; Jiménez RC et al., 2017). Tutorials (Thiel, 2020), trouble shooting guides (Orviz et al., 2017; Institute, 2022) and quick start examples (Thiel, 2020; van Gompel et al., 2016) are also recommended. (Smith et al., 2018a) suggests including instructions specifically for on-boarding new developers. For open source software in general (not just research software), (Fogel, 2005) recommends providing tutorial style examples, developer guidelines, demos and screenshots.

## 8. Developer Pain Points

Based on interviews with 4 developers, this section aims to answer the research questions: i) What are the pain points for developers working on research software projects (RQ7)?; and, ii) How do the pain points of developers from LBM compare to the pain points for research software in general (RQ8)? Below we go through each of the identified pain points and include citations that contrast the LBM experience with observations from researchers in other domains. Potential ways to address the pain points are covered in Section 9. The full interview questions are found in Smith et al. (2021).

(Pinto et al., 2018) lists some pain points that did not come up in our conversations with LBM developers: Cross-platform compatibility, interruptions while coding, scope bloat, lack of user feedback, hard to collaborate on software projects, and aloneness. (Wiese et al., 2019) repeat some of the previous pain points and add the following: dependency management, data handling concerns (like data quality, data management and data privacy), reproducibility, and software scope determination. Although LBM developers did not mention these pain points, we cannot conclude that they are not relevant for LBM software development, since we only interviewed 4 LBM developers for about an hour each.

**P1: Lack of Development Time** A developer of pyLBM noted that their small development team has a lack of time to implement new features. Small development teams are common for LBM software packages (as shown in the measurement table excerpt in Figure 2). Lack of time is also highlighted as a pain point by other research software developers Pinto et al. (2018, 2016); Wiese et al. (2019).

- P2: **Lack of Software Development Experience** A lack of software development experience was noted by the developer of TCLB, and others noted a need for improving software engineering education. Many of the team members on their project are domain experts, not computer scientists or software engineers. This same trend is noted by Nguyen-Hoan et al. (2010), which showed only 23% of research software survey respondents having a computing-related background. Similarly, (Nangia and Katz, 2017) show that the majority (54%) of postdocs have not received training in software development. The LBM developer suggesting an increasing role for formal software education matches the trend observed by Pinto et al. (2018), where their replication of a previous study (Hannay et al., 2009), shows a growing interest in formal training (From 13% of respondents in 2009 to 22% in 2018). (Pinto et al., 2018) found that some developers feel there is a mismatch between coding skills and subject-matter skills.
- P3: **Lack of Incentive and Funding** The TCLB developer noted a lack of incentives and funding in academia for developing widely used scientific software. This problem has also been noted others (Gewaltig and Cannon, 2012; Goble, 2014; Katerbow and Feulner, 2018). Wiese et al. (2019) reported developer pains related to publicity, since historically publishing norms make it difficult to get credit for creating software. As studied by Howison and Bullard (2016), research software (specifically biology software, but the trend likely applies to other research software domains) is infrequently cited. (Pinto et al., 2018) also mentions the lack of formal reward system for research software.
- P4: **Lack of External Support** A concern was raised that there are no organizations helping with the development of good quality software. This concern is not echoed in the literature because there are such organizations, including Better Scientific Software (BSSw), Software Sustainability Institute (Crouch et al., 2013), and Software Carpentry [WilsonAndLumsdaine2006, Wilson2016 —SS]. Over time awareness of these groups will grow, so this pain point is likely to disappear in the future for LBM and other research software developers.
- P5: **Technology Hurdles** Technology pain points include setting up parallelization and continuous integration.
- P6: **Ensuring Correctness** Difficulties with ensuring correctness were noted by several developers. Several developers alluded to difficulty with testing the correctness of large numbers of features, and some manually tested program output, as opposed to using automated testing. The TCLB developer commented that the amount of testing data needed was sometimes problematic, since free testing services do not offer adequate facilities for large amounts of data, which means in-house testing solutions are needed. Other research software domains point to the following problems with testing: i) (Pinto et al., 2018) mention the problem of insufficient testing; ii) the survey of (Hannay et al., 2009) shows that more developers think testing is important than the number that believe they have a sufficient understanding of testing concepts; and, iii) (Hannay et al., 2009; Kanewala and Bieman, 2013; Kelly et al., 2011; Wiese et al., 2019) point to the oracle problem, which occurs in research software when we do not have a means to judge the correctness of the calculated solutions. The LBM experience seems to overlap with i and ii, but the LBM developers did not allude to problem iii (the oracle problem) in our conversation; we believe that they have developed techniques to work around the oracle problem.
- P7: **Usability** Several developers noted that users sometimes try to use incorrect LBM method combinations to solve their problems. Furthermore, some users think that the packages will work out of the box to solve their cases, while in reality CFD knowledge needs to be applied to correctly modify the packages for the new endeavour. (Wiese et al., 2019) also interacted with developers that mentioned that users do not always have the expertise required to install or use the software.
- P8: **Technical Debt** The developer of ESPResSo said that their source code was written with a specific application in mind, which later caused too much coupling between components in the source code. This results in technical debt Kruchten et al. (2012), which has an impact on future modifiability and reusability. Concern with technical debt is likely why researchers in the survey of (Nguyen-Hoan et al., 2010) rated maintainability as the third most important software quality. More recently the push for sustainable software de Souza et al. (2019) is motivated by the pain that past developers have had with accumulating too much technical debt.
- P9: **Quality of Documentation** The importance of documentation for both users and developers was stressed throughout the interviews. However, it was noted several times that a lack of time and funding (P1) has a

negative affect on the documentation. Most of the developers are scientific researchers evaluated on the scientific papers that they produce. Writing and updating documentation is something that is done in their free time, if that time arises. Inadequate research software documentation is also mentioned by others (Pinto et al., 2018; Wiese et al., 2019) and the problem also arises with non-research software (Lethbridge et al., 2003). Recommendations on the development of research software state that developers should critically evaluate their own development processes in terms of quality assurance and comply with international standards for software documentation (Katerbow and Feulner, 2018).

## 9. Lessons from LBM Developers

This section summarizes the best practices from LBM developers that are taken to address the pain points mentioned in Section 8. The main source of information is the qualitative data from developer interviews (Section 2.7). The practices summarized in this section can potentially be emulated by the LBM software packages that do not currently follow them. Moreover, these practices may also provide examples that can be followed by other research software domains.

### 9.1. Design For Change

Increasing source code modularity, reducing duplicate information, and improving abstraction by developing well defined interfaces. This was noted by the developers of ESPResSo and pyLBM. A developer of pyLBM mentioned that the geometries and models of their system had been “decoupled”, using abstraction and modularization of the source code, to make it “very easy to add [new] features”. [\[Highlights the advantage of design. Other projects can look to these examples. Maybe cite the Anshu paper about Flash? Dune? and point to the advantages of design. —SS\]](#) Addresses maintainability. The developer of TCLB mentioned that their package had two sets of code, for executing the models on the CPU and GPU, and that maintenance was decreased by introducing macros, a practice which became a common part of the development process.

A high degree of code modularity and abstraction was noted by developers as a measure to ensure the ease of future changes. This can be ensured by separating components and hiding information behind well defined interfaces. The developer of ESPResSo also noted that some of the code base was transitioned from C to C++, which could ease modifiability of that software package. The developer of TCLB noted that their software package was designed to allow for the addition of some LBM features, but changes to major aspects of the system would be difficult. For example, “implementing a new model will be an easy contribution”, but changes to the “Cartesian mesh...will be a nightmare”. [\[example suggests identifying likely changes. —SS\]](#)

Modularize the source code, separate components, hide information behind well defined interfaces. This is suggested in SCS literature, and in developer comments. [\[one of Wilson’s best practices. —SS\]](#)

- Modifiability. Consider flexibility of data structures and data storage in the design stage. The package pyLBM redeveloped data structures to ease future changes.
- Reusability. Provide API documentation, if applicable. Only one (ESPResSo) of the top five ranked packages provided API documentation.

### 9.2. Verification and Validation

[\[Address Correctness \(P6\): Testing is not the only way to build confidence in correctness. Peer review. —SS\]](#)

Surface Correctness and Verifiability. Development teams should include both domain experts and experienced software developers. This suggestion is based on developer comments.

Visibility and Transparency. Consider peer review processes to assess contributions and ensure the tracking of information. High ranked package ESPResSo uses a peer review process for contributions.

### 9.3. Reproducibility

Software packages were not quantitatively measured for reproducibility. Instead, developers were asked if they had concerns that their computational results would not be reproducible in the future, and if they had taken any steps to ensure reproducibility. The developers all agreed that reproducibility is important, but they differ in how far they go to support reproducibility. ESPResSo does the most to support reproducibility. For instance, they compare the results of their methods against manually calculated results. These comparison tests are automatically run for all source code changes. The tests are run when a pull request is opened on GitHub. Even once these tests are complete, a peer review process is undertaken before changes are fully committed to the appropriate branch. The results for all of the LBM schemes on the software package development branch are also frequently compared for correctness, ensuring that the system output reflects the expected output.

For other teams, the priority is verifying the mathematical foundations of the models, but the output of the software package is not compared to other output. Depending on the package and how it outputs solutions, this may not be practical or feasible. A correct output may not be exactly reproducible, as it may be dependent on a probability distribution, so strictly comparing results may not be appropriate. [\[Ideas for dealing with reproducibility in these situations will be explored in the recommendations section \(like properties of the solution, such as conservation of mass\). —SS\]](#)

Some software packages, like Palabos, provide validation benchmarks for their core fundamental algorithmic ingredients (Latt et al., 2021). The stated intent of these benchmarks is to showcase the validity and usefulness of the package to stimulate the development of third-user extensions. The Palabos package identifies as a development framework for modelling problems in various CFD areas. [\[Add validation benchmarks as a “best practice” used by Palabos - others could emulate. Goal of this exercise is for people in the community to learn from each other, and potentially from our advice too. —SS\]](#)

- Reproducibility. Test output against automatically calculated or known correct results. High ranked package ESPResSo does this.
- Reproducibility. Automate the testing of output. Run tests after all code changes. High ranked package ESPResSo does this.
- Reproducibility. Consider peer review processes and task based inspection to assess contributions. High ranked package ESPResSo does this.

### 9.4. Documentation

Software packages were not quantitatively measured for traceability. In this project we asked developers to comment on traceability, specifically on their software package’s documentation and how it fit into their development process.

The interviewed developer of ESPResSo noted that all major additions to their package had accompanying changes to artifacts and documentation. They noted that considerable effort had been put into the documentation. They further commented that they want to lower the entry barrier for new developers, and because of that their package has a considerable amount of developer documentation. This documentation informs developers on how to get started, and orients them to the artifacts, source code, and system architecture, as well as how the software package build system works, and how the coupling between the simulation engine and the interface works. [\[Peter - these points about developer documentation seem like they would fit better under understandability, don’t you think? —SS\]](#) [\[After reviewing the definitions of the two qualities, I think you are right. I think that the point presented in the first sentence of this paragraph belongs here in traceability \(but could be reworded to note that ESPResSo also has detailed change logs in their docs - change logs are also available for Palabos and waLBerla\), but the rest of the paragraph can be moved to understandability. —PM\]](#) [\[If ESPResSo scored high \(I think it did\), we can use that to further promote the value of documentation. Also a threat to validity is that we have implicitly assumed documentation is valuable when measuring quality. —SS\]](#)

Finding ways to hasten updating documentation would increase the frequency of such updates and benefit both users and developers. [\[Same thing has come up in papers. I’ll try to find a reference for this. This is also something we can point to for recommendations related to code generation. —SS\]](#) [\[Peter - this also sounds like understandability](#)

related discussion? I wonder if we should drop Traceability as a quality that we assessed? There doesn't seem to be much content specific to traceability. —SS] [Based on the comments I just added above, I think we can keep at least a small part of what is here in traceability, rewording parts to highlight the importance of change logs. Some of the content in this section should indeed be moved to understandability. —PM] The developer of OpenLB noted the use of documentation generators like Doxygen. It would be advisable for more projects to use such automatic document generation tools, since some projects do not do this. [We can refer back to this for the recommendations. —SS]

[Address Usability (P7): Better documentation, with attention on traceability, and automatic code generation are suggested when designing software for change, and would help with these modifications. So far this problem of onboarding new users has been addressed by updating the documentation to better inform users of the underlying LBM theory and package requirements. Similar issues with LBM parameters were noted by another developer. Updating the user interface to better explain theoretical principles, as well as test user input for compatibility, was the implemented solution. As noted above, sometimes frequently asked questions on the underlying theory and on how to use the software are answered in the documentation. The interviewed developer of ESPResSo commented that parts of their package's source code had been refactored to Python to help address usability issues. Python was perceived as a much more usable language, and it would be easy for future users and developers to learn and understand the source code. —SS]

One software package (ESPResSo) changed some of its scripting language to Python to make it more usable. The developer commented that this was “the biggest step in terms of usability over the years”, further commenting that “most people in the field know [Python]” and that “it's easy to learn”. [A generative approach facilitates switching to whatever language is currently popular. —SS]

- Usability. Understandability. Unambiguity. State appropriate fluid dynamics problems that the software is designed to model in the documentation, and explicitly state the limits of the software. This is done in the ESPResSo user guide.
- Usability. Provide documentation that details the background theory information, or provide a reference to such information. This was done by several top ranked packages, including ESPResSo, Ludwig, LUMA, and OpenLB.
- Usability. Identify expected user characteristics. LIMBES, Ludwig, laboetie, and Palabos did this. The importance of specifying user characteristics is discussed in (Smith et al., 2007a).
- Usability. Keep all documentation in one location. This was done by top ranked packages.
- Usability. Do not duplicate artifact information. This is suggested as good software development practice. Duplicate information is difficult to maintain.

### 9.5. *Visibility and Transparency*

[Will likely remove this section, but should find a way to say the good things that ESPResSo does. —SS] Although visibility is not a priority, positive steps are being undertaken. For instance, all interviewed teams used GitHub, with its visibility enhancing features of branching, issue tracking, insights on contributors, the blame feature, wikis, pull requests, etc. Continuous integration, as used by ESPResSo, makes projects even more visible, since contributors can explicitly see the bar that must be crossed for code to be incorporated into the master branch. ESPResSo also uses peer review, which improves visibility by explicitly asking for feedback from other developers.

[in recommendations could point out what teams could do to get more external contributors, and potentially a longer life for their project. —SS]

## 10. Recommendations for Future Practices

Answers RQ10. practices for the future. Probably the easiest approach is to list the practice and then the PPs that it helps. Our recommendations are not lists of what should have been done in the past, or what should be done now; they are just suggestions for consideration in the future.

“unique challenges of scientific research (e.g., the frequent and unforeseen changes in requirements ...)” (Pinto et al., 2018). We can point out that in the future this viewpoint could change and why. Not really a unique challenge. Cite Smith 2016?

linters (Zadka, 2018) were rarely observed in LBM projects. Do not see much evidence of their presence in best practice guides.

[Address lack of development time (P1): Aside from on-boarding new developers, time constraints could be mitigated by increasing developer efficiency, which could be addressed in several ways, including by improving the quality of documentation, or incorporating automatic code generation. —SS]

[Address lack of funding (P3): The developer further commented that there are no journals that publish such scientific software source code. However, there are ways to get such source code cited. Work has been done to address this in (Smith et al., 2016a), which presents a set of software citation principles and discusses “how they could be used to implement software citation in the scholarly community” (Katz et al., 2019). other papers also mention this pain point. Solutions proposed by Katz, journal of open source etc. Journal of Open Source Software Smith et al. (2018c). Calling for direct software citations (Smith et al., 2016a). Guidance on software citation from Katz et al. (2021). Discussed in CarverEtAl2021 paper. —SS]

[Address quality of documentation (P9): Make required background of users explicit, possibly in a requirements document. —SS]

Surface Correctness and Verifiability. Use a requirements specification document. This is suggested in SCS literature, and several of the top ranked packages had such a document or reference to theory manuals. A potential template is presented in (Smith and Lai, 2005b).

### *10.1. Grow the Number of Contributors*

Maintainability. Have a defined process for accepting contributions, and make public documentation for making contributions to the project. The top five ranked software packages include information on how to contribute.

Papers that talk about how to do open source.

## **11. Threats To Validity**

This section examines potential threats to the validity of this state of the practice assessment. These can be categorized into methodology and data collection issues. The goal of this assessment isn’t to rank the software, but to use the ranking exercise as a means to understand the state of the practice of LBM software development.

The measures listed in our measurement template may not be broad enough to accurately capture some qualities. For example, there are only two measures of surface robustness. The measurement of robustness could be expanded, as it currently only measures unexpected input. Other faults could be introduced, but could require a large investment of time to develop, and might not be a fair measure for all packages. Similarly, reusability is assessed along the number of code files and LOC per file. While this measure is indicative of modularity, it is possible that some packages have many files, with few LOC, but the files do not contain source code that is easily reusable. The files may be poorly formatted, or the source code may be vague and have ambiguous identifiers. Furthermore, the measurement of understandability relies on 10 random source code files. It is possible that the 10 files that were chosen to represent a software package may not be a good representation of the understandability of that package.

Regarding data collection, a risk to the validity of this assessment is missing or incorrect data. Some software package data may not have been measured due to technology issues like broken links. This issue arose with the measurement of Palabos, which had a broken link to its user manual, as noted in Section 5.

Some pertinent data may not have been specified in public artifacts, or may be obscure within an artifact or webpage. The use of unit testing and continuous integration was mentioned in the artifacts of only three (ESPREsSo, Ludwig, Musubi) packages. However, interviews suggested a more frequent use of both unit testing and continuous integration in the development processes than what was observed from the initial survey of the artifacts. For example, OpenLB, pyLBM, and TCLB use such methods during development despite this not being explicitly clear from an analysis of the material available online.

Furthermore, design documentation was measured to be a “less common” artifact in this assessment, but it is probable that such documentation is part of all LBM packages. After all, developing SCS is not a trivial endeavour. It



is likely that many packages have such documentation but did not make it public, and due to this the measured data is not a true reflection of software package quality.

[\[There are more threats to validity. Brainstorm. Watch for them while editing. Look at Ao paper. —SS\]](#)

Problems with the measurement of qualities:

- The assumption that more code files is an indicator of reusability (Section 3.8) may not be a valid assumption.
- Understandability was measured using only 10 random files (Section 3.9). This could be improved.

Overall ranking with equally weighted qualities isn't realistic (Section 3.11).

Threat to validity - the gap between measures of everything else and Musubi (Section 2.3), and then the gap between the manual measures and the automated measures (Section 4).

From Section 6: "Interviews with the developers revealed a potentially more frequent use of both unit testing and continuous integration, compared to what was observed from studying the repository artifacts."

Interviews suggested a more frequent use of both unit testing and continuous integration in the development processes than what was observed from the initial survey. For example, OpenLB, pyLBM, and TCLB use such methods during development, despite this not being explicitly clear from an analysis of the material available online. The correctness and verifiability of such packages is not measured well using surface analysis.

## 12. Conclusion

We analyzed the state of the practice of software development in the Lattice Boltzmann Methods software domain by quantitatively and qualitatively measuring, and comparing, 24 software packages along quality attributes. The software qualities that were assessed in this report are listed in Section 2.1. A methodology for assessing the state of the practice of software development in SCS domains was presented. Domain packages were assessed to answer the software development related research questions listed in Section 1 to understand how software quality is impacted by software development choices, including principles, processes, and tools. Software developers were interviewed to identify development pain points, and to identify how software quality is ensured. Quantitative data was used to rank the software packages using the AHP. The ranking designations were compared with rankings from the software development community, and we found that many of our top 10 ranked packages are ranked highly by a domain expert. Recommendations for improving software along quality metrics were made, and highlights are presented in Section 12.1 of this conclusion. The findings of this report can be used to guide future development of SCS, specifically along quality attributes, and to reduce software quality failures.

[\[More on the lessons to learn from the top packages. The comparison to common practice - is LBM ahead or behind? More on best practices comparison. Future practices. —SS\]](#)

We understand that software packages vary in goals, developers, funding, and other aspects. Our goal was to highlight software quality successes through an evaluation of the entire domain software family. Furthermore, threats to the validity of the findings are highlighted in Section 11.

Recommendations for future state of the practice assessments are made in Section 12.2.

Our comparison may point out areas where some LBM software packages fall short of current best practices. This is not intended to be a criticism of any existing packages, especially since in practice not every project needs to achieve the highest possible quality. However, rather than delve into the nuances of which software can justify compromising which practice we will write our comparison under the ideal assumption that every project can have sufficient resources to match best practices.

### 12.1. Highlighted Recommendations

Many software packages would benefit from a rewrite or reorganization of installation instructions. A single location for installation instructions would improve their maintainability and correctness. Listing compatible operating system and dependency versions would decrease installation time and errors, as would adding instructions on installing dependencies. Installation process errors should prompt the system to display detailed messages. Once a software package is installed, either an automatic validation needs to be performed or the user needs to be able to perform a manual validation using test examples that include expected output. Finally, uninstallation instructions



should be included in the documentation. [Have to decide how much to emphasize installability. —SS] [Maybe at some point should mention more modern installation support, since most of the projects use make, and there are other options. —SS]

The following recommendations improve software quality along multiple attributes, and provide the greatest return on investment:

- Provide a detailed user manual. It should identify elements of user interfaces, and identify all requirements to model a system. Thirteen packages have a user manual. ESPResSo has a well detailed manual.
- State appropriate fluid dynamics problems that the software is designed to model in the documentation, and explicitly state the limits of the software. This is done in the ESPResSo user guide.
- Include detailed tutorials, including dependencies, expected output, and any additional supplementary documentation that may be required. This was done by many packages, including waLBerla, Palabos, MechSys, LUMA, and pyLBM.
- Keep all documentation in one location. This was done by top ranked packages.
- If possible, consider using popular user-friendly software languages like Python. Especially consider this for parts of the source code that is likely to be modified or reviewed by users. ESPResSo and Sailfish use Python to address several software qualities, including maintainability, modifiability and usability.
- Modularize the source code, separate components, hide information behind well defined interfaces. This is suggested in SCS literature, and in developer comments.
- Include descriptive error messages where appropriate. This was done by most packages that encountered a fault.
- Summarize the development process that is used. Provide information on how new users can contribute. Seven of the software packages have some artifacts outlining the general development process. Eleven packages have information on how to contribute.
- Consider peer review processes and task based inspection to assess contributions. High ranked package ESPResSo does this.
- Use continuous integration tools (Bamboo, Jenkins, and Travis CI) and processes during development. This was done by top ranked packages ESPResSo and Ludwig.
- Use project management tools, including change and version control tools (GitHub, GitLab, CVS), collaboration tools (GitHub, GitLab), and document generation tools (Doxygen, Drasil, Sphinx). This was done by all of the top five ranked packages.

Ensuring software quality can take significant time. An inability to develop high quality documentation due to time constraints could be mitigated in the future by the use of automatic document generation tools like Drasil. The Drasil Framework consists of a collection of Domain Specific Languages (DSL) for capturing scientific documents, structures, and computing knowledge, and then transforming this knowledge into relevant software artifacts without having to manually duplicate knowledge into multiple artifacts (Zhao, 2018). [Yuzhi is not the best reference to use for the Drasil work. —SS]

## 12.2. Future State Of The Practice Assessments

As mentioned in Section 11, the measures listed in our measurement template may not be broad enough to accurately capture some qualities. Adding or extending measures is worth considering. For example, usability experiments and performance benchmarks could be incorporated into the assessment.

Section 9.3 noted that developers were not asked to comment on the reproducibility of their source code from their requirements specifications and design documentation. Adding this question to the interview guide should be considered in the next iteration of state of the practice assessments. Furthermore, as mentioned in Section 11, it was

found that some pertinent information was not specified in public artifacts. The use of unit testing and continuous integration by several packages (OpenLB, pyLBM, TCLB) was only discovered during interviews with developers. Adding further questions to the interview guide regarding the measures that are on the measurement template could reduce instances of incorrect data being collected. This additional interview data could be analyzed and incorporated into the AHP ranking, ensuring quality designations more accurately represent the true quality of the software packages. [\[clarify the distinction between usability and understandability. —SS\]](#)

For the current project, we did not assess the stronger form of “reproducibility” known as replicability. A software project is considered replicable if the documentation alone (without the code) is sufficiently precise and complete to allow a third-part to re-obtain the results of the original code (Benureau and Rougier, 2017). Replicability is difficult to achieve with current documentation practices. This question should be considered in the next iteration of state of the practice assessments.

## References

2017. ISO/IEC/IEEE International Standard - Systems and software engineering—Vocabulary. *ISO/IEC/IEEE 24765:2017(E)* (2017), 1–541. <https://doi.org/10.1109/IEEESTD.2017.8016712>
- Karen S. Ackroyd, Steve H. Kinder, Geoff R. Mant, Mike C. Miller, Christine A. Ramsdale, and Paul C. Stephenson. 2008. Scientific Software Development at a Research Facility. *IEEE Software* 25, 4 (July/August 2008), 44–51.
- Yasmin AlNoamany and John A. Borghi. 2018. Towards computational reproducibility: researcher perspectives on the use and sharing of software. *PeerJ Computer Science* 4, e163 (September 2018), 1–25.
- Shadab Anwar and Michael C. Sukop. 2009. Regional scale transient groundwater flow modeling using Lattice Boltzmann methods. *Computers & Mathematics with Applications* 58, 5 (2009), 1015–1023. <https://doi.org/10.1016/j.camwa.2009.02.025>
- Yuanxun Bill Bao and Justin Meskas. 2011. Lattice Boltzmann method for fluid simulations. *Department of Mathematics, Courant Institute of Mathematical Sciences, New York University* (2011), 44.
- Martin Bauer, Sebastian Eibl, Christian Godenschwager, Nils Kohl, Michael Kuron, Christoph Rettinger, Florian Schornbaum, Christoph Schwarzmeier, Dominik Thönnies, Harald Köstler, et al. 2021a. waLBerla: A block-structured high-performance framework for multiphysics simulations. *Computers & Mathematics with Applications* 81 (2021), 478–501.
- Martin Bauer, Harald Köstler, and Ulrich Rüde. 2021b. lbmpy: Automatic code generation for efficient parallel lattice Boltzmann methods. *Journal of Computational Science* 49 (2021), 101269.
- Mario Christopher Bedrunka, Dominik Wilde, Martin Kliemank, Dirk Reith, Holger Foyss, and Andreas Krämer. 2021. Lettuce: PyTorch-based Lattice Boltzmann Framework. In *International Conference on High Performance Computing*. Springer, 40–55.
- F. Benureau and N. Rougier. 2017. Re-run, Repeat, Reproduce, Reuse, Replicate: Transforming Code into Scientific Contributions. *ArXiv e-prints* (Aug. 2017). arXiv:1708.08205 [cs.GL]
- Barry W Boehm. 2007. *Software engineering: Barry W. Boehm's lifetime contributions to software development, management, and research*. Vol. 69. John Wiley & Sons.
- Alys Brett, James Cook, Peter Fox, Ian Hinder, John Nonweiler, Richard Reeve, and Robert Turner. 2021. Scottish Covid-19 Response Consortium. <https://github.com/ScottishCovidResponse/modelling-software-checklist/blob/main/software-checklist.md>.
- Titus Brown. 2015. Notes from “How to grow a sustainable software development process (for scientific software)”. <http://ivory.idyll.org/blog/2015-growing-sustainable-software-development-process.html>.
- Jeffrey C. Carver, Richard P. Kendall, Susan E. Squires, and Douglass E. Post. 2007. Software Development Environments for Scientific and Engineering Software: A Series of Case Studies. In *ICSE '07: Proceedings of the 29th International Conference on Software Engineering*. IEEE Computer Society, Washington, DC, USA, 550–559. <https://doi.org/10.1109/ICSE.2007.77>
- Shiyi Chen and Gary D Doolen. 1998. Lattice Boltzmann method for fluid flows. *Annual review of fluid mechanics* 30, 1 (1998), 329–364.
- Z Chen, C Shu, LM Yang, X Zhao, and NY Liu. 2021. Phase-field-simplified lattice Boltzmann method for modeling solid-liquid phase change. *Physical Review E* 103, 2 (2021), 023308.
- S. Crouch, N. C. Hong, S. Hettrick, M. Jackson, A. Pawlik, S. Sufi, L. Carr, D. De Roure, C. Goble, and M. Parsons. 2013. The Software Sustainability Institute: Changing Research Software Attitudes and Practices. *Computing in Science Engineering* 15, 6 (Nov 2013), 74–80. <https://doi.org/10.1109/MCSE.2013.133>
- Mario Rosado de Souza, Robert Haines, Markel Vigo, and Caroline Jay. 2019. What Makes Research Software Sustainable? An Interview Study With Research Software Engineers. *CoRR* abs/1903.06039 (2019). arXiv:1903.06039 <http://arxiv.org/abs/1903.06039>
- Jean-Christophe Desplat, Ignacio Pagonabarraga, and Peter Bladon. 2001. LUDWIG: A parallel Lattice-Boltzmann code for complex fluids. *Computer Physics Communications* 134, 3 (2001), 273–290.
- Ao Dong. 2021. *Assessing the State of the Practice for Medical Imaging Software*. Master’s thesis. McMaster University, Hamilton, ON, Canada.
- Steve M. Easterbrook and Timothy C. Johns. 2009. Engineering the Software for Understanding Climate Change. *Computing in Science & Engineering* 11, 6 (November/December 2009), 65–74. <https://doi.org/10.1109/MCSE.2009.193>
- ESA. February 1991. *ESA Software Engineering Standards, PSS-05-0 Issue 2*. Technical Report. European Space Agency.
- Karl Fogel. 2005. *Producing Open Source Software: How to Run a Successful Free Software Project*. O’Reilly Media, Inc.
- Free/Libre and Open Source Software. 2022. FLOSS Best Practices Criteria (Passing Badge). <https://bestpractices.coreinfrastructure.org/en/criteria/0>.
- SA Galindo-Torres. 2013. A coupled Discrete Element Lattice Boltzmann Method for the simulation of fluid–solid interaction with particles of general shapes. *Computer Methods in Applied Mechanics and Engineering* 265 (2013), 107–119.

- Davood Domairry Ganji and Sayyid Habibollah Hashemi Kachapi. 2015. *Application of nonlinear systems in nanomechanics and nanofluids: analytical methods and applications*. William Andrew.
- Lauraine Genota. 2018. Why Generation Z Learners Prefer YouTube Lessons Over Printed Books. Education Week, <https://www.edweek.org/teaching-learning/why-generation-z-learners-prefer-youtube-lessons-over-printed-books/2018/09>.
- Marc-Oliver Gewaltig and Robert Cannon. 2012. Quality and sustainability of software tools in neuroscience. *Cornell University Library* (2012), 1–20.
- Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. 1991. *Fundamentals of software engineering*. Prentice Hall PTR.
- Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. 2003. *Fundamentals of Software Engineering* (2nd ed.). Prentice Hall, Upper Saddle River, NJ, USA.
- Ray Givler. 2020. A Checklist of Basic Software Engineering Practices for Data Analysts and Data Scientists. <https://www.linkedin.com/pulse/checklist-basic-software-engineering-practices-data-analysts-givler/?articleId=6681691007303630849>.
- Carole Goble. 2014. Better Software, Better Research. *IEEE Internet Computing* 18, 5 (2014), 4–8. <https://doi.org/10.1109/MIC.2014.88>
- Benjamin Graille and Loïc Gouarin. 2017. *pylbm Documentation*. (2017).
- Alan Gray and Kevin Stratford. 2013. Ludwig: multiple GPUs for a complex fluid lattice Boltzmann application. *Designing Scientific Applications on GPUs. Chapman & Hall/CRC Numerical Analysis and Scientific Computing Series, Taylor & Francis* (2013).
- Jonathan D Halverson, Thomas Brandes, Olaf Lenz, Axel Arnold, Staš Bevc, Vitaliy Starchenko, Kurt Kremer, Torsten Stuehn, and Dirk Reith. 2013. ESPResSo++: A modern multiscale simulation package for soft matter systems. *Computer Physics Communications* 184, 4 (2013), 1129–1149.
- Jo Erskine Hannay, Carolyn MacLeod, Janice Singer, Hans Petter Langtangen, Dietmar Pfahl, and Greg Wilson. 2009. How Do Scientists Develop and Use Scientific Software?. In *Proceedings of the 2009 ICSE Workshop on Software Engineering for Computational Science and Engineering (SECSE '09)*. IEEE Computer Society, Washington, DC, USA, 1–8. <https://doi.org/10.1109/SECSE.2009.5069155>
- Adrian RG Harwood, Joseph O'Connor, Jonathan Sanchez Muñoz, Marta Camps Santasmasas, and Alistair J Revell. 2018. LUMA: A many-core, fluid–structure interaction solver based on the lattice-Boltzmann method. *SoftwareX* 7 (2018), 88–94.
- Manuel Hasert, Kannan Masilamani, Simon Zimny, Harald Klimach, Jiaxing Qi, Jörg Bernsdorf, and Sabine Roller. 2014. Complex fluid simulations with the parallel tree-based lattice Boltzmann solver Musubi. *Journal of Computational Science* 5, 5 (2014), 784–794.
- Dustin Heaton and Jeffrey C. Carver. 2015. Claims About the Use of Software Engineering Practices in Science. *Inf. Softw. Technol.* 67, C (Nov. 2015), 207–219. <https://doi.org/10.1016/j.infsof.2015.07.011>
- Michael A. Heroux and David E. Bernholdt. 2018. Better (Small) Scientific Software Teams, tutorial in Argonne Training Program on Extreme-Scale Computing (ATPESC). [https://press3.mcs.anl.gov/atpesc/files/2018/08/ATPESC\\_2018\\_Track-6\\_3\\_8-8\\_1030am\\_Bernholdt-Better\\_Scientific\\_Software\\_Teams.pdf](https://press3.mcs.anl.gov/atpesc/files/2018/08/ATPESC_2018_Track-6_3_8-8_1030am_Bernholdt-Better_Scientific_Software_Teams.pdf). [https://doi.org/articles/journal\\_contribution/ATPESC\\_Software\\_Productivity\\_03\\_Better\\_Small\\_Scientific\\_Software\\_Teams/6941438](https://doi.org/articles/journal_contribution/ATPESC_Software_Productivity_03_Better_Small_Scientific_Software_Teams/6941438)
- Michael A. Heroux, James M. Bieman, and Robert T. Heaphy. 2008. Trilinos Developers Guide Part II: ASC Softwar Quality Engineering Practices Version 2.0. <https://faculty.csbsju.edu/mheroux/fall2012-csci330/TrilinosDevGuide2.pdf>.
- Vincent Heuveline and Mathias J Krause. 2010. OpenLB: towards an efficient parallel open source library for lattice Boltzmann fluid flow simulations. In *International Workshop on State-of-the-Art in Scientific and Parallel Computing. PARA*, Vol. 9. 570.
- Vincent Heuveline, Mathias J Krause, and Jonas Latt. 2009. Towards a hybrid parallelization of lattice Boltzmann methods. *Computers & Mathematics with Applications* 58, 5 (2009), 1071–1080.
- James Howison and Julia Bullard. 2016. Software in the Scientific Literature: Problems with Seeing, Finding, and Using Software Mentioned in the Biology Literature. *J. Assoc. Inf. Sci. Technol.* 67, 9 (sep 2016), 2137–2155. <https://doi.org/10.1002/asi.23538>
- IEEE. 1991. *IEEE Standard Glossary of Software Engineering Terminology*. Standard. IEEE.
- IEEE. 1998. Recommended Practice for Software Requirements Specifications. *IEEE Std 830-1998* (Oct. 1998), 1–40. <https://doi.org/10.1109/IEEESTD.1998.88286>
- Software Sustainability Institute. 2022. Online sustainability evaluation. <https://www.software.ac.uk/resources/online-sustainability-evaluation>.
- ISO/IEC. 2001. *ISO/IEC 9126. Software engineering – Product quality*. ISO/IEC.
- ISO/IEC. 2011. *Systems and software engineering - Systems and software Quality Requirements and Evaluation (SQuARE) - System and software quality models*. Standard. International Organization for Standardization.
- Michal Januszewski and Marcin Kostur. 2014. Sailfish: A flexible multi-GPU implementation of the lattice Boltzmann method. *Computer Physics Communications* 185, 9 (2014), 2350–2368.
- Kuzak M Jiménez RC, Alhamdoosh M, and et al. 2017. Four simple recommendations to encourage best practices in research software [version 1; peer review: 3 approved]. *F1000Research* 6, 876 (2017). <https://doi.org/10.12688/f1000research.11407.1>
- Panagiotis Kalagiakos. 2003. The Non-Technical Factors of Reusability. In *Proceedings of the 29th Conference on EUROMICRO*. IEEE Computer Society, 124.
- U. Kanewala and J. M. Bieman. 2013. Techniques for testing scientific programs without an oracle. In *Software Engineering for Computational Science and Engineering (SE-CSE), 2013 5th International Workshop on*. 48–57. <https://doi.org/10.1109/SECSE.2013.6615099>
- Matthias Katerbow and Georg Feulner. 2018. Recommendations on the development, use and provision of Research Software. <https://doi.org/10.5281/zenodo.1172988>
- DS Katz, NP Chue Hong, T Clark, A Muench, S Stall, D Bouquin, M Cannon, S Edmunds, T Faez, P Feeney, M Fenner, M Friedman, G Grenier, M Harrison, J Heber, A Leary, C MacCallum, H Murray, E Pastrana, K Perry, D Schuster, M Stockhause, and J Yeston. 2021. Recognizing the value of software: a software citation guide [version 2; peer review: 2 approved]. *F1000Research* 9, 1257 (2021). <https://doi.org/10.12688/f1000research.26932.2>
- Daniel S Katz, Daina Bouquin, Neil P Chue Hong, Jessica Hausman, Catherine Jones, Daniel Chivvis, Tim Clark, Mercè Crosas, Stephan Druskat, Martin Fenner, et al. 2019. Software citation implementation challenges. *arXiv preprint arXiv:1905.08674* (2019).
- Diane Kelly. 2013. Industrial Scientific Software: A Set of Interviews on Software Development. In *Proceedings of the 2013 Conference of the Center for Advanced Studies on Collaborative Research* (Ontario, Canada) (CASCON '13). IBM Corp., Riverton, NJ, USA, 299–310.

- <http://dl.acm.org/citation.cfm?id=2555523.2555555>
- Diane Kelly. 2015. Scientific software development viewed as knowledge acquisition: Towards understanding the development of risk-averse scientific software. *Journal of Systems and Software* 109 (2015), 50–61. <https://doi.org/10.1016/j.jss.2015.07.027>
- Diane F. Kelly and Rebecca Sanders. 2008. Assessing the Quality of Scientific Software. In *Proceedings of the First International Workshop on Software Engineering for Computational Science and Engineering (SECSE 2008)*. In conjunction with the 30th International Conference on Software Engineering (ICSE), Leipzig, Germany. <http://www.cse.msstate.edu/~SECSE08/schedule.htm>
- Diane F. Kelly, W. Spencer Smith, and Nicholas Meng. 2011. Software Engineering for Scientists. *Computing in Science & Engineering* 13, 5 (Oct. 2011), 7–11.
- Philippe Kruchten, Robert L Nord, and Ipek Ozkaya. 2012. Technical debt: From metaphor to theory and practice. *IEEE Software* 29, 6 (2012), 18–21.
- Jonas Latt, Orestis Malaspinas, Dimitrios Kontaxakis, Andrea Parmigiani, Daniel Lagrava, Federico Brogi, Mohamed Ben Belgacem, Yann Thorimbert, Sébastien Leclaire, Sha Li, et al. 2021. Palabos: parallel lattice Boltzmann solver. *Computers & Mathematics with Applications* 81 (2021), 334–350.
- Jörg Lenhard, Simon Harrer, and Guido Wirtz. 2013. Measuring the installability of service orchestrations using the square method. In *2013 IEEE 6th International Conference on Service-Oriented Computing and Applications*. IEEE, 118–125.
- T.C. Lethbridge, J. Singer, and A. Forward. 2003. How software engineers use documentation: the state of the practice. *IEEE Software* 20, 6 (2003), 35–39. <https://doi.org/10.1109/MS.2003.1241364>
- Maximilien Levesque, Magali Duvail, Ignacio Pagonabarraga, Daan Frenkel, and Benjamin Rotenberg. 2013. Accounting for adsorption and desorption in lattice Boltzmann simulations. *Physical Review E* 88, 1 (2013), 013308.
- Marco D Mazzeo and Peter V Coveney. 2008. HemeLB: A high performance parallel lattice-Boltzmann code for large scale fluid flow in complex geometries. *Computer Physics Communications* 178, 12 (2008), 894–914.
- J. McCall, P. Richards, and G. Walters. 1977. *Factors in Software Quality*. NTIS AD-A049-014, 015, 055.
- Peter Michalski. 2021. *State of The Practice for Lattice Boltzmann Method Software*. Master’s thesis. McMaster University, Hamilton, Ontario, Canada.
- JD Musa, Anthony Iannino, and Kazuhira Okumoto. 1987. Software reliability: prediction and application.
- Udit Nangia and Daniel S. Katz. 2017. Track 1 Paper: Surveying the U.S. National Postdoctoral Association Regarding Software Use and Training in Research. Zenodo, 1–6. <https://doi.org/10.5281/zenodo.814220> This paper was submitted to WSSSPE5.1 - <http://wssspe.researchcomputing.org.uk/wssspe5-1/> The final accepted version is <https://doi.org/10.6084/m9.figshare.5328442>.
- Luke Nguyen-Hoan, Shayne Flint, and Ramesh Sankaranarayana. 2010. A Survey of Scientific Software Development. In *Proceedings of the 2010 ACM-IEEE International Symposium on Empirical Software Engineering and Measurement (Bolzano-Bozen, Italy) (ESEM ’10)*. ACM, New York, NY, USA, Article 12, 10 pages. <https://doi.org/10.1145/1852786.1852802>
- Jakob Nielsen. 2012. Usability 101: Introduction to Usability. <https://www.nngroup.com/articles/usability-101-introduction-to-usability/>
- Pablo Orviz, Álvaro López García, Doña Cristina Duma, Giacinto Donvito, Mario David, and Jorge Gomes. 2017. A set of common software quality assurance baseline criteria for research projects. <https://doi.org/10.20350/digitalCSIC/12543>
- Gustavo Pinto, Igor Steinmacher, and Marco Aurélio Gerosa. 2016. More Common Than You Think: An In-depth Study of Casual Contributors. In *2016 IEEE 23rd International Conference on Software Analysis, Evolution, and Reengineering (SANER)*, Vol. 1. 112–123. <https://doi.org/10.1109/SANER.2016.68>
- Gustavo Pinto, Igor Wiese, and Luis Felipe Dias. 2018. How Do Scientists Develop and Use Scientific Software? An External Replication. In *Proceedings of 25th IEEE International Conference on Software Analysis, Evolution and Reengineering*. 582–591. <https://doi.org/10.1109/SANER.2018.8330263>
- Gede Artha Azriadi Prana, Christoph Treude, Ferdian Thung, Thushari Atapattu, and David Lo. 2018. Categorizing the Content of GitHub README Files. arXiv:1802.06997 [cs.SE]
- Suzanne Robertson and James Robertson. 1999. *Mastering the Requirements Process*. ACM Press/Addison-Wesley Publishing Co, New York, NY, USA, Chapter Volere Requirements Specification Template, 353–391.
- J. Rokicki and L. Laniewski-Wollk. 2016. Adjoint lattice Boltzmann for topology optimization on multi-GPU architecture. *Computers & Mathematics with Applications* 71, 3 (2016), 833–848.
- Mariusz Rutkowski, Wojciech Gryglas, Jacek Szumbarski, Christopher Leonardi, and Łukasz Łaniewski-Wollk. 2020. Open-loop optimal control of a flapping wing using an adjoint Lattice Boltzmann method. *Computers & Mathematics with Applications* 79, 12 (2020), 3547–3569.
- Reza Sadeghi, Seyedvahid Khodaei, Javier Ganame, and Zahra Keshavarz-Motamed. 2020. Towards non-invasive computational-mechanics and imaging-based diagnostic framework for personalized cardiology for coarctation. *Scientific Reports* 10, 1 (2020), 9048. <https://doi.org/10.1038/s41598-020-65576-y>
- Rebecca Sanders and Diane Kelly. 2008. Dealing with Risk in Scientific Software Development. *IEEE Software* 4 (July/August 2008), 21–28.
- Tobias Schlauch, Michael Meinel, and Carina Haupt. 2018. DLR Software Engineering Guidelines. <https://doi.org/10.5281/zenodo.1344612>
- Sebastian Schmieschek, Lev Shamardin, Stefan Frijters, Timm Krüger, Ulf D Schiller, Jens Harting, and Peter V Coveney. 2017. LB3D: A parallel implementation of the Lattice-Boltzmann method for simulation of interacting amphiphilic fluids. *Computer Physics Communications* 217 (2017), 149–161.
- Michael A Seaton, Richard L Anderson, Sebastian Metz, and William Smith. 2013. DL-MESO: highly scalable mesoscale simulations. *Molecular Simulation* 39, 10 (2013), 796–821.
- Judith Segal. 2005. When Software Engineers Met Research Scientists: A Case Study. *Empirical Software Engineering* 10, 4 (Oct. 2005), 517–536. <https://doi.org/10.1007/s10664-005-3865-y>
- Judith Segal and Chris Morris. 2008. Developing Scientific Software. *IEEE Software* 25, 4 (July/August 2008), 18–20.
- Arfon M Smith, Daniel S Katz, Kyle E Niemeyer, and FORCE11 Software Citation Working Group. 2016a. Software Citation Principles. *PeerJ Preprints* 4 (Aug. 2016), e2169v4. <https://doi.org/10.7287/peerj.preprints.2169v4>

- Arfon M. Smith, Kyle E. Niemeyer, Daniel S. Katz, Lorena A. Barba, George Githinji, Melissa Gymrek, Kathryn D. Huff, Christopher R. Madan, Abigail Cabunoc Mayes, Kevin M. Moerman, Pjotr Prins, Karthik Ram, Ariel Rokem, Tracy K. Teal, Roman Valls Guimera, and Jacob T. Vanderplas. 2018c. Journal of Open Source Software (JOSS): design and first-year review. *PeerJ Computer Science* 4 (12 Feb. 2018), e147+. <https://doi.org/10.7717/peerj-cs.147>
- Barry Smith, Roscoe Bartlett, and xSDK Developers. 2018a. xSDK Community Package Policies. <https://doi.org/10.6084/m9.figshare.4495136.v6>
- Spencer Smith, Lei Lai, and Ridha Khedri. 2007a. Requirements analysis for engineering computation: A systematic approach for improving reliability. *Reliable Computing* 13, 1 (2007), 83–107.
- Spencer Smith, Yue Sun, and Jacques Carette. 2015. State of the practice for developing oceanographic software. *McMaster University, Department of Computing and Software* (2015).
- W. Spencer Smith. 2016. A Rational Document Driven Design Process for Scientific Computing Software. In *Software Engineering for Science*, Jeffrey C. Carver, Neil Chue Hong, and George Thiruvathukal (Eds.). Chapman and Hall/CRC, Boca Raton, FL, Chapter Examples of the Application of Traditional Software Engineering Practices to Science, 33–63.
- W. Spencer Smith. 2018. Beyond Software Carpentry. In *2018 International Workshop on Software Engineering for Science (held in conjunction with ICSE'18)*. 1–8.
- W. Spencer Smith, Jacques Carette, Peter Michalski, Ao Dong, and Oluwaseun Owojaiye. 2021. Methodology for Assessing the State of the Practice for Domain X. <https://arxiv.org/abs/2110.11575>.
- W. Spencer Smith and Nirmitha Koothoor. 2016. A Document-Driven Method for Certifying Scientific Computing Software for Use in Nuclear Safety Analysis. *Nuclear Engineering and Technology* 48, 2 (April 2016), 404–418. <https://doi.org/10.1016/j.net.2015.11.008>
- W. Spencer Smith and Lei Lai. 2005a. A New Requirements Template for Scientific Computing. In *Proceedings of the First International Workshop on Situational Requirements Engineering Processes – Methods, Techniques and Tools to Support Situation-Specific Requirements Engineering Processes, SREP'05*, J. Ralyté, P. Ågerfalk, and N. Kraiem (Eds.). In conjunction with 13th IEEE International Requirements Engineering Conference, Paris, France, 107–121.
- W. Spencer Smith and Lei Lai. 2005b. A new requirements template for scientific computing. In *Proceedings of the First International Workshop on Situational Requirements Engineering Processes – Methods, Techniques and Tools to Support Situation-Specific Requirements Engineering Processes, SREP*, Vol. 5. Citeseer, 107–121.
- W. Spencer Smith, Lei Lai, and Ridha Khedri. 2007b. Requirements Analysis for Engineering Computation: A Systematic Approach for Improving Software Reliability. *Reliable Computing, Special Issue on Reliable Engineering Computation* 13, 1 (Feb. 2007), 83–107. <https://doi.org/10.1007/s11155-006-9020-7>
- W. Spencer Smith, Adam Lazzarato, and Jacques Carette. 2016b. State of Practice for Mesh Generation Software. *Advances in Engineering Software* 100 (Oct. 2016), 53–71.
- W. Spencer Smith, Adam Lazzarato, and Jacques Carette. 2018b. State of the Practice for GIS Software. <https://arxiv.org/abs/1802.03422>.
- W. Spencer Smith, Yue Sun, and Jacques Carette. 2018d. Statistical Software for Psychology: Comparing Development Practices Between CRAN and Other Communities. <https://arxiv.org/abs/1802.07362>. 33 pp.
- W. Spencer Smith, Zheng Zeng, and Jacques Carette. 2018e. Seismology Software: State of the Practice. *Journal of Seismology* 22, 3 (May 2018), 755–788.
- Carsten Thiel. 2020. EURISE Network Technical Reference. <https://technical-reference.readthedocs.io/en/latest/>.
- USGS. 2019. USGS Software Planning Checklist. <https://www.usgs.gov/media/files/usgs-software-planning-checklist>.
- Maarten van Gompel, Jauco Noordzij, Reinier de Valk, and Andrea Scharnhorst. 2016. Guidelines for Software Quality, CLARIAH Task Force 54.100. <https://github.com/CLARIAH/software-quality-guidelines/blob/master/softwareguidelines.pdf>.
- Florian Weik, Rudolf Weeber, Kai Szuttor, Konrad Breitsprecher, Joost de Graaf, Michael Kuron, Jonas Landsgesell, Henri Menke, David Sean, and Christian Holm. 2019. ESPResSo 4.0—an extensible software package for simulating soft matter systems. *The European Physical Journal Special Topics* 227, 14 (2019), 1789–1816.
- Wieggers. 2003. *Software Requirements*, 2e. Microsoft Press.
- I. S. Wiese, I. Polato, and G. Pinto. 2019. Naming the Pain in Developing Scientific Software. *IEEE Software* (2019), 1–1. <https://doi.org/10.1109/MS.2019.2899838>
- Greg Wilson, D. A. Aruliah, C. Titus Brown, Neil P. Chue Hong, Matt Davis, Richard T. Guy, Steven H. D. Haddock, Kathryn D. Huff, Ian M. Mitchell, Mark D. Plumbley, Ben Waugh, Ethan P. White, and Paul Wilson. 2014. Best Practices for Scientific Computing. *PLoS Biol* 12, 1 (Jan. 2014), e1001745. <https://doi.org/10.1371/journal.pbio.1001745>
- Greg Wilson, Jennifer Bryan, Karen Cranston, Justin Kitzes, Lex Nederbragt, and Tracy K. Teal. 2016. Good Enough Practices in Scientific Computing. *CoRR* abs/1609.00037 (2016). <http://arxiv.org/abs/1609.00037>
- Gregory V. Wilson. 2006. Where's the Real Bottleneck in Scientific Computing? Scientists would do well to pick some tools widely used in the software industry. *American Scientist* 94, 1 (2006). <http://www.americanscientist.org/issues/pub/wheres-the-real-bottleneck-in-scientific-computing>
- Yo Yehudi. 2021. Open Source for Researchers - Lightning talk. <https://doi.org/10.5281/zenodo.5655023>
- Moshe Zadka. 2018. How to open source your Python library. <https://opensource.com/article/18/12/tips-open-sourcing-python-libraries>.
- Duo Zhang, Qiong Cai, and Sai Gu. 2018. Three-dimensional lattice-Boltzmann model for liquid water transport and oxygen diffusion in cathode of polymer electrolyte membrane fuel cell with electrochemical reaction. *Electrochimica Acta* 262 (2018), 282–296. <https://doi.org/10.1016/j.electacta.2017.12.189>
- Yuzhi Zhao. 2018. Automated Knowledge Extraction Based On A Scientific Computing Software Documentation Generation Framework.