

Task 10 - Random Forest Classification

In this task, we build an end to end pipeline that reads in data in parquet format, converts it to CSV and loads it into a dataframe, trains a model and perform hyperparameter tuning.

1. Spark initialization

```
In [1]: %%bash
export version=`python --version |awk '{print $2}' |awk -F"." '{print $1$2}'`

echo $version

if [ $version == '36' ] || [ $version == '37' ]; then
    echo 'Starting installation...'
    pip3 install pyspark==2.4.8 wget==3.2 pyspark2pmml==0.5.1 > install.log 2> install.log
    if [ $? == 0 ]; then
        echo 'Please <<RESTART YOUR KERNEL>> (Kernel->Restart Kernel and Clear All Outputs)'
    else
        echo 'Installation failed, please check log:'
        cat install.log
    fi
elif [ $version == '38' ] || [ $version == '39' ]; then
    pip3 install pyspark==3.1.2 wget==3.2 pyspark2pmml==0.5.1 > install.log 2> install.log
    if [ $? == 0 ]; then
        echo 'Please <<RESTART YOUR KERNEL>> (Kernel->Restart Kernel and Clear All Outputs)'
    else
        echo 'Installation failed, please check log:'
        cat install.log
    fi
else
    echo 'Currently only python 3.6, 3.7 , 3.8 and 3.9 are supported, in case you need a different version please open an issue at https://github.co
    exit -1
fi
```

37
Starting installation...
Please <<RESTART YOUR KERNEL>> (Kernel->Restart Kernel and Clear All Outputs)

```
In [1]: from pyspark import SparkContext, SparkConf, SQLContext
from pyspark.sql import SparkSession
import os
from pyspark.ml.classification import LogisticRegression
from pyspark.ml import Pipeline
from pyspark.ml.evaluation import MulticlassClassificationEvaluator
from pyspark2pmml import PMMLBuilder
from pyspark.ml.feature import StringIndexer
from pyspark.ml.feature import VectorAssembler
from pyspark.ml.feature import MinMaxScaler
import logging
import shutil
import site
import sys
import wget
import re
import pandas as pd
```

```
In [2]: if sys.version[0:3] == '3.9':
    url = ('https://github.com/jpmml/jpmml-sparkml/releases/download/1.7.2/'
           'jpmml-sparkml-executable-1.7.2.jar')
    wget.download(url)
    shutil.copy('jpmml-sparkml-executable-1.7.2.jar',
                site.getsitepackages()[0] + '/pyspark/jars/')
elif sys.version[0:3] == '3.8':
    url = ('https://github.com/jpmml/jpmml-sparkml/releases/download/1.7.2/'
           'jpmml-sparkml-executable-1.7.2.jar')
    wget.download(url)
    shutil.copy('jpmml-sparkml-executable-1.7.2.jar',
                site.getsitepackages()[0] + '/pyspark/jars/')
elif sys.version[0:3] == '3.7':
    url = ('https://github.com/jpmml/jpmml-sparkml/releases/download/1.5.12/'
           'jpmml-sparkml-executable-1.5.12.jar')
    wget.download(url)
elif sys.version[0:3] == '3.6':
    url = ('https://github.com/jpmml/jpmml-sparkml/releases/download/1.5.12/'
           'jpmml-sparkml-executable-1.5.12.jar')
    wget.download(url)
else:
    raise Exception('Currently only python 3.6 , 3.7, 3,8 and 3.9 is supported, in case '
                    'you need a different version please open an issue at '
                    'https://github.com/IBM/claimed/issues')
```

```
In [3]: # Creating a spark context class
sc = SparkContext()

# Creating a spark session
spark = SparkSession \
    .builder \
    .appName("Python Spark Random Forest Classification") \
    .getOrCreate()
# .config("spark.some.config.option", "some-value") \
```

23/08/04 21:09:31 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
Setting default log level to "WARN".
To adjust logging level use sc.setLogLevel(newLevel). For SparkR, use setLogLevel(newLevel).

Task 10.1 : Reading the parquet file we created as part of Task 3

```
In [10]: data_parquet = 'data.parquet'
data_csv = 'randomforest.csv'
```

```
data_dir = './component-library/data/'
df = spark.read.parquet(data_dir + data_parquet)
```

```
-----
Py4JJavaError                                Traceback (most recent call last)
~/conda/envs/python/lib/python3.7/site-packages/pyspark/sql/utils.py in deco(*a, **kw)
    62         try:
--> 63             return f(*a, **kw)
    64         except py4j.protocol.Py4JJavaError as e:

~/conda/envs/python/lib/python3.7/site-packages/py4j/protocol.py in get_return_value(answer, gateway_client, target_id, name)
    327         "An error occurred while calling {0}{1}{2}.\n".
--> 328         format(target_id, ".", name), value)
    329     else:

Py4JJavaError: An error occurred while calling o196.parquet.
: org.apache.spark.sql.AnalysisException: Path does not exist: file:/resources/labs/BD0231EN/component-library/component-library/deploy/component-lib
rary/data/data.parquet;
    at org.apache.spark.sql.execution.datasources.DataSource$$anonfun$org$apache$spark$sql$execution$datasources$DataSource$$checkAndGlobPathIfNe
cessary$1.apply(DataSource.scala:558)
    at org.apache.spark.sql.execution.datasources.DataSource$$anonfun$org$apache$spark$sql$execution$datasources$DataSource$$checkAndGlobPathIfNe
cessary$1.apply(DataSource.scala:545)
    at scala.collection.TraversableLike$$anonfun$flatMap$1.apply(TraversableLike.scala:241)
    at scala.collection.TraversableLike$$anonfun$flatMap$1.apply(TraversableLike.scala:241)
    at scala.collection.immutable.List.foreach(List.scala:392)
    at scala.collection.TraversableLike$class.flatMap(TraversableLike.scala:241)
    at scala.collection.immutable.List.flatMap(List.scala:355)
    at org.apache.spark.sql.execution.datasources.DataSource.org$apache$spark$sql$execution$datasources$DataSource$$checkAndGlobPathIfNecessary(D
ataSource.scala:545)
    at org.apache.spark.sql.execution.datasources.DataSource.resolveRelation(DataSource.scala:359)
    at org.apache.spark.sql.DataFrameReader.loadV1Source(DataFrameReader.scala:223)
    at org.apache.spark.sql.DataFrameReader.load(DataFrameReader.scala:211)
    at org.apache.spark.sql.DataFrameReader.parquet(DataFrameReader.scala:641)
    at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
    at sun.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:62)
    at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
    at java.lang.reflect.Method.invoke(Method.java:498)
    at py4j.reflection.MethodInvoker.invoke(MethodInvoker.java:244)
    at py4j.reflection.ReflectionEngine.invoke(ReflectionEngine.java:357)
    at py4j.Gateway.invoke(Gateway.java:282)
    at py4j.commands.AbstractCommand.invokeMethod(AbstractCommand.java:132)
    at py4j.commands.CallCommand.execute(CallCommand.java:79)
    at py4j.GatewayConnection.run(GatewayConnection.java:238)
    at java.lang.Thread.run(Thread.java:745)

During handling of the above exception, another exception occurred:

AnalysisException                                Traceback (most recent call last)
/tmp/ipykernel_1003/1997914230.py in <module>
      2 data_csv = 'randomforest.csv'
      3 data_dir = './component-library/data/'
--> 4 df = spark.read.parquet(data_dir + data_parquet)

~/conda/envs/python/lib/python3.7/site-packages/pyspark/sql/readwriter.py in parquet(self, *paths)
    314         [('name', 'string'), ('year', 'int'), ('month', 'int'), ('day', 'int')]
    315         """
--> 316         return self._df(self._jreader.parquet(_to_seq(self._spark._sc, paths)))
    317
    318         @ignore_unicode_prefix

~/conda/envs/python/lib/python3.7/site-packages/py4j/java_gateway.py in __call__(self, *args)
    1255         answer = self.gateway_client.send_command(command)
    1256         return_value = get_return_value(
--> 1257             answer, self.gateway_client, self.target_id, self.name)
    1258
    1259         for temp_arg in temp_args:

~/conda/envs/python/lib/python3.7/site-packages/pyspark/sql/utils.py in deco(*a, **kw)
    67         e.java_exception.getStackTrace())
    68         if s.startswith('org.apache.spark.sql.AnalysisException: '):
--> 69             raise AnalysisException(s.split(':', 1)[1], stackTrace)
    70         if s.startswith('org.apache.spark.sql.catalyst.analysis'):
    71             raise AnalysisException(s.split(':', 1)[1], stackTrace)

AnalysisException: 'Path does not exist: file:/resources/labs/BD0231EN/component-library/component-library/deploy/component-library/data/data.parque
t;'
```

Task 10.2 : Converting the parquet file to CSV format.

```
In [ ]: if os.path.exists(data_dir + data_csv):
os.remove(data_dir + data_csv)
df.coalesce(1).write.option("header", "true").csv(data_dir + data_csv)
file = glob.glob(data_dir + data_csv + '/part-*')
shutil.move(file[0], data_dir + data_csv + '.tmp')
shutil.rmtree(data_dir + data_csv)
shutil.move(data_dir + data_csv + '.tmp', data_dir + data_csv)
```

Task 10.3 : Loading the CSV file into a dataframe

```
In [ ]: # Reading the file using `read_csv` function in pandas
pd_df_csv = pd.read_csv('./component-library/data/randomforest.csv')

# pd_df_csv.head() -- to view the first few rows of the dataframe

# using the `createDataFrame` function to load the data into a spark dataframe
sdf = spark.createDataFrame(pd_df_csv)
```

Task 10.4 : Creating a 80-20 training and test split with seed=1.

```
In [ ]: # casting feature columns to doubletype
sdf = sdf.withColumn("x", sdf.x.cast(DoubleType()))
sdf = sdf.withColumn("y", sdf.y.cast(DoubleType()))
sdf = sdf.withColumn("z", sdf.z.cast(DoubleType()))
```

```
# splitting dataframe into training and testing subsets
splits = sdf.randomSplit([0.8, 0.2], seed=1)
df_train = splits[0]
```

Task 10.5 : Train a Random Forest model with different hyperparameters listed below and report the best performing hyperparameter combinations.

Hyper parameters:

- number of trees : {10, 20}
- maximum depth : {5, 7}
- use random seed = 1 wherever needed

Task 10.6 : Use the accuracy metric when evaluating the model with different hyperparameters

```
In [ ]: # print parameters with highest accuracy

pd_df[pd_df['accuracy'] == pd_df['accuracy'].max()]
```