

Storage engines in MySQL

A storage engine is a software component that handles the operations that store and manage information in a database. MySQL is unusual among relational databases because it supports multiple storage engines.

Each storage engine has a particular set of operational characteristics, including the types of locks to manage query contention and whether the storage engine supports transactions. These properties have implications for database performance, so choose your storage engine based on the type of data you want to store and the operations you want to perform.

Most applications require only one storage engine for the whole database, but you can specify the storage engine on a table-by-table basis if your data has different requirements.

Storage engines available in MySQL

Engines	Description
InnoDB	<ul style="list-style-type: none">• Default storage engine for MySQL 5.5 and later.• Suitable for most data storage scenarios.• Provides ACID-compliant tables and FOREIGN KEY referential-integrity constraints.• Supports commit, rollback, and crash recovery capabilities to protect data.• Supports row-level locking.• Stores data in clustered indexes which reduces I/O for queries based on primary keys.
MyISAM	<ul style="list-style-type: none">• Manages non-transactional tables.• Provides high-speed storage and retrieval.• Supports full-text searching.
MEMORY	<ul style="list-style-type: none">• Provides in-memory tables, formerly known as HEAP.• Stores all data in RAM for faster access than storing data on disks.• Useful for quick lookups of reference and other identical data.
MERGE	<ul style="list-style-type: none">• Treats groups of similar MyISAM tables as a single table.• Handles non-transactional tables.
EXAMPLE	<ul style="list-style-type: none">• Allows developers to practice creating a new storage engine.• Allows developers to create tables.• Does not store or fetch data.
ARCHIVE	<ul style="list-style-type: none">• Stores a large amount of data.• Does not support indexes.
CSV	<ul style="list-style-type: none">• Stores data in Comma Separated Value format in a text file.
BLACKHOLE	<ul style="list-style-type: none">• Accepts data to store but always returns empty.
FEDERATED	<ul style="list-style-type: none">• Stores data in a remote database.

Commands for working with Storage Engines

If you're a DBA working with storage engines in MySQL, you should be familiar with the following common commands.

SHOW ENGINES

Displays status information about the server's storage engines. Useful for checking whether a storage engine is supported, or what the default engine is.

```
mysql> SHOW ENGINES;
```

Engine	Support	Comment	Transactions	XA	Savepoints
FEDERATED	NO	Federated MySQL storage engine	NULL	NULL	NULL
MRG_MYISAM	YES	Collection of identical MyISAM tables	NO	NO	NO
MyISAM	YES	MyISAM storage engine	NO	NO	NO
BLACKHOLE	YES	/dev/null storage engine (anything you write to it disappears)	NO	NO	NO
CSV	YES	CSV storage engine	NO	NO	NO
MEMORY	YES	Hash based, stored in memory, useful for temporary tables	NO	NO	NO
ARCHIVE	YES	Archive storage engine	NO	NO	NO
InnoDB	DEFAULT	Supports transactions, row-level locking, and foreign keys	YES	YES	YES
PERFORMANCE_SCHEMA	YES	Performance Schema	NO	NO	NO

9 rows in set (0.28 sec)

CREATE TABLE

Creates a table using the storage engine specified in the `ENGINE` clause, as shown in the following examples:

```
CREATE TABLE Products (i INT) ENGINE = INNODB;
```

```
CREATE TABLE Product_Codes (i INT) ENGINE = CSV;
```

```
CREATE TABLE History (i INT) ENGINE = MEMORY;
```

If you do not specify the `ENGINE` clause, the `CREATE TABLE` statement creates the table with the default storage engine, usually **InnoDB**.

SET

For databases with non-standard storage needs, you can specify a different default storage engine using the `set` command.

Set the default storage engine for the current session by setting the `default_storage_engine` variable using the `SET` command. For example, if you are creating a database to store archived data, you can use the following command:

```
SET default_storage_engine=ARCHIVE;
```

To set the default storage engine for all sessions, set the `default-storage-engine` option in the `my.cnf` configuration file.

ALTER TABLE

You can convert a table from one storage engine to another using an `ALTER TABLE` statement. For example, the following statement set the storage engine for the `Products` table to `Memory`:

```
ALTER TABLE Products ENGINE = MEMORY;
```

InnoDB is suitable for most data storage needs but setting and working with different storage engines in **MySQL** gives you more control over how your data is stored and accessed. Using the most appropriate storage engine for your data brings operational benefits like faster response times or efficient use of available storage.