

ReactJS — A1 Complete Assessment

Section A — Concept Application Answers

S1 — const, let, and var

Use **const** for restaurant name and minimum order value because they must not be reassigned. Use **let** for the currently selected dish because its value changes while browsing.

```
const restaurantName = "Spice Garden";
const minimumOrderValue = 200;
let selectedDish = "Paneer Tikka";
selectedDish = "Veg Biryani";
```

let and const are block-scoped. const prevents reassignment, while let permits it. var is function-scoped and can be redeclared, so modern ES6+ code normally prefers let or const.

S2 — Delivery Fee Logic

VIP users must be checked first because they always receive free delivery. Strict equality (===) should be used for the user type because it avoids implicit type conversion.

S3 — for-of vs forEach

Use for-of when loop control such as break or continue may be useful. Use forEach for a simple operation that should run for every array element. Both can display dishes and count vegetarian dishes.

S4 — Reusable Tax Function

A reusable function can receive price and category and apply 5% GST to food and 18% GST to beverages. Function declarations are hoisted; function expressions and arrow functions are not callable before initialization. For a small shared utility, an arrow function is concise and readable.

S5 — Event Handling

Attach the form's submit event using `addEventListener()`. Call `event.preventDefault()` so the browser does not perform its default form submission/reload. JavaScript can then validate the cart and address and show confirmation without reloading.

S6 — Promises vs async/await

Both `.then().catch()` and `async/await` handle asynchronous fetch operations. For this UI, `async/await` with `try/catch/finally` is preferred because loading, success and error handling are easy to read and the loading state can be reliably cleared in finally.