

# Unofficial Tagged Thesis LaTeX Template Manual

S McCarty

July 31, 2025

## Contents

|          |   |          |
|----------|---|----------|
| <b>1</b> | <b>Get Started</b>  | <b>3</b> |
| <b>2</b> | <b>Tips for Drafting</b>                                  | <b>3</b> |
| 2.1      | What about Overleaf? . . . . .                            | 4        |
| 2.2      | What about In-Browser but Not Overleaf? . . . . .         | 4        |
| <b>3</b> | <b>Types of Content</b>                                   | <b>5</b> |
| 3.1      | Text . . . . .  | 5        |
| 3.1.1    | Not Using Unicode . . . . .                               | 5        |
| 3.2      | Figures . . . . .   | 6        |
| 3.2.1    | Alt Text . . . . .  | 6        |
| 3.2.2    | Not Using Figure Environment . . . . .                    | 7        |
| 3.2.3    | Subfigures . . . . .                                      | 8        |
| 3.2.4    | List of Figures . . . . .                                 | 8        |
| 3.2.5    | Continued Figures . . . . .                               | 8        |
| 3.2.6    | Landscape Figure . . . . .                                | 9        |
| 3.3      | Tables . . . . .  | 9        |
| 3.3.1    | Tables Used For Formatting . . . . .                      | 10       |
| 3.3.2    | Not Using Table Environment . . . . .                     | 10       |
| 3.3.3    | Complex Tables with Multi-rows or Multi-columns . . . . . | 11       |
| 3.3.4    | List of Tables . . . . .                                  | 11       |
| 3.3.5    | Continued Table . . . . .                                 | 11       |
| 3.3.6    | Landscape Table . . . . .                                 | 12       |

|           |   |           |
|-----------|---|-----------|
| 3.4       | Math and Equations . . . . .                                | 12        |
| 3.5       | Theorems, Proofs, Definitions, etc. . . . .                 | 13        |
| 3.6       | Algorithms . . . . .  | 13        |
| 3.7       | Chemistry . . . . .   | 14        |
| <b>4</b>  | <b>Preliminary Pages</b>                                    | <b>14</b> |
| 4.1       | Title Page . . . . .  | 14        |
| 4.2       | Table of Contents . . . . .                                 | 16        |
| 4.3       | Abstract . . . . .  | 16        |
| 4.4       | Dedication . . . . .  | 16        |
| 4.5       | List of Tables, List of Figures . . . . .                   | 17        |
| 4.6       | Nomenclature . . . . .                                      | 17        |
| 4.7       | Acknowledgements . . . . .                                  | 17        |
| <b>5</b>  | <b>Page Numbers and Margins</b>                             | <b>17</b> |
| <b>6</b>  | <b>Headings</b>   | <b>17</b> |
| 6.1       | Appendices . . . . .  | 18        |
| <b>7</b>  | <b>Bibliography</b>   | <b>19</b> |
| <b>8</b>  | <b>Class Details</b>  | <b>20</b> |
| <b>9</b>  | <b>Checking the Tagging</b>                                 | <b>21</b> |
| <b>10</b> | <b>Special Situations</b>                                   | <b>22</b> |
| 10.1      | Using H floats . . . . .                                    | 22        |
| 10.2      | Shared Consent Form . . . . .                               | 22        |
| 10.3      | Error: "... does not doesn't match definition..." . . . . . | 23        |
| 10.4      | Error: Missing .... __um_group_begin . . . . .              | 23        |
| 10.5      | Parent-Child Warnings . . . . .                             | 23        |
| 10.5.1    | 'P/pdf2' -- > 'float/latex' . . . . .                       | 23        |
| 10.5.2    | Reference -- > Formula . . . . .                            | 24        |
| 10.6      | Warning: Patching footnotes failed. . . . .                 | 24        |
| <b>11</b> | <b>Thesis.tex Breakdown</b>                                 | <b>24</b> |

# 1 Get Started

To get started with the template, choose either Journal style or Traditional Style and download the corresponding folder.

Note, you must use LuaLatex and Biber (for the bibliography) to compile the template. It is highly recommended you install LaTeX onto your computer and use it offline. If you need help, there are many tutorials on the internet and specific tips in the folder *Setting Up Local LaTeX*. Make sure your latex version is up-to-date. You will have warnings after the first run. Run LuaLatex → Biber → LuaLatex to have a readable document. There may still be some warnings. Warnings about cross-references can be mostly ignored until you are preparing your final submission. To get rid of all warnings, you may have to run LuaLatex several times.

Your thesis must be tagged for accessibility. This template is set-up to have LaTeX do the tagging for you. The official list of packages compatible with tagging is located here: <https://latex3.github.io/tagging-project/tagging-status/>. The list is pessimistic - some packages labeled as incompatible have workarounds or cause only less-than-ideal tagging.

# 2 Tips for Drafting

1. If you need landscape tables/figures, subfigures, or algorithms, there are competing packages to do the same thing. Use the examples/packages used in the template.
2. LuaLatex and Biblatex are required in the template.
3. Instead of

---

$$x_{\text{someCommand}\{\text{whatever}\}}$$

---

you must use curly brackets and do

---

$$x_{\{\text{someCommand}\{\text{whatever}\}\}}$$

---

for tagging to work. If the subscript is a single character, you do not need curly brackets.

4. Don't overload the preamble - the template already implements the basics. If you don't know what a package/command in your draft's preamble does, the template probably already handles it.
5. Don't take any warning about tagging too seriously until you run Biber and recompile a few times. If that doesn't help, try deleting all auxillary files and starting fresh.

## 2.1 What about Overleaf?

There are two main problems with Overleaf:

First, as of Spring of 2025, Overleaf's latest version is TexLive 2024, which was probably frozen around March 2024. This version is too old to support tagging table headers. In the Summer of 2025, Overleaf will likely provide TexLive 2025, which will at least support tagging table headers (although the >1 year lag in updates will probably continue to be difficult to accommodate until tagging is fully matured).

Second, the compilation timeout on Overleaf is 4 minutes. This may be too short depending on the speed of Overleaf's servers and the complexity of your thesis.

## 2.2 What about In-Browser but Not Overleaf?

An up-and-coming (free as of 2025) alternative to Overleaf is Crixet.com. Similar to Overleaf, Crixet is all in-browser and allows for collaboration. Further, Crixet appears to update far more often than Overleaf and has a different behind-the-scenes infrastructure which prevents timeouts. To use Crixet, at the very top of thesis.tex, replace

---

```
%!LW recipe=lualatex-plain
```

---

with

---

```
% !TEX program = lualatex
```

---

Upon testing in Summer 2025, the template compiles on Crixet with tagging, however, it is much slower than installing and running LaTeX on your own computer. Using the draft option (see [section 8](#)) often is highly recommended if you choose this route.

## 3 Types of Content

### 3.1 Text

Text is tagged automatically.

The default font for LuaLatex is unicode based (great for non-latin characters and emojis), which is a little different than the old default font on pdflatex (the most popular latex compiler). A reasonable font choice for the body text is preset in the template, but you can change the font (it should be plain, 12 pt). You must use the same font throughout.

The easiest method to change the font is to like one of the fonts supported by the package fontsetup (see its documentation), and change the setting of libertinus to the one to your taste:

---

```
\usepackage[libertinus]{fontsetup}
```

---

This command is located in the preamble of thesis.tex.

If you would like to point LaTeX to a specific set of fonts on your computer, you can **delete** the fontsetup line above and replace it with:

---

```
\usepackage{unicode-math}
\setmainfont{texgyreagella}[
Extension    = .otf,
UprightFont  = *-regular,
ItalicFont   = *-italic,
BoldFont     = *-bold,
BoldItalicFont = *-bolditalic
]
\setmathfont{texgyreagella-math.otf}
```

---

where texgyreagella is the name of your chosen font. See fontspec and unicode-math package for more information.

#### 3.1.1 Not Using Unicode

It is possible to **not** use unicode, which may make documents look a little more familiar. However, without unicode, the accessibility of the math formulas is much worse (currently ISU has no requirements about the accessibility of math, so it is suitable for submission). To use old fonts instead of unicode, replace the fontsetup command with

---

```
\usepackage{lmodern}\usepackage[T1]{fontenc}
```

---

Also, delete the line

---

```
\let\bm\symbf
```

---

## 3.2 Figures

A figure consists of: the figure itself, a caption, and invisible alt text for screen readers.

The most basic figure has the following set-up.

---

```
\begin{figure}[b]%b may be replaced as needed
\centering
\includegraphics[alt={Alt text here}]{image.png}
\caption{A figure's caption.} %after includegraphics
\end{figure}
```

---

Whenever you use the figure environment, captions are automatically formatted for you, except for the fact captions for figures should be **below** the figure. Therefore, the caption command must be after the image.

### 3.2.1 Alt Text

You must set the alt text of all figures with a description for the visually impaired. Notice in the example above that `includegraphics` includes an argument for the alt text in the square brackets. Alt text can be set in a similar way for Tikz and Picture generated figures as well (if your LaTeX is from June 2025 or later).

---

```
\begin{figure}[b]
\centering
\begin{tikzpicture}[alt={tikz graphic}]
\draw[gray, thick] (-1,2) -- (2,-4);
\end{tikzpicture}
\caption{A figure's caption.}
\end{figure}
\begin{figure}[ht]
\centering
\begin{picture}[alt={more alt}](3,3)
```

```

\put(0,0){\color{blue}\circle*{0.25}}\hbox{\kern3pt
\texttt{(0,0)}}}
\end{picture}
\caption{A figure's caption.}
\end{figure}

```

---

If you are using LaTeX to generate a figure via a method that does not support alt text, you will want to generate the graphic separately from your main dissertation. For example, xy-pic is not supported by tagging. Therefore, move the xy-pic to a separate file which has its documentclass set to standalone.

---

```

\documentclass{standalone}
\usepackage[all]{xy}

\begin{document}

$$\begin{matrix}
A & \xrightarrow{d} & \xrightarrow{r} & \text{ \& } & B & \xrightarrow{d} & \xrightarrow{r} \\
C & \xrightarrow{r} & \text{ \& } & D
\end{matrix}$$

\end{document}

```

---

Compiling this document will generate the figure as a standalone PDF. This can then be included in your main thesis with includegraphics.

---

```

\includegraphics[alt={alt text}]{pathToOtherPDF.pdf}

```

---

If your standalone graphic needs to reference labels from your main dissertation, use the xr package.

### 3.2.2 Not Using Figure Environment

Most of the time figures will be in a figure environment. Occasionally, however, you may not want to use the figure environment. In such a case, use captionsetup before the figure to ensure proper formatting.

---

```

% no \begin{figure}...\end{figure}
\captionsetup{type=figure}%if you don't use floating figures, you must
tell latex that it is a figure
\includegraphics[alt={alt text}]{image.png}

```

---

### 3.2.3 Subfigures

Subfigures are supported by the template. They are supported via the `subcaption` package. See the example below.

---

```
\begin{figure}[b]
  \centering
  \begin{subfigure}[c]{0.495\textwidth}
    \includegraphics[alt={sample
      image},width=0.99\textwidth]{example-image-c}%
    \subcaption{\label{fig:2a}}
  \end{subfigure}
  \begin{subfigure}[c]{0.495\textwidth}
    \centering{\includegraphics[alt={sample
      image},width=0.99\textwidth]{example-image-c}}%
    \subcaption{\label{fig:2b}}%
  \end{subfigure}%
  \caption{A figure with two subfigures: (a) first subfigure; (b)
    second subfigure.\label{fig:2}}
\end{figure}
```

---

### 3.2.4 List of Figures

List of Figures is required if you have figures. It is generated automatically by the template by using the `listoffiguresTagged` command. If you want a shorter caption to be used in the List of Figures, use the optional argument of `caption`:

---

```
\caption[This is short and will appear in the List of
  Figures.]{This is the very, very long and detailed caption that
  will appear under the figure with all the details.}
```

---

### 3.2.5 Continued Figures

If your figure spans multiple pages, use `ContinuedFloat` and use “Continued” as the caption for the figure environments that appear on the later pages. This will automatically handle the numbering. Only one entry will appear in the List of Figures.

---

```
\begin{figure}
```



```

...
\caption{Main caption for big figure}
\end{figure}
\begin{figure}
\ContinuedFloat %first thing after begin{figure}
...
\caption{Continued} %below figure
\end{figure}

```

---

### 3.2.6 Landscape Figure

To have a landscape figure, wrap the figure in a landscape environment.

---

```

\begin{landscape}
\hfill
\vfill

\begin{figure}[h!]%h! necessary for it to be centered
...
\caption{...}
\end{figure}

\hfill
\vfill
\end{landscape}

```

---

A landscape figure should be on the page by itself.

## 3.3 Tables

Tables are generally entered by normal LaTeX means, however, they require some extra mark-up to be properly tagged. Note, several popular table related packages are compatible with tagging, such as booktabs. However, it is best to check compatibility if concerned (<https://latex3.github.io/tagging-project/tagging-status/>).

Table captions are automatically formatted. Table captions should be above the table, therefore the caption command should be before the table. Table cells are automatically tagged, but table headers must be tagged. Since LaTeX cannot

tell what are headers without help, you must also declare any header rows or columns using `tagpdfsetup` inside the table environment.

---

```

\begin{table}[h!tb] \centering
  \caption{A table caption.}
  \tagpdfsetup{table/header-rows={1}}%just row 1 is a header
  %\tagpdfsetup{table/header-rows={1,2}} would have rows 1 and 2 be
    header rows instead
  %Use \tagpdfsetup{table/header-columns={}} for header columns
    instead

  \begin{tabular}{ll}
    Musician & Piece \\
    Bach & Cello Suite Number 1 \\
    Beethoven & Cello Sonata Number 3 \\
    Brahms & Cello Sonata Number 1
  \end{tabular}
\end{table}

```

---

### 3.3.1 Tables Used For Formatting

Occasionally, a LaTeX table is used for formatting instead of being used as a real table. In such a case, it should be declared to be for presentation purposes with `tagpdfsetup`.

---

```

\begin{table}
  \tagpdfsetup{table/tagging=presentation}
  ...
\end{table}

```

---

### 3.3.2 Not Using Table Environment

Most of the time tables will be in a table environment. Occasionally, however, you may not want to use the table environment. In such a case, use `captionsetup` before the table to ensure proper formatting.

---

```

% no \begin{table}...\end{table}
\captionsetup{type=table}%if you don't use floating table, you must
  tell latex that it is a table

```

---

```
\begin{tabular}{...}
...
\end{tabular}
```

---

### 3.3.3 Complex Tables with Multi-rows or Multi-columns

Sometimes cells span multiple rows or columns. If a cell spans multiple columns, nothing further needs to be done. If a cell spans multiple rows, a `tagpdfsetup` inside the cell must be used to declare how many rows it spans. See example.

---

```
\begin{tabular}{rr}
1 & B & \\
0 & \tagpdfsetup{table/multirow={2}}\multirow{2}{*}{A} & \\
0 & & \\
\end{tabular}
```

---

### 3.3.4 List of Tables

List of Tables is required if you have tables. It is generated automatically by the template by using the `listoftablesTagged` command.

If you want a shorter caption to be used in the List of Tables, use the optional argument of caption:

---

```
\caption[This is short and will appear in the List of Tables.]{This
is the very, very long and detailed caption that will appear
above the table with all the details.}
```

---

### 3.3.5 Continued Table

If your table spans multiple pages, use `ContinuedFloat` and use “Continued” as the caption for the tables that appear on the later pages. This will automatically handle the numbering. Only one entry will appear in the List of Tables.

---

```
\begin{table}
\caption{Main table caption} %above table
...
\end{table}
\begin{table}
```

```

\ContinuedFloat %first thing after begin{table}
\caption{Continued} %above table
...
\end{table}

```

---

### 3.3.6 Landscape Table

To have a landscape table, wrap the table in a landscape environment.

---

```

\begin{landscape}
\hfill
\vfill

\begin{table}[h!]%h! necessary for it to be centered
\centering
\caption{This table shows almost nothing but is a
sideways table and takes up a whole page by itself}
\label{nothingelse}
\tagpdfsetup{table/header-rows={1}}%first row are headers
\begin{tabular}{lcc} \hline
\textbf{Element} & \textbf{Control} & \textbf{Experimental} \\ \hline
Moon Rings & 1.23 & 3.38 \\
Moon Tides & 2.26 & 3.12 \\
Moon Walk & 3.33 & 9.29 \\ \hline
\end{tabular}
\end{table}

\hfill
\vfill
\end{landscape}

```

---

A landscape table should be on the page by itself.

## 3.4 Math and Equations

It is suggested you use the `math-packages` document class option (see [section 8](#)). Then, math works as expected and automatically.

LuaLatex handles fonts a little differently than pdfLatex. To make bold math in LuaLatex with `unicode-math`, it is suggested to use the command `\sympf`. How-

ever, many people are used to using `bm`. The template re-maps the `bm` command to `sympbf` so you don't have to change anything. Nonetheless, there might be cases where the output looks slightly different.

Note, it is possible to **not** use `unicode-math` with the template, though not recommended. See [subsection 3.1](#).

### 3.5 Theorems, Proofs, Definitions, etc.

It is suggested you use the `math-packages` document class option (see [section 8](#)). Then, theorems, proofs, definitions, etc. work as expected. The `templatedTheoremTypes.sty` package file is optional, however, it conveniently predefines common environments of this type and sets the numbering to restart each chapter.

### 3.6 Algorithms

It is suggested you use the `algorithm-packages` document class option (see [section 8](#)) to have painless tagged algorithms. This option loads the packages `algorithm` and `algpseudocode`. While you may try to use other algorithm packages, they may not be compatible with tagging. This option also defines a `parstate` command which allows for states that must be wrapped onto multiple lines.

The command in the preamble:

---

```
\PassOptionsToPackage{noend}{algpseudocode}
```

---

is entirely optional. You can use similar commands to pass your preferred options to `algpseudocode`.

With `algorithm-packages` option, you may write captioned algorithms as usual and they will automatically be tagged.

---

```
\begin{algorithm}
  \caption{Score Algorithm}
  \begin{algorithmic}[1]
    \State {\textbf{Input: }}{$s$ is a sensor }
    \State Randomly choose $s$ days
    \For{$x$ in $\{1,2,\ldots,1000\}$}
      \parstate{Set $a$ to be something in this very long state that will
        have to be wrapped quite possibly around and around and around}
    \EndFor
  \end{algorithmic}
\end{algorithm}
```

```
\end{algorithm}
```

---

## 3.7 Chemistry

Chemistry packages have not been thoroughly tested. A standard for the tagging of chemistry formulas has not been well defined. In basic testing, mhchem is compatible with math-style tagging, however, chemformula is problematic.

Since the tagging of chemistry as math is questionable and might break the document, you might choose to disable the tagging of all math/chemistry formulas while keeping the tagging of headings, tables, figures, etc. To do this, replace DocumentMetadata at the top of thesis.tex with

---

```
\DocumentMetadata{  
  lang=en,  
  testphase={  
    phase-III,  
    table,  
    title,  
    firstaid,  
    tikz  
  },  
  pdfversion=2.0,  
  pdfstandard=ua-2,  
  pdfstandard=a-4f,  
}
```

---

It does have the unfortunate side effect that any math will also not be tagged.

## 4 Preliminary Pages

### 4.1 Title Page

Required. The required elements are implemented in the template. Ensure you fill out:

---

```
%Set author  
\newcommand{\theAuthor}{Alice Wonder}  
%Set the title
```

```
\twoLineTitle{This is the title of a thesis
submitted to Iowa State University on the first line}{
Second line, only the first letter of
the first word and names
are capitalized!}
```

---

in the preamble of thesis.tex to properly set the author and title. The PDF properties will be set for you. The title should only have the first word and proper nouns capitalized. If you have a one line title, leave the second argument blank.

---

```
%Set the tite
\twoLineTitle{A short title.}{}

```

---

Additionally, finish filling out the information in Preface > titlepage.tex according to the instructions. You must provide the name of your degree, your major, your major professor, and your committee members. There are additional instructions in that file if you have a co-major.

You can modify the spacing of the title page by editing the following section in isuthesis tagged.cls:

---

```
\long\def\maketitle{\begin{titlepage}
\ vbox to \textheight{
\begin{center}
\ vskip 25pt % space at top
{\bfseries \@title}
\ vskip 12pt % space between title and by
by \\
\ vskip 12pt % space below by
{\bfseries \@author}
\ vskip 40pt % space after author
A \@format\ submitted to \@submit\ \\
in partial fulfillment of the requirements for the degree of\\
\@degree \\[2.5pt]
\ vskip 40pt % space between degree and major
\@major
\ vskip 40pt % space between major and committee
\begin{singlespace}
Program of Study Committee: \\
\@mprof
\@mprofs
```

```

\@cmprofs
\@members
\vfll
\vspace{12pt} %space after committee
\@disclaimertitlepage
\end{singlespace}
\end{center}
\vfll
\vspace{12pt}%space before copyright
\@titlefoot } % end of \vbox
\end{titlepage}
}% end maketitle

```

---

For example, changing 12 pt to 24 pt will generally increase the space. However, note the macro forces the title page to fit on one page regardless of the space settings. Therefore, if too many spaces are too large, you may not see the expected effects (trying shrinking spaces instead).

## 4.2 Table of Contents

Required. It is automatically generated.

If you absolutely must add a page break inside the table of contents, then before the sectioning command (chapter/section/subsection/...) you want on the next page of the Table of Contents, add the command

---

```
\addtocontents{toc}{\protect\newpage}
```

---

Generally, however, it is best to leave the Table of Contents as-is.

## 4.3 Abstract

Required. See Preface > abstract.tex.

## 4.4 Dedication

Optional - maximum of 1 page. See Preface > dedication.tex.



## 4.5 List of Tables, List of Figures

Required if you have tables or figures, respectively. It is mostly automatic. See [subsubsection 3.3.4](#) and [subsubsection 3.2.4](#).

## 4.6 Nomenclature

Optional. Most use the nomenclature package and this is what is shown in the template file. See Preface > nomenclature.tex. To use the nomenclature package, in addition to running lualatex and biber (for the bibliography), you must also run a command along the lines of

---

```
makeindex .\LatexAux\thesis.nlo -s nomencl.ist -o
.\LatexAux\thesis.nls
```

---

See manual for the nomenclature package for details.

## 4.7 Acknowledgements

Optional - max 4 pages. See Preface > acknowledgements.tex.

# 5 Page Numbers and Margins

These requirements are handled by the template. The preliminary pages should have roman numerals and the body should have arabic numerals. If this is not working, you likely accidentally deleted some part of

---

```
\frontmattersetup
...
\pagestyle{fancy}
\pagenumbering{arabic}
```

---

in thesis.tex. See the original thesis.tex for placement.

# 6 Headings

If you use chapter, section, subsection, etc. commands, the styling and tagging of headings are handled automatically. Chapter headings must be all caps, but this too is handled automatically. For example,

---

```
\chapter{A Title}
```

---

will still be properly formatted as **CHAPTER 1. A TITLE**. If you have an exception to this all-caps requirement and need lower-case letters outside of math (which are automatically left alone), you can use `NoCaseChange`. For example,

---

```
\chapter{An \NoCaseChange{ReLU} Production}
```

---

will be formatted as **CHAPTER 2. AN ReLU PRODUCTION**.

In the **rare** case you create a heading *without using the sectioning commands* (*chapter/section/subsection/...*), you will manually need to instruct LaTeX to tag it. For example,

---

```
{  
\tagtool{para/tag=H3}%h2=section, h3=subsection,....  
\textbf{A great heading which is not part of a sectioning command}  
}
```

---

The curly brackets around `tagtool` and the text acting as a heading is required. Make sure the formatting of the heading matches the rest of the headings of that level.

## 6.1 Appendices

Appendices are handled differently in Journal and Traditional. In both cases, appendices are labeled with letters: *A, B, ...*

For a Journal style thesis, simply add another section labeled with “Appendix < *letter* >”:

---

```
\printbibliography[heading=subbibnumbered]  
%Appendices come after the bibliography  
\section{Appendix A: Appendix A Title Goes Here After The Colon}  
Appendix A things  
\section{Appendix B: Appendix B Title Goes Here After The Colon}  
Appendix B things
```

---

For a Traditional style thesis, the Appendices are additional chapters after the References chapter. In this case, the chapter command will automatically add Appendix < *letter* > to the title for you. If you have a single appendix:

---

```
\singleappendixtitle
\chapter{Appendix Name}
\finishAppendixSetup%must come immediately after chapter
...%body of the appendix
```

---

If you have multiple appendices, in the **first** appendix:

---

```
\appendixtitle
\appendix
\chapter{First Appendix Name}
\finishAppendixSetup%immediately after chapter in the first appendix
...%body of the appendix
```

---

In subsequent appendices, you only need the chapter command:

---

```
\chapter{Appendix of Second and Onward Appendix}
...%body of the appendix
```

---

In a traditional thesis, all headings *below* chapter (i.e. section, subsection, ...) in the appendices should be *unnumbered*. To do this, use the starred version of the sectioning commands:

---

```
\section*{Section Name}
...
\subsection*{Subsection Name}
```

---

## 7 Bibliography

To be compatible with tagging, you must use BibLaTeX (not BibTeX). The good news is BibLaTeX is quite backwards compatible with bibtex or natbib, such that you should not have to change your cite commands or your bib file. There are a wide variety of BibLatex styles - see BibLatex documentation.

By default, BibLatex uses biber, so ensure you are using biber to process the bib file or change the backend of biblatex.

If using the Journal Style, you include references for each chapter before any appendices. To do so, use the command

---

```
\printbibliography[heading=subbibnumbered]
```

---

within each chapter. You do **not** need to provide a heading.

If using the Traditional Style, you will have a Bibliography chapter for the whole thesis before any appendices. To do so, in `thesis.tex` there are the following lines:

---

```
\chapter*{BIBLIOGRAPHY}
\addToTOCwithoutChapter{BIBLIOGRAPHY}
\printbibliography[heading=none]
```

---

By default, some long bibliography entries may be broken across two pages. It is ISU's opinion that this is bad. You can prevent this by using the `bib-no-break` document class option (see [section 8](#)).

## 8 Class Details

The following packages are always loaded in `cls` file: `xpatch`, `fancyhdr`, `titlesec`, `setspace`, `nowidow`, `caption`, `subcaption`, `geometry`, `graphicx`. Further, `biblatex` and `hyperref` must also be loaded later in the preamble.

The class has options that can be set within the square brackets

---

```
\documentclass[options go here]{isuthesistagged}
```

---

Additional class options:

- `draft`: disables most of tagging, loading of figures, and other "expensive" tasks. Makes compilation much faster. Ignore any warnings from `tagpdf` when this option is on. Cannot be used for final submission. Automatically includes the option `no-mathml` and `no-tag-tree`.
- `math-packages`: loads `amsmath`, `amsthm`, `mathtools`, and associated tagging fixes
- `algorithms-packages`: loads `algorithm`, `algpseudocode`, fixes the numbering and tagging, also provides a command for long states
- `no-mathml`: disables math tagging (not required by Iowa State)
- `no-tag-tree`: disables a slow part of tagging (must be re-enabled before submission)

- `bib-no-break`: by default, page breaks in the middle of bibliography entries are discouraged, but may happen for a particularly long entry (4+ lines). With this option, a page break will never happen in the middle of an entry, no matter how long. This is "recommended" but not required by Iowa State.

The template must be compiled with LuaLatex. See your editor settings or the tips in Setting Up Local Latex. If you use a terminal instead of an editor, you will call `lualatex` and `biber` (for the bibliography) on the command line. I run commands of the form

---

```
lualatex --aux-directory=./LatexAux --synctex=1
--interaction=nonstopmode --c-style-errors .\thesis.tex
biber thesis --output-directory=./LatexAux
```

---

on MikTeX on Windows (this also puts the auxillary files in another directory). TexLive doesn't support auxillary files in another directory, so you would want to modify the commands to be

---

```
lualatex --synctex=1 --interaction=nonstopmode --c-style-errors
.\thesis.tex
biber thesis
```

---

## 9 Checking the Tagging

You can validate the PDF meets ISO tagging standards by using VeraPDF (either by downloading it or at [demo.verapdf.org](https://demo.verapdf.org)) and using the profile PDF/UA-2. Technically, it complains about the font Libertinus (problems with glyph width) in the example files, but that has nothing to do with tagging. If it bothers you, it can be fixed by switching to another font. If you actually want to manually inspect the tag structure, you can use [ngpdf.com](https://ngpdf.com) (upload the file, then choose the editor option).

Note, figures and tables are not located in the tagging tree exactly where they are located in the PDF. Instead, they are grouped together at the end of each subsection. Even though figures and tables physically interrupt the text, usually readers actually come back to them later. Therefore, it does not make sense to have figures and tables disrupt the text within the tagging tree.

## 10 Special Situations

### 10.1 Using H floats

H floats are a misnomer - they are not actually floating around anymore. H floats are not yet officially supported, but we can fix the tagging ourselves.

For the most useful tagging, you should ask yourself whether you expect the reader to stop reading the text exactly where you placed the float and switch to looking at the float. If so, then you will want to wrap the float in a “Part” tag:

---

```
\tagstructbegin{tag=Part}  
\begin{figure}[H]  
...  
\end{figure}  
\tagstructend
```

---

If instead the reader will probably finish the sentence/paragraph/section and return to the float later, then you will want to tag it like a float. In this case, it would look like:

---

```
\tagstructbegin{tag=float}  
\begin{figure}[H]  
...  
\end{figure}  
\tagstructend
```

---

If the float is alone in an appendix, I would suggest tagging it as a float.

### 10.2 Shared Consent Form

If you have co-authored papers, you may need a Shared Consent Form. A TeX Version of Type II of this form is available in Shared Consent Form folder (a Type I TeX form has not yet been created). You can copy the file to the Body folder and include this file with

---

```
\input{Body/sharedConsent.tex}
```

---

where needed.

To use this version, you need to use unicode and load a font that defines the characters ☐ and ☒ (many do not). One option is DejaVu Sans, available for free

here: <https://dejavu-fonts.github.io/Download.html>. Then, add

---

```
\newfontfamily\stix{DejaVu Sans}
```

---

to the preamble of thesis.tex where DejaVu Sans is the name of the font. This will **not** change the font of the whole document. Within the .tex file you can copy and paste:  $\square$  and  $\boxtimes$  from here to create the unchecked and checked boxes. The curly braces and the stix commands are important.

Note, the TERMS AND CONDITIONS section and the signatures are **not** to be included in the final submission. However, the code is provided for you to be able to print out and get signed as needed.

### 10.3 Error: "... does not doesn't match definition..."

First, trying running biber and re-running lualatex a few times. If the error still does not resolve, try deleting all auxillary files and running lualatex --> biber --> lualatex.

### 10.4 Error: Missing .... \_\_um\_group\_begin

It appears to happen when you have something like

---

```
x_\someCommand{whatever}
```

---

To resolve, add curly braces to the sub/super script:

---

```
x_{\someCommand{whatever}}
```

---

### 10.5 Parent-Child Warnings

In the standards for the PDF, there are rules about which tags in the tree should go under which other tags. For example, a table cell has to be a child of a table row. Some of these warnings are not a big deal, but there are ways to fix them.

#### 10.5.1 'P/pdf2' --> 'float/latex'

This warning can appear with some floats - especially algorithms. This is easily remedied by adding a blank line before beginalgorithm or other kind of floating environment if needed.

### 10.5.2 Reference -- > Formula

This is caused by math in caption or header (which then ends up in the list of figures/table/contents). The PDF standards were modified in 2025 to allow this. However, LaTeX has not yet been updated. I would suggest leaving it as is. However, if it bothers you, it can be worked-around.

If it is caused by math in a caption, wrap the formula in a Span. For example,

---

```
words
  {\tagstructbegin{tag=Span}$math$\tagstructend\tagmcent\tagmcbegin{}}
more words
```

---

If it is caused by math in a header, you should already be using texorpdfstring. Put the Span inside the tex argument:

---

```
\section{ words \texorpdfstring{ {
  \tagstructbegin{tag=Span}$math$\tagstructend\tagmcent\tagmcbegin{}}
} }{<plain text for the pdf metadata> more words }
```

---

Notice, all of

---

```
\tagstructbegin{tag=Span}$math$\tagstructend\tagmcent\tagmcbegin{}
```

---

is wrapped in a seemingly-extraneous set of .... This is necessary.

## 10.6 Warning: Patching footnotes failed.

Do not worry about this warning.

## 11 Thesis.tex Breakdown

---

```
%Required:DocumentMetadata turns on tagging
\DocumentMetadata{
  lang=en,
  tagging=on,
  pdfversion=2.0,
  pdfstandard=ua-2,
  pdfstandard=a-4f,
  %uncompress %can be helpful for debugging
```



```

}

%Optional:Does not put end at the end of algorithm
\PassOptionsToPackage{noend}{algpseudocode}

%12 pt font, loads math and algorithms packages
\documentclass[12pt,math-packages,algorithms-packages]{isuthesisstaged}

\usepackage{multirow}%Optional:allows multirow cells in table
\usepackage{pdfscape}%Optional:supports landscape pages

%Optional:Defines Theorem,Definition,Case,etc.
\usepackage{templatedTheoremTypes}

%Sets libertine as the font (uses unicode)
\usepackage[libertinus]{fontsetup}

%Remaps \bm to to \symbf for bold
\let\bm\symbf

%Required: biblatex
%Optional:natbib option - allows the use of natbib-style commands
%Optional:style=authoryear - can be set to preferred style
%In Journal theses, refsection=chapter is required because each
%chapter is separate. In Traditional style, refsection is omitted
%because there is just one bibliography
\usepackage[natbib=true,refsection=chapter,style=authoryear]{biblatex}
\addbibresource{thesisAccessTest.bib}%adds the bib file
\setlength{\bibitemsep}{13.2pt}%changes separation between bib items

%Set the author - to be modified as appropriate
\newcommand{\theAuthor}{Alice Wonder}
%Set the title
\twoLineTitle{This is the title of a thesis
submitted to Iowa State University on the first line}{
Second line, only the first letter of
the first word and names
are capitalized!}

%%The following set the author and title in the thesis

```

```

% and in the PDF metadata. No editing required.
\author{\theAuthor}
\title{\titleWithLineBreak}
\usepackage[linktocpage=true,pdfauthor={\theAuthor},pdftitle={\titleWithoutBreak},]{hyperref}
\hypersetup{colorlinks=true,linkcolor=blue,citecolor=blue,filecolor=blue,urlcolor=blue,bookmarks}
\usepackage{bookmark}

%Optional nomenclature package
\usepackage[notintoc,english]{nomencl}

%Optional: Tikz package for figures
\usepackage{tikz}

\begin{document}
\include{Preface/titlepage}%Required:titlepage.tex is included
\frontmattersetup%ensures all preliminary pages are formatted correctly

\include{Preface/dedication}%Optional:Dedication

\tableofcontentsTagged%Required:loads the table of contents
\cleardoublepage \phantomsection
\pagebreak %ensures newpage

\listoftablesTagged %remove if no tables, otherwise required

\cleardoublepage \phantomsection
\listoffiguresTagged %remove if no figures, otherwise required

%Optional nomenclature
%\cleardoublepage \phantomsection
%\nomenclatureTagged

%Required: Adds Chapter in front of chapter on TOC
\addtocontents{toc}{\def\protect\@chapapp{CHAPTER\ }}

%Optional Acknowledgements
\cleardoublepage \phantomsection
\include{Preface/acknowl}
%Required thesis abstract

```

```
\cleardoublepage \phantomsection
\include{Preface/abstract}
\newpage
\pagenumbering{arabic}
\pagestyle{fancy}%Required:helps set page numbering
%body of the thesis here
\tagtool{flush-floats=subsection}% to keep floats where they are
    supposed to be in the tagging tree
\clearpage
\pagebreak
\end{document}
```

---