

# Classification

CISC 7026: Introduction to Deep Learning

University of Macau

Many problems in ML can be reduced to **regression** or **classification**

Many problems in ML can be reduced to **regression** or **classification**

**Regression** asks how many

Many problems in ML can be reduced to **regression** or **classification**

**Regression** asks how many

- How much money will I make?

Many problems in ML can be reduced to **regression** or **classification**

**Regression** asks how many

- How much money will I make?
- How much rain will there be tomorrow?

Many problems in ML can be reduced to **regression** or **classification**

**Regression** asks how many

- How much money will I make?
- How much rain will there be tomorrow?
- How far away is this object?

Many problems in ML can be reduced to **regression** or **classification**

**Regression** asks how many

- How much money will I make?
- How much rain will there be tomorrow?
- How far away is this object?

**Classification** asks which one

Many problems in ML can be reduced to **regression** or **classification**

**Regression** asks how many

- How much money will I make?
- How much rain will there be tomorrow?
- How far away is this object?

**Classification** asks which one

- Is this a dog or muffin?



Many problems in ML can be reduced to **regression** or **classification**

**Regression** asks how many

- How much money will I make?
- How much rain will there be tomorrow?
- How far away is this object?

**Classification** asks which one

- Is this a dog or muffin?
- Will it rain tomorrow? Yes or no?

Many problems in ML can be reduced to **regression** or **classification**

**Regression** asks how many

- How much money will I make?
- How much rain will there be tomorrow?
- How far away is this object?

**Classification** asks which one

- Is this a dog or muffin?
- Will it rain tomorrow? Yes or no?
- What color is this object?

Many problems in ML can be reduced to **regression** or **classification**

**Regression** asks how many

- How much money will I make?
- How much rain will there be tomorrow?
- How far away is this object?

**Classification** asks which one

- Is this a dog or muffin?
- Will it rain tomorrow? Yes or no?
- What color is this object?

Now let us look at classification

# Classification

1. Define an example problem

# Classification

1. Define an example problem
2. Primer on probability

# Classification

1. Define an example problem
2. Primer on probability
3. Define our machine learning model  $f$

# Classification

1. Define an example problem
2. Primer on probability
3. Define our machine learning model  $f$
4. Define a loss function  $\mathcal{L}$

# Classification

1. Define an example problem
2. Primer on probability
3. Define our machine learning model  $f$
4. Define a loss function  $\mathcal{L}$
5. Use  $\mathcal{L}$  to learn the parameters  $\theta$  of  $f$

Does this look familiar?



# Classification

1. **Define an example problem**
2. Primer on probability
3. Define our machine learning model  $f$
4. Define a loss function  $\mathcal{L}$
5. Use  $\mathcal{L}$  to learn the parameters  $\theta$  of  $f$

**Task:** Given an pictures of clothes, predict their text descriptions

**Task:** Given an pictures of clothes, predict their text descriptions



**Task:** Given an pictures of clothes, predict their text descriptions



$Y$  : {T-shirt, Trouser, Pullover, Dress, Coat,  
Sandal, Shirt, Sneaker, Bag, Ankle boot}

**Approach:** Learn the parameters  $\theta$  that produce **class probabilities**

**Task:** Given an pictures of clothes, predict their text descriptions



$Y$  : {T-shirt, Trouser, Pullover, Dress, Coat,  
Sandal, Shirt, Sneaker, Bag, Ankle boot}

**Approach:** Learn the parameters  $\theta$  that produce **class probabilities**

$$f(x, \theta) = P(y \mid x) = P\left(\text{boot} \mid \begin{array}{c} \text{ankle boot} \\ \text{pullover} \end{array}\right)$$

**Task:** Given an pictures of clothes, predict their text descriptions



$Y : \{\text{T-shirt, Trouser, Pullover, Dress, Coat, Sandal, Shirt, Sneaker, Bag, Ankle boot}\}$

**Approach:** Learn the parameters  $\theta$  that produce **class probabilities**

$$f(x, \theta) = P(y \mid x) = P\left(\text{boot} \mid \text{img}\right)$$

# Classification

1. **Define an example problem**
2. Primer on probability
3. Define our machine learning model  $f$
4. Define a loss function  $\mathcal{L}$
5. Use  $\mathcal{L}$  to learn the parameters  $\theta$  of  $f$

# Classification

1. Define an example problem
2. **Primer on probability**
3. Define our machine learning model  $f$
4. Define a loss function  $\mathcal{L}$
5. Use  $\mathcal{L}$  to learn the parameters  $\theta$  of  $f$



In probability, we have **experiments** and **outcomes**

In probability, we have **experiments** and **outcomes**

An experiment yields one of many possible outcomes

In probability, we have **experiments** and **outcomes**

An experiment yields one of many possible outcomes

Flip a coin

Heads

In probability, we have **experiments** and **outcomes**

An experiment yields one of many possible outcomes

Flip a coin

Heads

Walk outside

Rain

In probability, we have **experiments** and **outcomes**

An experiment yields one of many possible outcomes

Flip a coin	Heads
Walk outside	Rain
Grab clothing from closet	Coat

In probability, we have **experiments** and **outcomes**

An experiment yields one of many possible outcomes

Flip a coin	Heads
Walk outside	Rain
Grab clothing from closet	Coat

The **sample space**  $S$  defines all possible outcomes for an experiment

The **sample space**  $S$  defines all possible outcomes for an experiment

Flip a coin

$$S = \{\text{heads}, \text{tails}\}$$



The **sample space**  $S$  defines all possible outcomes for an experiment

Flip a coin

$$S = \{\text{heads}, \text{tails}\}$$

Walk outside

$$S = \{\text{rain}, \text{sun}, \text{wind}, \text{cloud}\}$$

The **sample space**  $S$  defines all possible outcomes for an experiment

Flip a coin

$$S = \{\text{heads, tails}\}$$

Walk outside

$$S = \{\text{rain, sun, wind, cloud}\}$$

Grab clothing from closet

$$S = \{\text{T-shirt, Trouser, Pullover, Dress, Coat, Sandal, Shirt, Sneaker, Bag, Ankle boot}\}$$

An **event** is a subset of the sample space

An **event** is a subset of the sample space

Flip a coin

$\{\text{heads}\}$

An **event** is a subset of the sample space

Flip a coin

$\{\text{heads}\}$

Walk outside

$\{\text{rain, cloud, wind}\}$

An **event** is a subset of the sample space

Flip a coin

$\{\text{heads}\}$

Walk outside

$\{\text{rain, cloud, wind}\}$

Grab clothing from closet

$\{\text{Sneaker}\}$

The **probability** measures how likely an event is to occur

The **probability** measures how likely an event is to occur

The probability must be between 0 (never occurs) and 1 (always occurs)



The **probability** measures how likely an event is to occur

The probability must be between 0 (never occurs) and 1 (always occurs)

$$0 \leq P(A) \leq 1; \quad \forall A \in \mathcal{S}$$

The **probability** measures how likely an event is to occur

The probability must be between 0 (never occurs) and 1 (always occurs)

$$0 \leq P(A) \leq 1; \quad \forall A \in \mathcal{S}$$

The probabilities must sum to one

The **probability** measures how likely an event is to occur

The probability must be between 0 (never occurs) and 1 (always occurs)

$$0 \leq P(A) \leq 1; \quad \forall A \in S$$

The probabilities must sum to one

$$\sum_{A \in S} P(A) = 1$$

Flip a coin

$$P(\text{Heads}) = \frac{1}{2}$$

Flip a coin

$$P(\text{Heads}) = \frac{1}{2}$$

Walk outside

$$P(\text{Rain}) = 0.05$$

Flip a coin

$$P(\text{Heads}) = \frac{1}{2}$$

Walk outside

$$P(\text{Rain}) = 0.05$$

Grab clothing from closet

$$P(\text{Dress}) = 0$$

Flip a coin

$$P(\text{Heads}) = \frac{1}{2}$$

Walk outside

$$P(\text{Rain}) = 0.05$$

Grab clothing from closet

$$P(\text{Dress}) = 0$$

For **mutually exclusive** events, we can sum together probabilities



For **mutually exclusive** events, we can sum together probabilities

$$P(A \cup B) = P(A) + P(B)$$

For **mutually exclusive** events, we can sum together probabilities

$$P(A \cup B) = P(A) + P(B)$$

Grab clothing from closet

$$P(\text{Shirt}) = 0.1, P(\text{Bag}) = 0.05$$

$$P(\text{Shirt} \cup \text{Bag}) = 0.15$$

Be careful!

For **mutually exclusive** events, we can sum together probabilities

$$P(A \cup B) = P(A) + P(B)$$

Grab clothing from closet

$$P(\text{Shirt}) = 0.1, P(\text{Bag}) = 0.05$$

$$P(\text{Shirt} \cup \text{Bag}) = 0.15$$

Be careful!

Walk outside

$$P(\text{Rain}) = 0.05, P(\text{Sun}) = 0.4$$

$$P(\text{Rain} \cup \text{Sun}) \neq 0.45$$

If events are **independent**, we can multiply their probabilities

If events are **independent**, we can multiply their probabilities

$$P(A \cap B) = P(A) \cdot P(B)$$

If events are **independent**, we can multiply their probabilities

$$P(A \cap B) = P(A) \cdot P(B)$$

Be careful!

If events are **independent**, we can multiply their probabilities

$$P(A \cap B) = P(A) \cdot P(B)$$

Be careful!

Flip a coin

$$P(\text{Heads}) = 0.5, P(\text{Tails}) = 0.5$$
$$P(\text{Heads} \cap \text{Tails}) \neq 0.25$$

If events are **independent**, we can multiply their probabilities

$$P(A \cap B) = P(A) \cdot P(B)$$

Be careful!

Flip a coin

$$P(\text{Heads}) = 0.5, P(\text{Tails}) = 0.5$$
$$P(\text{Heads} \cap \text{Tails}) \neq 0.25$$



Events can be **conditionally dependent**

$$P(A \mid B) = \frac{P(A \cap B)}{P(B)}$$

Events can be **conditionally dependent**

$$P(A \mid B) = \frac{P(A \cap B)}{P(B)}$$

$$P(\text{Heads} \cap \text{Tails}) = 0$$

Flip a coin

$$P(\text{Tails}) = 0.5$$

$$P(\text{Heads} \mid \text{Tails}) = \frac{0}{0.5} = 0$$

Events can be **conditionally dependent**

$$P(A \mid B) = \frac{P(A \cap B)}{P(B)}$$

$$P(\text{Heads} \cap \text{Tails}) = 0$$

Flip a coin

$$P(\text{Tails}) = 0.5$$

$$P(\text{Heads} \mid \text{Tails}) = \frac{0}{0.5} = 0$$

$$P(\text{Rain} \cap \text{Cloud}) = 0.2$$

Walk outside

$$P(\text{Cloud}) = 0.4$$

$$P(\text{Rain} \mid \text{Cloud}) = \frac{0.2}{0.4} = 0.5$$

TODO: Random variable, distribution

# Classification

1. Define an example problem
2. **Primer on probability**
3. Define our machine learning model  $f$
4. Define a loss function  $\mathcal{L}$
5. Use  $\mathcal{L}$  to learn the parameters  $\theta$  of  $f$

Relax

Back to the problem...

**Task:** Given a picture of clothes, predict the text description



**Task:** Given a picture of clothes, predict the text description



**Task:** Given a picture of clothes, predict the text description



$Y$  : {T-shirt, Trouser, Pullover, Dress, Coat,  
Sandal, Shirt, Sneaker, Bag, Ankle boot}

**Approach:** Learn the parameters  $\theta$  that produce **event probabilities**

**Task:** Given a picture of clothes, predict the text description



$Y$  : {T-shirt, Trouser, Pullover, Dress, Coat,  
Sandal, Shirt, Sneaker, Bag, Ankle boot}

**Approach:** Learn the parameters  $\theta$  that produce **event probabilities**

$$f(x, \theta) = P(y \mid x) = P\left(\text{boot} \mid \begin{array}{c} \text{ankle boot} \\ \text{pullover} \end{array}\right)$$

**Task:** Given a picture of clothes, predict the text description



$Y$  : {T-shirt, Trouser, Pullover, Dress, Coat,  
Sandal, Shirt, Sneaker, Bag, Ankle boot}

**Approach:** Learn the parameters  $\theta$  that produce **event probabilities**

$$f(x, \theta) = P(y \mid x) = P\left(\text{boot} \mid \begin{array}{c} \text{img alt="Pullover image" data-bbox="645 708 735 865"} \end{array}\right)$$

# Classification

1. Define an example problem
2. Primer on probability
3. **Define our machine learning model  $f$**
4. Define a loss function  $\mathcal{L}$
5. Use  $\mathcal{L}$  to learn the parameters  $\theta$  of  $f$

We will again start with a linear model

We will again start with a linear model

$$f(x, \boldsymbol{\theta}) = f\left(x, \begin{bmatrix} W \\ b \end{bmatrix}\right) = Wx + b$$

We will again start with a linear model

$$f(x, \boldsymbol{\theta}) = f\left(x, \begin{bmatrix} W \\ b \end{bmatrix}\right) = Wx + b$$

However, the probabilities must sum to one which is nonlinear...



We will again start with a linear model

$$f(x, \boldsymbol{\theta}) = f\left(x, \begin{bmatrix} W \\ b \end{bmatrix}\right) = Wx + b$$

However, the probabilities must sum to one which is nonlinear...

We introduce the **softmax** operator to ensure all probabilities sum to 1

We will again start with a linear model

$$f(x, \boldsymbol{\theta}) = f\left(x, \begin{bmatrix} W \\ b \end{bmatrix}\right) = Wx + b$$

However, the probabilities must sum to one which is nonlinear...

We introduce the **softmax** operator to ensure all probabilities sum to 1

The softmax operator is heavily used in machine learning, especially where probabilities pop up

The softmax operator is heavily used in machine learning, especially where probabilities pop up

It maps a vector of real numbers to a vector of probabilities

The softmax operator is heavily used in machine learning, especially where probabilities pop up

It maps a vector of real numbers to a vector of probabilities

$$\text{softmax} : \mathbb{R}^n \mapsto \Delta^{n-1}$$

The softmax operator is heavily used in machine learning, especially where probabilities pop up

It maps a vector of real numbers to a vector of probabilities

$$\text{softmax} : \mathbb{R}^n \mapsto \Delta^{n-1}$$

$$\Delta^{n-1} = \left\{ \begin{bmatrix} p_1 \\ p_2 \\ \vdots \\ p_n \end{bmatrix} \mid \sum_{i=1}^n p_i = 1 \right\}$$

The simplex operator  $\Delta$  just means that the outputs of softmax sum to 1

The softmax operator is heavily used in machine learning, especially where probabilities pop up

It maps a vector of real numbers to a vector of probabilities

$$\text{softmax} : \mathbb{R}^n \mapsto \Delta^{n-1}$$

$$\Delta^{n-1} = \left\{ \begin{bmatrix} p_1 \\ p_2 \\ \vdots \\ p_n \end{bmatrix} \mid \sum_{i=1}^n p_i = 1 \right\}$$

The simplex operator  $\Delta$  just means that the outputs of softmax sum to 1

$$\text{softmax}\left(\begin{bmatrix} x_1 \\ \vdots \\ x_n \end{bmatrix}\right) = \frac{e^{x_i}}{\sum_{j=1}^n e^{x_j}} = \begin{bmatrix} \frac{e^{x_1}}{e^{x_1} + e^{x_2} + \dots e^{x_n}} \\ \frac{e^{x_2}}{e^{x_1} + e^{x_2} + \dots e^{x_n}} \\ \vdots \\ \frac{e^{x_n}}{e^{x_1} + e^{x_2} + \dots e^{x_n}} \end{bmatrix}$$



Using the softmax function, we learn the probability for each class/event

$$f(\mathbf{x}, \boldsymbol{\theta}) : \mathbb{Z}^n \mapsto \Delta^{|Y| - 1}$$

$$f(x, \boldsymbol{\theta}) = f\left(x, \begin{bmatrix} W \\ b \end{bmatrix}\right) = \text{softmax}(Wx + b)$$



Using the softmax function, we learn the probability for each class/event

$$f(\mathbf{x}, \boldsymbol{\theta}) : \mathbb{Z}^n \mapsto \Delta^{|Y| - 1}$$

$$f(x, \boldsymbol{\theta}) = f\left(x, \begin{bmatrix} W \\ b \end{bmatrix}\right) = \text{softmax}(Wx + b)$$

Each output dimension determines a specific class/event probability

$$f(x, \boldsymbol{\theta}) = \begin{bmatrix} P(\text{Ankle boot} \mid \text{Lee}) \\ P(\text{Bag} \mid \text{Lee}) \\ \vdots \end{bmatrix}$$



**Question:** Why do we output probabilities instead of just a one-hot vector

$$f(\mathbf{x}, \boldsymbol{\theta}) = \begin{bmatrix} P(\text{Shirt} \mid \text{img}) \\ P(\text{Bag} \mid \text{img}) \end{bmatrix}$$

$$f(\mathbf{x}, \boldsymbol{\theta}) = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

**Answer:** We do not always know the correct answer. There is always uncertainty.

Relax

# Classification

1. Define an example problem
2. Primer on probability
3. **Define our machine learning model  $f$**
4. Define a loss function  $\mathcal{L}$
5. Use  $\mathcal{L}$  to learn the parameters  $\theta$  of  $f$

# Classification

1. Define an example problem
2. Primer on probability
3. Define our machine learning model  $f$
4. **Define a loss function  $\mathcal{L}$**
5. Use  $\mathcal{L}$  to learn the parameters  $\theta$  of  $f$

We use squared error for regression, what about classification?



We use squared error for regression, what about classification?

$$f(\mathbf{x}_i, \boldsymbol{\theta}) = \begin{bmatrix} P(\text{Shirt} \mid \text{Lee}) \\ P(\text{Bag} \mid \text{Lee}) \end{bmatrix} = \begin{bmatrix} 0.6 \\ 0.4 \end{bmatrix}$$

We use squared error for regression, what about classification?

$$f(\mathbf{x}_i, \boldsymbol{\theta}) = \begin{bmatrix} P(\text{Shirt} \mid \text{img}) \\ P(\text{Bag} \mid \text{img}) \end{bmatrix} = \begin{bmatrix} 0.6 \\ 0.4 \end{bmatrix}$$

$$\mathbf{y}_i = \begin{bmatrix} P(\text{Shirt} \mid \text{img}) \\ P(\text{Bag} \mid \text{img}) \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

We use squared error for regression, what about classification?

$$f(\mathbf{x}_i, \boldsymbol{\theta}) = \begin{bmatrix} P(\text{Shirt} \mid \text{img}) \\ P(\text{Bag} \mid \text{img}) \end{bmatrix} = \begin{bmatrix} 0.6 \\ 0.4 \end{bmatrix}$$

$$\mathbf{y}_i = \begin{bmatrix} P(\text{Shirt} \mid \text{img}) \\ P(\text{Bag} \mid \text{img}) \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

$$f(\mathbf{x}_i, \boldsymbol{\theta}) = \begin{bmatrix} 0.6 \\ 0.4 \end{bmatrix}, \mathbf{y}_i = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

$$f(\mathbf{x}_i, \boldsymbol{\theta}) = \begin{bmatrix} 0.6 \\ 0.4 \end{bmatrix}, \mathbf{y}_i = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

We could compute the sum of square errors

$$f(\mathbf{x}_i, \boldsymbol{\theta}) = \begin{bmatrix} 0.6 \\ 0.4 \end{bmatrix}, \mathbf{y}_i = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

We could compute the sum of square errors

$$(0.6 - 1)^2 + (0.4 - 0)^2$$

$$f(\mathbf{x}_i, \boldsymbol{\theta}) = \begin{bmatrix} 0.6 \\ 0.4 \end{bmatrix}, \mathbf{y}_i = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

We could compute the sum of square errors

$$(0.6 - 1)^2 + (0.4 - 0)^2$$

In practice, this does not work very well

$$f(\mathbf{x}_i, \boldsymbol{\theta}) = \begin{bmatrix} 0.6 \\ 0.4 \end{bmatrix}, \mathbf{y}_i = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

We could compute the sum of square errors

$$(0.6 - 1)^2 + (0.4 - 0)^2$$

In practice, this does not work very well

Instead, we use the **cross-entropy loss**



$$f(\mathbf{x}_i, \boldsymbol{\theta}) = \begin{bmatrix} 0.6 \\ 0.4 \end{bmatrix}, \mathbf{y}_i = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$

We could compute the sum of square errors

$$(0.6 - 1)^2 + (0.4 - 0)^2$$

In practice, this does not work very well

Instead, we use the **cross-entropy loss**

Let us derive it

We can model  $f(\boldsymbol{x}, \boldsymbol{\theta})$  and  $\boldsymbol{y}$  as probability distributions

We can model  $f(\mathbf{x}, \boldsymbol{\theta})$  and  $\mathbf{y}$  as probability distributions

How do we measure the difference between probability distributions?

We can model  $f(x, \theta)$  and  $y$  as probability distributions


How do we measure the difference between probability distributions?


We use the **Kullback-Leibler Divergence (KL)**

We can model  $f(x, \theta)$  and  $y$  as probability distributions

How do we measure the difference between probability distributions?

We use the **Kullback-Leibler Divergence (KL)**





$$\text{KL}(P, Q) = \sum_i P(i) \log \frac{P(i)}{Q(i)}$$

TODO: Should be  $f(y_i \mid x, \theta)$

$$\text{KL}(P, Q) = \sum_i P(i) \log \frac{P(i)}{Q(i)} \quad \text{KL divergence}$$





TODO: Should be  $f(y_i \mid x, \theta)$

$$\text{KL}(P, Q) = \sum_i P(i) \log \frac{P(i)}{Q(i)} \quad \text{KL divergence}$$

$$\text{KL}(P(\mathbf{y} \mid \mathbf{x}), f(\mathbf{x}, \boldsymbol{\theta})) = \sum_{y \in Y} P(y \mid \mathbf{x}) \log \frac{P(y \mid \mathbf{x})}{f(\mathbf{x}, \boldsymbol{\theta})} \quad \text{Plug in } f, y$$



TODO: Should be  $f(y_i \mid x, \theta)$

$$\text{KL}(P, Q) = \sum_i P(i) \log \frac{P(i)}{Q(i)} \quad \text{KL divergence}$$

$$\text{KL}(P(\mathbf{y} \mid \mathbf{x}), f(\mathbf{x}, \boldsymbol{\theta})) = \sum_{y \in Y} P(y \mid \mathbf{x}) \log \frac{P(y \mid \mathbf{x})}{f(\mathbf{x}, \boldsymbol{\theta})} \quad \text{Plug in } f, y$$

$$\text{KL}(P(\mathbf{y} \mid \mathbf{x}), f(\mathbf{x}, \boldsymbol{\theta})) = \sum_{y \in Y} P(y \mid \mathbf{x}) [\log P(y \mid \mathbf{x}) - \log f(\mathbf{x}, \boldsymbol{\theta})] \quad \text{Log rule}$$



TODO: Should be  $f(y_i \mid x, \theta)$

$$\text{KL}(P, Q) = \sum_i P(i) \log \frac{P(i)}{Q(i)} \quad \text{KL divergence}$$

$$\text{KL}(P(\mathbf{y} \mid \mathbf{x}), f(\mathbf{x}, \boldsymbol{\theta})) = \sum_{y \in Y} P(y \mid \mathbf{x}) \log \frac{P(y \mid \mathbf{x})}{f(\mathbf{x}, \boldsymbol{\theta})} \quad \text{Plug in } f, y$$

$$\text{KL}(P(\mathbf{y} \mid \mathbf{x}), f(\mathbf{x}, \boldsymbol{\theta})) = \sum_{y \in Y} P(y \mid \mathbf{x}) [\log P(y \mid \mathbf{x}) - \log f(\mathbf{x}, \boldsymbol{\theta})] \quad \text{Log rule}$$

$$= \sum_{y \in Y} P(y \mid \mathbf{x}) \log P(y \mid \mathbf{x}) - \sum_{y \in Y} P(y \mid \mathbf{x}) \log f(\mathbf{x}, \boldsymbol{\theta}) \quad \text{Split sum}$$



TODO: Should be  $f(y_i \mid x, \theta)$

$$\text{KL}(P, Q) = \sum_i P(i) \log \frac{P(i)}{Q(i)} \quad \text{KL divergence}$$

$$\text{KL}(P(\mathbf{y} \mid \mathbf{x}), f(\mathbf{x}, \boldsymbol{\theta})) = \sum_{y \in Y} P(y \mid \mathbf{x}) \log \frac{P(y \mid \mathbf{x})}{f(\mathbf{x}, \boldsymbol{\theta})} \quad \text{Plug in } f, y$$

$$\text{KL}(P(\mathbf{y} \mid \mathbf{x}), f(\mathbf{x}, \boldsymbol{\theta})) = \sum_{y \in Y} P(y \mid \mathbf{x}) [\log P(y \mid \mathbf{x}) - \log f(\mathbf{x}, \boldsymbol{\theta})] \quad \text{Log rule}$$

$$= \sum_{y \in Y} P(y \mid \mathbf{x}) \log P(y \mid \mathbf{x}) - \sum_{y \in Y} P(y \mid \mathbf{x}) \log f(\mathbf{x}, \boldsymbol{\theta}) \quad \text{Split sum}$$

$$= - \sum_{y \in Y} P(y \mid \mathbf{x}) \log f(\mathbf{x}, \boldsymbol{\theta}) \quad \text{First term constant}$$





TODO: Should be  $f(y_i \mid x, \theta)$

$$\text{KL}(P, Q) = \sum_i P(i) \log \frac{P(i)}{Q(i)} \quad \text{KL divergence}$$

$$\text{KL}(P(\mathbf{y} \mid \mathbf{x}), f(\mathbf{x}, \boldsymbol{\theta})) = \sum_{y \in Y} P(y \mid \mathbf{x}) \log \frac{P(y \mid \mathbf{x})}{f(\mathbf{x}, \boldsymbol{\theta})} \quad \text{Plug in } f, y$$

$$\text{KL}(P(\mathbf{y} \mid \mathbf{x}), f(\mathbf{x}, \boldsymbol{\theta})) = \sum_{y \in Y} P(y \mid \mathbf{x}) [\log P(y \mid \mathbf{x}) - \log f(\mathbf{x}, \boldsymbol{\theta})] \quad \text{Log rule}$$

$$= \sum_{y \in Y} P(y \mid \mathbf{x}) \log P(y \mid \mathbf{x}) - \sum_{y \in Y} P(y \mid \mathbf{x}) \log f(\mathbf{x}, \boldsymbol{\theta}) \quad \text{Split sum}$$

$$= - \sum_{y \in Y} P(y \mid \mathbf{x}) \log f(\mathbf{x}, \boldsymbol{\theta}) \quad \text{First term constant}$$

This is the cross-entropy loss!

$$\mathcal{L}(\boldsymbol{x}, \boldsymbol{y}, \boldsymbol{\theta}) = - \sum_{y \in Y} P(y \mid \boldsymbol{x}) \log f(\boldsymbol{x}, \boldsymbol{\theta})$$

$$\mathcal{L}(\boldsymbol{x}, \boldsymbol{y}, \boldsymbol{\theta}) = - \sum_{y \in Y} P(y \mid \boldsymbol{x}) \log f(\boldsymbol{x}, \boldsymbol{\theta})$$

By minimizing the loss, we make  $f(\boldsymbol{x}, \boldsymbol{\theta})$  output the same probability distribution as  $\boldsymbol{y}$

$$\mathcal{L}(\mathbf{x}, \mathbf{y}, \boldsymbol{\theta}) = - \sum_{y \in Y} P(y \mid \mathbf{x}) \log f(\mathbf{x}, \boldsymbol{\theta})$$

By minimizing the loss, we make  $f(\mathbf{x}, \boldsymbol{\theta})$  output the same probability distribution as  $\mathbf{y}$

$$\min_{\boldsymbol{\theta}} \mathcal{L}(\mathbf{x}, \mathbf{y}, \boldsymbol{\theta}) = \min_{\boldsymbol{\theta}} \left[ - \sum_{y \in Y} P(y \mid \mathbf{x}) \log f(\mathbf{x}, \boldsymbol{\theta}) \right]$$

$$\mathcal{L}(\mathbf{x}, \mathbf{y}, \boldsymbol{\theta}) = - \sum_{y \in Y} P(y \mid \mathbf{x}) \log f(\mathbf{x}, \boldsymbol{\theta})$$

By minimizing the loss, we make  $f(\mathbf{x}, \boldsymbol{\theta})$  output the same probability distribution as  $\mathbf{y}$

$$\min_{\boldsymbol{\theta}} \mathcal{L}(\mathbf{x}, \mathbf{y}, \boldsymbol{\theta}) = \min_{\boldsymbol{\theta}} \left[ - \sum_{y \in Y} P(y \mid \mathbf{x}) \log f(\mathbf{x}, \boldsymbol{\theta}) \right]$$

$$f(\mathbf{x}, \boldsymbol{\theta}) = P(\mathbf{y} \mid \mathbf{x}) = P \left( \begin{bmatrix} \text{boot} \\ \text{dress} \\ \vdots \end{bmatrix} \mid \text{img} \right)$$

$$\mathcal{L}(\mathbf{x}, \mathbf{y}, \boldsymbol{\theta}) = - \sum_{y \in Y} P(y \mid \mathbf{x}) \log f(\mathbf{x}, \boldsymbol{\theta})$$

By minimizing the loss, we make  $f(\mathbf{x}, \boldsymbol{\theta})$  output the same probability distribution as  $\mathbf{y}$

$$\min_{\boldsymbol{\theta}} \mathcal{L}(\mathbf{x}, \mathbf{y}, \boldsymbol{\theta}) = \min_{\boldsymbol{\theta}} \left[ - \sum_{y \in Y} P(y \mid \mathbf{x}) \log f(\mathbf{x}, \boldsymbol{\theta}) \right]$$

$$f(\mathbf{x}, \boldsymbol{\theta}) = P(\mathbf{y} \mid \mathbf{x}) = P \left( \begin{bmatrix} \text{boot} \\ \text{dress} \\ \vdots \end{bmatrix} \mid \text{img} \right)$$

Our loss was just for a single image



Our loss was just for a single image

$$\min_{\theta} \mathcal{L}(\boldsymbol{x}, \boldsymbol{y}, \boldsymbol{\theta}) = \min_{\theta} \left[ - \sum_{y \in Y} P(y \mid \boldsymbol{x}) \log f(\boldsymbol{x}, \boldsymbol{\theta}) \right]$$

Our loss was just for a single image

$$\min_{\theta} \mathcal{L}(\boldsymbol{x}, \boldsymbol{y}, \boldsymbol{\theta}) = \min_{\theta} \left[ - \sum_{y \in Y} P(y \mid \boldsymbol{x}) \log f(\boldsymbol{x}, \boldsymbol{\theta}) \right]$$

Find the parameters over all images

Our loss was just for a single image

$$\min_{\theta} \mathcal{L}(\mathbf{x}, \mathbf{y}, \theta) = \min_{\theta} \left[ - \sum_{y \in Y} P(y \mid \mathbf{x}) \log f(\mathbf{x}, \theta) \right]$$

Find the parameters over all images

$$\min_{\theta} \mathcal{L}(\mathbf{x}, \mathbf{y}, \theta) = \min_{\theta} \left[ - \sum_{i=1}^n \sum_{y_i \in Y} P(y_i \mid \mathbf{x}_i) \log f(\mathbf{x}_i, \theta) \right]$$

Our loss was just for a single image

$$\min_{\theta} \mathcal{L}(\mathbf{x}, \mathbf{y}, \theta) = \min_{\theta} \left[ - \sum_{y \in Y} P(y \mid \mathbf{x}) \log f(\mathbf{x}, \theta) \right]$$

Find the parameters over all images

$$\min_{\theta} \mathcal{L}(\mathbf{x}, \mathbf{y}, \theta) = \min_{\theta} \left[ - \sum_{i=1}^n \sum_{y_i \in Y} P(y_i \mid \mathbf{x}_i) \log f(\mathbf{x}_i, \theta) \right]$$

# Classification

1. Define an example problem
2. Primer on probability
3. Define our machine learning model  $f$
4. **Define a loss function  $\mathcal{L}$**
5. Use  $\mathcal{L}$  to learn the parameters  $\theta$  of  $f$

Relax

# Classification

1. Define an example problem
2. Primer on probability
3. Define our machine learning model  $f$
4. Define a loss function  $\mathcal{L}$
5. **Use  $\mathcal{L}$  to learn the parameters  $\theta$  of  $f$**

Unlike linear regression, we use a softmax to model probabilities



Unlike linear regression, we use a softmax to model probabilities

$$f(x, \boldsymbol{\theta}) = f\left(x, \begin{bmatrix} W \\ b \end{bmatrix}\right) = \text{softmax}(Wx + b)$$

Unlike linear regression, we use a softmax to model probabilities

$$f(x, \boldsymbol{\theta}) = f\left(x, \begin{bmatrix} W \\ b \end{bmatrix}\right) = \text{softmax}(Wx + b)$$

There is no closed-form solution!

Unlike linear regression, we use a softmax to model probabilities

$$f(x, \boldsymbol{\theta}) = f\left(x, \begin{bmatrix} W \\ b \end{bmatrix}\right) = \text{softmax}(Wx + b)$$

There is no closed-form solution!

We need to use iterative solvers to find theta

Unlike linear regression, we use a softmax to model probabilities

$$f(x, \theta) = f\left(x, \begin{bmatrix} W \\ b \end{bmatrix}\right) = \text{softmax}(Wx + b)$$

There is no closed-form solution!

We need to use iterative solvers to find theta

We will come back to this when discussing neural networks