



# Ambisonics Decoder Description (.ADD)

Presented \* by VDT.

## Developing a new file format for Ambisonics decoding matrices

G. Arlauskas, J. Ohland, H. Schaar

*University of Applied Sciences Darmstadt, Germany, Email: jonas.ohland@stud.h-da.de*

### Abstract

Different software solutions have been developed for the calculation and implementation of Ambisonics decoding matrices. The present paper presents and describes a new data file format which can be used as an intermediate between solutions.

Currently available software solutions use particular data conventions causing difficult compatibility and exchangeability. In the present work an open-source toolkit is developed for storing, handling and using Ambisonics decoding matrices. The toolkit includes tools for conversion from common matrix data conventions to the ADD-format and back, calculating decoding matrices, decoding Ambisonics signals and extracting existing matrices from external decoding tools.

The new ADD-format and toolkit enables increased flexibility in production workflows and eliminates the drawbacks and limitations regarding compatibility between software solutions.

## 1. Introduction

### 1.1. Spatial Audio

Spatial Audio or 3D Audio is either achieved by having multiple speakers placed around, as well as above (and in some cases below) the listener or by using headphones with a head related transfer function (HRTF). This enables the creation of immersive audio experiences.

### 1.2. Ambisonics

Ambisonics is a 3D audio representation approach based on spherical harmonics. Compared to traditional multichannel audio where each channel contains the signal for one loudspeaker, in Ambisonics the channels contain information about certain properties of the acoustic field.

It was first developed in the 1970s by the British National Research Development Corporation for Broadcasting purposes.<sup>[citation needed]</sup> Recently the format has found new popularity as higher order implementations in virtual reality applications and irregular multichannel setups.

## 2. Ambisonics Encoding/Decoding

### 2.1. Spherical Harmonics

The Legendre polynomials  $P_n(x)$  are solutions to Legendre's differential equation and can be expressed with a Rodrigues representation

$$P_n(x) = \frac{1}{2^n n!} \frac{d^n}{dx^n} (x^2 - 1)^n$$

This is a Placeholder for Jonas' math wisdom

### 2.2. Normalization

For successful reconstruction of the sound field encoding and decoding have to agree on the method by which the spherical harmonic components are normalized. There are different approaches to calculating the normalization factor  $N$  of ambisonics channel  $m$  with order  $\ell$ . In the following the most common ones are described.

#### 2.2.1. SN3D

With SN3D or Schmidt semi-normalisation no component will ever exceed the peak value of the 0th order component

\* Please note that the papers at ICSA can be published by VDT, in print, online and as PDF download.

for single point sources. [4] Since the proposal of the AmbiX format it has been widely adopted in modern ambisonics software development.

$$N_{\ell,m}^{SN3D} = \sqrt{(2 - \delta_m) \frac{\ell - |m|!}{\ell + |m|!}}, \delta_m \begin{cases} 1 & \text{if } m = 0 \\ 1 & \text{if } m \neq 0 \end{cases}$$

### 2.2.2. N3D

N3D differs from SN3D only by a scaling factor. It ensures equal power of the encoded components in the case of a perfectly diffuse 3D field.[3] It is used in MPEG-H.

$$N_{\ell,m}^{N3D} = N_{\ell,m}^{SN3D} \sqrt{2\ell + 1}$$

(For further information on normalization see [2])

## 3. Motivation

When working with Ambisonics in irregular multichannel setups, the choice of decoder is a key component in the quality of the experience a listener might have. So having the option to easily work with multiple tools will be very helpful in designing a listening environment which is suitable for ones needs.

In the current field of ambisonics software tools, there is no agreed upon standard for saving and handling ambisonics decoding matrix data, which makes working with multiple software solutions difficult.

The creation of a software library which can be implemented by plugin developers will enable widespread adoption of the file format. For software which doesn't include *.add* functionality there are user facing tools for converting between file types. A list of compatible file types can be found in the *.add* specification [1]

## 4. Implementation

Lorem Ipsum

## 5. Conclusion

The final manuscript should be submitted in electronic form to the editors of the proceedings prior to the conference. In exceptional circumstances a later date must be agreed by the editors. If you have any questions, please ask the program team of ICSA (icsa-proceedings@imt.rz.tu-ilmenau.de).

Authors must make sure that they hold the copyrights of all of content in their manuscript. This is particularly important to any kind of picture, drawing etc.

Authors should not include any company logo or advertising information of a real product in the manuscript; otherwise the paper will be rejected from the Proceedings and handled like a Product presentation.

## 6. References

- [1] Gabriel Arlauskas, Jonas Ohland, and Henning Schaar. 2019. *.add* file format - specification.
- [2] Thibaut Carpentier. 2017. Normalization schemes in ambisonic: does it matter?
- [3] Jérôme Daniel. 2001. Représentation de champs acoustiques, application à la transmission et à la reproduction de scènes sonores complexes dans un contexte multimédia.
- [4] Christian Nachbar, Franz Zotter, and Etienne Deleflie. 2011. Ambix - a suggested ambisonics format.