

Mixed Hybrid Finite Element Eddington Acceleration of Discrete Ordinates Source Iteration

ANS Student Conference

Mathematics and Computation

Samuel S. Olivier

April 10, 2017

Department of Nuclear Engineering, Texas A&M University



NUCLEAR ENGINEERING
TEXAS A&M UNIVERSITY

1. Motivation
2. Source Iteration Background
3. Eddington Acceleration
4. Results
5. Conclusions

Motivation

Motivation

Radiation Hydrodynamics

- Describes the effects of emission, absorption, scattering on fluid momentum and energy
- Required in high energy density laboratory experiments (NIF, Z Machine) and astrophysics

Mixed Hybrid Finite Element Method (MHFEM) hydrodynamics

Problems

- MHFEM and first-order form of transport are incompatible \Rightarrow can't use linear acceleration scheme
- Radiation transport is expensive

Goal

Develop a transport algorithm that

1. Accelerates Discrete Ordinates Source Iteration
2. Bridges Linear Discontinuous Galerkin (LDG) transport and MHFEM multiphysics

Motivation

Radiation Hydrodynamics

- Describes the effects of emission, absorption, scattering on fluid momentum and energy
- Required in high energy density laboratory experiments (NIF, Z Machine) and astrophysics

Mixed Hybrid Finite Element Method (MHFEM) hydrodynamics

Problems

- MHFEM and first-order form of transport are incompatible \Rightarrow can't use linear acceleration scheme
- Radiation transport is expensive

Goal

Develop a transport algorithm that

1. Accelerates Discrete Ordinates Source Iteration
2. Bridges Linear Discontinuous Galerkin (LDG) transport and MHFEM multiphysics

Source Iteration Background

Boltzmann Equation

Steady-state, mono-energetic, isotropically-scattering, fixed-source **Linear Boltzmann Equation** in 1D slab geometry:

$$\mu \frac{\partial \psi}{\partial x}(x, \mu) + \Sigma_t(x) \psi(x, \mu) = \frac{\Sigma_s(x)}{2} \int_{-1}^1 \psi(x, \mu') d\mu' + \frac{Q(x)}{2}$$

$\mu = \cos \theta$ the cosine of the angle of flight θ relative to the x -axis

$\Sigma_t(x)$, $\Sigma_s(x)$ total and scattering macroscopic cross sections

$Q(x)$ the isotropic fixed-source

$\psi(x, \mu)$ the angular flux

Boltzmann Equation

Steady-state, mono-energetic, isotropically-scattering, fixed-source **Linear Boltzmann Equation** in 1D slab geometry:

$$\mu \frac{\partial \psi}{\partial x}(x, \mu) + \Sigma_t(x) \psi(x, \mu) = \frac{\Sigma_s(x)}{2} \int_{-1}^1 \psi(x, \mu') d\mu' + \frac{Q(x)}{2}$$

$\mu = \cos \theta$ the cosine of the angle of flight θ relative to the x -axis

$\Sigma_t(x)$, $\Sigma_s(x)$ total and scattering macroscopic cross sections

$Q(x)$ the isotropic fixed-source

$\psi(x, \mu)$ the angular flux

Integro-differential equation

Discrete Ordinates (S_N) Angular Discretization

Compute angular flux on N discrete angles

$$\psi(x, \mu) \xrightarrow{S_N} \begin{cases} \psi_1(x), & \mu = \mu_1 \\ \psi_2(x), & \mu = \mu_2 \\ \vdots \\ \psi_N, & \mu = \mu_N \end{cases}$$

Discrete Ordinates (S_N) Angular Discretization

Compute angular flux on N discrete angles

$$\psi(x, \mu) \xrightarrow{S_N} \begin{cases} \psi_1(x), & \mu = \mu_1 \\ \psi_2(x), & \mu = \mu_2 \\ \vdots \\ \psi_N, & \mu = \mu_N \end{cases}$$

$\mu_1, \mu_2, \dots, \mu_N$ defined by N -point Gauss Quadrature Rule

Discrete Ordinates (S_N) Angular Discretization

Compute angular flux on N discrete angles

$$\psi(x, \mu) \xrightarrow{S_N} \begin{cases} \psi_1(x), & \mu = \mu_1 \\ \psi_2(x), & \mu = \mu_2 \\ \vdots \\ \psi_N, & \mu = \mu_N \end{cases}$$

$\mu_1, \mu_2, \dots, \mu_N$ defined by N -point Gauss Quadrature Rule

Integrate order $2N - 1$ polynomials exactly with

$$\phi(x) = \int_{-1}^1 \psi(x, \mu) d\mu \xrightarrow{S_N} \sum_{n=1}^N w_n \psi_n(x)$$

S_N Equations

$$\mu_n \frac{d\psi_n}{dx}(x) + \Sigma_t(x)\psi_n(x) = \frac{\Sigma_s(x)}{2}\phi(x) + \frac{Q(x)}{2}, \quad 1 \leq n \leq N$$

$$\phi(x) = \sum_{n=1}^N w_n \psi_n(x)$$

N coupled, ordinary differential equations

All coupling in scattering term

Source Iteration

Decouple by lagging scattering term

$$\mu_n \frac{d\psi_n^{\ell+1}}{dx}(x) + \Sigma_t(x)\psi_n^{\ell+1}(x) = \frac{\Sigma_s(x)}{2}\phi^\ell(x) + \frac{Q(x)}{2}, 1 \leq n \leq N$$

N independent, first-order, ordinary differential equations

Solve each equation with well-known sweeping process

Source Iteration

1. Given previous estimate for $\phi^\ell(x)$, solve for $\psi_n^{\ell+1}$
2. Compute $\phi^{\ell+1}(x) = \sum_{n=1}^N w_n \psi_n^{\ell+1}(x)$
3. Update scattering term with $\phi^{\ell+1}(x)$ and repeat until:

$$\frac{\|\phi^{\ell+1}(x) - \phi^\ell(x)\|}{\|\phi^{\ell+1}(x)\|} < \epsilon$$


Need For Acceleration in Source Iteration

Convergence rate is linked to the number of collisions in a particle's lifetime

Need For Acceleration in Source Iteration

Convergence rate is linked to the number of collisions in a particle's lifetime


If $\phi^0(x) = 0$

$$\mu_n \frac{d\psi_n^1}{dx}(x) + \Sigma_t(x)\psi_n^1(x) = \frac{\Sigma_s(x)}{2} \phi^0(x) + \frac{Q(x)}{2}, 1 \leq n \leq N$$


Need For Acceleration in Source Iteration

Convergence rate is linked to the number of collisions in a particle's lifetime

If $\phi^0(x) = 0$


$$\mu_n \frac{d\psi_n^1}{dx}(x) + \Sigma_t(x)\psi_n^1(x) = \frac{\Sigma_s(x)}{2} \phi^0(x) + \frac{Q(x)}{2}, 1 \leq n \leq N$$


$\phi^1(x)$ is the uncollided flux

Need For Acceleration in Source Iteration

Convergence rate is linked to the number of collisions in a particle's lifetime

If $\phi^0(x) = 0$

$$\mu_n \frac{d\psi_n^1}{dx}(x) + \Sigma_t(x)\psi_n^1(x) = \frac{\Sigma_s(x)}{2} \phi^0(x) + \frac{Q(x)}{2}, 1 \leq n \leq N$$



$\phi^1(x)$ is the uncollided flux

$\phi^2(x)$ is uncollided and once collided flux

Need For Acceleration in Source Iteration

Convergence rate is linked to the number of collisions in a particle's lifetime

If $\phi^0(x) = 0$

$$\mu_n \frac{d\psi_n^1(x)}{dx} + \Sigma_t(x)\psi_n^1(x) = \frac{\Sigma_s(x)}{2} \phi^0(x) + \frac{Q(x)}{2}, 1 \leq n \leq N$$


$\phi^1(x)$ is the uncollided flux

$\phi^2(x)$ is uncollided and once collided flux


\vdots

$\phi^\ell(x)$ is the scalar flux of particles that have undergone at most $\ell - 1$ collisions

Need For Acceleration in Source Iteration

Convergence rate is linked to the number of collisions in a particle's lifetime

If $\phi^0(x) = 0$

$$\mu_n \frac{d\psi_n^1(x)}{dx} + \Sigma_t(x)\psi_n^1(x) = \frac{\Sigma_s(x)}{2} \phi^0(x) + \frac{Q(x)}{2}, 1 \leq n \leq N$$


$\phi^1(x)$ is the uncollided flux

$\phi^2(x)$ is uncollided and once collided flux

\vdots

$\phi^\ell(x)$ is the scalar flux of particles that have undergone at most $\ell - 1$ collisions

Slow to converge in optically thick systems with minimal losses to absorption and leakage

Need For Acceleration in Source Iteration

Radiation Hydrodynamics problems often contain highly diffusive regions

S_N is too expensive in these regions

Need an **acceleration scheme** that rapidly increases the rate of convergence of source iteration

Eddington Acceleration

Conservative Form of Boltzmann Equation

Take moments of Boltzmann equation until have enough equations for the number of unknowns

Conservative Form of Boltzmann Equation

Take moments of Boltzmann equation until have enough equations for the number of unknowns

Zeroth Moment: integrate over all angles

$$\int_{-1}^1 \mu \frac{d\psi}{dx}(x, \mu) d\mu + \int_{-1}^1 \Sigma_t(x) \psi(x, \mu) d\mu = \int_{-1}^1 \frac{\Sigma_s(x)}{2} \phi(x) d\mu + \int_{-1}^1 \frac{Q(x)}{2} d\mu$$

Conservative Form of Boltzmann Equation

Take moments of Boltzmann equation until have enough equations for the number of unknowns

Zeroth Moment: integrate over all angles

$$\int_{-1}^1 \mu \frac{d\psi}{dx}(x, \mu) d\mu + \int_{-1}^1 \Sigma_t(x) \psi(x, \mu) d\mu = \int_{-1}^1 \frac{\Sigma_s(x)}{2} \phi(x) d\mu + \int_{-1}^1 \frac{Q(x)}{2} d\mu$$

Use $J(x) = \int_{-1}^1 \mu \psi(x, \mu) d\mu$, $\phi(x) = \int_{-1}^1 \psi(x, \mu) d\mu$

Zeroth Angular Moment

$$\frac{d}{dx} J(x) + \Sigma_a(x) \phi(x) = Q(x)$$

Conservative Form of Boltzmann Equation

Take moments of Boltzmann equation until have enough equations for the number of unknowns

Zeroth Moment: integrate over all angles

$$\int_{-1}^1 \mu \frac{d\psi}{dx}(x, \mu) d\mu + \int_{-1}^1 \Sigma_t(x) \psi(x, \mu) d\mu = \int_{-1}^1 \frac{\Sigma_s(x)}{2} \phi(x) d\mu + \int_{-1}^1 \frac{Q(x)}{2} d\mu$$

Use $J(x) = \int_{-1}^1 \mu \psi(x, \mu) d\mu$, $\phi(x) = \int_{-1}^1 \psi(x, \mu) d\mu$

Zeroth Angular Moment

$$\frac{d}{dx} J(x) + \Sigma_a(x) \phi(x) = Q(x)$$

1 equation, 2 unknowns

Conservative Form of the Boltzmann Equation

First Moment: multiply by μ and integrate

$$\int_{-1}^1 \mu^2 \frac{d\psi}{dx}(x, \mu) d\mu + \int_{-1}^1 \mu \Sigma_t(x) \psi(x, \mu) d\mu = \int_{-1}^1 \mu \frac{\Sigma_s(x)}{2} \phi(x) d\mu + \int_{-1}^1 \mu \frac{Q(x)}{2} d\mu$$

Conservative Form of the Boltzmann Equation

First Moment: multiply by μ and integrate

$$\int_{-1}^1 \mu^2 \frac{d\psi}{dx}(x, \mu) d\mu + \underbrace{\int_{-1}^1 \mu \Sigma_t(x) \psi(x, \mu) d\mu}_{\Sigma_t(x) J(x)} = \int_{-1}^1 \mu \frac{\Sigma_s(x)}{2} \phi(x) d\mu + \int_{-1}^1 \mu \frac{Q(x)}{2} d\mu$$

Conservative Form of the Boltzmann Equation

First Moment: multiply by μ and integrate

$$\int_{-1}^1 \mu^2 \frac{d\psi}{dx}(x, \mu) d\mu + \underbrace{\int_{-1}^1 \mu \Sigma_t(x) \psi(x, \mu) d\mu}_{\Sigma_t(x) J(x)} = \underbrace{\int_{-1}^1 \mu \frac{\Sigma_s(x)}{2} \phi(x) d\mu + \int_{-1}^1 \mu \frac{Q(x)}{2} d\mu}_{\text{Isotropic} \Rightarrow 0}$$

Conservative Form of the Boltzmann Equation

First Moment: multiply by μ and integrate

$$\int_{-1}^1 \mu^2 \frac{d\psi}{dx}(x, \mu) d\mu + \underbrace{\int_{-1}^1 \mu \Sigma_t(x) \psi(x, \mu) d\mu}_{\Sigma_t(x) J(x)} = \underbrace{\int_{-1}^1 \mu \frac{\Sigma_s(x)}{2} \phi(x) d\mu + \int_{-1}^1 \mu \frac{Q(x)}{2} d\mu}_{\text{Isotropic} \Rightarrow 0}$$

Eddington Factor

Rearrange derivative

$$\frac{d}{dx} \int_{-1}^1 \mu^2 \psi(x, \mu) d\mu$$

Eddington Factor

Rearrange derivative

$$\frac{d}{dx} \underbrace{\int_{-1}^1 \mu^2 \psi(x, \mu) d\mu}_{\text{Second Moment of } \psi(x, \mu)}$$

Eddington Factor

Rearrange derivative

$$\frac{d}{dx} \underbrace{\int_{-1}^1 \mu^2 \psi(x, \mu) d\mu}_{\text{Second Moment of } \psi(x, \mu)}$$

Each moment adds an equation and an unknown

Eddington Factor

Rearrange derivative

$$\frac{d}{dx} \underbrace{\int_{-1}^1 \mu^2 \psi(x, \mu) d\mu}_{\text{Second Moment of } \psi(x, \mu)}$$

Each moment adds an equation and an unknown

Multiply and divide by $\int_{-1}^1 \psi(x, \mu) d\mu$

$$\frac{d}{dx} \int_{-1}^1 \psi(x, \mu) d\mu \frac{\int_{-1}^1 \mu^2 \psi(x, \mu) d\mu}{\int_{-1}^1 \psi(x, \mu) d\mu}$$

Eddington Factor

Rearrange derivative

$$\frac{d}{dx} \underbrace{\int_{-1}^1 \mu^2 \psi(x, \mu) d\mu}_{\text{Second Moment of } \psi(x, \mu)}$$

Each moment adds an equation and an unknown

Multiply and divide by $\int_{-1}^1 \psi(x, \mu) d\mu$

$$\frac{d}{dx} \underbrace{\int_{-1}^1 \psi(x, \mu) d\mu}_{\phi(x)} \frac{\int_{-1}^1 \mu^2 \psi(x, \mu) d\mu}{\underbrace{\int_{-1}^1 \psi(x, \mu) d\mu}_{\langle \mu^2 \rangle(x)}}$$

Eddington Factor

Rearrange derivative

$$\frac{d}{dx} \underbrace{\int_{-1}^1 \mu^2 \psi(x, \mu) d\mu}_{\text{Second Moment of } \psi(x, \mu)}$$

Each moment adds an equation and an unknown

Multiply and divide by $\int_{-1}^1 \psi(x, \mu) d\mu$

$$\frac{d}{dx} \underbrace{\int_{-1}^1 \psi(x, \mu) d\mu}_{\phi(x)} \underbrace{\frac{\int_{-1}^1 \mu^2 \psi(x, \mu) d\mu}{\int_{-1}^1 \psi(x, \mu) d\mu}}_{\langle \mu^2 \rangle(x)}$$

Eddington Factor

$$\langle \mu^2 \rangle(x) = \frac{\int_{-1}^1 \mu^2 \psi(x, \mu) d\mu}{\int_{-1}^1 \psi(x, \mu) d\mu}$$

Eddington Factor

Rearrange derivative

$$\frac{d}{dx} \underbrace{\int_{-1}^1 \mu^2 \psi(x, \mu) d\mu}_{\text{Second Moment of } \psi(x, \mu)}$$

Each moment adds an equation and an unknown

Multiply and divide by $\int_{-1}^1 \psi(x, \mu) d\mu$

$$\frac{d}{dx} \underbrace{\int_{-1}^1 \psi(x, \mu) d\mu}_{\phi(x)} \underbrace{\frac{\int_{-1}^1 \mu^2 \psi(x, \mu) d\mu}{\int_{-1}^1 \psi(x, \mu) d\mu}}_{\langle \mu^2 \rangle(x)}$$

Eddington Factor

$$\langle \mu^2 \rangle(x) = \frac{\int_{-1}^1 \mu^2 \psi(x, \mu) d\mu}{\int_{-1}^1 \psi(x, \mu) d\mu}$$

Angular flux weighted average of μ^2

Moment Equations

Moment Equations

$$\frac{d}{dx}J(x) + \Sigma_a(x)\phi(x) = Q(x) \quad (\text{Zeroth Moment})$$

$$\frac{d}{dx}\langle\mu^2\rangle(x)\phi(x) + \Sigma_t(x)J(x) = 0 \quad (\text{First Moment})$$

Moment Equations

Moment Equations

$$\frac{d}{dx}J(x) + \Sigma_a(x)\phi(x) = Q(x) \quad (\text{Zeroth Moment})$$

$$\frac{d}{dx}\langle\mu^2\rangle(x)\phi(x) + \Sigma_t(x)J(x) = 0 \quad (\text{First Moment})$$

3 unknowns ($\phi(x)$, $J(x)$, $\langle\mu^2\rangle(x)$), 2 equations

Moment Equations

Moment Equations

$$\frac{d}{dx}J(x) + \Sigma_a(x)\phi(x) = Q(x) \quad (\text{Zeroth Moment})$$

$$\frac{d}{dx}\langle\mu^2\rangle(x)\phi(x) + \Sigma_t(x)J(x) = 0 \quad (\text{First Moment})$$

3 unknowns ($\phi(x)$, $J(x)$, $\langle\mu^2\rangle(x)$), 2 equations

Closure: $\langle\mu^2\rangle(x)$ found through Boltzmann Equation

Moment Equations

Moment Equations

$$\frac{d}{dx}J(x) + \Sigma_a(x)\phi(x) = Q(x) \quad (\text{Zeroth Moment})$$

$$\frac{d}{dx}\langle\mu^2\rangle(x)\phi(x) + \Sigma_t(x)J(x) = 0 \quad (\text{First Moment})$$

3 unknowns ($\phi(x)$, $J(x)$, $\langle\mu^2\rangle(x)$), 2 equations

Closure: $\langle\mu^2\rangle(x)$ found through Boltzmann Equation

Moment Equations = angular flux informed diffusion

Moment Equations

Moment Equations

$$\frac{d}{dx}J(x) + \Sigma_a(x)\phi(x) = Q(x) \quad (\text{Zeroth Moment})$$

$$\frac{d}{dx}\langle\mu^2\rangle(x)\phi(x) + \Sigma_t(x)J(x) = 0 \quad (\text{First Moment})$$

3 unknowns ($\phi(x)$, $J(x)$, $\langle\mu^2\rangle(x)$), 2 equations

Closure: $\langle\mu^2\rangle(x)$ found through Boltzmann Equation

Moment Equations = angular flux informed diffusion

Transport information passed through $\langle\mu^2\rangle(x)$ and boundary conditions

Moment Equations

Moment Equations

$$\frac{d}{dx}J(x) + \Sigma_a(x)\phi(x) = Q(x) \quad (\text{Zeroth Moment})$$

$$\frac{d}{dx}\langle\mu^2\rangle(x)\phi(x) + \Sigma_t(x)J(x) = 0 \quad (\text{First Moment})$$

3 unknowns ($\phi(x)$, $J(x)$, $\langle\mu^2\rangle(x)$), 2 equations

Closure: $\langle\mu^2\rangle(x)$ found through Boltzmann Equation

Moment Equations = angular flux informed diffusion

Transport information passed through $\langle\mu^2\rangle(x)$ and boundary conditions

Just as accurate as S_N

Moment Equations

Moment Equations

$$\frac{d}{dx}J(x) + \Sigma_a(x)\phi(x) = Q(x) \quad (\text{Zeroth Moment})$$

$$\frac{d}{dx}\langle\mu^2\rangle(x)\phi(x) + \Sigma_t(x)J(x) = 0 \quad (\text{First Moment})$$

3 unknowns ($\phi(x)$, $J(x)$, $\langle\mu^2\rangle(x)$), 2 equations

Closure: $\langle\mu^2\rangle(x)$ found through Boltzmann Equation

Moment Equations = angular flux informed diffusion

Transport information passed through $\langle\mu^2\rangle(x)$ and boundary conditions

Just as accurate as S_N

Analytically pointless: if Boltzmann can be solved, don't need Moment Equations

Moment Equations

Moment Equations

$$\frac{d}{dx}J(x) + \Sigma_a(x)\phi(x) = Q(x) \quad (\text{Zeroth Moment})$$

$$\frac{d}{dx}\langle\mu^2\rangle(x)\phi(x) + \Sigma_t(x)J(x) = 0 \quad (\text{First Moment})$$

3 unknowns ($\phi(x)$, $J(x)$, $\langle\mu^2\rangle(x)$), 2 equations

Closure: $\langle\mu^2\rangle(x)$ found through Boltzmann Equation

Moment Equations = angular flux informed diffusion

Transport information passed through $\langle\mu^2\rangle(x)$ and boundary conditions

Just as accurate as S_N

Analytically pointless: if Boltzmann can be solved, don't need Moment Equations

Numerically: use S_N to compute estimate of $\langle\mu^2\rangle(x)$, Moment Equations to find $\phi(x)$

Eddington Acceleration

1. Given the previous estimate for the scalar flux, $\phi^\ell(x)$, solve for $\psi_n^{\ell+1/2}(x)$
2. Compute $\langle \mu^2 \rangle^{\ell+1/2}(x)$
3. Solve the Moment Equations for $\phi^{\ell+1}(x)$ using $\langle \mu^2 \rangle^{\ell+1/2}(x)$
4. Update the scalar flux estimate with $\phi^{\ell+1}(x)$ and repeat the iteration process until the scalar flux converges

Eddington Acceleration

1. Given the previous estimate for the scalar flux, $\phi^\ell(x)$, solve for $\psi_n^{\ell+1/2}(x)$
2. Compute $\langle \mu^2 \rangle^{\ell+1/2}(x)$
3. Solve the Moment Equations for $\phi^{\ell+1}(x)$ using $\langle \mu^2 \rangle^{\ell+1/2}(x)$
4. Update the scalar flux estimate with $\phi^{\ell+1}(x)$ and repeat the iteration process until the scalar flux converges

Acceleration occurs because

1. Angular shape of the angular flux converges quickly \Rightarrow Eddington factor quickly converges
2. Moment Equations model all scattering at once \Rightarrow dependence on source iterations to introduce scattering information is reduced

Produces 2 solutions (S_N and Moment)

Eddington Acceleration Properties

Produces 2 solutions (S_N and Moment)

Relaxes consistent differencing requirements important in linear acceleration

Eddington Acceleration Properties

Produces 2 solutions (S_N and Moment)

Relaxes consistent differencing requirements important in linear acceleration

Transport can be LDG and Moment can be MHFEM

Eddington Acceleration Properties

Produces 2 solutions (S_N and Moment)

Relaxes consistent differencing requirements important in linear acceleration

Transport can be LDG and Moment can be MHFEM

Moment Equations are conservative and relatively inexpensive to solve

Eddington Acceleration Properties

Produces 2 solutions (S_N and Moment)

Relaxes consistent differencing requirements important in linear acceleration

Transport can be LDG and Moment can be MHFEM

Moment Equations are conservative and relatively inexpensive to solve

Downside: Which solution is correct?

Eddington Acceleration Properties

Produces 2 solutions (S_N and Moment)

Relaxes consistent differencing requirements important in linear acceleration

Transport can be LDG and Moment can be MHFEM

Moment Equations are conservative and relatively inexpensive to solve

Downside: Which solution is correct?

Difference between S_N and Moment solutions can be used as a measure of mesh convergence

Results

S_8 in 1D slab geometry

Test Problem

S_8 in 1D slab geometry

Lumped Linear Discontinuous Galerkin transport

Test Problem

S_8 in 1D slab geometry

Lumped Linear Discontinuous Galerkin transport


Mixed Hybrid Finite Element Method Moment

Test Problem

S_8 in 1D slab geometry

Lumped Linear Discontinuous Galerkin transport

Mixed Hybrid Finite Element Method Moment



Diffusion Limit

Scale cross sections, source

$$\Sigma_t \rightarrow \Sigma_t/\epsilon$$

$$\Sigma_a \rightarrow \epsilon \Sigma_a$$

$$Q \rightarrow \epsilon Q$$

System becomes diffusive as $\epsilon \rightarrow 0$

Diffusion Limit


Scale cross sections, source

$$\Sigma_t \rightarrow \Sigma_t / \epsilon$$

$$\Sigma_a \rightarrow \epsilon \Sigma_a$$

$$Q \rightarrow \epsilon Q$$

System becomes diffusive as $\epsilon \rightarrow 0$



Diffusion Limit


Scale cross sections, source

$$\Sigma_t \rightarrow \Sigma_t / \epsilon$$

$$\Sigma_a \rightarrow \epsilon \Sigma_a$$

$$Q \rightarrow \epsilon Q$$

System becomes diffusive as $\epsilon \rightarrow 0$



Survives diffusion limit

Diffusion Limit


Scale cross sections, source

$$\Sigma_t \rightarrow \Sigma_t / \epsilon$$

$$\Sigma_a \rightarrow \epsilon \Sigma_a$$

$$Q \rightarrow \epsilon Q$$

System becomes diffusive as $\epsilon \rightarrow 0$




Survives diffusion limit

Performs similarly to consistently differenced, linear acceleration (S_2SA)


Convergence Rate Comparison

Unaccelerated




Convergence Rate Comparison

Unaccelerated




Accelerated




Convergence Rate Comparison

Unaccelerated



Accelerated



Fast rate of convergence of $\langle \mu^2 \rangle(x)$ is transferred to $\phi(x)$

Method of Manufactured Solutions Order of Accuracy


Set $Q(x)$ to force solution to

$$\phi(x) = \sin\left(\frac{\pi x}{x_b}\right)$$

Method of Manufactured Solutions Order of Accuracy

Set $Q(x)$ to force solution to


$$\phi(x) = \sin\left(\frac{\pi x}{x_b}\right)$$



Method of Manufactured Solutions Order of Accuracy

Set $Q(x)$ to force solution to

$$\phi(x) = \sin\left(\frac{\pi x}{x_b}\right)$$




All second order as expected

Method of Manufactured Solutions Order of Accuracy

Set $Q(x)$ to force solution to

$$\phi(x) = \sin\left(\frac{\pi x}{x_b}\right)$$




All second order as expected

Eddington Acceleration did not effect the order of accuracy of lumped LDG

Method of Manufactured Solutions Order of Accuracy

Set $Q(x)$ to force solution to

$$\phi(x) = \sin\left(\frac{\pi x}{x_b}\right)$$



All second order as expected

Eddington Acceleration did not effect the order of accuracy of lumped LDG

All slope recovery methods have similar accuracy

Data Reconstruction Solution Convergence

Compare

$$\frac{\|\phi_{S_N}(x) - \phi_{\text{Moment}}(x)\|}{\|\phi_{\text{Moment}}(x)\|}$$


as $h \rightarrow 0$

Data Reconstruction Solution Convergence

Compare

$$\frac{\|\phi_{S_N}(x) - \phi_{\text{Moment}}(x)\|}{\|\phi_{\text{Moment}}(x)\|}$$

as $h \rightarrow 0$




Data Reconstruction Solution Convergence

Compare

$$\frac{\|\phi_{S_N}(x) - \phi_{\text{Moment}}(x)\|}{\|\phi_{\text{Moment}}(x)\|}$$

as $h \rightarrow 0$




S_N and Moment solutions converge as mesh is refined

Data Reconstruction Solution Convergence

Compare

$$\frac{\|\phi_{S_N}(x) - \phi_{\text{Moment}}(x)\|}{\|\phi_{\text{Moment}}(x)\|}$$


as $h \rightarrow 0$




S_N and Moment solutions converge as mesh is refined

Slope recovery effects solution convergence but not accuracy

Data Reconstruction Diffusion Limit




Data Reconstruction Diffusion Limit



All data reconstruction methods survived diffusion limit

Data Reconstruction Diffusion Limit



All data reconstruction methods survived diffusion limit

Eddington Acceleration is extremely robust

Conclusions

Conclusions

- Scheme successfully accelerated source iteration in 1D slab geometry
- Eddington Acceleration is uniquely suited for radiation hydrodynamics
 - Transport and acceleration steps can be differenced with different methods
 - Reduces expense of source iteration
 - Provides inexpensive, conservative solution
- Showed MHFEM/LLDG pairing is robust

Conclusions

- Scheme successfully accelerated source iteration in 1D slab geometry
- Eddington Acceleration is uniquely suited for radiation hydrodynamics
 - Transport and acceleration steps can be differenced with different methods
 - Reduces expense of source iteration
 - Provides inexpensive, conservative solution
- Showed MHFEM/LLDG pairing is robust

Future Work

- Add temperature for radiative transfer
- Show still works in higher dimensions
- Develop an efficient rad hydro algorithm that makes use of the inexpensive Moment solution in multiphysics iterations

References

- [1] M. L. ADAMS AND E. W. LARSEN, *Fast Iterative Methods for Discrete-Ordinates Particle Transport Calculations*, vol. 40, Progress in Nuclear Technology, 2002.
- [2] R. E. ALCOUFFE, *Diffusion Synthetic Acceleration Methods for the Diamond-Differenced Discrete-Ordinates Equations*, 1977.
- [3] S. BOLDING AND J. HANSEL, *Second-Order Discretization in Space and Time for Radiation-Hydrodynamics*, Journal of Computational Physics, 2017.
- [4] F. BREZZI AND M. FORTIN, *Mixed and Hybrid Finite Element Methods*, Springer, 1991.
- [5] J. I. CASTOR, *Radiation Hydrodynamics*, Lawrence Livermore National Laboratory, 2003.
- [6] C. NEWMAN, D. KNOLL, AND R. PARK, *Nonlinear Acceleration of Transport Criticality Problems*, Los Alamos National Laboratory, 2011.
- [7] S. N. SHORE, *An Introduction to Astrophysical Hydrodynamics*, Academic Press, Inc., 1992.
- [8] J. S. WARSA, T. A. WAREING, AND J. E. MOREL, *Fully Consistent Diffusion Synthetic Acceleration of Linear Discontinuous Transport Discretizations on Three-Dimensional Unstructured Meshes*.

Questions?

Data Reconstruction Methods

MHFEM $\phi(x)$ is piecewise constant with discontinuous cell edges
 $(\phi_{i-1/2}, \phi_i, \phi_{i+1/2})$

LLDG is linear discontinuous $(\phi_{i,L}, \phi_{i,R})$

Need a way to recover slope information when S_N scattering term is updated with MHFEM $\phi(x)$

No Slopes:

$$\phi_{i,L/R} = \phi_{i \mp 1/2}^*$$

Slopes from Edges:



$$\phi_{i,L/R} = \phi_i^* \mp \frac{1}{2} (\phi_{i+1/2}^* - \phi_{i-1/2}^*)$$

vanLeer on Centers:

$$\phi_{i,L/R} = \phi_i^* \mp \frac{1}{2} \xi_{\text{vanLeer}} [(\phi_{i+1}^* - \phi_i^*) + (\phi_i^* - \phi_{i-1}^*)]$$


S_8 v. Diffusion

Small system \Rightarrow diffusion not expected to be accurate




S_8 v. Drift Diffusion

Use $\langle \mu^2 \rangle(x)$ from S_8 in Moment Equations



S_8 v. Drift Diffusion


Use $\langle \mu^2 \rangle(x)$ from S_8 in Moment Equations



Moment Equations and S_N match!

S_8 v. Drift Diffusion

Use $\langle \mu^2 \rangle(x)$ from S_8 in Moment Equations



Moment Equations and S_N match!

Requires knowledge of angular flux