



Kurumsal
İş Sistemleri

**Uyumsoft e-Invoice
and e-Archive System
Web Service Guide**

1

Contents

1	Contents	ii
2	Introduction	0
2.1	Definitions	0
2.2	TRA e-Invoice System	0
3	Uyumsoft e-Invoice and e-Archive System	1
3.1	e-Invoice Structure	1
3.1.1	Application Responses	1
3.2	E- Archive System	1
3.3	Uyumsoft Customer Web Services	1
4	Operations	3
4.1	CancelDraft	3
4.2	CancelEArchiveInvoice	3
4.3	ChangeInvoiceArchiveStatus	3
4.4	CloneInvoices	3
4.5	CompressedSaveAsDraft	4
4.6	CompressedSendInvoice	4
4.7	GetEInvoiceUsers	4
4.8	GetInboxInvoice	4
4.9	GetInboxInvoiceData	4
4.10	GetInboxInvoiceList	5
4.11	GetInboxInvoicePdf	5
4.12	GetInboxInvoices	5
4.13	GetInboxInvoicesData	5
4.14	GetInboxInvoiceStatusWithLogs	6
4.15	GetInboxInvoiceView	6
4.16	GetOutboxInvoice	6
4.17	GetOutboxInvoiceData	6
4.18	GetOutboxInvoiceList	6
4.19	GetOutboxInvoicePdf	7
4.20	GetOutboxInvoiceResponseView	7
4.21	GetOutboxInvoices	7

4.22	GetOutboxInvoicesData	7
4.23	GetOutboxInvoiceStatusWithLogs	7
4.24	GetOutboxInvoiceView	8
4.25	GetSystemDate	8
4.26	GetUserAliases	8
4.27	IsEInvoiceUser	8
4.28	QueryDocumentResponseStatus	9
4.29	QueryInboxInvoiceStatus	9
4.30	QueryOutboxInvoiceStatus	9
4.31	RetrySendInvoices	9
4.32	SaveAsDraft	9
4.33	SendDocumentResponse	10
4.34	SendDraft	10
4.35	SendInvoice	10
4.36	SetInvoicesTaken	10
4.37	SetXsltView	10
4.38	ValidateInvoice	11
5	Common Objects	11
5.1	BinaryRequestData	11
5.2	ClonedInvoiceInfo	11
5.3	CloneInvoiceServiceResponse	11
5.4	CustomerInfo	12
5.5	DateResponse	12
5.6	DocumentResponseEntityStatus	12
5.7	DocumentResponseInfo	12
5.8	DocumentResponseStatus	13
5.9	DocumentResponseStatusInfo	13
5.10	DocumentResponseStatusResponse	13
5.11	EArchiveCancelInvoiceContext	13
5.12	EArchiveInvoiceInformation	14
5.13	EArchiveWithHoldingInformation	14
5.14	EnvelopeStatus	14
5.15	FlagResponse	15

5.16	InboxInvoiceListItem	16
5.17	InboxInvoiceListQueryModel	16
5.18	InboxInvoiceListResponse	17
5.19	InboxInvoiceQueryModel	17
5.20	InternetSalesInformation	17
5.21	InvoiceData	18
5.22	InvoiceDataResponse	18
5.23	InvoiceDeliveryType	18
5.24	InvoiceIdentitiesResponse	18
5.25	InvoiceIdentity	19
5.26	InvoiceInfo	19
5.27	InvoiceLogItem	19
5.28	InvoiceQueryModel	20
5.29	InvoiceResponse	20
5.30	InvoiceScenarioChooosen	20
5.31	InvoiceScenarioType	21
5.32	InvoicesDataResponse	21
5.33	InvoicesResponse	21
5.34	InvoiceStatus	21
5.35	InvoiceStatusInfo	22
5.36	InvoiceStatusResponse	22
5.37	InvoiceStatusWithLogInfo	22
5.38	InvoiceStatusWithLogResponse	23
5.39	InvoiceTypes	23
5.40	InvoiceViewResponse	23
5.41	LineResponseInfo	23
5.42	MailAttachmentInformation	24
5.43	MailingInformation	24
5.44	NewGenerationPaymentRecorderInformation	24
5.45	NotificationInformation	25
5.46	OutboxInvoiceListQueryModel	25
5.47	OutboxInvoiceListResponse	25
5.48	PagedQueryContext	25

5.49	PagedResponseOfInboxInvoiceListItem.....	26
5.50	PagedResponseOfInvoiceData	26
5.51	PagedResponseOfInvoiceInfo	26
5.52	PagedResponseOfSystemUser	26
5.53	ShipmentCarrier	27
5.54	ShipmentInformation.....	27
5.55	SystemUser	27
5.56	SystemUserAlias.....	28
5.57	AliasType	28
5.58	SystemUserDefinition	28
5.59	SystemUsersResponse	28
5.60	SystemUserWithAlias.....	29
5.61	UserAliassesResponse.....	29
5.62	VerificationResult.....	29
5.63	ViewResult	29
5.64	XsltViewType.....	30
5.65	Response.....	30

2 Introduction

This document covers Uyumsoft solution web service operations, objects and concepts to ensure a healthy integration.

2.1 Definitions

TRA: It means Finance Revenue Administration of Turkish Ministry.

UBL-TR: This is the format of Universal Business Language(UBL) that is adapted to Turkey which is internalized by TRA. This format provides a common system which makes companies communicate with each other.

UBL-TR Invoice: A part of UBL-TR format that is assigned for e-invoice. TRA system manages the e-invoice document flow between companies with XML format.

StandartDocumentBusinessHeader: A standard format that is designated for the document flow between companies. It is called "envelope" by TRA system.

e-Invoice: The invoice format that is prepared with the UBL-TR standards. The center of e-Invoice system is managed by the TRA. TRA manages the intermediary system between companies. E-Invoices are transmitted by TRA system to the systems of companies when they send e-invoices to each other.

e-Archive Invoice: Electronic invoice document that enable end users and taxpayers who are not registered to TRA system to receive electronic invoices. This document generated with UBL-TR format even though it is permitted to be in different formats.

Application Response: Within TRA system, e-invoices with commercial type can be accepted or declined by their consumers. These response are the XML documents which are generated according to UBL-TR standards. In the TRA system, documents can be transmitted similar e-invoice documents.

Envelope: It is an XML file that prepared according to the TRA UBL-TR standards which XML file/files prepared with "StandartDocumentBusinessHeader".

2.2 TRA e-Invoice System

E-Invoice system is a service to provide a safe and healthy circulation of e-invoice, which is an electronic document format of invoice data, between suppliers and buyers. E-invoice circulation control between suppliers and buyers in Turkey is controlled and provided by Turkish Revenue Administration (TRA). System used in e-invoicing for Turkey is based on the control of TRA and the main objective of e-invoicing in Turkey is to support transparency and collect taxes from the stakeholders easily.

Taxpayers who are obliged to register to the e-Invoice system integrates the internal invoicing system to the TRA e-invoice system to send and receive invoices electronically.

TRA system provides the distribution of documents which are generated in envelope format. After the arrival of the envelope that are sent to TRA, postbox (alias) information -which takes place in the main informations of the envelope- is controlled by TRA and TRA sends it to the system where the post box of receiver stands. After the buyer receives the envelope, it will return an error or a success response to TRA system. If there is not an error creates an envelope that the envoleper has been successfully processed and sent this envelope to TRA.This envelope that reached to TRA is delivered to the sender.Thus, the process of sending documents between the parties is completed.

3 Uyumsoft e-Invoice and e-Archive System

3.1 e-Invoice Structure

E-Invoice covered by envelope file format before it's sent to TRA system. Every envelope which is created by Uyumsoft system has only one e-invoice in it even TRA system supports multiple invoices in an envelope file format.

Uyumsoft system manages invoice status and envelope status separately. Every envelope status change effects the invoice status. Querying only invoice status ignoring the envelopes is enough to provide the healthy system integration. Instead of managing many technical status codes, it is possible to control only invoice status basically.

The system supports UBL-TR formatted Xml file or object format invoice transmission via web service or via Uyumsoft portal.

Some of check points can be implemented by using the invoice status query methods of web service by developers.

Receival of invoices by Uyumsoft system should not be assumed as completed process. Integrated system should implement a mechanism to be sure if the invoices are received by the consumer party successfully.

3.1.1 Application Responses

Application responses are the "Accepted", "Rejected" and "Returned" documents that are sent as a response of commercial e-invoice documents. Only outgoing invoices has application response documents as a response.

Application response document format is covered by envelope ("StandartDocumentBusinessHeader") document similar to invoice documents. For the software developers, provides an object which named DocumentResponseInfo. [DocumentResponseInfo](#) is the object type that corresponds to Application response. Developers should fill the fields of this object for an incoming invoice. Uyumsoft system generates the Application Response Envelope and sent it to TRA system. In the system, the status of application responses are following by the invoice's UUID.

3.2 E-Archive System

The e-Archive invoicing is a system that enables the end users and taxpayers who are not registered to the e-Invoice system to receive electronic invoices, creation, preservation and if necessary, presentation of the second copies of the invoices and corresponding certificates that the mentioned parts are obliged to preserve.

In e-Archive system, the invoices does not transfer directly to TRA. Information such as the total amount, tax total etc. of the invoices, sent to TRA as digitally signed report format once a month.

e-Archive invoices are also as e-invoice created in UBL-TR format. Uyumsoft system can send e-archive invoices in the same way as e-invoice.

3.3 Uyumsoft Customer Web Services

Uyumsoft solution has web services for the connectivity of other systems which handles invoice information of companies. Uyumsoft is the system which is connected to TRA e-Invoice system and can be used both in private integration and direct integration model. Required informations to generate invoices received by Uyumsoft web service. Data that is sent to Uyumsoft web service processed to build e-invoice format for transferring to TRA system. All status changes that are received by TRA system handled by Uyumsoft solution. Also digital sign, creation of envelope packages and transmission is handled by Uyumsoft solution.

Uyumsoft web services can be reached by following addresses:

Live System: <https://efatura.uyumsoft.com.tr/services/Integration>

Test System: <https://efatura-test.uyumsoft.com.tr/services/Integration>

Username : Uyumsoft

Password: Uyumsoft

During the development process, the Uyumsoft Test Portal can be used as a user interface to list and to do some actions on invoices.

Test Portal: <https://portal-test.uyumsoft.com.tr>

Username : Uyumsoft

Password: Uyumsoft

4 Operations

4.1 CancelDraft

Cancels invoices which are in Draft status. Sets the status of invoices as canceled. For more information please look at InvoiceStatus type.

Method Signature	FlagResponse CancelDraft(List<string> invoiceIds)
Parameters	invoiceIds: The list of invoice Ids which will be canceled. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of a FlagResponse type.

4.2 CancelEArchiveInvoice

Cancels an e-archive invoice. This method can be applied only to the invoices which are Scenario is e-Archive.

If the invoice which will be canceled is in Draft status then the invoice will be set to Canceled status otherwise it will be marked as EArchiveCanceled.

The difference between Canceled and EArchiveCanceled is that the invoices which are in EArchiveCanceled status will be reported to the GIB as normaly which Canceled is not.

Method Signature	FlagResponse CancelEArchiveInvoice(EArchiveCancelInvoiceContext request)
Parameters	request: Represents the required information to cancel an e-archive invoice. The parameter is an instance of EArchiveCancelInvoiceContext type.
Return Value	Returns an instance of a FlagResponse type.

4.3 ChangeInvoiceArchiveStatus

Allows users to put/remove "Archived" flag to their invoices.

This method can be applied to both Inbox and Outbox invoices.

Method Signature	FlagResponse ChangeInvoiceArchiveStatus(List<string> invoiceIds, bool isInbox, bool isArchived)
Parameter	invoiceIds: The list of invoice Ids which will their archive flag will be changed. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object. isInbox: Represents the type of the invoices in the invoiceIds list. True for the Inbox invoices, false for the Outbox invoices. isArchived: If true, Archive flag will be applied to the given invoices otherwise Archive flag will be removed from the given invoices.
Return Value	Returns an instance of a FlagResponse type.

4.4 CloneInvoices

Creates new Invoice instances with the same properties of the given invoices and returns the Id and InvoiceNumber properties of the newly created invoices.

Method Signature	CloneInvoiceServiceResponse CloneInvoices(List<string> invoiceIds)
Parameters	invoiceIds: The list of outbox invoice Ids which will be cloned. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of CloneInvoiceServiceResponse type which contains the Id and InvoiceNumber properties of the newly created invoices.

4.5 CompressedSaveAsDraft

Provides functionality to save invoices in zip format to reduce the size of the data. This method has the same functionality as the [SaveAsDraft](#) method. Invoices will be saved as Draft.

Method Signature	InvoiceIdentitiesResponse CompressedSaveAsDraft(BinaryRequestData data)
Parameter	data: An instance of the BinaryRequestData type which contains the binary of the compressed data.
Return Value	Returns an instance of the InvoiceIdentitiesResponse type.

4.6 CompressedSendInvoice

Provides functionality to send invoices in zip format to reduce the size of the data. This method has the same functionality as the [SendInvoice](#) method.

Method Signature	InvoiceIdentitiesResponse CompressedSendInvoice(BinaryRequestData data)
Parameter	data: An instance of the BinaryRequestData type which contains the binary of the compressed data.
Return Value	Returns an instance of the InvoiceIdentitiesResponse type.

4.7 GetEInvoiceUsers

Provides functionality to query registered e-invoice users and their aliases in the TRA system.

Method Signature	SystemUsersResponse GetEInvoiceUsers(PagedQueryContext pagination)
Parameters	pagination: An instance of the PagedQueryContext type which contains required information to query system users as paged.
Return Value	Returns an instance of the SystemUsersResponse type.

4.8 GetInboxInvoice

Returns a single inbox invoice in UBL-TR format.

Method Signature	InvoiceResponse GetInboxInvoice(string invoiceId)
Parameter	invoiceId: A single invoice Id parameter. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the InvoiceResponse type.

4.9 GetInboxInvoiceData

Returns binary data of a single given inbox invoice. This method returns the invoice without apply any formatting to protect the signature of the invoice. You can run signature validation check on this invoice.

Method Signature	InvoiceDataResponse GetInboxInvoiceData(string invoiceId)
Parameter	invoiceId: A single invoice Id parameter. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the InvoiceDataResponse type.

4.10 GetInboxInvoiceList

Provides functionality to query Inbox invoices and returns the list of the invoices metadata which are meet the given criteria.

Method Signature	InboxInvoiceListResponse GetInboxInvoiceList(InboxInvoiceListQueryModel query)
Parameter	query: An instance of the InboxInvoiceListQueryModel type which contains the filtering and paging criterias.
Return Value	Returns an instance of the InboxInvoiceListResponse type.

4.11 GetInboxInvoicePdf

Transforms an Inbox invoice to Pdf and returns the data of the pdf as byte array.

Method Signature	InvoiceDataResponse GetInboxInvoicePdf(string invoiceId)
Parameter	invoiceId: A single invoice Id parameter. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the InvoiceDataResponse type.

4.12 GetInboxInvoices

Provides functionality to query Inbox invoices and returns the list of the invoices in UBL-TR format which are meet the given criteria.

Method Signature	InvoicesResponse GetInboxInvoices(InboxInvoiceQueryModel query)
Parameter	query: An instance of the InboxInvoiceQueryModel type which contains the filtering and paging criterias.
Return Value	Returns an instance of the InvoicesResponse type.

4.13 GetInboxInvoicesData

Provides functionality to query Inbox invoices and returns the binary data of these invoices without applying any formatting to protect signatures of these invoices which are meet the given criteria. You can run signature validation check on these invoices.

Method Signature	InvoicesDataResponse GetInboxInvoicesData(InboxInvoiceQueryModel query)
Parameter	query: An instance of the InboxInvoiceQueryModel type which contains the filtering and paging criterias.
Return Value	Returns an instance of the InvoicesDataResponse type.

4.14 GetInboxInvoiceStatusWithLogs

Provides functionality to query inbox invoices to get invoice status and envelope status and logs related with them.

Method Signature	InvoiceStatusWithLogResponse GetOutboxInvoiceData(List<string> invoiceIds)
Parameter	invoiceIds: The list of outbox invoice Ids which will be cloned. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the InvoiceStatusWithLogResponse type which contains InvoiceStatusWithLogInfo instances for each queried invoice.

4.15 GetInboxInvoiceView

Transforms an Inbox invoice to html and returns the html string including with the verification information.

Method Signature	InvoiceViewResponse GetInboxInvoiceView(string invoiceId)
Parameter	invoiceId: A single invoice Id parameter. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the InvoiceViewResponse type.

4.16 GetOutboxInvoice

Returns a single outbox invoice in UBL-TR.

Method Signature	InvoiceResponse GetOutboxInvoice(string invoiceId)
Parameter	invoiceId: A single invoice Id parameter. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the InvoiceResponse type.

4.17 GetOutboxInvoiceData

Returns binary data of a single given outbox invoice. This method returns the invoice without apply any formatting to protect the signature of the invoice. You can run signature validation check on this invoice.

Method Signature	InvoiceDataResponse GetOutboxInvoiceData(string invoiceId)
Parameter	invoiceId: A single invoice Id parameter. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the InvoiceDataResponse type.

4.18 GetOutboxInvoiceList

Provides functionality to query Outbox invoices and returns the list of the invoices metadata which are meet the given criteria.

Method Signature	OutboxInvoiceListResponse GetOutboxInvoices(OutboxInvoiceListQueryModel query)
Parameter	query: An instance of the OutboxInvoiceListQueryModel type which contains the filtering and paging criterias.

Return Value Returns an instance of the [OutboxInvoiceListResponse](#) type.

4.19 GetOutboxInvoicePdf

Transforms an Outbox invoice to Pdf and returns the data of the pdf as byte array.

Method Signature	InvoiceDataResponse GetOutboxInvoicePdf(string invoiceId)
Parameter	invoiceId: A single invoice Id parameter. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the InvoiceDataResponse type.

4.20 GetOutboxInvoiceResponseView

Transforms and Outbox Invoice Response (Application Response) to html and returns the html string including with the verification information.

Method Signature	InvoiceViewResponse GetOutboxInvoiceResponseView(string invoiceId)
Parameter	invoiceId: A single invoice Id parameter. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the InvoiceViewResponse type.

4.21 GetOutboxInvoices

Provides functionality to query Outbox invoices and returns the list of the invoices in UBL-TR format which are meet the given criteria.

Method Signature	InvoicesResponse GetOutboxInvoices(InvoiceQueryModel query)
Parameter	query: An instance of the InvoiceQueryModel type which contains the filtering and paging criterias.
Return Value	Returns an instance of the InvoicesResponse type..

4.22 GetOutboxInvoicesData

Provides functionality to query Outbox invoices and returns the binary data of these invoices without applying any formatting to protect signatures of these invoices which are meet the given criteria. You can run signature validation check on these invoices.

Method Signature	InvoicesDataResponse GetOutboxInvoicesData(InvoiceQueryModel query)
Parameter	query: An instance of the InvoiceQueryModel type which contains the filtering and paging criterias.
Return Value	Returns an instance of the InvoicesDataResponse type.

4.23 GetOutboxInvoiceStatusWithLogs

Method Signature	InvoiceStatusWithLogResponse GetInboxInvoiceStatusWithLogs(List<string> invoiceIds)
------------------	--

Parameter	invoiceIds: The list of outbox invoice Ids which will be cloned. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the InvoiceStatusWithLogResponse type which contains InvoiceStatusWithLogInfo instances for each queried invoice.

Provides functionality to query outbox invoices to get invoice status and envelope status and logs related with them.

4.24 GetOutboxInvoiceView

Transforms an Outbox invoice to html and returns the html string including with the verification information.

Method Signature	InvoiceViewResponse GetInboxInvoiceView(string invoiceId)
Parametreleri	invoiceId: A single invoice Id parameter. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the InvoiceViewResponse type.

4.25 GetSystemDate

Returns the system current date and time.

Method Signature	DateResponse GetSystemDate()
Parametreleri	Does not have any parameter.
Return Value	Returns an instance of DateResponse type.

4.26 GetUserAliases

Returns the list of all aliases of a given VKN or TCKN number from the TRA system.

Method Signature	UserAliasesResponse GetUserAliases(string vknTckn)
Parameter	vknTckn: Tckn or Vkn of the system user which you are querying. Tckn is 11 digit and used for the person and Vkn is 10 digit and used for the companies.
Return Value	Return of the UserAliasesResponse type.

4.27 IsInvoiceUser

Provides functionality to query that is a given Vkn/Tckn and alias exists in the TRA system or not? If alias is empty than this method will check only that is given Vkn/Tckn has any alias in the system.

Method Signature	FlagResponse IsInvoiceUser(string vknTckn, string alias)
Parameter	vknTckn: Tckn or Vkn of the system user which you are querying. Tckn is 11 digit and used for the person and Vkn is 10 digit and used for the companies.
	alias: An optional parameter which provides queirying a specific alias of a system user.
Return Value	Returns an instance of the FlagResponse type.

4.28 QueryDocumentResponseStatus

Provides functionality to query document responses (application response) status information.

Method Signature	DocumentResponseStatusResponse QueryDocumentResponseStatus(List<string> invoiceIds)
Parameter	invoiceIds: The list of outbox invoice Ids which will be cloned. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the DocumentResponseStatusResponse type.

4.29 QueryInboxInvoiceStatus

Provides functionality to query an Inbox invoice status.

Method Signature	InvoiceStatusResponse GetInboxInvoiceData(List<string> invoiceIds)
Parameter	invoiceIds: The list of outbox invoice Ids which will be cloned. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the InvoiceStatusResponse type.

4.30 QueryOutboxInvoiceStatus

Provides functionality to query an Outbox invoice status.

Method Signature	InvoiceStatusResponse QueryOutboxInvoiceStatus(List<string> invoiceIds)
Parameter	invoiceIds: The list of outbox invoice Ids which will be cloned. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the InvoiceStatusResponse type.

4.31 RetrySendInvoices

Sets status of an errorinuous invoice to Queue for resending this invoice.

Method Signature	Response RetrySendInvoices(string invoiceIds)
Parameter	invoiceId: A single invoice Id parameter. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns an instance of the Response type.

4.32 SaveAsDraft

Saves given invoice as draft. You can continue editing an invoice which is in Draft status. To send those invoices you can use [SendDraft](#) method.

Method Signature	InvoiceIdentitiesResponse SaveAsDraft(List<InvoiceInfo> invoices)
Parameter	invoices: The list of InvoiceInfo elements which contains required information and Ubl-Tr invoice object.
Return Value	Returns an instance of the InvoiceIdentitiesResponse type which contains InvoiceIdentity element for each invoices. InvoiceIdentity element contains InvoiceNumber and Invoice Id informations of the newly created invoices.

4.33 SendDocumentResponse

Adds provided DocumentResponse elements to the Queue for processing. This method allows you to send Accept/Decline/Return application responses to incoming invoices.

Method Signature	FlagResponse SendDocumentResponse(List<DocumentResponseInfo> responses)
Parameter	responses: The list of DocumentResponseInfo elements which contains required information to send Application Response to incoming invoices.
Return Value	Returns instance of the FlagResponse type.

4.34 SendDraft

Sets the status of provided invoices to Queued from Draft.

Method Signature	GetOutboxInvoiceData(List<string> invoiceIds)
Parameter	invoiceIds: The list of outbox invoice Ids which will be cloned. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns instance of the FlagResponse type.

4.35 SendInvoice

Provides functionality to send invoices to the system. Invoices which are send by this method will be set to Queued status and will be processed as soon as possible by the system.

Method Signature	InvoiceIdentitiesResponse SendInvoice(List<InvoiceInfo> invoices)
Parameter	invoices: The list of InvoiceInfo elements which contains required information and Ubl-Tr invoice object.
Return Value	Returns an instance of the InvoiceIdentitiesResponse type which contains InvoiceIdentity element for each invoices. InvoiceIdentity element contains InvoiceNumber and Invoice Id informations of the newly created invoices.

4.36 SetInvoicesTaken

Puts taken flag to the provided invoices. You can query invoices which has no Taken flag by using the GetInboxInvoices methods.

Method Signature	FlagResponse SetInvoicesTaken (List<string> invoices)
Parameter	invoiceIds: The list of inbox invoice Ids which will be cloned. Invoice Id is the unique Id of an invoice which is represented by the UUID element of the UBL Invoice object.
Return Value	Returns instance of the FlagResponse type.

4.37 SetXsltView

Provides functionality to upload xslt to the system for your usage.

Method Signature	FlagResponse SetXsltView(XsltViewType type, string fileContent)
------------------	--

Parameter	type: The parameter to identify the type of the Xslt. To see more about type of these parameter you can look at to the XsltViewType enumeration.
	fileContent: The content of the template file (xslt).
Return Value	Returns instance of the FlagResponse type.

4.38 ValidateInvoice

Provides functionality to run schema and schematron checks on invoices to validate that are they have any problems.

Method Signature	FlagResponse ValidateInvoice(InvoiceType invoice)
Parameter	Invoice: It is an invoice object in UBL-TR format which is of InvoiceType type. You can access the contents of the InvoiceType object http://efatura.gov.tr/dosyalar/kilavuzlar/Ek-4UBL-TRKilavuzlari_V-1.2.zip link.
Return Value	Returns instance of the FlagResponse type.

5 Common Objects

In this section, you can find more detailed explanations about the Types that are passed several times in this document.

5.1 BinaryRequestData

Represents a data object which contains a byte[] data and its hash value. The fields are as following.

Property Name	Type	Description
Data	List<Byte>	List of byte data.
Hash	String	Md5 hash of the data which is provided by the Data field.

5.2 ClonedInvoiceInfo

Represents an object which contains the source and newly created invoice Id's.

Property Name	Type	Description
SourceInvoiceId	String	Unique Id of the source invoice
ClonedInvoiceId	String	Unique Id of the newly created cloned invoice.

5.3 CloneInvoiceServiceResponse

Represents an object which contains list of ClonedInvoiceInfo objects.

Property Name	Type	Description
Value	List< ClonedInvoiceInfo >	List of ClonedInvoiceInfo objects.
IsSucceeded	Bool	Represents the status of the operation. If true it is succeeded otherwise not.

Message

String

Mostly it returns the error message in case of not succeeded.

5.4 CustomerInfo

Represents an object which contains the some required information about Customer.

Property Name	Type	Description
VknTckn	String	The VKN or TCKN number of the customer. VKN is for the companies and is 10 length digit, TCKN is for the people and is 11 length digit.
Alias	String	The alis of the customer.
Title	String	The name of the customer.

5.5 DateResponse

Represents and object which contans a datetime information in it.

Property Name	Type	Description
Value	DateTime	Represents the date time value.
IsSucceded	Bool	Represents the status of the operation. If true it is succeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeeded.

5.6 DocumentResponseEntityStatus

Represents the statuses of application response ([DocumentResponseInfo](#)). The values are as following.

Enum Value	Enum Description
Waiting	Document Response is in waiting mode.
Queued	Document Response is Queued and will be processed by Engine as soon as possible.
Processing	Document Response is processing by the engine.
SendToGib	Document Response is processed by the engine and sent to the TRA.
Success	All processes related with this response succeded.
Error	An error occurred during the processing of the DocumentResponse.

5.7 DocumentResponseInfo

Represents an application response information.

Property Name	Type	Description
LineResponses	List< LineResponseInfo >	List of LineResponses.

InvoiceId	String	The unique Id of the invoice which this response is belongs to.
ResponseStatus	DocumentResponseStatus	Represents the type of the DocumentResponse to the Invoice.
Reason	String	The reason for the document response. If it is Declined than why customer declined this invoice can be represented by this property.

5.8 DocumentResponseStatus

Represents the type of the document response code enumeration. Values are as following.

Enum Value	Enum Description
Approved	Represents that invoice is accepted.
Declined	Represents that invoice is declined.
Return	Represents that invoice is returned.

5.9 DocumentResponseStatusInfo

Contains information about a DocumentResponse status.

Property Name	Type	Description
Status	DocumentResponseEntityStatus	Represents the current status of the DocumentResponse.
InvoiceId	String	The unique Id of the invoice which this response is belongs to.
Message	String	Mostly it returns the detailed error message in case of error.

5.10 DocumentResponseStatusResponse

Represents a web service response object for the DocumentResponse status query.

Property Name	Type	Description
Value	List< DocumentResponseStatusInfo >	List of DocumentResponseStatusInfo objects which each one of them contains information for a single invoice.
IsSucceeded	Bool	Represents the status of the operation. If true it is succeeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeeded.

5.11 EArchiveCancelInvoiceContext

Contains required information to cancel an e-archive invoice.

Property Name	Type	Description
---------------	------	-------------

InvoiceId	String	The unique id of the e-archive invoice object.
CancelDate	DateTime	Represents the cancellation date of the invoice.

5.12 EArchiveInvoiceInformation

Represents required information for an e-archive invoice which can not provided by the UBL-TR.

Property Name	Type	Description
NewGenerationPaymentRecorderInfo	NewGenerationPaymentRecorderInformation	[Obsolete]
InternetSalesInfo	InternetSalesInformation	If invoice is a internet sales, it is the object that contains internet sales information.
WithHoldings	List< EArchiveWithHoldingInformation >	[Obsolete]
DeliveryType	InvoiceDeliveryType	Represents the transmitting type of the e-archive invoice.

5.13 EArchiveWithHoldingInformation

OBSOLETE. Do not use this type.

Property Name	Type	Description
Code	String	E-archive invoice's withholding code is kept in this field.
Rate	Decimal	E-archive invoice's withholding rate is kept in this field.
Total	Decimal	Total value indicates in this field.

5.14 EnvelopeStatus

Represents the type of an Envelope. Values are as follows;

Enum Value	Enum Description
Preparing	Envelope is preparing.
EnvelopIsQueued	Envelope is Queued at the moment.
EnvelopIsProcessing	Envelope is processing by the system.
FileIsNotZip	Envelope file is not a zip file.
InvalidEnvelopIdLength	Envelope Id is not a valid envelope identifier (Guid)
EnvelopCouldNotCopiedFromArchive	Could not read envelope from the disk.
CouldNotOpenZip	Could not open zip file.
ZipIsEmpty	Envelope zip does not contains any envelope data.
FileIsNotXml	Envelope file is not a xml file.
EnvelopeIdAndXmlNameMustBeSame	Envelope Identifier and Xml file name is not same.
CouldNotParseDocument	Could not parse (deserialize) the envelope document.

EnvelopeIdNotFound	Could not find Envelope Id
EnvelopeIdAndZipNameMustBeSame	Envelope Id and Zip file names are not same
InvalidVersion	The version of the envelope is invalid
SchematronCheckFailed	Schematron validation check failed
XmlSchemaCheckFailed	Schema check failed.
CouldNotTakeTcknVknForSigner	Could not find Tckn or Vkn information of the signer
CouldNotSaveSignature	Could not save the signature
EnvelopeIdIsAlreadyUsed	Envelope id is already used by the system.
CouldNotCheckPermission	Could not check signer permission.
DoesNotHaveSenderUnitPermission	You don't have sender unit permission to send this envelope.
DoesNotHavePostBoxPermission	Receiver does not have a postbox permission to receive this envelope.
CouldNotCheckSignPermission	Could not check the signer permission
SignerHasNoPermission	Signer has no permission to sign this document.
IllegalSign	Illegal sign
CouldNotCheckAddress	Could not check the address of the document.
AddressNotFound	The receiver address does not found in the system.
DoesNotHaveEntegratorApplication	You do not have any entegrator account.
CouldNotPrepareSystemResponse	System message could not be prepared.
SystemError	An error occurred during the processing the envelope.
EnvelopedProcessSuccessfully	Envelope processed successfully.
CouldNotSendDocumentToTheAddress	Could not send Envelope to receiver address.
DocumentSendingFailedWillNotRetry	Document could not send to the receiver address and will not try anymore.
TargetDoesNotSendSystemResponse	Receiver of the document does not send a system response for this envelope.
TargetSendFailedSystemResponse	Receiver of the envelope sent a failed system response.
CompletedSuccessfully	All operations related with this envelope completed successfully.

5.15 FlagResponse

Represents a true/false response for the web service operations.

Property Name	Type	Description
Value	Bool	Represents the result of the operation. If true then the operation completed successfully, otherwise there is an error.
IsSucceeded	Bool	Represents the status of the operation. If true it is succeeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeeded.

5.16 InboxInvoiceListItem

Represents meta data information of a single inbox invoice object. The fields are as following.

Property Name	Type	Description
IsNew	Bool	Represents that is this invoice processed by the client before. Whenever a new inbox invoice is received to the system this flag is set to true. Client must set to false this flag when they take this invoice from the server. This parameter is very usefully to synchronize your system with the integrator system.
InvoiceId	String	Represents Invoice Number.
DocumentId	String	Represents invoice unique document identifier.
Type	InvoiceTypes	Represents the type of the Invoice.
TargetTcknVkn	String	Represents the Tckn or Vkn of the sernder of the invoice.
TargetTitle	String	Represents the title of the sender of the invoice.
EnvelopeIdentifier	String	Represents the unique identifier of the Envelope which contains this invoice.
Status	InvoiceStatus	Represents the status of an invocie.
EnvelopeStatus	EnvelopeStatus	Represents the status of the envelope which contains this invoice.
Message	String	Mostly it returns the error message in case of error.
CreateDateUtc	DateTime	Represent the creation date of the invoice in UTC format.
ExecutionDate	Nullable<DateTime>	Represents the execution date of the invoice.
PayableAmount	Decimal	Represents the payable amount of the invoice.
TaxTotal	Decimal	Represents the total tax amount of the invoice.

5.17 InboxInvoiceListQueryModel

Represents a filter context for querying inbox invoices. Fields are as follows;

Property Name	Type	Description
PageSize	Int	Represents the number of items in a single page.
PageIndex	Int	Represents the index of the page which is queried. Index is 0 based.
InvoiceIds	List<String>	The unique id's of the invoices that will be queiried.
OnlyNewestInvoices	Bool	Filters only invoices whichs IsTaken property is false.
ExecutionStartDate	System.Nullable<System.DateTime>	Start date filter for the execution date property of the invoice.
ExecutionEndDate	System.Nullable<System.DateTime>	End date filter for the execution date property of the invoice.

CreateStartDate	System.Nullable<System.DateTime>	Start date filter for the Creation date of the invoice.
CreateEndDate	System.Nullable<System.DateTime>	End date filter for the Creation date of the invoice.
Status	InvoiceStatus	Status filter for the invoice

5.18 InboxInvoiceListResponse

Represents a web service response object for the inbox invoices list query. Fields are as follows;

Property Name	Type	Description
Value	PagedResponseOfInboxInvoiceListItem	Contains the result items.
IsSucceeded	Bool	Represents the status of the operation. If true it is succeeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeeded.

5.19 InboxInvoiceQueryModel

Represents a filter context for querying inbox invoices. Fileds are as follows;

Property Name	Type	Description
PageSize	Int	Represents the number of items in a single page.
PageIndex	Int	Represents the index of the page which is queried. Index is 0 based.
InvoiceIds	List<String>	The unique id's of the invoices that will be queried.
OnlyNewestInvoices	Bool	Filters only invoices whichs IsTaken property is false.
SetTaken	Bool	Represents that the returning invoices IsNew flag will be changed to false or not?
ExecutionStartDate	System.Nullable<System.DateTime>	Start date filter for the execution date property of the invoice.
ExecutionEndDate	System.Nullable<System.DateTime>	End date filter for the execution date property of the invoice.

5.20 InternetSalesInformation

Represents an object which contains extra information for e-archive invoices which are also internet sales. Fields are as follows;

Property Name	Type	Description
WebAddress	String	Represents the web address.
PaymentMidierName	String	Represents the name of the payment midier.

PaymentType	String	Represents the type of the payment.
PaymentDate	Nullable<DateTime>	Represents the date fo the payment.
ShipmentInfo	ShipmentInformation	Contains information related with the Shipping.

5.21 InvoiceData

Represents an object which provides file data of the invoice. The fields are as follows;

Property Name	Type	Description
Data	List<Byte>	The binary data of the file.
LocalDocumentId	String	Represents the LocalDocumentId of the invoice.
ExtraInformation	String	Represents the extra information of the invoice.
InvoiceId	String	Represents the unique Id of the invoice.

5.22 InvoiceDataResponse

Represents the web service response object for the Invoice data. The fields are as follows;

Property Name	Type	Description
Value	InvoiceData	You can see details about this object here .
IsSucceeded	Bool	Represents the status of the operation. If true it is succeeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeeded.

5.23 InvoiceDeliveryType

Enumeration that represents the type of the e-archive invoice delivery.

<u>Enum Value</u>	Enum Description
Paper	Invoice is delivered as paper.
Electronic	Invoice is delivered by electronically.

5.24 InvoiceIdentitiesResponse

Represents web service response for the InvoiceIdentity objects. The fields are as follows;

Property Name	Type	Description
Value	List< InvoiceIdentity >	List of InvoiceIdentity elements.
IsSucceeded	Bool	Represents the status of the operation. If true it is succeeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeeded.

5.25 InvoiceIdentity

Represents an object which contains identity informations of an invoice. The fields are as follows;

Property Name	Type	Description
Id	String	Represents the unique id of an invoice.
Number	String	Represents the invoice number of an invoice. It is in format AAAYYYNNNNNNNN where AAA indicates a prefix and may differ according to the customer. YYYY specifies 4 digit year. NNNNNNNNN is the value of the 9 digit number that indicates the customer's ordered invoice number in the given prefix and year.
InvoiceScenario	InvoiceScenarioType	Represents the scenario type of the invoice.

5.26 InvoiceInfo

Represents invoice information object which will be used to send/take invoices from/to system. The fields are as follows;

Property Name	Type	Description
Invoice	InvoiceType	It specifies the invoice data object in UBL-TR format. You can see details in following link. http://efatura.gov.tr/dosyalar/kilavuzlar/Ek-4UBL-TRKilavuzlari_V-1.2.zip
TargetCustomer	CustomerInfo	Represents the invoice receiver information for the Outbox invoices and Sender information for the Inbox invoices.
EArchiveInvoiceInfo	EArchiveInvoiceInformation	If invoice is an e-archive invoice this field represents the extra information of the e-archive invoice which can not be represented through the InvoiceType.
Scenario	InvoiceScenarioChosen	Represents the type of the invoice scenario chosen of the customer.
Notification	NotificationInformation	Contains notification information related with this invoice. If invoice will be processed successfully these notifications will be also run by the system.
LocalDocumentId	String	Represents a string value which customers can use this value to synchronize integrator system with their own systems. You can send unique invoice identifier of your system and use this value to synchronize your system with our system.
ExtraInformation	String	Represents an extra string value like LocalDocumentId. You can use this value to synchronize invoices with your system too.

5.27 InvoiceLogItem

Represents a log object for the invoices. The fields are as follows;

Property Name	Type	Description
---------------	------	-------------

Creator	String	User who takes action to cause this log record.
CreateDateUtc	DateTime	Represents the creation date of the log record in Utc format.
RemoteIpAddress	String	Represents the remote ip address of the requester who cause this log record.
LocalIpAddress	String	Represents the local server ip which this log record was created on.
MachineName	String	Represents the name of the server which this log record was created.
Type	Byte	Represents the type of the Log record.
Message	String	Represents the log message.

5.28 InvoiceQueryModel

Represents an object which can be used to query invoices. The fields are as follows;

Property Name	Type	Description
ExecutionStartDate	Nullable<System.DateTime>	Start date filter for the invoice execution date.
ExecutionEndDate	Nullable<System.DateTime>	End date filter for the invoice execution date.
InvoiceIds	List<String>	The list of the invoice unique ids which will be filtered.
PageIndex	Int	Represents the page number of the current page. PageIndex is 0 based.
PageSize	Int	Represents the number of items in a page.

5.29 InvoiceResponse

Represents a web service response for the invoice objects.

Property Name	Type	Description
Value	InvoiceInfo	Represents invoice information.
IsSucceeded	Bool	Represents the status of the operation. If true it is succeeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeeded.

5.30 InvoiceScenarioChosen

It's the enum that is used to invoice senarios (e-archive, e-invoice) of the choosen by System User. Members are as follows;

Enum Values	Description
Automated	System will automatically chose the scenario according to the target customer TCKN/VKN.
eInvoice	If the target customer is an e-invoice user, it is processed as e-invoice otherwise it returns error.
eArchive	If the target customer is an e-invoice user, returns error otherwise processes as e-archive.
MusteArchive	Always processed as e-archive invoice.

5.31 InvoiceScenarioType

Represents type type of the Invoice scenario. Members are as follows;

Enum Values	Description
EInvoice	It is electronic invoice senario (e-Invoice)
EArchive	It is electronic archive invoice senario (e-Archive)

5.32 InvoicesDataResponse

Represents an object which web service will returns for the Invoice data queries. The members are as follows;

Property Name	Type	Description
Value	PagedResponseOfInvoiceData	Paged list of the InvoiceData objects.
IsSucceded	Bool	Represents the status of the operation. If true it is succeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeded.

5.33 InvoicesResponse

Represents an object which web service will returns for the invoice queiries. The members are as follows;

Property Name	Type	Description
Value	PagedResponseOfInvoiceInfo	Paged list of the InvoiceInfo objects.
IsSucceded	Bool	Represents the status of the operation. If true it is succeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeded.

5.34 InvoiceStatus

Enumeration which identifies the status of an invoice. The members are as follows;

Enum Value	Description	Code
Draft	Invoice is in Draft status.	0
Canceled	Invoice is in Cancel status.	10
Queued	Invoice is in Queued status.	100
Processing	Invoice is Processing at the moment.	200
SentToGib	Invoice is sent to TRA.	300
Approved	Invoice is in approved status.	1000
WaitingForAppovement	Invoice is in waiting for appovement status.	1100
Declined	Invoice is in declined status.	1200
Return	Invoice is in returned status.	1300
eArchiveCanceled	Invoice is in e-archive canceled status. The difference between Canceled and e-ArchiveCanceled is that, Canceled invoices will not report to the TRA with the e-archive report but the EArchvieCanceled invoices will be reported.	1400
Error	Invoice is in Error status.	2000

5.35 InvoiceStatusInfo

Represents an object which contains information about an invoice status. The fields are as follows;

Property Name	Type	Description
Status	InvoiceStatus	Represents the status of the invoice.
InvoiceId	String	The unique id of the invoice.
Message	String	More detailed information about the status.

5.36 InvoiceStatusResponse

Represents a web service response object which returns the status information of queiried invoices. The fields are as follows;

Property Name	Type	Description
Value	List< InvoiceStatusInfo >	List of InvoiceStatusInfo objects.
IsSucceded	Bool	Represents the status of the operation. If true it is succeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeded.

5.37 InvoiceStatusWithLogInfo

Represents an object which contains information about an invoice status and logs. The fields are as follows;

Property Name	Type	Description
---------------	------	-------------

LocalDocumentId	String	Represents the LocalDocumentId of the invoice which customers can use this value to synchronize invoices with their system.
Logs	List< InvoiceLogItem >	List of InvoiceLogItem objects.
Status	InvoiceStatus	Represents the status of the invoice.
InvoiceId	String	The unique id of the invoice.
Message	String	More detailed information about the status.

5.38 InvoiceStatusWithLogResponse

Represents a web service response object which returns the status information and logs of the queried invoices. The fields are as follows;

Property Name	Type	Description
Value	List< InvoiceStatusWithLogInfo >	List of InvoiceStatusWithLogInfo objects.
IsSucceeded	Bool	Represents the status of the operation. If true it is succeeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeeded.

5.39 InvoiceTypes

Enumration represents the types of the invoices. Members are as follows;

Enum Values	Description
BaseInvoice	Invoice is Base invoice.
ComercialInvoice	Invoice is a Commercial Invoice.
InvoiceWithPassenger	Invoice is a Invoice With Passenger type.

5.40 InvoiceViewResponse

Represents a web service response object which returns the invoice view as html. The members are as follows;

Property Name	Type	Description
Value	List< ViewResult >	List of ViewResult objects for each invoice.
IsSucceeded	Bool	Represents the status of the operation. If true it is succeeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeeded.

5.41 LineResponseInfo

Represents an object which contains the required information about a line response. Fields are as follows;

Property Name	Type	Description
LineNumber	Int	Represents the number of invoice line which this line response is belongs to.
Description	String	Represents the response of the line.

5.42 MailAttachmentInformation

Represents an object which identifies required information about mail attachment. Fields are as follows;

Property Name	Type	Description
Xml	Bool	Does invoice xml will be attached to the mail or not?
Pdf	Bool	Does invoice pdf will be attached to the mail or not?
Html	Bool	Does invoice html view will be attached to the mail or not?

5.43 MailingInformation

Represents the mailing information for an invoice. The fields are as follows;

Property Name	Type	Description
Subject	String	Represents the mail subject.
Attachment	MailAttachmentInformation	Represents the attachment information of the mailing.
EnableNotification	Bool	If true mail notification will be send otherwise not.
To	String	Represents the mail address to whom this notification will be send.
BodyXsltIdentifier	String	Represents the mail body xslt identifier. If null, customer default mailing xslt will be used. If customer has no default xslt for mailing then system default xslt for mailing will be used.
EmailAccountIdentifier	String	Represents the email account identifier which mailing will be done by using that account. If null customer default email account will be used. If customer has no default email account then system email account will be used.

5.44 NewGenerationPaymentRecorderInformation

Represents the New generation oayment recorder information of the invoice. This is obsolete do not use this object.

Property Name	Type	Description
PaperNumber	String	The paper number is kept in this area.
PaperDate	DateTime	The paper date is kept in this area.
SerialNumber	String	The serial number is kept in this area.

ZNumber

String

The Z number is kept in this area.

5.45 NotificationInformation

Represents the notification information of an invoice. The fields are as follows;

Property Name	Type	Description
Mailing	List< MailingInformation >	The list of MailingInformation objects.

5.46 OutboxInvoiceListQueryModel

Represents a filter context for querying outbox invoices. Fields are as follows;

Property Name	Type	Description
Scenario	InvoiceScenarioType	Represents the type of the invoice scenario for filtering.
PageSize	Int	Represents the number of items in a single page.
PageIndex	Int	Represents the index of the page which is queried. Index is 0 based.
InvoiceIds	List<string>	The unique id's of the invoices that will be queried.
OnlyNewestInvoices	Bool	Filters only invoices whichs IsTaken property is false.
ExecutionStartDate	DateTime	Start date filter for the execution date property of the invoice.
ExecutionEndDate	DateTime	End date filter for the execution date property of the invoice.
CreateStartDate	DateTime	Start date filter for the Creation date of the invoice.
CreateEndDate	DateTime	End date filter for the Creation date of the invoice.

5.47 OutboxInvoiceListResponse

Represents a web service response object for the outbox invoices list query. Fields are as follows;

Property Name	Type	Description
Value	List< InvoiceIdentity >	Contains the result items.
IsSucceeded	Bool	Represents the status of the operation. If true it is succeeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeeded.

5.48 PagedQueryContext

Represents an object which can be used for paged query. The fields are as follows;

Property Name	Type	Description
---------------	------	-------------

PageSize	Int	Represents the number of items in a single page.
PageIndex	Int	Represents the index of the page which is queried. Index is 0 based.

5.49 PagedResponseOfInboxInvoiceListItem

Represents an object which contains the [InboxInvoiceListItem](#) as paged. The fields are as follows;

Property Name	Type	Description
Items	List< InboxInvoiceListItem >	The list of the items at the current page.
PageIndex	Int	Represents the index of the page which is queried. Index is 0 based.
PageSize	Int	Represents the number of items in a single page.
TotalCount	Int	Represents the total number of items.
TotalPages	Int	Represents the total number of pages.

5.50 PagedResponseOfInvoiceData

Represents an object which contains the [InvoiceData](#) objects as paged. The fields are as follows;

Property Name	Type	Description
Items	List< InvoiceData >	The list of items at the current page.
PageIndex	Int	Represents the index of the page which is queried. Index is 0 based.
PageSize	Int	Represents the number of items in a single page.
TotalCount	Int	Represents the total number of items.
TotalPages	Int	Represents the total number of pages.

5.51 PagedResponseOfInvoiceInfo

Represents an object which web service returns as the list of [InvoiceInfo](#) objects. The fields are as follows;

Property Name	Type	Description
Items	List< InvoiceInfo >	The list of items at the current page.
PageIndex	Int	Represents the index of the page which is queried. Index is 0 based.
PageSize	Int	Represents the number of items in a single page.
TotalCount	Int	Represents the total number of items.
TotalPages	Int	Represents the total number of pages.

5.52 PagedResponseOfSystemUser

Represents an object which web service returns as the list of the System users. The fields are as follows;

Property Name	Type	Description
Items	List< SystemUser >	The list of items at the current page.
PageIndex	Int	Represents the index of the page which is queried. Index is 0 based.
PageSize	Int	Represents the number of items in a single page.
TotalCount	Int	Represents the total number of items.
TotalPages	Int	Represents the total number of pages.

5.53 ShipmentCarrier

Represents an object which contains the Shipment Carrier information for the e-archive invoices. The fields are as follows;

Property Name	Type	Description
SenderTcknVkn	String	Represents the sender TCKN or VKN.
SenderName	String	Represents the name of the sender.

5.54 ShipmentInformation

Represents the shipment information for e-archive invoices. The fields are as follows;

Property Name	Type	Description
SendDate	System.Nullable<System.DateTime>	Represents the shipment date.
Carrier	ShipmentCarrier	Represents the shipment carrier information

5.55 SystemUser

System users means that the users in the TRA e-invoice system. System users are managed by the TRA and system automatically update the list in every one hour. You can query, get the users list from web services.

Property Name	Type	Description
Identifier	String	Represents the TCKN or VKN of the user.
PostboxAlias	String	Represents the Postbox alias of the user.
SenderboxAlias	String	Represents the Senderbox alias of the user. [Obsolete]
Title	String	Represents the name of the system user.
Type	String	This field contains one of the following values: "Kamu" means that registered tax payer is a governmental organization and "Özel" for private organizations.
SystemCreateDate	String	Represents the date of this aliases registration in the TRA system.
FirstCreateDate	String	Represents the first registration date of this tax payer in the TRA e-invoice system.
Enabled	Bool	Represents that is this alias active or not?

5.56 SystemUserAlias

Represents an alias information of a tax payer. The fields are as follows;

Property Name	Type	Description
Alias	String	Represents the alias.
Type	AliasType	Represents the type of the alias.
SystemCreateDate	String	Represents the creation date of the alias in the TRA system.
Enabled	Bool	Represents that is this alias active or not?

5.57 AliasType

Enumeration which identifies the type of the aliases.

Enum Values	Description
Receiverbox	Receiverbox alias means that system users can receive invoice to this address.
Senderbox	Senderbox alias means that system users can send invoice from this alias.

5.58 SystemUserDefinition

Represents a master definition of a tax payer record in the e-invoice system of TRA. Every single company or person has a single SystemUserDefinition record in the system. Their aliases will be related to this record and identified as SystemUser. The fields are as follows;

Property Name	Type	Description
Identifier	String	Represents the VKN / TCKN of the tax payer.
CreateDateUtc	DateTime	Represents the create date of the system user in integrator system as Utc format.
Title	String	Represents the name of the system user.
Type	String	This field contains one of the following values: "Kamu" means that registered tax payer is a governmental organization and "Özel" for private organizations.
SystemCreateDate	String	Represents the date of this aliases registration in the TRA system.

5.59 SystemUsersResponse

Represents an object which web service uses to return to the System User queries.

Property Name	Type	Description
Value	PagedResponseOfSystemUser	The paged list of the SystemUsers.

IsSuccesed	Bool	Represents the status of the operation. If true it is succeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeded.

5.60 SystemUserWithAlias

Represents an object which contain the required information for a system user and all its aliases. The fields are as follows;

Property Name	Type	Description
Definition	SystemUserDefinition	Represents the definition of the system user.
ReceiverboxAliases	List< SystemUserAlias >	The list of the receiverbox aliases of the system user.
SenderboxAliases	List< SystemUserAlias >	The list of the senderbox aliases of the system user.

5.61 UserAliasesResponse

Represents an object which web service returns to the system user queries. The fields are as follows;

Property Name	Type	Description
Value	SystemUserWithAlias	Represents the SystemUserWithAlias information.
IsSuccesed	Bool	Represents the status of the operation. If true it is succeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeded.

5.62 VerificationResult

Represents an object which contains the information about an invoice signature verification. The fields are as follows;

Property Name	Type	Description
Data	String	Represents the detailed verification result.
SigningDate	System.Nullable<System.DateTime>	Represents the date and time information of the invoice signature.
IsVerified	Bool	Represents that is signature verified or not?

5.63 ViewResult

Represents an invoice html view result object including its signature verification information. The fields are as follows;

Property Name	Type	Description
Html	String	Represents the tranformed html view of the invoice.

Verification	VerificationResult	Represents the verification information of the invoice.
IsUsingDefaultXslt	Bool	Indicates that is default xslt used to transform the invoice to html or not?

5.64 XsltViewType

Enumeration that represents the type of the Xslt's. The members are as follows;

Enum Value	Description
Invoice	Invoice xslt.
ApprovedInvoice	Approve Invoice application response xslt.
CancelInvoice	Cancel Invoice application response xslt.
eArchiveDefaultInvoice	e-Archive invoice default xslt.
eArchiveInternetSalesInvoice	e-Archive Internet Sales invoice xslt.
EmailBody	Represents an xslt which will be used as the body transformation to send an invoice to someone with email.
Ticket	Ticket xslt.
PassengerList	Passenger list xslt.

5.65 Response

Represents an empty web service response object which does not contains any Value field. The fields are as follows;

Property Name	Type	Description
IsSuccesed	Bool	Represents the status of the operation. If true it is succeded otherwise not.
Message	String	Mostly it returns the error message in case of not succeded.