



e-Irsaliye®

Web Servis ve Entegrasyon Kılavuzu

24.09.2018

V1.4

İçindekiler

1 Introduction.....	6
1.1 Content.....	6
1.2 Description.....	6
2 Contents	7
2.1 Definitons	7
2.2 TRA e-Despach System.....	7
3 Uyumsoft E-Despach System.....	8
3.1 E-Despach Structure.....	8
3.1.1 Aplication Responses.....	8
3.2 Uyumsoft Customer Web Services.....	8
4 Web Service Methods	10
4.1 CancelDrafts.....	10
4.2 ChangeDespachArchiveStatus	10
4.3 CloneDespatches.....	10
4.4 CompressedSaveAsDraft	10
4.5 CompressedSendDespatch	11
4.6 GetEDespachUsers.....	11
4.7 GetInboxDespatch.....	11
4.8 GetInboxDespatches	11
4.9 GetInboxDespatchesData	12
4.10 GetInboxDespatchList	12
4.11 GetInboxDespatchPdf.....	12
4.12 GetInboxDespatchStatusWithLogs.....	12
4.13 GetInboxDespatchView	13
4.14 GetOutboxDespatch	13
4.15 GetOutboxDespatches	13

4.16 GetOutboxDespatchesData	13
4.17 GetOutboxDespatchList.....	13
4.18 GetOutboxDespatchPdf.....	14
4.19 GetOutboxDespatchStatusWithLogs.....	14
4.20 GetOutboxDespatchView	14
4.21 GetUserAliases	14
4.22 GetSystemDate	15
4.23 IsEDespatchUser	15
4.24 QueryInboxDespatchStatus	15
4.25 QueryOutboxDespatchStatus	15
4.26 QueryReceiptAdviceStatus	16
4.27 RetrySendDespatches.....	16
4.28 SaveAsDraft.....	16
4.29 SendDespatch	16
4.30 SendReceiptAdvice.....	16
4.31 SendDraft.....	17
4.32 SetDespatchesTaken	17
4.33 SetDespatchReceiptAdvicesTaken	17
5 Common Objects	18
5.1 BinaryRequestData.....	18
5.2 ClonedDespatchInfo	18
5.3 ClonedDespatchServiceResponse	18
5.4 CustomerInfo	18
5.5 DateResponse	19
5.6 DespatchData.....	19
5.7 DespatchesDataResponse	19
5.8 DespatchesResponse.....	20
5.9 DespatchIdentitiesResponse	20
5.10 DespatchIdentity	20
5.11 DespatchInfo.....	20
5.12 DespatchLogItem	21

5.13 DespatchProfileType	21
5.14 DespatchResponse	21
5.15 DespatchStatus	22
5.16 DespatchStatusInfo	22
5.17 DespatchStatusResponse	23
5.18 DespatchStatusWithLogInfo	23
5.19 DespatchStatusWithLogResponse	23
5.20 DespatchTypeEnum.....	24
5.21 DespatchViewResponse	24
5.22 FlagResponse	24
5.23 InboxDespatchListItem	24
5.24 InboxDespatchListItemLine	26
5.25 InboxDespatchListQueryModel	27
5.26 InboxDespatchListResponse	28
5.27 InboxDespatchQueryModel.....	28
5.28 MailAttachmentInformation.....	29
5.29 MailingInformation	29
5.30 NotificationInformation.....	30
5.31 OutboxDespatchListItem	30
5.32 OutboxDespatchListItemLine.....	32
5.33 OutboxDespatchListQueryModel.....	33
5.34 OutboxDespatchListResponse	34
5.35 OutboxDespatchQueryModel	34
5.36 PagedQueryContext	35
5.37 PagedResponseOfDespatchData.....	35
5.38 PagedResponseOfDespatchInfo.....	35
5.39 PagedResponseOfInboxDespatchListItem.....	36
5.40 PagedResponseOfOutboxDespatchListItem	36
5.41 PagedResponseOfSystemUser	37
5.42 ReceiptAdviceInfo	37
5.43 ReceiptAdviceLineInfo	37

5.44 ReceiptAdviceStatus.....	38
5.45 ReceiptAdviceStatusInfo.....	38
5.46 ReceiptAdviceStatusResponse	39
5.47 Response.....	39
5.48 SmsMessageInformation.....	39
5.49 SystemUser	40
5.50 SystemUserAlias.....	40
5.51 SystemUserDefinition.....	41
5.52 SystemUsersResponse.....	41
5.53 SystemUserWithAlias	41
5.54 UserAliasesResponse	42
5.55 VerificationResult.....	42
5.56 ViewResult	42

1 Introduction

1.1 Content

This document covers Uyumsoft solution e-despatch web service objects, methods, and concepts to ensure a healthy integration

1.2 Description

Abbreviation	Description
--------------	-------------

VKN	Tax Identification Number
-----	---------------------------

TCKN	Identity Number
------	-----------------

TRA	Turkish Revenue Administration
-----	--------------------------------

UBL	Universal Bussiness Language
-----	------------------------------

2 Contents

2.1 Definitons

UBL-TR: This is the format of Universal Business Language(UBL) that is adapted to Turkey which is internalized by TRA. This format provides a common system which makes companies communicate with each other

UBL-TR Despatch: A part of UBL-TR format that is assigned for e-despatch. TRA system manages the e-despatch document flow between companies with XML format.

StandartDocumentBusinessHeader: A standard format that is designated for the document flow between companies. It is called “envelope” by TRA system.

e-Despatch: The despatch format that is prepared with the UBL-TR standards. The center of e-Despatch system is managed by the TRA. TRA manages the intermediary system between companies. E-Despatches are transmitted by TRA system to the systems of companies when they send e-despatches to each other.

Envelope: It is an XML file that prepared according to the TRA UBL-TR standards which XML file/files prepared with “StandartDocumentBusinessHeader”.

2.2 TRA e-Despacth System

TRA provides documents created by compressing them into zip format and placing them within envelopes are distributed among systems that integrate with it.

After the envelopes sent to TRA arrive, the mailbox (alias) information in the envelope's main details is checked by TRA and sent to the system where the recipient's mailbox is located. After receiving this envelope, if there is an error in the waybill documents inside the envelope, the recipient creates an envelope indicating the error, or if there is no error, an envelope indicating that the process was successful and sends it back to TRA. This envelope received by TRA directs to the sender, and completes the document transmission process between the parties.

3 Uyumsoft E-Despatch System

3.1 E-Despatch Structure

E-despatch covered by envelope file format before it's sent to TRA system. Every envelope which is created by Uyumsoft system has only one e- despatch in it even TRA system supports multiple despatches in an envelope file format.

Uyumsoft system manages despatch status and envelope status separately. Every envelope status change effects the despatch status. Querying only despatch status ignoring the envelopes is enough to provide the healthy system integration. Instead of managing many technical status codes, it is possible to control only despatch status basically.

Some of check points can be implemented by using the despatch status query methods of web service by developers.

Receival of despatches by Uyumsoft system should not be assumed as completed process. Integrated system should implement a mechanism to be sure if the despatches are received by the consumer party successfully.

Developers are provided with an object named "DespatchInfo" to enable sending despatches via web services. The content of this object is as below:

Despatch: The despatch object is in the DespatchAdviceType format in UBL-TR. It can be serialized into XML. The XML in UBL-TR format can be deserialized into the "Despatch" (DespatchAdvice) object in a file. The fields in this object are detailed in the UBL-TR guides published by TRA.

LocalDocumentId: The identifier ID of the despatch in the sender's own accounting/ERP system. With this ID, resending of despatches with the same ID can be prevented or various control structures can be created.

3.1.1 Application Responses

Application responses are the "Accepted", "Rejected" and "Partial Accepted" documents that are sent as a response of commercial e-despatch documents. Only outgoing despatches has application response documents as a response.

3.2 Uyumsoft Customer Web Services

Uyumsoft solution has web services for the connectivity of other systems which handles despatch information of companies. Uyumsoft is the system which is connected to TRA e-Despatch system and can be used both in private integration and direct integration model. Required informations to generate despatches received by Uyumsoft web service. Data that is sent to Uyumsoft web service processed to build e-despatch format for transferring to TRA system. All status changes that are received by TRA system handled by Uyumsoft solution. Also digital sign, creation of envelope packages and transmission is handled by Uyumsoft solution.

Uyumsoft web services can be reached by following addresses:

Live System: <https://efatura.uyumsoft.com.tr/Services/DespatchIntegration>

Test System: <https://efatura-test.uyumsoft.com.tr/Services/DespatchIntegration>

(Username: Uyumsoft, Password: Uyumsoft)

During the development process, the Uyumsoft Test Portal can be used as a user interface to list and to do some actions on despatches.

Test Portal: <https://portal-test.uyumsoft.com.tr/>

(Username: Uyumsoft, Password: Uyumsoft)

4 Web Service Methods

4.1 CancelDrafts

Cancels despatches which are in Draft status. Sets the status of despatches as canceled.

Method Signature `FlagResponse CancelDraft(List<string>despatchIds)`

Parameters `despatchIds`: One or more despatch IDs are sent with this parameter. It corresponds to the UBL-TR's UUID Parameters field.

Return Value Returns an instance of a `FlagResponse` type.

4.2 ChangeDespatchArchiveStatus

Provides users to put/remove "Archived" flag to their despatches.

This method can be applied to both Inbox and Outbox despatches.

Method Signature `FlagResponse`

`ChangeDespatchArchiveStatus(List<string>despatchesId, bool isInbox, bool isArchived)`

Parameters `despatchesId`: The list of despatch IDs which their archive flag will be changed. Despatch ID is the unique ID of a despatch which is represented by the UUID element of the UBL Despatch object.

`isInbox`: Represents the type of the despatches in the `despatchIds` list. True for the Inbox despatches, false for the Outbox despatches.

`isArchived`: If true, Archive flag will be applied to the given despatches otherwise Archive flag will be removed from the given despatches.

Return Value Returns an instance of a `FlagResponse` type.

4.3 CloneDespatches

The method that copies the despatch sent as a parameter and saves it to drafts, automatically resets the signature and UUID information of the copied despatch during the copying process, and optionally resets the despatch number to zero.

Method Signature `ClonedDespatchServiceResponse CloneDespatches(List<string>despatchesIds)`

Parameters `despatchIds`: One or more despatch IDs sent with this parameter. It corresponds to the UUID field in UBL-TR.

Return Value Returns an instance of a `ClonedDespatchServiceResponse` type.

4.4 CompressedSaveAsDraft

Provides functionality to save despatches in zip format to save as Draft and changes to be made as requested in the draft. This method has the same functionality as the `SaveAsDraft` method.

Method Signature	DespatchIdentitiesResponse
CompressedSaveAsDraft(BinaryRequestData data)	
Parameters	data: An instance of the BinaryRequestData type which contains the binary of the compressed data.
Return Value	Returns an instance of a DespatchIdentitiesResponse type.

4.5 CompressedSendDespatch

Provides functionality to send despatches in zip format to reduce the size of the data. This method has the same functionality as the [SendDespatch](#) method.

Method Signature	DespatchIdentitiesResponse
CompressedSendDespatch(BinaryRequestData data)	
Parameters	data: An instance of the BinaryRequestData type which contains the binary of the compressed data.
Return Value	Returns an instance of a DespatchIdentitiesResponse type.

4.6 GetEDespatchUsers

Provides functionality to query registered e-despatch users and their aliases in the TRA system.

Method Signature	SystemUsersResponse GetEDespatchUsers(PagedQueryContext pagination)
Parameters	Pagination: An instance of the PagedQueryContext type which contains required information to query system users as paged.
Return Value	Returns an instance of a SystemUsersResponse type.

4.7 GetInboxDespatch

Returns a single inbox despatch in UBL-TR format. This method processes only incoming despatches.

Method Signature	DespatchResponse GetInboxDespatch(string despatchId)
Parameters	despatchId: It is the unique identifier that taxpayers want to integrate with their own systems. It corresponds to the UUID field in UBL-TR format.
Return Value	Returns an instance of a DespatchResponse type.

4.8 GetInboxDespatches

This method provides for the retrieval of despatches that comply with filtering criteria by paginating them. This method only covers the incoming despatches.

Method Signature	DespatchesResponse
GetInboxDespatches(InboxDespatchQueryModel query)	
Parameters	query: An instance of the InboxDespatchQueryModel type

Return Value Returns an instance of a [DespatchesResponse](#) type.

4.9 GetInboxDespatchesData

Provides functionality to query Inbox despatches and returns the binary data of these despatches without applying any formatting to protect signatures of these despatches which are meet the given criteria. You can run signature validation check on these despatches. Only covers the incoming despatches.

Method Signature DespatchesDataResponse
GetInboxDespatchesData(InboxDespatchQueryModel query)

Parameters query: An instance of the [InboxDespatchQueryModel](#) type

Return Value Returns an instance of a [DespatchesDataResponse](#) type.

4.10 GetInboxDespatchList

This method retrieves the header information of the despatches that meet the filtering criteria as a list. Only covers the incoming despatches.

Method Signature InboxDespatchListResponse
GetInboxDespatchList(InboxDespatchListQueryModel query)

Parameters query: An instance of the [InboxDespatchListQueryModel](#) type.

Return Value Returns an instance of a [InboxDespatchListResponse](#) type.

4.11 GetInboxDespatchPdf

Transforms an Inbox despatch to Pdf and returns the data of the pdf as byte array.

Method Signature DespatchesDataResponse GetInboxDespatchPdf(string despatchId)

Parameters despatchId: The unique identifier that taxpayers want to integrate with their own systems. It corresponds to the UUID field in UBL-TR format.

Return Value Returns an instance of a [DespatchesDataResponse](#) type.

4.12 GetInboxDespatchStatusWithLogs

This is a method that takes one or more despatches and envelopes passed as parameters and returns their statuses and corresponding log records.

Method Signature DespatchStatusWithLogResponse
GetInboxDespatchStatusWithLogs(List<string> despatchIds)

Parameters despatchIds: One or more despatch IDs send with this parameter. It corresponds to the UUID field in UBL-TR.

Return Value Returns an instance of a [DespatchStatusWithLogResponse](#) type.

4.13 GetInboxDespatchView

Transforms an Inbox despatch to html and returns the html string including with the verification information.

Method Signature	DespatchViewResponse GetInboxDespatchView(string despatchId)
Parameters	despatchId: The unique identifier that taxpayers want to integrate with their own systems. It corresponds to the UUID field in UBL-TR format.
Return Value	Returns an instance of a DespatchViewResponse type.

4.14 GetOutboxDespatch

Returns a single outbox despatch in UBL-TR. Only processes outgoing despatches.

Method Signature	DespatchResponse GetOutboxDespatch(string despatchId)
Parameters	despatchId: The unique identifier that taxpayers want to integrate with their own systems. It corresponds to the UUID field in UBL-TR format.
Return Value	Returns an instance of a DespatchResponse type.

4.15 GetOutboxDespatches

Provides functionality to query Outbox despatches and returns the list of the despatches in UBL-TR format which are meet the given criteria. Only processes outgoing despatches.

Method Signature	DespatchesResponse GetOutboxDespatches(OutboxDespatchQueryModel query)
Parameters	query: An instance of the OutboxDespatchQueryModel type
Return Value	Returns an instance of a DespatchesResponse type.

4.16 GetOutboxDespatchesData

Returns binary data of a single given outbox despatch. This method returns the despatch without apply any formatting to protect the signature of the despatch. You can run signature validation check on this despatch. Only processes outgoing despatches.

Method Signature	DespatchesDataResponse GetOutboxDespatchesData(OutboxDespatchQueryModel query)
Parameters	query: An instance of the OutboxDespatchQueryModel type
Return Value	Returns an instance of a DespatchesDataResponse type.

4.17 GetOutboxDespatchList

Provides functionality to query Outbox despatches and returns the list of the despatches metadata which are meet the given criteria. Only processes outgoing despatches.

Method Signature	OutboxDespatchListResponse GetOutboxDespatchList(OutboxDespatchListQueryModel query)
Parameters	query: An instance of the OutboxDespatchListQueryModel type
Return Value	Returns an instance of a OutboxDespatchListResponse type.

4.18 GetOutboxDespatchPdf

Transforms an Outbox despatch to Pdf and returns the data of the pdf as byte array.

Method Signature	DespatchesDataResponse GetOutboxDespatchPdf(string despatchId)
Parameters	despatchId: The unique identifier that taxpayers want to integrate with their own systems. It corresponds to the UUID field in UBL-TR format.
Return Value	Returns an instance of a DespatchesDataResponse type.

4.19 GetOutboxDespatchStatusWithLogs

Provides returning the statuses of one or more outgoing despatches and envelopes passed as parameters, and corresponds log records.

Method Signature	DespatchStatusWithLogResponse GetOutboxDespatchStatusWithLogs(List<string> despatchIds)
Parameters	despatchIds: One or more despatch IDs send with this parameter. It corresponds to the UUID field in UBL-TR.
Return Value	Returns an instance of a DespatchStatusWithLogResponse type.

4.20 GetOutboxDespatchView

Transforms an Outbox despatch to html and returns the html string including with the verification information.

Method Signature	DespatchViewResponse GetOutboxDespatchView(string despatchId)
Parameters	despatchId: The unique identifier that taxpayers want to integrate with their own systems. It corresponds to the UUID field in UBL-TR format.
Return Value	Returns an instance of a DespatchViewResponse type.

4.21 GetUserAliasses

Returns the list of all aliasses of a given VKN or TCKN number from the TRA system.

Method Signature	UserAliassesResponse GetUserAliasses(string vknTckn)
Parameters	vknTckn: Tckn or Vkn of the system user which you are querying. Tckn is 11 digit and used for the person and Vkn is 10 digit and used for the companies.
Return Value	Returns an instance of a UserAliassesResponse type.

4.22 GetSystemDate

Returns the system current date and time.

Method Signature	DateResponse GetSystemDate()
Parameters	Does not have any parameter.
Return Value	Returns an instance of a DateResponse type.

4.23 IsEDespatchUser

Provides querying whether a given identification number (TCKN/VKN) and/or a combination of an identification number and alias are registered as a user in the e-despatch system. In cases where the alias field is empty, the method will only check whether the provided VKN/TCKN has an alias registered.

Method Signature	FlagResponse IsEDespatchUser(string vknTckn, string alias)
Parameters	vknTckn: Tckn or Vkn of the system user which you are querying. Tckn is 11 digit and used for the person and Vkn is 10 digit and used for the companies. alias: An optional parameter which provides queirying a specific alias of a system user.
Return Value	Returns an instance of a FlagResponse type.

4.24 QueryInboxDespatchStatus

Provides functionality to query one or more Inbox despatch status.

Method Signature	DespatchStatusResponse QueryInboxDespatchStatus(list<string> despatchIds)
Parameters	despatchIds: One or more despatch IDs send with this parameter. It corresponds to the UUID field in UBL-TR.
Return Value	Returns an instance of a DespatchStatusResponse type.

4.25 QueryOutboxDespatchStatus

Provides functionality to query one or more Outbox despatch status.

Method Signature	DespatchStatusResponse QueryOutboxDespatchStatus (list<string> despatchIds)
Parameters	despatchIds: One or more despatch IDs send with this parameter. It corresponds to the UUID field in UBL-TR.
Return Value	Returns an instance of a DespatchStatusResponse type.

4.26 QueryReceiptAdviceStatus

Provides functionality to query one or more despatch responses.

Method Signature ReceiptAdviceStatusResponse QueryReceiptAdviceStatus(list<string> despatchId)

Parameters despatchId: The unique identifier that taxpayers want to integrate with their own systems. It corresponds to the UUID field in UBL-TR format.

Return Value Returns an instance of a [ReceiptAdviceStatusResponse](#) type.

4.27 RetrySendDespatches

Sets status of an erroneous despatch to queue for resending this despatch.

Method Signature Response RetrySendDespatches(List<string> despatchIds)

Parameters despatchIds: One or more despatch IDs send with this parameter. It corresponds to the UUID field in UBL-TR.

Return Value Returns an instance of a [Response](#) type.

4.28 SaveAsDraft

Saves given despatch as draft. You can continue editing an despatch which is in Draft status. To send those despatches you can use [SendDraft](#) method.

Method Signature DespatchIdentitiesResponse SaveAsDraft(List<despatchInfo> despatches)

Parameters despatches: The list of DespatchInfo elements which contains required information and Ubl-Tr despatch object.

Return Value Returns an instance of a [DespatchIdentitiesResponse](#) type.

4.29 SendDespatch

Provides functionality to send despatches to the system. Despatches which are sent by this method will be set to Queued status and will be processed as soon as possible by the system.

Method Signature DespatchIdentitiesResponse SendDespatch(List<despatchInfo> despatches)

Parameters despatches: The list of DespatchInfo elements which contains required information and Ubl-Tr despatch object.

Return Value Returns an instance of a [DespatchIdentitiesResponse](#) type.

4.30 SendReceiptAdvice

Adds provided ReceiptAdviceResponse elements to the Queue for processing. This method provides to send Accept / Partial Accept application responses to incoming despatches.

Method Signature FlagResponse SendReceiptAdvice(List<ReceiptAdviceInfo> receiptAdvices)

Parameters despatches: The list of DespatchInfo elements which contains required information and Ubl-Tr despatch object.

Return Value Returns an instance of a [FlagResponse](#) type.

4.31 SendDraft

Sets the status of provided despatches to Queued from Draft.

Method Signature FlagResponse SendDraft(List<string> despatchIds)

Parameters despatchIds: One or more despatch IDs send with this parameter. It corresponds to the UUID field in UBL-TR.

Return Value Returns an instance of a [FlagResponse](#) type.

4.32 SetDespatchesTaken

Puts taken flag to the provided despatches. You can query despatches which has no Taken flag by using the [GetInboxDespatches](#) methods.

Method Signature FlagResponse SetDespatchesTaken(List<string> despatchIds)

Parameters despatchIds: One or more despatch IDs send with this parameter. It corresponds to the UUID field in UBL-TR.

Return Value Returns an instance of a [FlagResponse](#) type.

4.33 SetDespatchReceiptAdvicesTaken

Puts taken flag to the responses of outgoing despatches. You can query despatches which have or have not been marked with a taken flag by using the [GetOutboxDespatchList](#) methods.

Method Signature FlagResponse SetDespatchReceiptAdvicesTaken(string[] despatchIds)

Parameters despatchIds: One or more despatch IDs send with this parameter. It corresponds to the UUID field in UBL-TR.

Return Value Returns an instance of a [FlagResponse](#) type.

5 Common Objects

5.1 BinaryRequestData

Represents a data object which contains a byte[] data and its hash value. The fields are as follows;

Property Name	Type	Description
Data	List<Byte>	List of byte data.
Hash	String	Md5 hash of the data which is provided by the Data field.

Used methods: [CompressedSaveAsDraft](#), [CompressedSendDespatch](#)

5.2 ClonedDespatchInfo

Represents an object which contains the source and newly created despatch Id's. The fields are as follows;

Property Name	Type	Description
SourceDespatchId	string	Unique Id of the source despatch
ClonedDespatchId	string	Unique Id of the newly created cloned despatch.

Used object as parameter: [ClonedDespatchServiceResponse](#)

5.3 ClonedDespatchServiceResponse

Represents an object which contains list of ClonedDespatchInfo objects. The fields are as follows;

Property Name	Type	Description
IsSuccesed	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeded.
Value	list< ClonedDespatchInfo >	List of ClonedDespatchInfo objects

Used method: [CloneDespatches](#)

5.4 CustomerInfo

Represents an object which contains the some required information about Customer. The fields are as follows;

Property Name	Type	Description
VknTckn	string	The VKN or TCKN number of the customer. VKN is for the companies and is 10 length digit, TCKN is for the people and is 11 length digit
Alias	string	The alias of the customer.
Title	string	The name of the customer.

Used objects as parameter: [DespatchInfo](#)

5.5 DateResponse

Represents an object which contains a datetime information in it. The fields are as follows;

Property Name	Type	Description
IsSucceeded	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	String	Returns the error message in case of not succeeded.
Value	System.DateTime	Represents the date time value.

Used method: [GetSystemDate](#)

5.6 DespatchData

Represents an object which holds the despatch data in byte format according to UBL-TR format is referred to as a "byte array". The fields are as follows;

Property Name	Type	Description
Data	list<byte>	The binary data of the file.
LocalDocumentId	string	Represents the LocalDocumentId of the despatch.
ExtraInformation	string	Represents the extra information of the despatch.
DespatchId	string	Represents the unique Id of the despatch.

Used objects as parameter: [PagedResponseOfDespatchData](#)

5.7 DespatchesDataResponse

Represents an object which provides the UBL-TR despatch data to be listed in paginated byte format. The fields are as follows;

Property Name	Type	Description
IsSucceeded	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeeded.
Value	PagedResponseOfDespatchData	Provides paging and listing of the DespatchData object.

Used methods: [GetInboxDespatchesData](#), [GetInboxDespatchPdf](#), [GetOutboxDespatchesData](#), [GetOutboxDespatchPdf](#)

5.8 DespatchesResponse

Represents an object which web service will returns for the invoice queiries. The fields are as follows;

Property Name	Type	Description
IsSuccesed	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeded.
Value	PagedResponseOfDespatchInfo	Provides paging and listing of the DespatchInfo object.

Used methods: [GetInboxDespatches](#), [GetOutboxDespatches](#)

5.9 DespatchIdentitiesResponse

Represents web service response for the InvoiceIdentity objects. The fields are as follows;

Property Name	Type	Description
IsSuccesed	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeded.
Value	list< DespatchIdentity >	Provides listing of the Despatch IDs and Despatch numbers.

Used Methods: [CompressedSaveAsDraft](#), [CompressedSendDespatch](#), [SaveAsDraft](#), [SendDespatch](#)

5.10 DespatchIdentity

Represents an object which contains IDs and numbers of an despatch. The fields are as follows;

Property Name	Type	Description
Id	string	Represents the unique id of an despatch
Number	string	Represents the despatch number of an despatch

Used objects as parameter: [DespatchIdentitiesResponse](#)

5.11 DespatchInfo

Represents despatch information object which will be used to send/take despatches from/to system. The fields are as follows;

Property Name	Type	Description
DespatchAdvice	DespatchAdviceType	Specifies the despatch data in Ubl-TR format. You can access the object content from http://efatura.gov.tr .

TargetCustomer [CustomerInfo](#) Represents the despatch receiver information for the Outbox despatches and Sender information for the Inbox despatches.

Notification list<[NotificationInformation](#)> Notifications related to sending the despatch by email are kept in this field, if they exist.

LocalDocumentId string Represents the LocalDocumentId of the despatch

ExtraInformation string Represents the ExtraInformation of the despatch

Used methods: [SaveAsDraft](#), [SendDespatch](#), [DespatchResponse](#)

5.12 DespatchLogItem

Represents a log object for the despatches. The fields are as follows;

Property Name	Type	Description
Creator	string	User who takes action to cause this log record.
CreateDateUtc	System.DateTime	Represents the creation date of the log record in Utc format.
RemoteIpAddress	string	Represents the remote ip address of the requester who cause this log record.
LocalIpAddress	string	Represents the local server ip which this log record was created on.
MachineName	string	Represents the name of the server which this log record was created.
Type	byte	Represents the type of the Log record.
Message	string	Represents the log message.

Used object: [DespatchStatusWithLogInfo](#)

5.13 DespatchProfileType

Represents an enumeration which contains the types of despatch.

Enum Name	Description	Value
Base	Despatch is base despatch.	0

Objects which use enum: [InboxDespatchListItem](#), [OutboxDespatchListItem](#)

5.14 DespatchResponse

Represents an object which web service will returns for the despatch queiries. The fields are as follows;

Property Name	Type	Description
---------------	------	-------------

IsSuccesed bool If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".

Message string Returns the error message in case of not succeded.

Value [DespatchInfo](#) Represents the despatch information.

Used methods: [GetInboxDespatch](#), [GetOutboxDespatch](#)

5.15 DespatchStatus

Represents an enumeration which contains the status of despatch. The values are as follows;

Enum Name	Enum Description	Value
Deleted	Despatch status is deleted.	-100
Draft	Despatch status is draft.	0
Canceled	Despatch status is canceled.	10
Queued	Despatch status is queued.	100
Processing	Despatch status is processing.	200
SentToGib	Despatch status is Sent To TRA.	300
WaitingForAppovement	Despatch sent to receiver, waiting for receiver's approval.	1100
Approved	Despatch status is approved.	1000
PartialApproved	Despatch status is partial approved.	1010
Error	Despatch status is error.	2000

Objects which use enum: [InboxDespatchListItem](#), [OutboxDespatchListItem](#), [DespatchStatusInfo](#), [DespatchStatusWithLogInfo](#)

5.16 DespatchStatusInfo

Represents an object which contains information about despatch status. The fields are as follows;

Property Name	Type	Description
DespatchId	string	The unique identifier that taxpayers want to integrate with their own systems. It corresponds to the UUID field in UBL-TR format.
Message	string	Represents the despatch status message information.
StatusCode	int	Represents the despatch status code information.
StatusEnum	DespatchStatus	Represents the despatch status information

Used object: [DespatchStatusResponse](#)

5.17 DespatchStatusResponse

Represents an object which returns the status information of queried despatches. The fields are as follows;

Property Name	Type	Description
IsSucceeded	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeeded.
Value	list<DespatchStatusInfo>	Returns an instance of a DespatchStatusInfo type.

Used Methods: [QueryInboxDespatchStatus](#), [QueryOutboxDespatchStatus](#)

5.18 DespatchStatusWithLogInfo

Represents an object which contains information about despatch status and logs. The fields are as follows;

Property Name	Type	Description
DespatchId	string	The unique identifier that taxpayers want to integrate with their own systems. It corresponds to the UUID field in UBL-TR format.
LocalDocumentId	string	The identifier ID of the despatch in the sender's own account/ERP system.
Message	string	More detailed information about the status.
StatusCode	int	Represents the status code of the despatch.
StatusEnum	DespatchStatus	Represents the status enum the despatch.
Logs	list<DespatchLogItem>	List of DespatchLogItem objects.
EnvelopeStatusCode	int	Represents the status code of despatch's envelope.

Used object: [DespatchStatusWithLogResponse](#)

5.19 DespatchStatusWithLogResponse

Represents an object which contains the status and logs of a despatch in list format. The fields are as follows;

Property Name	Type	Description
IsSucceeded	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeeded.
Value	list<DespatchStatusWithLogInfo>	List of the status and logs of despatches.

Used methods: [GetInboxDespatchStatusWithLogs](#), [GetOutboxDespatchStatusWithLogs](#)

5.20 DespatchTypeEnum

Represents an enumeration which contains the type of despatch. The values are as follows;

Enum Name	Description	Value
Sending	Despatch is consign despatch.	0

Objects which use enum: [InboxDespatchListItem](#), [OutboxDespatchListItem](#)

5.21 DespatchViewResponse

Represents a web service response object which returns the despatch view as html. The fields are as follows;

Property Name	Type	Description
IsSucceeded	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeeded.
Value	ViewResult	Returns an instance of a ViewResult type.

Used methods: [GetInboxDespatchView](#), [GetOutboxDespatchView](#)

5.22 FlagResponse

Represents a true/false response for the web service operations. The fields are as follows;

Property Name	Type	Description
IsSucceeded	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeeded.
Value	bool	Represents the result of the operation. If "true" then the operation completed successfully, if "false" there is an error.

Used methods: [CancelDraft](#), [ChangeDespatchArchiveStatus](#), [IsEDespatchUser](#), [SendReceiptAdvice](#), [SendDraft](#), [SetDespatchesTaken](#), [SetDespatchReceiptAdvicesTaken](#)

5.23 InboxDespatchListItem

Represents meta data information of a single inbox despatch object. The fields are as follows;

Property Name	Type	Description
IsNew	bool	Indicates that the incoming despatch has been accessed at least once via web services. If it is "false", then it means that the despatch has already been retrieved through the web service and marked as taken using either the SetTaken method or the SetIsTaken query parameter. Otherwise, the despatch is a new one.

IsSeen	bool	Indicates the status of whether the incoming despatch has been read or not. If the despatch has been read, it returns a value of "true". Otherwise, it returns a value of "false".
IsVerified	bool	Indicates the approval status of the incoming despatch. If the despatch has been approved, it returns a value of "true". Otherwise, it returns a value of "false".
Signing Date incoming despatch .	nullable<System.DateTime>	Represents the signature information of the
VerificationResult	string	Represents the despatch verification object.
Lines	list<inboxDespatchListItemLine>	Holds the despatch item information.
ActualDespatchDate incoming despatch.	nullable<System.DateTime>	Represents the actual dispatch date of the
EnvelopeIdentifier despatch.	string	Represents the envelope ID of the relevant incoming
DespatchNumber incoming despatch.	string	Represents the dispatch number of the relevant
DespatchId relevant incoming despatch.	string	Represents the universal unique identifier of the
CreateDateUtc incoming despatch in UTC.	System.DateTime	Represents the creation date and time of the relevant
IssueDate despatch .	nullable<System.DateTime>	Represents the date of the relevant incoming
Status incoming despatch.	DespatchStatus	The object that returns the status of the relevant
StatusCode despatch .	int	Represents the status code of the relevant incoming
TypeEnum despatch.	DespatchTypeEnum	The enumeration that returns the type of the
Type	int	Returns the type of the despatch.
ProfileType	int	Returns the scenario of the despatch.
ProfileTypeEnum despatch.	DespatchProfileType	The enumeration that returns the scenario of the
LineNumber despatch .	int	Represents the line number of the relevant incoming
TargetTitle recipient .	string	Represents the title information of the despatch

TargetTcknVkn	string	Represents the TCKN or VKN information of the recipient .
TargetAlias	string	Represents the mailbox information of the despatch recipient .
IsArchived	bool	Represents the information whether the despatch is archived or not . If it is archived, the value is "true", otherwise it is "false".
IsAgentNew	bool	Returns "false" if the despatch has been accessed by the web service before; otherwise, it returns "true".
IsImported	bool	Represents the information whether the despatch is imported or not . If it is imported, the value is "true", otherwise it is "false".
Hash	string	Represents the MD5 hash value of the incoming despatch data .
AdditionalDocumentCount	int	Represents the number of additional documents in the despatch .
Message	string	Represents the error message in case of error situations.
EnvelopeStatusCode	int	Represents the status code of the incoming despatch envelope .

Used object as parameter: [PagedResponseOfInboxDespatchListItem](#)

5.24 InboxDespatchListItemLine

Represents item-based information of inbox despatches object. The fields are as follows;

Property Name	Type	Description
DespatchId	string	Represents the despatch number.
Status	int	This is an enum that keeps the response given to the item. Its value can be 10 for unspecified status, 20 for fully approved content of the item, and 30 for partial approval of the item.
DespatchLineId	string	Represents the line number of the item.
UnitCode	string	Represents the unit of the item.
Quantity	nullable<decimal>	Represents the quantity of the item.
ItemName	string	Represents the name of the item/service.
SellersItemIdentification	string	Represents the name of the item/service on the seller's side.
OrderLineReferenceId	string	Represents the ID of the item in the order.
Price	nullable<decimal>	Represents the unit price of the item.
LineExtensionAmount	nullable<decimal>	Represents the total amount of the item.

TimingComplaint	string	Represents where complaint information.
ReceivedQuantity	decimal	Represents the quantity of goods received.
RejectedQuantity	decimal	Represents the quantity of goods rejected.
RejectReason	string	Represents the reason for rejecting the goods.
RejectReasonCode	string	This field is where the code for the rejection reason is entered.
ShortQuantity	decimal	Represents the quantity of items missing.
OverSupplyQuantity	decimal	Represents the quantity of overplus items shipped.

Used object as parameter: [InboxDespatchListItem](#)

5.25 InboxDespatchListQueryModel

Represents a filter context for querying inbox despatches. The fields are as follows;

Property Name	Type	Description
OnlyNewestDespatches	bool	Returns only the latest dispatches (those with the new indicator still present).
ExecutionStartDate	nullable<System.DateTime>	Provides for the retrieval of dispatches created after this date, based on the dispatch date.
ExecutionEndDate	nullable<System.DateTime>	Provides for the return of dispatches created before this date, based on the dispatch date.
ActualDespatchStartDate	nullable<System.DateTime>	Provides for the retrieval of dispatches that were dispatched after this date, based on their actual dispatch date.
ActualDespatchEndDate	nullable<System.DateTime>	Provides for the retrieval of dispatches that were dispatched before this date, based on their actual dispatch date.
CreateStartDate	nullable<System.DateTime>	Provides for the retrieval of dispatches created after this date, based on their creation date.
CreateEndDate	nullable<System.DateTime>	Provides for the retrieval of dispatches created before this date, based on their creation date.
Statuses	list<int>	Provides for the retrieval of dispatches in the specified status, by taking a list of integers representing those statuses.
DespatchIds	list<string>	Provides for searching with one or more dispatch IDs.
DespatchNumbers	list<string>	Provides for searching with one or more dispatch numbers.
PageIndex	int	Keeps information about which page of dispatches to retrieve when the method is called. Index 0 represents the first page.

PageSize int Specifies how many dispatches should be returned in each query.

Used methods: [GetInboxDespatchList](#)

5.26 InboxDespatchListResponse

Represents a web service response object for the inbox dispatches list query (only meta data information). Fields are as follows;

Property Name	Type	Description
IsSucceeded	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeeded.
Value	PagedResponseOfInboxDespatchListItem	The object that provides a page listing of incoming despatch information.

Used methods: [GetInboxDespatchList](#)

5.27 InboxDespatchQueryModel

Represents a filter context for querying inbox dispatches. Fileds are as follows;

Property Name	Type	Description
SetTaken	bool	Provides removing the new flag of the upcoming dispatches obtained through QueryModel if it has not been removed before.
OnlyNewestDespatches	bool	Provides the retrieval of only recently arrived (not flagged as new) dispatches.
ExecutionStartDate	nullable<System.DateTime>	Provides the retrieval of dispatches created after this date, based on the date of the dispatch.
ExecutionEndDate	nullable<System.DateTime>	Provides the retrieval of dispatches created before this date, based on the date of the dispatch.
ActualDespatchStartDate	nullable<System.DateTime>	Provides the retrieval of dispatches shipped after this date, based on the actual shipping date of the dispatch.
ActualDespatchEndDate	nullable<System.DateTime>	Provides the retrieval of dispatches shipped before this date, based on the actual shipping date of the dispatch.
CreateStartDate	nullable<System.DateTime>	Provides the retrieval of dispatches created after this date, based on the creation date of the dispatch.
CreateEndDate	nullable<System.DateTime>	Provides the retrieval of dispatches created before this date, based on the creation date of the dispatch.
Statuses	list<int>	Provides the retrieval of dispatches with specified status codes.

DespatchIds dispatch IDs.	list<string>	Provides filtering by one or more
DespatchNumbers dispatch numbers.	list<string>	Provides filtering by one or more
PageIndex of dispatches should be retrieved when the method is called. The first page has an index of 0.	int	The value that indicates which page
PageSize be returned in a single call.	int	Specifies the number of dispatches to

Used methods: [GetInboxDespatches](#), [GetInboxDespatchesData](#)

5.28 MailAttachmentInformation

Represents an object which identifies required information about mail attachment. Fields are as follows;

Property Name	Type	Description
Xml form of Xml will be attached to the email or not.	bool	Specifies whether the despatch data in the
Pdf attached to the email or not.	bool	Specifies whether the despatch PDF will be
Html despatch will be attached to the email or not.	bool	Specifies whether the HTML view of the

Used object as parameter: [MailingInformation](#)

5.29 MailingInformation

Represents the mailing information for an despatch. The fields are as follows;

Property Name	Type	Description
Subject	string	Represents the mail subject information.
Attachment information of the mailing.	MailAttachmentInformation	Represents the attachment
EnableNotification	bool	Indicates whether or not the mail will be sent.
To notification will be sent.	string	Represents the mail address to whom this
BodyXsltIdentifier null, customer default mailing xslt will be used. If customer has no default xslt for mailing then system default xslt for mailing will be used.	string	Represents the mail body xslt identifier. If

EmailAccountIdentifier string Represents the email account identifier which mailing will be done by using that account. If null customer default email account will be used. If customer has no default email account then system email account will be used

Used object as parameter: [NotificationInformation](#)

5.30 NotificationInformation

Represents the notification information of an despatch. The fields are as follows;

Property Name	Type	Description
Mailing MailingInformation type.	List< MailingInformation >	Returns an instance of
Messaging SmsMessageInformation type.	List< SmsMessageInformation >	Returns an instance of

Used object as parameter: [DespatchInfo](#)

5.31 OutboxDespatchListItem

Represents meta data information of a single outbox despatch object. The fields are as follows;

Property Name	Type	Description
LocalDocumentId the sender's own accounting/ERP system.	string	The identifier ID of the despatch in
ExtraInformation information related to the corresponding outgoing dispatch.	string	Representsif there is any additional
ReceiptAdviceDate received dispatch response.	nullable<System.DateTime>	Representscreation date of the
IsReceiptAdviceTaken of the dispatch response has been removed is kept in this field.	bool	Information of whether the new mark
Lines outgoing dispatch list.	List< OutboxDespatchListItemLine >	Representsitems in the
ActualDespatchDate date of the relevant outgoing dispatch.	nullable<System.DateTime>	Representsactual dispatch
EnvelopIdentifier relevant outgoing dispatch.	string	Represents the envelope ID of the
DocumentId document number of the dispatch.	string	Representsuniversal unique
DespatchNumber relevant outgoing dispatch.	string	Representsdispatch number of the

CreateDateUtc dispatch information.	System.DateTime	Represents creation date of the
IssueDate related outgoing dispatch.	nullable<System.DateTime>	Represents the dispatch date of the
StatusEnum the related outgoing dispatch.	DespatchStatus	This object that returns the status of
StatusCode related outgoing dispatch.	int	Represents the status code of the
TypeEnum the dispatch.	DespatchTypeEnum	The enum that returns the profile of
Type	int	Represents the type of the dispatch.
ProfileType dispatch.	int	Represents the scenario of the
ProfileTypeEnum the dispatch.	DespatchProfileType	The enum that returns the scenario of
LineNumber related outgoing dispatch.	int	Represents the line number of the
TargetTitle the dispatch.	string	Represents the title information of
TargetTcknVkn information of the dispatch.	string	Represents the VKN/TCKN
TargetAlias of the dispatch.	string	Represents the mailbox information
IsArchived been archived, otherwise "false".	bool	Represents "true" if the dispatch has
IsAgentNew accessed the dispatch before, otherwise returns "true".	bool	Returns "false" if the web service has
IsImported been imported, otherwise "false".	bool	Represents "true" if the dispatch has
Hash the related outgoing dispatch data.	string	Represents the MD5 hash value of
AdditionalDocumentCount documents in the related outgoing dispatch.	int	Represents the number of additional
Message errors.	string	Represents error message in case of
EnvelopeStatusCode related outgoing dispatch's envelope.	int	Represents the status code of the

Objects used as parameter: [PagedResponseOfOutboxDespatchListItem](#)

5.32 OutboxDespatchListItemLine

Represents the object that keeps item-based information in outgoing despatches. The fields are as follows;

Property Name	Type	Description
DespatchId	string	Represents the dispatch number.
Status	int	This is an enum that keeps the response given to the line item. If the value is 10, the status is unspecified. If it is 20, the entire content of the item has been approved. If it is 30, the item has been partially approved.
DespatchLineId	string	Represents the line number of the item.
UnitCode	string	Represents the unit of the item.
Quantity	nullable<decimal>	Represents the quantity of the item.
ItemName	string	Represents the name of the goods or services provided by the item.
SellersItemIdentification	string	Represents the name of the goods or services provided by the seller for the item.
OrderLineReferenceId	string	Represents the ID of the item in the order.
Price	nullable<decimal>	Represents the unit price of the item.
LineExtensionAmount	nullable<decimal>	Represents the total amount of the item.
TimingComplaint	string	Represents information about complaints.
ReceivedQuantity	decimal	Represents the number of goods received.
RejectedQuantity	decimal	Represents the number of goods rejected.
RejectReason	string	Represents the reason for rejection.
RejectReasonCode	string	Represents the code for the reason for rejection.
ShortQuantity	decimal	Represents the number of missing goods.
OverSupplyQuantity	decimal	Represents the number of overplus goods sent.

Used object as parameter: [OutboxDespatchListItem](#)

5.33 OutboxDespatchListQueryModel

Represents a filter context for querying outbox despatches. The fields are as follows;

Property Name	Type	Description
ReceiptAdviceStartDate	nullable<System.DateTime>	Retrieves the list of despatches created after the date of the receipt advice.
ReceiptAdviceEndDate	nullable<System.DateTime>	Retrieves the list of despatches created before the date of the receipt advice.
IsOnlyReceiptAdviceTaken	boolean	Indicates whether the despatch with the new flag set should be removed or not.
ExecutionStartDate	nullable<System.DateTime>	Retrieves the list of despatches created after the execution date.
ExecutionEndDate	nullable<System.DateTime>	Retrieves the list of despatches created before the execution date.
ActualDespatchStartDate	nullable<System.DateTime>	Returning the list of despatches that have been shipped after the actual despatching date of the despatch note is provided through this field.
ActualDespatchEndDate	nullable<System.DateTime>	Returning the list of despatches that have been shipped before the actual despatching date of the despatch note is provided through this field.
CreateStartDate	nullable<System.DateTime>	Retrieves the list of despatches created after the create date of the despatch.
CreateEndDate	nullable<System.DateTime>	Retrieves the list of despatches created before the create date of the despatch.
Statuses	list<int>	Queries one or more despatch statuses.
DespatchIds	list<string>	Searches for one or more despatch IDs.
DespatchNumbers	list<string>	Searches for one or more despatch numbers.
PageIndex	int	Keeps information about which page of despatches to retrieve when the method is called. Index 0 represents the first page.
PageSize	int	Specifies how many despatches should be returned in each query.

Used methods: [GetOutboxDespatchList](#)

5.34 OutboxDespatchListResponse

Represents a web service response object for the outbox despatches list query (only meta data information). Fields are as follows;

Property Name	Type	Description
IsSucceeded	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeeded.
Value	PagedResponseOfOutboxDespatchListItem	The object that provides a page listing of outgoing despatch information.

Used methods: [GetOutboxDespatchList](#)

5.35 OutboxDespatchQueryModel

Represents a filter context for querying outbox despatches. The fields are as follows;

Property Name	Type	Description
ReceiptAdviceStartDate	nullable<System.DateTime>	Retrieves the list of despatches created after the date of the receipt advice.
ReceiptAdviceEndDate	nullable<System.DateTime>	Retrieves the list of despatches created before the date of the receipt advice.
IsOnlyReceiptAdviceTaken	boolean	Indicates whether the despatch with the new flag set should be removed or not.
ExecutionStartDate	nullable<System.DateTime>	Retrieves the list of despatches created after the execution date.
ExecutionEndDate	nullable<System.DateTime>	Retrieves the list of despatches created before the execution date.
ActualDespatchStartDate	nullable<System.DateTime>	Returning the list of despatches that have been shipped after the actual despatching date of the despatch note is provided through this field.
ActualDespatchEndDate	nullable<System.DateTime>	Returning the list of despatches that have been shipped before the actual despatching date of the despatch note is provided through this field.
CreateStartDate	nullable<System.DateTime>	Retrieves the list of despatches created after the create date of the despatch.
CreateEndDate	nullable<System.DateTime>	Retrieves the list of despatches created before the create date of the despatch.
Statuses	list<int>	Queries of certain despatch statuses.
DespatchIds	list<string>	Searches for one or more despatch IDs.

DespatchNumbers	list<string>	Searches for one or more despatch numbers.
PageIndex	int	Keeps information about which page of dispatches to retrieve when the method is called. Index 0 represents the first page.
PageSize	int	Specifies how many dispatches should be returned in each query.

Used methods: [GetOutboxDespatches](#), [GetOutboxDespatchesData](#)

5.36 PagedQueryContext

Represents an object which can be used for paged query. The fields are as follows;

Property Name	Type	Description
PageIndex	int	Keeps information about which page of dispatches to retrieve when the method is called. Index 0 represents the first page.
PageSize	int	Specifies how many objects should be returned in each query.

Used method: [GetEDespatchUsers](#)

5.37 PagedResponseOfDespatchData

Represents an object which contains a paginated list of UBL-TR despatch data in byte format. The fields are as follows;

Property Name	Type	Description
Items	list< DespatchData >	Contains the list of items on the page.
PageIndex	int	Represents which page the returned values belong to. Index 0 is the first page.
PageSize	int	Represents the number of records per page.
TotalCount	int	Represents the total number of records.
TotalPages	int	Represents the total number of pages.

Object used as parameter: [DespatchesDataResponse](#)

5.38 PagedResponseOfDespatchInfo

Represents an object which web service returns as the list of [DespatchInfo](#) objects. The fields are as follows;

Property Name	Type	Description
Items	list< DespatchInfo >	Contains the list of items on the page.

PageIndex	int	Represents which page the returned values belong to. Index 0 is the first page.
PageSize	int	Represents the number of records per page.
TotalCount	int	Represents the total number of records.
TotalPages	int	Represents the total number of pages.

Object used as parameter: [DespatchesResponse](#)

5.39 PagedResponseOfInboxDespatchListItem

Represents an object which web service returns as the list of [InboxDespatchListItem](#) objects. The fields are as follows;

Property Name	Type	Description
Items	list< InboxDespatchListItem >	Contains the list of items on the page.
PageIndex	int	Represents which page the returned values belong to. Index 0 is the first page.
PageSize	int	Represents the number of records per page.
TotalCount	int	Represents the total number of records.
TotalPages	int	Represents the total number of pages.

Object used as parameter: [InboxDespatchListResponse](#)

5.40 PagedResponseOfOutboxDespatchListItem

Represents an object which web service returns as the list of [OutboxDespatchListItem](#) objects. The fields are as follows;

Property Name	Type	Description
Items	list< OutboxDespatchListItem >	Contains the list of items on the page.
PageIndex	int	Represents which page the returned values belong to. Index 0 is the first page.
PageSize	int	Represents the number of records per page.
TotalCount	int	Represents the total number of records.
TotalPages	int	Represents the total number of pages.

Object used as parameter: [OutboxDespatchListResponse](#)

5.41 PagedResponseOfSystemUser

Represents an object which web service returns as the list of the System users. The fields are as follows;

Property Name	Type	Description
Items	list< SystemUser >	Contains the list of items on the page.
PageIndex	int	Represents which page the returned values belong to. Index 0 is the first page.
PageSize	int	Represents the number of records per page.
TotalCount	int	Represents the total number of records.
TotalPages	int	Represents the total number of pages.

Used object: [SystemUsersResponse](#)

5.42 ReceiptAdviceInfo

Represents an object which contains response of despatches. The fields are as follows;

Property Name	Type	Description
InboxDespatchId	string	Represents the incoming despatch id value.
Note	string	Keeps the note information for the delivery response.
DeliveryContactName	string	Represents the information of the recipient who received the delivery.
DespatchContactName	string	Represents the information of the person who dispatched the delivery.
ActualDeliveryDate	System.DateTime	Represents the actual delivery date.
ReceiptAdviceLineInfos	list< ReceiptAdviceLineInfo >	This is an object that contains information about the delivery note item.

Used methods: [SendReceiptAdvice](#)

5.43 ReceiptAdviceLineInfo

Represents an object which contains itemized list of responses for dispatched items. The fields are as follows;

Property Name	Type	Description
InboxDespatchLineId	int	Represents the lineId of the incoming despatch to which the response despatch is linked.
LineId	string	Represents line number in the despatch.
TimingComplaint	string	Field for storing complaint information.

ReceivedQuantity this field.	decimal	The amount of goods received is stored in
RejectedQuantity field.	decimal	The amount of goods rejected is stored in this
RejectReason goods.	string	Field for storing the reason for rejecting
RejectReasonCode reason.	string	Field for entering the code of the rejection
ShortQuantity are missing.	decimal	Field for entering the quantity of goods that
OverSupplyQuantity are over-supplied.	decimal	Field for entering the quantity of goods that

Object that use enum: [ReceiptAdviceInfo](#)

5.44 ReceiptAdviceStatus

Represents the enum which contains statuses of despatch's response. The fields are as follows;

Enum Name	Enum Description	Value
Draft	Response is in Draft status.	0
Queued	Response is in Queued status.	10
Processing	Response is in Processing status.	20
SentToGib	Response has been sent to TRA status.	30
Success	Response has been successfully delivered status.	40
Error	Response is in Error status. An error occurred while delivering the despatch response to the recipient or TRA.	50

Object that use enum: [ReceiptAdviceStatusInfo](#)

5.45 ReceiptAdviceStatusInfo

Represents the object that returns the status information of the despatch response. The fields are as follows;

Property Name	Type	Description
Status despatch response.	ReceiptAdviceStatus	Returns the status information of the
StatusCode response.	int	Represents status code of the despatch

DespatchId	string	RepresentsID of the despatch advice sent in the response. It corresponds to the UUID field.
Message	string	Representsany additional messages related to the despatch response status.

Used object: [ReceiptAdviceStatusResponse](#)

5.46 ReceiptAdviceStatusResponse

Represents the object that contains return values for status information of the despatch responses. The fields are as follows;

Property Name	Type	Description
IsSucceeded	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeeded.
Value	list< ReceiptAdviceStatusInfo >	Returns ReceiptAdviceStatusInfo object as a list.

Used methods: [QueryReceiptAdviceStatus](#)

5.47 Response

Returns results only in a true/false format. The fields are as follows;

Property Name	Type	Description
IsSucceeded	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeeded.

Used method: [RetrySendDespatches](#)

5.48 SmsMessageInformation

Represents the object that holds despatch information sent via SMS. The fields are as follows;

Property Name	Type	Description
To	string	Represents information of SMS recipient.
BodyXsltIdentifier	string	The XSLT SMS template to be used for sending the SMS represents the unique identifier information in e-despatch system. If it is empty, the customer's default SMS template will be used. If the customer's default SMS template is also empty, the system default template will be used.

Used object: [NotificationInformation](#)

5.49 SystemUser

System users means that the users in the TRA e-despatch system. System users are managed by the TRA and system automatically update the list in every one hour. You can query the taxpayer list from web services.

The fields of the SystemUser object are as follows;

Property Name	Type	Description
Identifier	string	Either Vkn or Tckn value, which are identification numbers, can be taken in this field.
PostboxAlias	string	Represents postbox alias.
SenderboxAlias	string	Represents sender unit alias.
Title	string	Represents the title of the taxpayer.
Type	string	Contains one of the following values: "Kamu" means that registered tax payer is a governmental organization and "Özel" for private organizations.
SystemCreateDate	string	Represents the creation date of the taxpayer's alias.
FirstCreateDate	string	Represents the date when the taxpayer was first opened in the Revenue Administration system.
Enabled	bool	Contains information about whether the user is active or not.

Used Object: [PagedResponseOfSystemUser](#)

5.50 SystemUserAlias

Represents an alias information of a tax payer. The fields are as follows;

Property Name	Type	Description
Alias	string	Represents the taxpayer's mailbox label.
Type	int	Represents the taxpayer's alias type.
SystemCreateDate	string	Contains the creation date of the taxpayer's alias information.
SystemDeleteDate	string	Contains the deletion date of the taxpayer's alias information.
Enabled	bool	Indicates whether the taxpayer's alias is active or inactive.

Used Object: [SystemUserWithAlias](#)

5.51 SystemUserDefinition

Indicates the identification information of the taxpayer registered in the e-despatch system. A unique SystemUserDefinition record is kept in the system for each firm. The aliases of the companies are associated with these records and identifiers as SystemUsers. The fields are as follows;

Property Name	Type	Description
CreateDateUtc	System.DateTime	Represents the creation date of the taxpayer in the Uyumsoft system.
Identifier	string	Represents the TCKN/VKN information of the taxpayer.
Title	string	Represents the name of the taxpayer.
Type	string	Contains following two values: "Kamu" means that registered tax payer is a governmental organization and "Özel" for private organizations.
SystemCreateDate	string	Contains the creation date of the taxpayer in the TRA system.

Used object: [SystemUserWithAlias](#)

5.52 SystemUsersResponse

Represents an object which web service uses to return to the System User queiries. The fields are as follows;

Property Name	Type	Description
Value	PagedResponseOfSystemUser	Contains a list of system users in a page.
IsSuccesed	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeded.

Used Method: [GetEDespatchUsers](#)

5.53 SystemUserWithAlias

Represents an object which contain the required infromation for a system user and all its aliases. The fields are as follows;

Property Name	Type	Description
Definition related to taxpayer.	SystemUserDefinition	Represents definition information
ReceiverboxAliases	list< SystemUserAlias >	Represents invoice receiver aliases.
SenderboxAliases	list< SystemUserAlias >	Represents invoice sender aliases.
DespatchReceiverboxAliases	list< SystemUserAlias >	Represents despatch receiver aliases.

DespatchSenderboxAliases list<[SystemUserAlias](#)> Represents despatch sender aliases.
Used object: [UserAliassesResponse](#)

5.54 UserAliassesResponse

Represents an object which web service returns to the system user queries. The fields are as follows;

Property Name	Type	Description
Value	SystemUserWithAlias	Specifies a taxpayer and its aliases
IsSuccesed	bool	If an error occurred during the operation, it returns a value of "false", otherwise it returns a value of "true".
Message	string	Returns the error message in case of not succeded.

5.55 VerificationResult

Represents an object which contains the information about a despatch signature verification. The fields are as follows;

Property Name	Type	Description
Data	string	Represents the detailed verification result.
SigningDate	system.Nullable<System.DateTime>	Represents the date and time information of the despatch signature.
IsVerified	bool	Verified or not verified information is kept with this field. Value returns "True" if verified, otherwise "False".

Used object: [ViewResult](#)

5.56 ViewResult

Represents a despatch html view result object including its signature verification information. The fields are as follows;

Property Name	Type	Description
Html	string	Represents the tranformed html view of the despatch.
Verification	VerificationResult	Represents the verification information of the despatch.
IsUsingDefaultXslt	bool	Indicates that is default xslt used to transform the despatch to html or not.

Used method: [DespatchViewResponse](#)