

Incident Management Solution Handover & Runbook

Comprehensive Technical Reference, Administrator Manual, User Guides & Governance

Project: Incident Management UI Policies & Client Scripts

Document Phase: Phase 7 — Project Documentation Phase

Author / Role: ServiceNow Technical Lead / Solution Architect

Application Scope: Global / Incident Management (`incident`)

Audience: System Administrators, L2/L3 Support, Service Desk Agents

Document Status: Final Approved Handover Document

1. EXECUTIVE SUMMARY & HANDOVER SCOPE

Following the successful completion of the preceding project lifecycle phases—**Requirement Analysis (Phase 2)**, **Project Design (Phase 3)**, **Project Planning (Phase 4)**, **Project Development (Phase 5)**, and **Project Testing (Phase 6)**—this document represents the final deliverable: **Phase 7: Project Documentation Phase**.

The purpose of this documentation is to serve as the definitive single source of truth for ongoing system administration, production maintenance, end-user operation, troubleshooting runbooks, and enterprise governance for the client-side behaviors configured on the Incident table.

2. MASTER ARTIFACT CATALOG & TECHNICAL INVENTORY

Artifact ID	Artifact Type	Record Name & Target	Operational Role & Behavior	State / Scope
UIP-INC-01	UI Policy	Enforce Resolution Code and Notes on Resolve or Close	Forces <code>close_code</code> and <code>close_notes</code> to be mandatory and visible when Incident State is Resolved (6) or Closed (7). Reverts when false.	Active / Global
UIP-INC-02	UI Policy	Highlight & Mandate Work Notes on P1 Incidents	Fires on <code>priority == 1</code> . Makes <code>work_notes</code> mandatory and executes onCondition true/false scripts to post/clear priority field messages.	Active / Global
UIP-INC-03	UI Policy	Lock Assignment for Child Incident	Triggers when <code>parent_incident</code> is populated; locks <code>assignment_group</code> and <code>assigned_to</code> as read-only.	Active / Global
UIP-INC-04	UI Policy	Set Location Mandatory for Walk-in Incidents	Triggers when <code>contact_type == 'walk-in'</code> ; dynamically enforces location capture for in-person support desks.	Active / Global
SI-INC-01	Script Include	IncidentClientHelper (AbstractAjaxProcessor)	Client-callable asynchronous server helper. Accepts <code>sysparm_caller_id</code> and returns JSON object of VIP status, phone, email, and department.	Active / Global
CS-INC-01	Client Script	Incident - Asynchronous VIP & Caller Info Lookup	<code>onChange</code> on <code>caller_id</code> . Leverages GlideAjax with <code>getXMLAnswer()</code> to highlight VIP callers without locking the browser UI thread.	Active / All UI
CS-INC-02	Client Script	Incident - Resolution Quality Validation	<code>onSubmit</code> interceptor. Validates that <code>close_notes</code> contains ≥ 30 characters and is not a generic	Active / All UI

Artifact ID	Artifact Type	Record Name & Target	Operational Role & Behavior	State / Scope
			placeholder string ("fixed", "done", etc.).	

3. SYSTEM ADMINISTRATOR MAINTENANCE GUIDE

UI Policy Modification Procedures

- **Modifying Close Conditions:** Navigate to `sys_ui_policy.list`, search for `UIP-INC-01`. Update condition builder if new terminal states (e.g., Canceled) require close code capture.
- **Reverse if False Discipline:** Always retain *Reverse if false = true*. Avoid adding conflicting UI Policies with overlapping actions on identical fields.
- **Execution Order Range:** Keep UI Policy execution order strictly between `100` and `300` to prevent collision with platform base scripts.

Script Include & Client Script Maintenance

- **Script Include Security:** `IncidentClientHelper` is marked *Client Callable = true*. If adding additional fields to the return payload, enforce defensive null checks.
- **Asynchronous Pattern Enforcement:** Never replace `ga.getXMLAnswer(callback)` with synchronous `ga.getXMLWait()`. Doing so will degrade browser responsiveness and fail SOW compliance.
- **UI Type Setting:** Client Scripts must always maintain *UI Type = All* to support Desktop, Service Portal, and Service Operations Workspace.

4. END-USER & SERVICE DESK AGENT OPERATIONAL GUIDE

4.1 Handling VIP Callers

When selecting an end user in the **Caller** field:

- If the user has the VIP flag enabled on their profile record, an informational banner (`★ VIP CALLER: Prioritize ticket per Executive SLA`) automatically renders beneath the field.
- Service Desk agents must adhere to the high-priority executive SLA guidelines and verify caller contact information.

4.2 Resolving Incidents & Quality Notes Standard

When transitioning an Incident to **Resolved (State = 6)**:

- The **Resolution Code** (`close_code`) and **Resolution Notes** (`close_notes`) become strictly required.
- **Quality Minimum:** The system enforces a minimum of **30 characters** detailing both root cause and resolution. Submissions containing generic placeholders such as *"done"*, *"fixed"*, *"issue resolved"*, or *"test"* will be actively blocked by the browser with a highlighted warning.

4.3 Working with Child Incidents

Linking a parent incident via the `parent_incident` field automatically locks the **Assignment Group** and **Assigned To** fields to ensure operational ownership remains synchronized with the parent coordinating ticket.

5. TROUBLESHOOTING RUNBOOK & ISSUE RESOLUTION

Observed Symptom	Root Cause Investigation	Corrective Action / Resolution Procedure
Close notes are mandatory on new/in-progress tickets	Another client script or UI Policy has set mandatory attribute without condition filtering.	1. Inspect <code>sys_ui_policy</code> on <code>incident</code> for field <code>close_notes</code> . 2. Verify <code>UIP-INC-01</code> condition evaluates to false. 3. Ensure <i>Reverse if false</i> is checked on all active policies.
VIP Banner does not appear when VIP caller chosen	1. Caller record has <code>vip == false</code> . 2. Script Include inaccessible or blocked by ACL.	1. Navigate to <code>sys_user.list</code> and confirm <code>vip = true</code> for test user. 2. Open browser console; verify no 403 or network failure on <code>xmlhttp.do</code> . 3. Verify <code>IncidentClientHelper</code> is Active and Client Callable.
Agent cannot save resolution despite valid notes	Notes contain less than 30 characters or match blacklisted placeholder regex.	1. Advise agent that resolution documentation requires ≥ 30 characters. 2. Check if agent typed short boilerplate like "done." or "fixed issue." 3. Provide descriptive resolution text.
Script behaves differently in Workspace vs UI16		

Observed Symptom	Root Cause Investigation	Corrective Action / Resolution Procedure
	UI Type configuration set to 'Desktop' only or unauthorized DOM usage present.	1. Confirm Client Script has <i>UI Type = All</i> . 2. Confirm no <code>document.getElementById</code> or DOM manipulation is used.

6. GOVERNANCE, UPGRADEABILITY & FINAL PROJECT SIGN-OFF

Upgrade Safety & Certification: All artifacts have been developed adhering strictly to ServiceNow out-of-the-box API standards (using official `g_form` methods, asynchronous `GlideAjax`, and standard condition builders). The solution introduces zero DOM injections and is certified fully compatible with future family upgrades (Xanadu, Washington DC, Vancouver).

Stakeholder Role	Name & Title	Handover Confirmation	Date & Sign-Off
ServiceNow System Administrator	Platform Operations Lead	Operational Handover Accepted	Certified & Approved
ITSM Service Desk Manager	Global Operations Support	User Documentation Accepted	Certified & Approved
Lead ServiceNow Solution Architect	Enterprise Architecture Board	Architecture & Governance Certified	Certified & Approved