

TOOLS FOR WRITING
CONSISTENT AND RELIABLE


PYTHON CODE

TODAY WE'LL TALK ABOUT ...

- ▶ Writing consistent Python code.
- ▶ Tools for enforcing code consistency.
- ▶ Type hints and `mypy` (trigger warning).
- ▶ Writing consistent docstrings.
- ▶ ... will not talk about unit testing.

MOTIVATION

- ▶ Make your programming life easier.
- ▶ Inefficient workflow, wasted time on individual coding quirks.
- ▶ Simple tools can help you become a better programmer.



DISCLAIMER

- ▶ I am not an expert, just very interested.
- ▶ Which tools make sense in a data science context?

**INCONSISTENCY IS THE
HOBGOBLIN OF LITTLE MINDS.**

PEP 8: Style Guide for Python Code

WHY SHOULD YOU CARE ABOUT CODING STYLE?

- ▶ The mental health of your future self.
- ▶ The mental health of your coworkers.
- ▶ Spend less time on formatting, more on logic.

PEP 8 – THE OFFICIAL STYLE GUIDE

- ▶ **P**ython **E**nhancement **P**roposal.
- ▶ PEP 8 formalises a recommended programming style.
- ▶ PEP 8 covers:
 - ▶ Naming styles and conventions.
 - ▶ Whitespace, maximum line lengths, indentations, trailing commas, and much more.

EXAMPLE: NAMING STYLES

Type	Example
Function/method	<code>function, my_function</code>
Variable	<code>variable, my_variable</code>
Class	<code>Class, MyClass</code>
Constant	<code>CONSTANT, MY_CONSTANT</code>
Module	<code>module.py, my_module.py</code>
Package	<code>package, mypackage</code>

**PLEASE, PLEASE,
PLEASE READ PEP 8**

ENFORCING CONSISTENCY

- ▶ Memorise PEP 8? Ain't nobody got time for dat.
- ▶ Use linters!
- ▶ Linters check your code for logical errors and compliance with PEP 8.
- ▶ Most IDEs already use linting tools.

POPULAR PYTHON LINTERS

- ▶ `pylint`
 - ▶ Very powerful.
 - ▶ User-unfriendly defaults.
- ▶ `flake8`
 - ▶ Wrapper around `pyflakes`, `pycodestyle` and `mccabe`.
 - ▶ User-friendly defaults.

FLAKE8

- ▶ `pyflakes` checks your source files for errors. Does not complain about style.
- ▶ `pycodestyle` (formerly `pep8`) checks PEP 8 compliance.
- ▶ `mccabe` checks the complexity of your code (switched off by default).

EXAMPLE: USING FLAKE8

- ▶ Run `flake8` on `code_with_lint.py` through command line interface.
- ▶ Clone repository* to play with this example.

<https://github.com/smu095/presentations/tree/master/python101>

FLAKE8 OUTPUT

`{filename}:{line}:{column}:{error code} {message}`

- ▶ `W*** / E***` are PEP 8 warnings (pycodestyle).
- ▶ `F***` are syntax errors (pyflakes).
- ▶ `C9**` are complexity errors (mccabe).
- ▶ Customisable, error messages can be ignored.

AUTOFORMATTING CODE

- ▶ Linters check your code, doesn't fix it.
- ▶ Autoformatters enforce consistency by refactoring your code.
- ▶ **Idea:** Avoid formatting arguments in code review, focus on logic.

BLACK – THE UNCOMPROMISING CODE FORMATTER

- ▶ `black` is an opinionated autoformatter that enforces a superset of PEP 8.
- ▶ Produces smallest diffs possible to make code review faster.
- ▶ Some stylistic deviations from PEP 8, e.g.
 - ▶ maximum line length is 88 characters.
 - ▶ all single quotes replaced by double quotes.

EXAMPLE: USING BLACK

- ▶ Run `black` on `unformatted_code.py` through command line interface.
- ▶ Clone repository* to play with this example.

<https://github.com/smu095/presentations/tree/master/python101>

SO FAR WE HAVE TALKED ABOUT...

- ▶ Community guidelines for coding style.
- ▶ Linters that check your code for errors.
- ▶ Autoformatters that refactor your code so you don't have to.
- ▶ There is a third linting tool, which relies on *type hints*.

STATIC VS. DYNAMIC TYPING

- ▶ Statically typed languages:
 - ▶ Variables bound to both type and object.
 - ▶ Types checked before code execution.
- ▶ Dynamically typed languages:
 - ▶ Variables bound object.
 - ▶ Types checked during code execution.

PYTHON IS DYNAMICALLY TYPED

- ▶ Objects are allowed to change types.
- ▶ Types are correctly inferred at runtime.

EXAMPLE: TYPES IN PYTHON

```
1 >>> if False:
2 ...     1 + "two"
3 ... else:
4 ...     1 + 2
5 3
6
7 >>> 1 + "two" # This will throw a TypeError
```

```
1 >>> thing = "Hello"
2 >>> type(thing)
3 <class 'str'>
4 >>> thing = 42
5 >>> type(thing)
6 <class 'int'>
```

STATIC TYPE CHECKING WITH MYPY

- ▶ `mypy` performs static type checking, i.e. code doesn't need to run to catch type errors.
- ▶ Needs your help, in the form of *type annotations*.
- ▶ Introduced in PEP 484, also called *type hints*.
- ▶ Completely optional, types are suggested but not enforced.

FUNCTION ANNOTATION

```
def some_function(argument: type = default) -> type:  
    do_something()
```

EXAMPLE: USING TYPE HINTS

- ▶ Run `mypy` on `type_hinting_example.py` through command line interface.
- ▶ Run `mypy` on `variable_hints.py` through command line interface.
- ▶ Clone repository* to play with this example.

<https://github.com/smu095/presentations/tree/master/python101>

SHOULD WE USE TYPE HINTING?

- ▶ Adds little value in short, throw-away scripts.
- ▶ Potential for a lot of value in bigger, collaborative projects.

TYPE HINTING YES-MEN

- ▶ More understandable, helps document code.
- ▶ More maintainable, easier to refactor.
- ▶ More reliable, catches bugs early.


TYPE HINTING NAY-SAYERS

- ▶ Requires time and effort.
- ▶ Introduces some overhead.
- ▶ Introduces unnecessary verbosity.
- ▶ Only available in Python 3.5+*.

* Works in earlier versions too, but with different syntax.

TYPE HINTING TAKEAWAYS

- ▶ Mildly controversial.
- ▶ Completely optional, Python will remain dynamically typed.
- ▶ More and more projects use type hinting and `mypy`, worth familiarising yourself with.
- ▶ Use your best judgement!



FFFFFFFF

FFFFFFFF

FFFFFFF

FFFUU

UUUU

UUUU

UUUU

UUUU

UUUU-

UUUU-

UUUU

DOCSTRINGS

- ▶ **Problem:** Terribly documented code, took forever to figure out how it worked.
- ▶ PEP 257 formalises a style guide for docstrings.
- ▶ Docstrings come in different formats.
- ▶ Up to you, but stay consistent within your project.

A MINIMAL FUNCTION DOCSTRING

- ▶ Every docstring should at the very least contain:
 - ▶ A one-liner summarising the function.
 - ▶ A description of the parameters.
 - ▶ A description of the return value.
- ▶ Surround by triple quotes, place immediately after function declaration.

EXAMPLE: UNDOCUMENTED FUNCTION

```
1 def get_spreadsheet_cols(file_loc, print_cols=False):
2     file_data = pd.read_excel(file_loc)
3     col_headers = list(file_data.columns.values)
4
5     if print_cols:
6         print("\n".join(col_headers))
7
8     return col_headers
```


EXAMPLE: RESTRUCTURED TEXT

```
1  """Gets and prints the spreadsheet's header columns
2
3  :param file_loc: The file location of the spreadsheet
4  :type file_loc: str
5  :param print_cols: A flag used to print the columns to the console
6                      (default is False)
7  :type print_cols: bool
8  :returns: a list of strings representing the header columns
9  :rtype: list
10 """
```

EXAMPLE: GOOGLE DOCSTRINGS

```
1  """Gets and prints the spreadsheet's header columns
2
3  Parameters:
4      file_loc (str): The file location of the spreadsheet
5      print_cols (bool): A flag used to print the columns to the console
6                          (default is False)
7
8  Returns:
9      list: a list of strings representing the header columns
10 """
```

EXAMPLE: NUMPY/SCIPY DOCSTRINGS

```
1  """Gets and prints the spreadsheet's header columns
2
3  Parameters
4  -----
5  file_loc : str
6      The file location of the spreadsheet
7  print_cols : bool, optional
8      A flag used to print the columns to the console (default is False)
9
10 Returns
11 -----
12 list
13     a list of strings representing the header columns
14 """
```

INCLUDING EXAMPLES

- ▶ The `numpy` docstring format strongly encourages examples in docstrings.
- ▶ Examples use the `doctest` module to parse docstrings for runnable examples of code.
- ▶ **Idea:** Make sure examples are running as shown, not intended as tests.

BUILDING DOCUMENTATION

- ▶ reStructuredText, Google and Numpy docstrings are widely used.
- ▶ Can produce well-formatted reference guides using tools like `sphinx` and `autodoc`.

PRACTICAL USE OF LINTING TOOLS

- ▶ Typically used in continuous integration pipeline.

```
37  # ----- script: run the build script -----
38  before_script:
39      - pip install . # Install the package
40      - pip show treedoc # Show information about the package
41      - black . --check # Check that code is formatted correctly w.r.t. black
42      - flake8 treedoc --select=F401 --exclude=__init__.py # Unused imports
43      - bash ./linting.sh # Spelling errors
44      - mypy treedoc/*.py --ignore-missing-imports --show-error-context # Static type analysis
```

SUMMARY

- ▶ Read PEP 8.
- ▶ Follow the community's recommended style guide.
- ▶ Use linting and autoformatting tools when appropriate.
- ▶ Probably a good idea to familiarise yourself with type hints.
- ▶ Make a habit of writing good docstrings.

THE END